

Aiways		Baujahr	Typ	LK/LZ	Nabe		
Aiways U5 NEU		ab 2020	MAS861, -/WVTA	5/112	57,1	e13*2007/46*2315*..., e13*KS07/46*1629*..., e13*KS07/46*1631*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	40	-	55, 60	215/65		Orig.-Verschr.
		38	-	55, 60	215/65, 225/60, 235/60		Orig.-Verschr.
7 x 17	RC27	40+42+43	-	55, 60	215/65, 225/60, 235/60, 245/55		Orig.-Verschr.
	B39	40	-	55, 60	215/65, 225/60, 235/60, 245/55		Orig.-Verschr.
	CA 26	42	ZP562D	55, 60	215/65, 225/60, 235/60, 245/55		
7,5 x 17	RC27	40+41	-	55, 60	215/65, 225/60, 235/60		Orig.-Verschr.
	RC29	35	ZP562D	55, 60	215/65, 225/60, 235/60		
	B24 / B36	35	ZP562D	55, 60	215/65, 225/60, 235/60		
7 x 18	RC27	43	-	55, 60	215/60, 225/55, 235/55, 245/50		Orig.-Verschr.
8 x 18	B24 / B42	35	ZP562D	55, 60	225/55		
	B44	35	ZP562D	55, 60	225/55		
	AC-M10	40	- +R	55, 60	225/55, 235/55		Orig.-Verschr. +Red.Ringe 66,6-57,1
	AC-MB6	39	- +R	55, 60	225/55, 235/55		Orig.-Verschr. +Red.Ringe 66,6-57,1
	AC-522	35	- +R	55, 60	225/55		Orig.-Verschr. +Red.Ringe 66,6-57,1
		40	- +R	55, 60	225/55, 235/55		Orig.-Verschr. +Red.Ringe 66,6-57,1
7 x 19	RC27	43	-	55, 60	225/50, 235/50		Orig.-Verschr.
7,5 x 19	CA 26	40	ZP562D	55, 60	225/50, 245/45		
8 x 19	AC-521	35	AV1	55, 60	225/50		
	Oxigin 29	39	ZP562D	55, 60	225/50, 245/45		
		43	ZP562D	55, 60	225/50, 235/50, 245/45		
8,5 x 19	B43	38	ZP569F	55, 60	245/45		
	Oxigin 28	40	ZP562D	55, 60	245/45		
8,5 x 20	B24	42	ZP562D	55, 60	235/45, 245/40		
	B43	43	ZP560D	55, 60	235/45, 245/40		
9 x 20	RC36	42	-	55, 60	235/45, 245/40		Orig.-Verschr.
	B43	42	-	55, 60	235/45, 245/40		Orig.-Verschr.
	AC-521	42	-	55, 60	235/45, 245/40		Orig.-Verschr.
Aiways U6 NEU i.V.		1.Quartal 2023					

Alfa Romeo		Baujahr	Typ	LK/LZ	Nabe		
Giulietta		ab 05.10	940	5/110	65,1	e3*2007/46*0027*...	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC28	41	ZP538F	77,85,88	195/55, 205/55		Achtung Bremsen siehe TÜV!
				77-125	195/50, 195/55, 205/55, 215/55, 225/45, 225/50		nicht für Bremse 305mm
7 x 17	RC27	37	ZP538F	77-129	205/50, 215/45, 225/45		Achtung Bremsen siehe TÜV!
		41	ZP538F	77-129	205/50, 215/45, 225/45		nur für Bremse 305mm
	RC30	40	ZP538F	77-129	205/50, 215/45, 225/45		nur für Bremse 305mm
7,5 x 17	B24	38	ZP538F	77-129	205/50, 215/45, 225/45		nicht Bremse 330mm u. nicht Brembo-Bremse in Verb. mit 305mm
	AC-518	40	ZP538F	77-129	205/50, 215/45, 225/45, 235/45		nicht Brembo-Bremse in Verb. mit 305mm u. nicht 330mm
7 x 18	RC27	40	ZP538F	77-125	215/40		nicht Brembo-Bremse
7,5 x 18	RC32	37	-	77-177	215/40		Orig.-Verschr.
	B32	41	ZP538F	77-129	205/45, 215/40, 225/40,		nicht Bremse 330mm
	B39	38	ZP538F	77-129	205/45, 215/40, 225/40		nicht Brembo-Bremse in Verb. mit 305mm u. nicht 330mm
8 x 18	AC-518	40	ZP538F	77-129	215/40, 225/40		nicht Brembo-Bremse in Verb. mit 305mm u. nicht 330mm
7,5 x 19	B39	40	ZP538F	77-129	225/35		nur für Bremse 305mm

Giulia		ab 06.2016		952	5/110	65,1	e3*2007/46*0382*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 16	Originaldim.	31			225/55			
7,5 x 17	RC27	31	ZP568F	100-206	205/50, 235/45			
	RC32	29	ZP568F	100-206	205/50, 215/50, 225/45, 235/45			Heckantrieb
				132-206	225/50, 245/45			Allrad
7 x 18	RC27	33	-	110-132	225/40, 225/45			Orig.-Verschr.
8 x 18	RC27	33	ZP568F	100-206	225/40, 225/45			
	RC32	33	ZP568F	100-206	225/45, 235/40, 245/40			nur Allrad
	B38	33	ZP568F	100-147	225/45			nur Bremse 305mm
				100-147	215/45, 235/40			
				100-206	225/45, 245/40			

	AC-518	33	AV4	100-147	215/45, 235/40HA		
				100-206	225/45, 245/40HA		
8 x 19	RC34	VA 33	-	100-206	VA 225/40		Orig.-Verschr., Allrad von 132-206kW
9 x 19		HA 34			HA 255/35		
8 x 19	B40	VA 33	ZP568F	100-206	VA 225/35, 225/40		
9 x 19		HA 34			HA 225/40, 245/35, 255/30, 255/35		
8 x 19	B38	33	ZP568F	100-132	225/35		bei 225/40 ✖
				100-206	225/40, 245/35		
	AC-518	33	AV4	100-132	225/35		bei 225/40 ✖
				100-206	225/40, 245/35		
8,5 x 20	RC34	31	ZP568F	132-206	225/35		nur Allrad

Giulia Quadrifoglio					952	5/110	65,1	e3*2007/46*0382*..	
Sensor - Brocksens Universal									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
Kombinationen									
9 x 19	B40	32	-	375	VA 245/35			Orig.-Verschr.	
10,5 x 19		40			HA 265/35M+S				

Junior NEU i.V.			ab 2024	FH1	4/108	65,1	e3*2018/858*00078*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
Noch kein Fahrzeuganbau vorhanden lt. Brock - Stand: 20.01.2025								

Junior elektro NEU i.V.			ab 2024	FH1	4/108	65,1	e3*2018/858*00078*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
Noch kein Fahrzeuganbau vorhanden lt. Brock - Stand: 20.01.2025								

Stelvio		ab 05.2017		949	5/110	65,1	e3*2007/46*0435*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC32	29	ZP568F	110-206	225/65, 235/60, 235/65, 245/60			
	RC27	31	ZP568F	110-206	225/65, 235/65			
8 x 18	RC32	34	ZP568F	110-206	225/60, 235/55, 235/60, 245/55			
	RC27	33	ZP568F	110-206	235/55, 235/60			auch Allrad
	RC32	33	ZP567F	110-206	225/60, 235/55, 235/60, 245/55			
	AC-518	33	AV4	110-206	225/60, 235/55, 235/60, 255/50HA, 255/55HA			
8 x 19	RC29	34	ZP568F	110-206	235/50, 235/55, 255/45, 255/50			
	RC32	34	ZP568F	110-206	235/55			
	RC34	34	-	110-206	225/55, 235/50, 235/55, 245/50, 255/45			Orig.-Verschr.
	B43	34	ZP568F	110-206	235/50, 235/55, 255/45, 255/50HA			
	B38	33	ZP568F	110-206	235/50, 235/55, 255/45, 255/50			
	B40	33	ZP568F	110-206	235/50, 235/55, 255/45, 255/50HA			
	AC-518	33	AV4	110-206	235/50, 235/55, 255/45, 255/50HA			
8,5 x 19	Oxigin 14	32	ZP540	110-206	235/50, 235/55, 255/45			
8,5 x 20	RC29	31	ZP568F	110-206	245/45, 255/40, 255/45			
	RC34	31	ZP568F	110-206	235/45, 245/45, 255/40, 255/45			
	B24	35	ZP568F	110-206	245/45			
9 x 21	B32	30	ZP568F	110-206	245/40, 255/40			
8,5 x 21	B41	30	-	110-206	245/40, 255/35, 255/40			Orig.-Verschr.

Kombinationen							
8 x 19	RC34	33	-	110-206	VA+HA 255/45		Orig.-Verschr.
9 x 19		34					

Tonale		2. Quartal 2022		AV1	5/110	65,1	e3*2018/858*00061*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	37	ZP538F	96	215/60, 225/55, 235/55		Orig.-Verschr., nicht Bremse 330mm	
7,5 x 17	RC27	31	ZP538F	96	215/60, 225/55, 235/55			
				117-132	215/60, 225/55, 235/55		Allrad, für Fahrzeuge mit Brembo-Bremse	
	RC32	29	ZP538F	96-120	215/60		auch Mild-Hybrid	
7,5 x 18	RC30	37	ZP538F	96	215/55, 225/50, 235/50, 245/45		Orig.-Verschr., nicht Bremse 330mm	
	RC32	37	-	96-120	215/55, 225/50, 235/50, 245/45		Orig.-Verschr.	
8 x 18	RC27	33	ZP538F	96	225/50, 245/45			
				117-132	225/50, 245/45		Allrad, für Fahrzeuge mit Brembo-Bremse	
	RC32	34	ZP538F	96-117	215/55, 225/50, 245/45			
8 x 19	RC34	37	-	96-120	225/45, 235/45, 245/40, 245/45		Orig.-Verschr., auch Mild-Hybrid	
	RC32	34	ZP538F	96-120	215/50, 225/45, 235/45, 245/40, 245/45		auch Mild-Hybrid	
	RC34	34	-	96-120	215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr., auch Mild-Hybrid	
	B40	33	ZP538F	96	225/45, 235/45, 245/40		nicht Bremse 330mm	

	B43	34	ZP538F	96	225/45, 235/45, 245/40		nicht Bremse 330mm
8,5 x 19	B32	35	ZP538F	96	225/45, 235/45, 245/40		
				117-132	225/45, 235/45, 245/40		Allrad, für Fahrzeuge mit Brembo-Bremse
	8300 - 1972	33	-	96-120	225/45, 235/45		Orig.-Verschr.
8 x 20	RC36	37	ZP538F	96	225/40, 235/40 , 245/35		nicht Bremse 330mm
	B43	37					i.V.

Audi		Baujahr	Typ	LK/LZ	Nabe		
Audi e-tron		ab 2019	GE	5/112	66,6	e1*2007/46*1914*0-1	
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	RC34	34	-	158	255/55	 Orig.-Verschr.	
	B43	34	ZP559F	158	255/55, 265/50, 265/55, 275/50	 M+S	
	RC27	28	-	158	255/55, 265/50, 265/55	Orig.-Verschr.	
	RC32	28	-	158	255/55	Orig.-Verschr., nur M+S	
	B43	27+28	ZP559F	158	255/55	nur M+S	
	FMI07 Atena	39	F95	158	255/55	Orig.-Verschr., nur M+S	
8,5 x 19	RC34	36	-	158	255/55	 Orig.-Verschr.	
				158	255/55, 265/50, 265/55		
	B41	36	ZP559F	158	255/55, 265/50, 265/55		
	RC34	28	-	158	255/55	Orig.-Verschr.	
	B41	28	ZP559F	158	255/55		
	CA 20	35	ZP568F	158	255/55, 265/50, 265/55		
	FMI07 Atena	28+40	F95	158	255/55		
9 x 19	B41	38	ZP559F	158	255/55		
8 x 20	B40	28	-	158	255/55	Orig.-Verschr., nur M+S	
	B43	27+30	ZP559F	158	255/50	nur M+S	
8,5 x 20	B41 / B43	35	ZP559F	158	255/50, 265/50, 275/45		
	FMI07 Atena	39	F95	158	255/50, 275/45		
9 x 20	B41	38	ZP559F	158	255/50, 275/45, 285/45		
	B43	38	ZP559F	158	255/50, 275/45		
	CA 23	38	ZP559F	158	255/50		
	B40	34	ZP568F	158	255/50, 265/45, 265/50, 275/45, 285/45		
	B41	35	ZP559F	158	255/50, 275/45, 285/45		
	B43	33	ZP559F	158	255/50, 275/45		
		35	ZP559F	158	255/50, 265/50, 275/45, 285/45		
	AC-M08	25	AV1	158	265/45	nicht Bremse 400mm	
	AC-518	33	-	158	255/50, 265/45, 265/50, 275/45, 285/45	Orig.-Verschr., nicht Bremse 400mm	
	AC-522	25	AV1	158	265/45		
		33	-	158	255/50, 265/45, 265/50, 275/45, 285/45	Orig.-Verschr.	
		FMI07 Atena	33	F95	158	255/50, 275/45, 285/45	
	9,5 x 20	CA 17	36	ZP568F	158	265/45, 265/50, 275/45, 285/45	
8,5 x 21	B41	30+34+37+40	ZP559F	158	255/45, 265/45		
	B43	30+37	ZP559F	158	265/45		
9 x 21	B43	36	ZP559F	158	265/45, 275/40		
	CA 17	25	ZP568F	158	265/40, 265/45		
		30+35	ZP568F	158	265/40, 265/45, 275/45		
	Oxigin 18	28	ZP568F	158	265/40, 265/45, 275/45		
9,5 x 21	B41	36	ZP559F	158	255/45, 265/45, 275/40		
	B43	36	ZP559F	158	265/45, 275/40		
	B41	31	ZP559F	158	255/45, 265/45		
9 x 22	AC-M08	26	-	158	255/40, 265/40	Orig.-Verschr.	
9,5 x 22	B41	37	ZP559F	158	275/35		
	AF18	31	-	158	255/40, 265/40, 275/35, 275/40	Orig.-Verschr.	
		37	-	158	255/40, 265/40, 275/35, 275/40, 285/35	Orig.-Verschr.	
10 x 22	B32	32	-	158	265/40	Orig.-Verschr.	
	CA 17	30	ZP568F	158	255/40, 265/40	nicht Bremse 400mm	
	Oxigin 14	35	ZP568	158	255/40, 265/40, 275/35, 275/40		

Audi e-tron Sportback		ab 12/2019		GE		5/112		66,6		e1*2007/46*1914*..	
indirekt - teilweise direkt Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 19	RC34	34	-	158	255/55				Orig.-Verschr.		
	B43	34	ZP559F	158	255/55, 265/50, 265/55, 275/50				M+S		
	RC32	28	-	158	255/55				Orig.-Verschr., nur M+S		
	B43	27+28	ZP559F	158	255/55				nur M+S		
	FMI07 Atena	39	F95	158	255/55				Orig.-Verschr., nur M+S		
8,5 x 19	RC34	36	-	158	255/55				Orig.-Verschr.		
				158	255/55, 265/50, 265/55						
	B41	36	ZP559F	158	255/55, 265/50, 265/55						
	RC34	28	-	158	255/55				Orig.-Verschr.		
	B41	28	ZP559F	158	255/55						
	CA 20	35	ZP568F	158	255/55, 265/50, 265/55						
	FMI07 Atena	28	F95	158	255/55						
8 x 20	B40	28	-	158	255/55				Orig.-Verschr., nur M+S		
	B43	27+30	ZP559F	158	255/50				nur M+S		
8,5 x 20	B41 / B43	35	ZP559F	158	255/50, 265/50, 275/45						

9 x 20	FMI07 Atena	39	F95	158	255/50, 275/45		
	B41	38	ZP559F	158	255/50, 275/45, 285/45		
	B43	38	ZP559F	158	255/50, 275/45		
	CA 23	38	ZP559F	158	255/50		
	B41	35	ZP559F	158	255/50, 275/45, 285/45		
	B43	33	ZP559F	158	255/50, 275/45		
		35	ZP559F	158	255/50, 265/50, 275/45, 285/45		
	AC-M08	25	AV1	158	265/45		nicht Bremse 400mm
	AC-518	33	-	158	255/50, 265/45, 265/50, 275/45, 285/45		Orig.-Verschr., nicht Bremse 400mm
	AC-522	25	AV1	158	265/45		
		33	-	158	255/50, 265/45, 265/50, 275/45, 285/45		Orig.-Verschr.
	FMI07 Atena	33	F95	158	255/50, 275/45, 285/45		
9,5 x 20	CA 17	36	ZP568F	158	265/45, 265/50, 275/45, 285/45		
8,5 x 21	B41	30+34+37+40	ZP559F	158	255/45, 265/45		
	B43	30+37	ZP559F	158	265/45		
9 x 21	B43	36	ZP559F	158	265/45, 275/40		
	CA 17	25	ZP568F	158	265/40, 265/45		
		30+35	ZP568F	158	265/40, 265/45, 275/45		
	Oxigin 18	28	ZP568F	158	265/40, 265/45, 275/45		
9,5 x 21	B41	36	ZP559F	158	265/45		
	B43	36	ZP559F	158	265/45, 275/40		
	B41	31	ZP559F	158	255/45, 265/45		
9 x 22	AC-M08	26	-	158	255/40, 265/40		Orig.-Verschr.
9,5 x 22	B41	37	ZP559F	158	275/35		
	AF18	31	-	158	255/40, 265/40, 275/35, 275/40		Orig.-Verschr.
		37	-	158	255/40, 265/40, 275/35, 275/40, 285/35		Orig.-Verschr.
10 x 22	B32	32	-	158	265/40		Orig.-Verschr.
	CA 17	30	ZP568F	158	255/40, 265/40		nicht Bremse 400mm

Audi e-tron S / e-tron S-Sportback NEU				GE	5/112	66,6	e1*2007/46*1914*..
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	FMI07 Atena	20	F90	226	255/50		
	FMI16 Taara	20	F90	226	255/50		
	B41	20	ZP559F	226	255/50, 265/45, 275/45, 285/45		nur M+S
	AC-522	20	-	226	255/50, 275/45		Orig.-Verschr., nur M+S
10 x 21	B41	20	ZP559F	226	285/40, 295/40, 305/35		
10,5 x 21	B41	19	ZP559F	226	285/40, 295/40		
10 x 22	FMI07 Atena	18	-	226	285/35, 295/35		Orig.-Verschr.
10,5 x 22	B41	19	ZP559F	226	285/35, 295/35		
10 x 23	STC-23	18	KIT0613	226	295/30		Achtung - Kit ist nicht kostenlos - Nettopreis: € 52,00

Audi e-tron GT		ab Mai 2021		FW	5/130	71,6	e1*2018/858*00005*..	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
Kombinationen:								
9 x 20	B41	VA 50	-	140	VA 245/45, 255/40, 265/40			Orig.-Verschr., auch für RS e-tron GT
10,5 x 20		HA 55			HA 285/40, 295/35, 305/35, 315/35			
10 x 22	AC-M08	VA 50	-	140-142	VA 255/35+HA 305/30			Orig.-Verschr., auch für RS e-tron GT, nicht Carbon / Keramikbremse, HA ✖
11,5 x 22		HA 52						

Audi A1/ Sportback (siehe Konfigurator)				ab 08.10	8X	5/100	57,1	e1*2007/46*0414*...., e1*2007/46*0509*...
---	--	--	--	----------	----	-------	------	---

Audi A1 Sportback				11.18	GB	5/100	57,1	e1*2007/46*1892*..
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
5,5 x 15	RC19	40	-	70-85	185/65, 195/60, 195/65, 205/55, 205/60		Orig.-Verschr.	
				70-110	185/65, 195/60, 205/55, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm	
6 x 15	RC27	37	-	70-110	185/65, 195/60, 195/65		Orig.-Verschr., nicht Bremse 312mm	
	RC24	38	-	70-85	185/65, 195/60, 195/65, 205/55, 205/60		Orig.-Verschr., nicht Bremse 312mm	
				70-110	185/65, 195/60, 205/55, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm	
	RC27	35	-	70, 85	185/65, 195/60, 195/65		Orig.-Verschr., nicht Bremse 312mm	
				70-110	185/65, 195/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm	
				70-110	185/65, 195/60, 205/55, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm	
	RC30	38	-	70-85	185/65, 195/60, 195/65, 205/55, 205/60		Orig.-Verschr., nicht Bremse 312mm	
				70-110	185/65, 195/60, 205/55, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm	
	RC27	35+38	-	70-85	185/55, 185/60, 195/55		Orig.-Verschr.	
				70-110	185/55M+S, 185/60M+S, 195/55M+S			
		45	-	70-85	185/55, 185/60, 195/55, 205/50, 205/55, 215/50		Orig.-Verschr.	

6 x 16	RC30	38	-	70-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr., nur M+S
				70-85	185/55, 185/60, 195/55		Orig.-Verschr.
				70-110	185/55M+S, 185/60M+S, 195/55M+S		
		45	-	70-85	185/55, 185/60, 195/55, 205/50, 205/55, 215/50	Orig.-Verschr.	
				70-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr., nur M+S
6,5 x 16	RC32	40	-	70-147	185/55, 185/60, 195/55 , 205/50, 205/55		Orig.-Verschr.
	70-110			185/55M+S, 185/60M+S, 195/55		Orig.-Verschr.	
	RC27	40	-	70-155			195/55M+S
	70-85			185/55			
	RC34	40	-	70-152	185/60, 195/55 , 205/55		Orig.-Verschr.
	RC30	38	-	70-85	185/55, 185/60		Orig.-Verschr.
				70-110	185/55M+S, 185/60M+S, 195/55		
				70-152	195/55M+S		
6,5 x 17	RC27	39+40	-	70-110	185/50M+S, 205/45		Orig.-Verschr.
				70-147	205/45M+S		
7 x 17	RC30	46	-	70-110	205/45, 215/45, 225/45		Orig.-Verschr.
				70-147	205/45M+S, 215/45M+S		
	B39	46	-	70-110	205/45, 215/45, 225/45		Orig.-Verschr.
				70-147	205/45M+S, 215/45M+S		
7,5 x 17	RC27	46	-	70-147	205/45, 215/45		Orig.-Verschr.
	RC32	46	-	70-152	195/45, 205/45, 215/45 , 225/45		Orig.-Verschr.
	RC34	46	-	70-147	195/45, 205/45, 215/45 , 225/45		Orig.-Verschr.
7 x 18	RC27	47	-	70-147	215/40		Orig.-Verschr., Frontantrieb
	RC32	39	-	70-147	215/40		Orig.-Verschr.
7,5 x 18	RC32	46	-	70-147	205/40, 215/40 , 225/35		Orig.-Verschr.
	B39	42	ZP516	70-152	205/40		

Audi A1 City Carver / Allstreet				ab 2019	GB	5/100	57,1	e1*2007/46*1892*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 16	RC32	40	-	70-110	205/60, 215/55, 215/60				Orig.-Verschr.
	RC34	40	-	70-110	205/60, 215/55, 215/60				Orig.-Verschr.
	RC27	40	-	70-110	205/60, 215/55				Orig.-Verschr.
	RC30	38	-	70-110	205/60, 215/55				Orig.-Verschr.
	CA 20	38	ZP516	70-110	205/60, 215/55				
6,5 x 17	RC27	40	-	70-110	205/50, 205/55, 215/50				Orig.-Verschr.
7 x 17	RC34	43	-	70-110	205/55				Orig.-Verschr.
	RC27	43	ZP516	70-110	205/50, 205/55, 215/50, 225/45				
7 x 18	RC32	39	-	70-110	205/45, 205/50, 215/45				Orig.-Verschr.
7,5 x 18	Oxigin 25	36	ZP516	70-110	205/45, 215/45				

Audi A3 / Sportback / Cabrio			ab 07.12	8V	5/112	57,1	e1*2007/46*0607*...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC27	48	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. FL2016, nur M+S, ECE nur für Sportback
	RC30	48	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. FL2016, nur M+S
	RC34	48	-	77-140	205/55		Orig.-Verschr., nur M+S
	RC27	43+50	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. FL2016, nur M+S, ET50 nur Sportback
	RC34	43	-	77-140	205/55		Orig.-Verschr., nur M+S, Sportback
6,5 x 16	RC24	43	-	77-135	205/55M+S		Orig.-Verschr.
		-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., bei 225/50 ✖	
		46	-	77-135	205/55		Orig.-Verschr.
		-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016	
	RC27	43	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., nur M+S, incl. Facelift 2016, nur Limousine u. Cabrio
		46	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016
	RC30	46	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. FL2016
	RC32	43	-	77-140	205/55, 205/60, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Cabrio u. Stufenheck, nur M+S
		46	-	77-140	205/55, 215/50, 215/55		Orig.-Verschr., Sportback
			-	77-140	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Sportback, auch Hybrid Fahrzeuge
			-	77-140	205/55, 205/60, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Cabrio u. Stufenheck, nur M+S
	RC34	43	-	77-140	205/55, 205/60, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Stufenheck u. Cabrio
		46	-	77-140	205/55, 205/60, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Stufenheck u. Cabrio
	RC24	50	-	77-140	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Sportback
			-	77-140	205/55, 215/55, 225/50		Orig.-Verschr.
	RC27	42	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016, Sportback bei 225/50 ✖
		44+50	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016
		44	-	77-135	205/55, 215/55, 225/50		Orig.-Verschr.
	RC30	48+50	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016

7 x 16	RC32	48	-	77-140	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Sportback
					205/55, 205/60, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Cabrio u. Stufenheck, nur M+S
	CA 20	45	ZP560D	77-140	205/55, 215/55, 225/50		incl. Facelift 2016, nur M+S
	RC30	48	-	77-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2016
6,5 x 17	RC34	43	-	77-140	205/55		Orig.-Verschr., nur Stufenheck u. Cabrio
	RC27	43	-	77-140	205/50M+S		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio, ET43
		48,5	-	77-140	205/50		Orig.-Verschr., incl. Facelift 2016, nur M+S
7 x 17	RC27	42+43+45+46	- (V7)	77-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016, Ausführung "V7"
		47	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
	RC30	38+40+45+49	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016, ET38 Sportback nur 215/45 auflagenfrei!
	RC32	45+47+49	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., Sportback
				77-140	205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr., Stufenheck u. Cabrio
	B39	40+49	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
	RC27	45	ZP568F (V10)	77-140	205/50, 215/45, 225/45		incl. Facelift 2016, Ausführung "V10"
7,5 x 17	RC27	51	-	77-140	225/45		Orig.-Verschr., incl. Facelift 2016
	RC29	51	-	77-140	225/45		Orig.-Verschr., incl. Facelift 2016
				77-140	205/50, 215/45, 225/45		Orig.-Verschr., nur Sportback
	RC32	43	-	77-140	225/45		Orig.-Verschr.
		51	-	77-140	225/45		Orig.-Verschr.
				77-140	205/50, 215/45, 225/45		Orig.-Verschr., nur Sportback
	RC34	51	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., nur Sportback
				77-140	205/45, 215/45		Orig.-Verschr., Stufenheck u. Cabrio
	RC24	51	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. FL2016, nur Sportback
	RC27	49	-	77-132	225/45		Orig.-Verschr.
				77-140	205/50, 215/45, 225/45		Orig.-Verschr., Sportback bei 205/50, 225/45 ✖
	RC29	49	-	77-140	205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
	RC32	49	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., Sportback
				77-140	205/45, 205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., Stufenheck u. Cabrio
	RC34	46+47	-	77-140	205/50, 215/45, 225/45		Orig.-Verschr., nur Sportback
				77-140	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr., Stufenheck u. Cabrio
	RC28	45	ZP560D	77-140	205/50, 215/45, 225/45, 235/45		incl. Facelift 2016, Sportback bei 235/45 ✖
7 x 18	B24	47	ZP560D	77-140	205/50, 215/45, 225/45, 235/45		incl. Facelift 2016, Sportback bei 235/45 ✖
	Oxigin 18 / 19	45	ZP560D	77-135	215/45, 225/45, 235/45		
	Oxigin 25	45	ZP560D	77-140	215/45, 225/45, 235/45		Limousine u. Cabrio, nicht für 18 Zoll Serie
	RC27	45	-	77-140	215/40		Orig.-Verschr.
	RC32	43+45	-	77-140	205/40, 205/45, 215/40		Orig.-Verschr.
	RC30	51	-	77-140	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016, nur Sportback
	RC32	51	-	77-140	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
	RC34	51	-	77-140	225/40		Orig.-Verschr.
	B32	51	-	77-140	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., Sportback, incl. Facelift 2016
	B39	51	-	77-140	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016, nur Sportback
7,5 x 18	Oxigin 18	51	-	77-221	225/40		Orig.-Verschr.
	RC30	49	-	77-140	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
		45	-	77-140	205/40, 205/45, 215/40		Orig.-Verschr.
	RC32	49	-	77-140	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
	RC34	46	-	77-140	205/40, 205/45, 215/40		Orig.-Verschr.
	AC-521	50	-	77-140	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
	RC27	46	-	77-140	215/40, 225/35, 225/40, 235/35, 235/40		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio, ECE nur Limousine u. Cabrio
				77-140	215/40, 225/35, 225/40		Orig.-Verschr., Sportback
	RC32	46	-	77-140	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr., Stufenheck u. Cabrio
				77-140	205/40, 205/45, 215/40		Orig.-Verschr., Sportback
8 x 18	RC27	44		77-140	205/40, 215/40, 215/45, 225/40, 235/35		Orig.-Verschr.
	RC29	44	-	77-140	215/40, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr. bei 245/35 ✖
		50	-	77-140	215/40, 225/35, 225/40		Orig.-Verschr.
	RC32	44	-	77-140	205/40, 205/45, 215/40, 215/45, 225/35, 225/40, 235/35		Orig.-Verschr.
	RC34	40+45	-	77-140	205/40		Orig.-Verschr., nur Sportback, ET45 auch 215/40
					205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr., Limousine u. Cabrio
	B37	44	-	77-135	215/40, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr. bei 245/35 ✖
		50	-	77-135	215/40, 225/35, 225/40		Orig.-Verschr.
	B38	44	-	77-140	215/40, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr., Limousine u. Cabrio, bei 245/35 ✖
				77-140	215/40		Orig.-Verschr., nur Sportback
		50	-	77-140	215/40, 225/35, 225/40		Orig.-Verschr.
	RC34	48	ZP560D	77-140	205/40, 205/45, 215/40		nur Sportback
					205/40, 205/45, 215/40, 215/45, 225/35, 225/40, 235/35, 235/40		Limousine u. Cabrio

	B36	45	ZP560D	77-140 77-140	215/40, 225/35, 225/40, 235/35, 235/40 215/40, 225/35, 225/40		incl. FL2016, Limousine u. Cabrio incl. Facelift 2016, Sportback
	B42 / B44	45	ZP560D	77-140 77-140	215/40, 225/35, 225/40, 235/40 215/40, 225/35, 225/40		incl. FL2016, Limousine u. Cabrio incl. Facelift 2016, Sportback
	AC-518	50	AV4	77-140	215/40, 225/35, 225/40		incl. Facelift 2016
	AC-521	45	- +R	77-140	215/40, 225/35, 225/40, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2016, Limousine u. Cabrio
				77-140	215/40, 225/35, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2016, Sportback
	AF18 / AF20	48	-	77-140	215/40, 225/35, 225/40, 235/35, 235/40 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016, Limousine u. Cabrio Orig.-Verschr., incl. Facelift 2016, Sportback
					215/40, 225/35, 225/40, 235/40		incl. FL2016, Cabrio u. Limousine
7,5 x 19	RC32	51	-	77-140	215/35, 225/35		Orig.-Verschr.
	RC34	48	-	77-140	215/35, 225/35		Orig.-Verschr.
	B32	43	-	77-140	215/35, 225/35		Orig.-Verschr.
		51	-	77-140	215/35, 225/35		Orig.-Verschr., incl. Facelift 2016, nur Sportback
	B39	51	-	77-140	215/35, 225/35		Orig.-Verschr., incl. FL2016, nur Sportback
	AC-521	50	-	77-140	215/35, 225/35		Orig.-Verschr., incl. Facelift 2016
	Oxigin 18	51	-	77-140	225/35		Orig.-Verschr.
8 x 19	RC29	49	-	77-140	235/35		Orig.-Verschr., incl. Facelift 2016
				77-140	215/35, 225/35, 235/35		Orig.-Verschr.
	RC34	49	-	77-140	235/35		Orig.-Verschr.
	B40	49	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr., incl. Facelift 2016
	FMI07 Atena	49	-	77-140	235/35		Orig.-Verschr.
	B43	49	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr.
	RC27	44	-	77-140	225/35, 235/35		Orig.-Verschr., Cabrio u. Limousine
	RC32	49	-	77-140	235/35		Orig.-Verschr., i.V.
		50	-	77-140	215/35, 225/35		Orig.-Verschr.
	RC34	50	-	77-140	215/35, 225/30, 225/35		Orig.-Verschr., Stufenheck u. Cabrio
				77-140	215/35, 225/35		Orig.-Verschr., Sportback
	B38	44+50	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr., incl. FL2016, bei ET50 nur bis 225/35
	B40	45	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
		50	-	77-140	215/35, 225/35		Orig.-Verschr., incl. FL2016, Sportback
	B43	45+47	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr., incl. Facelift 2016
		40+50	-	77-140	215/35, 225/35		Orig.-Verschr., incl. Facelift 2016
	AC-518	47	AV4	77-140	215/35, 225/35, 235/35		incl. Facelift 2016, Limousine u. Cabrio
				77-140	215/35, 225/35		incl. Facelift 2016, Sportback
	AC-521	45	-	77-140	215/35, 225/35, 235/35		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
	CA 17	43	ZP560D	77-140	225/35, 235/35		Limousine u. Cabrio
		45	ZP560D	77-140	215/35 225/35, 235/35		Sportback Limousine u. Cabrio
	CA 19	47	ZP560D	77-140	225/35, 235/35		Limousine u. Cabrio
	Oxigin 29	43	ZP560D	77-140	215/35, 225/35, 235/35		
8,5 x 19	B36 / B37	45	ZP560D	77-140	215/35, 225/35, 235/30, 235/35		Limousine u. Cabrio
	B42	47	ZP560D	77-140	215/35, 225/35		incl. Facelift 2016, Limousine u. Cabrio
					215/35		incl. Facelift 2016, Sportback
	B44	42	ZP560D	77-140	215/35, 225/35		incl. Facelift 2016, nur Limousine u. Cabrio
	AF18	48	-	77-140	215/35, 225/35		Orig.-Verschr., incl. Facelift 2016
	CA 23	45	ZP560D	77-140	215/35, 225/35, 235/30, 235/35		incl. Facelift 2016, nur Limousine u. Cabrio
	Oxigin 18	45	ZP560D	77-140	215/35, 225/35, 235/30, 235/35		incl. Facelift 2016, nur Cabrio u. Limousine
8 x 20	B38	40	-	77-140	225/30		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
		41	-	77-140	225/30		Orig.-Verschr., Limousine u. Cabrio
	B40	41	-	77-140	225/30		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
	B43	45	-	77-140	225/30, 235/30		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
8,5 x 20	RC29	45	ZP560D	77-140	235/30		incl. Facelift 2016, Limousine u. Cabrio
	B32	45	ZP560D	77-140	235/30		incl. Facelift 2016, Limousine u. Cabrio
	B42	45	ZP560D	77-140	235/30		incl. Facelift 2016, Limousine u. Cabrio
	AC-518	45	- +R	77-140	235/30		Orig.-Verschr. + Red.Ringe BA25 , incl. FL2016, Limousine u. Cabrio
	AC-521	45	-	77-140	235/30		Orig.-Verschr., incl. FL2016, Limousine u. Cabrio
	AF18	45	- +R	77-140	235/30		Orig.-Verschr. + Ringe BA25 , nicht Sportback

Audi A3 / Sportback e-tron			2014 - 2016		8V	5/112	57,1	e1*2007/46*0607*...	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6 x 16	RC27	48	-	110	205/55, 215/55				Orig.-Verschr., incl. FL2016, nur M+S
		43+50	-	110	205/55, 215/55				Orig.-Verschr., incl. FL2016, nur M+S

6,5 x 16	RC30	46	-	110	205/55		Orig.-Verschr., incl. Facelift 2016
	RC30	46	ZP560D	110	205/55, 215/55		incl. Facelift 2016
	CA 20	45	ZP560D	110	205/55, 215/55		incl. Facelift 2016
7 x 16	RC30	48	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2016
6,5 x 17	RC27	39+46	-	110	205/50		Orig.-Verschr., incl. Facelift 2016
	RC27	46	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
7 x 17	RC30	45+49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
	RC27	45	ZP568F (V10)	110	205/50, 215/45, 225/45		incl. Facelift 2016, Ausführung "V10"
7,5 x 17	RC27	51	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
	RC29	51	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
		49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2016
	RC28 / RC29	45	ZP560D	110	205/50, 215/45, 225/45		incl. Facelift 2016
	AC-518	47	AV4	110	205/50, 215/45, 225/45		incl. Facelift 2016
7,5 x 18	B32	48	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
	AC-521	50	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
8 x 18	RC27	46	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
	RC29	50	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
	B42 / B44	45	ZP560D	110	215/40, 225/35, 225/40		incl. Facelift 2016
	AC-518	50	AV4	110	215/40, 225/35, 225/40		incl. Facelift 2016
	AC-521	45	- +R	110	215/40, 225/35, 225/40		Orig.-Verschr. + Ringe 66,6-57,1 , incl. FL2016
	AF18 / AF20	48	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2016
	CA 20	45	ZP560D	110	215/40, 225/35, 225/40		incl. Facelift 2016
7,5 x 19	AC-521	50	-	110	225/35		Orig.-Verschr., incl. Facelift 2016
8 x 19	B40	49+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2016
	B43	45+47+ 49+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2016
	AC-518	47	AV4	110	225/35		incl. Facelift 2016
	AC-521	45	-	110	225/35		Orig.-Verschr., incl. Facelift 2016
8,5 x 19	AF18	48	-	110	225/35		Orig.-Verschr., incl. Facelift 2016

Audi A3

ab 2020

GY

5/112

57,1

e1*2007/46*2060*...

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	43	-	110-147	205/55	 Orig.-Verschr. nur M+S
	RC34	43	-	81-147	205/55, 205/60, 215/50, 215/55, 225/50	 Orig.-Verschr.
	RC24	43	-	110	205/55, 215/55, 225/50	 Orig.-Verschr. nur M+S
	RC27	46	-	110	205/55, 215/55, 225/50	Orig.-Verschr. nur M+S
	RC30	41	-	110-147	205/55, 215/55	Orig.-Verschr. nur M+S
		42+46	-	110-147	205/55, 215/55, 225/50	Orig.-Verschr. nur M+S
		44+48	-	110	205/55, 215/55, 225/50	Orig.-Verschr. nur M+S
	RC32	41	-	81-147	205/55, 205/60, 215/50, 215/55	Orig.-Verschr.
		43	-	81-147	205/55, 205/60, 215/50, 215/55, 225/50	 Orig.-Verschr.
		46+48	-	110	205/55, 205/60, 215/50, 215/55, 225/50, 235/50	Orig.-Verschr.
	RC34	46	-	81-147	205/55, 205/60, 215/50, 215/55, 225/50, 235/50	Orig.-Verschr.
	CA 20	45	ZP560D	110-147	205/55, 215/55, 225/50	nur M+S
7 x 16	RC30	43	-	81-110	205/55, 215/55, 225/50	
				110-147	205/55, 215/55, 225/50	Sportback bei 225/50 ✖
6,5 x 17	RC27	43	-	110-147	205/50, 215/50	 Orig.-Verschr. nur M+S
	RC34	43	-	81-150	205/50, 215/50	 Orig.-Verschr.
	RC27	38	-	81-147	205/50, 215/50	Orig.-Verschr., nur M+S
	RC34	46	-	81-147	205/50, 215/50	Orig.-Verschr.
7 x 17	RC27	39	-	110	205/50, 215/50	Orig.-Verschr. nur M+S
		40+42+ 43+45+ 46	-	110	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
				110, 147	205/50, 215/45, 215/50, 225/45	Orig.-Verschr. nur M+S
		47	-	110	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
				110-147	205/50, 215/45, 215/50, 225/45	Orig.-Verschr. nur M+S
		40	-	110	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
	RC30	45	-	110	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
				110-147	205/50, 215/45, 215/50, 225/45	Orig.-Verschr. nur M+S
	RC32	40+47	-	81-147	205/50, 215/45, 225/45	Orig.-Verschr.
		49	-	110	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
	RC34	40	-	81-147	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
	RC27	45	ZP568F (V10)	110	205/50, 215/45, 215/50, 225/45	Ausführung "V10"
				110-147	205/50, 215/45, 215/50, 225/45	nur M+S, Ausführung "V10"
	CA 26	42+47	ZP560D	110	205/50, 215/45, 215/50, 225/45	
				110-147	205/50, 215/45, 215/50, 225/45	nur M+S
8 x 19	RC27	40	-	110	205/50, 215/45, 215/50, 225/45, 235/45	Orig.-Verschr., Limousine
				110-147	205/50, 215/45, 215/50, 225/45, 235/45	Orig.-Verschr., nur M+S, Limousine
	RC34	43	-	81-147	205/50, 215/45, 215/50, 225/45, 235/45	Orig.-Verschr.

7,5 x 17		46	-	110	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.	
	RC34	46	-	81-147	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.	
		47+51	-	110	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., ET47 auch 245/45	
	RC28 / RC29	45	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45		RC29 nicht Bremse 340mm	
				110-147	205/50, 215/45, 215/50, 225/45, 235/45		nur M+S, RC29 nicht Bremse 340mm	
	B24	47	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45			
				110-147	205/50, 215/45, 215/50, 225/45, 235/45			
B36	45	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45		nicht Bremse 340mm		
			110-147	205/50, 215/45, 215/50, 225/45, 235/45		nur M+S		
Oxigin 25	45	ZP560D	81-147	205/50, 215/45, 215/50, 225/45, 235/45				
7 x 18	RC27	43+45	-	110	205/45, 215/40, 215/45		Orig.-Verschr.	
				81-147	205/45, 215/40, 215/45		Orig.-Verschr.	
7,5 x 18	RC32	40+45	-	110	205/40, 205/45, 215/40, 215/45		Orig.-Verschr.	
	RC32	45	-	110	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr.	
	RC34	46	-	110	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr.	
	B32	48	-	81-147	205/45, 215/40, 215/45, 225/40		Orig.-Verschr.	
	RC30	45	ZP560D	110	205/45, 215/40, 215/45, 225/40			
				110, 147	205/45, 215/40, 215/45, 225/40		M+S	
	B32	45	ZP560D	81-147	205/45, 215/40, 215/45, 225/40			
	B39	45	ZP560D	81-110	205/45, 215/40, 215/45, 225/40			
				110-147	205/45, 215/40, 215/45, 225/40		nur M+S	
	AC-MB6 / AC-M10	45	- +R	110	205/45, 215/40, 215/45, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
Oxigin 25	44	ZP560D	81-147	205/45, 215/40, 215/45, 225/40		nur M+S		
8 x 18	RC27	46	-	81-147	215/40M+S, 215/45M+S, 225/40, 235/40		Orig.-Verschr.	
				110	215/40, 215/45			
	RC32	46	-	81-147	225/40		Orig.-Verschr.	
	RC27	44	-	110	215/40, 215/45		Orig.-Verschr.	
				110, 147	215/40M+S, 215/45M+S, 225/40, 235/40			
	RC29	44	-	110	215/40, 215/45		Orig.-Verschr.	
				110, 147	215/40M+S, 215/45M+S, 225/40			
		50	-	110	215/40, 215/45		Orig.-Verschr.	
	RC34	40	-	110	205/40, 205/45, 215/40, 215/45		Orig.-Verschr.	
		45	-	81-147	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr.	
	B37	44+50	-	110	215/40, 215/45		Orig.-Verschr., ET44 bei 235/40 ✖	
				110, 147	215/40M+S, 215/45M+S, 225/40, 235/40			
	B38	50	-	110	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.	
	RC34	40	ZP560D	81-147	205/40, 205/45, 215/40, 215/45			
		43	ZP560D	110	205/40, 205/45, 215/40, 215/45, 225/40			
		48	ZP560D	81-147	215/40, 215/45, 225/40, 235/35, 235/40			
	B24	48	ZP560D	110	215/40, 215/45			
				110-147	215/40M+S, 215/45M+S, 225/40, 235/40			
	B42	45	ZP560D	110	215/40, 215/45			
				110-147	215/40M+S, 215/45M+S, 225/40			
	B44	45	ZP560D	110	215/40, 215/45			
				110-147	215/40M+S, 215/45M+S, 225/40, 235/40			
	AC-M10	40	- +R	110	215/40, 215/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, Sportback bei 225/40 ✖	
				110, 147	215/40M+S, 215/45M+S, 225/40			
		45	ZP560D	110	215/40, 215/45		Sportback bei 235/40 ✖	
	AC-521	45	- +R	110	215/40, 215/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
				110, 147	215/40M+S, 215/45M+S, 225/40			
	AF20	48	-	110	215/40, 215/45		Orig.-Verschr.	
				110, 147	215/40M+S, 215/45M+S, 225/40, 235/40			
	CA 20	45	ZP560D	110	215/40, 215/45			
				110, 147	215/40M+S, 215/45M+S, 225/40			
	FMI11 Elatha	39	- +R	81-147	205/40, 205/45, 215/40, 215/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
	FMI12 Kari	45	Kit 0353	81-147	205/40, 205/45, 215/40, 215/45, 225/40			
	8,5 x 18	B32	48	ZP560D	110	215/40		
					110, 147	215/40M+S, 225/40		
	7,5 x 19	RC32	51	-	81-147	215/35, 225/35		Orig.-Verschr.
RC34		48	-	81-147	215/35, 225/35		Orig.-Verschr.	
CA 26		40	ZP560D	110	215/35, 225/35			
			110-147	225/35M+S				
	RC34	49	-	110-147	235/35		Orig.-Verschr.	
	B40	49	-	110-147	225/35, 235/35		Orig.-Verschr.	
				110	215/35			
	FMI07 Atena	49	-	110	235/35		Orig.-Verschr.	
	B43	49	-	110-147	225/35, 235/35		Orig.-Verschr.	
				110	215/35			
RC29	49	-	110	215/35		Orig.-Verschr.		

8 x 19	RC29	45	-	110, 147	225/35, 235/35	Orig.-Verschr.
	RC32	45	-	110	215/35, 225/35	Orig.-Verschr.
		50	-	110	215/35, 225/35, 235/35	Orig.-Verschr.
	RC34	44+45	-	81-147	215/35, 225/35	Orig.-Verschr.
		50	-	81-147	215/35, 225/35, 235/35	Orig.-Verschr.
	B38 / B40	50	-	110	215/35	Orig.-Verschr.
				110, 147	225/35, 235/35	
	B43	45+47+50	-	81-110	215/35	Orig.-Verschr.
				110-147	225/35, 235/35	
	AC-521	45	-	110	215/35	Orig.-Verschr.
			110-147	225/35, 235/35		
CA 17	45	ZP560D	81-110	225/35		
CA 19	47	ZP560D	81-228	225/35, 235/35	nicht Bremse 357x34mm	
Oxigin 29	43	ZP560D	110	215/35		
			110-147	225/35		
8,5 x 19	B36	45	ZP560D	110	215/35, 235/30	Sportback bei 235/30 u. 235/35 ✖
				110-147	225/35, 235/35	
	B37	45	ZP560D	110	215/35, 235/30	
				110-147	225/35, 235/35	
	B42	47	ZP560D	110	215/35	
				110, 147	225/35	
	B44	42	ZP560D	110	215/35	nur Limousine
				110, 147	225/35	
	AC-M10	45	AV4+R	110	215/35, 235/30	+ Red.Ringe BA25=66,6-57,1, Sportback bei 235/30 u. 235/35 ✖
				110, 147	225/35, 235/35	
CA 23	45	ZP560D	110	215/35, 235/30	Sportback bei 235/30 u. 235/35 ✖	
			110-147	225/35, 235/35		
Oxigin 28	45	ZP560D	110	215/35, 235/30	Sportback bei 235/30 u. 235/35 ✖	
			110-147	225/35, 235/35		
FMI11 Elatha	45	- +R	81-147	215/35, 225/35	Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
8300 - 1972	45	F85+R	81-147	225/35	+Red.Ringe BA25=66,6-57,1	
8 x 20	RC36	47+50	-	110	225/30	Orig.-Verschr.
				110-147	235/30	
	B43	45+47+50	-	110	225/30	Orig.-Verschr.
				110, 147	235/30	
	B38 / B43	48	ZP560D	110	225/30	
110, 147				235/30		
8,5 x 20	RC29	45	ZP560D	110-147	235/30	Limousine
	B42	45	ZP560D	110-147	235/30	Sportback ✖
	AC-521	45	-	110-147	235/30	Orig.-Verschr.

Audi A3 Sportback 40 TFSle Hybrid				ab 2020	GY	5/112	57,1	e1*2007/46*2060*...
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC24	42	-	110	205/55, 215/55, 225/50		Orig.-Verschr. nur M+S, nicht Bremse 340mm	
	RC27	46	-	110	205/55, 215/55, 225/50		Orig.-Verschr. nur M+S	
	RC30	41+42+46	-	110	205/55, 215/55, 225/50		Orig.-Verschr. nur M+S, nicht Bremse 340mm, ET41 bei 225/50 ✖	
	CA 20	45	ZP560D	110	205/55, 215/55, 225/50		nur M+S, nicht Bremse 340mm	
7 x 16	RC30	43	-	110	205/55, 215/55		Orig.-Verschr., nicht Bremse 340mm	
		48	-	110	205/55, 215/55, 225/50		Orig.-Verschr., nicht Bremse 340mm	
6,5 x 17	RC27	43	-	110	205/50		Orig.-Verschr., nur M+S	
		39+48,5	-	110	205/50, 215/50		Orig.-Verschr., nur M+S	
		40+42+43+46+47	-	110	205/50, 215/45, 215/50, 225/45		Orig.-Verschr.	
7 x 17	RC27	40+45	-	110	205/50, 215/45, 215/50, 225/45		Orig.-Verschr.	
	B39	40	-	110	205/50, 215/45, 215/50, 225/45		Orig.-Verschr.	
	RC27	45	ZP568F (V10)	110	205/50, 215/45, 215/50, 225/45		Ausführung "V10"	
	B39	47	ZP560D	110	205/50, 215/45, 215/50, 225/45			
	CA 26	42+47	ZP560D	110	205/50, 215/45, 215/50, 225/45			
	RC24	42	-	110	205/50, 215/45, 225/45		Orig.-Verschr.	
7,5 x 17	RC27	40	-	110	205/50, 215/45, 225/45		Orig.-Verschr.	
	RC28 / RC29	45	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45		RC29 nicht Bremse 340mm	
	B24	47	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45			
	B36	45	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45		nicht Bremse 340mm	
	Oxigin 25	45	ZP560D	110	205/50, 215/45, 215/50, 225/45, 235/45			
7 x 18	RC27	45	-	110	205/45, 215/40, 215/45		Orig.-Verschr.	
	B32	46+48	-	110	205/45, 215/40, 215/45, 225/40		Orig.-Verschr.	
7,5 x 18	RC30	35	ZP560D	110	205/45			
		45	ZP560D	110	205/45, 215/40, 215/45, 225/40			
	B32	45	ZP560D	110	205/45, 215/40, 215/45, 225/40			

	B39	45	ZP560D	110	205/45, 215/40, 215/45, 225/40		
				110, 130	205/45, 215/40, 215/45, 225/40		nur M+S
	AC-MB6	45	- +R	110	205/45, 215/40, 215/45, 225/40		Orig.-Verschr. + Red.Ringe 66,6-57,1
8 x 18	RC27	46	-	110	225/40		Orig.-Verschr.
				110	215/40, 215/45		
				110, 130	225/40, 235/40		
		44	-	110	215/40, 215/45, 225/40		Orig.-Verschr.
	RC29	44	-	110	215/40, 215/45, 225/40		Orig.-Verschr.
		50	-	110	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.
	B37	44+50	-	110	215/40, 215/45, 225/40, 235/40		Orig.-Verschr., ET44 bei 235/40 ✖
	B38	50	-	110	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.
	RC29	45	ZP560D	110	215/40, 215/45, 225/40		
	B24	48	ZP560D	110	215/40, 215/45, 225/40, 235/40		
	B37 / B38	45	ZP560D	110	215/40, 215/45, 225/40		
	B36 / B42	45	ZP560D	110	215/40, 215/45, 225/40		
	B44	45	ZP560D	110	215/40, 215/45, 225/40		
	AC-M10	40	- +R	110	215/40, 215/45		Orig.-Verschr. + Red.Ringe 66,6-57,1
		45	ZP560D	110	215/40, 215/45, 225/40		
	AC-521	45	- +R	110	215/40, 215/45, 225/40		Orig.-Verschr. + Red.Ringe 66,6-57,1
	AF20	48	-	110	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.
	CA 20	45	ZP560D	110	215/40, 215/45, 225/40		
8,5 x 18	B32	48	ZP560D	110	215/40, 225/40		
7,5 x 19	B32	43	-	110	225/35		Orig.-Verschr.
	B39	43	ZP560D	110	225/35		
	CA 26	40	ZP560D	110	225/35		
8 x 19	RC27	50	-	110	225/35, 235/35		Orig.-Verschr.
	RC29	49	-	110	225/35, 235/35		Orig.-Verschr.
	B38	50	-	110	225/35, 235/35		Orig.-Verschr.
	B40	49+50	-	110	225/35, 235/35		Orig.-Verschr.
	B43	47+49+50	-	110	225/35, 235/35		Orig.-Verschr.
	AC-518	47	ZP568F	110	225/35, 235/35		
	AC-521	45	-	110	225/35		Orig.-Verschr.
	CA 19	47	ZP560D	110	225/35, 235/35		nicht Bremse 357x34mm
8,5 x 19	Oxigin 29	43	ZP560D	110	225/35		
	B36 / B37	45	ZP560D	110	225/35		
	B42	47	ZP560D	110	225/35		
	AC-M10	45	AV4+R	110	225/35		+ Red.Ringe BA25=66,6-57,1
	CA 23	45	ZP560D	110	225/35		
	Oxigin 28	45	ZP560D	110	225/35		
8 x 20	RC36	47+50	-	110, 130	235/30		Orig.-Verschr.
	B43	45+47	-	110	235/30		Orig.-Verschr.
		50	-	110, 130	235/30		Orig.-Verschr.
	B38 / B43	48	ZP560D	110	235/35		

Audi A3 Allstreet		NEU	im Laufe 2022		GY	e1*2007/46*2060*22-24	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
Keine Räder in Planung lt. Thorsten - Stand: 21.10.2024							

Audi S3 / Sportback (siehe Konfigurator)	ab 2013	8V	5/112	57,1	e1*2007/46*0607*...		
---	---------	----	-------	------	---------------------	--	--

Audi S3 Sportback	GY	5/112	57,1	e1*2007/46*2060*..
kein Sensor - indirektes RDKS				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	43	-	228	205/50		Orig.-Verschr., nur M+S, auch Limousine
	RC34	43	-	228	205/50		Orig.-Verschr., nur M+S
7 x 17	RC27	40+42+43+45+46+47	-	228	205/50, 215/45, 215/50, 225/45		Orig.-Verschr., nur M+S
	RC30	45	-	228	205/50, 215/45, 215/50, 225/45		Orig.-Verschr., nur M+S
	RC34	40	-	228	205/50		Orig.-Verschr., nur M+S
	RC27	45	ZP568F (V10)	228	205/50, 215/45, 215/50, 225/45		incl. Facelift 2016, nur M+S, Ausführung "V10"
	CA 26	42+47	ZP560D	228	205/50, 215/45, 215/50, 225/45		nur M+S
7,5 x 17	RC24	42	-	228	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., nur M+S, auch Limousine, Sportback bei 215/50 u. 235/45 ✖
	RC27	40+41	-	228	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., nur M+S, auch Limousine, Sportback bei 215/50 u. 235/45 ✖
	RC28	45	ZP560D	228	205/50, 215/45, 215/50, 225/45, 235/45		nur M+S
	B24	47	ZP560D	228	205/50, 215/45, 215/50, 225/45, 235/45		nur M+S

7,5 x 18	RC30	49	-	228	205/45, 215/40, 215/45		Orig.-Verschr., nur M+S
				228, 245	225/40		
	B39	49+51	-	228	205/45, 215/40, 215/45		Orig.-Verschr., nur M+S
				228, 245	225/40		
		45	ZP560D	228	205/45, 215/40, 215/45		nur M+S
	AC-MB6 / AC-M10			228, 245	225/40		
		45	- +R	228	205/45, 215/40, 215/45		Orig.-Verschr. + Red.Ringe 66,6-57,1, nur M+S
8 x 18	RC27	46	-	228, 245	225/40		Orig.-Verschr.
				228	215/40M+S, 215/45M+S		
				228, 245	225/40, 235/40		
	RC32	46	-	228	225/40		Orig.-Verschr.
	RC34	45	-	228	225/40		Orig.-Verschr.
	RC27	44	-	228	215/40, 215/45		Orig.-Verschr., nur M+S
				228, 245	225/40, 235/40		Orig.-Verschr., Sportback bei 235/40 ✖
	RC29	44	-	228	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr.
		50	-	228	215/40M+S, 215/45M+S, 225/40, 235/40		Orig.-Verschr.
	B37	44	-	228	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr.
		50	-	228	215/40M+S, 215/45M+S		Orig.-Verschr., Sportback nicht 245/35
				228, 245	225/40, 235/40, 245/35		
	RC29	45	ZP560D	228	215/40M+S, 215/45M+S, 225/40		
	RC34	48	ZP560D	228	225/40, 235/40		
	B24	48	ZP560D	228	215/40M+S, 215/45M+S, 225/40, 235/40, 245/35		Limousine
					215/40M+S, 215/45M+S, 225/40, 235/40		Sportback
	B36 / B37	45	ZP560D	228	215/40M+S, 215/45M+S, 225/40		
	B42	45	ZP560D	228	215/40M+S, 215/45M+S, 225/40, 235/40		Limousine
				228	215/40M+S, 215/45M+S, 225/40		Sportback
	B44	45	ZP560D	228	215/40M+S, 215/45M+S, 225/40, 235/40		
				228, 245	225/40, 235/40		
	AC-M10	40	- +R	228	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr. + Red.Ringe 66,6-57,1, Limousine
					215/40M+S, 215/45M+S		Orig.-Verschr. + Red.Ringe 66,6-57,1, Sportback
		45	ZP560D	228	215/40M+S, 215/45M+S, 225/40, 235/40		Limousine
					215/40M+S, 215/45M+S, 225/40		Sportback
	AC-521	45	- +R	228	215/40M+S, 215/45M+S, 225/40, 235/40		Orig.-Verschr. + Red.Ringe 66,6-57,1, Limousine
					215/40M+S, 215/45M+S, 225/40		Orig.-Verschr. + Red.Ringe 66,6-57,1, Sportback
	AF20	48	-	228	215/40M+S, 215/45M+S, 225/40, 235/40		Orig.-Verschr.
	CA 20	45	ZP560D	228	215/40M+S, 215/45M+S		
				228, 245	225/40, 235/40		
8,5 x 18	B32	48	ZP560D	228	215/40M+S, 225/40		
7,5 x 19	CA 26	40	ZP560D	228, 245	225/35M+S		
8 x 19	RC34	49	-	228	235/35		Orig.-Verschr.
	B40	49	-	228, 245	225/35, 235/35		Orig.-Verschr.
				228, 245	235/35		
	B43	49	-	228, 245	225/35, 235/35		Orig.-Verschr.
	RC29	49	-	228	225/35, 235/35		Orig.-Verschr.
	RC27	50	-	228, 245	225/35, 235/35		Orig.-Verschr.
	RC34	45	-	228	225/35		Orig.-Verschr.
		50	-	228	225/35, 235/35		Orig.-Verschr.
	B38	50	-	228	225/35, 235/35		Orig.-Verschr.
	B40	50	-	228, 245	225/35, 235/35		Orig.-Verschr.
	B43	47	-	228	225/35, 235/35		Orig.-Verschr.
		50	-	228, 245	225/35, 235/35		Orig.-Verschr.
	AC-521	45	-	228	225/35, 235/35		Orig.-Verschr., Limousine
				228	225/35		Orig.-Verschr., Sportback
8,5 x 19	CA 19	47	ZP560D	228	225/35, 235/35		nicht Bremse 357x34mm
	Oxigin 29	43	ZP560D	228	225/35		
	B36	45	ZP560D	228	225/35		
	B36 / B37	45	ZP560D	228	225/35, 235/35		Sportback bei 235/35 ✖
	B42	47	ZP560D	228	225/35		
	AC-M10	45	AV4+R	228	225/35, 235/35		Sportback bei 235/35 ✖
	CA 23	45	ZP560D	228	225/35, 235/35		Sportback bei 235/35 ✖
8 x 20	Oxigin 28	45	ZP560D	228	225/35, 235/35		Sportback bei 235/35 ✖
	RC36	47+50	-	228, 245	235/30		Orig.-Verschr.
	B43	45	-	228	235/30		Orig.-Verschr., Limousine
		47+50	-	228, 245	235/30		Orig.-Verschr.
8,5 x 20	B38 / B43	48	ZP560D	228	235/30		
	RC29	45	ZP560D	228	235/30		Limousine
	B42	45	ZP560D	228	235/30		Limousine
	AC-521	45	-	228	235/30		Orig.-Verschr., incl. FL2016, nur Limousine
	FMI12 Kari	50	F94	228	235/30		

Audi A4		11/2015		B8, B81 / B9		5/112		66,6		e1*2001/116*0430*35-..., e13*2007/46*1084*19-... (FIN:WAUZZZF4...)	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
ACHTUNG! Bei Audi A4 auf die FIN. Nummer achten, damit man das alte bzw. neue Modell unterscheiden kann!											
7 x 16	RC30	35	-	110	195/65				Orig. Verschr., incl. Facelift 2019		
	RC28	35	ZP568F	90-150	205/60, 215/55, 225/55, 235/50						
7 x 17	RC27	42	-	90-210	225/50				Orig. Verschr., nur M+S, nicht Bremse 350mm		
				90-150	205/55, 215/50, 225/50				Orig. Verschr., nicht Bremse 350 mm, inkl. FL2019		
				90-210	225/50				Orig. Verschr., nur M+S, nicht Bremse 350mm		
	RC30	42	-	90-210	225/50				Orig. Verschr., incl. Facelift 2019, nur M+S, nicht Bremse 350mm		
				90-140	205/55, 215/50, 225/50				Orig. Verschr.		
				90-200	225/50				Orig. Verschr., nur M+S		
	RC32	42	-	100-110	225/50				Orig. Verschr.		
	RC27	35	ZP568F	90-150	205/55, 215/50, 225/50				incl. Facelift 2019		
				90-210	225/50M+S						
	RC30	35	ZP568F	90-150	205/55, 215/50, 225/50				incl. Facelift 2019		
				90-210	225/50M+S						
	RC32	38	-	90-210	205/50, 205/55, 215/50, 225/45, 225/50				Orig. Verschr.		
		43	-	90-200	205/50, 205/55, 215/50, 225/45, 225/50				Orig. Verschr.		
	B39	35	ZP568F	90-140	205/55, 215/50, 225/50						
				90-210	225/50 M+S						
CA 26	42	ZP568F	90-150	205/55, 215/50, 225/50				incl. Facelift 2019, nicht Bremse 318, 338 u. 350mm			
			90-210	225/50 M+S							
7,5 x 17	RC27	38	-	90-210	225/50, 235/45, 245/45				Orig. Verschr., incl. Facelift 2019		
				90-150	205/55, 215/50						
	RC32	38	-	90-210	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr.		
	RC27	36	-	90-210	205/55, 215/50, 225/50, 235/45, 245/45				Orig.-Verschr.		
	RC29	35	ZP568F	90-150	205/55, 215/50				incl. Facelift 2019		
				90-210	225/50, 235/45, 245/45						
	RC32	36	-	90-210	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr.		
	RC34	29	ZP568F	90-210	205/50, 205/55, 215/50, 225/45, 235/45						
		36+40+41	ZP568F	90-210	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45						
	B36	35	ZP568F	90-140	205/55, 215/50						
				90-210	225/50, 235/45, 245/45						
AC-518	30	F95	90-140	205/55, 215/50							
			90-210	235/45							
Oxigin 25	35	ZP568F	90-210	225/50, 235/45, 245/45							
7,5 x 18	RC32	39	-	90-210	205/45, 215/45, 225/40, 225/45				Orig.-Verschr.		
	RC34	39	-	90-210	205/45, 215/45, 225/40, 225/45				Orig.-Verschr.		
	RC30	35	ZP568F	100-140	215/45						
				100-200	225/45						
	B32	29	-	90-140	215/45				Orig.-Verschr.		
				90-210	225/45						
				35	ZP568F	90-150	215/45				incl. Facelift 2019
	90-210	225/45									
	B39	35	ZP568F	90-150	215/45				incl. Facelift 2019		
				90-210	225/45						
	Oxigin 18	35	ZP568F	90-200	225/40, 225/45, 235/45				nicht Bremse 350mm		
8 x 18	RC32	40	-	90-210	205/45, 215/45, 225/40, 225/45, 235/40, 245/40				Orig.-Verschr., ab Modelljahr 2016		
	RC34	40	ZP568F	90-210	205/45, 215/45, 225/40, 225/45, 235/40, 245/40				Ausführung D3		
		40	-	90-210	205/45, 215/45, 225/40, 225/45, 235/40, 245/40				Orig.-Verschr., Ausführung D7		
	B37	40	-	100-200	245/40				Orig.-Verschr.		
				90-140	215/45						
				90-210	225/45, 235/40, 245/40						
	RC27	39	-	90-200	225/40, 225/45, 235/45, 245/40				Orig.-Verschr.		
		41	-	90-200	225/40, 225/45, 235/45				Orig.-Verschr.		
	RC29	39	-	90-150	215/45				Orig.-Verschr., incl. Facelift 2019		
				90-210	225/45, 235/40, 245/40						
	RC32	31	-	90-210	205/45, 215/45, 225/40, 225/45, 235/40				Orig.-Verschr.		
		39	-	90-210	205/45, 215/45, 225/40, 225/45, 235/40, 245/40				Orig.-Verschr.		
	B36	35	ZP568F	90-150	215/45				incl. Facelift 2019		
				90-210	225/45, 235/40, 245/40						
	B38	35	ZP568F	90-200	215/45, 225/45, 235/40, 245/40						
	B42 / B44	30	ZP568F	90-150	215/45				incl. Facelift 2019		
				90-210	225/45						
				35	ZP568F	90-150	215/45				incl. Facelift 2019

		33	ET 3001	90-210	225/45, 235/40, 245/40		nicht Facelift 2019
	AC-M10	40	-	90-150	215/45		Orig.-Verschr., incl. Facelift 2019
				90-210	225/45, 235/40, 245/40		
	AF18	35+40	-	90-140	215/45		Orig.-Verschr., ET40 ist original-ET
				90-210	225/45, 235/40, 245/40		
	AF20	35	-	90-150	215/45		Orig.-Verschr., incl. Facelift 2019
				90-210	225/45, 235/40, 245/40		
	AC-518	40	AV4	90-140	215/45		
				90-210	225/45, 235/40, 245/40		
	CA 20	45	-	90-150	215/45		Orig.-Verschr., incl. Facelift 2019, nicht Bremse 350mm
				90-210	225/45, 235/40, 245/40		
	CA 23	39	-	90-150	215/45		Orig.-Verschr., incl. Facelift 2019
				90-210	225/45, 235/40, 245/40		
	FMI08 Thoe	26	F31	90-210	205/45, 215/45, 225/40		
		34	F31	90-210	205/45, 215/45, 225/40, 235/40, 245/40		
	FMI11 Elatha	26	-	90-210	205/45, 215/45, 225/40		Orig.-Verschr.
	FMI12 Kari	34	Kit 0354	90-210	205/45, 215/45, 225/40, 225/45, 235/40, 245/40		
7,5 x 19	B32	33	-	90-200	225/40		Orig.-Verschr.
	B39	33	ZP568F	90-200	225/40		
	CA 26	32	ZP568F	90-210	225/40		
8 x 19	RC29	35	ZP568F	90-210	225/40, 235/35, 245/35		incl. Facelift 2019
	RC34	38	ZP568F	90-210	225/35, 225/40, 235/35, 245/35		
	B24	35	ZP568F	90-210	225/40, 235/35, 245/35		
	B38	35	ZP568F	90-200	225/40, 235/35, 245/35		
	B40	39	-	90-210	225/40, 235/35, 245/35		incl. Facelift 2019, nicht Bremse 390mm u. nicht Keramik
	B43	34	ZP568F	90-210	225/40, 235/35		incl. Facelift 2019
		38	ZP568F	90-210	225/40, 235/35, 245/35		incl. Facelift 2019
	AC-518	38	AV4	90-210	225/40, 235/35, 245/35		
	AC-521	35	-	90-210	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2019
	CA 17	37	ZP568F	90-200	225/40, 235/35		
	FMI07 Atena	39	F95	90-210	225/35, 225/40, 235/35, 245/35		
	Oxigin 29	32	ZP568F	90-210	225/40, 235/35		incl. Facelift 2019
		39	ZP568F	90-210	225/40, 235/35, 245/35		incl. Facelift 2019
8,5 x 19	RC32	40	-	90-210	245/35, 255/35		Orig.-Verschr.
	RC34	40	-	90-210	245/35, 255/35		Orig.-Verschr.
				90-210	225/35, 225/40, 235/35, 245/35, 255/30		
	B37	40	-	90-210	225/40, 235/35, 245/35		Orig.-Verschr.
	B43	40	ZP568F	90-210	225/40, 235/35, 245/35		incl. Facelift 2019
	CA 20	40	-	90-210	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2019
	CA 23	40	-	90-210	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2019
	CA 26	40	ZP568F	90-210	225/40, 235/35, 245/35		incl. Facelift 2019, nicht Bremse 350mm
	Oxigin 18	40	ZP568F	90-210	245/35		incl. Facelift 2019, nicht Bremse 318, 338 u. 350mm
	FMI07 Atena	40	-	90-200	245/35		Orig.-Verschr.
	B36	35	ZP568F	90-210	225/40, 235/35		nicht Bremse 318 u. 350mm
	B41	36	ZP568F	90-210	225/35, 235/35, 245/35		
		39	ZP568F	90-210	225/35, 225/40, 235/35, 245/35, 255/30		
	B42	35	ZP568F	90-210	225/40, 235/35		incl. Facelift 2019
		42	ZP568F	90-210	225/40, 235/35, 245/35, 255/35		incl. Facelift 2019, nicht Bremse 318 u. 350mm
	B44	35	ZP568F	90-210	225/40, 235/35		incl. Facelift 2019
		42	ZP568F	90-210	225/40, 235/35, 245/35, 255/35		incl. Facelift 2019
	AC-M10	40	-	90-210	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2019
	AF18	40	-	90-200	225/40, 235/35, 245/35		Orig.-Verschr.
	Oxigin 20	40	ZP568F	90-200	225/40, 235/35, 245/35		nicht Bremse 318mm
	Oxigin 25	35	ZP568F	90-200	225/40		nicht Bremse 350mm
	Oxigin 26	40	ZP568F	90-200	225/40, 235/35		
				90-260	245/35		
	Oxigin 28	40	ZP568F	90-210	225/40, 235/35, 245/35		nicht Bremse 350mm
	8300 - 1972	32	F85	90-210	225/35, 235/35		
8 x 20	B38	35	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019
	B43	30	ZP568F	90-210	225/35		incl. Facelift 2019
		39	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019
	RC29	40	ZP568F	90-210	225/35, 245/30		
	RC34	33	ZP568F	90-210	235/30		
		37	ZP568F	90-210	225/35, 235/30, 245/30		
		38	ZP568F	90-210	235/30, 245/30		
	RC36	40	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019
	B24	42	ZP568F	90-210	225/35, 245/30		
	B41	35	ZP568F	90-210	235/30		
	B42	35	ZP568F	90-210	225/35		incl. Facelift 2019
		40	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019, nicht Bremse 350mm

8,5 x 20	B43	40	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019
	B44	35	ZP568F	90-210	225/35		incl. Facelift 2019
		40	ZP568F	90-210	225/35, 245/30		incl. Facelift 2019, nicht Bremse 350mm
	AC-518	32	-	90-210	225/35		Orig.-Verschr.
	AC-521	32	-	90-210	225/35		Orig.-Verschr., incl. Facelift 2019
	AC-M10	40	-	90-210	225/35, 245/30		Orig.-Verschr., incl. Facelift 2019
	AF18	32	-	90-210	225/35		Orig.-Verschr.
	CA 17	40	ZP568F	90-200	225/35		nicht Bremse 350x34mm
	FMI07 Atena	39	-	90-210	225/35, 235/30, 245/30		Orig.-Verschr.
	Oxigin 14	35	ZP568	90-200	225/35		
9 x 20	B41	35	ZP568F	90-210	235/30		
		38	ZP568F	90-210	225/35, 235/30		
	B43	35	ZP568F	90-210	225/35		
	AC-522	40	-	90-200	225/35		Orig.-Verschr.
	AF18	40	-	90-200	225/35, 245/30		Orig.-Verschr.
	Oxigin 28	35	ZP568F	90-210	225/35		incl. Facelift 2019

Audi S4	ab BJ2015	8W / B9	5/112	66,6	e1*2001/116*0430*..., e13*2007/46*1084*... (FIN:WAUZZZF4...)
---------	-----------	---------	-------	------	--

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC32	39	-	251-260	225/40, 225/45		Orig.-Verschr.
	RC30	35	ZP568F	251-260	225/45M+S		incl. Facelift 2019
		29	-	260	225/45M+S		Orig.-Verschr.
	RC34	39	-	251-260	225/40, 225/45		Orig.-Verschr.
	B32	35	ZP568F	255, 260	225/45		incl. Facelift 2019, nur M+S, nicht Bremse 375mm
	B39	35	ZP568F	255, 260	225/45		nur M+S
	Oxigin 18	35	ZP568F	260	225/40, 225/45, 235/45		
8 x 18	RC32	40	-	251-260	245/40		Orig.-Verschr.
			-	260	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., bis 235/40 nur M+S
	RC34	40	ZP568F	251-260	225/40, 225/45, 235/40, 245/40		bis 235/40 nur M+S, Ausführung D3
			-	251-260	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Ausführung D7
	RC27	41	-	260	225/40, 225/45, 235/45		Orig.-Verschr., nur M+S
	RC29	35	ZP568F	251-260	225/45M+S, 235/40M+S, 245/40		incl. Facelift 2019
			-	251-260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr., incl. FL2019, nicht Bremse 375mm
	RC32	39	-	260	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., bis 235/40 nur M+S
	RC34	30	ZP568F	251-260	225/40, 225/45, 235/40		nur M+S
	B36	35	ZP568F	251-260	225/45M+S, 235/40M+S, 245/40		incl. Facelift 2019, nicht Bremse 375mm
	B42 / B44	35	ZP568F	251-260	225/45M+S, 235/40M+S, 245/40		incl. Facelift 2019
	AC-M10	40	-	251-260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr., incl. Facelift 2019
			F95	251-260	225/45M+S, 235/40M+S, 245/40		incl. Facelift 2019
	AC-518	40	AV4	260	225/45M+S, 235/40M+S, 245/40		
			-	255, 260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr.
	AF18	40	-	255, 260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr., nicht Bremse 375mm
			-	255, 260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr., incl. Facelift 2019
	AF20	40	-	255, 260	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr., incl. FL2019, nicht Bremse 375mm
			-	255, 260	225/45M+S, 235/40M+S, 245/40		bis 235/40 nur M+S
	FMI08 Thoe	34	F31	251-260	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
FMI11 Elatha	26	-	251-260	225/40M+S			
7,5 x 19	B32	33	-	260	225/40		Orig.-Verschr., nur M+S
	B39	33	ZP568F	260	225/40		nur M+S
			-	260	225/40		
8 x 19	RC29	35	ZP568F	251-260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
	RC34	38	ZP568F	260	225/40M+S, 235/35M+S, 245/35		
	B24	35	ZP568F	255, 260	225/40M+S, 235/35M+S, 245/35		
			-	251-260	225/40M+S, 235/35M+S, 245/35		Orig.-Verschr., incl. Facelift 2019
	B40	38	ZP568F	255, 260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
			-	251-260	225/40M+S, 235/35M+S		incl. Facelift 2019
	B43	38	ZP568F	251-260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
			-	255, 260	225/40M+S, 235/35M+S, 245/35		
	AC-518	38	AV4	255, 260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
	AC-521	35	AV1	251-260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
	CA 17	43	ZP568F	260	225/40M+S, 235/35M+S		
FMI07 Atena	39	F95	260	225/40M+S, 235/35M+S, 245/35			
Oxigin 29	32	ZP568F	251-260	225/40M+S, 235/35M+S		incl. Facelift 2019	
		ZP568F	251-260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019	
7,5 x 19	RC32	40	-	251-260	245/35, 255/35		Orig.-Verschr.
			-	251-260	245/35, 255/35		
	RC34	40	-	251-260	225/40, 235/35, 245/35, 255/30		Orig.-Verschr.
			-	260	225/40M+S, 235/35M+S, 245/35, 255/35		Orig.-Verschr.
	CA 20	40	-	255	255/35		Orig.-Verschr., incl. Facelift 2019
			-	260	245/35		
			251-260	225/40M+S, 235/35M+S, 245/35			
	CA 23	40	-	251, 255	255/35		Orig.-Verschr., incl. Facelift 2019
				260	245/35		
			251-260	225/40M+S, 235/35M+S, 245/35, 255/30			

8,5 x 19	B32	34,5	ZP568F	260	225/40M+S, 235/35M+S		
	B41	36	ZP568F	251-260	235/35M+S, 245/35		
		39	ZP568F	251-260	225/40M+S, 235/35M+S, 245/35, 255/30		
	B42	35	ZP568F	251-260	225/40M+S, 235/35M+S		incl. Facelift 2019
	B43	40	ZP568F	251-260	225/40M+S, 235/35M+S, 245/35		incl. Facelift 2019
	B44	35	ZP568F	251-260	225/40M+S, 235/35M+S		incl. Facelift 2019
		42	ZP568F	251-260	225/40M+S, 235/35M+S, 245/35, 255/30		incl. Facelift 2019
	AC-M10	40	-	251-260	225/40M+S, 235/35M+S, 245/35		Orig.-Verschr.
	AF18	40	-	260	225/40M+S, 235/35M+S, 245/35		Orig.-Verschr.
8 x 20	FMI07 Atena	39	F95	260	225/40M+S, 235/35M+S, 245/35		
	Oxigin 19	40	ZP568F	260	225/40M+S, 235/35M+S		
	B38	35	ZP568F	255, 260	225/35M+S, 245/30		
8,5 x 20	B43	30	ZP568F	251-260	225/35M+S		incl. Facelift 2019
		39	ZP568F	251-260	225/35M+S, 245/30		incl. Facelift 2019
	RC29	40	ZP568F	260	225/35M+S, 245/30		
	RC34	37+38	ZP568F	260	225/35M+S, 245/30		
	RC36	40	ZP568F	251-260	225/35M+S, 245/30		incl. Facelift 2019
	B42	35	ZP568F	251-260	225/35M+S		incl. Facelift 2019
	B43	40	ZP568F	251-260	225/35M+S, 245/30		incl. Facelift 2019
	B44	35	ZP568F	251-260	225/35M+S		incl. Facelift 2019
	CA 17	40	ZP568F	260	225/35		nur M+S, nicht Bremse 350x34mm
	AC-521	32	-	251-260	225/35M+S		Orig.-Verschr.
	AC-M10	40	-	251-260	225/35M+S, 245/30		Orig.-Verschr., incl. Facelift 2019
	FMI07 Atena	39	-	260	225/35M+S, 245/30		Orig.-Verschr.
	Oxigin 14	35	ZP568	260	225/35M+S		
	9 x 20	B41	38	ZP568F	260	225/35M+S	
AC-522		40	-	260	225/35M+S		Orig.-Verschr.
AF18		40	-	260	225/35M+S, 245/30		Orig.-Verschr.
Audi A4 Allroad ab MJ2016 B8 / B9 5/112 66,6 e1*2001/116*0430*40-..., e13*2007/46*1084*25-..., (FIN: WAUZZZF4...)							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	29	-	100-210	225/55, 235/50		Orig.-Verschr.
	RC29	29	-	100-210	225/55, 235/50		Orig.-Verschr.
	RC32	29	-	100-210	225/50, 225/55, 235/50		Orig.-Verschr.
	RC34	29	ZP568F	100-210	225/50, 225/55, 235/50		
	RC24	28	-	100-200	225/55, 235/50		Orig.-Verschr.
	RC27	28	-	100-210	225/55, 235/50		Orig.-Verschr.
		36	-	90-200	225/50, 235/45, 245/45		Orig.-Verschr.
	AC-518	30	F95	100-200	225/55, 235/50, 245/50		
7,5 x 18	Oxigin 14	35	ZP568	100-200	225/55, 235/50		bei 235/50 ✖
	RC30	29	-	100-200	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 18	B32	29	-	100-200	245/45		Orig.-Verschr.
	RC27	26+28	-	100-200	225/50, 235/45, 245/45, 255/45		Orig.-Verschr., nur 235/45 ist auflagenfrei! ✖
	RC32	29	-	100-200	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
		31	-	100-200	225/45, 225/50, 235/45, 245/45, 255/45		Orig.-Verschr.
	RC34	30	ZP568F	100-210	225/45, 225/50, 235/45, 245/45		
	B36	30	ZP568F	100-200	225/45, 225/50, 235/45, 245/45, 255/45		
	B42 / B44	30	ZP568F	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
	AC-M10	30	AV4	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
	AC-MB6	29	ZP567F	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
	AC-518	30	F95	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
	AF18 / AF20	28	-	100-200	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	FMI08 Thoe	26	F31	100-210	225/45, 235/45		
		34	F31	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
	FMI11 Elatha	26	-	100-210	225/45, 235/45		Orig.-Verschr.
	FMI12 Kari	26	Kit 0354	100-210	225/45, 235/45		
		34	Kit 0354	100-210	225/45, 225/50, 235/45, 245/45, 255/45		
8,5 x 18	B32	30	ZP568F	100-210	225/45, 235/45, 245/45		
7,5 x 19	CA 26	32	ZP568F	100-210	225/40, 225/45		
8 x 19	Oxigin 29	32	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	RC27	26	-	100-200	235/40, 245/40		Orig.-Verschr., nur 235/40 ist auflagenfrei! ✖
	RC32	27	-	100-210	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
		32	-	100-200	245/40		Orig.-Verschr., i.V.
	RC34	27	ZP568F	100-210	225/40, 225/45, 235/40, 245/40		
	B40	31	ZP568F	100-200	225/40, 225/45, 235/40, 245/35, 245/40		
	B43	27+28	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	CA 19	30	ZP568F	100-210	235/40, 245/40		
	CA 24	30	ZP568F	100-210	235/40, 245/40		
	FMI08 Thoe	26	F31	100-210	225/40, 225/45, 235/40		
FMI14 Jupiter	26	Kit0386	100-210	225/40, 225/45, 235/40			
	B32	25	ZP568F	100-200	225/40, 225/45, 235/40, 245/35, 245/40, 255/35,		ab 245/35 ✖

8,5 x 19	B32	28	ZP568F	100-210	255/40		ab 245/35
	B36	30	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	B37	25+32	ZP568F	100-200	225/40, 225/45, 235/40, 245/35, 245/40, 255/35		ET25 ab 245/35
	B41	28	ZP568F	100-210	225/40, 225/45, 235/40		
	B42	30	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	B43	25	ZP568F	100-210	225/40, 225/45, 235/40		
	B44	25	ZP568F	100-210	225/40, 225/45, 235/40		
		30	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	AC-M10	30	AV4	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	AF18 / AF20	30	-	100-200	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	CA 23	30	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
	FMI07 Atena	28	-	100-210	225/40, 225/45, 235/40		Orig.-Verschr.
	8300 - 1972	32	F85	100-210	225/40, 225/45, 235/40, 245/40		
	Oxigin 28	30	ZP568F	100-210	225/40, 225/45, 235/40, 245/35, 245/40		
8 x 20	B43	27+30	ZP568F	100-210	235/35, 245/35		
8,5 x 20	RC29	29	ZP568F	100-200	235/35, 245/35		
	RC34	30	ZP568F	100-210	235/35, 245/35		
		33	ZP568F	100-210	235/35, 245/35, 255/30		
	B32	30	ZP568F	100-210	235/35, 245/35		
	B42 / B43	30	ZP568F	100-210	235/35, 245/35		
	B44	30	ZP568F	100-210	235/35, 245/35		
	AC-518	32	-	100-210	235/35, 245/35, 255/30, 255/35		Orig.-Verschr.
	AC-521	32	-	100-210	235/35, 245/35, 255/30, 255/35		Orig.-Verschr.
	AC-M10	30	ZP567F	100-210	235/35, 245/35		
	FMI12 Kari	34	F94	100-210	235/35, 245/35, 255/30		
9 x 20	B37	29	ZP568F	100-210	235/35		
	B41	33	ZP568F	100-210	235/35, 245/35		
	CA 23	30	ZP568F	100-210	235/35, 245/35		
	FMI07 Atena	33	-	100-210	235/35, 245/35		Orig.-Verschr.
	FMI11 Elatha	34	-	100-210	235/35, 245/35		Orig.-Verschr.
9,5 x 20	B37C	32	ZP568F	100-200	235/35		
8,5 x 21	B41 / B43	30	ZP568F	100-210	245/30		
9 x 21	B32	30	ZP568F	100-210	245/30		

Audi A5 (siehe Konfigurator)	ab 06.07	B8 / B81	5/112	66,6	e1*2001/116*0430*..., e13*2007/46*1084*... (FIN: WAUZZZ8T...od. ...ZZZ8F...)
------------------------------	----------	----------	-------	------	---

Audi A5	ab MJ2016	B8 (B9)	5/112	66,6	e1*2001/116*0430*43-..., e13*2007/46*1084*27-... FIN: WAUZZZF56...
indirekt - teilweise direkt Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 17	RC27	29	-	100-210	225/50, 235/45, 235/50, 245/45	Orig.-Verschr., incl. Facelift 2019
	RC29	29	-	110-200	225/50	Orig.-Verschr.
				100-210	225/50, 235/45, 235/50, 245/45	Orig.-Verschr., incl. Facelift 2019
	RC32	29	-	90-210	225/45, 225/50, 235/45, 235/50, 245/45	Orig.-Verschr.
	RC34	29	ZP568F	90-210	225/45, 225/50, 235/45, 235/50, 245/45	
	RC24	28	-	100-210	225/50, 235/45, 235/50, 245/45	Orig.-Verschr.
7,5 x 18	AC-518	30	F95	100-210	225/50, 235/45, 235/50, 245/45	
	RC30	29	-	110-200	225/45	Orig.-Verschr.
	B32	29	-	100-210	225/45	Orig.-Verschr.
8 x 18	RC27	31	-	110-260	235/40, 235/45, 245/40	Orig.-Verschr., nur M+S
	RC32	31	-	100-210	225/40, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr.
	RC27	26+28	-	110-200	225/45, 235/40, 235/45	Orig.-Verschr.
				110-260	245/40	
	RC32	26+29	-	100-210	225/40, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr.
	RC34	30	ZP568F	90-210	225/40, 225/45, 235/40, 235/45, 245/40	
	B36	30	ZP568F	110-200	225/45, 235/40, 245/40	
	B42 / B44	30	ZP568F	100-210	225/45, 235/40, 245/40	incl. Facelift 2019
	AC-M10	30	AV4	100-210	225/45, 235/40, 245/40	incl. Facelift 2019
	AC-518	30	F95	100-210	225/45, 235/40, 245/40	incl. Facelift 2019
	AF18 / AF20	28	-	100-210	225/45, 235/40, 245/40	Orig.-Verschr.
	FMI08 Thoe	26+34	F31	90-210	225/40, 225/45, 235/40, 235/45, 245/40	
	FMI11 Elatha	26	-	90-210	225/40, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr.
7,5 x 19	FMI12 Kari	26-34	Kit 0354	90-210	225/40, 225/45, 235/40, 235/45, 245/40	
	B32	33	-	110-210	225/40	Orig.-Verschr.
	B39	33	ZP568F	110-210	225/40	
	CA 26	32	ZP568F	100-210	225/40	incl. Facelift 2019
8 x 19	RC27	26	-	110-200	225/40	Orig.-Verschr.
				110-260	245/35	
	RC32	27	-	90-210	225/35, 225/40, 235/35, 245/35	Orig.-Verschr.
	RC34	27	ZP568F	90-210	225/35, 225/40, 235/35, 245/35	
	B40	31	ZP568F	100-210	225/40, 235/35, 245/35	incl. Facelift 2019
	B43	27+28	ZP568F	100-210	225/40, 235/35, 245/35	incl. Facelift 2019

	CA 24	30	ZP568F	100-200	225/40		
				100-260	245/35		
	FMI08 Thoe	26	F85	100-210	225/40, 235/35, 245/35		
	Oxigin 29	32	ZP568F	100-210	225/40, 235/35, 245/35		
8,5 x 19	RC32	32	-	100-210	255/35		Orig.-Verschr.
	B37	32	ZP568F	100-210	225/40, 235/35, 245/35, 255/35		
	B36 / B42	30	ZP568F	110-210	225/40, 235/35, 245/35, 255/35		
	B41	28	ZP568F	90-210	225/35, 225/40, 235/35, 245/35		
	B43	25	ZP568F	100-210	225/40, 235/35		incl. Facelift 2019
	B44	25	ZP568F	100-210	225/40, 235/35		incl. Facelift 2019
		30	ZP568F	100-210	225/40, 235/35, 245/35, 255/35		incl. Facelift 2019
	AC-M10	30	AV4	100-210	225/40, 235/35, 245/35, 255/35		incl. Facelift 2019
	AF18 / AF20	30	-	100-210	225/40, 235/35, 245/35, 255/35		Orig.-Verschr.
	CA 23	30	ZP568F	100-210	225/40, 235/35, 245/35, 255/35		
	FMI07 Atena	28	-	90-210	225/35, 225/40, 235/35, 245/35		Orig.-Verschr.
	FMI11 Elatha	21	-	90-210	225/35, 225/40		Orig.-Verschr.
	8300 - 1972	32	F85	90-210	225/35, 225/40, 235/35, 245/35, 255/30, 255/35		
	Oxigin 20	35	ZP568F	100-260	245/35, 255/35		
	Oxigin 25	35	ZP568F	100-260	245/35, 255/35		nicht Bremse 350mm
	Oxigin 26	30	ZP568F	100-200	225/40		
				100-260	245/35, 255/35		
	Oxigin 28	30	ZP568F	100-210	225/40, 235/35, 245/35, 255/35		incl. Facelift 2019
9 x 19	CA 24	35	ZP568F	100-200	225/40		
				100-260	245/35, 255/35, 265/30, 265/35		
8 x 20	B43	27+30	ZP568F	100-210	225/35, 245/30		incl. Facelift 2019
8,5 x 20	RC29	29+33	ZP568F	100-210	225/35, 235/30, 245/30, 255/30		
	RC34	30	ZP568F	90-210	225/35, 235/30, 245/30, 255/30		
		33	ZP568F	90-210	225/35, 235/30, 245/30, 255/30		
	B24	33	ZP568F	100-210	225/35, 235/30, 245/30, 255/30		
	B32	30	ZP568F	100-210	235/30, 245/30, 255/30		
	B41	35	ZP568F	90-210	225/35, 235/30, 245/30, 255/30		
	B42 / B43	30	ZP568F	100-210	225/35, 235/30, 245/30, 255/30		incl. Facelift 2019
	B44	25	ZP568F	100-210	225/35, 235/30		incl. Facelift 2019
		30	ZP568F	100-210	225/35, 235/30, 245/30, 255/30		incl. Facelift 2019
	AC-518	32	-	100-210	225/35, 235/30, 245/30, 255/30		Orig.-Verschr., incl. Facelift 2019
	AC-521	32	-	100-210	225/35, 235/30, 245/30, 255/30		Orig.-Verschr., incl. Facelift 2019
	AC-M10	30	ZP567F	100-210	225/35, 235/30, 245/30, 255/30		incl. Facelift 2019
	AF18	32	-	100-210	225/35, 235/30, 245/30, 255/30		Orig.-Verschr.
	CA 17	35	ZP568F	100-260	255/30		
	CA 19	32	ZP568F	100-260	255/30		
	FMI12 Kari	34	F94	90-210	225/35, 235/30, 245/30, 255/30		
9 x 20	Oxigin 14	35	ZP568	110-260	255/30		
	B40	34	ZP568F	100-260	255/30, 265/30		ECE 100-210KW
	B41	33	ZP568F	100-210	225/35, 245/30, 255/30		
		35	ZP568F	90-210	225/35, 235/30, 245/30, 255/30		
	B43	33	ZP568F	100-210	225/35, 245/30, 255/30		incl. Facelift 2019
		35	ZP568F	100-210	225/35, 235/30, 245/30, 255/30		incl. Facelift 2019
	CA 20	35	ZP568F	100-210	225/35, 245/30, 255/30, 265/30		incl. Facelift 2019
	CA 23	30	ZP568F	100-210	225/35, 245/30		incl. Facelift 2019
	Oxigin 18	35	ZP568F	110-260	255/30, 265/30		nicht Bremse 350mm
	Oxigin 19 / 25	35	ZP568F	100-260	255/30, 265/30		
	Oxigin 28	35	ZP568F	100-210	225/35, 245/30, 255/30, 265/30		incl. Facelift 2019
	AC-522	33	-	100-260	255/30, 265/30		Orig.-Verschr.
	AC-M08	33	AV1	110-260	255/30, 265/30		
	AF18	33	AV1	110-210	225/35, 245/30, 255/30		
	FMI07 Atena	33	-	90-210	235/30, 245/30, 255/30		Orig.-Verschr.
	FMI11 Elatha	34	-	90-210	235/30, 245/30, 255/30		Orig.-Verschr.

Audi A5 NEU		2024	F2	5/112	66,6	e1*2007/46*1801*47..	
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC32	38	-	110-150	205/55, 205/60 , 215/55, 225/50, 225/55, 235/50		Orig.-Verschr., Ausführ. D7
		42	-	110-150	205/55, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., Ausführ. D7
7,5 x 17	RC34	41	-	110-150	205/55, 215/55 , 225/50, 225/55 , 235/50		Orig.-Verschr., Ausführ. D7
	RC27	36	-	110, 150	205/60, 215/55, 225/50, 225/55, 235/50		Orig.-Verschr., Ausführ. D7
	RC34	40	ZP568F	110-150	205/55, 205/60, 215/55, 225/50, 225/55, 235/50		
7,5 x 18	RC32	39	-	110-150	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC34	39	-	110-150	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 18	RC32	40	-	110-150	215/50, 225/45, 225/50, 235/45 , 245/45		Orig.-Verschr., Ausführ. D7
	RC34	40	ZP568F	110-150	215/50, 225/45, 225/50, 235/45 , 245/45		Ausführung D3
		40	-	110-150	215/50, 225/45, 225/50, 235/45 , 245/45		Orig.-Verschr., Ausführ. D7
		RC27	39	-	110, 150	225/45, 225/50, 235/45, 245/45	

	RC32	39	-	110-150	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Ausführ. D7
	B37	40	-	110, 150	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 19	Originaldim.	44			245/40		
	RC34	43	ZP568F	110-150	215/40, 215/45, 225/40, 225/45, 235/40, 245/35, 245/40		
	B40	39	-	110, 150	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
		38	ZP568F	110, 150	225/40, 225/45, 235/40, 245/40		
	B43	43			245/40		i.V.
8,5 x 19	RC34	40	-	110-150	215/40, 225/40, 225/45, 235/40		Orig.-Verschr.
	B37	40	-	110, 150	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
8 x 20	RC36	39	ZP568F	110, 150	235/35, 245/35		
8,5 x 20	RC36	46	-	110, 150	235/35, 245/35 , 255/30		Orig.-Verschr.
		40	ZP568F	110, 150	235/35, 245/35		
	B43	43			245/35		i.V.
	B44	40	ZP568F	110, 150	235/35, 245/35		

Audi A5 / A5 Avant TFSle		NEU	2024	F2	5/112	66,6	e1*2007/46*1801*52-..
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	39	-	185	235/45, 245/45		Orig.-Verschr., Ausführung D7
	B37	40	-	185	235/45, 245/45		Orig.-Verschr.
8 x 19	B40	39	-	185	235/40, 245/40		Orig.-Verschr.
		38	ZP568F	185	235/40, 245/40		
8,5 x 19	B37	40	-	185	235/40, 245/40		Orig.-Verschr.
8 x 20	RC36	39	ZP568F	185	245/35		
8,5 x 20	RC36	46	-	185	245/35		Orig.-Verschr.
		40	ZP568F	185	245/35		
	B44	40	ZP568F	185	235/35, 245/35		

Audi S5		ab MJ2016	B8 (B9)	5/112	66,6	e1*2001/116*0430*43-.., e13*2007/46*1084*27-.., WAUZZZF5...)	(FIN:
----------------	--	-----------	---------	-------	------	--	-------

indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	31	-	260	245/40		Orig.-Verschr., nur M+S
	RC32	31	-	255-260	245/40		Orig.-Verschr.
	RC32	26+29	-	255-260	245/40		Orig.-Verschr., nur M+S
	RC34	30	ZP568F	251-260	245/40		nur M+S
	B36	30	ZP568F	260	245/40		nur M+S
	B42 / B44	30	ZP568F	251-260	245/40		incl. Facelift 2019, nur M+S
	AC-M10	30	AV4	251-260	245/40		incl. Facelift 2019, nur M+S
	AC-518	30	F95	251-260	245/40		incl. Facelift 2019, nur M+S
	AF18	28	-	255, 260	245/40		Orig.-Verschr., nur M+S
	AF20	28	-	255, 260	245/40		Orig.-Verschr., incl. Facelift 2019, nur M+S
	FMI08 Thoe	26+34	F31	251-260	245/40		nur M+S
8 x 19	FMI11 Elatha	26	-	251-260	245/40		Orig.-Verschr., nur M+S
	RC27	26	-	260	245/35		Orig.-Verschr.
	RC32	27	-	260	245/35		Orig.-Verschr., nur M+S
	RC34	27	ZP568F	255-260	245/35		nur M+S
	B40	31	ZP568F	245, 260	235/35, 245/35		nur M+S
	B43	27+28	ZP568F	251-260	245/35		nur M+S
	CA 24	30	ZP568F	260	245/35		
	FMI08 Thoe	26	F85	260	245/35		nur M+S
	Oxigin 29	32	ZP568F	251-260	245/35		incl. Facelift 2019, nur M+S
	RC32	32	-	251-260	255/35		Orig.-Verschr.
8,5 x 19	B37	32	ZP568F	255, 260	245/35, 255/35		
	B36	30	ZP568F	255, 260	245/35, 255/35		
	B41	28	ZP568F	260	245/35		
	B42	30	ZP568F	255, 260	245/35, 255/35		
	B44	30	ZP568F	251-260	245/35, 255/35		incl. Facelift 2019
	AC-M10	30	AV4	251-260	245/35, 255/35		incl. Facelift 2019
	AF18 / AF20	30	-	260	245/35, 255/35		Orig.-Verschr.
	CA 23	30	ZP568F	251-260	245/35, 255/35		
	FMI07 Atena	28	-	255-260	245/35		Orig.-Verschr.
	Oxigin 14	35	ZP568	260	245/35, 255/35		
	Oxigin 28	30	ZP568F	251-260	245/35, 255/35		incl. Facelift 2019
8 x 20	B43	27+30	ZP568F	251-260	245/30		incl. Facelift 2019, nur M+S
8,5 x 20	RC29	29+33	ZP568F	255, 260	245/30, 255/30		
	RC34	30+33	ZP568F	251-260	245/30, 255/30		
	B24	33	ZP568F	255, 260	245/30, 255/30		
	B32	30	ZP568F	255, 260	245/30, 255/30		
	B41	35	ZP568F	251-260	245/30, 255/30		
	B42 / B43	30	ZP568F	251-260	245/30, 255/30		incl. Facelift 2019

9 x 20	AC-518	32	-	255, 260	245/30, 255/30		Orig.-Verschr., incl. Facelift 2019
	AC-521	32	-	251-260	245/30, 255/30		Orig.-Verschr., incl. Facelift 2019
	AC-M10	30	ZP567F	251-260	245/30, 255/30		incl. Facelift 2019
	AF18	32	-	260	245/30, 255/30		Orig.-Verschr.
	CA 19	32	ZP568F	260	255/30		
	B40	34	ZP568F	260	255/30, 265/30		
	B37	29	ZP568F	251-260	245/30		
	B41	33	ZP568F	260	255/30		
		35	ZP568F	255-260	245/30, 255/30		
	B43	33	ZP568F	251-260	245/30, 255/30		incl. Facelift 2019
		35	ZP568F	251-260	245/30, 255/30, 265/30		incl. Facelift 2019
	B44	30	ZP568F	251-260	245/30, 255/30		incl. Facelift 2019
	AC-518	33	F95	260	255/30, 265/30		Orig.-Verschr.
	AC-M08	33	AV1	260	255/30, 265/30		
	AF18	33	AV1	260	245/30, 255/30		
	CA 20	35	ZP568F	251-260	245/30, 255/30, 265/30		incl. Facelift 2019
	FMI07 Atena	33	-	255-260	245/30, 255/30		Orig.-Verschr.
	FMI11 Elatha	34	-	251-260	245/30, 255/30		Orig.-Verschr.
	Oxigin 18 / 19	35	ZP568F	260	255/30, 265/30		Oxigin 18 nicht Bremse 350mm
	Oxigin 28	35	ZP568F	251-260	245/30, 255/30, 265/30		incl. Facelift 2019

Audi S5 / S5 Avant NEU		2024	F2	5/112	66,6	e1*2007/46*1801*47-..	
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC27	39	-	270	235/45, 245/45		Orig.-Verschr., nur M+S, Ausführung D7
	B37	40	-	270	235/45, 245/45		Orig.-Verschr., nur M+S
8 x 19	B40	39	-	270	235/40M+S, 245/40		Orig.-Verschr.
		38	ZP568F	270	235/40M+S, 245/40		
8,5 x 19	B37	40	-	270	235/40M+S, 245/40		Orig.-Verschr.
8 x 20	RC36	39	ZP568F	270	245/35		
8,5 x 20	RC36	46	-	270	245/35		Orig.-Verschr.
		40	ZP568F	270	245/35		

Audi A6 / Avant		2014-2018	4G/4G1	5/112	66,6	e1*2007/46*0436*..., e13*2007/46*1147*...	
indirekt - teilweise direkt Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	39	-	100-245	245/45		Orig.-Verschr.
	RC29	39	-	100-245	225/50, 235/50, 245/45, 255/45		Orig.-Verschr., incl. FL2014, nicht Bremse 356mm
	RC32	39	-	100-245	225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	CA 23	39	-	100-245	245/45		Orig.-Verschr., nicht Bremse 356mm
	CA 26	39	ZP568F	100-245	245/45		nicht Bremse 356mm
7,5 x 19	FMI11 Elatha	39	-	100-245	245/45		Orig.-Verschr., nicht Keramikbremse
	B32	33	-	100-245	235/45, 245/40		Orig.-Verschr., nur M+S, incl. FL2014
	B39	33	ZP568F	100-245	235/45, 245/40		incl. Facelift 2014
8,5 x 19	FMI07 Atena	45	-	100-245	255/40		Orig.-Verschr., nicht Bremse 400mm VA u. 355mm HA u. nicht 356mm VA u. 330mm HA
	FMI11 Elatha	45	-	100-245	255/40		Orig.-Verschr., nicht Bremse 356x34mm
8,5 x 20	RC29	45	ZP568F	100-245	255/35		incl. Facelift 2014
	RC34	43	ZP568F	100-245	225/35, 235/35, 245/35, 255/35		auch ET43 ist ECE
	CA 19	43	-	100-245	255/35		Orig.-Verschr., nicht Bremse 356, 380 u. 400mm

weitere Dimensionen/Designs siehe Konfigurator

Audi S6 (siehe Konfigurator)		ab 2012	4G	5/112	66,6	e1*2007/46*0436*...., e13*2007/46*1147*...	
---	--	---------	----	-------	------	--	--

Audi A6		Modell 2018		F2	5/112	66,6	e1*2007/46*1801*...	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC27	36	-	120-210	205/65, 225/60			Orig.-Verschr., Ausführung D7
	RC32	36	-	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			Orig.-Verschr.
	RC34	36	ZP568F	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			
	RC24	37+45	-	120-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			Orig.-Verschr.
	RC27	38	-	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			Orig.-Verschr., nicht Bremse 374mm
	RC28	35	ZP568F	150-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			
	RC29	29	-	100-210	205/65, 215/60, 215/65, 225/60			Orig.-Verschr.
		35	ZP568F	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			
	RC32	38	-	120-180	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			Orig.-Verschr.
	RC34	41	-	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60, 245/55, 255/50, 255/55			Orig.-Verschr., Ausführung D7
	B24	35	ZP568F	150-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			
B36	45	ZP568F	100-210	205/65, 215/60, 215/65, 225/60, 235/55, 235/60			nicht Bremse 338 u. 350mm	
	RC30	35	ZP568F	100-210	215/55, 225/55, 235/50, 235/55			

7,5 x 18	RC32 / RC34	45	ZP568F	100-210	215/55, 225/55, 235/50, 235/55, 245/50		ET45 nicht Bremse 350mm
		39	-	100-210	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	B32	29	-	120-210	215/55, 225/55		Orig.-Verschr.
		35	ZP568F	120-210	215/55, 225/55, 235/50, 235/55		ET35 nicht Bremse 375mm
		45	ZP568F	120-210	215/55, 225/55, 235/50, 235/55, 245/50		ET45 nicht Bremse 350mm
	B39	35	ZP568F	100-210	215/55, 225/55, 235/50, 235/55		
		45	ZP568F	100-210	215/55, 225/55, 235/50, 235/55, 245/50		nicht Bremse 318, 350 u. 375mm
	AC-MB6	45	-	100-210	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nicht Bremse 350 u. 375mm
8 x 18	CA 20	40	ZP568F	100-210	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		nicht Bremse 374,5x36mm
	Oxigin 25	44	ZP568F	100-250	225/55, 235/50, 235/55, 245/50, 255/50		
	RC27	39	-	100-250	225/55 , 235/50, 235/55, 255/45		Orig.-Verschr., nur Bremse bis 350mm
	RC29	39	-	100-210	225/55 , 235/50, 235/55, 255/45		Orig.-Verschr., nicht Bremse 375mm
	RC32	39	-	100-250	225/55		Orig.-Verschr., nicht Allradlenkung
				100-270	215/55, 225/55, 235/50, 235/55, 255/45		Orig.-Verschr.
	CA 23	39	-	100-250	225/55 , 235/50, 235/55, 255/45		Orig.-Verschr., nicht Bremse 338 u. 375mm
	CA 26	39	ZP568F	100-250	225/55		nicht Bremse 350 u. 375mm
	FMI07 Atena	39	-	100-250	225/55		Orig.-Verschr.
	FMI11 Elatha	39	-	100-250	225/55		Orig.-Verschr., nicht Keramikbremse
	RC27	41	-	150-250	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	RC32	31	-	100-250	215/55		Orig.-Verschr.
		40	-	100-270	215/55, 225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	RC34	40	ZP568F	100-270	215/55, 225/55, 235/50, 235/55, 245/50, 255/45		Ausführung D3
		43	ZP568F	100-250	215/55, 225/55, 235/50, 235/55, 245/50, 255/45, 255/50		
		40	-	100-270	215/55, 225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr., Ausführung D7
	B36	45	ZP568F	100-250	225/55, 235/50, 235/55, 245/50, 255/45		nicht Bremse 318 u. 350mm
	B38	45	ZP568F	120-250	225/55, 235/50, 235/55, 245/50, 255/45		nicht Bremse 350mm
	B42 / B44	45	ZP568F	100-250	225/55, 235/50, 235/55, 245/50, 255/45		nicht Bremse 318, 350 u. 375mm
	AC-M10	40	-	100-250	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
		45	AV4	100-250	225/55, 235/50, 235/55, 245/50, 255/45		nicht Bremse 318, 350 u. 375mm
	AC-MB6	45	ZP567F	100-250	225/55, 235/50, 235/55, 245/50, 255/45		
	AC-521	45	-	100-250	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr., nicht Bremse 350mm
	AF18	40	-	120-250	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	CA 20	39	-	100-250	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr., nicht Bremse 350 u. 375mm
	FMI08 Thoe	34	F31	100-250	215/55, 225/55		
	FMI11 Elatha	45	-	100-250	215/55, 225/55, 235/50, 235/55, 245/50, 255/45, 255/50		Orig.-Verschr., nicht Bremse 370x32mm
	FMI12 Kari	34	Kit 0354	100-250	215/55, 225/55		
		45	Kit 0354	100-250	215/55, 225/55, 235/50, 235/55, 245/50, 255/45, 255/50		
8 x 19	RC32	39	-	100-250	225/45, 235/45, 235/50, 245/45 , 255/45		Orig.-Verschr., bei Allrad auch für Hybrid Fahrzeuge
	B40	39	-	100-250	225/45, 235/45, 235/50, 245/45 , 255/45		Orig.-Verschr.
	Oxigin 29	39	ZP568F	100-250	225/45, 235/45, 235/50, 245/45 , 255/45		
	FMI07 Atena	39	F95	100-250	225/45, 235/45, 235/50, 245/45 , 255/45		
	RC27	26	-	170-250	225/45		Orig.-Verschr.
	RC29	35	ZP568F	100-210	225/45, 235/45, 245/45		
		45	ZP568F	120-210	225/45, 235/45, 235/50, 245/45, 255/45		ET45 nicht Bremse 350mm
	RC34	38+43	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/45		
		35	ZP568F	120-250	225/45, 235/45, 245/45		
	B24	45	ZP568F	120-250	225/45, 235/45, 235/50, 245/45, 255/45		ET45 nicht Bremse 350 u. 375mm
		35+45	ZP568F	150-210 150-250	225/45, 235/45, 235/50 245/45, 255/45		ET35 bei 235/50 u. 255/45 ✖, ET45 nicht Bremse 350 u. 375mm
	B40	38+43	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/45		
	B43	34	ZP568F	100-250	225/45, 235/45, 245/45		
		38+43	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/45		ET43 nicht Bremse 350 u. 375mm
	AC-518	38	AV4	120-250	225/45, 235/45, 235/50, 245/45, 255/45		
	AC-521	35	-	100-250	225/45, 235/45, 245/45		Orig.-Verschr.
	CA 17	45	ZP568F	100-250	235/50, 245/45, 255/45		nicht Bremse 349, 350 u. 374mm
	CA 24	43	ZP568F	100-250	235/45, 235/50, 245/45, 255/45		nicht Bremse 400mm
	RC32	40	-	100-250	245/45		Orig.-Verschr.
	RC34	40	-	100-250	245/45		Orig.-Verschr.
				100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B37	40	-	150-250	245/45		Orig.-Verschr.
				100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B43	40	ZP568F	100-250	225/45, 235/45, 235/50, 245/45 , 255/40, 255/45		
	CA 20	40	-	100-210	245/45		Orig.-Verschr.
				100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	CA 23	40	-	100-250	225/45, 235/45, 235/50, 245/45 , 255/40, 255/45		Orig.-Verschr.
	CA 26	40	ZP568F	100-250	225/45, 235/45, 235/50, 245/45 , 255/40, 255/45		nicht Bremse 350mm
	Oxigin 18	40	ZP568F	100-250	245/45		nicht Bremse 318, 338, 350 u. 375mm

8,5 x 19	FMI07 Atena	40	-	100-250	225/45, 235/45, 235/50, 245/45 , 255/40, 255/45		Orig.-Verschr.
	B32	45	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B36	35	ZP568F	100-250	225/45, 235/45, 245/45		nicht Bremse 318 u. 350mm
	B37	43	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 350
		45	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 350 u. 375mm
	B41	36	ZP568F	100-250	225/45, 235/45, 245/45		
		39	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B42	35	ZP568F	100-250	225/45, 235/45, 245/45		
		42	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 318, 350 u. 375mm
	B44	35	ZP568F	100-250	225/45, 235/45, 245/45		
		42	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	AC-M10	40	-	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
		45	AV4	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	AF18	40	-	150-210 150-250	225/45, 235/45, 235/50 245/45, 255/40, 255/45		Orig.-Verschr.
	CA 20	45	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 318, 350 u. 375mm
	CA 23	45	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 350mm
	FMI07 Atena	45	-	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
	8300 - 1972	45	F31	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	Oxigin 18	35	ZP568F	120-250	225/45, 235/45, 245/45		nicht Bremse 318, 350 u. 375mm
	Oxigin 28	40	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 350mm
		45	ZP568F	100-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		nicht Bremse 318, 350 u. 375mm
8 x 20	B38	35	ZP568F	100-250	225/40, 235/40, 245/40		
	B40	43	ZP568F	120-250	225/40, 235/40, 245/40		
	B43	30	ZP568F	120-250	225/40, 235/40		
		39	ZP568F	100-250	225/40, 235/40, 245/40		
8,5 x 20	FMI08 Thoe	45	F31	100-250	215/45, 225/40, 235/40, 245/40		
	B43	43	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		nicht Hybrid
	RC34	43	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	CA 19	43	-	100-257	255/40		Orig.-Verschr.
				100-250	235/45, 245/40, 255/35, 255/40		
	RC29	40	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
		45	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	RC34	37	ZP568F	100-250	225/40, 235/40, 245/40		
	RC36	40	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	B24	42	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	B32	40	ZP568F	120-250	235/40, 245/40, 255/35, 255/40		
	B41	35	ZP568F	100-195	225/40, 235/40, 245/40		Frontantrieb
				150-250	235/40, 245/40		Allrad
	B42	35	ZP568F	100-250	225/40, 235/40, 245/40		
		40	ZP568F	100-210	225/40, 235/40, 245/40, 255/35, 255/40		ET40 nicht Bremse 350 u. 375mm
		45	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		Achtung Bremsen! siehe TÜV!
	B43	35+40	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		ET35 ab 255/35 ✖
	B44	35	ZP568F	100-250	225/40, 235/40, 245/40		
		40	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		ET40 nicht Bremse 350mm
	AC-521	32	-	100-250	225/40, 235/40		Orig.-Verschr.
	AC-M10	40	-	100-250	225/40, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr.
	AF18	32	-	150-210	225/40, 235/40		Orig.-Verschr.
	CA 17	35	ZP568F	100-250	235/45, 245/40		Bremse bis 350mm zulässig!
		40	ZP568F	100-250	235/45, 245/40, 255/35, 255/40		Achtung Bremsen! siehe TÜV!
	CA 19	45	ZP568F	100-250	235/45, 245/40, 255/35, 255/40		Achtung Bremsen! siehe TÜV!
	FMI07 Atena	39	-	100-250	225/40, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr.
	FMI12 Kari	34	F94	100-250	225/40, 235/40		
		40	F94	100-250	225/40, 235/40, 245/40, 255/35, 255/40		ET40 nicht Bremse 338x30mm
9 x 20	B40	34	ZP568F	150-250	235/45		
	B41	35	ZP568F	100-195	225/40, 235/40		Frontantrieb
				150-250	235/40		Allrad
		38	ZP568F	100-195	225/40, 235/40, 245/40		Frontantrieb
				150-250	235/40, 245/40		Allrad
	B43	42+44	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	AC-518	41	F95	100-250	235/45, 245/40, 255/35, 255/40		
	AC-522	40	-	100-250	235/45, 245/40		Orig.-Verschr., Reifen 245/40 nur bis Achslast 1550kg!
	AC-M08	40	-	100-250	235/45		Orig.-Verschr.
	AF18	40	-	150-210	225/40, 235/40		Orig.-Verschr.
				150-250	245/40		
	CA 20	45	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		Achtung Bremsen! siehe TÜV!
	CA 23	45	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		
	FMI11 Elatha	34	-	100-250	235/40		Orig.-Verschr., nicht Bremse 338x30mm
	Oxigin 25	35	ZP568F	100-250	235/45		
	Oxigin 28	35	ZP568F	100-250	225/40, 235/40		
		45	ZP568F	100-250	225/40, 235/40, 245/40, 255/35, 255/40		nicht Bremse 350 u. 375mm

9,5 x 20	B42	42	ZP568F	100-210	235/40, 245/40		
	CA 19	43	ZP568F	100-250	245/40		
8,5 x 21	B41	43	ZP568F	100-250	245/35, 255/30, 255/35		
		37	ZP568F	100-250	245/35		
		40	ZP568F	100-250	245/35, 255/30, 255/35		
	B43	37	ZP568F	100-250	245/35		
		43	ZP568F	100-250	245/35, 255/35		
9 x 21	B32	40	ZP568F	120-250	245/35		
	AF18	37	-	120-250	245/35		Orig.-Verschr.
	CA 20	45	ZP568F	100-250	245/35, 255/35		Achtung Bremsen! siehe TÜV!
9,5 x 21	B41	43	ZP568F	100-250	245/35, 255/30		
	FMI10 e-Joule	41,5	F95	100-250	245/35		

Audi A6 Avant TFSle Plug-in Hybrid				F2	5/112	66,6	e1*2007/46*1801*..
indirekt - teilweise direkt Brocksens 2							

Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC27	39	-	185, 195	225/55, 235/50, 235/55, 255/45		Orig.-Verschr.
	RC25	45	ZP568F	185, 195	225/55, 235/50, 235/55, 245/50, 255/45		
	RC27	41	-	185	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	AC-M10	40	-	185, 195	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	AC-MB6	45	ZP567F	185, 195	225/55, 235/50, 235/55, 245/50, 255/45		
	AC-521	45	-	185, 195	225/55, 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	AF20	35	-	185	225/55		Orig.-Verschr.
8 x 19	B40	39	-	185, 195	235/45, 235/50, 245/45M+S, 255/45		Orig.-Verschr.
	Oxigin 29	39	ZP568F	185, 195	235/45, 235/50, 245/45M+S, 255/45		
	RC29	35	ZP568F	185	235/45, 245/45		
	B40	43	ZP568F	185, 195	235/45, 235/50, 245/45, 255/45		
	B43	34	ZP568F	185, 195	235/45, 245/45		
		38	ZP568F	185, 195	235/45, 235/50, 245/45, 255/45		
	AC-521	35	-	185, 195	235/45, 245/45		Orig.-Verschr.
	Oxigin 29	32	ZP568F	185, 195	235/45, 245/45		
		43	ZP568F	185, 195	235/45, 235/50, 245/45, 255/45		
8,5 x 19	B43	40	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	CA 20	40	-	185	245/45		Orig.-Verschr.
				185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	CA 23	40	-	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
	CA 26	40	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	B32	45	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	B36	35	ZP568F	185, 195	235/45, 245/45		
		40	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	B37	43	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
			ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	AC-M10	45	AV4	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	AF20	40	-	185	235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
CA 23	45	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45			
8 x 20	Oxigin 28	40	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45		
	B43	39	ZP568F	185, 195	245/40		
8,5 x 20	B43	43	ZP568F	185, 195	245/40, 255/35, 255/40		
	RC29	40+45	ZP568F	185, 195	245/40, 255/35, 255/40		
	RC36	40	ZP568F	185, 195	245/40, 255/35, 255/40		
	B24	42	ZP568F	185, 195	245/40, 255/35, 255/40		
	B32	40	ZP568F	185	245/40, 255/35, 255/40		
	B42	35	ZP568F	185, 195	245/40		
	B43	40	ZP568F	185, 195	245/40, 255/35, 255/40		
	B44	40	ZP568F		255/40		i.V.
	AC-518	45	-	185	245/40, 255/35, 255/40		Orig.-Verschr.
	AC-M10	40	-	185, 195	245/40, 255/35, 255/40		Orig.-Verschr.
9 x 20	B43	38	ZP568F	185, 195	245/40		
		42+44	ZP568F	185, 195	245/40, 255/35, 255/40		
	CA 23	45	ZP568F	185, 195	245/40, 255/35, 255/40		
9,5 x 20	B42	42	ZP568F	185	245/40		
8,5 x 21	B43	43	ZP568F	185, 195	255/35		

Audi S6	ab 06.2019	F2	5/112	66,6	e1*2007/46*1801*..
indirekt - teilweise direkt Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC27	39	-	257	235/55		Orig.-Verschr.
8 x 19	RC32	39	-	257	245/45		Orig.-Verschr., nicht Keramikbremse
	B40	39	-	253, 257	245/45 , 255/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	FMI07 Atena	39	F95	257	245/45		nicht Keramikbremse
	B24	35	ZP568F	257	245/45		nur M+S, nicht Keramikbremse
	B40	38	ZP568F	257	245/45, 255/45		nur M+S, nicht Keramikbremse
	B43	34	ZP568F	253, 257	245/45		nur M+S, nicht Keramikbremse

8,5 x 19		38	ZP568F	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
	AC-521	35	-	253, 257	245/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	FMI07 Atena	40	-	257	245/45		Orig.-Verschr.
	RC34	40	-	253-257	245/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	B36	35	ZP568F	253, 257	245/45		nur M+S, nicht Keramikbremse
	B37	35	ZP568F	253, 257	245/45		nicht Keramikbremse
	B41	36+39	ZP568F	253-257	245/45		nur M+S, nicht Keramikbremse
	B42	35	ZP568F	253, 257	245/45		nur M+S, nicht Keramikbremse
	B43	40	ZP568F	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
	B44	42	ZP568F	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
	AC-M10	40	-	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
		45	AV4	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
	CA 20	40	-	253, 257	245/45, 255/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	CA 26	40	ZP568F	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
8 x 20	Oxigin 28	40	ZP568F	253, 257	245/45, 255/45		nur M+S, nicht Keramikbremse
	B38	35	ZP568F	253, 257	245/40		nur M+S
8,5 x 20	B43	39	ZP568F	253, 257	245/40		nur M+S
	B43	43	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Hybrid
	RC34	43	ZP568F	253-257	255/35, 255/40		nicht Keramikbremse
	RC29	40	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
		45	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	RC34	37	ZP568F	253-257	255/35, 255/40		nicht Keramikbremse
	RC36	40	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	B32	40	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	B41	35	ZP568F	253-257	255/35, 255/40		nicht Keramikbremse
	B42	35	ZP568F	253, 257	245/40M+S		nicht Keramikbremse
	B43	40	ZP568F	253, 257	245/40M+S, 255/35, 255/40		
	B44	40	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	AC-518	45	-	253, 257	245/40M+S, 255/35, 255/40		Orig.-Verschr., nicht Keramikbremse
	AC-M10	40	-	253, 257	245/40M+S, 255/35, 255/40		Orig.-Verschr.
9 x 20	FMI07 Atena	39	-	257	255/35, 255/40		Orig.-Verschr., nicht Keramikbremse
	B41	38	ZP568F	257	255/35, 255/40		nicht Keramikbremse
9,5 x 20	B43	42+44	ZP568F	253, 257	245/40M+S, 255/35, 255/40		
	B42	42	ZP568F	253, 257	245/40M+S		
8,5 x 21	B41	43	ZP568F	253-257	255/35		nicht Keramikbremse
		34+37+40	ZP568F	253-257	255/35		nicht Keramikbremse
	B43	43	ZP568F	253, 257	255/35		
9 x 21	CA 20	45	ZP568F	253, 257	255/35		nicht Keramikbremse
9,5 x 21	FMI10 e-Joule	41,5	F95	253-257	255/35		nicht Keramikbremse

Audi A6 NEU		2025		F2 / C9	5/112	66,6	e1*2007/46*1801*52-..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC32	36	-	120-195	225/60			Orig.-Verschr., Ausführung D7
8 x 18	RC32	39	-		225/55			Orig.-Verschr., i.V., Ausführung D7
8,5 x 19	RC34	40	-		245/45			Orig.-Verschr., i.V., Ausführung D7

Audi A6 e-tron NEU i.V.		2024		GH	5/130	66,6	e1*2018/858*00393*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	RC36	VA 40	-	100-138	VA 235/45			Orig.-Verschr., i.V.
9 x 20		HA 57			HA 265/40			
8 x 20	B40	VA 40	-		VA 235/45			Orig.-Verschr., i.V.
9 x 20		HA 57			HA 265/40			

Audi A6 Allroad (siehe Konfigurator)		ab 2012	4G/4G1	5/112	66,6	e1*2007/46*0436*..., e13*2007/46*1147*...		
---	--	---------	--------	-------	------	---	--	--

Audi A6 Allroad Quattro			ab 02.2019		F2	5/112	66,6	e1*2007/46*1801*13-..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 18	RC27	39	-	150-257	235/55				Orig.-Verschr., nicht Bremse 400mm
	CA 23	39	-	150-257	235/55				Orig.-Verschr., nicht Bremse 375 u. 400mm
	CA 26	39	ZP568F	150-257	235/55				nicht Bremse 375 u. 400mm
	FMI07 Atena	39	-	170-257	235/55				Orig.-Verschr.
	FMI11 Elatha	39	-	150-257	235/55				Orig.-Verschr.
	RC29	39	-	170-257	235/55				Orig.-Verschr., nicht Bremse 375 u. 400mm
	RC32	40	-	150-257	235/55, 245/50, 245/55, 255/50				Orig.-Verschr.
	RC34	40	-	150-257	235/55, 245/50, 245/55, 255/50				Orig.-Verschr., Ausführung D7
		40	ZP568F	150-257	235/55, 245/50, 245/55, 255/50				Ausführung D3
	B36	35	ZP568F	150-257	235/55				nicht Bremse 375 u. 400mm
	B37	40	-	170-257	235/55				Orig.-Verschr., nicht Bremse 375 u. 400mm
	B42 / B44	35	ZP568F	150-257	235/55				nicht Bremse 400mm

	AC-M10	40	-	150-257	235/55		Orig.-Verschr., nicht Bremse 400mm
	CA 20	39	-	150-257	235/55		Orig.-Verschr., nicht Bremse 350, 375 u. 400mm
	CA 23	39	-	150-257	235/55		Orig.-Verschr., nicht Bremse 375 u. 400mm
	FMI08 Thoe	34	F31	150-257	235/55		
	FMI12 Kari	34	Kit 0354	150-257	235/55		
8 x 19	B43	40	ZP568F	150-257	235/50		nicht Bremse 400mm
	RC29	35	ZP568F	170-257	235/50, 245/45, 255/45		
	RC32	39	-	150-257	235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	RC34	38	ZP568F	150-257	235/50, 245/45, 245/50, 255/45		nicht 6-Kolben Festsattel mit 399x38,5mm
	B24	35	ZP568F	170-257	235/50, 245/45, 255/45		
	B40	38	ZP568F	150-257	235/50, 245/45, 255/45		
		39	-	150-257	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	34+38	ZP568F	150-257	235/50, 245/45, 255/45		
	CA 17	45	ZP568F	150-257	235/50, 245/45, 245/50, 255/45, 255/50		
	CA 24	43	ZP568F	150-257	235/50, 245/45, 245/50, 255/45, 255/50		nicht Bremse 400mm
	AC-521	35	-	150-257	235/50, 245/45, 255/45		Orig.-Verschr.
8,5 x 19	Oxigin 29	39	ZP568F	150-257	235/50, 245/45, 255/45		nicht Bremse 400mm
	RC32	40	-	150-257	235/50		Orig.-Verschr.
	RC34	40	-	150-257	235/50		Orig.-Verschr.
				150-257	235/50, 245/45, 245/50, 255/45, 265/45		
	CA 20	40	-	170-257	235/50 , 245/45, 255/45		Orig.-Verschr.
	CA 23	40	-	150-257	235/50 , 245/45, 255/45		Orig.-Verschr., nicht Bremse 400mm
	CA 26	40	ZP568F	150-257	235/50 , 245/45, 255/45		
	Oxigin 18	40	ZP568F	150-257	235/50		nicht Bremse 350, 375 u. 400mm
	FMI07 Atena	40	-	170-257	235/50		Orig.-Verschr.
	B36	35	ZP568F	170-257	235/50, 245/45, 255/45		
	B37	35	ZP568F	150-257	235/50, 245/45, 255/45		
		40	-	150-257	235/50, 245/45, 255/45		Orig.-Verschr., nicht Bremse 400mm
	B41	36	ZP568F	150-257	235/50, 245/45, 255/45		
		39	ZP568F	150-257	235/50, 245/45, 245/50, 255/45, 265/45		
	B42	35	ZP568F	150-257	245/45, 255/45		
	B43	40	ZP568F	150-257	235/50, 245/45, 255/45		
	B44	35	ZP568F	150-257	235/50, 245/45, 255/45		
	AC-M10	40	-	150-257	235/50, 245/45, 255/45		Orig.-Verschr.
	Oxigin 18	35	ZP568F	170-257	235/50, 245/45, 255/45		nicht Bremse 375mm
	Oxigin 25	35	ZP568F	170-257	245/45		
	Oxigin 26	40	ZP568F	150-257	235/50, 245/45, 255/40, 255/45, 265/45		
		45	ZP568F	150-257	235/50, 245/45, 245/50, 255/40, 255/45, 265/45		
	Oxigin 28	40	ZP568F	150-257	235/50, 245/45, 255/45		
	8300 - 1972	32	F85	150-257	245/45		
9 x 19	B41	38	ZP568F	150-257	245/45, 255/45		
	CA 19	43+44	ZP568F	150-257	245/45, 255/40, 255/45, 265/40, 265/45		
8 x 20	B38	35	ZP568F	150-257	235/45, 245/40, 245/45		
	B43	27	ZP568F	150-257	235/45		
		30+39	ZP568F	150-257	235/45, 245/40, 245/45		
8,5 x 20	RC34	37	ZP568F	150-257	235/45, 245/40, 245/45 , 255/40		
	RC29	33+40	ZP568F	150-257	235/45, 245/40, 245/45, 255/40		
	RC34	30	ZP568F	150-257	235/45		
		33	ZP568F	150-257	235/45, 245/40, 245/45		
	RC36	40	ZP568F	150-257	235/45, 245/40, 245/45, 255/40		
	B24	33	ZP568F	150-257	235/45, 245/40, 245/45		
	B32	40	ZP568F	170-257	235/45, 245/40, 245/45, 255/40		
	B42	35	ZP568F	150-257	235/45, 245/40, 245/45, 255/40		
		40	ZP568F	170-257	235/45, 245/40, 245/45, 255/40		ET40 nicht Bremse 375mm
	B43	35+40	ZP568F	150-257	235/45, 245/40, 245/45, 255/40		
	B44	30	ZP568F	150-257	235/45		
		40	ZP568F	150-257	235/45, 245/40, 245/45, 255/40		
	AC-518	32	-	170-257	235/45, 245/40, 245/45		Orig.-Verschr.
	AC-521	32	-	150-257	235/45, 245/40, 245/45		Orig.-Verschr.
	AC-M10	40	-	150-257	235/45, 245/40, 245/45, 255/40		Orig.-Verschr.
	CA 17	35	ZP568F	170-257	235/45, 245/40, 245/45		
		40	ZP568F	170-257	235/45, 245/40, 245/45, 255/40, 255/45		
	CA 19	43+45	ZP568F	150-257	235/45, 245/40, 245/45, 255/40, 255/45		
	FMI12 Kari	34	F94	150-257	235/45, 245/40, 245/45		
		40	F94	150-257	235/45, 245/40, 245/45, 255/40		
9 x 20	B37	37	ZP568F	150-257	235/45, 245/40, 245/45		
	B40	34	ZP568F	170-257	235/45, 245/40, 245/45		
	B41	33	ZP568F	150-257	235/45		
	B43	35+38	ZP568F	150-257	235/45, 245/40, 245/45		
	AC-518	41	F95	150-257	235/45		
	AC-522	33	-	150-257	235/45		Orig.-Verschr.
		40	-	150-257	235/45, 245/40, 245/45, 255/40, 255/45		Orig.-Verschr.

	AC-M08	33	AV1	150-257	235/45		
		40	-	150-257	235/45, 245/40, 245/45, 255/40, 255/45		Orig.-Verschr.
	CA 20	35	ZP568F	150-257	235/45, 245/40, 245/45		
	CA 23	38	ZP568F	150-257	235/45, 245/40, 245/45		nicht Bremse 400mm
9,5 x 20	Oxigin 28	35	ZP568F	150-257	235/45, 245/40, 245/45		
	CA 19	43	ZP568F	150-257	245/40, 255/40, 255/45		
8,5 x 21	B41	37	ZP568F	150-257	245/35, 245/40 , 255/35		
		40	ZP568F	150-257	245/35, 245/40, 255/35		
	B43	34	ZP568F	150-257	245/40		
		37	ZP568F	150-257	245/40, 255/35		
9 x 21	B32	40	ZP568F	150-257	245/40		
	B43	36	ZP568F	150-257	245/40		
	CA 20	37	ZP568F	150-257	245/40		
9,5 x 21	FMI10 e-Joule	41,5	F95	150-257	245/35		
	FMI12 Kari	41	-	150-257	245/35		Orig.-Verschr.

Audi A7 (siehe Konfigurator)	ab 07.10	4G/ 4G1	5/112	66,5	e1*2007/46*0436*..., e13*2007/46*1147*...
-------------------------------------	-----------------	----------------	--------------	-------------	---

Audi S7 (siehe Konfigurator)	ab 2012	4G/ 4G1	5/112	66,6	e1*2007/46*0436*..., e13*2007/46*1147*...
-------------------------------------	----------------	----------------	--------------	-------------	---

Audi A7 Sportback	2018	F2	5/112	66,6	e1*2007/46*1801*..., e1*2007/46*1840*..
indirekt - teilweise direkt Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC27	36	-	100-210	205/65		Orig.-Verschr., nicht Bremse 374mm, Ausführung "D7"
				100-250	225/60		
8 x 18	RC27	26	-	150-250	225/55		Orig.-Verschr.
	RC32	26	-	150-250	225/55 , 235/50, 235/55, 245/50		Orig.-Verschr.
	FMI08 Thoe	26	F85	150-250	225/55		
	FMI11 Elatha	26	-	150-250	225/55 , 235/50, 235/55, 245/50		Orig.-Verschr., nicht Keramikbremse
	FMI14 Jupiter	26	F85	150-250	225/55		
	RC27	28	-	210	235/50, 235/55, 255/45		Orig.-Verschr.
		31	-	210	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	RC32	20	-	120-250	225/55 , 235/50, 235/55		Orig.-Verschr.
		29+31	-	150-250	225/55 , 235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	B36	30	ZP568F	150-250	225/55, 235/50, 235/55, 245/50, 255/45, 255/50		nicht Bremse 375mm
	B42 / B44	30	ZP568F	150-250	225/55, 235/50, 235/55, 245/50, 255/45, 255/50		
	AC-MB6	29	ZP567F	150-250	225/55 , 235/50, 235/55, 245/50, 255/45		
	AC-M10	30	AV4	150-250	225/55, 235/50, 235/55, 245/50, 255/45, 255/50		
	AC-518	30	F95	150-250	225/55, 235/50, 235/55, 245/50, 255/45, 255/50		
	AF18	28	-	150-250	225/55 , 235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	CA 17	35	ZP568F	150-250	245/50		
	FMI08 Thoe	26	F31	120-250	225/55 , 235/50, 235/55, 245/50		
	FMI12 Kari	26	Kit 0354	120-250	225/55 , 235/50, 235/55, 245/50		
8 x 19	RC32	27	-	120-250	235/45, 235/50, 245/45 , 255/45		Orig.-Verschr., Fahrzeuge mit Allradlenkung nicht geprüft!
	RC34	27	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/45		
	B43	27	ZP568F	150-250	235/45, 235/50, 245/45 , 255/45		
	RC27	26	-	210	245/45		Orig.-Verschr.
	RC32	26	-	120-250	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	28	ZP568F	150-250	225/45 , 235/45, 235/50, 245/45, 255/45		
	CA 24	30	ZP568F	120-250	235/50, 255/45		nicht Bremse 400mm
8,5 x 19	RC32	27	-	120-250	245/45		Orig.-Verschr.
	B32	25	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B37	25	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B41	20+21	ZP568F	150-250	235/45, 245/45		
		28	ZP568F	150-250	235/45, 235/50, 245/45, 255/45		
	B42	30	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B43	25	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	B44	25+30	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	AC-M10	30	AV4	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	AF18	30	-	170-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
	CA 23	30	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
	FMI07 Atena	28	-	150-250	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	FMI11 Elatha	21	-	120-250	235/45, 245/45		Orig.-Verschr.
	8300 - 1972	32	F85	120-250	235/45, 235/50, 245/45, 255/45		
	Oxigin 26	30	ZP568F	120-250	235/50, 245/45, 255/40, 255/45		
	Oxigin 28	30	ZP568F	150-250	225/45, 235/45, 235/50, 245/45, 255/40, 255/45		
9 x 19	CA 19	25	ZP568F	120-250	235/45		
	CA 24	35	ZP568F	120-250	255/40, 255/45		
	FMI12 Kari	20					
8 x 20	B43	27+30	ZP568F	150-250	225/40, 235/40, 245/40		

8,5 x 20	B43	30	ZP568F	120-250	225/40, 235/40, 245/40, 255/35, 255/40		nicht Hybrid
	RC34	30	ZP568F	120-250	235/40, 245/40, 255/40		
	RC29	29	ZP568F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
	B32	30	ZP568F	150-250	235/40, 245/40, 255/35, 255/40		
	B41	20	ZP568F	120-250	235/40, 245/40		
	B42	30	ZP568F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
	B44	25	ZP568F	150-250	225/40, 235/40, 245/40		
		30	ZP568F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
	AC-M10	30	ZP567F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
	AF18	20	AV1	170-250	225/40, 235/40		
	CA 17	35	ZP568F	150-250	255/35, 255/40		
	CA 19	32	ZP568F	120-250	255/35, 255/40		
9 x 20	Oxigin 14	35	ZP568	210	255/35, 255/40		
	B37	29	ZP568F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
	B40	34	ZP568F	150-210	255/35, 255/40		
	AC-518	41	F95	120-250	245/40, 255/35, 255/40		Orig.-Verschr.
	AC-522	33	-	120-250	245/40, 255/35, 255/40		
	AC-M08	33	F95	120-250	245/40, 255/35, 255/40		
	AF18	25	-	170-250	225/40, 235/40, 245/40		Orig.-Verschr.
	CA 23	30	ZP568F	150-250	225/40, 235/40, 245/40, 255/35, 255/40		
9,5 x 20	Oxigin 25	35	ZP568F	150-250	255/35, 255/40		
	Oxigin 28	20	ZP568F	150-250	225/40, 235/40		
8,5 x 21	B42	25	ZP568F	150-250	235/40		
	B41	30	ZP568F	120-250	245/35, 255/35		
	FMI11 Elatha	30	-	120-250	255/35		Orig.-Verschr.
	B41	19	ZP568F	120-250	245/35		
9 x 21	B43	30	ZP568F	150-250	245/35, 255/35		
	B32	30	ZP568F	150-250	245/35, 255/35		
	AF18	30	-	150-250	245/35, 255/35		Orig.-Verschr.
	CA 17	35	ZP568F	120-250	245/35, 255/35		
	CA 20	30	ZP568F	150-250	245/35, 255/35		
9,5 x 21	B41	31	ZP568F	120-250	245/35, 255/35, 265/30		
	FMI12 Kari	31	-	120-250	245/35, 255/35, 265/30		Orig.-Verschr.

Audi A7 Sportback TFSle

Plug-in-Hybrid NEU

F2

5/112

66,6

e1*2007/46*1801*..

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	RC27	26	-	185, 195	225/55 , 235/50, 235/55, 245/50, 255/45	 Orig.-Verschr.
		28	-	185	225/55, 235/50, 235/55, 245/50, 255/45	Orig.-Verschr.
	AC-MB6	29	ZP567F	185, 195	225/55, 235/50, 235/55, 245/50, 255/45	
	AC-M10	30	AV4	185, 195	225/55, 235/50, 235/55, 245/50, 255/45, 255/50	
8,5 x 18	AC-518	30	AV1	185	225/55, 235/50, 235/55, 245/50, 255/45, 255/50	
	B32	30	ZP568F	185, 195	225/55, 235/50, 235/55, 245/50, 255/45, 265/45	
8 x 19	RC27	26	-	185, 195	235/45, 235/50, 245/45, 255/45	Orig.-Verschr.
	B43	27+28	ZP568F	185, 195	235/45, 235/50, 245/45, 255/45	
8,5 x 19	B32	25	ZP568F	185	235/45, 235/50, 245/45, 255/40, 255/45	
	B36	30	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
	B37	25	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
	B43	25	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
	AC-M10	30	AV4	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
	CA 23	30	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
	Oxigin 28	30	ZP568F	185, 195	235/45, 235/50, 245/45, 255/40, 255/45	
8 x 20	B43	27+30	ZP568F	185, 195	245/40	
8,5 x 20	B43	30	ZP568F	185, 195	245/40, 255/40	
	RC29	29	ZP568F	185, 195	245/40, 255/40	
	B32	30	ZP568F	185	245/40, 255/40	
	B42	30	ZP568F	185, 195	245/40, 255/40	
	AC-M10	30	ZP567F	185, 195	245/40, 255/40	
9 x 20	B37	29	ZP568F	185, 195	245/40, 255/40	
	CA 23	30	ZP568F	185, 195	245/40, 255/40	
8,5 x 21	B43	30	ZP568F	185, 195	255/35	
9 x 21	CA 20	30	ZP568F	185, 195	255/35	

Audi S7 Sportback

ab 05.2019

F2

5/112

66,6

e1*2007/46*1801*..

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	FMI14 Jupiter	26	F85	253, 257	225/55	
8 x 19	B43	27+28	ZP568F	253, 257	245/45, 255/45	nur M+S, nicht Keramikbremse
	B32	25	ZP568F	253, 257	245/45, 255/40, 255/45	nur M+S, nicht Keramikbremse
		30	ZP568F	253, 257	245/40, 255/35, 255/40	nicht Keramikbremse
	B36	30	ZP568F	253, 257	245/45, 255/40, 255/45	nur M+S, nicht Keramikbremse
	B37	25	ZP568F	253, 257	245/45, 255/40, 255/45	nur M+S, nicht Keramikbremse

8,5 x 19	B42	30	ZP568F	253, 257	245/45, 255/40		nur M+S, nicht Keramikbremse
	B43	25	ZP568F	253, 257	245/45, 255/40, 255/45		nur M+S, nicht Keramikbremse
	B44	25	ZP568F	253, 257	245/45, 255/40, 255/45		nur M+S, nicht Keramikbremse
		30	ZP568F	253, 257	245/45, 255/40		nur M+S, nicht Keramikbremse
	AC-M10	30	AV4	253, 257	245/45, 255/40, 255/45		nur M+S, nicht Keramikbremse
	CA 23	30	ZP568F	253, 257	245/45, 255/40, 255/45		nur M+S, nicht Keramikbremse
	Oxigin 28	30	ZP568F	253, 257	245/45, 255/40, 255/45		nur M+S, nicht Keramikbremse
8 x 20	B43	27+30	ZP568F	253, 257	245/40		nur M+S
8,5 x 20	B43	30	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Hybrid
	RC29	29	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	B32	30	ZP568F	257	245/40M+S, 255/35, 255/40		
	B42	30	ZP568F	253, 257	245/40M+S, 255/35, 255/40		nicht Keramikbremse
	B44	30	ZP568F	253, 257	245/40M+S, 255/35, 255/40		
	AC-M10	30	ZP567F	253, 257	245/40M+S, 255/35, 255/40		
9 x 20	B37	29	ZP568F	253, 257	245/40M+S, 255/35, 255/40		
8,5 x 21	B43	30	ZP568F	253, 257	255/35		

Audi A8	ab 11.2017	F8	5/112	66,6	e1*2007/46*1751*...
----------------	-------------------	-----------	--------------	-------------	----------------------------

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	RC32	29	-	210-250	235/50, 235/55 , 245/50, 245/55	 Orig.-Verschr.
	FMI07 Atena	29	-	210-250	235/55	 Orig.-Verschr.
	RC29	35	ZP568F	210, 250	235/55, 245/50, 255/50	Orig.-Verschr., nicht Bremse 375mm
		39	-	210, 250	235/55, 245/50, 255/50	Orig.-Verschr., nicht Bremse 375mm
	RC32	26	-	210-250	235/50, 235/55	Orig.-Verschr.
		31+39+40	-	210-250	235/50, 235/55, 245/50, 245/55, 255/50	Orig.-Verschr.
	RC34	30	ZP568F	210-250	235/50, 235/55, 245/50, 245/55	
		40	ZP568F	210-250	235/50, 235/55, 245/50, 245/55, 255/50	Ausführung D3
		40	-	210-250	235/50, 235/55, 245/50, 245/55, 255/50	Orig.-Verschr., Ausführung D7
	B36 / B37	35	ZP568F	210, 250	235/55, 245/50, 255/50	nicht Bremse 375mm
	AC-MB6	39	-	210, 250	235/55, 245/50, 255/50	Orig.-Verschr.
	AC-M10	40	-	210, 250	235/55, 245/50, 255/50	nicht Bremse 400mm u. nicht Keramik
	AC-518	40	AV4	210, 250	235/55, 245/50, 255/50	nicht Bremse 375mm
		28	-	210, 250	235/55, 245/50	Orig.-Verschr.
	AF18	35+40	-	210, 250	235/55, 245/50, 255/50	Orig.-Verschr., ET40 nich Bremse 375mm
		39	-	210, 250	235/55, 245/50, 255/50	Orig.-Verschr., nicht Bremse 375 u. 400mm u. nicht Keramikbremse
	FMI08 Thoe	26	F31	210-250	235/50, 235/55	
		34	F31	210-250	235/50, 235/55, 245/50, 245/55, 255/50	
8 x 19	FMI11 Elatha	26	-	210-250	235/50, 235/55	Orig.-Verschr.
	FMI12 Kari	26	Kit 0354	210-250	235/50, 235/55	
		34	Kit 0354	210-250	235/50, 235/55, 245/50, 245/55, 255/50	
	Oxigin 29	32	ZP568F	210-338	235/50	 nicht Keramikbremse
				210-338	235/50, 245/45, 255/45	 nicht Bremse 400mm u. nicht Keramik
	RC29	35	ZP568F	210-338	235/50, 245/45, 255/45	ab 251 KW nur M+S, nicht Bremse 400 mm
	RC32	32	-	210, 250	235/50	 Orig.-Verschr., i.V.
		27+39	-	210-338	235/45, 235/50, 245/45, 255/45	Orig.-Verschr., ET39 auch für Hybrid Fahrzeuge
	RC34	27+38	ZP568F	210-338	235/45, 235/50, 245/45, 255/45	ET38 nicht 6-Kolben Festsattel mit 399x38,5mm
	B24	35	ZP568F	210, 250	235/50, 245/45, 255/45	
	B40	31	ZP568F	210-338	235/50, 245/45, 255/45	
		38	ZP568F	210, 250	235/50, 245/45, 255/45	
		39	-	210-338	235/50, 245/45, 255/45	Orig.-Verschr.
	B43	27+28+34+38	ZP568F	210-338	235/50, 245/45, 255/45	
	AC-518	38	AV4	210, 250	235/50, 245/45, 255/45	
	AC-521	35	-	210-338	235/50, 245/45, 255/45	Orig.-Verschr.
	CA 24	30	ZP568F	210-250	235/50, 255/45	
	FMI07 Atena	39	F95	210-338	235/45, 235/50, 245/45, 255/45	
8,5 x 19	Oxigin 29	39	ZP568F	210-338	235/50, 245/45, 255/45	nicht Bremse 400mm u. nicht Keramik
	RC34	40	-	210-338	235/45, 235/50, 245/45, 255/45, 265/45	Orig.-Verschr., nicht Bremse 420x40mm
	B32	25+34,5	ZP568F	210-338	235/50, 245/45, 255/45	
	B36	30	ZP568F	210-338	235/50, 245/45, 255/45, 265/45	
	B37	25+32	ZP568F	210, 250	235/50, 245/45, 255/45, 265/45	ET25 bei 265/45 ✖
		40	ZP568F	210-338	235/50, 245/45, 255/45, 265/45	ET40 nicht Bremse 400mm
	B41	28	ZP568F	210-338	235/45, 235/50, 245/45, 255/45	
		36+39	ZP568F	210-338	235/45, 235/50, 245/45, 255/45, 265/45	
	B43	25	ZP568F	210-338	235/50, 245/45, 255/45	
		40	ZP568F	210-338	235/50, 245/45, 255/45, 265/45	
	AC-M10	30	AV4	210-338	235/50, 245/45, 255/45, 265/45	nicht Keramikbremse
		40	-	210-338	235/50, 245/45, 255/45, 265/45	Orig.-Verschr.
	AF18	30+40	-	210, 250	235/50, 245/45, 255/45, 265/45	Orig.-Verschr.

	CA 20	40	-	210-338	235/50, 245/45, 255/45, 265/45		Orig.-Verschr., nicht Keramikbremse
	CA 23	30	ZP568F	210-338	235/50, 245/45, 255/45, 265/45		
		40	-	210-338	235/50, 245/45, 255/45, 265/45		Orig.-Verschr., ET40 nicht Bremse 400mm
	CA 26	40	ZP568F	210-338	235/50, 245/45, 255/45, 265/45		nicht Bremse 350mm u. nicht Keramik
	FMI07 Atena	28	-	210-338	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		40	F95	210-338	235/45, 235/50, 245/45, 255/45, 265/45		nicht Bremse 399mm
	FMI11 Elatha	21	F95	210-338	235/45		nicht Bremse 420x40mm
	8300 - 1972	32	F85	210-338	235/45, 235/50, 245/45, 255/45, 265/45		nicht Bremse 420x40mm
	Oxigin 18	35	ZP568F	210-338	235/50, 245/45, 255/45, 265/45		nicht Bremse 350, 375 u. 400mm
Oxigin 25	35	ZP568F	210-250	235/50, 245/50, 255/45, 265/45		bei 245/50 ✖	
Oxigin 28	30+40	ZP568F	210-338	235/50, 245/45, 255/45, 265/45		ET40 nicht Bremse 350mm	
9 x 19	B41	38	ZP568F	210-338	235/45, 245/45, 255/45, 265/40, 265/45, 275/40		nicht Bremse 420x40mm
	CA 24	35	ZP568F	210-250	255/45		
8 x 20	RC36	39	ZP568F	210-338	235/45, 245/40		
	B43	27+30+39	ZP568F	210-338	235/45, 245/40		
8,5 x 20	RC29	29	ZP568F	210-338	235/45, 245/40, 255/40		
		33+40	ZP568F	210-338	235/45, 245/40, 255/40		
	RC34	30+33+37	ZP568F	210-338	235/45, 245/40, 255/40		
	RC36	40	ZP568F	210-338	235/45, 245/40, 255/40		nicht Keramikbremse
	B24	33	ZP568F	210, 250	235/45, 245/40, 255/40		
	B32	30+40	ZP568F	210-338	235/45, 245/40, 255/40		
	B41	35	ZP568F	210-338	235/45, 245/40, 255/40		
		30	ZP568F	210-338	235/45, 245/40, 255/40		
	B42	35	ZP568F	210-338	235/45, 245/40, 255/40		
		30	ZP568F	210-338	235/45, 245/40, 255/40		
	B43	35+40	ZP568F	210-338	235/45, 245/40, 255/40		
		32	-	210-338	235/45, 245/40, 255/40		Orig.-Verschr.
	AC-521	32	-	210-338	235/45, 245/40, 255/40		Orig.-Verschr.
	AC-M10	40	-	210-338	235/45, 245/40, 255/40		Orig.-Verschr.
	AF18	32	-	210, 250	235/45, 245/40, 255/40		Orig.-Verschr.
	FMI07 Atena	39	-	210-338	235/45, 245/40, 255/40		Orig.-Verschr.
	FMI12 Kari	34+40	F94	210-338	235/45, 245/40, 255/40		
9 x 20	B37	37	ZP568F	210, 250	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		
	B40	34	ZP568F	210-250	255/40		
	B41	35+38	ZP568F	210-338	235/45, 245/40, 255/40, 265/35, 265/40, 275/35		
				210, 250	235/45, 245/40		
	B43	35+38	ZP568F	210-338	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		bis 245/40 M+S
				40	-	210-250	255/40, 265/40
	AC-522	40	-	210-250	255/40, 265/40		Orig.-Verschr.
	AF18	25	-	210, 250	235/45, 245/40		Orig.-Verschr.
		33	AV1	210, 250	235/45, 245/40, 255/40, 265/40		
		40	-	210, 250	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		Orig.-Verschr.
	CA 20	35	ZP568F	210, 250	235/45, 245/40		
				210-338	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		bis 245/40 M+S
	CA 23	38	ZP568F	210, 250	235/45, 245/40		nicht Bremse 400mm u. nicht Keramik
				210-338	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		bis 245/40 M+S
	FMI07 Atena	33	-	210-338	235/45, 245/40, 255/40, 265/35, 265/40		Orig.-Verschr.
	Oxigin 19	35	ZP568F	210-250	255/40		
Oxigin 28	35	ZP568F	210, 250	235/45, 245/40			
			210-338	235/45, 245/40, 255/40, 265/40, 275/35, 275/40		bis 245/40 M+S	
9,5 x 20	B37C	32	ZP568F	210, 250	245/40, 255/40		
		38	ZP568F	210-338	245/40, 255/40, 265/40, 275/35, 275/40		
	B42	35	ZP568F	210-338	245/40, 255/40, 265/40		
8,5 x 21	B41	30+34+37+40	ZP568F	210-338	255/35		
	B43	30+34+37	ZP568F	210, 250	255/35		
338				255/35M+S			
9 x 21	B32	40	ZP568F	210, 250	255/35, 275/30		
				210-338	265/35, 275/35		
				338	255/35, 275/30		
	B43	36	ZP568F	210, 250	255/35, 275/30		
				210-338	265/35, 275/35		
				338	255/35, 275/30		
	AF18	37	-	210, 250	255/35, 265/35, 275/30, 275/35		Orig.-Verschr.
CA 17	35	ZP568F	210-250	255/35			
CA 20	37	ZP568F	210, 250	255/35, 275/30			
			210-338	265/35, 275/35			
9,5 x 21	B41	31	ZP568F	210-338	255/35		
		31	ZP568F	210-338	255/35		
	B43			210, 250	255/35, 275/30		bei 275/30 ✖

Angaben sind ohne Gewähr, für den konkreten Anwendungsfall sind die jeweiligen TÜV- Gutachten maßgeblich! Die Radabdeckung und die Übereinstimmung der EU- Genehmigungsnummer mit den Fahrzeugpapieren ist in jedem Einzelfall zu prüfen!

9,5 x 21	B40	36	ZP568F	210-338	265/35, 275/35		bei 275/35 ✖
				338	255/35, 275/30		bei 275/30 ✖
	FMI10 e-Joule	41,5	F95	210-338	255/35, 265/35, 275/30, 275/35		
9 x 22	AF18	35	-	210, 250	265/30		Orig.-Verschr.
				338	265/30		
10 x 22	CA 20	38	ZP568F	210, 250	265/30		
				338	265/30		

Audi A8 Facelift i.V.	2. Quartal 2022	F8	5/112	66,6	e1*2007/46*1751*20-27
------------------------------	-----------------	----	-------	------	-----------------------

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension		Info
Audi S8 (siehe Konfigurator)	ab 2012		4H	5/112	66,6	e1*2007/46*0284*..., e1*2007/46*0398*...	

Audi S8	ab 09.2019	F8	5/112	66,6	e1*2007/46*1751*11-..
----------------	------------	----	-------	------	-----------------------

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	FMI07 Atena	29	-	420	235/55	 Orig.-Verschr.
	Oxigin 29	32	ZP568F	420	235/50	 nicht Keramikbremse
8 x 19	B40	31+38	ZP568F	420	235/50, 245/45, 255/45	nur M+S, nicht Keramikbremse
		39	-	420	235/50, 245/45, 255/45	Orig.-Verschr., nur M+S, nicht Keramikbremse
	B43	27+28+34+38	ZP568F	420	235/50, 245/45, 255/45	nur M+S, nicht Keramikbremse
	AC-521	35	-	420	235/50, 245/45, 255/45	Orig.-Verschr., nur M+S, nicht Keramikbremse
8,5 x 19	B32	34,5	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	B36	30+35	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	B37	25	ZP568F	420	235/50, 245/45, 255/45	nur M+S, nicht Keramikbremse
		32+35	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	B43	25	ZP568F	420	235/50, 245/45, 255/45	nur M+S, nicht Keramikbremse
		40	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	AC-M10	30	AV4	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
		40	-	420	235/50, 245/45, 255/45, 265/45	Orig.-Verschr., nur M+S, nicht Keramikbremse
	CA 20	40	-	420	235/50, 245/45, 255/45, 265/45	Orig.-Verschr., nur M+S, nicht Keramikbremse
	CA 23	30	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	CA 26	40	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
	Oxigin 28	30+40	ZP568F	420	235/50, 245/45, 255/45, 265/45	nur M+S, nicht Keramikbremse
8 x 20	B43	27+30	ZP568F	420	235/45, 245/40	nur M+S
		39	ZP568F	420	235/45, 245/40	nur M+S
8,5 x 20	RC29	29+33+40	ZP568F	420	235/45, 245/40, 255/40	nur M+S, nicht Keramikbremse
	B32	30+40	ZP568F	420	235/45, 245/40, 255/40	nur M+S, nicht Keramikbremse
	B42	30+35	ZP568F	420	235/45, 245/40, 255/40	nur M+S, nicht Keramikbremse
	B43	30+35+40	ZP568F	420	235/45, 245/40, 255/40	nur M+S
	AC-518	32	-	420	235/45, 245/40, 255/40	Orig.-Verschr., nur M+S, nicht Keramikbremse
	AC-521	32	-	420	235/45, 245/40, 255/40	Orig.-Verschr., nur M+S
	AC-M10	30	ZP568F	420	235/45, 245/40, 255/40	nur M+S
		40	-	420	235/45, 245/40, 255/40	Orig.-Verschr., nur M+S
9 x 20	B37	29	ZP568F	420	235/45M+S, 245/40M+S, 255/40	
		37	ZP568F	420	235/45M+S, 245/40M+S, 255/40, 265/40, 275/35, 275/40	
	B43	33	ZP568F	420	235/45M+S, 245/40M+S, 255/40, 265/40	
		35+38	ZP568F	420	235/45M+S, 245/40M+S, 255/40, 265/40, 275/35, 275/40	
	CA 20	35	ZP568F	420	235/45M+S, 245/40M+S, 255/40, 265/40, 275/35, 275/40	
	Oxigin 28	35	ZP568F	420	235/45M+S, 245/40M+S, 255/40, 265/40, 275/35, 275/40	
9,5 x 20	B37C	38	ZP568F	420	245/40M+S, 255/40, 265/40, 275/35, 275/40	
	B42	35	ZP568F	420	245/40M+S, 255/40, 265/40	nicht Keramikbremse
8,5 x 21	B43	30+34+37	ZP568F	420	255/35M+S	
9 x 21	B32	40	ZP568F	420	255/35, 265/35, 275/30, 275/35	
	B43	36	ZP568F	420	255/35, 265/35, 275/30, 275/35	
	CA 20	37	ZP568F	420	255/35, 265/35, 275/30, 275/35	
9,5 x 21	B43	36	ZP568F	420	255/35, 265/35	nicht Keramikbremse

Audi R8 (siehe Konfigurator)	ab 2007 bis 2015	42 I 42A	5/112	57,1
-------------------------------------	------------------	----------	-------	------

Audi R8 NEU (siehe Konfigurator)	ab 08/2016	42 (4S)	5/112	VA 57,1 / HA 66,6	e1*2001/116*0399*..
---	------------	---------	-------	-------------------	---------------------

Audi RS3		ab 2017		8V	5/112	57,1	e1*2007/46*0608*01-	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	49	-	270-294	235/35			Orig.-Verschr.
	FMI07 Atena	49	-	270	235/35			Orig.-Verschr.
	RC32	50	-	270-294	235/35			Orig.-Verschr.
	RC34	50	-	270-294	235/35			Orig.-Verschr.
	B43	40	-	294	235/35			Orig.-Verschr.
	RC29	45	ZP560D	270	235/35, 245/35			nicht Keramikbremse ✖
8,5 x 19	RC34	48	ZP560D	270-294	235/35			
				294	235/35, 255/30			Limousine, nicht Keramikbremse, bei 255/30 ✖
				270, 294	235/35, 255/30			Sportback,incl. FL2017,nicht Keramikbremse, ✖
8,5 x 20	RC29	45	ZP560D	294	235/30			Limousine
	B32	45	ZP560D	294	235/30			nicht Keramikbremse ✖
	B43	43	ZP560D	294	235/30			Limousine
	AC-518	45	- +R	294	235/30			Orig.-Verschr. + Red.Ringe BA25, Limousine
	AC-521	45	-	294	235/30			Orig.-Verschr.,nicht Keramikbremse,nur Limousine

Audi RS3		2021 /2022		GY	5/112	57,1	e1*2007/46*2144*..	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	VA 25 HA 46	-	294-299	VA+HA 235/35			Orig.-Verschr.
9 x 19		VA 25 HA 46	-	294-299	VA 265/30			Orig.-Verschr.
8 x 19					HA 245/35			

Audi RS4 AVANT		ab 2018		B8 (B9)		5/112		66,6		e1*2001/116*0447*11-.. (FIN: WAUZZZF4...)	
indirekt - teilweise direkt Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 19	RC32	26	-	331	235/40, 245/35, 245/40				Orig.-Verschr.		
	FMI08 Thoe	26	F85	331	235/40, 245/35, 245/40				nur M+S		
	FMI14 Jupiter	26	Kit0386	331	235/40, 245/35, 245/40				nur M+S		
	RC32	27	-	331	235/40, 245/35, 245/40				Orig.-Verschr., nur M+S		
8,5 x 19	B32	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B37 / B43	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B44	25	ZP568F	332	235/40, 245/35, 245/40, 255/35				nur M+S		
9 x 19	B41	21	ZP568F	331-346	265/35, 275/30, 275/35						
8,5 x 20	B41	20	ZP568F	331	235/35, 255/30				nur M+S		
	B43	20	ZP568F	331	235/35				nur M+S		
	B44	25	ZP568F	331	235/35				nur M+S		
	AF18	20	AV1	331	235/35				nur M+S		
9 x 20	FMI15 Zelos	26	Kit0354	331	275/30						
	B41	20	ZP568F	331	265/30						
	B43	20	ZP568F	331	265/30						
	AF18	25	-	331	265/30, 275/30				Orig.-Verschr.		
	FMI07 Atena	20	-	331	265/30				Orig.-Verschr.		
	Oxigin 19	28	ZP568F	331	265/30						
	Oxigin 28	20	ZP568F	331	265/30						
9,5 x 20	B42	25	ZP568F	331	265/30, 275/30						

Audi RS4 NEU i.V.		3. Quartal 2022						
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
Audi RS5 (siehe Konfigurator)		2012-2017		B8	5/112	66,6	e1*2001/116*0447*01-... (FIN: WAUZZZ8T..., WAUZZZ8F...)	

Audi RS5 Coupé		ab 2017		B8 (B9)		5/112		66,6		e1*2001/116*0447*10-... (FIN: WAUZZZF5...)	
indirekt - teilweise direkt Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 19	RC32	26	-	331	235/40				Orig.-Verschr.		
	FMI08 Thoe	26	F85	331	235/40, 245/35, 245/40				nur M+S		
	FMI14 Jupiter	26	Kit0386	331	235/40, 245/35, 245/40						
8,5 x 19	B32	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B37	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B41	20+21	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B43	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	B44	25	ZP568F	331	235/40, 245/35, 245/40, 255/35				nur M+S		
	CA 17	23	ZP568F	331	255/30				nur M+S		
	FMI11 Elatha	21	-	331	235/40, 245/35, 245/40, 255/35				Orig.-Verschr., nur M+S		
9 x 19	B41	21	ZP568F	331-346	235/40, 245/35, 245/40, 255/35, 265/35, 275/30, 275/35				nur M+S		
	CA 19	25	ZP568F	331	235/40, 245/35, 255/35, 265/35						

8,5 x 20	B41	20	ZP568F	331	235/35, 245/30, 245/35, 255/30		nur M+S
	B43	20	ZP568F	331	235/35, 245/30		nur M+S
	B44	25	ZP568F	331	235/35, 245/30		nur M+S
	AF18	20	AV1	331	235/35, 245/30		nur M+S
9 x 20	FMI15 Zelos	26	Kit0354	331	275/30		
	B41	20	ZP568F	331	235/35, 245/30, 245/35, 255/30, 265/30		bis 255/30 nur M+S
	B43	20	ZP568F	331	245/30M+S, 265/30		
	AF18	25	-	331	245/30M+S, 265/30, 275/30		Orig.-Verschr.
	FMI07 Atena	20	-	331	235/35, 245/30, 245/35, 255/30, 265/30		Orig.-Verschr., bis 255/30 M+S
9,5 x 20	Oxigin 28	20	ZP568F	331	245/30M+S, 265/30		
	B42	25	ZP568F	331	265/30, 275/30		
9 x 21	CA 19	25	ZP568F	331	255/30		
	FMI07 Atena	26	-	331	245/30		Orig.-Verschr.

Audi RS6 (siehe Konfigurator)	ab 2014	4G	5/112	66,6	e1*2007/46*0544*01-...
-------------------------------	---------	----	-------	------	------------------------

Audi RS6	ab 2020	F2	5/112	66,6	e1*2007/46*1840*..
----------	---------	----	-------	------	--------------------

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 21	B41	19	ZP568F	441-463	245/40M+S, 255/35, 255/40	nicht geprüft mit Audi Keramikbremsanlage
	FMI11 Elatha	19	-	441-463	245/40M+S	Orig.-Verschr., nur M+S
	B43	19	ZP568F	441, 463	245/40, 255/35	nur mit Keramikbremsanlage, nur M+S
9,5 x 21	AF18	20	-	441	245/40, 255/35, 265/35, 275/35	Orig.-Verschr., nur mit Keramikbremsanlage, nur M+S
	AF20	20	AV1	441	245/40, 255/35, 265/35, 275/35	nur mit Keramikbremsanlage, nur M+S
	FMI12 Kari	20	-	441-463	245/40, 255/35, 255/40, 265/35, 275/35, 285/35	Orig.-Verschr., nur M+S, nicht geprüft mit Audi Keramikbremsanlage
10 x 21	B41	20	-	441-463	255/35, 255/40, 265/35, 275/35, 285/35	Orig.-Verschr., nur M+S, nicht geprüft mit Audi Keramikbremsanlage
	FMI07 Atena	19	-	441-463	255/35, 255/40, 265/35, 275/35, 285/35	Orig.-Verschr., nur M+S, nicht geprüft mit Audi Keramikbremsanlage
	FMI12 Kari	19	Kit0454	441-463	255/35, 255/40, 265/35, 275/35, 285/35	nur M+S, nicht geprüft mit Audi Keramikbremsanlage
10,5 x 21	B41	19	ZP568F	441-463	265/35M+S, 275/35, 285/35, 295/30, 305/30	nicht geprüft mit Audi Keramikbremsanlage
	B43	19	ZP568F	441, 463	265/35M+S, 275/35, 285/35, 295/30	nur mit Keramikbremsanlage
	CA 20	19	ZP568F	441, 463	265/35M+S, 275/35, 285/35, 295/30	nur mit Keramikbremsanlage
10 x 22	CA 20	20	ZP568F	441	285/30, 295/30	nur mit Keramikbremsanlage, nur M+S
	FMI07 Atena	18	F95	441-463	255/35, 265/30, 275/30, 285/30	nur M+S, nicht geprüft mit Audi Keramikbremsanlage
10,5 x 22	B41	19	ZP568F	441	285/30	nicht geprüft mit Audi Keramikbremsanlage
				441-463	285/30, 295/30, 305/25	nicht geprüft mit Audi Keramikbremsanlage

Audi RS7 (siehe Konfigurator)	ab 2013	4G	5/112	66,6	e1*2007/46*0544*02-...
-------------------------------	---------	----	-------	------	------------------------

Audi RS7	ab 2018	F2	5/112	66,6	e1*2007/46*1840*..
----------	---------	----	-------	------	--------------------

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 21	FMI11 Elatha	19	-	441, 463	245/40	Orig.-Verschr., nur M+S
	B43	19	ZP568F	441, 463	245/40, 255/35	nur mit Keramikbremsanlage, nur M+S
9,5 x 21	AF18	20	-	441	245/40, 255/35, 265/35, 275/35	Orig.-Verschr., nur mit Keramikbremsanlage, nur M+S
10,5 x 21	B43	19	ZP568F	441, 463	265/35M+S, 275/35, 285/35, 295/30	nur mit Keramikbremsanlage
	CA 17	19	ZP568F	441, 463	265/35M+S, 275/35, 285/35, 295/30	nur mit Keramikbremsanlage
10 x 22	CA 20	20	ZP568F	441	285/30, 295/30	nur mit Keramikbremsanlage, nur M+S

Audi TT III (siehe Konfigurator)	ab 2015	8J (8S)	5/112	57,1	e1*2001/116*0369*17-...
----------------------------------	---------	---------	-------	------	-------------------------

Audi TT III	ab Facelift 2018	8J (8S)	5/112	57,1	e1*2001/116*0369*31-...
-------------	------------------	---------	-------	------	-------------------------

kein Sensor - indirektes System

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	AC-518	40	AV4+R	180	225/40, 225/45, 235/40	+ Red.Ringe BA25=66,6-57,1
	AF18	35	AV1	180	225/40, 225/45	
		40	AV1	180	225/40, 225/45, 235/40	
	AF20	35	AV1	180	225/40, 225/45	
8 x 19	B40	40	-	180	225/35, 225/40, 235/35	Orig.-Verschr.
	B43	40	-	180	225/35, 225/40, 235/35	Orig.-Verschr.
	B40	38	ZP560D	180	225/35, 225/40	
	AC-518	38	AV4+R	180	225/35, 225/40	+ Red.Ringe BA25=66,6-57,1
8,5 x 19	B32	42	-	180	225/35, 225/40, 235/35	Orig.-Verschr.
	B32	45	ZP560D	180	225/35, 225/40, 235/35, 245/35	
8 x 20	AC-518	45	- +R	180	235/30, 245/30	Orig.-Verschr. + Ringe BA25=66,6-57,1

9 x 20	AC-521	45	-	180	235/30, 245/30		Orig.-Verschr.
	B40	52	-	180	245/30, 255/30		Orig.-Verschr.
	B40	49	ZP560D	180	245/30		
Audi TTS Cabrio / Coupé (siehe Konfigurator)			ab 2015	8J (8S)	5/112	57,1	e1*2001/116*0369*17-...
Audi TT RS (III) (siehe Konfigurator)			2009 - 2014		5/112	57,1	e1*2007/46*1686*..., e1*K507/46*0054*..
Audi Q2			ab 2017	GA	5/112	57,1	e1*2007/46*1552*...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC27	43	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC30	43	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC34	43	-	81-140	205/60, 205/65, 215/55, 215/60, 225/55, 225/60		Orig.-Verschr.
6,5 x 16	RC24	43	-	85, 110	205/60M+S, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC27	43	-	85, 110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC32	43	-	81-140	205/60, 205/65, 215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr., ohne Radhausverbr. ab 235/50 ✖
	RC34	43	-	81-140	205/60, 205/65, 215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr., ohne Radhausverbr. ab 235/50 ✖
	RC27	44	-	85, 110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
		46	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC30	41+42+44	-	85, 110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr., ET41 ohne Verbr. ab 225/55 ✖
		46	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC32	41	-	85-140	205/60, 205/65, 215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr., ohne Radhausverbr. ab 235/50 ✖
	CA 20	45	ZP560D	81-110	205/60, 215/55, 215/60, 225/55, 225/60		
6,5 x 17	RC27	39	-	85, 110	205/55, 205/60, 215/55		Orig.-Verschr.
		43	-	85, 110	205/55, 205/60, 215/55, 225/50, 225/55		Orig.-Verschr.
	RC34	43	-	81-140	205/50, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
7 x 17	RC27	45	- (V7)	81-110	205/55, 205/60, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., Ausführung "V7", ohne Radhausverbr. ab 235/50 ✖
	RC30	45	-	81-110	205/55, 205/60, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., Frontantrieb, ohne Radhausverbr. ab 235/50 ✖
	RC32	45	-	85-140	205/50, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., ohne Radhausverbr. bei 235/50 ✖
	RC34	45	-	81-140	215/55		Orig.-Verschr.
	CA 26	45	-	81-110	215/55		Orig.-Verschr.
	RC32	38	-	85-140	205/50, 205/55		Orig.-Verschr.
		40	-	85-140	205/50, 205/55, 215/50, 215/55		Orig.-Verschr.
	B39	40	-	81-140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50		Orig.-Verschr., ohne Radhausverbr. ab 215/55 ✖
RC27	45	ZP568F (V10)	81-110	205/55, 205/60, 215/55, 225/50, 225/55		Ausführung "V10"	
7,5 x 17	RC24	42	-	85, 110	205/55, 205/60, 215/55, 225/50, 225/55, 235/50, 245/45		Orig.-Verschr., ohne Radhausverbr. ab 215/55 ✖
	RC27	40	-	85-140	205/50, 205/55, 215/50, 215/55, 225/50, 225/55, 235/45, 235/50, 245/45		Orig.-Verschr., ohne Radhausverbr. ab 215/50 ✖
	RC32	43	-	81-140	205/50, 205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr., ohne Radhausverbr. bei 225/50 u. ab 235/50 ✖
	RC34	40	ZP560D	81-140	205/50, 205/55, 215/50, 215/55, 225/50, 235/45, 235/50, 245/45		ohne Radhausverbr. ab 215/50 u. mit Verbr. bei 225/50 u. ab 235/50 ✖
		45	ZP560D	81-140	205/50, 205/55, 215/50, 215/55, 225/50, 235/45, 235/50, 245/45		ohne Radhausverbr. bei 225/50 u. ab 235/50 ✖
	B36	45	ZP560D	81-110	205/55, 205/60, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		ohne Radhausverbr. ab 225/50 u. mit Verbr. ab 245/50 ✖
	AC-518	42	AV4+R	85, 110	205/55, 205/60, 215/55, 225/50, 225/55, 235/50, 245/45		+ Red.Ringe BA25=66,6-57,1, ohne Radhausverbr. ab 215/55 ✖
	Oxigin 25	45	ZP560D	81-140	205/50, 205/55, 215/50, 215/55, 235/45		
7 x 18	RC27	45	-	81-110	205/45, 205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC32	45	-	85-140	205/45, 215/45, 215/50, 225/45		Orig.-Verschr.
	RC34	45	-	81-140	215/50		Orig.-Verschr.
7,5 x 18	RC32	45	-	85-140	205/45, 215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr., ohne Radhausverbr. bei 245/45 ✖
	RC30	45	ZP560D	81-110	215/50, 225/45, 235/45		
	B32	45	ZP560D	85, 110	215/50, 225/45, 235/45		
	B39	45	ZP560D	85, 110	215/50, 225/45, 235/45		
	Oxigin 18	45	-	85-140	205/45, 205/55, 215/45, 215/50, 225/40, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., ET45 ohne Radhausverbr. ab 225/50 ✖
	RC27	44	-	85-140	215/45, 225/40, 225/45, 225/50, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr., ohne Radhausverbr. ab 225/50 ✖
	RC29	44	-	85, 110	215/50, 225/45, 235/45		Orig.-Verschr., ohne Radhausverbr. nur 225/45 auflagenfrei!

Angaben sind ohne Gewähr, für den konkreten Anwendungsfall sind die jeweiligen TÜV- Gutachten maßgeblich! Die Radabdeckung und die Übereinstimmung der EU- Genehmigungsnummer mit den Fahrzeugpapieren ist in jedem Einzelfall zu prüfen!

8 x 18	RC32	40	-	85-140	205/45, 215/45		Orig.-Verschr.
		44	-	85-140	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., ohne Radhausver. ab 235/40 ✖
	RC34	40+45	-	81-140	205/45, 215/45, 215/50, 225/45, 235/40, 235/45		Orig.-Verschr., ET40 ohne Verbr. ab 215/50 ✖
	B38	44	-	85, 110	215/50, 225/45, 235/45, 245/40HA		Orig.-Verschr., ohne Radhausver. ab 235/35 ✖
	B37	45	ZP560D	85, 110	215/50, 225/45, 235/45, 245/45		ohne Radhausverbr. nur 225/45 auflagenfrei
	B42	45	ZP560D	81-110	215/50, 225/45, 235/45, 245/40HA		ohne Radhausverbr. nur 225/45 auflagenfrei
	CA 20	45	ZP560D	81-110	215/50, 225/45, 235/45, 245/40HA		ohne Radhausverbr. nur 225/45 auflagenfrei, ✖
	FMI11 Elatha	39	- +R	81-140	205/45, 215/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
45		- +R	81-140	205/45, 215/45, 215/50, 225/45, 235/40, 235/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
7,5 x 19	B32	43	-	85, 110	225/40		Orig.-Verschr., nur Frontantrieb
	B39	33+43	ZP560D	85, 110	225/40		ET33 ohne Radhausverbr. ✖
	Oxigin 18	37	-	85-140	225/40		Orig.-Verschr., ohne Radhausverbr. ✖
8 x 19	RC27	45	-	81-140	235/40		Orig.-Verschr., mit Radhausverbreiterungen
	RC32	45	-	81-140	235/40		Orig.-Verschr.
	RC34	45	-	81-140	225/35, 225/40, 235/35, 235/40		Orig.-Verschr.
	B40	45	-	81-110	225/40, 235/35, 235/40, 245/35HA		Orig.-Verschr., ohne Radhausver. ab 235/35 ✖
	B43	45	-	81-110	225/40, 235/40		Orig.-Verschr., mit Radhausverbreiterungen
	RC27	44	-	85-140	225/40, 235/35, 235/40, 245/35, 245/40		Orig.-Verschr., ohne Radhausver. ab 235/35 ✖
	B38	44	-	85, 110	225/40, 235/35, 235/40, 245/35, 245/40		Orig.-Verschr., ohne Radhausver. ab 235/35 ✖
	RC29	45	ZP560D	85, 110	225/40, 235/35, 235/40, 245/35		ohne Radhausver. ab 235/35 ✖
	RC34	43	ZP560D	85-140	225/35, 225/40, 235/35, 235/40, 245/35		ohne Radhausverbr., ab 235/35 ✖
	B24 / B38	45	ZP560D	85, 110	225/40, 235/35, 235/40, 245/35HA, 245/40		ohne Radhausverbr., ab 235/35 ✖
	AC-521	45	-	81-110	225/40, 235/35, 235/40, 245/35HA		Orig.-Verschr., ohne Radhausver. ab 235/35 ✖
	CA 17	43	ZP560D	85-140	225/40		
		45	ZP560D	85-140	225/40		

weitere Dimensionen/Designs siehe Konfigurator

Audi Q2 Quattro			ab 2017		GA		5/112		57,1		e1*2007/46*1552*01-..	
kein Sensor - indirektes RDKS												
Dimension	Design	ET	KIT	KW	Reifendimension				Info			
6 x 16	RC27	43	-	110, 140	205/60, 205/65, 215/60, 225/55, 225/60					Orig.-Verschr.		
	RC30	43	-	110, 140	205/60, 225/55					Orig.-Verschr.		
6,5 x 16	RC27	43	-	110, 140	205/60, 205/65, 215/60, 225/55, 225/60					Orig.-Verschr.		
	RC24	43	-	110, 140	205/60, 205/65, 215/60, 225/55, 225/60					Orig.-Verschr.		
	RC27	44+46	-	110, 140	205/60, 205/65, 215/60, 225/55, 225/60					Orig.-Verschr.		
	RC30	39+41+42+44	-	110, 140	205/60, 205/65, 215/60, 225/55, 225/60					Orig.-Verschr., ET39+41 ohne Radhausverbr. ab 225/55		
	CA 20	45	ZP560D	110, 140	205/60, 205/65, 215/60, 225/55, 225/60							
6,5 x 17	RC27	39	-	110, 140	205/55, 205/60, 215/55					Orig.-Verschr.		
		43	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55					Orig.-Verschr.		
7 x 17	RC27	45	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55					Orig.-Verschr.		
	RC30	45	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55					Orig.-Verschr.		
	CA 26	45	-	110, 140	215/55					Orig.-Verschr.		
	RC27	40	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50					Orig.-Verschr., ohne Radhausverbr. ab 215/55		
		42+43	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50					Orig.-Verschr., ohne Radhausverbr. ab 225/50		
	B39	40	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50					Orig.-Verschr., ohne Radhausverbr. ab 215/55		
	RC27	45	ZP568F (V10)	110, 140	205/55, 205/60, 215/55, 225/50, 225/55					Ausführung "V10"		
7,5 x 17	RC24	42	-	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50					Orig.-Verschr., ohne Radhausverbr. ab 215/55		
	RC28	45	ZP560D	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 245/45					ohne Radhausverbr. ab 225/50		
	B36	45	ZP560D	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 235/50					ohne Radhausverbr. ab 225/50		
	AC-518	42	AV4+R	110, 140	205/55, 205/60, 215/55, 225/50, 225/55, 245/45					+ Red.Ringe BA25=66,6-57,1, ohne Radhausverbr. ab 215/55		
	Oxigin 25	45	ZP560D	81-140	205/50, 205/55, 215/50, 215/55, 235/45							
7 x 18	RC27	45	-	110, 140	215/50					Orig.-Verschr.		
7,5 x 18	B32 / B39	45	ZP560D	110, 140	215/50, 225/45, 235/45, 245/45					ohne Radhausverbr. bei 245/45		
8 x 18	RC29	44	-	110, 140	215/50, 225/45, 235/45					Orig.-Verschr., ohne Radhausverbr. nur 225/45 auflagenfrei!		
	B38	44	-	110, 140	215/50, 225/45, 235/45					Orig.-Verschr., ohne Radhausverbr. nur 225/45 auflagenfrei!		
	B37 / B42	45	ZP560D	110, 140	215/50, 225/45, 235/45					ohne Radhausverbr. bei 215/50 u. 235/45		
	CA 20	45	ZP560D	110, 140	215/50, 225/45, 235/45					ohne Radhausverbr. nur 225/45 auflagenfrei		
7,5 x 19	B32	43	-	110, 140	225/40					Orig.-Verschr.		
	B39	43	ZP560D	110, 140	225/40							
8 x 19	RC32	45	-	85-140	235/40					Orig.-Verschr.		
	B40	45	-	110, 140	225/40, 235/35, 235/40					Orig.-Verschr., ohne Radhausverbr. ab 235/35		
	B43	45	-	110, 140	225/40, 235/35, 235/40					Orig.-Verschr., ohne Radhausverbr. ab 235/35		
	RC29	45	ZP560D	110, 140	225/40, 235/35, 235/40					ohne Radhausverbr. ab 235/35		
	B38	45	ZP560D	110, 140	225/40, 235/35, 235/40					ohne Radhausverbr. ab 235/35		
	CA 17	45	ZP560D	85-140	225/40							
	AC-521	45	-	110, 140	225/40, 235/35, 235/40					Orig.-Verschr., ohne Radhausverbr. ab 235/35		

weitere Dimensionen/Designs siehe Konfigurator

Audi SQ2 Quattro		ab 2019		GA	5/112	57,1	e1*2007/46*1552*09-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	39	-	221	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, mit Verbreiterungen
		43	-	221	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, mit Verbreiterungen
	RC34	43	-	221	215/50, 215/55, 225/50, 235/50			Orig.-Verschr., nur M+S
7 x 17	RC27	38+45	-	221	215/55, 225/50, 225/55			Orig.-Verschr., nur M+S, mit Verbreiterungen
		40+42+43	-	221	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, mit Verbreiterungen
	RC30	38+45	-	221	215/55, 225/50, 225/55			Orig.-Verschr., nur M+S, mit Verbreiterungen
		40	-	221	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, mit Verbreiterungen
	RC32	40	-	221	215/50, 215/55, 225/50			Orig.-Verschr., nur M+S
		45	-	221	215/50, 215/55, 225/50, 235/50			Orig.-Verschr., nur M+S
	B39	40	-	221	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, mit Verbreiterungen
	RC27	45	ZP568F (V10)	221	215/55, 225/50, 225/55			Ausführung "V10"
7,5 x 17	RC24	42	-	221	215/55, 225/50, 225/55, 245/45			Orig.-Verschr., nur M+S, mit Verbreiterungen
	RC27	40	-	221	215/55M+S, 225/50, 225/55			Orig.-Verschr.
	RC32	43	-	221	215/50, 215/55, 225/50, 245/45			Orig.-Verschr., nur M+S
	RC24	42	ZP560D	221	215/55, 225/50, 225/55, 245/45			nur M+S, mit Verbreiterungen
	RC28	45	ZP560D	221	215/55, 225/50, 225/55, 245/45			nur M+S, mit Verbreiterungen
	RC34	40	ZP560D	221	215/50, 215/55			nur M+S
		45	ZP560D	221	215/50, 215/55, 225/50, 235/50, 245/45			nur M+S
	AC-518	42	AV4+R	221	215/55, 225/50, 225/55, 245/45			+ Red.Ringe BA25=66,6-57,1, nur M+S, mit Verbreiterungen
7 x 18	RC27	43+45	-	221	215/50, 225/45, 225/50			
	RC32	40+43+45	-	221	215/45, 215/50, 225/45			Orig.-Verschr., nur M+S
7,5 x 18	RC32	45	-	221	215/45, 215/50, 225/45, 235/45, 245/45			Orig.-Verschr., nur M+S
	RC34	35	-	221	215/45, 225/45			Orig.-Verschr., nur M+S
	B32	35	ZP560D	221	215/50, 225/45, 235/45			nur M+S, mit Verbreiterungen
		45		221	215/50, 225/45, 235/45, 245/45			nur M+S, mit Verbreiterungen
	B39	45	ZP560D	221	215/50, 225/45, 235/45, 245/45			nur M+S, mit Verbreiterungen
	AC-MB6	45	- +R	221	215/50, 225/45, 235/45, 245/45			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, mit Verbreiterungen
8 x 18	RC34	45	-	221	215/45M+S, 215/50M+S, 225/45M+S, 235/40, 235/45, 245/40, 245/45			Orig.-Verschr.
	RC32	40	-	221	215/45M+S, 225/45M+S, 235/40, 235/45			Orig.-Verschr.
		44	-	221	215/45M+S, 225/45M+S, 235/40, 235/45, 245/40, 245/45			Orig.-Verschr.
	RC34	40	-	221	215/45M+S, 215/50M+S, 225/45M+S, 235/40, 235/45			Orig.-Verschr.
	B37	44	-	221	215/50M+S, 225/45M+S, 235/45			Orig.-Verschr., mit Verbreiterungen
	B38	44	-	221	215/50M+S, 225/45M+S, 235/45			Orig.-Verschr., mit Verbreiterungen
	B36 / B38	45	ZP560D	221	215/50M+S, 225/45M+S, 235/45			mit Verbreiterungen
	B37 / B42	45	ZP560D	221	215/50M+S, 225/45M+S, 235/45			mit Verbreiterungen
	AC-M10	40	AV1	221	215/50M+S, 225/45M+S, 235/45			mit Verbreiterungen
		45	ZP560D	221	215/50M+S, 225/45M+S, 235/45			mit Verbreiterungen
	AC-518	40	AV4+R	221	215/50M+S, 225/45M+S, 235/45			+ Red.Ringe BA25=66,6-57,1, mit Verbreiter.
	AC-521	45	- +R	221	215/50M+S, 225/45M+S, 235/45			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	221	215/50M+S, 225/45M+S, 235/45			
	AF20	35	AV1	221	225/45M+S			mit Verbreiterungen
	CA 20	45	ZP560D	221	215/50M+S, 225/45M+S, 235/45			mit Verbreiterungen
	FMI11 Elatha	39	- +R	221	215/45M+S, 225/45M+S			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	- +R	221	215/45M+S, 215/50M+S, 225/45M+S, 235/40, 235/45, 245/40, 245/45			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		FMI12 Kari	45	Kit 0353	221	215/45M+S, 215/50M+S, 225/45M+S, 235/40, 235/45, 245/40, 245/45		
8 x 19	RC27	45	-	221	235/40			Orig.-Verschr., mit Verbreiterungen
	RC32	45	-	221	235/40			Orig.-Verschr.
	RC34	45	-	221	225/40M+S, 235/35, 235/40, 245/35			Orig.-Verschr.
	B40	45	-	221	225/40M+S, 235/35, 235/40			Orig.-Verschr., mit Verbreiterungen
	B43	45	-	221	225/40M+S, 235/35, 235/40			Orig.-Verschr., mit Verbreiterungen
	RC27	44	-	221	235/40			Orig.-Verschr.
	RC29	45	ZP560D	221	225/40M+S, 235/35, 235/40			mit Verbreiterungen
	RC32	44	-	221	225/40M+S, 235/35, 235/40, 245/35			Orig.-Verschr.
	B24	45	ZP560D	221	225/40M+S, 235/35, 235/40			mit Verbreiterungen
	AC-521	45	-	221	225/40M+S, 235/35, 235/40			Orig.-Verschr., mit Verbreiterungen
	CA 17	45	ZP560D	221	235/40			
	FMI07 Atena	39	- +R	221	225/40M+S			Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
	Oxigin 29	43	ZP560D	221	225/40M+S, 235/35, 235/40			mit Verbreiterungen
B37	43	ZP560D	221	225/40M+S, 235/35, 235/40			mit Verbreiterungen	

8,5 x 19	B41	39	ZP560D	221	225/40M+S		
	B42 / B44	42	ZP560D	221	225/40M+S, 235/35, 235/40		mit Verbreiterungen
	AF18	40	AV1	221	225/40M+S, 235/35, 235/40		mit Verbreiterungen
	AF20	40	- +R	221	225/40M+S, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 23	40	- +R	221	225/40M+S, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI07 Atena	45	- +R	221	225/40M+S, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	8300 - 1972	45	F85+R	221	225/40M+S, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1
	Oxigin 20	45	ZP560D	221	225/40		
	Oxigin 25	45	ZP560D	221	225/40		
9 x 19	Oxigin 28	40	ZP560D	221	225/40M+S, 235/35, 235/40		mit Verbreiterungen
	CA 19	44	ZP560D	221	225/40		
8 x 20	B40	41	-	221	235/35		Orig.-Verschr., mit Verbreiterungen
	B43	45	-	221	235/35		Orig.-Verschr., mit Verbreiterungen
8,5 x 20	B32	41	-	221	235/35		Orig.-Verschr., mit Verbreiterungen
	RC29	40	ZP560D	221	235/35		mit Verbreiterungen
	RC34	43	ZP560D	221	225/35M+S, 235/30, 235/35		
	B24	42	ZP560D	221	235/35		mit Verbreiterungen
	B42	40	ZP560D	221	235/35		mit Verbreiterungen
	FMI07 Atena	39	- +R	221	225/35M+S		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1

Audi Q3 (siehe Konfigurator)	ab 09.11	8U/ 8U1	5/112	57,1	e1*2007/46*0591*..., e13*2007/46*1163*...
-------------------------------------	----------	---------	-------	------	---

Audi Q3, Sportback		2018	F3	5/112	57,1	e1*2007/46*1900*... (FIN: WAUZZZF39...)	
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC34	38	- (V9)	110-180	215/65		Orig.-Verschr.
7 x 17	RC27	40	- (V9)	110-169	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
	RC30	40	- (V9)	110-169	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
	RC27	45	ZP568F (V10)	110-180	215/65, 225/60, 225/65, 235/60		Ausführung "V10"
	B39	35	ZP562D	110-169	215/65, 225/60, 225/65, 235/60		
	CA 26	42	ZP562D	110-180	215/65, 225/60, 225/65, 235/60		
7,5 x 17		45	-	110-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC24	42	ZP562D	110-169	215/65, 225/60, 225/65, 235/60		
	RC28	45	ZP562D	110-180	215/65, 225/60, 225/65		
	RC29	35	ZP562D	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne Radhausverbr. ab 235/60 ✖
		45	ZP562D	110-180	215/65, 225/60, 225/65		ET45 nicht Bremse 340mm
	RC34	36	ZP560D	110-169	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		ohne Radhausverbr. ab 235/60 ✖
		40	ZP560D	110-169	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne Radhausverbr. ab 245/55 ✖
	B24	35	ZP562D	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne Radhausverbr. ab 235/60 ✖
	B36	35	ZP562D	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne Radhausverbr. ab 235/60 ✖
		45	ZP562D	110-180	215/65, 225/60, 225/65		nicht Bremse 340mm
	AC-518	42	AV4+R	110-169	215/65, 225/60, 225/65, 235/60		+ Red Ringe BA25=66,6-57,1
Oxigin 25	45	ZP560D	110-180	215/65, 225/60, 225/65, 235/60, 245/55		incl. Hybrid	
7 x 18	RC27	43	- (V9)	110-180	225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
	RC32	43	- (V9)	110-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., auch Hybrid
	RC34	43	- (V9)	110-180	235/55		Orig.-Verschr.
7,5 x 18	RC30	35	ZP562D	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 255/50		ohne Radhausverbr. ab 235/50 ✖
		45	ZP562D	110-180	215/55, 215/60, 225/55, 225/60		
	B32	35+45	ZP562D	110-169	215/55, 215/60, 225/55, 225/60		
	B39	35	ZP562D	110-169	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 255/50		ohne Radhausverbr. ab 235/50 ✖
		45	ZP562D	110-180	215/55, 215/60, 225/55, 225/60		
	AC-MB6	45	AV1	110-180	215/55, 215/60, 225/55, 225/60		
	AC-M10	45	AV1	110-180	215/55, 215/60, 225/55, 225/60		
	Oxigin 25	44	ZP560D	110-180	225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		
8 x 18	RC34	43	ZP560D	110-180	215/55, 225/55, 235/50, 235/55		auch Hybrid
	AC-518	40	AV4+R	110-169	225/55, 225/60, 235/50, 235/55		+ Red Ringe BA25=66,6-57,1
	AF18	40	AV1	110-169	225/55, 225/60, 235/50, 235/55		
	CA 17	45	ZP562D	110-180	225/55, 225/60, 235/50, 235/55, 245/50, 245/55		incl. Hybrid
	AC-M10	40	AV1	110-180	225/55, 225/60, 235/50, 235/55		
	AC-MB6	39	AV1	110-180	225/55, 225/60, 235/50, 235/55		ohne Radhausverbr. ab 235/50 ✖
	FMI11 Elatha	39	F95	110-180	215/55, 225/55, 235/50, 235/55, 245/50, 255/50		mit Serienverbreiterungen
		45	F95	110-180	215/55, 225/55, 235/50, 235/55, 245/50		
FMI12 Kari	45	- +R	110-180	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr. + Red Ringe BA25=66,6-57,1	
7 x 19	RC27	43	- (V9)	110-180	225/50, 235/50		Orig.-Verschr.

7,5 x 19	RC34	43	- (V9)	110-180	235/50		Orig.-Verschr., auch Hybrid
	RC34	38	- (V9)	110-180	235/45, 235/50, 245/45		Orig.-Verschr.
	CA 26	40	ZP562D	110-180	225/50, 235/45, 235/50, 245/45		
	Oxigin 18	50	ZP560D	110-169	235/45, 235/50, 245/45		
8 x 19	RC29	35	ZP562D	110-169	235/45		
	RC34	38	ZP560D	110-169	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
		43	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		
	B40	38	ZP562D	110-169	225/50, 235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
		43	ZP562D	110-169	225/50, 235/45, 245/45		
	CA 17	43	ZP560D	110-169	235/45, 235/50, 245/45, 245/50, 255/45		
		45	ZP560D	110-180	235/45, 235/50, 245/45, 245/50, 255/45		
	CA 19	47	ZP560D	110-180	235/45, 235/50, 245/45, 245/45		incl. Hybrid
	AC-518	38	AV4+R	110-169	235/45, 245/45		+ Red Ringe BA25=66,6-57,1
	AC-521	35	AV1	110-180	225/50, 235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. nur 235/45 auflagenfrei
	FMI07 Atena	39	F95	110-169	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
Oxigin 29	39	ZP562D	110-180	225/50, 235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖	
	43	ZP562D	110-180	225/50, 235/45, 245/45			
8,5 x 19	RC32	38	- (V9)	110-180	255/45		Orig.-Verschr.
	B43	38	ZP569F	110-180	255/45		auch Hybrid, mit Radhausverbreiterungen
				110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
	CA 26	38	ZP569F	110-180	255/45		mit Radhausverbreiterungen
	B36	35	ZP562D	110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
	B37	35	ZP562D	110-169	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
	B41	36+39	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
	B42	35	ZP562D	110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
	AC-M10	40	AV1	110-180	235/45, 245/45		
	AF18 / AF20	40	AV1	110-169	235/45, 245/45		
	CA 23	40	OX556F+R	110-180	235/45, 245/45		+ Red Ringe BA25=66,6-57,1
	FMI07 Atena	45	F95	110-169	235/45, 245/45		
	FMI11 Elatha	32	F95	110-180	235/45, 245/45, 255/45		mit Radhausverbreiterungen
	8300 - 1972	45	F85+R	110-180	235/45, 245/45		+ Red Ringe BA25=66,6-57,1
	Oxigin 20	45	ZP560D	110-169	235/45, 235/50, 245/45, 255/45		
	Oxigin 25	45	ZP560D	110-169	235/45, 235/50, 245/45, 255/45		
	Oxigin 28	40	ZP562D	110-180	235/45, 245/45		
9 x 19	CA 17	45	ZP560D	110-180	235/45, 245/45		
		49	ZP560D	110-169	235/45		
	CA 19	43	ZP560D	110-180	235/45, 245/45		
44		ZP560D	110-180	235/45, 245/45, 255/45			
8 x 20	B38	35	ZP562D	110-169	235/40, 235/45, 245/40		ohne Radhausverbr. bei 245/40 ✖
	B43	39	ZP560D	110-180	235/40, 235/45, 245/40		
8,5 x 20	RC34	38	ZP568F	110-169	255/40		
			ZP568F	110-169	235/40, 235/45, 245/40, 255/40		ohne Radhausverbr. ab 245/40 ✖
	RC29	40	ZP562D	110-180	235/40, 235/45, 245/40		
		45	ZP562D	110-180	235/40, 235/45		
	RC34	43	ZP560D	110-169	235/40, 235/45, 245/40		
	B32	30+40	ZP562D	110-169	235/40, 235/45, 245/40		ET30 ohne Radhausverbr. ✖
		45	ZP562D	110-169	235/40, 235/45		
	B41	35	ZP562D	110-169	235/40, 235/45, 245/40, 255/40		ohne Radhausverbr. ✖
	B42	40	ZP562D	110-180	235/40, 235/45, 245/40		
		45	ZP562D	110-180	235/40, 235/45		
	B43	40	ZP560D	110-180	235/40, 235/45, 245/40		
		35+43	ZP560D	110-180	235/40, 235/45		
	B44	35	ZP562D	110-180	235/40, 235/45, 245/40, 255/40		ohne Radhausverbr. ab 245/40 ✖
		40	ZP562D	110-180	235/40, 235/45, 245/40		
	AC-518	45	AV1	110-169	235/40, 235/45		
	AC-521	45	AV1	110-180	235/40, 235/45		
	AC-M10	40	AV1	110-180	235/40, 235/45, 245/40		
	AF18	45	AV1	110-169	235/40, 235/45		
	CA 17	35	ZP560D	110-169	235/45		
		40+48	ZP560D	110-169	235/45, 245/40, 245/45		
	CA 19	45	ZP560D	110-180	235/45, 245/40, 245/45, 255/40		
	FMI07 Atena	39	- +R	110-169	235/40, 235/45, 245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25, ohne Radhausverbr. ab 245/40 ✖
	FMI12 Kari	34	F94	110-180	235/40, 235/45, 245/40, 255/40		
		40	F94	110-180	235/40, 235/45, 245/40, 255/40		
9 x 20	B37	37	ZP562D	110-180	235/40, 235/45		
	B41	38	ZP560D	110-169	235/40, 235/45, 245/40, 255/40, 265/35		ohne Radhausverbr. ✖
	AC-521	42	AV1	110-180	235/40, 235/45		
	CA 20	45	ZP560D	110-180	235/45, 245/40, 245/45		
	CA 23	38	ZP562D	110-180	235/40, 235/45		
	Oxigin 25	45	ZP560D	110-169	235/45, 245/40, 245/45		
Oxigin 26	45	ZP560D	110-180	235/45, 245/40, 245/45			

	Oxigin 28	35	ZP562D	110-180	235/40, 235/45, 245/40, 255/40		ohne Radhausverbr. 
9,5 x 20	CA 19	43	ZP560D	110-180	245/40		
8,5 x 21	B41	34	ZP560D	110-180	245/35		mit Radhausverbreiterungen
		37	ZP560D	110-180	245/35, 255/35		ohne Radhausverbr. 
		40	ZP560D	110-180	245/35		
		38	ZP568F	110-180	245/35, 255/35		ohne Radhausverbr. 
9 x 21	B32	30	ZP562D	110-169	245/35		mit Radhausverbreiterungen
	CA 17	45	ZP561F+R	110-180	245/40		+ Red.Ringe BA25=66,6-57,1, incl. Hybrid
Audi RS Q3 (siehe Konfigurator) 2013 - 2018 8U/ 8U1 5/112 57,1 e1*2007/46*0590*01-...							

Audi RS Q3 / Sportback (II)							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 19	RC34	38	-	294	225/50, 235/50, 245/45		Orig.-Verschr.
8 x 19	RC29	35	ZP562D	294	225/50, 235/45, 235/50, 245/45, 255/45		nur M+S, nicht Keramikbremse
	RC34	38	ZP560D	294	225/50, 235/50, 245/45		nur M+S, nicht Keramikbremse
	B24 / B38	35	ZP562D	294	225/50, 235/45, 235/50, 245/45, 255/45		nur M+S, nicht Keramikbremse
	AC-521	35	AV1	294	225/50, 235/45, 235/50, 245/45, 255/45		nur M+S, nicht Bremse 380mm
	FMI08 Thoe	26	ZP560D	294	225/50, 245/45		nur M+S, nicht Keramikbremse mit 380x38mm
	Oxigin 29	32	ZP562D	294	225/50, 235/45, 235/50, 245/45, 255/45		nur M+S
8,5 x 19	B32	34,5	ZP562D	294	235/45, 235/50, 245/45, 255/45		nur M+S, nicht Keramikbremse
	B37	32+35	ZP562D	294	235/45, 235/50, 245/45, 255/45		nur M+S, nicht Keramikbremse
	B41	36	ZP560D	294	235/50, 245/45		nur M+S, nicht 6-Kolben Festsattel mit 375x36mm
	B42	30	ZP562D	294	235/45, 245/45		nur M+S, nicht Keramikbremse
	B44	35	ZP562D	294	235/45, 235/50, 245/45, 255/45		nur M+S, nicht Bremse 380mm
	AC-M10	30	AV4	294	235/45, 245/45		nur M+S
	AF20	30	AV1	294	235/45, 245/45		nur M+S, nicht Keramikbremse
	FMI07 Atena	28	AV1	294	245/45		nur M+S, nicht Bremse 380x38mm
	FMI11 Elatha	32	F95	294	245/45		nur M+S, nicht Bremse 380x38mm
	8300 - 1972	32	F85+R	294	235/50, 245/45		nur M+S, nicht Keramikbremse mit 380x38mm
	Oxigin 28	30	ZP562D	294	235/45, 245/45		nur M+S, nicht Bremse 380mm
	CA 24	35	ZP562D	294	235/45, 245/45		nur M+S, nicht Keramikbremse
8 x 20	B43	30	ZP560D	294	235/40, 245/40		nur M+S
8,5 x 20	RC34	38	ZP568F	294	235/40M+S, 245/40M+S, 255/40		nicht Keramikbremse mit 380x38mm
	RC29	33	ZP562D	294	235/45M+S, 245/40M+S, 255/40		nicht Keramikbremse
	RC34	33	ZP560D	294	235/40M+S, 245/40M+S, 255/40		nicht Bremse 380x38mm
	B24	33	ZP562D	294	235/45M+S, 245/40M+S, 255/40		nicht Keramikbremse
	B32	30	ZP562D	294	235/45, 245/40		nur M+S, nicht Keramikbremse
	B41	35	ZP560D	294	235/40M+S, 245/40M+S, 255/40		nicht 1-Kolben Faustsattel mit 320x30mm
	B43	35	ZP560D	294	235/40M+S, 245/40M+S, 255/40		nicht Bremse 380mm
	B44	30	ZP562D	294	235/45, 245/40		nur M+S, nicht Bremse 380mm
	AC-521	32	AV1	294	235/45M+S, 245/40M+S, 255/40		
	AC-M10	30	ZP560D	294	235/45, 245/40		nur M+S
	FMI12 Kari	34	F94	294	235/40M+S, 245/40M+S, 255/40		nicht Bremse 380x38mm
9 x 20	B37	29	ZP562D	294	235/45M+S		
	B40	34	ZP562D	294	235/45M+S, 245/40M+S, 255/40		nicht Keramikbremse
	B41	38	ZP560D	294	255/40, 265/35		
	CA 20	35	ZP560D	294	235/45M+S, 245/40M+S, 255/40		nicht Bremse 380mm
	FMI11 Elatha	34	F95	294	255/40		nicht Keramikbremse mit 380x38mm
	Oxigin 28	35	ZP562D	294	235/45M+S, 245/40M+S, 255/40		nicht Bremse 380mm
8,5 x 21	B41	34+37	ZP560D	294	255/35		nicht Keramikbremse mit 380x38mm
	B43	38	ZP568F	294	245/35M+S, 255/35		
9 x 21	B32	30	ZP562D	294	245/35M+S		nicht Keramikbremse
9 x 22	AF18	35	AV1	294	255/30		nicht Keramikbremse
Audi Q4 e-tron ab 3.Quartal 2021 FZ 5/112 57,1 e1*2018/858*00006*..							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 19	RC27	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr., mit Trommelbremse an HA
	RC32	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr., auch Sportback
				70-89	VA+HA 255/50 od. VA 235/55+HA 255/50		
	RC34	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr., auch Sportback
	B40	45	-	70, 77	VA 235/55 u. HA 255/50		Orig.-Verschr., mit Trommelbremse an HA
		45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr., mit Trommelbremse an HA
		45	-	70	VA 235/55 u. HA 255/50		Orig.-Verschr., mit Trommelbremse an HA, nur Bremse 358mm VA
	RC29	45	ZP560D	70, 77	VA 235/55 u. HA 255/50		mit Trommelbremse an HA

	RC32	44	-	70-89	VA+HA 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr., auch Sportback
	B43	40	-	70, 77	VA 235/55 u. HA 255/50		Orig.-Verschr., mit Trommelbremse an HA
	FMI08 Thoe	47	F31+R	70-77	VA+HA 255/50 od. VA 235/55+HA 255/50		+ Red.Ringe BA25=66,6-57,1
	Oxigin 29	39+43	ZP560D	70-89	VA 235/55 u. HA 255/50		mit Trommelbremse an HA
8,5 x 19	B32	42	-	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Orig.-Verschr., mit Trommelbremse an HA
	B32	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		mit Trommelbremse an HA
	B36	35	ZP560D	70	VA 245/50+HA 275/45		VA  , nur für Trommelbremse an der HA, nur Bremse 358mm VA
	B37	43	ZP560D	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		nur für Trommelbremse an der HA, nur Bremse 358mm VA
		45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		nur für Trommelbremse an der HA
	B41	39	ZP560D	70-77	VA 235/55+HA 255/50		
	B43	38	ZP568F	70, 77	VA 235/55+HA 255/50		nur für Trommelbremse an der HA
	AC-M10	40	+ R	70-89	VA 235/55+HA 255/50		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , mit Trommelbremse an HA
	CA 20	45	ZP560D	70-89	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		mit Trommelbremse an HA
	CA 23	40	- +R	70, 77	VA 235/55+HA 255/50		+ Red.Ringe BA25=66,6-57,1 , mit Trommelbremse an HA
		45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		mit Trommelbremse an HA
	Oxigin 28	40	ZP560D	70, 77	VA 235/55+HA 255/50		mit Trommelbremse an HA
		45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		mit Trommelbremse an HA
8 x 20	B40	45	-	70, 77	VA 235/50, 245/45		Orig.-Verschr., nur für Trommelbremse an der HA, nur Bremse 358mm VA
9 x 20		42			HA 255/45, 275/40		
8 x 20	B43	45	-	70, 77	VA 235/50		Orig.-Verschr., nur für Trommelbremse HA
9 x 20		42			HA 255/45		
8 x 20	B43	45	-	70-89	VA 235/50, 245/45		Orig.-Verschr.
9 x 20		42			HA 255/45, 275/40		
8 x 20	RC36	38+45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
	B40	40	-	70	VA 235/50+HA 255/45		Orig.-Verschr., nur für Trommelbremse an der HA, nur Bremse 358mm VA
		41+45	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr., nur für Trommelbremse an der HA, nur Bremse 358mm VA
	B43	41	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr., nur für Trommelbremse an der HA
		45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
		39	ZP560D	70-89	VA 235/50+HA 255/45		
	FMI08 Thoe	45	F31+R	70-77	VA+HA 255/45 od. VA 235/50+HA 255/45		+ Red.Ringe BA25=66,6-57,1
8,5 x 20	B43	40	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr.
	RC29	38	-	70	VA 235/50+HA 255/45		Orig.-Verschr., für Trommelbremse an der HA, nur Bremse 358mm VA
		40+45	ZP560D	70	VA 235/50+HA 255/45		nur für Trommelbremse an der HA, nur Bremse 358mm VA
	B24	42	ZP560D	70, 77	VA+HA 255/45 od. VA 235/50+HA 255/45		nur für Trommelbremse an der HA, nur Bremse 358mm VA
	B42	40+45	ZP560D	70, 77	VA 235/50+HA 255/45		für Trommelbremse an der HA
	B43	40+43	ZP560D	70, 77	VA 235/50+HA 255/45		für Trommelbremse an der HA
	B44	40	ZP560D	70, 77	VA 235/50+HA 255/45		für Trommelbremse an der HA
	AC-521	45	-	70, 77	VA+HA 255/45 od. VA 235/50+HA 255/45		Orig.-Verschr.
	AC-M10	40	- +R	70, 77	VA+HA 255/45 od. VA 235/50+HA 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	FMI12 Kari	40	F94	70-77	VA+HA 255/45 od. VA 235/50+HA 255/45		
9 x 20	RC36	42	-	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		Orig.-Verschr.
	B40	42	-	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		Orig.-Verschr.
	B43	42	-	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		Orig.-Verschr.
	B37	37	ZP560D	70, 77	VA 245/45+HA 275/40		für Trommelbremse an der HA
	AC-521	42	-	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		Orig.-Verschr., nur für Trommelbremse an der HA
	CA 20 / CA 23	45	ZP560D	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		für Trommelbremse an der HA
	FMI11 Elatha	46	- +R	70-77	VA+HA 255/45, 265/40, 265/45 od. VA 235/50+HA 255/45 u. VA 245/45+HA 265/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 26	45	ZP560D	70-77	VA 245/45+HA 265/40		
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45+HA 255/40		Orig.-Verschr., nur für Trommelbremse an der HA, nur Bremse 358mm VA
9 x 21		HA 42					
8,5 x 21		VA 40					

9 x 21		HA 42			HA 255/40, 275/35		Bremse 358mm VA
8,5 x 21	B41	40	-	70-89	VA+HA 255/40 od. VA 235/45+HA 255/40		Orig.-Verschr., auch Sportback
	B43	40	-	70-89	VA 235/45+HA 255/40		Orig.-Verschr., nur für Trommelbremse an der HA
	B41	37+40	ZP560D	70-77	VA+HA 255/40 od. VA 235/45+HA 255/40		
	B43	38	ZP568F	70-89	VA 235/45+HA 255/40		nur für Trommelbremse an der HA
9 x 21	B32	40	ZP560D	70	VA 245/40+HA 275/35		nur für Trommelbremse an der HA, nur Bremse 358mm VA
	CA 17	45	ZP560D	70-77	VA 245/40+HA 275/35		
	CA 20	37	ZP560D	70-89	VA 235/45+HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA
		45	ZP560D	70-89	VA 235/45+HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA
9,5 x 21	FMI10 e-Joule	41,5	F95	70-77	VA 245/40+HA 275/35		

Kombinationen

8,5 x 20	B42	VA 40	ZP560D	70-89	VA 235/50, 245/45		
9,5 x 20		HA 42			HA 255/45, 275/40		
8,5 x 20	CA 19	VA 45	ZP560D	70-77	VA 235/50		
9,5 x 20		HA 43			HA 255/45		

Audi Q5 (siehe Konfigurator)	ab 11.08	8R / 8R1/2	5/112	66,6	e1*2001/116*0473*..., e1*2001/116*0497*..., e13*2007/46*1083*..., e13*2007/46*1179*...
------------------------------	----------	------------	-------	------	--

Audi Q5 / Q5 Sportback	ab 02.2017	FY	5/112	66,6	e1*2007/46*1550*46, e1*2007/46*1685*..
indirekt - teilweise direkt Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	34	-	100-210	235/65		Orig.-Verschr., incl. Facelift 2021, nur M+S
	RC32	34	-	100-210	235/65, 245/60, 255/60		Orig.-Verschr., ohne Radhausverbr. bei 255/60 ✖
	RC27	37	-	100-210	235/65, 255/55, 255/60		Orig.-Verschr., nur M+S
	RC30	35	ZP567F	110-185	235/65, 255/55, 255/60		nur M+S, ab 255/55 ✖
	B39	35	ZP567F	100-210	235/65		nur M+S
7,5 x 17	RC29	35	ZP567F	110-210	235/65		incl. Facelift 2021, nur M+S
	RC34	36+40	ZP568F	100-210	235/65, 245/60, 255/60		nur M+S, ET36 ohne Radhausverbr. ab 255/60 ✖
	B36	35	ZP567F	110-185	235/65, 255/55, 255/60		nur M+S, ab 255/55 ✖
7,5 x 18	RC30	35	ZP567F	100-210	235/55, 235/60		incl. Facelift 2021, nur M+S
	B32 / B39	35	ZP567F	100-210	235/55, 235/60, 255/50, 255/55		nur M+S, ab 255/50 ✖
	CA 20	40	ZP568F	100-210	235/55, 235/60, 245/55, 255/55		
	Oxigin 25	44	ZP568F	100-210	255/55		nicht Bremse 350x34mm
8 x 18	RC27	39	-	100-210	235/60		Orig.-Verschr.
				100-210	235/60, 245/55, 245/60, 255/55		Orig.-Verschr. bei 255/55 ✖
	RC32	39	-	100-210	235/55, 235/60, 245/55		Orig.-Verschr.
	CA 26	39	ZP568F	100-210	235/60		nicht Bremse 350mm
	FMI07 Atena	39	F95	100-210	235/60		
	FMI11 Elatha	39	F95	100-210	235/55, 235/60, 245/55, 255/55		
	RC29	35	ZP567F	100-210	235/60		
	RC34	40	ZP568F	100-210	235/55, 235/60, 245/55		
	B36	35	ZP567F	100-210	235/60		incl. Facelift 2021
	AC-M10	40	AV1	100-210	235/60		incl. Facelift 2021
	AC-518	40	AV4	100-210	235/60		
	AF18	40	AV1	100-210	235/60		
	AF20	35+40	AV1	100-210	235/60		incl. Facelift 2021
7 x 19	FMI08 Thoe	34	F31	100-210	235/55, 235/60		
	FMI12 Kari	34	-	100-210	235/55, 235/60, 245/55		Orig.-Verschr., mit Verbreiterungen
	RC27	34	-	100-210	235/55, 245/50		Orig.-Verschr., incl. Facelift 2021, nur M+S
7,5 x 19	RC34	34	-	100-210	235/55		Orig.-Verschr.
	B39	33	ZP567F	100-210	235/55, 245/50		nur M+S, bei 245/50 ✖
	Oxigin 18	35	ZP568F	100-260	235/55, 245/50		nicht Bremse 350mm, bei 245/50 ✖
8 x 19	RC29	39	-	100-210	235/55, 245/50, 255/45		Orig.-Verschr.
	RC32	39	-	100-210	235/50, 235/55, 245/50		Orig.-Verschr., auch für Hybrid Fahrzeuge
	B38	39	-	100-210	235/55, 245/50, 255/45		Orig.-Verschr., incl. Facelift 2021, auch Sportback
	B40	39	-	100-210	235/55, 245/50, 255/45		Orig.-Verschr., incl. Facelift 2021
	Oxigin 29	39	ZP568F	100-210	235/55, 245/50, 255/45		incl. Facelift 2021
	FMI07 Atena	39	F95	100-210	235/50, 235/55, 245/50		
	RC29	35	ZP567F	110-210	235/55, 255/45		
	RC34	34	-	100-210	235/50, 235/55		Orig.-Verschr., ohne Verbreiterung
		38	ZP567F	100-210	235/50, 235/55, 245/50, 255/50		ohne Radhausverbr. ab 255/50 ✖
	B38	35	ZP567F	100-210	255/45		incl. Facelift 2021, auch Sportback
	B40	38	ZP567F	100-210	235/55, 245/50, 255/45		
	B43	34	ZP568F	100-210	235/55, 255/45		incl. Facelift 2021, auch Sportback
		38	ZP568F	100-210	235/55, 245/50, 255/45		incl. Facelift 2021, auch Sportback
	CA 17	43	ZP568F	100-260	245/50, 255/50		nicht Bremse 340 u. 350mm

	CA 24	43	ZP568F	100-260	245/50, 255/50		
	AC-518	38	AV4	100-210	235/55, 245/50, 255/45		
	AC-521	35	AV1	100-210	235/55, 255/45		incl. Facelift 2021
	RC34	36	-	100-210	235/50, 235/55		Orig.-Verschr.
8,5 x 19	B36	35	ZP567F	100-210	235/55, 255/45		incl. FL2021, nicht Bremse 318, 338 u. 350mm
	B37	34	-	100-210	235/55, 245/50		Orig.-Verschr., nur M+S
		35	ZP567F	100-210	235/55, 255/45		incl. Facelift 2021
	B41	39	ZP568F	100-210	235/50, 235/55, 265/45, 275/45		ohne Radhausverbr. bei 275/45 ✖
	B42	35	ZP567F	100-210	235/55, 255/45		incl. Facelift 2021
	B43	40	ZP568F	100-210	235/55, 245/50, 255/45		incl. Facelift 2021
	AC-M10	40	AV1	100-210	235/55, 245/50, 255/45		incl. Facelift 2021
	AF20	40	AV1	100-210	235/55, 245/50, 255/45		incl. Facelift 2021
	CA 26	40	ZP568F	100-210	235/55, 245/50, 255/45		incl. Facelift 2021, nicht Bremse 338 u. 350mm
	Oxigin 19 / 20	40	ZP568F	100-260	235/55		nicht Bremse 318x30 u. 350x34mm
	Oxigin 28	40	ZP568F	100-210	235/55, 245/50, 255/45		incl. Facelift 2021
	FMI07 Atena	40	F95	100-210	235/50, 235/55, 245/50, 265/45		
8 x 20	RC36	39	ZP567F	100-210	235/45, 245/45, 255/45		incl. Facelift 2021
	B40	39	-	100-210	235/45, 245/45, 255/45		Orig.-Verschr., incl. Facelift 2021, auch Sportback
	B38	35	ZP567F	100-210	235/45, 245/45, 255/45		incl. Facelift 2021, auch Sportback
	B43	30	ZP568F	100-210	235/45, 245/45		incl. Facelift 2021, auch Sportback
8,5 x 20	RC29	33	ZP567F	100-210	235/45, 245/45		incl. Facelift 2021
		40	ZP567F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	RC34	33	ZP568F	100-210	235/45, 245/45, 255/45, 265/45		ohne Radhausverbr. ab 255/45 ✖
		37+38	ZP568F	100-210	235/45, 245/45, 255/45		
	B24	33	ZP567F	100-210	235/45, 245/45		
	B32	40	ZP567F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	B41	35	ZP568F	100-210	235/45, 245/45, 255/45, 265/45		ohne Radhausverbr. ab 255/45 ✖
	B42	35+40	ZP567F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021, ET40 nicht Bremse 338 u. 350mm
	B43	35+40	ZP568F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	B44	35+40	ZP568F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021, ET40 nicht Bremse 350mm
	AC-518	32	AV1	100-210	235/45, 245/45		incl. Facelift 2021
	AC-521	32	AV1	100-210	235/45, 245/45		incl. Facelift 2021
	AC-M10	40	AV1	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	CA 17	35	ZP568F	100-260	245/45		nicht Bremse 350x34mm
		40	ZP568F	100-260	255/40, 255/45, 265/45		nicht Bremse 350x34mm
	FMI07 Atena	39	F95	100-210	235/45, 245/45, 255/45		
	FMI12 Kari	34	F94	100-210	235/45, 245/45, 255/45, 265/45		ohne Radhausverbr. ab 255/45 ✖
		40	F94	100-210	235/45, 245/45, 255/45		
	Oxigin 14	35	ZP568	100-260	245/45		
9 x 20	B37	33	-	100-210	235/45		Orig.-Verschr.
		37	ZP567F	110-210	235/45, 245/45, 255/40, 255/45, 265/40, 265/45		incl. Facelift 2021, ab 255/40 ✖
	B40	33	-	100-210	235/45		Orig.-Verschr.
	B41	35	ZP568F	100-210	235/45, 245/45, 255/45		ohne Radhausverbr. ab 255/45 ✖
		38	ZP568F	100-210	235/45, 245/45, 255/45, 265/40		ohne Radhausverbr. ab 255/45 ✖
	B43	33	ZP568F	100-210	235/45		incl. Facelift 2021
		35	ZP568F	100-210	235/45, 245/45		incl. Facelift 2021
		38	ZP568F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	AC-518	41	-	100-260	255/40, 255/45		Orig.-Verschr.
	AC-522	40	AV1	100-260	245/45, 255/40, 255/45		
	AC-M08	40	AV1	100-260	245/45, 255/40, 255/45		
	AF18	33	-	100-210	235/45		Orig.-Verschr.
	CA 20	35	ZP568F	100-210	235/45, 245/45		incl. Facelift 2021
	CA 23	38	ZP568F	100-210	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	FMI07 Atena	33	F95	100-210	235/45, 245/45, 255/45		ohne Radhausverbr. nur 235/45 auflagenfrei!
	FMI11 Elatha	34	F95	100-210	235/45, 245/45, 255/45		ohne Radhausverbr. nur 235/45 auflagenfrei!
	Oxigin 18	35	ZP568F	110-185	235/45, 245/45		
	Oxigin 25	45	ZP568F	100-260	255/40, 255/45		nicht Bremse 318 u. 330mm
	Oxigin 28	35	ZP568F	100-210	235/45, 245/45		incl. Facelift 2021
8,5 x 21	B41	34	ZP568F	100-210	245/40, 255/40		
		30+37+40	ZP568F	100-210	245/40, 255/40		ET30 ohne Radhausverbr. ✖
	B43	34	ZP568F	100-210	245/40		incl. Facelift 2021
		37	ZP568F	100-210	245/40, 255/40		incl. Facelift 2021
9 x 21	B43	36	ZP568F	100-210	245/40		incl. Facelift 2021
	AF18	37	AV1	100-210	245/40		

Audi Q5 / Q5 Sportback NEU				ab 2025	GU / FY	5/112	66,6	e1*2007/46*1550*47..
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 20	RC36	39	ZP567F	150	235/45, 235/50, 245/45, 255/45			nur Bremse 360mm
8,5 x 20	RC36	40	ZP567F	150	235/45, 235/50, 245/45, 255/45			nur Quattro, nur Bremse 360mm

8,5 x 21	B41	40	ZP559F	150	235/45, 245/40, 255/40		
----------	-----	----	--------	-----	------------------------	--	--

Audi Q5 TFSI e Plug-in-Hybrid ab 2019 FY 5/112 66,6 e1*2007/46*1550*12...							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	34	-	185, 195	235/65		Orig.-Verschr., incl. Facelift 2021, nur M+S
		37	-	185	235/65, 255/55, 255/60		Orig.-Verschr., nur M+S
7,5 x 18	RC30	35	ZP567F	185	235/65		Orig.-Verschr., nur M+S
	B32	35	ZP567F	185	235/55, 235/60		incl. Facelift 2021, nur M+S
8 x 18	RC27	39	-	185, 195	235/60		Orig.-Verschr., incl. Facelift 2021
	B36	35	ZP567F	185, 195	235/60		incl. Facelift 2021
	AC-M10	40	AV1	185, 195	235/60		incl. Facelift 2021
	AC-518	40	AV4	185, 195	235/60		incl. Facelift 2021
	AF20	35+40	AV1	185, 195	235/60		incl. Facelift 2021
7 x 19	RC27	34	-	185, 195	235/55, 245/50		Orig.-Verschr., incl. Facelift 2021, nur M+S
8 x 19	B38	39	-	185, 195	235/55, 245/50, 255/45		Orig.-Verschr., incl. Facelift 2021
	B40	39	-	185, 195	235/55, 245/50, 255/45		Orig.-Verschr., incl. Facelift 2021
	Oxigin 29	39	ZP568F	185, 195	235/55, 245/50, 255/45		incl. Facelift 2021
	RC29	39	-	185	235/55, 245/50, 255/45		Orig.-Verschr.
	B40	38	ZP567F	185	235/55, 245/50, 255/45		
	B43	34	ZP568F	185, 195	235/55, 255/45		incl. Facelift 2021
		38	ZP568F	185, 195	235/55, 245/50, 255/45		incl. Facelift 2021
8,5 x 19	AC-521	35	AV1	185, 195	235/55, 255/45		incl. Facelift 2021
	B37	35	ZP567F	185, 195	235/55, 255/45		incl. Facelift 2021
	B43	40	ZP568F	185, 195	235/55, 245/50, 255/45		incl. Facelift 2021
	AC-M10	40	AV1	185, 195	235/55, 245/50, 255/45		incl. Facelift 2021
8 x 20	AF20	40	AV1	185, 195	235/55, 245/50, 255/45		incl. Facelift 2021
	RC36	39	ZP567F	185, 195	235/45, 245/45, 255/45		incl. Facelift 2021
	B40	39	-	185, 195	235/45, 245/45, 255/45		Orig.-Verschr., incl. Facelift 2021
8,5 x 20	B43	39	ZP568F	185, 195	235/45, 245/45, 255/45		incl. Facelift 2021
		30	ZP568F	185, 195	235/45, 245/45		incl. Facelift 2021
	RC29	33	ZP567F	185, 195	235/45, 245/45		incl. Facelift 2021
		40	ZP567F	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	B24	33	ZP567F	185, 195	235/45, 245/45		incl. Facelift 2021
	B32	40	ZP567F	185	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	B42	30	ZP567F	185, 195	235/45		incl. Facelift 2021
		35	ZP567F	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	B43	35+40	ZP568F	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	AC-518	32	AV1	185, 195	235/45, 245/45		incl. Facelift 2021
	AC-521	32	AV1	185, 195	235/45, 245/45		incl. Facelift 2021
	AC-M10	40	AV1	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
9 x 20	B37	33	-	185, 195	235/45		Orig.-Verschr., incl. Facelift 2021
		37	ZP567F	185, 195	235/45, 245/45, 255/40, 255/45, 265/40, 265/45		incl. Facelift 2021, ab 255/40 ✖
	B43	33	ZP568F	185, 195	235/45		incl. Facelift 2021
		35	ZP568F	185, 195	235/45, 245/45		incl. Facelift 2021
		38	ZP568F	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
	CA 20	35	ZP568F	185, 195	235/45, 245/45		incl. Facelift 2021
	CA 23	38	ZP568F	185, 195	235/45, 245/45, 255/40, 255/45		incl. Facelift 2021
8,5 x 21	Oxigin 28	35	ZP568F	185, 195	235/45, 245/45		incl. Facelift 2021
		34	ZP568F	185, 195	245/40		incl. Facelift 2021
9 x 21	B43	37	ZP568F	185, 195	245/40, 255/40		incl. Facelift 2021
		36	ZP568F	185, 195	245/40		incl. Facelift 2021

Audi Q5 TFSIe / Sportback NEU ab MJ2025 GU / FY 5/112 66,6 e1*2007/46*1550*53...							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 20	RC36	39	ZP567F	185	235/45, 235/50, 245/45, 255/45		nur Allrad, Plug-in Hybrid
8,5 x 20	RC36	40	ZP567F	185	235/45, 235/50, 245/45, 255/45		nur Allrad, Plug-in Hybrid

Audi SQ5 (siehe Konfigurator) 2013 - 2016 8R/ 8R1 5/112 66,6 e1*2001/116*0473*..., e13*2007/46*1083*...							
---	--	--	--	--	--	--	--

Audi SQ5 ab 02.2017 FY 5/112 66,6 e1*2007/46*1550*..							
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 19	RC27	34	-	251-260	235/55, 245/50, 255/50		Orig.-Verschr., incl. Facelift 2021, nur M+S, mit Radhausverbreiterungen
	RC34	34	-	251-270	235/55		Orig.-Verschr.
7,5 x 19	B39	33	ZP567F	260	235/55, 245/50, 255/50		nur M+S, bei 255/50 ✖
	Oxigin 18	35	ZP568F	260	235/55, 245/50		nicht Bremse 350mm
	RC29	39	-	255, 260	235/55, 245/50, 255/45, 255/50		Orig.-Verschr., nur M+S

8 x 19	RC29	35	ZP567F	255, 260	235/55, 245/50, 255/45		nur M+S
	RC32	39	-	251-260	235/50, 235/55, 245/50, 255/50		nur M+S, ohne Radhausverbr. bei 255/50 ✖
	RC34	34	-	251-270	235/50, 235/55		Orig.-Verschr., nur M+S, ohne Verbreiterung
		38	ZP567F	251-260	235/50, 235/55, 245/50, 255/50		ohne Radhausverbr. bei 255/50 ✖
	B24	35	ZP567F	255, 260	235/55, 245/50, 255/45		nur M+S
	B38	39	-	251-260	235/55, 245/50, 255/45, 255/50		Orig.-Verschr., incl. Facelift 2021, nur M+S
	B40	38	ZP567F	255, 260	235/55, 245/50, 255/45, 255/50		nur M+S, mit Radhausverbreiterung
		39	-	255, 260	235/55, 245/50, 255/45, 255/50		Orig.-Verschr., nur M+S, mit Radhausverbreiterung
	B43	34	ZP568F	251-260	235/55, 245/50, 255/45		incl. Facelift 2021, nur M+S, mit Radhausverbr.
		38	ZP568F	251-260	235/55, 245/50, 255/45, 255/50		incl. Facelift 2021, nur M+S, mit Radhausverbr.
	AC-518	38	AV4	255, 260	235/55, 245/50, 255/45, 255/50		nur M+S, mit Radhausverbreiterung
	AC-521	35	AV1	251-260	235/55, 245/50, 255/45		nur M+S, mit Radhausverbreiterung
	CA 24	43	ZP568F	260	245/50, 255/50		
8,5 x 19	FMI07 Atena	39	F95	255-260	235/50, 235/55, 245/50		nur M+S
	Oxigin 29	32	ZP568F	251-260	235/55, 255/45		incl. Facelift 2021, nur M+S
		39	ZP568F	251-260	235/55, 245/50, 255/45, 255/50		incl. FL2021, nur M+S, mit Radhausverbreiterung
	RC34	36	-	251-270	235/50, 235/55		Orig.-Verschr., nur M+S
		30	ZP567F	251-260	235/45, 245/45		incl. Facelift 2021, nur M+S, mit Radhausverbr.
	B32	34,5	ZP567F	255, 260	235/55, 255/45		nur M+S
		34	-	260	235/55, 245/50, 255/50		Orig.-Verschr., nur M+S
	B37	35	ZP567F	251-260	235/55, 245/50, 255/45, 255/50, 275/45		incl. Facelift 2021, nur M+S, ab 255/50 ✖
		36	ZP568F	251-260	235/50, 235/55		nur M+S
	B41	39	ZP568F	251-260	235/50, 235/55, 265/45, 275/45		ohne Radhausverbr. bei 275/45 ✖
		35	ZP567F	251-260	235/55, 245/50, 255/45, 255/50, 275/45		
	B42	40	ZP568F	251-260	235/55, 245/50, 255/45		incl. Facelift 2021, nur M+S, mit Radhausverbr.
	AC-M10	40	AV1	251-260	235/55, 245/50, 255/45		incl. Facelift 2021, nur M+S, mit Radhausverbr.
8 x 20	FMI07 Atena	40	F95	255-260	235/50, 235/55, 245/50, 265/45		nur M+S
	Oxigin 19	40	ZP568F	260	235/55		nicht Bremse 318x30 u. 350x34mm
	B40	39	-	251-260	235/45, 245/45, 255/45		Orig.-Verschr., incl. FL2021, bis 245/45 nur M+S
	B43	39	ZP568F	251-260	235/45, 245/45, 255/45		incl. FL2021, bis 245/45 nur M+S
	RC36	39	ZP567F	251-260	235/45M+S, 245/45M+S, 255/45		incl. Facelift 2021
	B38	35	ZP567F	251-260	235/45M+S, 245/45M+S, 255/45		incl. Facelift 2021
	B40	28	-	255, 260	235/45, 245/45, 255/45		Orig.-Verschr., nur M+S, ab 255/45 ✖
	B43	30	ZP568F	251-260	235/45M+S, 245/45M+S, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
	RC29	33	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
		40	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
	RC34	30+37	ZP568F	251-260	255/45		
		38	ZP568F	255-260	255/45		
	B24	33	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, ohne Radhausverbr. ✖
8,5 x 20	B32	30+40	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		ET40 incl. Facelift 2021
	B41	35	ZP568F	251-260	255/45, 265/45		ohne Radhausverbr. ✖
		30	ZP567F	251-260	235/45, 245/45		nur M+S, ohne Radhausverbr. ✖
	B42	35	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45, 265/45		incl. Facelift 2021, ohne Radhausverbr. ✖
		35	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45, 265/45		incl. Facelift 2021, ohne Radhausverbr. ✖
	B43	40	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021
		35	ZP567F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45, 265/45		incl. Facelift 2021, ohne Radhausverbr. ✖
	B44	32	AV1	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021
	AC-518	32	AV1	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021
	AC-521	32	AV1	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021
	AC-M10	40	AV1	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
	CA 17	35	ZP568F	260	245/45		nicht Bremse 350x34mm
		40	ZP568F	260	255/40, 255/45, 265/45		nicht Bremse 350x34mm
	FMI07 Atena	39	F95	255-260	255/45		
9 x 20	B41	38	ZP568F	255-260	255/45, 265/40		ohne Radhausverbr. ✖
	B43	33	ZP568F	251-260	235/45, 245/45		incl. Facelift 2021, nur M+S
		35	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021
		38	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45, 265/40, 265/45		incl. Facelift 2021, ohne Radhausverbr. ✖
	AC-518	41	-	260	255/40, 255/45		Orig.-Verschr.
	AC-522	40	AV1	260	245/45, 255/40, 255/45		
	AF18	33	-	260	235/45, 245/45		Orig.-Verschr., nur M+S
	CA 20	35	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
	FMI07 Atena	33	F95	255-260	255/45		mit Radhausverbreiterungen
	FMI11 Elatha	34	F95	251-260	235/45, 245/45, 255/45		mit Radhausverbreiterungen
	Oxigin 28	35	ZP568F	251-260	235/45M+S, 245/45M+S, 255/40, 255/45		incl. Facelift 2021, mit Radhausverbreiterungen
	B37C	38	ZP567F	251-260	255/40, 255/45		incl. Facelift 2021, ohne Radhausverbr. ✖
		34	ZP568F	251-260	255/40		
8,5 x 21	B41	30+37+40	ZP568F	251-260	255/40		ET30 ohne Radhausverbr. ✖
		34	ZP568F	251-260	255/40		incl. Facelift 2021
	B43	37	ZP568F	251-260	255/40		incl. Facelift 2021
9 x 21	B43	36	ZP568F	251-260	255/40		incl. Facelift 2021
	AF18	37	AV1	255, 260	255/40, 265/35		

	CA 20	37	ZP568F	251-260	255/40, 265/35		incl. Facelift 2021, ohne Radhausverbr. ✖
--	-------	----	--------	---------	----------------	--	---

Audi SQ5 / Sportback NEU		ab MJ2025		GU / FY	5/112	66,6	e1*2007/46*1550*48-..	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 20	RC36	39	ZP567F	270	235/45, 245/45, 255/45			
8,5 x 20	RC36	40	ZP567F	270	235/45M+S, 245/45M+S, 255/45			

Audi Q6 e-tron NEU		2 / 3. Quartal 2024		GF	5/130	66,6	e1*2018/858*00337*.., e1*2018/858*00338*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
Kombinationen:								

Kombinationen:

8 x 18		VA 40			VA 235/65		It. Thorsten aktuell KEINE 18Zoll in Planung (Stand:02.10.2024)
9 x 18		HA 45			HA 255/60		
8 x 19	B40	VA 40	-	100, 120	VA 235/60		Orig.-Verschr.
9 x 19		HA 45			HA 255/55		
8,5 x 20	B32	VA 35	-	100, 120	VA 235/55, 255/50		nur ABE und nur in SG
9,5 x 20		HA 39			HA 285/45		
8,5 x 20	B43	VA 35	-	100, 120	VA 235/55, 255/50, 265/45, 275/45		Orig.-Verschr.
10 x 20		HA 39			HA 285/45, 295/40, 305/40		
8,5 x 20	FMI15 Zelos	VA 35	-		VA 255/50		Orig.-Verschr., i.V.
10 x 20		HA 39			HA 285/45		
8,5 x 20	AC-MB6	VA 34	-	100, 120	VA 235/55, 255/50, 265/45, 275/45		Orig.-Verschr.
10 x 20		HA 38			HA 285/45, 295/40, 305/40		
9 x 21	B43	VA 29	-	100, 120	VA 255/45		Orig.-Verschr.
10 x 21		HA 39			HA 285/40		
9 x 21		VA 29	-	100, 120	VA 245/45, 255/45		Orig.-Verschr.
10 x 21		HA 39			HA 275/40, 285/40, 295/40		

Audi SQ6 NEU i.V.		4. Quartal 2024		GF	5/130	66,6	e1*2018/858*00337*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
Noch kein Fahrzeuganbau vorhanden - Info von Thorsten - (Stand:20.01.2025)							

Kombinationen:

8,5 x 20	FMI15 Zelos	VA 35	-		VA 255/50		Orig.-Verschr., i.V.
10 x 20		HA 39			HA 285/45		

Audi Q7 (siehe Konfigurator)		ab 03.06		4L/4L1	5/130	71,6	e1*2001/116*0350*00-19, e1*2001/116*0367*00-04, e13*2007/46*1081*00-05
------------------------------	--	----------	--	--------	-------	------	--

Audi Q7 (2. Generation Model 4M)		ab 2015		4L/4L1	5/112	66,6	e1*2001/116*0350*20-..., 0367*05-..., e13*2007/46*1081*06-...	
indirekt - teilweise direkt Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	25	-	155-245	255/60, 265/55, 285/50		Orig.-Verschr., bei 285/50 ✖	
	RC32	20	-	155-185	235/65		Orig.-Verschr., beide ET's sind ECE	
		25	-	155-250	255/60, 265/55			
	RC25	25	-	155-185	235/65, 245/60		Orig.-Verschr., 235/65 nur wenn schon Serie	
				155-250	255/60			
	RC34	30	ZP567F	155-250	255/60, 265/55, 285/50, 285/55			
	FMI08 Thoe	26+34	F31	155-250	255/60, 265/55			
FMI11 Elatha	26	F95	155-250	255/60, 265/55				
FMI12 Kari	26+34	Kit 0354	155-250	255/60, 265/55				
8 x 19	RC27	28		155-250	255/55, 265/50, 275/50		Orig.-Verschr., bei 275/50 ✖	
	RC32	28	-	155-250	255/50, 255/55, 265/50, 275/50		Orig.-Verschr.	
	B43	28	ZP559F	155-250	255/55, 265/50, 275/50		auch Hybrid	
	RC34	27	ZP567F	155-250	255/50, 255/55, 265/50, 275/50		Orig.-Verschr.	
		34	-	155-250	255/50, 255/55, 265/50, 275/50			
	B43	27+34	ZP559F	155-250	255/55, 265/50, 275/50			
	CA 24	30	ZP568F	155-250	265/50, 265/55, 275/50			
	FMI08 Thoe	26	F85	155-250	255/50, 255/55, 265/50, 275/50			
	FMI14 Jupiter	26	Kit 0386	155-250	255/50, 255/55, 265/50, 275/50			
Oxigin 29	32	ZP561F	155-250	255/55, 265/50, 275/50		nicht Bremse 400mm		
8,5 x 19	RC34	28	-	155-245	255/55		Orig.-Verschr.	
				155-250	255/50, 255/55, 265/50, 275/50			
	B41	28	ZP559F	155-245	255/50, 255/55, 265/50, 275/50			
	FMI07 Atena	28	F95	155-250	255/50, 255/55, 265/50, 275/50			
	RC25	28	-	155-245	255/55, 265/50, 275/50		Orig.-Verschr.	
	B32	25	-	155-250	255/55, 265/50		Orig.-Verschr., Achslast max. 1.500 kg	
	B41	20+21	ZP559F	155-250	255/50, 255/55, 265/50, 275/50		ohne Radhausverbr. ab 265/50 ✖	
	B43	25	ZP559F	155-250	255/55, 265/50			
Oxigin 19 / 20					255/55, 265/50, 265/55, 275/50		für Kit + € 44,00 Aufpreis! ✖	

	8300 - 1972	32	F85	155-250	255/50, 255/55, 265/50, 275/50		
8 x 20	B40	28	-	155-250	255/50 M+S		Orig.-Verschr.
	B43	27+30	ZP559F	155-250	255/50		
	RC34	30+33	ZP568F	155-250	255/45, 255/50, 265/45, 275/45		
8,5 x 20	B41	20+35	ZP559F	155-250	255/45, 255/50, 265/45, 275/45		
	B43	30+35	ZP559F	155-250	255/50, 265/45, 275/45		
	AF18	20	-	155-245	255/50, 265/45, 275/45		Orig.-Verschr.
	CA 17	23	ZP568F	155-245	265/45, 275/45		nicht für Keramikbremse
	CA 19	32	ZP568F	155-245	255/50, 265/45, 265/50, 275/45		nicht für Keramikbremse
	Oxigin 19	23	OX567	155-245	255/50, 265/45, 265/50, 275/45		max. Achslast 1720kg, für Kit + € 44,00 Aufpreis!
	FMI12 Kari	34	F94	155-250	255/45, 255/50, 265/45, 275/45		
	FMI07 Atena	33	F95	155-250	255/45, 255/50, 265/45, 275/45, 285/45		
9 x 20	B37	33	-	155-250	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., bis 275/45 nur M+S
	B40	33	-	155-250	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., bis 275/45 nur M+S
	B41	33	ZP559F	155-250	255/45, 255/50, 265/45, 275/45, 285/45		
	B43	33	ZP559F	155-250	255/50, 265/45, 275/45, 285/45		
	AC-M08	25	AV1	155-245	265/45, 275/45		nicht Keramikbremse
	AC-518	33	-	155-245 155-373	255/50, 265/45, 275/45 285/45		Orig.-Verschr., nicht Keramikbremse
	AC-522	33	-	155-245 155-373	255/50, 265/45, 275/45 285/45		Orig.-Verschr., nicht Keramikbremse
	AF18	33	-	155-245	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., bis 275/45 nur M+S
	CA 20	35	ZP568F	155-250	255/50, 265/45, 275/45, 285/45		
	CA 23	30	ZP561F	155-250	255/50, 265/45, 275/45, 285/45		nicht Bremse 400mm u. nicht Keramikbremse
	FMI11 Elatha	34	F95	155-250	255/45, 255/50, 265/45, 275/45, 285/45		
	Oxigin 19	28	OX567F	155-245 155-320	255/50, 265/45, 275/45 285/45		für Kit + € 44,00 Aufpreis! nicht für Keramikbremse, bei 285/45 ✖
	Oxigin 20	28	OX567	155-245	255/50, 265/45, 265/50, 275/45, 285/45		für Kit + € 44,00 Aufpreis!, nicht Keramik Bremse 265/50 u. 285/45 ✖
9,5 x 20	B32	22	-	155-245	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., auf Achslast achten!!!
	B37C	22	-	155-245	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., auf Achslast achten!!!
	CA 19	25	ZP568F	155-245	265/45		nicht Keramikbremse
8,5 x 21	B41	19 30+34	ZP559F ZP559F	155-250 155-250	255/45 255/45, 265/45		
	Oxigin 18	28	OX567F	155-245	265/45		nicht Keramik-Bremse, für Kit + € 44,00 Aufpreis!
9 x 21	B32	25	-	155-245	255/40, 265/40, 265/45, 275/40		Orig.-Verschr., auf Achslast achten!!!
	CA 17	30	ZP561F	155-245	265/45		nicht Keramikbremse
	B41	31	ZP559F	155-250	255/45, 265/40, 265/45, 275/40, 285/40		
9,5 x 21	B43	31	ZP559F	155-250	255/40, 265/40, 265/45, 275/40, 285/40		mit Radhausverbreiterungen
	B41	22	ZP559F	155-250	255/45, 265/40, 275/40		ohne Radhausverbr. bei 275/40 ✖
	AF18	31	-	155-245	255/40, 265/40, 265/45, 275/40		Orig.-Verschr., auf Achslast achten!!!
10,5 x 21	B41	31	ZP559F	155-250	265/40, 275/40		
9 x 22	AC-M08	26	-	155-245	265/35		Orig.-Verschr., nicht Keramikbremse
	AF18	31	-	155-245 155-320	265/35 285/35		Orig.-Verschr., nicht Keramikbremse Orig.-Verschr., nicht Keramikbremse, ✖
10 x 22	B32	25	-	155-250	265/35, 265/40, 275/35, 285/35		Orig.-Verschr., auf Achslast achten!!! Ohne Radhausverbr. ab 275/35 ✖
		32	-	155-250	265/35, 265/40, 275/35, 285/35		Orig.-Verschr., auf Achslast achten!!!
	AF18	21	AV1	155-250	265/35, 265/40, 275/35		nur M+S, nur mit Radhausverbr. ohne Auflagen
		26	-	155-250	265/35, 265/40		Orig.-Verschr.
	CA 17	30	ZP568F	155-245	265/35		nicht Keramikbremse
	FMI09 CRATOS	21	F31	155-250	265/35, 275/35		mit Radhausverbreiterungen
		31	F31	155-250	265/35, 275/35		
	Oxigin 18	20	OX567	155-245	265/35		für Kit + € 44,00 Aufpreis! ✖

Audi SQ7 (2. Generation Model 4M)		ab 2016	4L, 4L1	5/112	66,6	e1*2001/116*0350*26-..., e13*2007/46*1081*12-...	
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 20	B40	28	-	320, 373	255/50		Orig.-Verschr., nur M+S
	B43	27+30	ZP559F	320, 373	255/50		nur M+S
8,5 x 20	RC34	30+33	ZP568F	320-373	255/45, 265/45		nur M+S
	B41	20+35	ZP559F	320-373	255/45, 255/50, 265/45, 275/45		nur M+S
	B43	30+35	ZP559F	320-373	255/50, 265/45, 275/45		nur M+S
	AF18	20	-	320	265/45		Orig.-Verschr., nur M+S, nicht für Keramikbremse
	CA 17	23	ZP568F	320	265/45, 275/45		nur M+S, nicht für Keramikbremse
	CA 19	32	ZP568F	320-373	255/50, 265/45, 265/50, 275/45		nur M+S, nicht für Keramikbremse
	FMI12 Kari	34	F94	320-373	255/45, 255/50, 265/45, 275/45		nur M+S
	B37	33	-	320, 373	255/50, 265/45, 275/45, 285/45		Orig.-Verschr, bis 275/45 nur M+S
	B40	33	-	320, 373	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., bis 275/45 nur M+S
	B41	33	ZP559F	320	285/45		
	B43	33	ZP559F	320, 373	255/50, 265/45, 275/45, 285/45		bis 275/45 nur M+S
	FMI07 Atena	33	F95	320	255/45, 255/50, 265/45, 275/45, 285/45		bis 275/45 nur M+S

9 x 20	AC-M08	25	AV1	320-373	265/45, 275/45		nicht Keramikbremse, nur M+S
	AC-518	33	-	320-373	255/50, 265/45, 275/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	AC-522	33	-	320-373	255/50, 265/45, 275/45		Orig.-Verschr., nur M+S, nicht Keramikbremse
	AF18	33	-	320	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., nicht Keramikbremse, bis 275/45 nur M+S
	CA 20	35	ZP561F	320, 373	255/50, 265/45, 275/45, 285/45		bis 275/45 nur M+S
	FMI11 Elatha	20	F95	320-373	255/45, 265/45, 275/45		nur M+S, mit Verbreiterungen, nicht Bremse 420x40mm
		34	F95	320-373	255/45, 255/50, 265/45, 275/45, 285/45		bis 275/45 nur M+S, nicht Bremse 420x40mm
	Oxigin 19	28	OX567F	320	255/50, 265/45, 275/45		nur M+S, nicht Keramik-Bremse, für Kit + € 44,00 Aufpreis!
9,5 x 20	B37C	22	-	320	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., bis 275/45 nur M+S, ohne Radhausverbr. nur 265/45 auflagenfrei! ✖
	CA 19	25	ZP568F	320-373	265/45		nur M+S, nicht Keramikbremse
8,5 x 21	B41	19	ZP559F	320-373	255/45		
		30+34	ZP559F	320-373	255/45, 265/45		nur M+S
9 x 21	Oxigin 18	28	OX567F	320-373	265/45		nur M+S, nicht Keramik-Bremse, für Kit + € 44,00 Aufpreis!
	B32	25	-	320	255/40, 265/40, 265/45, 275/40		nur M+S
	CA 17	30	ZP561F	320-373	265/45		nur M+S, nicht Keramikbremse
9,5 x 21	B41	31	ZP559F	320-373	255/45, 265/40, 265/45, 275/40, 285/40		bis 275/40 nur M+S
	B43	31	ZP559F	320, 373	255/40, 265/40, 265/45, 275/40, 285/40		
	B41	22	ZP559F	320-373	255/45, 265/40, 275/40		ohne Radhausverbr. bei 275/40 ✖
	AF18	31	-	320	255/40, 265/40, 265/45, 275/40		Orig.-Verschr.
	FMI12 Kari	31	F95	320-373	255/45, 265/40, 265/45, 275/40, 285/40		bis 275/40 nur M+S
10,5 x 21	B41	31	ZP559F	320-373	265/40, 275/40		nur M+S
9 x 22	AC-M08	26	-	320-373	265/35		Orig.-Verschr., nur M+S, nicht Keramikbremse
9,5 x 22	AF18	31	-	320	265/35		Orig.-Verschr., nur M+S, nicht für Keramikbremse
10 x 22	B32	25	-	320, 373	265/35, 265/40, 275/35, 285/35		Orig.-Verschr., bis 275/35 nur M+S, ohne Radhausverbr. ab 275/35 ✖
		32	-	320, 373	265/35, 265/40, 275/35, 285/35		Orig.-Verschr., bis 275/35 nur M+S
	AF18	21	AV1	320	265/35, 265/40, 275/35		nur M+S, nur mit Radhausverbr. ohne Auflagen
		26	-	320	265/35, 265/40		Orig.-Verschr.
	CA 17	30	ZP568F	320-373	265/35		nur M+S, nicht Keramikbremse
	FMI09 Cratos	21	F31	320-373	265/35, 275/35		nur M+S, mit Radhausverbreiterungen
		31	F31	320-373	265/35, 275/35		

Audi Q8		2018	4L	5/112	66,6	e1*2001/116*0350*32..	
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 19	B32	20	-	170-250	265/55, 275/55, 285/55		Orig.-Verschr.
	B37	20	-	170-250	265/55, 275/55, 285/55		Orig.-Verschr.
	B41	20	ZP559F	170-250	265/55, 275/50, 275/55		
	8300 - 1972	21	F85	170-250	265/55, 275/50, 275/55		
9 x 19	CA 19	25	ZP568F	170-373	255/55, 265/55, 275/50, 275/55		nicht Keramikbremse
8,5 x 20	B41	20	ZP559F	170-250	265/50, 275/45, 275/50, 285/50		
	B43	20	ZP559F	170-250	265/50, 275/50, 285/50		auch Hybrid
	AF18	20	-	170-250	265/50, 275/50, 285/50		Orig.-Verschr.
	CA 17	23	ZP568F	170-250	265/50, 275/45, 275/50		
9 x 20	B37	20	-	170-250	265/50, 275/50, 285/45, 285/50		Orig.-Verschr.
	B41	20	ZP559F	170-250	265/50, 275/45, 275/50, 285/45, 285/50		
	B43	20	ZP559F	170-250	265/50, 275/50, 285/45, 285/50		
	FMI07 Atena	20	Kit0455	170-250	265/50, 275/45, 275/50, 285/45, 285/50		
	FMI16 Taara	20	Kit0455	170-250	275/50		
	AC-518	33	-	170-373	285/45		Orig.-Verschr., nicht Keramikbremse
	AC-M08	25	AV1	170-373	265/50, 275/45, 285/45		nicht Keramikbremse
	AC-522	20	-	170-373	265/50, 275/45, 275/50, 285/45		Orig.-Verschr., nicht Keramikbremse
		33	-	170-373	285/45		Orig.-Verschr., nicht Keramikbremse
	FMI11 Elatha	20	Kit0455	170-250	265/50, 275/45, 275/50, 285/45, 285/50		
9,5 x 20	B37C	22	-	170-250	265/50, 275/50, 285/45, 295/45, 305/45		Orig.-Verschr.
	CA 19	25	ZP568F	170-373	265/50, 275/45, 275/50, 285/45, 295/45, 305/45		nicht Keramikbremse
8,5 x 21	B41	19	ZP559F	170-250	265/45, 275/45		
9 x 21	CA 17	25	ZP561F	170-373	275/45		nicht Keramikbremse
	Oxigin 18	20	ZP568F	170-250	275/45, 285/45		
9,5 x 21	B41	22	ZP559F	170-250	265/45, 275/40, 275/45, 285/40, 285/45		
	AF18	20	-	170-250	265/45, 275/45, 285/40, 285/45		Orig.-Verschr.
10 x 21	B41	20	ZP559F	170-250	285/45		auch für Hybrid
	B43	20	ZP559F	170-250	265/45, 275/45, 285/40, 285/45, 295/40		auch für Hybrid
	FMI07 Atena	19	Kit0455	170-250	265/45, 275/40, 275/45, 285/40, 285/45, 295/40		
	FMI12 Kari	19	Kit0454	170-250	265/45, 275/40, 275/45, 285/40, 285/45, 295/40		
10,5 x 21	B41	19	ZP559F	170-250	275/40, 275/45, 285/40, 285/45, 295/40		
	B43	19	ZP559F	170-250	275/45, 285/40, 285/45, 295/40		

10,5 x 21	CA 17	30	ZP561F	170-373	275/45		nicht Keramikbremse
	Oxigin 18	20	ZP568F	210	275/45, 285/40, 285/45, 295/40		
10 x 22	FMI09 Cratos	21	Kit0613	170-250	285/40		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00
	AC-M08	19	-	170-373	275/40, 285/35, 285/40, 295/35		Orig.-Verschr., nicht Keramikbremse
	AF18	21	AV1	170-250	265/40, 275/40, 285/40, 295/35, 295/40, 305/35		
	CA 17	20	ZP568F	170-373	275/40, 285/35, 285/40, 295/35, 305/35		nicht Keramikbremse
		30	ZP568F	170-373	275/40		nicht Keramikbremse
	FMI07 Atena	18	-	170-250	265/40, 275/35, 275/40, 285/35, 285/40, 295/35, 295/40		Orig.-Verschr.
	FMI09 Cratos	21	Kit0613	170-250	265/40, 275/35, 275/40, 285/35, 285/40, 295/35, 295/40, 305/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00
11 x 22	B32	15	-	170-250	275/40		Orig.-Verschr.
10 x 23	AF18	18	-	170-373	285/35, 295/30, 295/35		Orig.-Verschr., nicht Keramikbremse
	STC-23	18	Kit0613	170-250	285/35, 295/30, 295/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00

Audi SQ8	ab 04.2019	4L	5/112	66,6	e1*2001/116*0350*37-..
----------	------------	----	-------	------	------------------------

indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 20	B41	20	ZP559F	320-373	265/50, 275/45, 275/50, 285/50		nur M+S
	B43	20	ZP559F	320, 373	265/50, 275/50, 285/50		nur M+S
9 x 20	B37	20	-	320, 373	265/50, 275/50, 285/45, 285/50		Orig.-Verschr., nur M+S
	B41	20	ZP559F	320	265/50, 275/45, 275/50, 285/45, 285/50		nur M+S
	B43	20	ZP559F	320, 373	265/50, 275/50, 285/45, 285/50		nur M+S
	AC-M08	25	AV1	320-373	265/50, 275/45, 285/45		nicht Keramikbremse
	AC-518	33	-	373	285/45		Orig.-Verschr., nicht Keramikbremse
	AC-522	20	-	170-373	265/50, 275/45, 275/50, 285/45		Orig.-Verschr., nicht Keramikbremse
		33	-	170-373	285/45		Orig.-Verschr., nicht Keramikbremse
	FMI07 Atena	20	Kit0455	320	265/50, 275/45, 275/50, 285/45, 285/50		nur M+S
	FMI11 Elatha	20	Kit0455	320-373	265/50, 275/45, 275/50, 285/45, 285/50		nur M+S, nicht Bremse 420x40mm
9,5 x 20	CA 19	25	ZP568F	170-373	265/50, 275/45, 275/50, 285/45, 295/45, 305/45		nicht Keramikbremse
8,5 x 21	B41	19	ZP559F	320-373	265/45, 275/45		nur M+S
9 x 21	CA 17	25	ZP561F	373	275/45		nicht Keramikbremse
9,5 x 21	B41	22	ZP559F	320-373	265/45, 275/40, 275/45, 285/40, 285/45		nur M+S
	AF18	20	-	320, 373	265/45, 275/45, 285/40, 285/45		Orig.-Verschr., nur M+S
	FMI12 Kari	20	-	320-373	265/45, 275/40, 275/45, 285/40, 285/45		Orig.-Verschr., nur M+S
10 x 21	B41	20	ZP559F	320-373	285/45		
	B43	20	ZP559F	320, 373	265/45M+S, 275/45M+S, 285/40, 285/45, 295/40		
	FMI07 Atena	19	Kit0455	320-373	265/45, 275/40, 275/45, 285/40, 285/45, 295/40		bis 275/45 nur M+S
	FMI12 Kari	19	Kit0454	320-373	265/45, 275/40, 275/45, 285/40, 285/45, 295/40		bis 275/45 nur M+S
10,5 x 21	B41	19	ZP559F	320-373	275/40, 275/45, 285/40, 285/45, 295/40		
	B43	19	ZP559F	320, 373	275/45M+S, 285/40, 285/45, 295/40		
	CA 17	30	ZP561F	170-373	275/45		nicht Keramikbremse
10 x 22	FMI09 Cratos	21	Kit0613	320-373	285/40		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00
	AC-M08	19	-	373	275/40, 285/35, 285/40, 295/35		Orig.-Verschr., nicht Keramikbremse
	AF18	21	AV1	320	265/40, 275/40, 285/40, 295/35, 295/40, 305/35		bis 275/40 nur M+S
	CA 17	20	ZP568F	320-373	275/40, 285/35, 285/40, 295/35, 305/35		nicht Keramikbremse
		30	ZP568F	373	275/40		nicht Keramikbremse
	FMI07 Atena	18	-	320-373	265/40, 275/35, 275/40, 285/35, 285/40, 295/35, 295/40		Orig.-Verschr., bis 275/40 nur M+S
	FMI09 Cratos	21	Kit0613	320-373	265/40, 275/35, 275/40, 285/35, 285/40, 295/35, 295/40, 305/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00, bis 275/40 nur M+S
11 x 22	B32	15	-	320, 373	275/40		Orig.-Verschr., nur M+S
10 x 23	AF18	18	-	373	285/35, 295/30, 295/35		Orig.-Verschr., nicht Keramikbremse
	STC-23	18	Kit0613	320-373	285/35, 295/30, 295/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00

Audi RS Q8	ab 2020	4L	5/112	66,6	e1*2001/116*0367*06-..
------------	---------	----	-------	------	------------------------

indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
10 x 22	AC-M08	19	-	441	275/40M+S, 285/40M+S, 295/35, 295/40		Orig.-Verschr.
	FMI07 Atena	18	-	441	VA 275/40+HA 295/40		Orig.-Verschr.
					275/40M+S, 295/35, 295/40, 305/35, 305/40		
	FMI09 Cratos	21	Kit0613	441	275/40M+S, 295/35, 295/40, 305/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00
11 x 22	B32	15	-	441	275/40, 285/40		Orig.-Verschr., nur M+S, für Keramikbremsen
10 x 23	AF18	18	-	441	295/35		Orig.-Verschr.
	STC-23	18	Kit0613	441	295/35, 305/35		!!!ACHTUNG!!! Kit ist NICHT kostenlos - Nettopreis: € 52,00

Audi Q8 e-tron		NEU		im Laufe 2023		GE	5/112	66,6	e1*2007/46*1914*..	
indirekt - teilweise direkt Brocksens 2										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
8 x 19	RC34	34	-	158	255/55				Orig.-Verschr., incl. Sportback	
	B43	34	ZP559F	158	255/55				nur M+S, incl. Sportback	
	RC32	28	-	158	255/55				Orig.-Verschr., nur M+S, incl. Sportback	
8,5 x 19	RC34	36	-	158	255/55				Orig.-Verschr., auch Sportback	
				158	255/55, 265/50, 265/55					
	B41	36	ZP559F	158	255/55				auch Sportback	
	RC34	28	-	158	255/55				Orig.-Verschr., auch Sportback	
	CA 20	35	ZP568F	158	255/55, 265/50, 265/55				auch Sportback	
9 x 19	B41	38	ZP559F	158	255/55				auch Sportback	
8 x 20	B43	30	ZP559F	158	255/50				nur M+S, incl. Sportback	
9 x 20	CA 23	38	ZP559F	158	255/50				incl. Sportback	
	B43	33	ZP559F	158	255/50, 275/45				nur M+S, incl. Sportback	
		38	ZP559F	158	255/50, 275/45				nur M+S, incl. Sportback	
	AC-522	33	-	158	255/50, 265/45, 265/50, 275/45, 285/45				Orig.-Verschr., incl. Sportback	
8,5 x 21	B41	40	ZP559F	158	255/45, 265/45				auch Sportback	
	B43	30	ZP559F	158	265/45				incl. Sportback	
		34+37	ZP559F	158	265/45				incl. Sportback	
9,5 x 21	B43	36	ZP559F	158	265/45, 275/40				incl. Sportback	

Audi SQ8 e-tron		NEU		im Laufe 2023		GE	5/112	66,6	e1*2007/46*1914*..	
indirekt - teilweise direkt Brocksens 2										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
9 x 20	FMI16 Taara	20	F90	226	255/50				nur M+S	
10 x 21	B41	20	ZP559F	226	285/40, 295/40, 305/35				auch Sportback	
10,5 x 21	B41	19	ZP559F	226	285/40, 295/40				auch Sportback	
10 x 22	FMI07 Atena	18	-	226	285/35, 295/35				Orig.-Verschr., auch Sportback	
10 x 23	STC-23	18	Kit0613	226	295/30				Achtung - Kit ist nicht kostenlos - Nettopreis: € 52,00	

Audi Q9		im Laufe 2022							
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
auf Anfrage									

BMW

BMW		Baujahr	Typ	LK/LZ	Nabe		
BMW i3		2014	BMWi-1	5/112	66,6	e1*KS07/46*1213*..., e1*2007/46*1213*	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
5 x 19	eb1	43	-	75	155/70		Orig.-Verschr.
					155/70M+S		Orig.-Verschr., nur Range Extender

BMW i3 S		2018	BMW-i-1	5/112	66,6	e1*2007/46*1213*07	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
5 x 19	eb1	28	-	75	155/70M+S		Orig.-Verschr.

BMW i4 eDrive 40		ab Februar 2022		G4C		5/112		66,7		e1*2018/858*00122*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7,5 x 17	RC32	30	-	80-105	225/55, 235/50				Orig.-Verschr., Achlast bis 1.620 kg		
		27	-	80-105	225/55				Orig.-Verschr.		
8 x 18	RC27	30	-	80, 105	225/50, 245/45				Orig.-Verschr.		
	RC32	30	-	80-105	225/50, 245/45				Orig.-Verschr.		
	RC34	30	-	105	225/50, 245/45				Orig.-Verschr.		
	AC-M10	30	-	80, 105	225/50, 245/45				Orig.-Verschr., nicht Bremse 374mm		
	CA 20	30	ZP593F	80, 105	225/50, 245/45						
	CA 23 / CA 26	30	ZP599F	80, 105	225/50, 245/45				nicht Bremse 374mm		
	FMI08 Thoe	34	-	80-105	225/50, 245/45, 255/45				Orig.-Verschr.		
	FMI12 Kari	34	Kit 0334	80-105	225/50, 245/45, 255/45						
8,5 x 18	RC34	36	-	80-105	245/45				Orig.-Verschr.		
	B32	36	-	80-105	245/45, 255/45					Orig.-Verschr.	
9 x 18	CA 17	35	ZP593F	105 (250)	245/45				nicht Bremse 374mm		
8 x 19	RC32	30	-	80-105	245/40				Orig.-Verschr.		
8,5 x 19	B41	36	-	80-105	245/40				Orig.-Verschr.		
	8300 - 1972	32	-	80-105	245/40				Orig.-Verschr.		
8,5 x 19	RC34	VA 35	-	80-105	VA 245/40				Orig.-Verschr.		
9 x 19		HA 42			HA 255/40						
8,5 x 19	B41	VA 35	-	80-105	VA 245/40				Orig.-Verschr.		
9 x 19		HA 42			HA 255/40						
8 x 19	B40	VA 27	-	105 (250)	VA 225/45				Orig.-Verschr.		
9 x 19		HA 40			HA 255/40						
8 x 19	B43	VA 27	-	105 (250)	VA 225/45, 245/40				Orig.-Verschr.		
8,5 x 19		HA 40			HA 255/40						
8,5 x 20	B43	VA 35	-	105 (250)	VA 245/35				Orig.-Verschr.		
9 x 20		HA 42			HA 255/35 HL						
8,5 x 20	B41	35	-	80-105	VA 245/35+HA 255/35				Orig.-Verschr.		
	B42	35	-	80, 105	VA 245/35+HA 255/35				Orig.-Verschr.		
	B43	35	-	105 (250)	VA 245/35+HA 255/35				Orig.-Verschr.		
9 x 20	B41	35	-	80-105	VA 245/35+HA 255/35				HA ✖		
	CA 20	35	ZP593F	80, 105	VA 245/35+HA 255/35				HA ✖		
	Oxigin 28	35	ZP593F	80, 105	VA 245/35+HA 255/35				HA ✖		

BMW i4 M50 NEU		im Laufe 2023		G4C	5/112	66,7	e1*2018/858*00122*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 18	RC34	36	-	125	245/45			Orig.-Verschr.
8,5 x 19	RC32	29	-	125	VA 245/40+HA 255/40			Orig.-Verschr., nur M+S, HA ✖
	B41	36	-	125	VA 245/40+HA 255/40			Orig.-Verschr., nur M+S
8,5 x 19	RC34	VA 35	-	125	VA 245/40			Orig.-Verschr.
9 x 19		HA 42			HA 255/40			
8,5 x 19	B41	VA 35	-	125	VA 245/40+HA 255/40			Orig.-Verschr.
9 x 19		HA 42						
8,5 x 20	B41	35	-	125	VA+HA 255/35 od.			Orig.-Verschr.
					VA 245/35+HA 255/35			
9 x 20	B41	35	-	125	VA 245/35+HA 255/35			Orig.-Verschr., HA ✖

Kombinationen

8,5 x 19	B41	VA 29	-	125	VA 245/40	Orig.-Verschr.
9 x 19		HA 41			HA 255/40	

BMW i5 NEU		im Laufe 2023		G6E	5/112	66,7	e1*2018/858*00317*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	VA 29	-	105, 127	VA 245/45+HA 275/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
10 x 19		HA 46						
	RC32	29	-	105	245/45		Orig.-Verschr., nicht Bremse 370x24mm HA	
	RC34	29	-	105	245/45		Orig.-Verschr., nicht Bremse 370x24mm HA	

8,5 x 19	B41	29	-	105	245/45		Orig.-Verschr., nicht Bremse 374x36mm VA u. 345x24mm HA
	B43	29	-	105, 127	245/45		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
	RC34	26	-	105	245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
	B41	28	-	105	245/45		Orig.-Verschr., nicht Bremse 374x36mm VA u. 345x24mm HA
	B43	25	-		245/45		Orig.-Verschr., i.V.
	AC-MB6	30	-	105, 127	245/45		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
8,5 x 20	B43	VA 28	-	105, 127	VA 245/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35		
8,5 x 20	B43	VA 28	-	105, 127	VA 245/40, 255/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35, 285/35		
8,5 x 20	B41	28	-	105	255/40		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	28	-	105, 127	255/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
9 x 20	CA 23	30	ZP599F	105, 127	255/40		nicht zulässig mit 6-Kolben Festsattelbremse
8,5 x 21	B41	30	-	105	255/35		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	30	-	105, 127	255/35		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
9 x 21	CA 20	30	ZP599F	105, 127	255/35		nicht zulässig mit 6-Kolben Festsattelbremse

Kombinationen

8,5 x 19	B41	VA 29	-	105	VA 245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
9 x 19		HA 41			HA 275/40		
9 x 20	B41	VA 24	-	105	VA 245/40		Orig.-Verschr., nicht Bremse 370x24mm HA
10,5 x 20		HA 44			HA 275/35		
8,5 x 21	B41	VA 30	-	105	VA+HA 255/35 od. VA 245/35+HA 285/30, VA 255/35+HA 285/30		Orig.-Verschr., nicht Bremse 374x36mm VA u. 345x24mm HA
10,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	105, 127	VA 245/35, 255/35		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
10,5 x 21		HA 43			HA 285/30		

BMW i5 M60 xDrive NEU		2024		G6E	5/112	66,7	e1*2018/858*00317*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19 10 x 19	B43	VA 29 HA 46	-	127	VA 245/45+HA 275/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
8,5 x 19		B43	29	-	127	245/45M+S		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
	AC-MB6	30	-	127	245/45M+S		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
8,5 x 20 10 x 20	B43	VA 28 HA 46	-	127	VA 245/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
8,5 x 20 10 x 20		B43	VA 28 HA 46	-	127		HA 275/35	Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
	8,5 x 20 10 x 20	B43	VA 28 HA 46	-	127	VA 245/40, 255/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
HA 275/35, 285/35						Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse		
8,5 x 20	B43	28	-	127	255/40M+S		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
9 x 20	CA 23	30	ZP599F	127	255/40M+S		nicht zulässig mit 6-Kolben Festsattelbremse	

Kombinationen

8,5 x 21	B43	VA 30	-	127	VA 245/35, 255/35		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
10,5 x 21		HA 43			HA 285/30		

BMW i5 Touring NEU		im Laufe 2024		G6E	5/112	66,7	e1*2018/858*00317*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	VA 29	-	105, 127	VA 245/45+HA 275/40		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
10 x 19		HA 46						
8,5 x 20	B43	VA 28	-		VA 245/40+HA 275/35		Orig.-Verschr., i.V.	
10 x 20		HA 46						

Kombinationen

9 x 20	B41	VA 24	-	105-127	VA 245/40		Orig.-Verschr., nicht Bremse 370x24mm HA
10,5 x 20		HA 44			HA 275/35		
8,5 x 21	B43	VA 30	-	105, 127	VA 245/35, 255/35		Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse
9,5 x 21		HA 43			HA 285/30		

BMW i5 M60 xDrive Touring		NEU	im Laufe 2024		G6E	5/112	66,7	e1*2018/858*00317*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 19	B43	VA 29	-	127	VA 245/45+HA 275/40			Orig.-Verschr., nicht zulässig mit 6-Kolben Festsattelbremse	
10 x 19		HA 46							

BMW i7 NEU		im Laufe 2023		G7L / G70	5/112	66,7	e1*2018/858*00154*..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 19	RC34	26	-	125-280	245/50		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
			-	125-280	245/50, 255/45, 265/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
	B41	26	-	125-280	245/50		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
	B41	28	-	125-280	255/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
9 x 19	B41	21	-	125-280	255/45, 265/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
	FMI08 Thoe	20	-	125-280	255/45, 265/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
8,5 x 20	B41	20	-	125-280	245/45, 255/40, 255/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		28	-	125-280	255/40, 255/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
9 x 20	B41	VA 24	-	125-280	VA 255/45		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 20		HA 44			HA 285/40		
9 x 20	B41	20	-	125-280	245/45, 255/40, 255/45, 265/40		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
9 x 21	FMI07 Atena	26	F93	125-280	245/40, 255/40		nur Bremse 395x36mm VA u. 370x24mm HA
9,5 x 21	B41	22	-	125-280	245/40, 255/40, 265/35		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA

Kombinationen

9 x 20	B41	VA 24	-	125-280	VA 255/40+HA 285/35 od. VA 255/45+HA 285/40 od. VA 265/40+HA 295/35		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 20		HA 44					
9,5 x 21	B41	VA 22	-	125-280	VA 255/40+HA 285/35 od. VA 265/35+HA 305/30 od. VA 265/40+HA 295/35		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 21		HA 43					

BMW 1er (siehe Konfigurator)	ab Ende 2011	1K2/1K4 (F20 / F21)	5/120	72,6	e1*2007/46*0273*04..., e1*2007/46*0283*04...
---	--------------	---------------------	-------	------	--

BMW 1er M135i / M140i (siehe Konfigurator)	ab 2012	1K2/1K4	5/120	72,6	e1*2007/46*0273*04-..., e1*2007/46*0283*04-...
---	---------	---------	-------	------	--

BMW 1er		ab 10.2019		F1H (F40)		5/112		66,7		e1*2007/46*2018*...	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 16	RC32	54	-	80-110	195/55, 195/60, 205/55, 205/60				Orig.-Verschr., nur M+S		
	Pro1	48	F93	80-110	195/55, 195/60				nur M+S		
7 x 16	RC30	52	-	80-110	195/60M+S, 205/55, 215/55				Orig.-Verschr.		
6,5 x 17	RC27	45	-	80-140	195/55, 205/50				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
7 x 17	RC30	47	-	85-140	195/55, 205/50, 225/45				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
				85-110	205/50, 225/45				Orig.-Verschr., nicht Bremse 360mm		
	RC32	47	-	80-140	195/50, 195/55				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
	RC34	47	-	80-140	195/50, 195/55				Orig.-Verschr., nicht Bremse 360x30mm		
	CA 26	47	ZP599F	80-140	195/55M+S				nicht Bremse 360mm		
	RC27	49	-	85-110	205/50, 225/45				Orig.-Verschr., nicht Bremse 360mm		
				85-140	195/55, 205/50, 225/45				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
		54	-	80-110	205/50, 215/50, 225/45				Orig.-Verschr., nicht Bremse 360mm		
				80-140	195/55, 205/50, 215/50, 225/45				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
	CA 26	54	ZP599F	80-110	205/50, 215/50, 225/45				nicht Bremse 360mm		
				80-140	195/55, 205/50, 215/50, 225/45				nur M+S, nicht Bremse 360mm		
7,5 x 17	RC27	54	-	85-140	205/50, 215/45, 215/50, 225/45, 235/45				Orig.-Verschr., nicht Bremse 360mm		
	RC32	54	-	80-140	205/50, 215/45, 225/45				Orig.-Verschr., nicht Bremse 360x30mm		
	Oxigin 25	54	ZP599F	80-140	205/50, 215/45, 215/50, 225/45, 235/45				nicht für M-Sportbremse		
6,5 x 18	RC34	41	-	80-225	205/45				Orig.-Verschr.		
7 x 18	RC32	54	-	85-225	195/50M+S, 205/40, 205/45, 215/40, 215/45				Orig.-Verschr., nicht Bremse 360mm		
7,5 x 18	RC30	51	-	85-225	205/45, 215/45, 225/40				Orig.-Verschr., nicht Bremse 360mm		
	RC32	50	-	80-225	205/40, 205/45				Orig.-Verschr.		
		51	-	85-225	205/40, 205/45, 215/40, 215/45				Orig.-Verschr.		
	RC34	50	-	80-225	205/40, 205/45				Orig.-Verschr.		
		51	-	80-225	205/40, 205/45, 215/40, 215/45				Orig.-Verschr.		
	B39	51	-	80-110	205/45, 215/45				Orig.-Verschr., nicht Bremse 360mm		
				80-140	225/40						
				80-225	205/45, 215/45, 225/40				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
	CA 20	51	-	80-195	205/40, 205/45, 215/40, 215/45				Orig.-Verschr., nicht Bremse 330x24mm VA u. 300x20mm HA		
	Oxigin 25	51	-	80-225	205/45, 215/45, 225/40				Orig.-Verschr., nicht für M-Sportbremse		
RC27	57	-	85-140	215/45, 225/40				Orig.-Verschr., nicht Bremse 360mm			
			85-225	205/45 M+S							

8 x 18	RC32	54	-	80-225	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr., auch ET54 ist ECE
		57	-	80-140	225/40		Orig.-Verschr.
				80-225	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr.
	RC34	54	-	80-225	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr., auch ET54 ist ECE
	RC29	57	-	80-110	215/45, 235/40		Orig.-Verschr., nicht Bremse 360mm
				80-225	215/45M+S, 225/40		
	B37	54	-	80-110	215/45		Orig.-Verschr., nicht Bremse 360mm
				80-225	215/45M+S, 225/40		
B38	52	-	85-110	215/45		Orig.-Verschr., nicht Bremse 360mm	
			85-225	215/45M+S, 225/40			
AC-518	50	-	80-225	215/45M+S		Orig.-Verschr., nicht Bremse 360mm	
8 x 19	B43	54	-	80-225	235/35		Orig.-Verschr., nicht Bremse 360mm
	RC27	57	-	85-225	235/35		Orig.-Verschr., nicht Bremse 360mm
	RC29	57	-	85, 103	215/35		Orig.-Verschr., nicht Bremse 360mm
				85-225	225/35		
	RC32	57	-	80-225	215/35, 225/35		Orig.-Verschr., nicht 4-Kolben Feststättel Bremse 360mm VA u. 330x20mm HA
8 x 20	B38	52	-	80-103	225/30		Orig.-Verschr., nicht Bremse 360mm
				80-225	235/30		Orig.-Verschr., nicht Bremse 360mm 

BMW 1er NEU		2024		F7 / G70		5/112		66,7		e1*2018/858*00397*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 17	RC27	45	-	90-150	195/55, 205/55 , 215/50, 225/50				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
7 x 17	RC32	47	-	90-150	195/55, 195/60				Orig.-Verschr., nur M+S		
7,5 x 17	RC27	53	-	90-150	205/55 , 215/50, 225/50HA, 235/45				Orig.-Verschr., nicht Bremse 360mm		
	RC34	52	-	90-150	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/45, 235/50, 245/45				Orig.-Verschr.		
6,5 x 18	RC34	42	-	90-150	195/50				Orig.-Verschr.		
7,5 x 18	RC32	50	-	90-150	205/45, 205/50, 215/45, 225/40, 225/45, 235/45				Orig.-Verschr.		
	RC34	51	-	90-150	205/45, 205/50, 215/45, 225/40, 225/45, 235/45				Orig.-Verschr.		
8 x 18	RC32	54	-	90-150	205/45, 215/45, 225/40, 225/45 , 235/40, 235/45				Orig.-Verschr., nicht Brembo-Bremse mit 360x30mm		
	RC34	54	-	90-150	205/45, 215/45, 225/40, 225/45 , 235/40, 235/45				Orig.-Verschr., nicht Brembo-Bremse mit 360x30mm		
		48	-	90-150	205/45, 215/45, 225/40, 225/45, 235/40, 235/45				Orig.-Verschr.		
8 x 19	RC34	53	-	90-150	225/40				Orig.-Verschr.		
		48	-	90-150	215/40, 225/35, 225/40, 235/35				Orig.-Verschr.		
8 x 20	RC36	46	-	90-150	225/30, 225/35				Orig.-Verschr.		
	B43	46+48	-	90-150	225/30, 225/35				Orig.-Verschr., mit M-Sportbremse, nur Bremse 360mm		

BMW 1er M135 NEU				2024		F7 / G70		5/112		66,7		e1*2018/858*00397*..	
Sensor - Brocksens 1													
Dimension		Design		ET	KIT	KW	Reifendimension			Info			
8 x 20		RC36		46	-	221	225/30, 225/35				Orig.-Verschr.		
		B43		46+48	-	221	225/30, 225/35				Orig.-Verschr.		

BMW 2er Coupé / Cabrio (siehe Konfigurator)		ab 2014		1C		5/120		72,6		e1*2007/46*0277*08-...	
BMW 2er M235i / M240i Coupé (siehe Konfigurator)				1C		5/120		72,6		e1*2007/46*0277*08-...	

BMW 2er Active Tourer (siehe Konfigurator)		ab 2014		F45/UKL-L		5/112		66,7		e1*2007/46*0371*13-..., e1*2007/46*1675*...	
---	--	---------	--	-----------	--	-------	--	------	--	---	--

BMW 225xe Active Tourer (siehe Konfigurator)				UKL-L, F2AT		5/112		66,7		e1*2007/46*0371*21-..., e1*2007/46*1675*..	
---	--	--	--	-------------	--	-------	--	------	--	--	--

BMW 225xe Active Tourer Hybrid					ab 2018	UKL-L, F2AT	5/112	66,7	e1*2007/46*0371*21-..., e1*2007/46*1675*..		
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
7,5 x 17	RC27	54	-	100	205/55					Orig.-Verschr.	

BMW 2er Active Tourer NEU		im Laufe 2022		U2AT		5/112		66,7		e1*2018/858*00117*...	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 16	RC30	41	-	90-115	205/65, 215/60, 215/65				Orig.-Verschr., nur Bremse 307mm		
	RC27	41	-	90-150	205/60, 215/55				Orig.-Verschr.		
	RC34	41	-	90-115	205/60				Orig.-Verschr.		
	RC30	47	-	100-115	205/60, 215/55, 225/55				Orig.-Verschr., nur Bremse 307mm		
	RC32	47	-	90-115	215/55, 215/60, 225/55				Orig.-Verschr.		
	RC34	47	-	90-115	215/55, 215/60, 225/55				Orig.-Verschr.		
	Pro1	49	ZP599F	90-115	215/55, 215/60, 225/55, 235/55						
7,5 x 17	RC32	52	-	90-115	215/55				Orig.-Verschr.		
	RC34	52	-	90-115	215/55				Orig.-Verschr.		

		RC32	45	-	90-115	205/60, 215/55, 215/60		Orig.-Verschr.
7,5 x 18		RC32	50	-	90-115	205/55, 225/45, 225/50 , 235/45, 245/45		Orig.-Verschr.
		RC34	50	-	90-115	205/55, 225/45, 225/50 , 235/45, 245/45		Orig.-Verschr.
		RC30	51	-	90-150	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
		RC34	51	-	90-115	225/45, 235/45		Orig.-Verschr.
		B32 / B39	51	-	90-150	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
		CA 20	51	-	90-115	225/45, 235/45		Orig.-Verschr.
		Oxigin 25	51	-	90-150	225/50, 245/45		Orig.-Verschr.
8 x 18		RC34	48	-	90-115	225/45, 235/45		Orig.-Verschr.
		B42 / B44	45	-	90-150	235/45		Orig.-Verschr.
		AC-MB6	45	-	90-150	235/45		Orig.-Verschr.
		AC-M10	45	-	90-150	235/45		Orig.-Verschr.
		FMI08 Thoe	49	-	90-115	225/45, 235/45		Orig.-Verschr.
		FMI11 Elatha	45	F93	90-115	225/45		
		FMI12 Kari	45	Kit 0334	90-115	225/45		
7,5 x 19		RC34	45,5	-	90-115	225/40, 225/45		Orig.-Verschr.
8 x 19		RC32	46	-	90-115	225/40, 225/45		Orig.-Verschr.
		RC34	46	-	90-115	225/40, 225/45		Orig.-Verschr.
		B43	46	-	100-115	225/45 , 235/40		Orig.-Verschr., nur Bremse 307mm
		RC27	47	-	90-150	225/45, 235/40		Orig.-Verschr.
		RC32	47	-	90-115	225/40, 225/45, 235/40		Orig.-Verschr.
		RC34	48	-	90-115	225/40, 225/45, 235/40		Orig.-Verschr.
		B40	47	-	100-115	225/45, 235/40		Orig.-Verschr., nur Bremse 307mm
		B43	43	-	100-115	225/45		Orig.-Verschr., nur Bremse 307mm
		CA 17	45	ZP593F	100-150	225/40, 225/45, 235/40		nicht Bremse 330mm
		CA 24	43	ZP599F	90-150	225/40, 225/45		
		Oxigin 29	43	ZP599F	90-150	225/45		
		B42	47	-	90-150	225/45		Orig.-Verschr.
8,5 x 19		AC-M10	45	-	90-150	225/45		Orig.-Verschr.
		CA 20	45	ZP599F	90-150	225/45		
		CA 23	45	ZP593F	90-150	225/45		
		Oxigin 26	45	ZP599F	100-150	225/40, 225/45		nicht Bremse 330mm
		Oxigin 28	45	ZP593F	90-150	225/45		
		CA 17	49	ZP593F	90-150	255/40		
9 x 19		CA 24	49	ZP599F	90-150	225/40		
		RC36	46	-	90-150	225/40, 235/35		Orig.-Verschr.
8 x 20		B43	46	-	90-150	225/40, 235/35		Orig.-Verschr.
			48	-	90-150	225/40, 235/35		Orig.-Verschr.
8,5 x 20		B42	45	-	100-115	225/40		Orig.-Verschr., nur Bremse 307mm
			48	-	90-150	225/40, 235/35		Orig.-Verschr.
		CA 17	48	ZP599F	90-150	225/40, 235/35		
		AC-MB6	50	-	90-150	225/40, 235/35		Orig.-Verschr.

BMW 2er Active Tourer PHEV NEU	im Laufe 2023	U2AT	5/112	66,7	e1*2018/858*00117*...
--	----------------------	-------------	--------------	-------------	-----------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 16	RC30	41	-	100	205/65	 Orig.-Verschr., nur Bremse 307mm
7 x 17	RC27	41	-	100, 110	205/60	 Orig.-Verschr.
7,5 x 18	RC30	51	-	100, 110	205/55, 215/50, 225/50, 235/45, 245/45	Orig.-Verschr.
	B32 / B39	51	-	100, 110	205/55, 215/50, 225/50, 235/45, 245/45	Orig.-Verschr.
8 x 18	B42 / B44	45	-	100, 110	235/45	Orig.-Verschr.
	AC-MB6	45	-	100, 110	235/45	Orig.-Verschr.
	AC-M10	45	-	100, 110	235/45	Orig.-Verschr.
8 x 19	RC34	46	-	90-115	225/45	 Orig.-Verschr.
	B43	46	-	100, 110	225/45	 Orig.-Verschr.
	RC27	47	-	100, 110	225/45, 235/40	Orig.-Verschr.
	FMI08 Thoe	47	-	90-115	225/40, 225/45, 235/40	Orig.-Verschr.
	Oxigin 29	43	ZP599F	100, 110	225/45	
8,5 x 19	B42	47	-	100, 110	225/45	Orig.-Verschr.
	AC-M10	45	-	100, 110	225/45	Orig.-Verschr.
	CA 20	45	ZP599F	100, 110	225/45	
	CA 23	45	ZP593F	100, 110	225/45	
	Oxigin 28	45	ZP593F	100, 110	225/45	
8 x 20	RC36	46	-	100, 110	225/40	Orig.-Verschr.
	B43	46+48	-	100, 110	225/40	Orig.-Verschr.
8,5 x 20	B42	48	-	100, 110	225/40	Orig.-Verschr.
	AC-MB6	50	-	100, 110	225/40	Orig.-Verschr.

BMW 2er Grand Tourer (siehe Konfigurator)	ab 2014	F46/UKL-L	5/112	66,7	e1*2007/46*0371*18-..., e1*2007/46*1677*...
---	----------------	------------------	--------------	-------------	---

BMW 2er Active Tourer, Grand Tourer	F2AT	5/112	66,7	e1*2007/46*1675*...
--	-------------	--------------	-------------	---------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 17	RC34	52	-	100	205/55	 Orig.-Verschr.

BMW 2er Coupe NEU			ab 2022		G2C	5/112	66,7	e1*2018/858*00123*..	
Sensor - Brocksens 1									
Dimension		Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC32	30	-	115-180	225/50, 235/50			Orig.-Verschr.	
	CA 20	30	ZP599F	115-180	225/50, 235/45, 245/45			Orig.-Verschr., nicht Bremse 348x36 u. 374mm	
	RC32	27	-	115-180	225/50			Orig.-Verschr.	
7,5 x 18	RC34	VA 25	-	115-180	VA 225/45			Orig.-Verschr.	
8,5 x 18		HA 40			HA 255/40				
7,5 x 18	RC32	23+25	-	115-180	225/45			Orig.-Verschr.	
	RC34	25	-	115-180	225/45			Orig.-Verschr.	
	B32	25	-	115-180	225/45			Orig.-Verschr., nicht Bremse 374mm	
8 x 18	RC27	30	-	115-180	225/45, 235/40, 245/40HA			Orig.-Verschr.	
	RC32	30	-	115-180	225/45			Orig.-Verschr.	
	RC34	30	-	115-180	225/45			Orig.-Verschr.	
	B42	30	-	115-180	225/45, 235/40, 245/40HA			Orig.-Verschr.	
	B44	30	-	115-180	225/45, 235/40, 245/40HA			Orig.-Verschr.	
	AC-M10	30	-	115-180	225/45, 235/40, 245/40HA			Orig.-Verschr., nicht Bremse 374mm	
	AC-MB6	29	-	115-180	225/45, 235/40, 245/40HA			Orig.-Verschr., nicht Bremse 374mm	
	CA 20	30	ZP599F	115-180	225/45, 235/40, 245/40HA				
	CA 23 / CA 26	30	ZP599F	115-180	225/45, 235/40, 245/40HA			nicht Bremse 374mm	
	FMI08 Thoe	26	-	115-180	225/45			Orig.-Verschr.	
	FMI11 Elatha	26	F93	115-180	225/45				
	FMI12 Kari	26	Kit 0334	115-180	225/45				
7,5 x 19	RC34	32	-	120-180	225/40			Orig.-Verschr.	
8 x 19	RC34	VA 27	-	115-180	VA 225/40			Orig.-Verschr.	
8,5 x 19		HA 40			HA 255/35				
8 x 19	B43	VA 27	-	115-180	VA 225/40, 245/35			Orig.-Verschr.	
8,5 x 19		HA 40			HA 245/35, 255/35				
8 x 19	RC32	30	-	115-180	225/40			Orig.-Verschr.	
	B40	30	-	115-180	225/40, 235/35, 245/35HA			Orig.-Verschr.	
	B43	28	-	115-180	225/40, 235/35, 245/35HA			Orig.-Verschr.	
	FMI08 Thoe	26	-	115-180	225/40			Orig.-Verschr.	
	FMI14 Jupiter	26	-	115-180	225/40			Orig.-Verschr.	
8,5 x 19	RC32	29	-	115-180	225/40			Orig.-Verschr.	
	RC34	26+29	-	115-180	225/40			Orig.-Verschr.	
	B32	25	-	115-180	225/40			Orig.-Verschr.	
	B41	28+29	-	115-180	225/40			Orig.-Verschr.	
	B42	30	-	115-180	225/40			Orig.-Verschr.	
	B43	25+29	-	115-180	225/40			Orig.-Verschr.	
	B44	25+30	-	115-180	225/40			Orig.-Verschr.	
	AC-MB6	30	-	115-180	225/40			Orig.-Verschr.	
	AC-M10	30	-	115-180	225/40			Orig.-Verschr.	
	CA 23	30	ZP599F	115-180	225/40				
	Oxigin 28	30	ZP599F	115-180	225/40				
	8300 - 1972	32	-	115-180	225/40			Orig.-Verschr.	
8 x 20	RC36	VA 27	-	115-180	VA 225/35			Orig.-Verschr.	
8,5 x 20		HA 40			HA 255/30				
8 x 20	B43	VA 27	-	115-180	VA 225/35			Orig.-Verschr.	
8,5 x 20		HA 40			HA 255/30				
8 x 20	B43	27+30	-	115-180	225/35			Orig.-Verschr.	
8,5 x 20	B41	20	-	115-180	225/35			Orig.-Verschr.	
	B42	30	-	115-180	225/35			Orig.-Verschr.	
	B43	28+30	-	115-180	225/35			Orig.-Verschr.	
	B44	25+30	-	115-180	225/35			Orig.-Verschr.	
	AC-M10	30	-	115-180	225/35			Orig.-Verschr.	

Kombinationen

8 x 19	RC34	VA 27	-	115-180	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8,5 x 19	B41	VA 29	-	115-180	VA 225/40		Orig.-Verschr.
9 x 19		HA 41			HA 255/35		
8 x 20	B43	VA 27	-	115-180	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		

BMW M240i NEU		ab 2022		G2C	5/112	66,7	e1*2018/858*00123*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC34	VA 25		275	VA 225/45		i.V.	
8,5 x 18		HA 40			HA 255/40			
8 x 18	RC27	30	-	275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S	
	B42	30	-	275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S	
	B44	30	-	275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S	
	CA 20	30	ZP599F	275	225/45, 235/40, 245/40HA		nur M+S	

8 x 19	B43	VA 27	-	275	VA 225/40, 245/35		Orig.-Verschr.
8,5 x 19		HA 40			HA 245/35, 255/35		
8 x 19	B40	30	-	275	225/40, 235/35, 245/35HA		Orig.-Verschr., nur M+S
	B43	28	-	275	225/40, 235/35, 245/35HA		Orig.-Verschr., nur M+S
8,5 x 19	B42	30	-	275	225/40, 245/35, 255/35		Orig.-Verschr., HA ✖
	B43	29	-	275	225/40		Orig.-Verschr.
	B44	25	-	275	225/40		Orig.-Verschr.
		30	-	275	225/40, 245/35HA, 255/35HA		Orig.-Verschr., HA ✖
	AC-MB6	30	-	275	225/40, 245/35HA, 255/35HA		Orig.-Verschr., HA ✖
	AC-M10	30	-	275	225/40, 245/35HA, 255/35HA		Orig.-Verschr., HA ✖
	Oxigin 28	30	ZP599F	275	225/40		
8 x 20	RC36	VA 27	-	275	VA 225/35		Orig.-Verschr., auch mit M-Technik-Paket, mit Radlauf-Verbreiterungen
8,5 x 20		HA 40			HA 255/30		
8 x 20	B43	VA 27	-	275	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		
8 x 20	RC36	27	-	275	225/35		Orig.-Verschr., nur M+S
	B43	27+30	-	275	225/35		Orig.-Verschr., nur M+S
8,5 x 20	B42	30	-	275	225/35		Orig.-Verschr., nur M+S
	B43	28	-	275	225/35		Orig.-Verschr., nur M+S
				275	VA 225/35+HA 255/30		Orig.-Verschr., mit M-Technik-Paket
		30	-	275	225/35		Orig.-Verschr., nur M+S
	B44	25+30	-	275	225/35		Orig.-Verschr.

Kombinationen

8 x 20	B43	VA 27	-	275	VA 225/35		Orig.-Verschr., mit M-Technik-Paket, mit Radlaufverbreiterungen
8,5 x 20		HA 40			HA 255/30		

BMW 2er Gran Coupe/2er xDrive Gran Coupe					ab 2020	F2GC	5/112	66,7	e1*2007/46*2064*..
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 16	Pro1	48	F93	85-110	195/55, 195/60, 205/55			nur M+S	
7 x 16	RC30	52	-	85-110	195/60M+S, 205/55, 215/55			Orig.-Verschr.	
6,5 x 17	RC27	45	-	85-140	195/55, 205/50			Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	RC32	47	-	85-140	195/55			Orig.-Verschr., nicht Bremse 360x30mm	
7 x 17	RC34	47	-	85-140	195/50M+S, 195/55, 205/45, 215/45			Orig.-Verschr., nicht Bremse 360x30mm	
	CA 26	47	ZP599F	85-140	195/55M+S			nicht Bremse 360mm	
	RC27	54	-	85-110	205/50, 215/50, 225/45			Orig.-Verschr., nicht Bremse 360mm	
				85-140	195/55, 205/50, 215/50, 225/45			Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	Pro1	49	ZP599F	85-140	205/45, 205/50, 215/45, 225/45			Orig.-Verschr., nicht Bremse 360x30mm	
	CA 26	54	ZP599F	85-110	205/50, 215/50, 225/45			nicht Bremse 360mm	
				85-140	195/55, 205/50, 215/50, 225/45			nur M+S, nicht Bremse 360mm	
7,5 x 17	RC27	54	-	85-140	225/45			Orig.-Verschr., nicht Bremse 360mm	
	RC32	54	-	85-140	205/45, 205/50, 215/45, 215/50, 225/45, 235/45			Orig.-Verschr., nicht Bremse 360x30mm	
	RC34	52	-	85-140	205/45, 205/50, 215/45, 225/45			Orig.-Verschr., nicht Bremse 360x30mm	
		45	-	85-140	205/45			Orig.-Verschr., nicht Bremse 360x30mm	
		52	-	85-140	205/45, 205/50, 215/45, 225/45			Orig.-Verschr., nicht Bremse 360x30mm	
6,5 x 18	Oxigin 25	54	ZP599F	85-140	205/50, 215/50, 225/45, 235/45			nicht für M-Sportbremse	
	RC34	41	-	85-225	205/45			Orig.-Verschr.	
7,5 x 18	RC30	51	-	85-225	205/45, 215/45, 225/40			Orig.-Verschr., nicht Bremse 360mm	
	RC32	50	-	85-225	205/40, 205/45, 215/40			Orig.-Verschr.	
	RC34	50	-	85-225	205/40, 205/45, 215/40			Orig.-Verschr.	
		51	-	85-225	205/40, 205/45, 215/40, 225/35, 225/40			Orig.-Verschr.	
	B32 / B39	51	-	85-110	205/45, 215/45			Orig.-Verschr., nicht Bremse 360mm	
				85-140	225/40				
				85-225	205/45, 215/45, 225/40			Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	CA 20	51	-	85-225	205/40, 205/45, 215/40, 225/35, 225/40			Orig.-Verschr., nicht Bremse 330x24mm VA u. 300x20mm HA	
8 x 18	RC32	54	-	85-225	205/40, 205/45, 215/40, 225/35, 225/40			Orig.-Verschr., auch ET54 ist ECE	
		57	-	85-140	225/40			Orig.-Verschr.	
				85-225	205/40, 205/45, 215/40, 225/35, 225/40			Orig.-Verschr.	
	RC34	54	-	85-225	205/40, 205/45, 215/40, 225/35, 225/40			Orig.-Verschr., auch ET54 ist ECE	
	RC29	57	-	85-110	215/45, 235/40			Orig.-Verschr., nicht Bremse 360mm	
				85-225	215/45M+S, 225/40				
	B37	54	-	85-110	215/45			Orig.-Verschr., nicht Bremse 360mm	
				85-225	215/45M+S, 225/40				
	AC-518	50	-	85-110	215/45			Orig.-Verschr., nicht Bremse 360mm	
8 x 19	FMI08 Thoe	49	-	85-225	215/45M+S			Orig.-Verschr., nicht Bremse 360mm	
				85-225	205/40, 205/45			Orig.-Verschr.	
	B43	54	-	85-225	235/35			Orig.-Verschr. nicht Bremse 360 mm VA	
				85-140	225/35				
				100, 103	215/35				
	RC29	57	-	131	225/35			Orig.-Verschr., nicht Bremse ab 330mm, bei 245/30 ✖	
				85-140	225/35, 245/30				
	RC32	57	-	85-225	225/35			Orig.-Verschr., nicht Bremse 360x30mm VA u.	

ROSE	37		33 229	229/33		330x20mm HA
------	----	--	--------	--------	--	-------------

BMW 3er / Kombi (siehe Konfigurator)	ab 02.12	F30/ 3L F31/ 3K	5/120	72,6	Limo: e1*2007/46*0314*05-..., e1*2007/46*0315*06, e24*2007/46*0022*03...	Kombi:
---	-----------------	------------------------	--------------	-------------	---	--------

BMW 3er	ab 03.2019	G3L (G20) / G3K (G21)	5/112	66,7	e1*2007/46*1947*..., e1*2007/46*2017*...	
----------------	-------------------	------------------------------	--------------	-------------	--	--

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	22	-	85-140	205/60 , 215/60, 225/55	 Orig.-Verschr.
	RC32	22	-	85-140	205/60 , 215/55, 215/60	 Orig.-Verschr.
	RC34	22	-	85-140	205/60 , 215/60	 Orig.-Verschr., Heckantrieb
7,5 x 17	RC32	30	-	85-210	205/55, 215/50, 215/55, 225/50 , 235/45, 245/45	 Orig.-Verschr.
	BR-I	30	-	100-195	225/50	 Orig.-Verschr., nicht Bremse 348 u. 374mm
	CA 20	30	ZP593F	85-210	225/50	 nicht Bremse 348x30 u. 348x36mm
	RC27	27	-	85-140	205/55, 215/50	
				85-210	225/50, 245/45	
	RC32	27	-	85-210	205/55, 215/50, 215/55, 235/45	Orig.-Verschr., Heckantrieb
				120-210	235/45	
	Oxigin 25	35	ZP599F	85-275	225/50, 235/45, 245/45	nicht Bremse 348mm, nicht Brembo u. M-Sportbremse
7 x 18	RC32	22	-	85-140	205/50, 215/45, 225/45	Orig.-Verschr.
7,5 x 18	RC34	VA 25 HA 40	-	85-210	VA 225/45	 Orig.-Verschr.
8,5 x 18					HA 255/40	
7,5 x 18	RC32	25	-	85-210	205/50, 215/45, 225/45	 Orig.-Verschr.
				120-210	225/45	 Orig.-Verschr., Allrad
	RC34	25	-	85-210	225/45	 Orig.-Verschr., Heckantrieb
				120-210	225/45	 Orig.-Verschr., Allrad
	B32	25	-	85-210	225/45	 Orig.-Verschr., nicht Bremse 374mm
				85-140	215/45	
	BR-I	25	-	100-195	225/45	 Orig.-Verschr., nicht Bremse 374mm
	Oxigin 25	25	-	85-275	225/45	 Orig.-Verschr.
	RC34	25	-	85-210	205/50, 215/45, 225/45	 Orig.-Verschr., Heckantrieb
				120-210	225/45	
	RC32	23	-	85-210	205/50, 215/45, 225/45	Orig.-Verschr., Heckantrieb
				120-210	225/45	
8 x 18	RC27	30	-	100-275	225/45, 235/40	Orig.-Verschr., nicht zulässig mit 18" Sportbremse
	RC32 / RC34	30	-	85-210	215/45, 225/45, 235/40, 235/45	Orig.-Verschr., Heckantrieb
				120-210	225/45, 235/40, 235/45	
	B42	30	-	85-140	215/45	Orig.-Verschr.
				85-210	225/45, 235/40, 245/40HA	
	B44	30	-	85-140	215/45	Orig.-Verschr.
				85-210	225/45, 235/40, 245/40HA	
	AC-M10	30	-	85-140	215/45	Orig.-Verschr., nicht Bremse 374mm
				85-210	225/45, 235/40, 245/40HA	
	AC-MB6	29	-	85-140	215/45	Orig.-Verschr., nicht Bremse 374mm
				85-210	225/45, 235/40, 245/40HA	
	CA 17	35	ZP593F	100-275	225/45, 235/40	nur G3L, nicht für Fahrzeuge mit 18" Sportbremse
	CA 23 / CA 26	30	ZP599F	85-140	215/45	nicht Bremse 374mm
				85-210	225/45, 235/40, 245/40HA	
	FMI08 Thoe	26	-	85-210	215/45, 225/45	Orig.-Verschr., Heckantrieb
				120-210	225/45	
	FMI11 Elatha	26	F93	85-210	215/45, 225/45	Heckantrieb
				120-210	225/45	
8,5 x 18	Oxigin 20	35	ZP599F	120-195	225/45, 235/40	Typ G3K , nicht für Fahrzeuge mit 18" Sportbremse
				100-275	225/45, 235/40	Typ G3L , nicht Bremse 348mm
7,5 x 19	RC34	32	-	85-210	225/40	Orig.-Verschr.
8 x 19	RC34	VA 27 HA 40	-	85-210	VA 225/40	 Orig.-Verschr.
8,5 x 19					HA 255/35	
8 x 19	B43	VA 27 HA 40	-	85-210	VA 225/40	 Orig.-Verschr.
8,5 x 19					HA 255/35	
8 x 19	BR-I	VA 27 HA 40	-	85-210	VA 225/40	 Orig.-Verschr.
8,5 x 19					HA 255/35	
8 x 19	RC27	30	-	100-275	225/40, 235/40	Orig.-Verschr., nicht zulässig mit 18" Sportbremse
	RC32	30	-	85-210	225/40, 235/35, 235/40	Orig.-Verschr., auch für Hybrid
	RC34	27	-	85-195	225/40	Orig.-Verschr.
	B40	30	-	85-210	225/40, 235/35, 245/35HA	Orig.-Verschr., Typ G3K nicht 235/35
	B43	28	-	85-210	225/40, 235/35	Orig.-Verschr., Typ G3K nicht 235/35
	BR-I	27	-	85-195	225/40, 235/35	Orig.-Verschr., nicht Bremse 374mm, Typ G3L
				100-195	225/40	
	CA 24	30	ZP599F	85-275	225/40, 235/40	Orig.-Verschr., nicht Bremse 374mm, Typ G3K
	FMI08 Thoe	26	-	85-210	225/40	Orig.-Verschr.
	RC32	29	-	85-210	225/40	Orig.-Verschr.

7,5 x 18	B32	25	-	120-135	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 245/40, 255/40		
8 x 19	B40	27	-	120-135	VA 225/40, 235/35, 245/35		Orig.-Verschr., bei 275/30 ✖
9 x 19		40			HA 255/35, 275/30		
8 x 20	B40	27	-	120-135	VA 225/35		Orig.-Verschr., HA bei 265/30 ✖
9 x 20		40			HA 265/30		

BMW M340i xDrive							
ab 2019				G3L (G20)	5/112	66,7	e1*2007/46*1947*..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC32	30	-	250-275	225/50, 235/45, 245/45		Orig.-Verschr., nur M+S
		27	-	250-275	235/45		Orig.-Verschr., nur M+S
	RC27	27	-	250, 275	225/50, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
7,5 x 18	RC34	VA 25		250-275	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 40			HA 255/40		
7,5 x 18	B32	25	-	250, 275	225/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	RC32 / RC34	25	-	250-275	225/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	RC32	23	-	250-275	225/45		Orig.-Verschr., nur M+S
8 x 18	RC27	30	-	250, 275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S
	RC32	30	-	250-275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	RC34	30	-	250-275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	B42	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B44	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	AC-M10	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	CA 23 / CA 26	30	ZP599F	250, 275	225/45, 235/40, 245/40HA		nicht Bremse 374mm
	FMI11 Elatha	26	F93	250-275	225/45		Orig.-Verschr., nur M+S, nicht Bremse 374x36mm VA u. 345x24mm HA
7,5 x 19	RC34	32	-	250-275	225/40		Orig.-Verschr., nur M+S
8 x 19	RC34	VA 27	-	250-275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	B43	VA 27	-	250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	BR-I	VA 27	-	250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	RC32	30	-	250-275	225/40, 235/35, 245/35		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	B40	30	-	275	225/40, 235/35, 245/35		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	B43	28	-	250, 275	225/40		Orig.-Verschr., nur M+S
				275	235/35		
	BR-I	27	-	275	225/40, 235/35		Orig.-Verschr., nur M+S, nicht Bremse 374mm
8,5 x 19	FMI08 Thoe	26	-	250-275	225/40		Orig.-Verschr., nur M+S
	B42	30	-	250, 275	225/40, 245/35M+S, 255/35		Orig.-Verschr., ab 245/35 ✖
				275	235/35		Orig.-Verschr., nur M+S
	B43	29	-	250, 275	225/40, 245/35M+S, 255/35		Orig.-Verschr., ab 245/35 ✖
				275	235/35		Orig.-Verschr., nur M+S
	B44	30	-	250, 275	225/40, 245/35HA M+S, 255/35HA		Orig.-Verschr., ab 245/35 ✖
				275	235/35		Orig.-Verschr., nur M+S
	AC-MB6 / AC-M10	30	-	250, 275	225/40, 245/35HA M+S, 255/35HA		Orig.-Verschr., ab 245/35 ✖
				275	235/35		Orig.-Verschr., nur M+S
	Oxigin 28	30	ZP593F	250, 275	225/40, 245/35M+S, 255/35		ab 245/35 ✖
				275	235/35		nur M+S
8 x 20	RC36	VA 27	-	250, 275	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		
8 x 20	B43	VA 27	-	250, 275	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		
8,5 x 20	RC29	26	-	275	VA 225/35+HA 255/30		Orig.-Verschr., nicht Bremse 374mm, HA ✖
	B42	30	-	250, 275	VA 225/35+HA 255/30		Orig.-Verschr., HA ✖

Kombinationen

7,5 x 18	B32	25	-	250, 275	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 255/40		
8 x 19	B40	27	-	250, 275	VA 225/40, 235/35, 245/35		Orig.-Verschr., bei 275/30 ✖
9 x 19		40			HA 255/35, 275/30		
8 x 19	FMI08 Thoe	26	-	250-275	VA 225/40+HA 255/35		Orig.-Verschr., nicht Bremse 374x36mm
9 x 19		41					
8 x 20	B40	27	-	250, 275	VA 225/35+HA 255/30		Orig.-Verschr., HA ✖
9 x 20		40					
8 x 20	FMI08 Thoe	26	-	250-275	VA 225/35+HA 255/30		Orig.-Verschr., nicht Bremse 374x36mm
9 x 20		41					
8,5 x 20	B42	30	-	250, 275	VA 225/35+HA 255/30		Orig.-Verschr.
9,5 x 20		42					

BMW M340i xDrive Touring							
ab 2019				G3K	5/112	66,7	e1*2007/46*2017*..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

7,5 x 17	RC32	30	-	250-275	225/50, 235/45, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
		27	-	250-275	235/45		Orig.-Verschr., nur M+S
	RC27	27	-	250, 275	225/50, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
7,5 x 18	RC34	VA 25		250-275	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 40			HA 255/40		
7,5 x 18	B32	25	-	250, 275	225/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	RC32	25	-	250-275	225/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
8 x 18	RC27	30	-	250, 275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S
	RC32	30	-	250-275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	RC34	30	-	250-275	225/45, 235/40, 235/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	B42	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B44	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	AC-M10	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	CA 23 / CA 26	30	ZP599F	250, 275	225/45, 235/40, 245/40HA		nicht Bremse 374mm
7,5 x 19	RC34	32	-	250-275	225/40		Orig.-Verschr., nur M+S
8 x 19	RC34	VA 27		250-275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	B43	VA 27		250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	BR-I	VA 27		250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
7,5 x 19	RC32	32	-	250-275	225/40		Orig.-Verschr., nur M+S, nicht Bremse 374mm
8 x 19	RC32	30	-	250-275	225/40, 235/35, 245/35		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	FMI08 Thoe	26	-	250-275	225/40		Orig.-Verschr., nur M+S
	B42 / B44	30	-	250, 275	VA 225/40+HA 255/35		Orig.-Verschr., bei 255/35 ✖
8,5 x 19	B43	29	-	250, 275	VA 225/40+HA 255/35		Orig.-Verschr., bei 255/35 ✖
	AC-MB6 / AC-M10	30	-	250, 275	VA 225/40+HA 255/35		Orig.-Verschr., bei 255/35 ✖

Kombinationen

7,5 x 18	B32	25	-	250, 275	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 255/40		
8 x 19	B40	27	-	250, 275	VA 225/40, 235/35, 245/35		Orig.-Verschr., bei 275/30 ✖
9 x 19		40			HA 255/35, 275/30		
8 x 19	FMI08 Thoe	26	-	250-275	VA 225/40+HA 255/35		Orig.-Verschr., nicht Bremse 374x36mm
9 x 19		41					
8 x 20	FMI08 Thoe	26	-	250-275	VA 225/35+HA 255/30		Orig.-Verschr., nicht Bremse 374x36mm
9 x 20		41					

BMW M2 Coupé		ab 2016		F87	5/120	72,6	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 19	Race LS	42	14x1,5x40	272	245/35		+751207411006 +2ZR 10 mm Spurverbr. VA+HA
	Fascinate	38	14x1,5x35	272	245/35		+751207410504 5 mm Spurverbr. VA+HA
9 x 20	B37	25	-	272, 302	245/30		Orig.-Verschr., nur M+S, nur Bremse 380mm

Kombinationen

8,5 x 19	Race LS	42	14x1,5x40	272	VA245/35+HA265/35		+751207411006 +2ZR 10 mm Spurverbr.VA
9,5 x 19		42	14x1,5x35				+751207410504 5 mm Spurverbr. HA
8,5 x 19	Fascinate	38	14x1,5x35	272	VA245/35+HA265/35		+751207410504 5 mm Spurverbr. VA+HA
9,5 x 19		42					
8,5 x 20	GTS 2	35	14x1,5x35	272	VA245/30+HA265/30		+751207410504 5 mm Spurverbr. VA+HA
10 x 20		46					

BMW M2 NEU		ab 2023		G2M	5/112	66,7	e1*2018/858*00211*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
9 x 19	B40	VA 20	-	338, 353	VA+HA 275/35		Orig.-Verschr., nur Bremse 380mm u. nicht Keramikbremse	
9,5 x 19		HA 20						
9,5 x 19	B40	VA 20	-	338, 353	VA 275/35+HA 285/30		Orig.-Verschr., nur Bremse 380mm u. nicht Keramikbremse, Achtung - unterschiedliche Zollgrößen an VA u. HA!	
10,5 x 20		HA20						

BMW M3, M4		ab 2015	M3/F80, M4/F82/F83	5/120	72,6	e1*2007/46*0377*06-	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	B37	25	-	317, 332	255/30		Orig.-Verschr., nur M+S, nicht Keramikbremse

Kombinationen

8,5 x 19	B32	VA 30	-	317	VA 255/35M+S		Orig.-Verschr., nicht Keramik Bremse
9,5 x 19		HA 25			HA 255/35M+S		

BMW M3, M4 NEU		2023		G234M	5/112	66,6	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 19	B40	VA 20	-	352, 390	VA+HA 275/35M+S		Orig.-Verschr., nur Bremse 380mm u. nicht

9,5 x 19	B40	HA 20		353-390	VA 275/35+HA 285/30		Keramikbremse
9,5 x 19		VA 20					Orig.-Verschr., nur Bremse 380mm u. nicht
10,5 x 20		HA20	-	353-390	VA 275/35+HA 285/30		Keramikbremse, Achtung - unterschiedliche Zollgrößen an VA u. HA!

BMW 4er REIHE (siehe Konfigurator)	ab 2013	F32 / F33/ 3C	5/120	72,6	e1*2007/46*0316*08-... e1*2007/46*0316*09
---	---------	---------------	-------	------	---

BMW 4er Gran Coupé (siehe Konfigurator)	ab 2013	F36 / 3C	5/120	72,6	e1*2007/46*0316*10-...
--	---------	----------	-------	------	------------------------

BMW 4er Coupe / Cabrio	ab März 2021	G3C	5/112	66,7	e1*2007/46*2126*..
-------------------------------	--------------	-----	-------	------	--------------------

Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC32	30	-	120-275	225/50		Orig.-Verschr.
	CA 20	30	ZP593F	120-210	225/50, 245/45		nicht Bremse 374mm u. nicht 348x30 u. 348x36mm
	RC27	27	-	120-210	225/50, 245/45		Orig.-Verschr., nicht Bremse 374mm
7,5 x 18	RC34	VA 25		120-210	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 40			HA 255/40		
7,5 x 18	B32	25	-	120-210	225/45		Orig.-Verschr., nicht Bremse 374mm
	RC34	25	-	120-210	225/45		Orig.-Verschr.
	Oxigin 25	25	-	120-175	225/45		Orig.-Verschr.
	RC32	25	-	120-210	225/45		Orig.-Verschr.
8 x 18	RC27	30	-	120-210	225/45, 235/40, 245/40HA		Orig.-Verschr.
	RC34	30	-	120-275	225/45		Orig.-Verschr.
	B42	30	-	120-210	225/45, 235/40, 245/40HA		Orig.-Verschr.
	B44	30	-	120-210	225/45, 235/40, 245/40HA		Orig.-Verschr.
	AC-M10	30	-	120-210	225/45, 235/40, 245/40HA		Orig.-Verschr., nicht Bremse 374mm
	CA 20	30	ZP593F	120-210	225/45, 235/40, 245/40HA		
	CA 23 / CA 26	30	ZP599F	120-210	225/45, 235/40, 245/40HA		nicht Bremse 374mm
7,5 x 19	RC32	32	-	120-275	225/40		Orig.-Verschr.
	RC34	32	-	120-210	225/40		Orig.-Verschr.
8 x 19	RC34	VA 27	-	120-210	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	B43	VA 27	-	120-210	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	BR-I	VA 27	-	120-210	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	RC32	30	-	120-210	225/40		Orig.-Verschr.
	B40	30	-	120-210	225/40, 235/35, 245/35		Orig.-Verschr., Coupe
				120-180	225/40, 245/35HA		Orig.-Verschr., Cabrio
	B43	28	-	120-210	225/40, 235/35		Orig.-Verschr., Coupe
				120-180	225/40		Orig.-Verschr., Cabrio
8,5 x 19	CA 24	30	ZP599F	120-275	225/40		
	B43	29	-	120-210	225/40, 235/35		Orig.-Verschr., Coupe
				120-210	225/40		Orig.-Verschr., Cabrio
	B44	30	-	120-210	225/40, 235/35		Orig.-Verschr., Coupe
				120-210	225/40		Orig.-Verschr., Cabrio
	AC-MB6	30	-	120-210	225/40, 235/35		Orig.-Verschr., Coupe
				120-210	225/40		Orig.-Verschr., Cabrio
	AC-M10	30	-	120-210	225/40, 235/35		Orig.-Verschr., Coupe
				120-210	225/40		Orig.-Verschr., Cabrio
	CA 23	30	ZP593F	120-210	225/40, 235/35		Coupe
				120-210	225/40		Cabrio
	Oxigin 28	30	ZP593F	120-210	225/40, 235/35		Coupe
				120-210	225/40		Cabrio
	8300 - 1972	32	-	120-210	225/40		Orig.-Verschr.
8 x 20	RC36	VA 27	-	120-210	VA 225/35		Orig.-Verschr., nur Coupe
8,5 x 20		HA 40			HA 255/30		
8 x 20	B43	VA 27	-	120-210	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		
8 x 20	B40	27	-	120-210	225/35		Orig.-Verschr.
	B43	27+30	-	120-210	225/35		Orig.-Verschr., nur Coupe

Kombinationen

7,5 x 18	B32	25	-	120-210	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 245/40, 255/40		
8 x 19	FMI08 Thoe	26	-	120-275	VA+HA 235/35, 245/35		Orig.-Verschr.
9 x 19		41					
8 x 20	B40	27	-	120-210	VA 225/35		Orig.-Verschr., HA bei 265/30 ✖
9 x 20		40			HA 255/30, 265/30		
8 x 20	FMI08 Thoe	26	-	120-275	VA+HA 245/30		Orig.-Verschr.
9 x 20		41					

BMW M440 i/d Coupe NEU	2021	G3C	5/112	66,7	e1*2007/46*2126*..
--	------	-----	-------	------	--------------------

Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	27	-	250, 275	225/50, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
7,5 x 18	RC34	VA 25		250-275	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 40			HA 255/40		
7,5 x 18	RC34	25	-	250-275	225/45		Orig.-Verschr.
	B32	25	-	250, 275	225/45M+S		Orig.-Verschr., nicht Bremse 374mm
8 x 18	RC27	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B42	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B44	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	AC-M10	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	CA 20	30	ZP593F	250, 275	225/45, 235/40, 245/40HA		nur M+S
	CA 26	30	ZP599F	250, 275	225/45, 235/40, 245/40HA		nur M+S, nicht Bremse 374mm
7,5 x 19	RC34	32	-	250-275	225/40		Orig.-Verschr., nur M+S
8 x 19	B43	28	-	250, 275	225/40, 235/35		Orig.-Verschr., nur M+S
	B43	29	-	250, 275	225/40, 235/35M+S		Orig.-Verschr.
	B44	30	-	250, 275	225/40, 235/35M+S, 245/35HA M+S, 255/35HA		Orig.-Verschr., ab 245/35 ✖
	AC-MB6 / AC-M10	30	-	250, 275	225/40, 235/35M+S, 245/35HA M+S, 255/35HA		Orig.-Verschr., ab 245/35 ✖
	Oxigin 28	30	ZP593F	250, 275	225/40, 235/35M+S		
8 x 19	RC34	VA 27	-	250-275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	B43	VA 27	-	250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	BR-I	VA 27	-	250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 20	RC36	VA 27	-	250, 275	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		
8 x 20	B43	VA 27	-	250, 275	VA 225/35		Orig.-Verschr.
8,5 x 20		HA 40			HA 255/30		

Kombinationen

7,5 x 18	B32	25	-	250, 275	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 245/40M+S, 255/40		
8 x 20	B40	27	-	250, 275	VA 225/35+HA 265/30		Orig.-Verschr., HA ✖
9 x 20		40					

BMW M440 i xDrive Cabrio NEU 2021 G3C 5/112 66,7 e1*2007/46*2126*..							
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	27	-	250, 275	225/50, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 374mm
7,5 x 18	B32	25	-	275	225/45M+S		Orig.-Verschr., nicht Bremse 374mm
7,5 x 18	RC34	VA 25		250-275	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 40			HA 255/40		
8 x 18	RC27	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B42	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	B44	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S
	AC-M10	30	-	250, 275	225/45, 235/40, 245/40HA		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	CA 20	30	ZP593F	250, 275	225/45, 235/40, 245/40HA		nur M+S
	CA 26	30	ZP599F	250, 275	225/45, 235/40, 245/40HA		nur M+S, nicht Bremse 374mm
7,5 x 19	RC34	32	-	250-275	225/40		Orig.-Verschr., nur M+S
8 x 19	B43	28	-	275	225/40		Orig.-Verschr., nur M+S
	B43	29	-	250, 275	225/40		Orig.-Verschr.
8,5 x 19	B44	30	-	250, 275	225/40, 255/35HA		Orig.-Verschr., bei 255/35 ✖
				275	225/40, 245/35HA		Orig.-Verschr., nur M+S, bei 245/35 ✖
	AC-MB6 / AC-M10	30	-	250, 275	225/40, 255/35HA		Orig.-Verschr., bei 255/35 ✖
				275	225/40, 245/35HA		Orig.-Verschr., nur M+S, bei 245/35 ✖
	Oxigin 28	30	ZP593F	250, 275	225/40		
8 x 19	RC34	VA 27	-	250-275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	B43	VA 27	-	250, 275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		
8 x 19	BR-I	VA 27	-	275	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/35		

Kombinationen

7,5 x 18	B32	25	-	275	VA 225/45		Orig.-Verschr., nicht Bremse 374mm
8,5 x 18		40			HA 245/40M+S, 255/40		
8 x 20	B40	27	-	250, 275	VA 225/35+HA 265/30		Orig.-Verschr., HA ✖
9 x 20		40					

BMW 4er Gran Coupe NEU 2021 G4C 5/112 66,7 e1*2018/858*00122*..							
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
	RC32	30	-	120-210	225/55		Orig.-Verschr.

7,5 x 17	CA 20	30	ZP593F	120-210	225/55, 235/50		nicht Bremse 348x36mm u. nicht 348x30mm VA u. 330x20mm HA
	RC27	27	-	120-210	225/55		Orig.-Verschr.
	CA 20	35	ZP599F	120-210	225/55, 235/50, 245/50		nicht Bremse 348x36mm u. nicht 348x30mm VA u. 330x20mm HA
7,5 x 18	RC32	23	-	120-210	225/45		Orig.-Verschr.
		25	-	120-210	225/45, 235/45		Orig.-Verschr.
	RC34	25	-	120-210	225/45, 235/45		Orig.-Verschr.
8 x 18	B32	25	-	120-210	235/45		Orig.-Verschr., nicht Bremse 374mm
	RC27	30	-	120-210	225/50, 235/45, 245/45		Orig.-Verschr.
	RC32	30	-	120-210	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	B42	30	-	120-210	225/50, 235/45, 245/45		Orig.-Verschr.
		35	-	120-210	225/50, 235/45, 245/45, 255/45		Orig.-Verschr.
	B44	30	-	120-210	225/50, 235/45, 245/45		Orig.-Verschr.
		35	-	120-210	225/50, 235/45, 245/45, 255/45		Orig.-Verschr.
	AC-M10	30	-	120-210	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 374mm
	CA 20	30	ZP593F	120-210	225/50, 235/45, 245/45		
	CA 23 / CA 26	30	ZP599F	120-210	225/50, 235/45, 245/45		nicht Bremse 374mm
	FMI08 Thoe	26	-	120-210	225/45		Orig.-Verschr.
		34	-	120-210	225/45, 225/50, 235/45, 245/45, 255/45		Orig.-Verschr.
	FMI11 Elatha	26	F93	120-210	225/45		
	FMI12 Kari	34	Kit 0334	120-210	225/45, 225/50, 235/45, 245/45, 255/45		
8,5 x 18	RC34	36	-	120-210	245/45		Orig.-Verschr.
	B32	36	-	120-210	235/45, 245/45, 255/40, 255/45		Orig.-Verschr.
9 x 18	CA 17	35	ZP593F	120-210	235/45, 245/45		nicht Bremse 374mm
7,5 x 19	RC34	32	-	120-210	225/40, 225/45		Orig.-Verschr.
8 x 19	RC32	30	-	120-210	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
	B43	28	-	120-210	225/45, 235/40		Orig.-Verschr.
		34	-	120-210	225/45, 235/40, 245/40		Orig.-Verschr.
	CA 24	30	ZP599F	120-180 120-275	235/40 245/40		
	FMI08 Thoe	26	-	120-210	225/40, 225/45		Orig.-Verschr.
	FMI14 Jupiter	26	-	120-210	225/40, 225/45		Orig.-Verschr.
	Oxigin 29	32	ZP599F	120-210	225/45, 235/40, 245/40		
8,5 x 19	RC32	29	-	120-210	225/40, 225/45, 235/40		Orig.-Verschr.
	RC34	26	-	120-210	225/40, 225/45		Orig.-Verschr.
		29	-	120-210	225/40, 225/45, 235/40		Orig.-Verschr.
	B41	28	-	120-210	225/40, 225/45		Orig.-Verschr.
		29	-	120-210	225/40, 225/45, 235/40		Orig.-Verschr.
		36	-	120-210	225/40, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr.
	B42	35	-	120-210	225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nicht Bremse 374mm
	B43	29	-	120-210	225/45, 235/40		Orig.-Verschr.
	B44	30	-	120-210	225/45, 235/40		Orig.-Verschr.
		35	-	120-210	225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr.
	AC-MB6	30	-	120-210	225/45, 235/40		Orig.-Verschr.
	AC-M10	30	-	120-210	225/45, 235/40		Orig.-Verschr.
	CA 20	35	ZP599F	120-210	225/45, 235/40, 245/40, 255/35, 255/40		
	CA 23	30	ZP593F	120-210	225/45, 235/40		
	Oxigin 28	30	ZP593F	120-210	225/45, 235/40		
8,5 x 19	8300 - 1972	32	-	120-210	225/40, 225/45, 235/40		Orig.-Verschr.
	RC34	VA 35 HA 42	-	120-210	VA 245/40 HA 255/40		Orig.-Verschr.
9 x 19							
8,5 x 19	B41	VA 35 HA 42	-	120-210	VA 245/40 HA 255/40		Orig.-Verschr.
9 x 19							
8,5 x 20	B41	35	-	120-210	245/35		Orig.-Verschr.
	B42	35	-	120-210	245/35, 255/35		Orig.-Verschr.
	B43 / B44	35	-	120-210	245/35, 255/35		Orig.-Verschr.
8 x 20	B43	30	-	120-210	245/35		Orig.-Verschr.
9 x 20	B41	35	-	120-210	245/35		Orig.-Verschr.
	B43	35	-	120-210	245/35		Orig.-Verschr.
	CA 20	35	ZP599F	120-210	245/35		
	Oxigin 28	35	ZP593F	120-210	245/35		
8,5 x 20							
9 x 20	B43	VA 35 HA 42	-	120-210	VA 245/35 HA 255/35		Orig.-Verschr.

Kombinationen

7,5 x 18	RC34	25	-	120-210	VA+HA 235/45, 245/45		Orig.-Verschr., VA bei 245/45 ✖
8,5 x 18		40					
8 x 19	RC34	VA 27	-	120-210	VA 245/40		Orig.-Verschr.
8,5 x 19		HA 40			HA 255/40		
8 x 19	B40	27	-	120-210	VA 225/45		Orig.-Verschr.
9 x 19		40			HA 245/40, 255/40		
8 x 19	B43	27	-	120-210	VA 225/45, 245/40		Orig.-Verschr.
8,5 x 19		40			HA 245/40, 255/40		

8 x 20	B40	27	-	120-180	VA 245/35		Orig.-Verschr.
9 x 20		40			HA 255/35		
8,5 x 21	B41	30	-	120-210	VA 245/30		Orig.-Verschr., bei VA 
9,5 x 21		43			HA 255/30		

BMW M440 i xDrive Gran Coupé NEU				2021	G4C	5/112	66,7	e1*2018/858*00122*..
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 18	RC34	36		275	245/45			i.V.
	B32	36	-	275	245/45, 255/40, 255/45			Orig.-Verschr.
9 x 18	CA 17	35	ZP593F	275	245/45			nicht Bremse 374mm
8,5 x 19	B42	35	-	275	245/40, 255/35, 255/40			Orig.-Verschr., nicht Bremse 374mm
	B44	35	-	275	245/40, 255/35, 255/40			Orig.-Verschr.
8,5 x 20	B43	VA 35	-	275	VA 245/35+HA 255/35			Orig.-Verschr.
9 x 20		HA 42						
8,5 x 20	B42 / B43	35	-	275	245/35, 255/35			Orig.-Verschr.
	B44	35	-	275	245/35, 255/35			Orig.-Verschr.
9 x 20	B40	35	-	275	245/35			Orig.-Verschr.
	B43	35	-	275	245/35			Orig.-Verschr.
	CA 20	35	ZP593F	275	245/35			
	Oxigin 28	35	ZP593F	275	245/35			

BMW 5er / Kombi (siehe Konfigurator)				ab 07.10	5L(F10) / 5K(F11)	5/120	72,6	Kombi: e1*2007/46*0455*..., e1*2007/46*0508*..., Limo: e1*2007/46*0363*...
--------------------------------------	--	--	--	----------	-------------------	-------	------	---

BMW 5er		ab 02.2017	G5L (G30), G5K (G31)	5/112	66,7	e1*2007/46*1688*..., e1*2007/46*1750*...		
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC27	27	-	100-265	225/55, 235/50			Orig.-Verschr.
	RC32	27	-	100-265	225/55			Orig.-Verschr., auch für Hybrid
		30	-	100-265	225/55, 235/50, 245/50			Orig.-Verschr.
7,5 x 18	RC32	23	-	100-265	225/50, 235/45, 245/45			Orig.-Verschr., G5L
		25	-	100-265	235/45			Orig.-Verschr., G5K
			-	100-265	225/50, 235/45, 245/45			Orig.-Verschr.
	RC34	25	-	100-265	225/50, 235/45, 245/45			Orig.-Verschr.
	B32	25	-	100-265	225/45, 225/50, 235/45, 245/45			Orig.-Verschr., Kombi nicht 225/45, nicht Bremse 374mm, incl. Plug-in Hybrid
8 x 18	RC32	30	-	100-265	VA 245/45			Orig.-Verschr.
9 x 18		44			HA 275/40			
8 x 18	RC27	30	-	100-340	245/45			Orig.-Verschr., G5K bis 294kW
				100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr., G5L
				100-265	225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr., G5K
	RC32	30	-	100-265	225/50, 235/45, 245/45, 245/45			Orig.-Verschr.
	RC34	30	-	100-265	225/50, 235/45, 245/45			Orig.-Verschr.
	CA 23	30	-	100-265	245/45			Orig.-Verschr., nicht Bremse 374mm
	CA 26	30	-	100-265	245/45			Orig.-Verschr., nicht Bremse 374mm
	B42	30	-	100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr., nur G5L
	B44	30	-	100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr., nur G5L
	CA 17	35	ZP599F	100-340	245/45			Typ G5L, nicht Bremse 374mm
	AC-M10	30	-	100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Typ G5L, nicht Bremse 374mm
				100-265	225/50, 235/45, 245/45, 255/45HA			Typ G5K, nicht Bremse 374mm
	CA 23	30	ZP599F	100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Typ G5L, nicht Bremse 374mm
				100-265	225/50, 235/45, 245/45, 255/45HA			Typ G5K, nicht Bremse 374mm
	CA 26	30	-	100-265	225/45, 225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr.,Typ G5L,nicht Bremse 374mm
				100-265	225/50, 235/45, 245/45, 255/45HA			Orig.-Verschr.,Typ G5K,nicht Bremse 374mm
	FMI08 Thoe	26	-	100-265	225/50, 235/45, 245/45, 255/45			Orig.-Verschr.,Typ G5L,nicht Bremse 374x36mm
				100-265	235/45			Orig.-Verschr.,Typ G5K,nicht Bremse 374x36mm
	FMI11 Elatha	26	F93	100-265	225/50, 235/45, 245/45, 255/45			Typ G5L, nicht Bremse 374x36mm
				100-265	235/45			Typ G5K, nicht Bremse 374x36mm
	FMI12 Kari	26	Kit 0334	100-265	225/50, 235/45, 245/45, 255/45			Typ G5L, nicht Bremse 374x36mm
				100-265	235/45			Typ G5K, nicht Bremse 374x36mm
8 x 19	B40	VA 30	-	120-265	VA 225/40, 225/45, 235/40, 245/40			Orig.-Verschr., nicht Bremse 395mm
9 x 19		HA 44			HA 245/40, 255/35, 255/40, 265/35, 275/35			
8 x 19	CA 19	VA 30	ZP599F	100-390	VA 245/40			
9 x 19		HA 44			HA 275/35			
8 x 19	RC27	30	-	100-390	245/40			Orig.-Verschr.
	RC32	30	-	100-265	225/40, 225/45, 235/40, 245/40			Orig.-Verschr., auch für Hybrid
	B40	30	-	120-265	225/40, 225/45, 235/40, 245/40			Orig.-Verschr., nicht Bremse 395mm
	CA 19	30	ZP599F	100-390	245/40			
	CA 24	30	-	100-390	245/40			Orig.-Verschr.
	BR-I	30	-	120-265	245/40			Orig.-Verschr., Typ G5K, nicht Bremse 395mm
		27	-	120-265	225/40, 225/45, 235/40, 245/40			Orig.-Verschr., Typ G5L, incl. Plug-in-Hybrid, nicht Bremse 395mm
	RC34	27	-	100-265	225/40, 225/45, 235/40, 245/40			Orig.-Verschr., Typ G5L
				100-265	225/45, 245/40			Orig.-Verschr., Typ G5K

	B43	28	-	100-265	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Typ G5L, nicht Bremse 395mm
				100-265	225/45, 235/40, 245/40		Orig.-Verschr., Typ G5K, nicht Bremse 395mm
	FMI08 Thoe	26	-	100-265	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Typ G5L
				100-265	225/45		Orig.-Verschr., Typ G5K
8,5 x 19	RC32	29	-	100-265	225/40, 225/45, 235/40, 245/40, 255/35		Orig.-Verschr., Typ G5L, auch für Hybrid
				100-265	225/45		Orig.-Verschr., Typ G5K, auch für Hybrid
	RC34	26+29	-	100-265	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Typ G5L, auch für Hybrid
				100-265	225/45		Orig.-Verschr., Typ G5K, auch für Hybrid
	B32	25	-	120-265	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 395mm
	B41	20+21	-	100-265	225/40, 225/45		Orig.-Verschr., Typ G5L
		28+29	-	100-265	225/40, 225/45, 235/40, 245/40, 255/35		Orig.-Verschr., Typ G5L, auch für Hybrid
				100-265	225/45		Orig.-Verschr., Typ G5K, auch für Hybrid
	B42	30	-	120-265	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr., Typ G5L, nicht Bremse 395mm
	B43	25	-	100-265	225/40, 225/45, 235/40		Orig.-Verschr.
		29	-	100-265	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
	B44	25	-	100-265	225/40, 225/45, 235/40		Orig.-Verschr., nur Typ G5L
		30	-	100-265	225/40, 225/45, 235/40, 255/35, 255/40		Orig.-Verschr., Typ G5L, nicht Bremse 395mm
	AC-MB6	30	-	100-265	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nicht Bremse 395mm
	AC-M10	30	-	100-265	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nicht Bremse 395mm
	CA 23	30	ZP593F	100-265	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		nicht Bremse 395mm
	FMI07 Atena	28	F93	100-265	225/40, 225/45, 235/40, 245/40, 255/35		
	FMI11 Elatha	21	F93	100-265	225/40, 225/45, 235/40		
	8300 - 1972	21	-	100-265	225/40, 225/45, 235/40		Orig.-Verschr., nur Typ G5L
	Oxigin 18	23	ZP593F	120-265	225/40, 225/45		nicht Bremse 374mm
	Oxigin 19	35	ZP593F	100-340	245/40		nicht Bremse 348 u. 374mm
	Oxigin 25	35	ZP593F	100-390	245/40		Limousine nicht Bremse 374mm
	Oxigin 28	30	ZP593F	100-265	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		
	Race LS 2	52	14x1,25x50	135-340	245/40		m. 20mm Spurplatte 751126652006
8 x 20	B40	VA 30	-	120-265	VA 235/35, 245/35		Orig.-Verschr., G5K an HA nur 275/30
9 x 20		HA 44			HA 245/35, 265/30, 275/30		
8 x 20	B43	VA 30	-	100-265	VA 235/35, 245/35		Orig.-Verschr., bei Kombi nur Luftfederung HA
9 x 20		HA 44			HA 265/30, 275/30		
8 x 20	BR-I	VA 30	-	120-265	VA 245/35		Orig.-Verschr., nicht Bremse 374mm
9 x 20		HA 44			HA 275/30		
8 x 20	RC36	27	-	100-265	245/35		Orig.-Verschr., nur Limousine
	B40	27	-	120-265	245/35		Orig.-Verschr., nur Limousine
	B43	27+30	-	100-265	245/35		Orig.-Verschr., nur Limousine
8,5 x 20	RC34	30	-	100-265	235/35, 245/35		Orig.-Verschr., nur Limousine, auch Hybrid
	B32	30	-	120-265	245/35		Orig.-Verschr.
	B42	30	-	100-265	245/35		Orig.-Verschr., nur G5L
	B43 / B44	30	-	120-265	245/35		Orig.-Verschr., nur G5L
	CA 17	35	ZP593F	100-390	245/35		
	CA 19	32	ZP599F	100-340	245/35		
	AC-M10	30	-	100-265	245/35		Orig.-Verschr., nur G5L
	Oxigin 14	35	ZP599F	120-340	245/35		
	Hibonit	24	14x1,25x30	135-340	245/35		ET24 ohne Spurplatten
		35	14x1,25x40	135-350	245/35		+ 11mm Spurplatte
	Fascinate	30	14x1,25x30	135-340	245/35, 255/35		Sternschraube!!!
	Race LS 2	35	14x1,25x40	135-340	245/35, 255/35		
9 x 21	Fascinate	30	14x1,25x30	135-340	255/30		Sternschraube!!!
	Race LS 2	30	14x1,25x30	135-340	255/30		

Kombinationen:

8 x 19	FMI08 Thoe	26	-	100-265	VA+HA 225/40, 235/40, 245/40 od.		Orig.-Verschr., nur Typ G5L
9 x 19		41			VA 245/40+HA 275/35		
8 x 20	FMI08 Thoe	26	-	100-265	VA+HA 235/35, 245/35 od.		Orig.-Verschr., nur Typ G5L
9 x 20		41			VA 245/35+HA 275/30		
8,5 x 20	B32	30	-	120-265	VA 235/35, 245/35		Orig.-Verschr., bei 285/30 ✖
9,5 x 20		42			HA 245/35, 265/30, 275/30, 285/30		
8,5 x 20	Hibonit	24+35	14x12,5x40	135-340	VA 245/35+HA 275/30		ET35 +11mm Distanzscheiben
10 x 20		38	14x1,25x30				
8,5 x 20	Race LS 2	35	14x1,25x40	135-340	VA 245/35 + HA 275/30		+ 11mm Distanzscheiben
10 x 20		38	14x1,25x30				
8,5 x 20	Fascinate	30	14x1,25x30	135-340	VA 245/35 + HA 275/30		Sternschraube!!!
10 x 20		35					

BMW 5er Hybrid		ab 2020		G5L (G30)		5/112		66,7		e1*2007/46*1688*...	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
7,5 x 17	RC27	27	-	120-265	225/55, 235/50					Orig.-Verschr.	
8,5 x 20	RC34	30	-	100-265	235/35, 245/35					Orig.-Verschr. Limousine	

Kombination

8 x 18	RC32	VA 30	-	100-265	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 18		HA 44					
8 x 20	B43	VA 30	-	100-265	VA 245/35 HA 275/30		Orig.-Verschr., bei Kombi nur Luftfederung HA
9 x 20		HA 44					

BMW M550 i/d xDrive / xDrive Touring ab 2017 G5L / G5K 5/112 66,7 e1*2007/46*1688*..., e1*2007/46*1750*02-..							
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC32	30	-	294-390	245/45		Orig.-Verschr., nur M+S
				294-390	245/45		Orig.-Verschr., nur M+S, Typ G5L
				294	245/45		Orig.-Verschr., nur M+S, Typ G5K
	RC34	30	-	294-390	245/45		Orig.-Verschr., nur M+S
	RC27	30	-	294, 340	245/45		Orig.-Verschr., nur M+S, Typ G5K nur 294kW
	B42	30	-	294-390	245/45		Orig.-Verschr., nur M+S, nur Typ G5L
	B44	30	-	294-390	245/45		Orig.-Verschr., nur M+S, nur Typ G5L
8 x 19	B40	VA 30	-	294-390	VA 245/40		Orig.-Verschr., nicht Bremse 395mm, G5K nur 294kW
9 x 19		HA 44			HA 275/35		
8 x 19	RC27	30	-	294-390	245/40		Orig.-Verschr., nur M+S, ECE nur Typ GL , nicht Bremse 395mm, Typ G5K nur mit 294kW
	RC32	30	-	294-390	245/35, 245/40		Orig.-Verschr., nur M+S, Typ G5L
				294	245/40		Orig.-Verschr., nur M+S, Typ G5K
	B40	30	-	294-390	245/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
		30		294-340	245/40		Orig.-Verschr., nur M+S, nicht Bremse 390mm
	BR-I	27	-	294-390	245/40		Orig.-Verschr., nur M+S, nur Typ G5L, nicht Bremse 374mm
	RC34	27	-	294-390	245/35, 245/40		Orig.-Verschr., nur M+S, Typ G5L
				294	245/40		Orig.-Verschr., nur M+S, Typ G5K
	B43	28	-	294-390	245/40M+S		Orig.-Verschr., Typ G5L, nicht Bremse 395mm
				294	245/40M+S		Orig.-Verschr., Typ G5K, nicht Bremse 395mm
8,5 x 19	FMI08 Thoe	26	-	294-390	245/35, 245/40		Orig.-Verschr., nur M+S, nur Typ G5L
	RC32	29	-	294-390	245/35, 245/40, 255/35		Orig.-Verschr., nur M+S
	RC34	29	-	294-390	245/35, 245/40, 255/35		Orig.-Verschr., nur M+S
	B41	28+29	-	294-390	245/35, 245/40, 255/35		Orig.-Verschr., nur M+S
	B42 / B44	30	-	294-390	245/40		Orig.-Verschr., Typ G5L , nur M+S, nicht Bremse 395mm
	B43	29	-	294-390	245/40		Orig.-Verschr., nur M+S, G5L
				294	245/40		Orig.-Verschr., nur M+S, G5K
	AC-MB6	30	-	294-390	245/40M+S		Orig.-Verschr., G5L , nicht Bremse 395mm
				294	245/40M+S		Orig.-Verschr., G5K , nicht Bremse 395mm
	AC-M10	30	-	294-390	245/40		Orig.-Verschr., nur M+S, G5L
				294	245/40		Orig.-Verschr., nur M+S, G5K
	CA 23	30	ZP593F	294-390	245/40		nur M+S, nicht Bremse 395mm, G5L
				294	245/40		nur M+S, nicht Bremse 395mm, G5K
	Oxigin 28	30	ZP593F	294-390	245/40		nur M+S, G5L
				294	245/40		nur M+S, G5K
	FMI07 Atena	28	F93	294-390	245/35, 245/40, 255/35		nur M+S, nicht Bremse 395mm
8 x 20	B40	VA 30	-	294, 340	VA 245/35		Orig.-Verschr.
9 x 20		HA 44			HA 275/30		
8 x 20		VA 30			VA 245/35		
9 x 20		HA 44			HA 275/30		
8 x 20	B43	VA 30	-	294-390	VA 245/35		Orig.-Verschr., bei Kombi nur Luftfederung HA
9 x 20		HA 44			HA 275/30		
8 x 20	RC36	27	-	294-390	245/35		Orig.-Verschr., nur M+S, nur Typ G5L
	B40	27	-	294-390	245/35		Orig.-Verschr., nur M+S, nur Typ G5L
	B43	27+30	-	294-390	245/35		Orig.-Verschr., nur M+S, nur Typ G5L
8,5 x 20	RC29	26	-	294, 340	245/35, 255/35		Orig.-Verschr., nur M+S, nicht Bremse 395mm, ✖
	RC34	30	-	294-390	245/35		Orig.-Verschr., nur M+S
	B32	30	-	294-390	245/35		Orig.-Verschr., nur M+S
	B42 / B43 / B44	30	-	294-390	245/35		Orig.-Verschr., nur M+S, nur G5L
	AC-M10	30	-	294-390	245/35		Orig.-Verschr., nur M+S, nur G5L

Kombinationen:							
8 x 18	RC32	30	-	294-390	VA 245/45 + HA 275/40		Orig.-Verschr., nur M+S
9 x 18		44					
8 x 19	FMI08 Thoe	26	-	294-390	VA+HA 245/35M+S, 245/40M+S od.		Orig.-Verschr., nur Typ G5L
9 x 19		41			VA 245/40+HA 275/35		
8 x 20	FMI08 Thoe	26	-	294-390	VA+HA 245/35M+S od.		Orig.-Verschr., nur Typ G5L
9 x 20		41			VA 245/35+HA 275/30		
8,5 x 20	B32	30	-	294, 340	VA 245/35		Orig.-Verschr., bei 285/30 ✖
9,5 x 20		44			HA 245/35 M+S, 275/30, 285/30		

BMW 5er Limousine NEU ab 2023 G6L / G60 5/112 66,7 e1*2018/858*00316*..							
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info

7,5 x 18	RC32	23	-	120-210	225/50, 225/55, 235/50		Orig.-Verschr., nicht Bremse 330x24mm VA u. nicht 330x20 u. 370x24mm HA
	RC34	25	-	120-210	225/50, 225/55, 235/50		Orig.-Verschr., nicht Bremse 370x24mm HA
	B32	25	-	120-210	225/55, 235/50, 245/50		Orig.-Verschr., nur Bremse 348mm
8 x 18	B42	30	-	120-145	225/55, 235/50, 255/45		Orig.-Verschr., nur Bremse 348mm
	B44	30	-	120-145	225/55, 235/50, 255/45		Orig.-Verschr., nur Bremse 348mm
	AC-M10	30	-	120-145	225/55, 235/50, 255/45		Orig.-Verschr., nur Bremse 348mm
	CA 20 / CA 23	30	ZP599F	120-145	225/55, 235/50, 255/45		nur Bremse 348mm
	CA 26	30	ZP599F	120-145	225/55, 235/50, 255/45		nur Bremse 348mm
7,5 x 19	RC34	32	-	120-210	235/45, 245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
8 x 19	B40	30	-	120-145	225/50, 235/45, 245/45		Orig.-Verschr., nur Bremse 348mm
	Oxigin 29	32	ZP599F	120-145	225/50, 235/45, 245/45		nicht zulässig für 6-Kolben Festsattelbremse
8,5 x 19	B43	VA 29	-	120-210	VA 245/45+HA 275/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 19		HA 46					
8,5 x 19	RC32	29	-	120-230	245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
				120-230	235/45, 245/40, 245/45, 255/40		
	RC34	29	-	120-230	245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
				120-230	235/45, 245/40, 245/45, 255/40		
	B41	29	-	120-230	235/45, 245/40, 245/45, 255/40		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	29	-	120-145	235/45, 245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	Oxigin 18	29	-	120-210	245/45		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse u. nicht Bremse 374mm
	RC34	26	-	120-230	225/45, 235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
	B32	25	-	120-145	235/45, 245/45, 255/40		Orig.-Verschr., nur Bremse 348mm
	B41	28	-	120-230	225/45, 235/45, 245/40, 245/45, 255/40		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	25	-	120-145	235/45, 245/45, 255/40		Orig.-Verschr., nur Bremse 348mm
	B44	25+30	-	120-145	235/45, 245/45, 255/40		Orig.-Verschr., nur Bremse 348mm
	AC-MB6	30	-	120-210	235/45, 245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	AC-M10	30	-	120-145	235/45, 245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
8,5 x 20	B43	VA 28	-	120-145	VA 245/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35		
8 x 20	RC36	27	-	120-210	235/40, 245/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
8,5 x 20	B41	28	-	120-230	225/40, 235/40, 245/35, 245/40, 255/35, 255/40		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	28	-	120-145	235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	B44	25+30	-	120-145	235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nur Bremse 348mm
	AC-M10	30	-	120-145	235/40, 245/40, 255/35, 255/40		Orig.-Verschr., nur Bremse 348mm
	B41	20	-	120-230	245/40		Orig.-Verschr., nicht Bremse 370x24mm HA
9 x 20	CA 23	30	ZP599F	120-145	235/40, 245/40		nicht zulässig für 6-Kolben Festsattelbremse
	Oxigin 18	28	ZP599F	120-145	245/40		
8,5 x 21	B41	30	-	120-230	245/35, 255/35		Orig.-Verschr., nicht Bremse 370x24mm HA
		34	-	120-230	245/35		Orig.-Verschr., nicht Bremse 370x24mm HA
	B43	30	-	120-145	245/35, 255/35		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9 x 21	CA 20	25	ZP599F	120-145	245/35		nicht zulässig für 6-Kolben Festsattelbremse
		30	ZP599F	120-145	245/35, 255/35		nicht zulässig für 6-Kolben Festsattelbremse

<u>Kombinationen:</u>							
8 x 19	RC34	VA 27	-	120-210	VA+HA 245/40		Orig.-Verschr., nicht Bremse 370x24mm HA
8,5 x 19		HA 40					
8,5 x 19	B41	VA 29	-	120-230	VA 245/45		Orig.-Verschr., nicht Bremse 370x24mm HA
9 x 19		HA 41			HA 275/40		
8 x 20	B43	VA 30	-	120-145	VA 245/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9 x 20		HA 44			HA 275/35		
8,5 x 20	B41	VA 28	-	120-145	VA 245/40, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35, 285/35		
9 x 20	B41	VA 24	-	120-230	VA 245/40		Orig.-Verschr., nicht Bremse 370x24mm HA
10,5 x 20		HA 44			HA 275/35		
8,5 x 21	B41	VA 30	-	120-230	VA 245/35, 255/35		Orig.-Verschr., nicht Bremse 370x24mm HA
9,5 x 21		HA 43			HA 275/30, 285/30		
8,5 x 21	B43	VA 30	-	120-210	VA 245/35, 255/35		Orig.-Verschr., nur Bremse 348mm
9,5 x 21		HA 43			HA 275/30, 285/30		
9 x 21		VA 24	-	120-210	VA 245/35		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10,5 x 21		HA 44			HA 275/30		

BMW 5er 530e PHEV		NEU	ab 2023		G6L / G60		5/112	66,7	e1*2018/858*00316*..	
Sensor - Brocksens 1										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
8,5 x 19	B43	VA 29	-	120, 140	VA 245/45+HA 275/40				Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
10 x 19		HA 46								

8,5 x 19	B43	29	-	120, 140	245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	Oxigin 18	29	-	120, 140	245/45		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse u. nicht Bremse 374mm
	B32	25	-	120, 140	245/45, 255/40		Orig.-Verschr., nur Bremse 348mm
	B43	25	-	120, 140	245/45, 255/40		Orig.-Verschr., nur Bremse 348mm
	AC-MB6	30	-	120, 140	245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	AC-M10	30	-	120, 140	245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
8,5 x 20	B43	VA 28	-	120, 140	VA 245/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35		
8,5 x 20	B43	28	-	120, 140	245/40, 255/35, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
	AC-M10	30	-	120, 140	245/40, 255/35, 255/40		Orig.-Verschr., nur Bremse 348mm
9 x 20	CA 23	30	ZP599F	120, 140	245/40		nicht zulässig für 6-Kolben Festsattelbremse
8,5 x 21	B43	30	-	120, 140	245/35, 255/35		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9 x 21	CA 20	25	ZP599F	120, 140	245/35		nicht zulässig für 6-Kolben Festsattelbremse
		30	ZP599F	120, 140	245/35, 255/35		nicht zulässig für 6-Kolben Festsattelbremse

Kombinationen:							
8,5 x 20	B43	VA 28	-	120, 140	VA 245/40, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35, 285/35		
8,5 x 21	B43	VA 30	-	120, 140	VA 245/35, 255/35		Orig.-Verschr., nur Bremse 348mm
9,5 x 21		HA 43			HA 285/30		

BMW 5er 550e PHEV		xDrive NEU	ab 2023	G6L / G60	5/112	66,7	e1*2018/858*00316*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	VA 29	-	230	VA 245/45+HA 275/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
10 x 19		HA 46						
8,5 x 19	B43	29	-	230	245/45		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
	AC-MB6	30	-	230	245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
	AC-M10	30	-	230	245/45, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
8,5 x 20	B43	VA 28	-	230	VA 245/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
10 x 20		HA 46			HA 275/35			
8,5 x 20	B43	28	-	230	245/40, 255/35, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
9 x 20	CA 23	30	ZP599F	230	245/40		nicht zulässig für 6-Kolben Festsattelbremse	
8,5 x 21	B43	30	-	230	245/35, 255/35		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse	
9 x 21	CA 20	25	ZP599F	230	245/35		nicht zulässig für 6-Kolben Festsattelbremse	
		30	ZP599F	230	245/35, 255/35		nicht zulässig für 6-Kolben Festsattelbremse	

Kombinationen:							
8,5 x 20	B43	VA 28	-	230	VA 245/40, 255/40		Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 20		HA 46			HA 275/35, 285/35		
8,5 x 21	B43	VA 30	-	230	VA 245/35, 255/35		nicht zulässig für 6-Kolben Festsattelbremse
9,5 x 21		HA 43			HA 285/30		

BMW 5er Touring Kombi NEU		3.Quartal 2024		G6K / G60		5/112		66,7		e1*2018/858*00360*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7,5 x 18	RC32	23	-	120-210	225/55				Orig.-Verschr., nicht Bremse 370x24mm HA		
7,5 x 19	RC34	32	-	120-210	235/45, 245/45				Orig.-Verschr., nicht Bremse 370x24mm HA		
8,5 x 19	B43	VA 29	-	120-210	VA 245/45+HA 275/40				Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse		
10 x 19		HA 46									
8,5 x 19	RC32	29	-	120-210	245/45				Orig.-Verschr., nicht Bremse 370x24mm HA		
				120-210	235/45, 245/40, 245/45, 255/40						
	RC34	29	-	120-230	245/45				Orig.-Verschr., nicht Bremse 370x24mm HA		
				120-210	235/45, 245/40, 245/45, 255/40						
	B41	29	-	120-210	235/45, 245/40, 245/45, 255/40				Orig.-Verschr., nicht Bremse 370x24mm HA		
	B43	29	-	120-210	245/45						
	Oxigin 18	29	-	120-210	245/45				Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse		
	RC34	26	-	120-210	235/45, 245/40, 245/45, 255/40						
	B41	28	-	120-210	235/45, 245/40, 245/45, 255/40			Orig.-Verschr., nicht Bremse 370x24mm HA			
9 x 19	B41	21	-	120-210	235/45, 245/40, 245/45			Orig.-Verschr., nicht Bremse 370x24mm HA			
8 x 20	RC36	27	-	120-210	245/40			Orig.-Verschr., nicht zulässig für 6-Kolben			

Größe	Modell	ET	Kit	KW	Reifendimension	Info
8,5 x 20	B41	28	-	120-230	245/35, 245/40, 255/35, 255/40	Festsattelbremse Orig.-Verschr., nicht Bremse 370x24mm HA
8,5 x 21	B41	30	-	120-230	245/35, 255/35	Orig.-Verschr., nicht Bremse 370x24mm HA
		34	-	120-230	245/35	Orig.-Verschr., nicht Bremse 370x24mm HA

Kombinationen:						
8 x 19	RC34	VA 27	-	120-210	VA+HA 245/40	Orig.-Verschr., nicht Bremse 370x24mm HA
8,5 x 19		HA 40				
8,5 x 19	B41	VA 29	-	120-210	VA 245/45	Orig.-Verschr., nicht Bremse 370x24mm HA
9 x 19		HA 41			HA 275/40	
9 x 20	B41	VA 24	-	120-230	VA 245/40	Orig.-Verschr., nicht Bremse 370x24mm HA
10,5 x 20		HA 44			HA 275/35	
8,5 x 21	B41	VA 30	-	120-230	VA 245/35, 255/35	Orig.-Verschr., nicht Bremse 370x24mm HA
9,5 x 21		HA 43			HA 275/30, 285/30	
8,5 x 21	B43	VA 30	-	120-210	VA 245/35, 255/35	Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9,5 x 21		HA 43			HA 275/30, 285/30	
9 x 21	B43	VA 24	-	120-210	VA 245/35	Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10,5 x 21		HA 44			HA 275/30	

BMW 5er Touring 530e PHEV NEU						
		ab 2023	G6K / G60	5/112	66,7	e1*2018/858*00360*..
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 19	B43	VA 29	-	120, 140	VA 245/45+HA 275/40	 Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 19		HA 46				
8,5 x 19	B43	29	-	120, 140	245/45M+S	 Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse

Kombinationen:						
8,5 x 21	B43	VA 30	-	120, 140	VA 245/35, 255/35	Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9,5 x 21		HA 43			HA 285/30	

BMW 5er Touring 550e PHEV NEU						
		ab 2023	G6K / G60	5/112	66,7	e1*2018/858*00360*..
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 19	B43	VA 29	-	230	VA 245/45+HA 275/40	 Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
10 x 19		HA 46				
8,5 x 19	B43	29	-	230	245/45M+S	 Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
Kombinationen:						
8,5 x 21	B43	VA 30	-	230	VA 245/35, 255/35	Orig.-Verschr., nicht zulässig für 6-Kolben Festsattelbremse
9,5 x 21		HA 43			HA 285/30	

BMW M5 (siehe Konfigurator)						
		bis 2016	M5 F10	5/120	72,6	

BMW M5, M5 Competition						
		F95 / F5LM	5/112	66,6	e1*2007/46*1828*..	
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
9,5 x 19	B40	VA 26	-	441, 460	VA 265/40M+S, 275/40	 Orig.-Verschr., nicht Keramikbremse
10,5 x 19		HA 28			HA 285/40	
9,5 x 19	B40	26	-	441, 460	265/40, 275/40, 285/40	 Orig.-Verschr., nur M+S, nicht Keramikbremse
	B32	25	ZP599F	441, 460	VA 265/40+HA 285/40 od. VA 275/40+HA 285/40	nur M+S, nicht Keramikbremse
	B42	25	ZP599F	441, 460	265/35, 275/35, 285/35HA	nicht Keramikbremse
11 x 23	Race LS 3	30	14x1,25x30	441, 460	VA+HA 315/25	

Kombinationen						
11 x 23	Race LS 3	30	14x1,25x30	441, 460	VA+HA 315/25	
11,5 x 23		30				

BMW M6, M6 Competition NEU						
		F96	5/112	66,6		
Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
11 x 23	Race LS 3	30	14x1,25x30	441, 460	VA+HA 315/25	

Kombinationen						
11 x 23	Race LS 3	30	14x1,25x30	441, 460	VA+HA 315/25	
11,5 x 23		30				

BMW M8 NEU						
		ab 2021	F8CM	5/112	66,6	e1*2007/46*2019*..
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
9 x 21	CA 17	25	ZP599F	441, 460	VA 275/30	

10,5 x 21	30	ET 30	771 700	HA 285/30		
-----------	----	-------	---------	-----------	--	--

BMW 6er GT						
ab 11.2017				G6GT / G32	5/112	66,7
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 17	RC32	27	-	120-265	225/60, 235/55, 245/50, 245/55	 Orig.-Verschr., auch für Hybrid
	RC27	27	-	120-265	225/60, 235/55, 245/55, 255/50	 Orig.-Verschr., nur Bremse 348mm
	RC32	30	-	120-265	225/60, 235/55, 245/50, 245/55, 255/50	Orig.-Verschr., auch für Hybrid
7,5 x 18	RC32	23	-	120-265	245/45	Orig.-Verschr.
		25	-	120-265	245/45, 245/50	Orig.-Verschr.
	RC34	25	-	120-265	245/45, 245/50	Orig.-Verschr.
	Oxigin 25	25	-	120-265	235/50, 245/50, 255/50	Orig.-Verschr., nicht zulässig mit 19" Bremsanlage
8 x 18	RC27	30	-	120-265	235/50, 245/50, 255/45	 Orig.-Verschr.
	RC32	30	-	120-265	245/45, 245/50, 255/45	 Orig.-Verschr.
	RC34	30	-	120-265	245/45, 245/50, 255/45	 Orig.-Verschr.
	CA 23	30	-	120-265	225/55, 235/50, 245/50, 255/45	 Orig.-Verschr., incl. Facelift 2020, nicht Bremse 374 u. 395mm
	CA 26	30	-	120-265	225/55, 235/50, 245/50, 255/45	 Orig.-Verschr., incl. Facelift 2020, nicht Bremse 374 u. 395mm
	RC32	20	-	120-265	245/45	Orig.-Verschr.
	B42	30	-	120-265	225/55, 235/50, 245/50, 255/45	 Orig.-Verschr., nicht Bremse 395mm
	B44	30	-	120-265	225/55, 235/50, 245/50, 255/45	 Orig.-Verschr., nicht Bremse 395mm
	AC-M10	30	-	120-265	225/55, 235/50, 245/50, 255/45	 Orig.-Verschr., nicht Bremse 374 u. 395mm
	FMI08 Thoe	26	-	120-265	245/45, 255/45	Orig.-Verschr., nicht Bremse 374x36mm
	FMI11 Elatha	26	F93	120-265	245/45, 255/45	nicht Bremse 374x36mm
	FMI12 Kari	26	Kit 0334	120-265	245/45, 255/45	nicht Bremse 374x36mm
9 x 18	RC32	32	-	120-265	245/45, 255/45	Orig.-Verschr.
7,5 x 19	RC32 / RC34	32	-	120-265	245/45	Orig.-Verschr.
8 x 19	RC27	30	-	120-265	245/45, 255/45	Orig.-Verschr.
	RC32	30	-	120-265	245/45	Orig.-Verschr.
	RC34	27	-	120-265	245/45	Orig.-Verschr.
	B43	28	-	120-265	245/45, 255/45	Orig.-Verschr., nicht Bremse 395mm
	CA 24	30	ZP599F	120-265	245/45, 255/45	nicht zulässig mit 19" Bremsanlage
	FMI08 Thoe	26	-	120-265	245/45	Orig.-Verschr.
8,5 x 19	B43	25	-	120-265	245/45, 255/40, 255/45	 Orig.-Verschr., incl. FL2020
	CA 26	25	ZP599F	120-265	245/45	 Orig.-Verschr., incl. FL2020
	RC32	29	-	120-265	245/45, 255/40	Orig.-Verschr.
	RC34	26+29	-	120-265	245/45, 255/40	Orig.-Verschr.
	B41	28+29	-	120-265	245/45, 255/40	Orig.-Verschr., auch für Hybrid
	B43	29	-	120-265	245/45, 255/40, 255/45	Orig.-Verschr., incl. FL2020
	B44	25+30	-	120-265	245/45, 255/40, 255/45	Orig.-Verschr., incl. FL2020, ET30 nicht Bremse 395mm
	AC-MB6	30	-	120-265	245/45, 255/40, 255/45	Orig.-Verschr., incl. FL2020, nicht Bremse 395mm
	AC-M10	30	-	120-265	245/45, 255/40, 255/45	Orig.-Verschr., incl. FL2020, nicht Bremse 395mm
	CA 23	30	ZP593F	120-265	245/45, 255/40, 255/45	incl. Facelift 2020, nicht Bremse 395mm
	FMI07 Atena	28	F93	120-265	245/45, 255/40	
	8300 - 1972	32	-	120-265	245/45, 255/40	Orig.-Verschr.
	Oxigin 20	23	ZP599F	120-265	245/45, 255/40, 255/45	nicht Bremse 374mm
	Oxigin 28	30	ZP593F	120-265	245/45, 255/40, 255/45	incl. Facelift 2020
	Race LS 2	35	14x1,25x30	190-250	225/45, 235/45	
9 x 19	CA 19	25	ZP599F	120-265	245/45, 255/40, 255/45	nicht zulässig mit 19" Bremsanlage
8 x 20	RC36	27	-	120-265	245/40	Orig.-Verschr.
	B43	27+30	-	120-265	245/40	Orig.-Verschr.
8,5 x 20	RC29	26	-	120-265	245/40, 255/35, 255/40	Orig.-Verschr.
	RC34	30	-	120-265	245/40, 255/35	Orig.-Verschr.
	B42	30	-	120-265	245/40, 255/35, 255/40	Orig.-Verschr., incl. Facelift 2020
	B43	28+30	-	120-265	245/40, 255/35, 255/40	Orig.-Verschr., incl. Facelift 2020
	B44	25+30	-	120-265	245/40, 255/35, 255/40	Orig.-Verschr., incl. Facelift 2020
	CA 19	32	ZP599F	120-265	245/40	nicht zulässig mit 19" Bremsanlage
	AC-M10	30	-	120-265	245/40, 255/35, 255/40	Orig.-Verschr., incl. Facelift 2020
	Fascinate	30	14x1,25x30	190-250	245/40, 255/35	Sternschraube!!!!
	GTS	24	14x1,25x30	190-250	245/40, 255/35	
9 x 20	Hibonit	24	14x1,25x30	190-250	245/40, 255/35	
	AC-522	20+25	F93	120-265	245/40	nicht zulässig mit 19" Bremsanlage
	CA 23	30	ZP599F	120-265	245/40, 275/35HA	incl. Facelift 2020, nicht Bremse 395mm
	Oxigin 19	28	ZP599F	155-265	245/40	
8,5 x 21	Oxigin 25	28	ZP593F	120-265	245/40	
	B41	30	-	120-265	245/35	Orig.-Verschr.
	B43	30	-	120-265	245/35, 255/35	Orig.-Verschr., incl. Facelift 2020
	CA 20	25	ZP599F	120-265	245/35	incl. Facelift 2020

30	ZP599F	120-265	245/35, 275/30HA	incl. Facelift 2020
----	--------	---------	------------------	---------------------

Kombinationen

8 x 18	RC32	20	-	120-265	VA 255/45+HA255/45		Orig.-Verschr.
9 x 18		28					
8 x 19	FMI08 Thoe	26	-	120-265	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 19		41					
8,5 x 19	B41	VA 29	-	120-265	VA 245/45		Orig.-Verschr.
9 x 19		HA 41			HA 275/40		
8 x 20	B40	27	-	120-265	VA 245/40		Orig.-Verschr., incl. Facelift 2020
9 x 20		40			HA 275/35		
8 x 20	FMI08 Thoe	26	-	120-265	VA 245/40+HA 275/35		Orig.-Verschr.
9 x 20		41					
8,5 x 20	Hibonit	24	14x1,25x30	190-250	VA 245/40+HA 275/35, V 245/40+HA 285/35,		
10 x 20		38			VA 255/35+HA 285/30, VA 255/35+HA 295/30		
8,5 x 20	Fascinate	30	14x1,25x30	190-250	VA 245/40+HA 275/35, VA 245/40+HA 285/35,		Sternschraube!!!
10 x 20		35			VA 255/35+HA 285/30		
8,5 x 20	GTS	24	14x1,25x30	190-250	VA 245/40+HA 275/35, VA 245/40+HA 285/35,		
10 x 20		38			VA 255/35+HA 285/30, VA 255/35+HA 295/30		
8,5 x 21	B41	30	-	120-265	VA 245/35		Orig.-Verschr.
9,5 x 21		43			HA 245/35, 275/30, 285/30		
9 x 21	GTS	30	14x1,25x40	190-250	VA 245/35+HA 285/30, VA 255/30+HA 295/25		+Spurverbr. 751126651106 (11 mm) für VA
10 x 21		38			14x1,25x30		
9 x 21	Fascinate	30	14x1,25x40	190-250	VA 245/35+HA 285/30, VA 255/30+HA 295/25		Sternschrauben!!!! +Spurverbr. 751126651106 (11 mm) für VA
10,5 x 21		44			14x1,25x30		
9 x 21	LS 2	30	14x1,25x40	190-250	VA 245/35+HA 285/30, VA 255/30+HA 295/25		+Spurverbr. 751126651106 (11 mm) für VA
10,5 x 21		44			14x1,25x30		

BMW 7er		ab 2016	7L (G11 / G12)	5/112	66,6	e1*2007/46*0276*10-...	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	27	-	155-240	225/60, 235/55, 245/55		Orig.-Verschr.
	RC32	27	-	155-250	225/60, 235/55, 245/55, 255/50		Orig.-Verschr., auch Hybrid, nur Baureihe G11
7,5 x 18	RC32	23+25	-	155-250	225/55, 235/50, 245/50		Orig.-Verschr.
	RC34	25	-	155-250	225/55, 235/50, 245/50		Orig.-Verschr.
8 x 18	Oxigin 25	25	-	155-250	235/50		Orig.-Verschr.
	RC27	30	-	155-330	245/50		Orig.-Verschr.
	RC32	30	-	155-330	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.
	RC34	30	-	155-330	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.
	CA 23	30	-	155-330	245/50, 255/45		Orig.-Verschr., nicht Bremse 374 u. 395mm
	CA 26	30	-	155-330	245/50, 255/45		Orig.-Verschr., nicht Bremse 374 u. 395mm
	RC32	20	-	155-330	225/55		Orig.-Verschr.
	B42	30	-	155-330	245/50, 255/45		Orig.-Verschr., nicht Bremse 395mm
	B44	30	-	155-330	245/50, 255/45		Orig.-Verschr., nicht Bremse 395mm
	AC-M10	30	-	155-330	245/50, 255/45		Orig.-Verschr., nicht Bremse 374 u. 395mm
	FMI08 Thoe	26	-	155-330	225/55, 235/50, 245/50, 255/45		Orig.-Verschr., nicht Bremse 374x36mm VA u. 370x24mm HA
	FMI11 Elatha	26	F93	155-330	225/55, 235/50, 245/50, 255/45		nicht Bremse 374x36mm VA u. 370x24mm HA
	FMI12 Kari	26	Kit 0335	155-330	225/55, 235/50, 245/50, 255/45		nicht Bremse 374x36mm VA u. 370x24mm HA
8 x 19	RC32	30	-	155-330	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11 , auch für Hybrid
	RC34	27	-	155-330	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11
	B40	30	-	155-330	245/45, 255/45		Orig.-Verschr., nicht Bremse 395mm
	B43	28	-	155-330	245/45, 255/45		Orig.-Verschr., nicht Bremse 395mm
	BR-I	27	-	155-330	245/45, 255/45		Orig.-Verschr., nicht Bremse 395mm
8,5 x 19	BR-I	25	-	155-390	245/45		Orig.-Verschr., nicht Bremse 395mm, nur für Fahrz. ohne Kunststoff-Verschlusskappen auf Fahrzeugnabe
	B43	25	-	155-390	245/45		Orig.-Verschr., auch Hybrid
	CA 26	25	ZP599F	155-390	245/45		Orig.-Verschr., nicht Bremse 395mm
	B32	25	-	155-330	245/45, 255/40, 255/45		Orig.-Verschr., nicht Bremse 395mm, ab 255/40 ✖
	RC32	29	-	155-390	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11
	RC34	26	-	155-390	225/45, 235/45, 245/45, 255/40		Orig.-Verschr., auch Hybrid
		29	-	155-390	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11
	B41	20	-	155-390	225/45, 235/45		Orig.-Verschr., nur Typ G11
		21+29	-	155-390	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11
		28	-	155-390	225/45, 235/45, 245/45, 255/40		Orig.-Verschr., nur Typ G11 , auch für Hybrid
	B42	30	-	155-390	245/45, 255/40, 255/45		Orig.-Verschr., nicht Bremse 395mm
	B43	29	-	155-390	245/45, 255/40, 255/45		Orig.-Verschr.
	B44	25	-	155-390	245/45		Orig.-Verschr.
		30	-	155-390	245/45, 255/40, 255/45		Orig.-Verschr., nicht Bremse 395mm
	AC-MB6	30	-	155-390	245/45, 255/40, 255/45		Orig.-Verschr., nicht Bremse 395mm
	AC-M10	30	-	155-390	245/45, 255/40, 255/45		Orig.-Verschr., nicht Bremse 395mm
	CA 23	30	ZP593F	155-390	245/45, 255/40, 255/45		nicht Bremse 395mm

9 x 19	FMI07 Atena	28	F93	155-390	235/45, 245/45, 255/40, 255/45		nur Typ G11, nicht Bremse 395x36mm
	FMI11 Elatha	21	F93	155-390	225/45, 235/45, 245/45		nur Typ G11
	8300 - 1972	21	-	155-390	225/45, 235/45, 245/45		Orig.-Verschr., nur Typ G11
	Oxigin 26	30	ZP599F	155-330	235/45		
	Oxigin 28	30	ZP593F	155-390	245/45, 255/40, 255/45		
	Race LS 2	52	14x1,25x50	155-448	245/45		+ Spurverbr. 751126652006
	FMI08 Thoe	20	-	155-390	235/45		Orig.-Verschr., nicht Bremse 395x36mm
	RC36	27	-	155-390	245/40		Orig.-Verschr.
	B40	27	-	155-390	245/40		Orig.-Verschr.
	B43	27+30	-	155-390	245/40		Orig.-Verschr.
8 x 20	RC29	26	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr., nicht Bremse 395mm
	RC34	30	-	155-390	245/40		Orig.-Verschr.
	B32	30	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr.
	B42	30	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr.
	B43	28+30	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr.
	B44	30	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr.
	AC-M10	30	-	155-390	245/40, 255/35, 255/40		Orig.-Verschr.
	Race LS 2	30	14x1,25x30	155-448	245/40		
8,5 x 20	Fascinate	30	14x1,25x30	155-448	245/40		Sternschraube!!!!
	Hibonit	24	14x1,25x30	155-448	245/40		
	B43	30	-	155-390	245/35, 255/35		Orig.-Verschr.
	CA 20	25	ZP599F	155-390	245/35		
	Fascinate	30	14x1,25x30	155-448	245/35		Sternschraube!!!!
	Race LS 2	30	14x1,25x30	155-448	245/35		
	Fascinate	30	14x1,25x30	155-448	245/30		Sternschraube!!!!
	Race LS 2	30	14x1,25x30	155-448	245/30		

weitere Dimensionen/Designs siehe Konfigurator

BMW 7er NEU		ab November 2022		G7L / G70		5/112		66,7		e1*2018/858*00154*..	
Sensor - Brocksens 1											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
8,5 x 19		RC34		26	-	125-280	245/50				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		B41		26	-	125-280	245/50, 255/45, 265/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		RC34		26	-	125-280	245/50, 255/45, 265/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		B41		28	-	125-280	255/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
9 x 19		B41		21	-	125-280	255/45, 265/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		BR-I		38	14x1,25x50	125-280	255/50, 275/45				+ Distanzscheiben 20mm - 751126652006
		FMI08 Thoe		20	-	125-280	255/45, 265/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
8,5 x 20		B41		20	-	125-280	245/45, 255/40, 255/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
				28	-	125-280	255/40, 255/45				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
9 x 20		B41		VA 24 HA 44		-	125-280	VA 255/45			Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 20								HA 285/40			
9 x 20		B41		20	-	125-280	245/45, 255/40, 255/45, 265/40				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		BR-I		32	14x1,25x 40,45,50	125-280	255/45				+ Distanzscheiben 11, 15, 20mm lt. Zuordnung Breyton
9 x 21		FMI07 Atena		26	F93	125-280	245/40, 255/40				nur Bremse 395x36mm VA u. 370x24mm HA
9,5 x 21		B41		22	-	125-280	245/40, 255/40, 265/35				Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
		BR-I		36	14x1,25x 40,45	125-280	255/40				+ Distanzscheiben 11, 15mm lt. Zuordnung Breyton, Achtung! mind. Loadindex 105 an HA
		BR-I		VA+HA 36	14x1,25x 40,45,50	125-280	VA 255/40			+ Distanzscheiben 11, 15, 20mm lt. Zuordnung Breyton	
					14x1,25x 40,45		HA 285/35			+ Distanzscheiben 11, 15mm lt. Zuordnung Breyton, Achtung! mind. Loadindex 105 an HA	

Kombinationen

9 x 20	B41	VA 24	-	125-280	VA 255/40+HA 285/35 od. VA 255/45+HA 285/40 od. VA 265/40+HA 295/35		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 20		HA 44					
9,5 x 21	B41	VA 22	-	125-280	VA 255/40+HA 285/35 od. VA 265/35+HA 305/30 od. VA 265/40+HA 295/35		Orig.-Verschr., nur Bremse 395x36mm VA u. 370x24mm HA
10,5 x 21		HA 43					

BMW M760Li xDrive	7L	5/112	66,6	e1*2007/46*0276*14-...
Sensor - Brocksens 1				

Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 19	B43	25	-	430-448	245/45M+S		Orig.-Verschr.

BMW 8er / 840d xDrive		ab 2019	G8C (G14)	5/112	66,7	e1*2007/46*1906*...	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC32	30	-	235	245/45M+S		Orig.-Verschr.
				235-250	245/45M+S		Orig.-Verschr., nicht Bremse 374x36mm
	RC34	30	-	235-250	245/45		Orig.-Verschr.
	RC27	30	-	235-250	245/45, 255/45		Orig.-Verschr., nur M+S
	B42	30	-	235-250	245/45, 255/45		Orig.-Verschr., nur M+S
	B44	30	-	235-250	245/45, 255/45		Orig.-Verschr., nur M+S
	CA 20	30	ZP593F	235-250	245/45, 255/45		nur M+S
	FMI08 Thoe	26	-	235-250	245/45M+S		Orig.-Verschr., nicht Bremse 348x36mm VA u. 345x24mm HA
	FMI11 Elatha	26	F93	235-250	245/45M+S		nicht Bremse 348x36mm VA u. 345x24mm HA
	FMI12 Kari	26	Kit 0334	235-250	245/45M+S		nicht Bremse 348x36mm VA u. 345x24mm HA
8 x 19	FMI08 Thoe	VA 26	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr.
9 x 19		HA 41					
8 x 19	FMI14 Jupiter	VA 26	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr.
9 x 19		HA 41					
8 x 19	RC27	30	-	235-390	245/40M+S		Orig.-Verschr., nicht Bremse 395mm
	RC32	30	-	235-250	245/40		Orig.-Verschr.
	CA 19	30	ZP599F	235-390	245/40M+S		nicht Bremse 395mm
	CA 24	30	-	235-390	245/40M+S		Orig.-Verschr., nicht Bremse 395mm
	RC34	27	-	235-250	245/40		Orig.-Verschr., nur M+S
		30	-	235-250	245/45		Orig.-Verschr., nur M+S
	B40	30	-	235-250	245/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
	B43	28	-	235-250	245/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
	FMI08 Thoe	26	-	235-250	245/40		Orig.-Verschr., nur M+S
8,5 x 19	RC32	29	-	235-250	245/40		Orig.-Verschr., nur M+S
	RC34	29	-	235-250	245/40		Orig.-Verschr., nur M+S
	B41	29	-	235-250	245/40		Orig.-Verschr., nur M+S
	B43	29	-	235-250	245/40		Orig.-Verschr., nur M+S
	B44	30	-	235-250	245/40, 255/35, 255/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
	AC-MB6	30	-	235-250	245/40, 255/35, 255/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
	AC-M10	30	-	235-250	245/40, 255/35, 255/40		Orig.-Verschr., nur M+S, nicht Bremse 395mm
	CA 23	30	ZP593F	235-250	245/40, 255/35, 255/40		nur M+S, nicht Bremse 395mm
	8300 - 1972	32	-	235-250	245/40		Orig.-Verschr., nur M+S
	Oxigin 26	30	ZP599F	235-390	245/40		nur M+S, nicht Bremse 395mm
Oxigin 28	30	ZP593F	235-250	245/40, 255/35, 255/40		nur M+S	
8 x 20	FMI08 Thoe	VA 26	-		VA 245/35+HA 275/30		Orig.-Verschr.
9 x 20		HA 41					
8 x 20	RC36	27	-	235-250	245/35		Orig.-Verschr., nur M+S
	B40	27	-	235-250	245/35		Orig.-Verschr., nur M+S
	B43	27+30	-	235-250	245/35		Orig.-Verschr., nur M+S
8,5 x 20	RC29	26	-	235-250	245/35		Orig.-Verschr., nur M+S
	RC34	30	-	235-250	245/35		Orig.-Verschr., nur M+S
	B42 / B43	30	-	235-250	245/35, 255/35		Orig.-Verschr., nur M+S
	B44	30	-	235-250	245/35, 255/35		Orig.-Verschr., nur M+S
	AC-M10	30	-	235-250	245/35, 255/35		Orig.-Verschr., nur M+S
	CA 19	32	ZP599F	235-390	245/35		nur M+S
	Hibonit	24+35	14x1,25x30	235	245/35		

Kombinationen

8 x 18	RC32	20	-	235-250	VA 245/45 + HA 275/40		
9 x 18		28					
8 x 19	B40	27	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr., nicht Bremse 395mm
9 x 19		40					
8,5 x 19	B41	VA 29	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr.
9 x 19		HA 41					
8 x 20	B40	27	-	235-250	VA 245/35+HA 275/30		Orig.-Verschr.
9 x 20		40					
8,5 x 20	Hibonit	24+35	14x1,25x30	235	VA 245/35+HA 275/30		
10 x 20		38					

BMW 8er / M850i xDrive		ab 2019	G8C (G14)		5/112	66,7	e1*2007/46*1906*...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	FMI14 Jupiter	VA 26	-	390	VA 245/40+HA 275/35		Orig.-Verschr.	
9 x 19		HA 41						
8 x 19	RC32	30	-	390	245/40		Orig.-Verschr., nicht Bremse 380x28mm	
	CA 24	30	-	390	245/40M+S		Orig.-Verschr., nicht Bremse 395mm	
	RC34	27	-	390	245/40		Orig.-Verschr., nur M+S	

8,5 x 19	RC32	29	-	390	245/40		Orig.-Verschr., nur M+S, nicht Bremse 400x38mm VA u. 380x28mm HA
	RC34	29	-	390	245/40		Orig.-Verschr., nur M+S, nicht Bremse 380x28mm HA
	8300 - 1972	32	-	390	245/40		Orig.-Verschr., nur M+S
	Oxigin 26	30	ZP599F	390	245/40		nur M+S, nicht Bremse 395mm
8 x 20	FMI08 Thoe	VA 26	-	390	VA 245/35+HA 275/30		Orig.-Verschr.
9 x 20		HA 41					
8 x 20	RC36	27	-	390	245/35		Orig.-Verschr., nur M+S
	B40	27	-	390	245/35		Orig.-Verschr., nur M+S
8,5 x 20	RC34	30	-	390	245/35		Orig.-Verschr., nur M+S
	B42	30	-	390	245/35, 255/35		Orig.-Verschr., nur M+S
	B44	30	-	390	245/35, 255/35		Orig.-Verschr., nur M+S
	CA 19	32	ZP599F	390	245/35		nur M+S
	Hibonit	24+35	14x1,25x30	390	245/35		

Kombinationen

8 x 20	B40	27	-	390	VA 245/35+HA 275/30		Orig.-Verschr.
9 x 20		40					
8,5 x 20	Hibonit	24+35	14x1,25x30	390	VA 245/35+HA 275/30		
10 x 20		38					

BMW 8er Gran Coupé				G8C (G16)	5/112	66,7	e1*2007/46*1906*...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	B42	30	-	235-250	245/45, 255/45			Orig.-Verschr., nur M+S
	B44	30	-	235-250	245/45, 255/45			Orig.-Verschr., nur M+S
	CA 20	30	ZP593F	235-250	245/45, 255/45			nur M+S
8 x 19	FMI14 Jupiter	VA 26	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr.	
9 x 19		HA 41						
8 x 19	B40	30	-	235-250	245/40			Orig.-Verschr., nur M+S, nicht Bremse 395mm
	CA 24	30	ZP599F	235-390	245/40			nur M+S, nicht Bremse 395mm
8,5 x 19	B44	30	-	235-250	245/40, 255/35, 255/40			Orig.-Verschr., nur M+S, nicht Bremse 395mm
	AC-MB6	30	-	235-250	245/40, 255/35, 255/40			Orig.-Verschr., nur M+S, nicht Bremse 395mm
	Oxigin 26	30	ZP599F	235-390	245/40			nur M+S, nicht Bremse 395mm
8 x 20	B43	27+30	-	235-250	245/35			Orig.-Verschr., nur M+S
8,5 x 20	B32	30	-	235-250	245/35, 255/35			Orig.-Verschr., nur M+S
	B42	30	-	235-250	245/35, 255/35			Orig.-Verschr., nur M+S
	B43	30	-	235-250	245/35, 255/35			Orig.-Verschr., nur M+S
	AC-M10	30	-	235-250	245/35, 255/35			Orig.-Verschr., nur M+S
	CA 19	32	ZP599F	235-390	245/35			nur M+S

Kombinationen

8 x 19	B40	27	-	235-250	VA 245/40+HA 275/35		Orig.-Verschr., nicht Bremse 395mm
9 x 19		40					

BMW M850i xDrive Coupé, Cabrio					G8C (G16)	5/112	66,7	e1*2007/46*1906*...	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
8,5 x 19	Oxigin 28	30	ZP593F	390	245/40, 255/35, 255/40			nur M+S	
	B44	30	-	390	245/35, 255/35			Orig.-Verschr., nur M+S	
8,5 x 20	AC-M10	30	-	390	245/35, 255/35			Orig.-Verschr., nur M+S	

BMW M850i xDrive Gran Coupé					G8C (G16)	5/112	66,7	e1*2007/46*1906*...
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	Oxigin 28	30	ZP593F	390	245/40, 255/35, 255/40			nur M+S
8 x 20	B43	27+30	-	390	245/35			Orig.-Verschr., nur M+S
8,5 x 20	B42 / B43	30	-	390	255/35			Orig.-Verschr., nur M+S
	B44	30	-	390	255/35			Orig.-Verschr., nur M+S
	AC-M10	30	-	390	255/35			Orig.-Verschr., nur M+S
	CA 19	32	ZP599F	390	245/35			nur M+S

BMW XM NEU							
2023				G09 / F56XM	5/120	66,6	e1*2007/46*2066*..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 21	B41	26	-(W15)	230-360	285/40, 285/45		Orig.-Verschr., nur M+S
	FMI09 Cratos	26	-		285/45		Orig.-Verschr., nur M+S

Kombinationen

9,5 x 21	B41	VA 19	-(W15)	230-360	VA 275/45+HA 315/40		Orig.-Verschr.
10,5 x 21		HA 42					
10 x 23	STC 23	VA 22	-	230-360	VA 275/35+HA 315/30 und VA 275/35+HA 325/30		Orig.-Verschr.

11,5 x 23	HA 42						Orig. Version
-----------	-------	--	--	--	--	--	---------------

BMW X1		ab 2015	F48/UKL-L/F1X	5/112	66,7	e1*2007/46*0371*19-..., e1*2007/46*1676*...	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	39	-	85-170	205/60, 215/55, 215/60, 225/55		Orig.-Verschr. nur M+S, ab 215/55 ✖
	RC34	39	-	85-170	205/60M+S		Orig.-Verschr., nicht Bremse 360x30mm
7,5 x 17	RC27	52	-	85-170	225/55		Orig.-Verschr., auch Typ F1X
	RC32	52	-	85-170	205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., auch Typ F1X, bis 215/60 nur M+S
	RC34	52	-	85-170	205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., auch F1X, nicht Bremse 360x30bl
	BR-I	52	-	85-170	225/55		Orig.-Verschr., auch Typ F1X, nicht Bremse 360mm, nur zulässig für Fahrzeuge ohne Kunststoff-Verschlusskappen auf den Fahrzeugnaben
6,5 x 18	RC34	41	-	85-170	205/55		Orig.-Verschr., auch Typ F1X
7,5 x 18	RC30	51	-	85-170	215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., auch Typ F1X
	RC32	51	-	85-170	205/55, 215/50, 215/55, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Typ F1X, bis 215/55 nur M+S
	B32	51	-	85-170	215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., auch Typ F1X
	B39	51	-	85-170	215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., auch Typ F1X
	BR-I	51	-	85-170	225/50		Orig.-Verschr., auch Typ F1X, nicht Bremse 360mm, nur zulässig für Fahrzeuge ohne Kunststoff-Verschlusskappen auf den Fahrzeugnaben
	CA 20	51	-	85-170	225/50		Orig.-Verschr., auch Typ F1X, nicht Bremse 360x30mm
	Oxigin 25	51	-	85-170	225/50		Orig.-Verschr., auch Typ F1X
215/50M+S, 225/50, 235/45						Orig.-Verschr., nicht Brembo Bremse mit 335mm	
8 x 19	RC27	47	-	85-170	225/40, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., nicht Bremse 335mm, nur 225/45 auflagenfrei!
	RC32	47	-	85-170	225/40, 225/45		Orig.-Verschr., auch F1X
	B40	47	-	85-170	225/45		Orig.-Verschr., auch F1X
	FMI07 Atena	47	F93	85-170	225/40, 225/45		
	FMI08 Thoe	47	-	85-170	225/40, 225/45		Orig.-Verschr.
	FMI14 Jupiter	47	-	85-170	225/45		Orig.-Verschr., auch F1X
	BR-I	47	-	85-170	225/45		Orig.-Verschr., nicht Bremse 360mm, nur für Fahrzeuge ohne Kunststoff Verschlusskappen auf den Fahrzeugnaben
	CA 19	47	ZP599F	85-170	225/45		nicht Bremse 307mm

BMW X1 Plug-in-Hybrid NEU		ab 2020	F1X	5/112	66,7	e1*2007/46*1676*...	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	39	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC34	39	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm
7 x 17	RC27	41	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC30	47	-	92	205/60, 215/55, 215/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC32	47	-	92	215/55, 215/60		Orig.-Verschr., nur M+S
	RC34	41	-	92	205/60		Orig.-Verschr., nur M+S
		47	-	92	215/55, 215/60		Orig.-Verschr., nur M+S
	B39	47	-	92	205/60, 215/55, 215/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm
	Pro1	49	ZP599F	92	215/55, 225/55		Orig.-Verschr., nur M+S
7,5 x 17	RC27	52	-	92	225/55		Orig.-Verschr., nicht Bremse 360mm
	RC32	52	-	92	225/55		Orig.-Verschr.
6,5 x 18	RC34	41	-	92	205/55		Orig.-Verschr.
7,5 x 18	B32	51	-	92	205/55M+S, 215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	CA 20	51	-	92	225/50		Orig.-Verschr.
	RC30	51	-	92	205/55M+S, 215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	RC32	50	-	92	235/45		Orig.-Verschr.
	RC34	51	-	92	225/50, 235/45, 245/45		Orig.-Verschr.
		50	-	92	235/45		Orig.-Verschr.
8 x 18	B38	52	-	92	235/45		Orig.-Verschr., nicht Bremse 360mm
7,5 x 19	RC34	45,5	-	92	225/45		Orig.-Verschr.
	B39	51	-	92	225/45		Orig.-Verschr., nicht Bremse 360mm
8 x 19	RC27	47	-	92	225/45		Orig.-Verschr.
	B40	47	-	92	225/45		Orig.-Verschr.
	RC32	47	-	92	225/45		Orig.-Verschr.
	RC34	48	-	92	225/45		Orig.-Verschr.
	B38	52	-	92	225/45, 235/40		Orig.-Verschr., nicht Bremse 360mm
	B43	46	-	92	225/45		Orig.-Verschr.
	FMI08 Thoe	47	-	92	225/45		Orig.-Verschr.
8 x 20	B38	52	-	92	225/40		Orig.-Verschr., nicht Bremse 360mm
	B43	46+48	-	92	225/40		Orig.-Verschr.
8,5 x 20	RC29	52	-	92	225/40		Orig.-Verschr.

BMW X1 NEU		im Laufe 2022	U1X / U11	5/112	66,7	e1*2018/858*00153*..	
------------	--	---------------	-----------	-------	------	----------------------	--

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	39	-	100-150	205/65, 215/60, 215/65, 225/60	Orig.-Verschr., nur M+S
		45	-	100-150	205/65, 215/60, 225/60, 235/55	Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC34	39	-	100-150	205/65, 215/60, 215/65, 225/60	Orig.-Verschr., nicht Bremse 360x30mm
7 x 17	RC27	41	-	100-150	205/65, 215/60, 215/65, 225/60	Orig.-Verschr., nicht Hybrid, nicht Elektro
	RC34	41	-	100-150	205/65	Orig.-Verschr., nicht Bremse 360x30mm
				94-150	205/65, 215/60, 215/65, 225/60	
	RC30	47	-	100, 110	205/65, 215/60, 215/65, 225/60, 235/55, 245/55	Orig.-Verschr.
	RC32	47	-	100-150	215/60, 215/65, 225/60, 235/55	Orig.-Verschr., nicht Bremse 360x30mm
	RC34	47	-	100-150	215/60, 215/65, 225/60, 235/55	Orig.-Verschr., nicht Bremse 360x30mm
	Pro1	49	ZP599F	100-150	215/60, 215/65, 225/60, 235/55, 245/55	nicht Bremse 360x30mm
7,5 x 17	RC32	52	-	94-150	225/60, 235/55, 245/55	Orig.-Verschr.
	RC34	52	-	100-150	215/60, 225/60, 235/55, 245/55	Orig.-Verschr., nicht Bremse 360x30mm
		45	-	100-150	205/65, 215/60, 215/65, 225/60	Orig.-Verschr., nicht Bremse 360x30mm
6,5 x 18	RC34	41	-	100-221	205/60	Orig.-Verschr.
7,5 x 18	RC32	50	-	100-150	225/55	Orig.-Verschr.
				100-221	225/55, 235/50, 245/50	Orig.-Verschr.
				100-150	225/55	Orig.-Verschr.
	RC34	50	-	100-221	225/55, 235/50, 245/50	Orig.-Verschr.
				100-150	205/60, 215/55, 225/55, 235/50	Orig.-Verschr.
	RC34	51	-	100-221	225/55, 235/50, 245/50	Orig.-Verschr.
	B32	51	-	100-150	205/60, 215/55, 225/55, 235/50	Orig.-Verschr.
	B39	51	-	100-150	205/60, 215/55, 225/55, 235/50	Orig.-Verschr., nicht Bremse 360mm
	CA 20	51	-	100-221	225/55, 235/50, 245/50	Orig.-Verschr., nicht Bremse 360x30mm
	Oxigin 25	51	-	100-150	215/55, 225/50, 225/55	Orig.-Verschr., nicht für M-Sportbremse
				100-221	215/55M+S	
		44	ZP599F	100-150	205/60, 215/55, 225/50, 225/55	nicht für Fahrzeuge mit 19"-Sportbremse
8 x 18	RC34	48	-	100-221	225/55	Orig.-Verschr.
				100-150	225/55	Orig.-Verschr., nicht Bremse 360mm
	B42 / B44	45	-	100-150	225/55	Orig.-Verschr., nicht Bremse 360mm
	AC-MB6	45	-	100-150	225/55	Orig.-Verschr., nicht Bremse 360mm
	AC-M10	45	-	100-150	225/55	Orig.-Verschr., nicht Bremse 360mm
7,5 x 19	FMI08 Thoe	49	-	100-221	225/55, 235/50, 255/45	Orig.-Verschr.
	RC34	45,5	-	100-221	205/55, 225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
8 x 19	RC32	46	-	100-221	245/45	Orig.-Verschr.
				110-221	225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
	RC34	46	-	100-221	245/45	Orig.-Verschr.
				110-221	225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
	B43	46	-	100-150	225/50, 235/45, 245/45	Orig.-Verschr., nicht Bremse 360mm
	RC27	47	-	100-150	225/50, 235/45, 245/45	Orig.-Verschr.
	RC32	47	-	100-221	225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
	RC34	43	-	100-221	225/45, 235/45	Orig.-Verschr.
		48	-	100-221	225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
	B40	47	-	100-150	225/50, 235/45, 245/45	Orig.-Verschr.
	CA 24	43	ZP599F	100-110	225/45	nicht Bremse 360mm
				100-150	225/45, 235/45	
8,5 x 19	FMI08 Thoe	47	-	100-221	225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
	Oxigin 29	43	ZP599F	100-150	235/45	nicht Bremse 360mm
	B37	47	-	100-115	235/45, 245/45	Orig.-Verschr.
	B42	47	-	100-150	235/45, 245/45	Orig.-Verschr.
	AC-M10	45	-	100-150	235/45	Orig.-Verschr., nicht Bremse 360mm
	CA 20	45	ZP599F	100-150	235/45	nicht Bremse 360mm
	CA 23	45	ZP593F	100-150	235/45	
	Oxigin 28	45	ZP593F	100-150	235/45	
9 x 19	8300 - 1972	45	-	94-150	225/45, 235/45	Orig.-Verschr.
	CA 17	49	ZP593F	100-150	235/45	nicht Bremse 360mm
	CA 24	49	ZP599F	100-150	235/45	nicht Bremse 360mm
	FMI12 Kari	49	F93	94-150	235/45	
8 x 20	RC36	46	-	100-150	215/45, 225/40, 235/40, 245/40	Orig.-Verschr.
	B43	46	-	100-150	215/45, 225/40, 235/40, 245/40	Orig.-Verschr.
		48	-	100-150	215/45, 225/40, 235/40, 245/40	Orig.-Verschr.
8,5 x 20	B42	45	-	100-115	225/40, 235/40	Orig.-Verschr., Achtung Bremsen!
		48	-	100-150	225/40, 235/40, 245/40	Orig.-Verschr., nicht Bremse 360mm
	B43	40	-	100, 110	225/40	Orig.-Verschr.
		43	-	100, 110	225/40, 235/40	Orig.-Verschr.
	B44	40	-	100-150	225/40	Orig.-Verschr., nicht Bremse 360mm
	CA 17	48	ZP599F	100-150	225/40, 235/40	nicht für M-Sportbremse
				100-221	245/40	
9 x 20	AC-MB6	50	-	100-150	225/40, 235/40, 245/40	Orig.-Verschr.
	B43	44	-	100-150	225/40	Orig.-Verschr.
	CA 20	45	ZP599F	100-150	225/40	nicht Bremse 360mm
	CA 23	45	ZP599F	100-150	225/40	nicht Bremse 360 u. 385mm
	Oxigin 28	45	ZP593F	100-115	225/40	

BMW X1 PHEV NEU		im Laufe 2023		U1X / U11		5/112		66,7		e1*2018/858*00153*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 17	RC27	39	-	100, 110	205/65, 215/60, 215/65, 225/60				Orig.-Verschr., nur M+S		
		45	-	100, 110	205/65, 215/60, 225/60, 235/55				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
7 x 17	RC27	41	-	100, 110	205/65, 215/60, 215/65, 225/60				Orig.-Verschr.		
	RC34	41	-	68-104	205/65				Orig.-Verschr.		
7,5 x 18	RC32	50	-	100, 110	225/55				Orig.-Verschr., i.V.		
				100-221	225/55, 235/50, 245/50				Orig.-Verschr.		
	RC34	50	-	100, 110	225/55				Orig.-Verschr., i.V.		
	RC30	51	-	100, 110	205/60, 215/55, 225/55, 235/50				Orig.-Verschr.		
	B32	51	-	100, 110	205/60, 215/55, 225/55, 235/50				Orig.-Verschr.		
	B39	51	-	100, 110	205/60, 215/55, 225/55, 235/50				Orig.-Verschr., nicht Bremse 360mm		
	Oxigin 25	51	-	68-104	215/55, 225/50, 225/55				Orig.-Verschr., nicht für M-Sportbremse		
		44	ZP599F	100-150 100-221	205/60, 215/55, 225/50, 225/55 215/55M+S				nicht für Fahrzeuge mit 19"-Sportbremse		
8 x 18	B42 / B44	45	-	100, 110	225/55				Orig.-Verschr.		
	AC-MB6	45	-	100, 110	225/55				Orig.-Verschr., nicht Bremse 360mm		
	AC-M10	45	-	100, 110	225/55				Orig.-Verschr., nicht Bremse 360mm		
8 x 19	RC32	46	-	100, 110	245/45				Orig.-Verschr., i.V.		
	RC34	46	-	100-221	245/45				Orig.-Verschr.		
	B43	46	-	100, 110	225/50, 235/45, 245/45				Orig.-Verschr., nicht Bremse 360mm		
	RC27	47	-	100, 110	225/50, 235/45, 245/45				Orig.-Verschr.		
	B40	47	-	100, 110	225/50, 235/45, 245/45				Orig.-Verschr.		
	CA 24	43	ZP599F	68-104	225/45, 235/45				nicht Bremse 360mm		
	Oxigin 29	43	ZP599F	100, 110	235/45				nicht Bremse 360mm		
8,5 x 19	B42	47	-	100, 110	235/45, 245/45				Orig.-Verschr.		
	AC-M10	45	-	100, 110	235/45				Orig.-Verschr., nicht Bremse 360mm		
	CA 20	45	ZP599F	100, 110	235/45				nicht Bremse 360mm		
	CA 23	45	ZP593F	100, 110	235/45						
	Oxigin 28	45	ZP593F	100, 110	235/45						
9 x 19	CA 17	49	ZP593F	68-104	235/45				nicht Bremse 360mm		
	CA 24	49	ZP599F	68-104	235/45				nicht Bremse 360mm		
8 x 20	RC36	46	-	100, 110	215/45, 225/40, 235/40, 245/40				Orig.-Verschr.		
	B43	46	-	100, 110	215/45, 225/40, 235/40, 245/40				Orig.-Verschr.		
	B40	47	-	100, 110	225/50, 235/45, 245/45				Orig.-Verschr.		
	B43	48	-	100, 110	215/45, 225/40, 235/40, 245/40				Orig.-Verschr.		
8,5 x 20	B42	48	-	100, 110	225/40, 235/40, 245/40				Orig.-Verschr.		
	B44	40	-	100, 110	225/40				Orig.-Verschr., nicht Bremse 360mm		
	CA 17	48	ZP599F	68-104	235/40, 245/40				nicht für M-Sportbremse		
	AC-MB6	50	-	100, 110	225/40, 235/40, 245/40				Orig.-Verschr.		
9 x 20	B43	44	-	100, 110	225/40				Orig.-Verschr.		
	CA 20	45	ZP599F	100, 110	225/40				nicht Bremse 360mm		
	CA 23	45	ZP599F	100, 110	225/40				nicht Bremse 360 u. 385mm		

BMW iX1 xDrive30 NEU		2. Quartal 2023		U1X	5/112	66,7	e1*2018/858*00153*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 17	RC27	45	-	68-104	205/65, 215/60, 225/60, 235/55			Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC34	39	-	100-150	205/65, 215/60, 215/65, 225/60			Orig.-Verschr., nicht Bremse 360x30mm
7 x 17	RC27	41	-	68-104	205/65, 215/60, 215/65, 225/60, 235/55, 245/55			Orig.-Verschr., nicht Bremse 360mm
	RC34	41	-	68-104	205/65, 215/60, 215/65, 225/60			Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
	RC32	47	-	68-104	215/60, 215/65, 225/60, 235/55			Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
	RC34	47	-	68-104	215/60, 215/65, 225/60, 235/55			Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
	Pro1	49	ZP599F	68-104	215/60, 215/65, 225/60, 235/55			nur M+S, nicht Bremse 360x30mm
	RC32	52	-	94-150	225/60, 235/55, 245/55			Orig.-Verschr.
7,5 x 17	RC34	52	-	68-104	215/60, 225/60, 235/55, 245/55			Orig.-Verschr., nicht Bremse 360x30mm
		45	-	68-108	205/65, 215/60, 215/65, 225/60			Orig.-Verschr., nicht Bremse 360x30mm
	CA 20	35	ZP599F	68-104	205/65, 215/60, 215/65, 225/60			nicht Bremse 360mm
6,5 x 18	RC34	41	-	68-104	205/60			Orig.-Verschr.
7,5 x 18	RC32	50	-	68-104	225/55			Orig.-Verschr.
	RC34	50	-	68-104	225/55			Orig.-Verschr.
				68-104	215/55, 225/55, 235/50, 245/50			
	RC30	51	-	68-104	205/60, 215/55, 225/55, 235/50			Orig.-Verschr., nicht Bremse 360mm
	RC34	51	-	68-104	215/55, 225/55, 235/50, 245/50			Orig.-Verschr.
	B32 / B39	51	-	68-104	205/60, 215/55, 225/55, 235/50			Orig.-Verschr., nicht Bremse 360mm
	CA 20	51	-	68-104	215/55, 225/55, 235/50, 245/50			Orig.-Verschr., nicht Bremse 360x30mm
	Oxigin 25	51	-	68-104	215/55, 225/50, 225/55			Orig.-Verschr., nicht für M-Sportbremse
44		ZP599F	68-104	205/60, 215/55, 225/50, 225/55			nicht für Fahrzeuge mit 19"-Sportbremse	
8 x 18	RC34	43	-	68-104	215/55, 225/55			Orig.-Verschr.
		48	-	68-104	215/55, 225/55			Orig.-Verschr.
	B42 / B44	45	-	68-104	225/55, 235/50, 245/50, 255/45			Orig.-Verschr., nicht Bremse 360mm
	AC-MB6	45	-	68-104	225/55, 235/50, 245/50, 255/45		Orig.-Verschr., nicht Bremse 360mm	

	AC-M10 CA 20 FMI08 Thoe	45	-	68-104	225/55, 235/50, 245/50, 255/45		Orig.-Verschr., nicht Bremse 360mm
		45	ZP599F	68-104	225/55, 235/50, 245/50, 255/45		nicht Bremse 360mm
		49	-	68-104	215/55, 225/55, 235/50, 255/45		Orig.-Verschr.
7,5 x 19	RC34	45,5	-	68-104	205/55, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 19	RC32	46	-	68-104	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC34	46	-	68-104	245/45		Orig.-Verschr.
				68-104	225/45, 225/50, 235/45, 245/45		
	B43	46	-	68-104	245/45		Orig.-Verschr., nicht Bremse 360mm
				68-104	225/50, 235/45, 245/45		Orig.-Verschr.
	RC27	47	-	94 (200)	225/50, 235/45, 245/45		Orig.-Verschr.
	RC32	47	-	68-104	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC34	43	-	68-104	225/45, 235/45		Orig.-Verschr.
		48	-	68-104	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	B40	47	-	94 (200)	225/50, 235/45, 245/45		Orig.-Verschr.
	CA 24	43	ZP599F	68-104	225/45, 235/45		nicht Bremse 360mm
	FMI08 Thoe	47	-	68-104	225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8,5 x 19	Oxigin 29	39	ZP599F	68-104	225/50, 235/45		nicht Bremse 360mm
		43	ZP599F	68-104	225/50, 235/45, 245/45		nicht Bremse 360mm
	B43	40	-	94 (200)	235/45, 245/45		Orig.-Verschr.
	B44	42	-	68-104	235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	AC-M10	45	-	68-104	235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	CA 23	45	ZP593F	94 (200)	235/45, 245/45		
	FMI11 Elatha	45	F93	94	225/45, 235/45		
	8300 - 1972	45	-	94-150	225/45, 235/45		Orig.-Verschr.
9 x 19	Oxigin 28	40+45	ZP593F	94 (200)	235/45, 245/45		
	CA 17 / CA 24	49	ZP599F	68-104	235/45		nicht Bremse 360mm
	FMI12 Kari	49	F93	94-150	235/45		
8 x 20	RC36	46	-	68-104	235/40, 245/40		Orig.-Verschr.
	B43	46	-	68-104	235/40, 245/40		Orig.-Verschr.
		48	-	68-104	235/40, 245/40		Orig.-Verschr.
8,5 x 20	B42	48	-	94 (200)	235/40, 245/40		Orig.-Verschr., nicht Bremse 360mm
	AC-MB6	50	-	68-104	235/40, 245/40		Orig.-Verschr.
9 x 20	B43	44	-	94 (200)	235/40, 245/40		Orig.-Verschr.
	CA 20	45	ZP599F	68-104	235/40, 245/40		nicht Bremse 360mm
	CA 23	45	ZP599F	68-104	235/40, 245/40		nicht Bremse 360 u. 385mm
9 x 21	CA 20	45	ZP599F	68-105	245/35		nicht Bremse 360mm

BMW X1 M35i xDrive NEU

im Laufe 2023

U1X / U11

5/112

66,7

e1*2018/858*00153*..

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 19	B43	46	-	221	245/45	 Orig.-Verschr., nicht Bremse 360mm
				221	225/50M+S, 235/45M+S, 245/45	
8,5 x 19	Oxigin 29	43	ZP599F	221	235/45M+S	nicht Bremse 360mm
	AC-M10	45	-	221	235/45M+S	Orig.-Verschr., nicht Bremse 360mm
8 x 20	CA 20	45	ZP599F	221	235/45M+S	nicht Bremse 360mm
	RC36	46	-	221	245/40	 Orig.-Verschr.
					215/45M+S, 225/40M+S, 235/40M+S, 245/40	
	B43	46	-	221	245/40	 Orig.-Verschr.
					215/45M+S, 225/40M+S, 235/40M+S, 245/40	
					215/45M+S, 225/40M+S, 235/40M+S, 245/40	Orig.-Verschr.
9 x 20	CA 20	45	ZP599F	221	225/40M+S	nicht Bremse 360mm

BMW X2

2018

F2X/F39

5/112

66,7

e1*2007/46*1824*...

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	39	-	100-170	205/60	 Orig.-Verschr., nur M+S
	RC34	39	-	85-170	205/60M+S	 Orig.-Verschr., nicht 4-Kolben Festsattel Kennz. M blau mit Bremse 360x30mm
	RC27	45	-	85-170	205/60, 215/55, 215/60, 225/55	Orig.-Verschr., nur M+S, nicht Bremse 360mm
7 x 17	RC27	41	-	85-170	205/60	Orig.-Verschr., nur M+S, nicht Bremse 360mm
		49	-	85-170	205/60, 215/55, 215/60, 225/55	Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC30	47	-	85-170	205/60, 215/55, 215/60	Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC32	47	-	85-170	205/60	Orig.-Verschr., nur M+S, nicht Bremse 360mm
	RC34	41+47	-	85-170	205/60	Orig.-Verschr., nur M+S, nicht Bremse 360mm
	B39	47	-	100-170	205/60, 215/55, 215/60	Orig.-Verschr., nur M+S
	Pro1	49	ZP599F	85-170	205/60	nur M+S, nicht Bremse 360x30mm
7,5 x 17	RC27	52	-	85-170	225/55	 Orig.-Verschr.
	RC32	52	-	85-170	205/60M+S, 225/55	 Orig.-Verschr., nicht Bremse 360x30mm
	RC34	52	-	85-170	205/60M+S, 225/55	 Orig.-Verschr.,auch Hybrid,nicht Bremse 360mm
	BR-I	52	-	100-170	225/55	 Orig.-Verschr., nicht Bremse 360mm
	RC32	54	-	85-170	205/60	Orig.-Verschr., nur M+S, auch Hybrid Fahrzeuge, nicht 4-Kolben Festsattel Kennz. M blau mit Bremse 360x30
	AC-518	47	ZP593F	100-170	205/60M+S	Orig.-Verschr., nicht Bremse 360mm

6,5 x 18	RC34	41	-	85-225	205/55		Orig.-Verschr.
7 x 18	RC27	54	-	85-170	225/50		Orig.-Verschr.
	RC32	54	-	85-170	205/55M+S		Orig.-Verschr., nicht Bremse 360mm
7,5 x 18	RC30	51	-	85-170	205/55M+S, 215/50M+S, 225/50 , 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	RC32	51	-	100-170	225/50		Orig.-Verschr.
				85-170	205/55M+S, 225/45, 225/50, 235/45		Orig.-Verschr.
	B32 / B39	51	-	85-170	225/50 , 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
				85-225	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr., nur M+S, nicht Bremse 360mm
	BR-I	51	-	100-170	225/50		Orig.-Verschr., nicht Bremse 360mm
	CA 20	51	-	85-170	225/50		Orig.-Verschr., nicht Bremse 360x30mm
	Oxigin 25	51	-	85-170	225/50		Orig.-Verschr., nich für M-Sportbremse
	B39	51	-	100-170	205/55M+S, 215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm
	RC34	50	-	85-225	205/55M+S, 225/45, 225/50, 235/45		Orig.-Verschr.
		51	-	85-225	205/55M+S, 225/45, 225/50, 235/45		Orig.-Verschr.
8 x 18	CA 20	51	-	85-225	205/55M+S, 225/45, 225/50, 235/45		Orig.-Verschr., nicht Bremse 360x30mm
	RC34	48	-	85-225	225/45, 235/45		Orig.-Verschr.
	B38	52	-	100-170	235/45		Orig.-Verschr., nicht Bremse 360mm
	AC-518	50	-	100-170	235/45		Orig.-Verschr.
	FMI08 Thoe	49	-	85-225	225/45, 235/45		Orig.-Verschr.
	FMI11 Elatha	45	F93	85-225	225/45		
7,5 x 19	FMI12 Kari	45	Kit 0334	85-225	225/45		
	RC34	45,5	-	85-225	225/45		Orig.-Verschr.
8 x 19	RC27	47	-	120-170	225/45		Orig.-Verschr.
	RC32	47	-	85-225	225/45		Orig.-Verschr.
	B40	47	-	85-225	225/45		Orig.-Verschr.
	BR-I	47	-	100-170	225/45		Orig.-Verschr., nicht Bremse 360mm
				85-225	225/45		Orig.-Verschr., nicht Bremse 360mm, nur für Fahrzeuge ohne Kunststoff Verschlusskappen auf den Fahrzeugnaben
	CA 19	47	ZP599F	85-225	225/45		
	FMI07 Atena	47	F93	85-225	225/45		
	FMI08 Thoe	47	-	85-225	225/45		Orig.-Verschr.
	FMI14 Jupiter	47	-	85-225	225/45		Orig.-Verschr.
	RC32	46	-	85-225	225/45		Orig.-Verschr.
	RC34	46	-	85-225	225/45		Orig.-Verschr.
		48	-	85-225	225/45, 235/40		Orig.-Verschr.
	B38	52	-	85-225	225/45, 235/40		Orig.-Verschr., nicht Bremse 360mm
	B43	46	-	85-225	225/45		Orig.-Verschr.
8,5 x 19	B37	47	-	100-170	225/45, 235/40, 245/40		Orig.-Verschr., ✖
	B42	47	-	85-225	225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 330 u. 360mm, ✖
	8300 - 1972	45	-	85-225	235/40		Orig.-Verschr.
	LS 2	52	14x1,25x40	140-170	225/45		Spurverbr. 751126651106 (11 mm)
9 x 19	CA 17	49	ZP599F	85-170	225/40		✖
8 x 20	RC36	46	-	85-225	225/35, 225/40		Orig.-Verschr.
	B38	52	-	85-225	225/35, 225/40, 235/35		Orig.-Verschr., nicht Bremse 360mm
	B43	46+48	-	85-225	225/35, 225/40		Orig.-Verschr.
	FMI08 Thoe	45	-	85-225	225/40		
8,5 x 20	RC29	52	-	85-225	225/35, 225/40		Orig.-Verschr.

BMW X2 Plug-in-Hybrid				2020	F2X	5/112	66,7	e1*2007/46*1824*..
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	39	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	RC34	39	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm bzw. 4-Kolben Bremssattel	
7 x 17	RC27	45	-	92	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	RC27	41	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	RC30	47	-	92	205/60, 215/55, 215/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	RC34	47	-	92	205/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
	B39	47	-	92	205/60, 215/55, 215/60		Orig.-Verschr., nur M+S, nicht Bremse 360mm	
7,5 x 17	RC27	52	-	92	225/55		Orig.-Verschr.	
7,5 x 18	B32	51	-	92	205/55M+S, 215/50M+S, 225/50 , 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm	
	B39	51	-	92	205/55M+S, 215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm	
	RC30	51	-	92	205/55M+S, 215/50M+S, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 360mm	
8 x 18	RC34	48	-	92	225/45, 235/45		Orig.-Verschr.	
	B38	52	-	92	235/45		Orig.-Verschr., nicht Bremse 360mm	
	AC-518	50	-	92	235/45		Orig.-Verschr., nicht Bremse 360mm	
7,5 x 19	B39	51	-	92	225/45		Orig.-Verschr., nicht Bremse 360mm	
8 x 19	RC27	47	-	92	225/45		Orig.-Verschr.	
	B40	47	-	92	225/45		Orig.-Verschr.	
	B38	52	-	92	225/45, 235/40		Orig.-Verschr., nicht Bremse 360mm	
	B43	46	-	92	225/45		Orig.-Verschr.	
8 x 20	B38	52	-	92	225/40, 235/35		Orig.-Verschr., nicht Bremse 360mm	
	B43	46+48	-	92	225/40		Orig.-Verschr.	

8,5 x 20	RC29	52	-	92	225/40		Orig.-Verschr.
----------	------	----	---	----	--------	--	----------------

BMW X2 NEU		ab März 2024		U2X / U10		5/112	66,7	e1*2018/858*00371*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 17	RC27	45	-	100-115	205/65, 215/60, 225/60, 235/55				Orig.-Verschr., nur M+S, nicht Bremse 360mm
7 x 17	RC27	41	-		205/65				Orig.-Verschr., i.V.
	RC34	41	-	100-115	205/60, 205/65				Orig.-Verschr., nur M+S, nicht Bremse 360x30mm
	RC32	47	-	100-115	205/60				Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
7,5 x 17	RC34	45	-	100-115	205/60, 205/65				Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
6,5 x 18	RC34	41	-	100-221	205/60				Orig.-Verschr.
7,5 x 18	RC32	50	-	100-115	225/55				Orig.-Verschr., nicht Bremse 360x30mm
				100-115	205/55M+S, 225/50, 225/55, 235/50, 245/45, 245/50				
				100-115	225/55				
	RC34	50	-	100-115	205/55M+S, 225/50, 225/55, 235/50, 245/45, 245/50				Orig.-Verschr., nicht Bremse 360x30mm
				100-115					
				100-115	205/55M+S, 225/50, 225/55, 235/50, 245/45, 245/50				
	B39 CA 20	51	-	100-115	205/60, 215/55, 225/55, 235/50				Orig.-Verschr., nicht Bremse 360mm
		51	-	100-115	205/55M+S, 225/50, 225/55, 235/50, 245/45, 245/50				Orig.-Verschr., nicht Bremse 360x30mm
		Oxigin 25	51	-	100-115	215/55M+S, 225/50, 225/55			
100-115	225/50, 225/55					Orig.-Verschr., mit M-Sportpaket Radhausverbr., nicht für M-Sportbremse			
100-221	215/55M+S								
8 x 18	RC34	43	-	100-115	225/50, 225/55, 235/50, 245/45, 255/45				Orig.-Verschr.
		48	-	100-115	225/50, 225/55, 235/50, 245/45, 245/50, 255/45				Orig.-Verschr.
7,5 x 19	RC34	32	-	100-115	205/55M+S, 225/45, 235/45				Orig.-Verschr.
		45,5	-	100-115	205/55M+S, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr.
8 x 19	RC32	46	-	100-115	245/45				Orig.-Verschr.
				100-115	225/45, 225/50, 235/45, 245/40, 245/45				Orig.-Verschr.
	RC34	46	-	100-115	245/45				Orig.-Verschr., nicht Bremse 360x30mm
				100-115	225/45, 225/50, 235/45, 245/40, 245/45				Orig.-Verschr.
	RC32	47	-	100-115	225/45, 225/50, 235/45, 245/40, 245/45				Orig.-Verschr., i.V.
RC34	43+48	-	100-115	225/45, 225/50, 235/45, 245/40, 245/45				Orig.-Verschr.	
8,5 x 19	B41	39	-	100-115	225/45, 235/45				Orig.-Verschr.
8 x 20	RC36	46	-	100-115	245/40				Orig.-Verschr.
					215/45M+S, 225/40, 235/40, 245/40				
	B43	46	-	100-115	245/40				Orig.-Verschr.
				215/45M+S, 225/40, 235/40, 245/40					
8,5 x 20	CA 17	48	ZP599F	100-115	225/40, 235/40, 245/40				mit Standard Radhausverbr., nicht für M-Sportbremse
				100-115	225/40, 235/40				mit M-Sportpaket Radhausverbr., nicht für M-Sportbremse
				100-221	245/40				
	AC-MB6	50	-	100-115	225/40, 235/40, 245/40				Orig.-Verschr.
8,5 x 21	B41	43	-	100-115	245/30, 245/35				Orig.-Verschr.

BMW X2 elektro NEU		ab März 2024		U2X / U10		5/112	66,7	e1*2018/858*00371*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 18	Oxigin 25	51	-	68-104	215/55M+S, 225/50, 225/55			Orig.-Verschr., mit Standard Radhausverbr., nicht für M-Sportbremse	
				68-104	215/55M+S, 225/50, 225/55			Orig.-Verschr., mit M-Sportpaket Radhausverbr., nicht für M-Sportbremse	
7,5 x 18	Oxigin 25	44	ZP599F	68-104	205/60M+S, 215/55, 225/50, 225/55			mit Standard Radhausverbr., nicht für 19"-Sportbremse	
				68-104	205/60M+S, 215/55, 225/50, 225/55, 235/50			mit M-Sportpaket Radhausverbr., nicht für 19"-Sportbremse	
8,5 x 20	CA 17	48	ZP599F	68	235/40			mit Standard Radhausverbr., nicht für M-Sportbremse	
				68-104	245/40				
				68	235/40			mit M-Sportpaket Radhausverbr., nicht für M-Sportbremse	
				68-104	245/40				

BMW iX2 NEU		ab März 2024		U2X / U10		5/112		66,7		e1*2018/858*00371*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 17	RC27	45	-	68, 104	205/65, 215/60, 225/60, 235/55				Orig.-Verschr., nur M+S, nicht Bremse 360mm		
7 x 17	RC27	41	-		205/65				Orig.-Verschr., i.V.		
	RC34	41	-	68-104	205/60, 205/65				Orig.-Verschr., nur M+S, nicht Bremse 360x30mm		

	RC32	47	-	68-104	205/60		Orig.-Verschr.,nur M+S,nicht Bremse 360x30mm
7,5 x 17	RC34	45	-	68-104	205/60, 205/65, 215/60, 215/65, 225/55, 225/60, 235/55, 245/50, 245/55		Orig.-Verschr., nicht Bremse 360x30mm
		52	-	68-104	215/60, 225/55, 225/60, 235/55, 245/55		Orig.-Verschr., nicht Bremse 360x30mm
6,5 x 18	RC34	41	-	68-104	205/60		Orig.-Verschr.
7,5 x 18	RC32	50	-	68-104	225/55		Orig.-Verschr.
				68-104	205/55, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr., nicht Bremse 360x30mm
	RC34	50	-	68-104	225/55		Orig.-Verschr., nicht Bremse 360x30mm
				68-104	205/55, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr., nicht Bremse 360x30mm
		51	-	68-104	205/55, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr.
	B39	51	-	68, 104	205/60, 215/55, 225/55, 235/50		Orig.-Verschr., nicht Bremse 360mm
	CA 20	51	-	68-104	205/55, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr., nicht Bremse 360x30mm
8 x 18	RC34	43	-	68-104	215/55, 225/50, 225/55, 235/50, 245/45, 255/45		Orig.-Verschr.
		48	-	68-104	215/55, 225/50, 225/55, 235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
7,5 x 19	RC34	32	-	68-104	205/55, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
		45,5	-	68-104	205/55, 215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 19	RC32	46	-	68-104	245/45		Orig.-Verschr.
				68-104	215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC34	46	-	68-104	245/45		Orig.-Verschr., nicht Bremse 360x30mm
				68-104	215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
	B43	46	-		245/45		Orig.-Verschr., ECE i.V.
				68, 104	225/50, 235/45, 245/45		Orig.-Verschr.
	RC32	47	-	68-104	215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse 360x30mm
	RC34	43+48	-	68-104	215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
8,5 x 19	B41	39	-	68-104	225/45, 235/45		Orig.-Verschr.
8 x 20	RC36	46	-	68, 104	245/40		Orig.-Verschr.
				68	215/45, 225/40, 235/40		Orig.-Verschr.
	B43	46	-	68, 104	245/40		Orig.-Verschr.
				68	215/45, 225/40, 235/40		Orig.-Verschr.
		48	-	68, 104	245/40		Orig.-Verschr.
				68, 104	245/40		Orig.-Verschr.
8,5 x 20	RC36	40	-	68	225/40, 235/40		Orig.-Verschr.
				68, 104	245/40		Orig.-Verschr.
	AC-MB6	50	-	68	225/40, 235/40		Orig.-Verschr.
				68, 104	245/40		Orig.-Verschr.
8,5 x 21	B41	43	-	68-104	245/35		Orig.-Verschr.

BMW X2 M35i xDrive		2024		U2X		5/112		66,7		e1*2018/858*00371*..	
Sensor - Brocksens 1											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
8 x 20	RC36	46	-	221	245/40				Orig.-Verschr.		
					215/45M+S, 225/40M+S, 235/40M+S, 245/40						
	B43	46	-	221	245/40				Orig.-Verschr.		
					215/45M+S, 225/40M+S, 235/40M+S, 245/40						
					215/45M+S, 225/40M+S, 235/40M+S, 245/40						
8,5 x 20	RC36	40	-	221	225/40M+S, 235/40M+S				Orig.-Verschr.		

BMW X3 (siehe Konfigurator)		ab 09.10		X3/F25		5/120		72,6		e1*2007/46*0512*..., e1*2007/46*0454*...	
-----------------------------	--	----------	--	--------	--	-------	--	------	--	--	--

BMW X3 (siehe Konfigurator)		ab 09.10	X3/F25	5/120	72,6	e1*2007/46*0512*...., e1*2007/46*0454*...	
-----------------------------	--	----------	--------	-------	------	---	--

BMW X3		ab 11/2017		G01 / G3X		5/112		66,7		e1*2007/46*1797..	
Sensor - Brocksens 1											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
7 x 18	RC27	22	-	100-195	225/60				Orig.-Verschr.		
				120-195	225/60, 235/55, 245/55						
	RC32	22	-	100-210	225/55, 225/60				Orig.-Verschr. nur bis 1.600 kg Achslast		
	RC34	22	-	100-210	225/60				Orig.-Verschr.		
7,5 x 18	BR-I	22	-	100-195	225/60				Orig.-Verschr.		
	RC32	23+25	-	100-210	225/55, 225/60				Orig.-Verschr.		
	RC34	25	-	100-210	225/55, 225/60				Orig.-Verschr.		
	B32	25	-	100-195	225/60, 235/55				Orig.-Verschr.		
	RC27	30	-	100-195	225/60, 235/55, 235/60				Orig.-Verschr.		
	RC32	30	-	100-210	225/55, 225/60				Orig.-Verschr.		
	RC34	30	-	100-210	225/55, 225/60				Orig.-Verschr.		

8 x 18	B42	30+35	-	100-210	225/60, 235/55		Orig.-Verschr.
	B44	30+35	-	100-210	225/60, 235/55		Orig.-Verschr.
	CA 17	35	ZP593F	100-195	245/55		
	CA 26	30	ZP599F	100-210	225/60, 235/55		
	AC-M10	30	-	100-210	225/60, 235/55		Orig.-Verschr.
7,5 x 19	FMI08 Thoe	34	-	100-210	235/55, 245/55		Orig.-Verschr.
	RC32	32	-	100-195	245/50		Orig.-Verschr.
	RC34	32	-	100-210	245/50		Orig.-Verschr., auch Hybrid
	B32	32	-	100-265	245/50M+S		Orig.-Verschr.
				100-210	225/55, 235/50, 245/50		
	BR-I	32	-	100-195	225/55, 235/50, 245/50		Orig.-Verschr., nicht Bremse 348x36mm
				100-265	245/50M+S		
	CA 26	32	ZP599F	100-210	245/50		
				100-265	245/50M+S		
	B43	28	-	100-265	255/45M+S		Orig.-Verschr.
				100-210	225/55, 235/50, 255/45		
Oxigin 18	35	ZP599F	265	255/50		Allradantrieb	
8 x 19	RC27	30	-	100-195	225/55, 235/50, 255/45		Orig.-Verschr.
	RC32	30	-	100-210	225/55		Orig.-Verschr., auch für Hybrid
	RC34	27	-	100-195	225/55		Orig.-Verschr.
	B40	30	-	100-195	225/55, 235/50, 255/45		Orig.-Verschr.
				265	255/45M+S		
	CA 19 / CA 24	30	ZP599F	100-210	225/55, 235/50, 255/45		incl. Hybrid
	FMI08 Thoe	26	-	100-210	225/50, 225/55		Orig.-Verschr.
	FMI14 Jupiter	26	-	100-210	225/50, 225/55		Orig.-Verschr.
	Oxigin 29	32	ZP599F	100-210	225/55, 235/50, 245/50, 255/45		
100-265				245/50, 255/45			
8,5 x 19	B32	25	-	120-195	235/50, 245/50, 255/45, 265/45, 275/45		Orig.-Verschr. ✖
	B42 / B44	30	-	100-210	235/50, 255/45		Orig.-Verschr.
				100-265	255/45M+S		
	AC-M10	30	-	100-210	235/50, 255/45		Orig.-Verschr.
				100-265	255/45M+S		
	CA 23	30	ZP599F	100-210	235/50, 255/45		
	Oxigin 14	35	ZP599F+R	100-195	245/50, 255/45, 265/45		+ Red Ringe BA12=72,6-66,6, nicht Bremse 348mm
	Oxigin 19	35	ZP593F	100-195	245/50, 255/45, 265/45		nicht Bremse 348mm
		40	ZP593F	100-195	255/45		
	Oxigin 20	35	ZP599F	100-195	245/50, 255/45, 265/45		
		40	ZP599F	100-195	255/45		
Oxigin 28	30	ZP599F	100-210	235/50, 255/45			
			100-265	255/45M+S			
			Race LS 2	35	14x1,25x30		135-265
9 x 19	CA 24	35	ZP599F	100-210	255/45		
8 x 20	RC36	VA 27	-	100-265	VA 245/45		Orig.-Verschr.
9,5 x 20		HA 43			HA 275/40		
8 x 20	B40	VA 27	-	100-265	VA 245/45		Orig.-Verschr.
9,5 x 20				100-195	VA 235/45		
				100-265	HA 275/40		
				100-195	HA 245/45, 265/40		
8 x 20	BR-I	VA 27	-	100-265	VA 245/45		Orig.-Verschr.
9,5 x 20		HA 43			HA 275/40		
8 x 20	RC36	27	-	100-265	245/45		Orig.-Verschr., nur M+S
				100-210	235/45, 245/45		Orig.-Verschr.
	B40	27	-	100-265	245/45		Orig.-Verschr., nur M+S
				100-195	235/45, 245/45		Orig.-Verschr.
				100-265	245/45M+S		
	B43	27	-	100-265	245/45		Orig.-Verschr., nur M+S
				100-210	235/45, 245/45		Orig.-Verschr.
				100-265	245/45		Orig.-Verschr., nur M+S
8,5 x 20	RC29	26	-	120-195	235/45, 245/45, 255/40		Orig.-Verschr., ab 245/45 ✖
				100-210	235/45, 245/40, 245/45		Orig.-Verschr., auch für Hybrid Fahrzeuge
				100-195	245/40, 245/45, 255/40		
	B32	30	-	100-195	235/45, 245/45, 255/40		Orig.-Verschr.
				100-265	245/45M+S, 255/40M+S		
	B41	35	-	100-210	235/45, 245/40, 245/45, 255/40		Orig.-Verschr., auch für Hybrid
	B42 / B43	30+35	-	100-210	235/45, 245/45, 255/40		Orig.-Verschr.
				100-265	245/45M+S, 255/40M+S		
	B44	30+35	-	100-210	235/45, 245/45, 255/40		Orig.-Verschr.
				100-265	245/45M+S, 255/40M+S		
	AC-M10	30	-	100-210	235/45, 245/45, 255/40		Orig.-Verschr.
				100-265	245/45M+S, 255/40M+S		
	CA 17	35	ZP593F	100-195	255/40, 255/45		
	CA 19	32	ZP599F	100-210	255/40, 255/45		

	Race LS 2	30	14x1,25x30	135-265	235/45, 245/45, 245/40, 255/40		
	Fascinate	30	14x1,25x30	135-265	235/45, 245/40, 245/45, 255/40		Sternschrauben!!!!
	Hibonit	24	14x1,25x30	135-265	235/45, 245/40, 245/45, 255/40		
9 x 20	RC36	35	-	100-210	235/45, 245/45, 255/40HA		Orig.-Verschr.
				100-265	245/45M+S		
	B40	34	ZP599F	100-265	245/45, 255/40, 255/45		
				100-195	235/45, 245/45, 255/40HA		Orig.-Verschr.
	B41	35	-	100-265	245/45M+S		
				100-210	245/40, 245/45		Orig.-Verschr.
	B43	35	-	100-210	235/45, 245/45, 255/40HA		Orig.-Verschr.
				100-265	245/45M+S		
	BR-IT	35	-	100-195	235/45, 245/45, 265/40HA, 255/40HA		Orig.-Verschr., ab 265/40 ✖
				100-265	245/45, 275/40		Orig.-Verschr., nur M+S, bei 275/40 ✖
	CA 20	35	ZP599F	100-210	235/45, 245/45, 255/40HA		
				100-265	245/45M+S		
	Oxigin 19	35	ZP568F	120-265	245/45, 255/40, 255/45		
	Oxigin 25	35	ZP593F	100-195	245/45, 255/40, 255/45		
	Oxigin 28	35	ZP599F	100-210	235/45, 245/45, 255/40HA		
				100-265	245/45M+S		
	AC-518	33	F93	100-210	245/45		incl. Hybrid
	AC-522	33	F93	100-210	245/45		incl. Hybrid
	FMI07 Atena	33	F93	100-195	245/40, 245/45		
8,5 x 21	B41	VA 30	-	100-210	VA 245/35, VA 245/40+HA 275/35, 285/30		Orig.-Verschr., bei 285/30 ✖
9,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	100-265	VA 245/40+HA 275/35		Orig.-Verschr.
9,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	100-265	VA 245/40, 255/40		Orig.-Verschr., HA bei 285/35 ✖
9,5 x 21		HA 43			HA 275/35, 285/35		
8,5 x 21	B41	30	-	100-210	245/35, 245/40		Orig.-Verschr.
		34	-	100-210	245/35, 245/40, 255/35		Orig.-Verschr.
	B43	30+34	-	100-210	245/40, 255/35, 255/40		Orig.-Verschr.
				100-265	245/40, 255/35		Orig.-Verschr., nur M+S
9 x 21	CA 17	30	ZP599F	100-210	245/40		
	Oxigin 18	35	ZP593F	100-195	255/40		nicht Bremse 348mm
	Fascinate	30	14x1,25x30	135-265	245/40		Sternschrauben!!!!
	GTS	30	14x1,25x30	135-265	245/40		
	Race LS 2	30	14x1,25x30	135-265	245/40		
9 x 22	Fascinate	30	14x1,25x30	135-265	245/35, 255/30		Sternschrauben!!!!
	LS 2	30	14x1,25x30	135-265	245/35, 255/30		

Kombinationen

8 x 19	B40	27+30	-	100-195	VA 235/50, 245/50, 255/45		Orig.-Verschr.
9 x 19		40+44			HA 245/50, 255/45, 275/45		
8 x 20	B43	30	-	100-210	VA 235/45, 245/45		Orig.-Verschr.
9 x 20		44			HA 265/40, 275/40		
8,5 x 20	B32	VA 30	-	120-195	VA 235/45, 245/45, 255/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 20		HA 42			HA 245/45, 255/40, 265/40, 275/40, 285/35		
8,5 x 20	Hibonit	24	14x1,25x30	135-265	VA 235/45+HA 265/40, VA 245/45+HA 275/40,		
10 x 20		38			VA 245/40+HA 275/35, VA 245/40+HA 285/35		
8,5 x 20	Race LS 2	30	14x1,25x30	135-265	VA 235/45+HA 265/40, VA 245/45+HA 275/40		
10 x 20		38			VA 245/40+HA 275/35, VA 245/40+HA 285/35		
9 x 21	Fascinate	30	14x1,25x30	135-265	VA 245/40,+HA 275/35, VA 245/35+HA 285/30		Sternschrauben!!!!
10,5 x 21		44					
9 x 21	GTS	30	14x1,25x30	135-265	VA 245/40,+HA 275/35, VA 245/35+HA 285/30		
10,5 x 21		38					
9 x 21	Race LS 2	30	14x1,25x30	135-265	VA 245/40,+HA 275/35, VA 245/35+HA 285/30		
10,5 x 21		44					

BMW X3 xDrive 30e NEU		2021	G01 / G3X	5/112	66,7	e1*2007/46*1797..	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 18	RC27	22	-	120, 135	225/60		Orig.-Verschr., Plug-in-Hybrid
8 x 18	RC27	30	-	120, 135	225/60, 235/55		Orig.-Verschr., Plug-in-Hybrid
	AC-M10	30	-	120, 135	225/60, 235/55		Orig.-Verschr., Plug-in-Hybrid
	CA 23 / CA 26	30	ZP599F	120, 135	225/60, 235/55		Plug-in-Hybrid
7,5 x 19	B32	32	-	120, 135	245/50		Orig.-Verschr., Plug-in-Hybrid
	CA 26	32	ZP599F	120, 135	245/50		Orig.-Verschr., Plug-in-Hybrid
	RC32	32	-	120, 135	225/55, 235/50, 245/50		Orig.-Verschr., Plug-in-Hybrid
8 x 19	RC27	30	-	120, 135	225/55, 235/50, 245/50		Orig.-Verschr., Plug-in-Hybrid
	B43	28	-	120, 135	225/55, 235/50, 255/45		Orig.-Verschr., Plug-in-Hybrid
	Oxigin 29	32	ZP599F	120, 135	225/55, 235/50, 245/50, 255/45		Plug-in-Hybrid
8,5 x 19	AC-M10	30	-	120, 135	235/50, 255/45		Orig.-Verschr., Plug-in-Hybrid
	CA 23	30	ZP599F	120, 135	235/50, 255/45		Plug-in-Hybrid
	Oxigin 28	30	ZP599F	120, 135	235/50, 255/45		Plug-in-Hybrid

8 x 20	RC36	VA 27	-	120, 135	VA 245/45		Orig.-Verschr., Plug-in-Hybrid
9,5 x 20		HA 43			HA 275/40		
8 x 20	RC36	27	-	120, 135	235/45, 245/45		Orig.-Verschr., nur M+S, Plug-in-Hybrid
	B40	27	-	120, 135	245/45		Orig.-Verschr., nur M+S, Plug-in-Hybrid
	B43	27	-	120, 135	235/45, 245/45		Orig.-Verschr., Plug-in-Hybrid
		30	-	120, 135	235/45, 245/45		Orig.-Verschr., Plug-in-Hybrid
8,5 x 20	B42 / B43	30+35	-	120, 135	235/45, 245/45, 255/40		Orig.-Verschr., Plug-in-Hybrid
	AC-M10	30	-	120, 135	235/45, 245/45, 255/40		Orig.-Verschr., Plug-in-Hybrid
9 x 20	RC36	35	-	120, 135	VA 235/45+HA 255/40		Orig.-Verschr., Plug-in-Hybrid
	B40 / B43	35	-	120, 135	VA 235/45+HA 255/40		Orig.-Verschr., Plug-in-Hybrid
	CA 20	35	ZP599F	120, 135	235/45, 245/45, 255/40HA		Plug-in-Hybrid
	Oxigin 28	35	ZP599F	120, 135	235/45, 245/45, 255/40HA		Plug-in-Hybrid
8,5 x 21	B43	VA 30	-	120, 135	VA 245/40+HA 275/35		Orig.-Verschr., Plug-in-Hybrid
9,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	120, 135	VA 245/40, 255/40		Orig.-Verschr., HA bei 285/35 ✖
9,5 x 21		HA 43			HA 275/35, 285/35		
8,5 x 21	B43	30+34	-	120, 135	245/40, 255/40		Orig.-Verschr., Plug-in-Hybrid

Kombinationen

8 x 20	B40	27+30	-	120, 135	VA 235/45, 245/45		Orig.-Verschr., Plug-in-Hybrid
9 x 20		40+44			HA 265/40, 275/40		
8 x 20	B43	30	-	120, 135	VA 235/45, 245/45		Orig.-Verschr.
9 x 20		44			HA 265/40, 275/40		
8,5 x 20	B32 / B42	30	-	120, 135	VA 235/45, 245/45, 255/40		Orig.-Verschr., Plug-in-Hybrid, HA bei 285/35 ✖
9,5 x 20		42			HA 255/40, 265/40, 275/40, 285/35		

BMW X3 M40d, X3 M40i	NEU	2021	G3X	5/112	66,7	e1*2007/46*1797..
----------------------	-----	------	-----	-------	------	-------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 19	RC32	32	-	240-265	245/50	Orig.-Verschr., nur M+S
	RC34	32	-	240-265	245/50	Orig.-Verschr., auch Hybrid
8 x 19	RC27	30	-	240-265	255/45	Orig.-Verschr.
	CA 19 / CA 24	30	ZP599F	240-265	255/45	incl. Hybrid
8,5 x 19	Oxigin 25	35	ZP593F	240-265	245/50, 255/45, 265/45	
9 x 19	CA 24	35	ZP599F	240-265	255/45	incl. Hybrid
8 x 20	B40	VA 27	-	265	VA 245/45	Orig.-Verschr.
9,5 x 20		HA 43		265	HA 275/40	
8,5 x 20	RC34	30	-	240-265	245/40, 245/45	Orig.-Verschr., nur M+S
		33	-	240-265	245/40, 245/45, 255/40	Orig.-Verschr., nur M+S
	B41	35	-	240-265	245/40, 245/45, 255/40	Orig.-Verschr., nur M+S
	CA 19	32	ZP599F	240-265	255/40, 255/45	
9 x 20	B41	33+35	-	240-265	245/40, 245/45	Orig.-Verschr., nur M+S
	AC-518	33	F93	240-265	245/45	incl. Hybrid
	AC-522	33	F93	240-265	245/45	incl. Hybrid
	FMI07 Atena	33	F93	240-265	245/40, 245/45	nur M+S
	Oxigin 25	35	ZP593F	240-265	245/45, 255/40, 255/45	
	Oxigin 26	35	ZP599F	240-265	245/45, 255/40, 255/45	
8,5 x 21	B41	VA 30	-	240-265	VA 245/40+HA 275/35	Orig.-Verschr.
9,5 x 21		HA 43				
8,5 x 21	B41	VA 30	-	240-265	VA+HA 245/35, 245/40, 255/35 od.	Orig.-Verschr.
9,5 x 21		HA 43			VA 245/40+HA 275/35	
8,5 x 21	B41	34	-	240-265	245/35, 245/40, 255/35	Orig.-Verschr.
9 x 21	CA 17	30	ZP599F	240-265	245/40	incl. Hybrid
	FMI07 Atena	33	F93	240-265	245/35, 245/40, 255/35	

BMW X3	NEU	2024	G3XN (G45)	5/112	66,7	e1*2018/858*00409*..
--------	-----	------	------------	-------	------	----------------------

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	RC27	15	-	120-145	225/60, 235/55, 235/60	Orig.-Verschr.
8,5 x 19	RC34	26	-	120-280	245/50	Orig.-Verschr., nur Bremse 348x30mm VA und 345x24mm HA
	B43	26	-	120-145	245/50	Orig.-Verschr.
		25	-		245/50	Orig.-Verschr.
9 x 20	B41	VA 24	-	120-280	VA 255/45	Orig.-Verschr., nur Bremse 348x30mm VA und 345x24mm HA
10,5 x 20		HA 44			HA 285/40	
9 x 21	B43	VA 24	-	120-145	VA 255/40	Orig.-Verschr.
10,5 x 21		HA 44			HA 285/35	

Kombinationen

9 x 20	B41	VA 24	-	120-280	VA 255/40+HA 285/35 od. VA 255/45+HA 285/40 od. VA 265/40+HA 295/35		Orig.-Verschr., nur Bremse 348x30mm VA u. 345x24mm HA
10,5 x 20		HA 44					
9,5 x 21	B41	VA 22	-	120-280	VA 255/40+HA 285/35		Orig.-Verschr.
10,5 x 21		HA 43					
9 x 21	B43	VA 24	-	120-145	VA 245/40, 255/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 275/35, 285/35		

BMW X3 e30 xDrive NEU		2024		G3XN (G45)	5/112	66,7	e1*2018/858*00409*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	26	-	140	245/50			Orig.-Verschr.

Kombinationen

9 x 21	B43	VA 24	-	140	VA 255/40		Orig.-Verschr.
10,5 x 21		HA 44			HA 285/35		

BMW X3 M50 xDrive NEU		2024		G3XN (G45)	5/112	66,7	e1*2018/858*00409*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	26	-	280	245/50			Orig.-Verschr., nur M+S

Kombinationen

9 x 21	B43	VA 24	-	280	VA 255/40		Orig.-Verschr.
10,5 x 21		HA 44			HA 285/35		

BMW X3 M / X4 M Competition NEU			F34XM	5/112	66,7	e1*2007/46*1988*..	
Sensor - Brocksens 1							

Kombinationen

8,5 x 20	Fascinate	VA 30	14x1,25x30	353-375	VA 255/45			
10 x 20		HA 35			HA 265/45, 285/40			
8,5 x 20	Race LS 2	VA 30	14x1,25x30	353-375	VA 255/45			
10 x 20		HA 35			HA 265/45, 285/40			
9 x 20	RC36	VA 28	-	353, 375	VA 255/45			Orig.-Verschr.
10 x 20		HA 39			HA 265/45			
9 x 20	B43	VA 28	-	353, 375	VA 255/45			Orig.-Verschr.
10 x 20		HA 39			HA 265/45			
9 x 20	B37	VA 29	ZP599F	353-375	VA 255/45, 265/45			
9,5 x 20		HA 38			HA 255/45, 285/40			
9 x 22	AC-M08	VA 26	F93	353-375	VA 255/35, 265/35			HA ✖
10 x 22		HA 19			HA 295/30			
10 x 22	CA 17	VA+HA 30	ZP593F	353-375	VA 255/35, 265/35			
					HA 295/30			HA ✖

BMW iX ^{NEU}	2021	BMW i-N	5/112	66,7	e1*2018/858*00109*..
Sensor - Brocksens 1					

8,5 x 20	B41	28	-	102	235/60			Orig.-Verschr.
				102-140	235/55, 235/60			
		35		102-140	235/55, 255/50, 255/55, 265/50			Orig.-Verschr.
9 x 20	B43	35	-	102	235/60, 255/55, 265/50			Orig.-Verschr.
	B40	35	-	102	235/60, 255/55			Orig.-Verschr.
	B41	33+35	-	102-140	255/50, 255/55			Orig.-Verschr.
	B43	35	-	102	235/60, 255/55			Orig.-Verschr.
	AC-522	33	-	102-140	255/55			Orig.-Verschr.
8,5 x 21	CA 20	35	-	102	235/60, 255/55			Orig.-Verschr.
		30	-	102-140	265/45, 275/45			Orig.-Verschr.
	B41	34	-	102	255/50, 265/45, 275/45			Orig.-Verschr.
		30	-	102	265/45, 275/45			Orig.-Verschr.
		34	-	102	255/50, 265/45, 275/45			Orig.-Verschr.
9 x 21	B43	36	-	102, 140	255/50			Orig.-Verschr.
				102	255/50, 265/45, 275/45			
	FMI10 e-Joule	36	-	102	255/50			Orig.-Verschr.
	CA 17	30	ZP599F	102-140	255/50, 265/45, 275/45			bei 255/50 ✖
	CA 20	30	-	102	265/45			Orig.-Verschr.
		37	-	102	255/50, 265/45, 275/45			Orig.-Verschr.
9,5 x 21	FMI07 Atena	33	F93	102	255/50, 265/45, 275/45			
	B41	31	-	102-140	265/45			Orig.-Verschr.
		36	-	102-140	265/45, 275/45			Orig.-Verschr.
	B43	36	-	102	255/50, 265/45, 275/45			Orig.-Verschr.
9,5 x 22	FMI12 Kari	31	F93	102	265/45			
9,5 x 22	B41	37	-	102	255/45, 265/40, 275/40			Orig.-Verschr.

BMW iX3	NEU	ab März 2021	G3XE / G08	5/112	66,7	e1*2007/46*2130*..
Sensor - Brocksens 1						

8 x 19	RC34	34	-	80	245/50			Orig.-Verschr.
	B43	34	-	80	245/50, 255/45			Orig.-Verschr.
	FMI10 e-Joule	34	-	80	245/50			Orig.-Verschr.
	RC32	30	-	80	255/45			Orig.-Verschr.
	B43	28	-	80 (210)	255/45			Orig.-Verschr.

8,5 x 19	CA 24	30	ZP599F	80	255/45		
	Oxigin 29	32	ZP599F	80 (210)	245/50, 255/45		
	B41	36	-	80	255/45, 265/45		Orig.-Verschr.
	AC-M10	30	-	80 (210)	255/45		Orig.-Verschr.
	Oxigin 28	30	ZP599F	80 (210)	255/45		
9 x 19	CA 24	35	ZP599F	80	255/45		
8 x 20	RC36	VA 26	-	80 (210)	VA 245/45		Orig.-Verschr.
9,5 x 20		HA 43			HA 275/40		
8 x 20	RC36	27	-	80 (210)	245/45		Orig.-Verschr.
	B40	27	-	80 (210)	245/45		Orig.-Verschr.
	B43	27+30	-	80 (210)	245/45		Orig.-Verschr.
8,5 x 20	B41	35	-	80	255/40		Orig.-Verschr.
	B43	30+35	-	80 (210)	245/45, 255/40		Orig.-Verschr.
	AC-M10	30	-	80 (210)	245/45, 255/40		Orig.-Verschr.
	CA 19	32	ZP599F	80	255/40, 255/45		
9 x 20	RC36	35	-	80 (210)	245/45		Orig.-Verschr.
	B40	35	-	80 (210)	245/45		Orig.-Verschr.
	B41	33	-	80	245/45		Orig.-Verschr.
		35	-	80	255/40		Orig.-Verschr.
	B43	35	-	80 (210)	VA 245/45+HA 275/40		Orig.-Verschr., HA ✖
	AC-522	33	F93	80	245/45		Reifen nur zulässig bis Achslast 1750kg
	BR-I	35	14x1,25x30	80	VA+HA 255/40 od. VA 235/45+HA 265/40		
	CA 20	35	ZP599F	80 (210)	VA 245/45+HA 275/40		HA ✖
	Oxigin 28	35	ZP599F	80 (210)	VA 245/45+HA 275/40		HA ✖
8,5 x 21	B43	30+34	-	80 (210)	255/40		Orig.-Verschr.
9 x 21	CA 17	35	ZP599F	80	255/40		

Kombinationen

8,5 x 19	B41	VA 29	-	80	VA 245/50+HA 275/45		Orig.-Verschr.
9 x 19		HA 41					
8 x 19	B40	VA 30	-	80 (210)	VA+HA 265/45		Orig.-Verschr.
9 x 19		HA 44					
8 x 20	B40	VA 27+30	-	80 (210)	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 20		HA 40+44					
8 x 20	B43	VA 30	-	80 (210)	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 20		HA 44					
8,5 x 20	B43	VA 35	-	80 (210)	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 20		HA 42					
8,5 x 20	Race LS 2	VA 30	14x1,25x30	80	VA+HA 255/40 od. VA 235/45+HA 265/40		
10 x 20		HA 38					
8,5 x 20		VA 35	14x1,25x30	80	VA+HA 255/40 od. VA 235/45+HA 265/40		
10 x 20		HA 38					
8,5 x 21	B41	VA 30	-	80	VA 245/40+HA 275/35		Orig.-Verschr.
10,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	80 (210)	VA 245/40, 255/40		Orig.-Verschr., HA bei 285/35 ✖
10,5 x 21		HA 44			HA 275/35, 285/35		
9 x 21	Race LS 3	VA 30		80	VA 245/40		
10,5 x 21		HA 44			HA 275/35		
9 x 22	Race LS 3	VA 30		80	VA 245/35		
10 x 22		HA 30			HA 285/30		

BMW X4 (siehe Konfigurator)	ab 2014	X3, X-N1	5/120	72,6	e1*2007/46*0512*11-..., 0454*13-...
-----------------------------	---------	----------	-------	------	-------------------------------------

BMW X4	2018	G4X/G02	5/112	66,7	e1*2007/46*1881*...
--------	------	---------	-------	------	---------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 18	RC27	22	-	120-195	225/60	Orig.-Verschr.
				120-185	225/60, 235/55, 235/60	
	RC32	22	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	RC34	22	-	120-210	225/60	Orig.-Verschr.
7,5 x 18	BR-I	22	-	120-195	225/60	Orig.-Verschr.
	RC32	23+25	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	RC34	25	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	B32	25	-	120-195	225/60, 235/55, 255/50, 255/55	Orig.-Verschr.
8 x 18	RC32	20	-	120-195	225/55, 225/60, 235/55	Orig.-Verschr.
		30	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	RC34	30	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	B42	30+35	-	120-210	225/60, 235/55	Orig.-Verschr.
	B44	30+35	-	120-210	225/60, 235/55	Orig.-Verschr.
	AC-M10	30	-	120-210	225/60, 235/55	Orig.-Verschr.
	CA 26	30	ZP599F	120-210	225/60, 235/55	
	EMI08 Thoe	26	-	120-210	225/55, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.

	FMI00 Thoe	34	-	120-210	245/55, 255/50		Orig.-Verschr.	
	FMI11 Elatha	26	F93	120-210	225/55, 225/60, 235/55, 245/55, 255/50			
	FMI12 Kari	26	Kit 0334	120-210	225/55, 225/60, 235/55, 245/55, 255/50			
7,5 x 19	RC32	32	-	120-195	245/50		Orig.-Verschr.	
	RC34	32	-	120-210	245/50		Orig.-Verschr., auch Hybrid	
	B32	32	-	120-210 120-265	225/55, 235/50, 245/50 245/50M+S		Orig.-Verschr.	
	BR-I	32	-	120-195 120-265	225/55, 235/50, 245/50 245/50M+S		Orig.-Verschr., nicht Bremse 348x36mm	
	CA 26	32	ZP599F	120-210 120-265	245/50 245/50M+S		Orig.-Verschr.	
8 x 19	RC27	30	-	120-195	245/50, 255/45		Orig.-Verschr.	
	RC32	30	-	120-210	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.	
	RC34	27	-	120-195	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.	
	B40	30	-	120-195 120-265	225/55, 235/50, 245/50, 255/45 245/50, 255/45		Orig.-Verschr. Orig.-Verschr., nur M+S	
	B43	28	-	120-210 120-265	225/55, 235/50, 245/50, 255/45 245/50, 255/45		Orig.-Verschr. Orig.-Verschr., nur M+S	
	CA 19 / CA 24	30	ZP599F	120-210	245/50, 255/45		incl. Hybrid	
	FMI08 Thoe	26	-	120-210	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.	
	Oxigin 29	32	ZP599F	120-210 120-265	225/55, 235/50, 245/50, 255/45 245/50, 255/45		nur M+S	
8,5 x 19	RC32	29	-	120-210	235/50, 245/50, 255/45, 265/45, 275/45		Orig.-Verschr.	
	RC34	26+29	-	120-210	235/50, 245/50, 255/45, 265/45, 275/45		Orig.-Verschr.	
	B32	25	-	120-195 120-260	235/50, 255/45 255/45M+S		Orig.-Verschr.	
	B41	28+29	-	120-210	235/50, 245/50, 255/45, 265/45, 275/45		Orig.-Verschr.	
	B42	30	-	120-210 120-265	235/50, 255/45, 265/45 255/45M+S, 265/45M+S		Orig.-Verschr.	
	B43	25	-	120-210 120-265	235/50, 255/45 255/45M+S		Orig.-Verschr.	
		29	-	120-210 120-265	235/50, 245/50, 255/45, 265/45, 275/45HA 245/50, 255/45, 265/45, 275/45HA		Orig.-Verschr. Orig.-Verschr., nur M+S	
	B44	25	-	120-210 120-265	235/50, 255/45 255/45M+S		Orig.-Verschr.	
		30	-	120-210 120-265	235/50, 245/50, 255/45 245/50M+S, 255/45M+S		Orig.-Verschr.	
	AC-M10	30	-	120-210 120-265	235/50, 245/50, 255/45, 265/45, 275/45HA 245/50, 255/45, 265/45, 275/45HA		Orig.-Verschr. Orig.-Verschr., nur M+S	
	CA 23	30	ZP599F	120-210 120-265	235/50, 245/50, 255/45, 265/45, 275/45HA 245/50, 255/45, 265/45, 275/45HA		nur M+S	
	Oxigin 14	35	ZP599F+R	120-185 120-195	235/50 255/45		+ Red. Ringe BA12= 72,6-66,6, nicht Bremse 348mm	
	Oxigin 19 / 25	35	ZP593F	120-185 120-195	235/50 255/45		Oxigin 19 nicht Bremse 348mm	
	Oxigin 28	30	ZP599F	120-210 120-265	235/50, 245/50, 255/45, 265/45, 275/45HA 245/50, 255/45, 265/45, 275/45HA		nur M+S	
	FMI07 Atena	28	F93	120-195	235/50, 245/50, 255/45, 265/45, 275/45			
	FMI11 Elatha	21	F93	120-210	235/50, 255/45			
	8300 - 1972	32	-	120-210	245/50, 255/45, 265/45, 275/45		Orig.-Verschr.	
	8 x 20	RC36	VA 27	-	120-265	VA 245/45		Orig.-Verschr.
	9,5 x 20		HA 43			HA 275/40		
	8 x 20	B40	VA 27	-	120-265	VA 245/45		Orig.-Verschr.
9,5 x 20				120-195	VA 235/45			
	HA 43			120-265	HA 275/40			
				120-195	HA 245/45, 255/40, 265/40			
8 x 20	BR-I	VA 27	-	120-265	VA 245/45		Orig.-Verschr.	
9,5 x 20		HA 43			HA 275/40			
8 x 20	RC36	27	-	120-265 120-210	245/45M+S 235/45, 245/45		Orig.-Verschr.	
	B40	27	-	120-265 120-195	245/45M+S 235/45, 245/45		Orig.-Verschr.	
	B43	27	-	120-265 120-210	245/45M+S 235/45, 245/45		Orig.-Verschr.	
		30	-	120-265 120-210	245/45M+S 235/45, 245/45		Orig.-Verschr.	
8,5 x 20	RC29	26	-	120-210 120-265	235/45, 245/45, 255/40 245/45M+S, 255/40M+S		Orig.-Verschr.	
	RC34	30	-	120-195	235/45, 245/40, 245/45, 255/40		Orig.-Verschr.	
		33	-	120-195	245/40, 245/45, 255/40		Orig.-Verschr.	
	B32	30	-	120-195 120-260	235/45, 245/45, 255/40 245/45M+S, 255/40M+S		Orig.-Verschr.	
	B41	20	-	120-210	235/45, 245/40, 245/45, 255/40		Orig.-Verschr., auch Hybrid	
		35	-	120-210	245/40, 245/45, 255/40		Orig.-Verschr., auch Hybrid	

8,5 x 20	B42 / B43	30+35	-	120-210	235/45, 245/45, 255/40		Orig.-Verschr.
				120-265	245/45M+S, 255/40M+S		
	B44	25+30+35	-	120-210	235/45, 245/45, 255/40		Orig.-Verschr.
				120-265	245/45M+S, 255/40M+S		
	AC-M10	30	-	120-210	235/45, 245/45, 255/40		Orig.-Verschr.
				120-265	245/45M+S, 255/40M+S		
9 x 20	CA 17	23	ZP593F	120-195	235/45		
	CA 19	32	ZP599F	120-210	255/40, 255/45		
	RC36	35	-	120-210	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		Orig.-Verschr.
				120-265	245/45, 275/40HA		Orig.-Verschr., nur M+S
	B40	34	ZP599F	120-260	245/45		
		35	-	120-195	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		Orig.-Verschr.
				120-260	245/45, 275/40HA		Orig.-Verschr., nur M+S
	B41	33+35	-	120-195	245/40, 245/45, 255/40, 265/40		Orig.-Verschr.
	B43	35	-	120-210	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		Orig.-Verschr.
				120-265	245/45, 275/40HA		Orig.-Verschr., nur M+S
	BR-IT	35	-	120-195	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		Orig.-Verschr.
				120-265	245/45, 275/40HA		Orig.-Verschr., nur M+S
	AC-518	33	F93	120-210	235/45, 245/45, 255/40, 255/45		auch für Hybrid
		25	F93	120-210	235/45		incl. Hybrid
	AC-522	33	F93	120-210	235/45, 245/45, 255/40, 255/45		incl. Hybrid, Reifen 235/45 nur zulässig bis Achslast 1600KG
	CA 20	35	ZP599F	120-210	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		
				120-265	245/45, 275/40HA		nur M+S
	FMI07 Atena	33	F93	120-195	245/40, 245/45, 255/40, 265/40		
	FMI11 Elatha	34	F93	120-210	245/40, 245/45, 255/40, 265/40		
	Oxigin 25	35	ZP593F	120-185	245/45		
	Oxigin 28	35	ZP599F	120-210	235/45, 245/45, 255/40HA, 265/40HA, 275/40HA		
				120-265	245/45, 275/40HA		nur M+S
8,5 x 21	B41	VA 30	-	120-210	VA 245/35, VA 245/40+HA 275/35 , 285/30		Orig.-Verschr.
9,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	120-265	VA 245/40+HA 275/35		Orig.-Verschr.
9,5 x 21		HA 43					
8,5 x 21	B43	VA 30	-	120-265	VA 245/40, 255/40		Orig.-Verschr.
9,5 x 21		HA 43			HA 275/35, 285/35		
8,5 x 21	B41	30	-	120-210	245/35, 245/40, 255/35		Orig.-Verschr.
		34	-	120-210	245/35, 245/40, 255/35		Orig.-Verschr.
	B43	30+34	-	120-210	245/40, 255/35, 255/40		Orig.-Verschr.
				120-265	245/40, 255/35		Orig.-Verschr., nur M+S
9,5 x 21	B41	22	-	120-195	245/35, 245/40		Orig.-Verschr.
		31	-	120-210	245/35, 245/40, 255/35, 265/35		Orig.-Verschr.
10 x 22	FMI09 CRATOS	31	-	120-210	265/30		Orig.-Verschr.

Kombinationen

8 x 19	B40	27	-	120-195	VA 235/50, 245/50, 255/45		Orig.-Verschr.
9 x 19		40			HA 245/50, 255/45, 275/45		
8 x 19		30	-	120-195	VA 235/50, 245/50, 255/45		Orig.-Verschr.
9 x 19		44			HA 245/50, 255/45, 275/45		
8,5 x 19	B41	35	-	120-210	VA+HA 275/45		Orig.-Verschr.
9 x 19		42					
8 x 20	B43	30	-	120-210	VA 235/45, 245/45		Orig.-Verschr.
9 x 20		41			HA 255/40, 265/40, 275/40		
8 x 20	FMI08 Thoe	26	-	120-210	VA 245/45+HA 275/40		Orig.-Verschr.
9 x 20		41					
8,5 x 20	B43	35	-	120-210	VA 235/45, 255/40		Orig.-Verschr.
9 x 20				42	120-265		
		120-210			HA 255/40, 265/40		
		120-265			HA 275/40		
9 x 20	B41	35	-	120-195	VA245/45+HA275/40		Orig.-Verschr.
10,5x20		40					
8,5 x 20	Fascinate	30	14x1,25x30	135-265	VA245/45+HA275/40, VA245/40+HA275/35		Sternschraube!!!!
10 x 20		35					
8,5 x 20	Hibonit	24	14x1,25x30	135-265	VA245/45+HA275/40, VA245/40+HA275/35, VA245/40+HA285/35, VA255/40+HA285/35		
10 x 20		38					
8,5 x 20	LS 2	30	14x1,25x30	135-265	VA245/45+HA275/40, VA245/40+HA275/35, VA245/40+HA285/35, VA255/40+HA285/35		
10 x 20		38					
9 x 21	Fascinate	30	14x1,25x30	135-265	VA245/40+HA275/35, VA245/40,+HA285/35		Sternschraube!!!!
10,5 x 21		44					
9 x 21	LS 2	30	14x1,25x30	135-265	VA245/40+HA275/35, VA245/40,+HA285/35		
10,5 x 21		44					
9 x 21	GTS	30	14x1,25x30	135-265	VA245/40+HA275/35, VA245/40,+HA285/35		
10 x 21		38					

BMW X4 M40d, X4 M40i	2018	G4X	5/112	66,7	e1*2007/46*1881*..
----------------------	------	-----	-------	------	--------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 19	RC32	32	-	240-265	245/50	 Orig.-Verschr.
	RC34	32	-	240-265	245/50	 Orig.-Verschr., auch Hybrid
8 x 19	RC27 / RC32	30	-	240-265	245/50, 255/45	Orig.-Verschr., nur M+S
	RC34	27	-	240-265	245/50, 255/45	Orig.-Verschr., nur M+S
	CA 19 / CA 24	30	ZP599F	240-265	245/50, 255/45	incl. Hybrid
	FMI08 Thoe	26	-	240-265	245/50, 255/45	Orig.-Verschr., nur M+S
8,5 x 19	RC32	29	-	240-265	245/50, 255/45, 265/45, 275/45	Orig.-Verschr., nur M+S, auch für Hybrid
	RC34	26+29	-	240-265	245/50, 255/45, 265/45, 275/45	Orig.-Verschr., nur M+S, auch für Hybrid
	B41	28+29	-	240-265	245/50, 255/45, 265/45, 275/45	Orig.-Verschr., nur M+S, auch für Hybrid
	FMI07 Atena	28	F93	240-265	245/50, 255/45, 265/45, 275/45	nur M+S
	FMI11 Elatha	21	F93	240-265	255/45	nur M+S
	8300 - 1972	32	-	240-265	245/50, 255/45, 265/45, 275/45	Orig.-Verschr., nur M+S
	Oxigin 25	35	ZP593F	240-265	235/50, 255/45	
8,5 x 20	Oxigin 26	30	ZP599F	240-265	235/50, 255/45	incl. Hybrid
	RC34	30+33	-	240-265	245/40, 245/45, 255/40	Orig.-Verschr., nur M+S
	B41	20+35	-	240-265	245/40, 245/45, 255/40	Orig.-Verschr., nur M+S
	CA 17	23	ZP593F	240-265	235/45	
9 x 20	CA 19	32	ZP599F	240-265	255/40, 255/45	
	B41	33+35	-	240-265	245/40, 245/45, 255/40, 265/40	Orig.-Verschr., nur M+S
	AC-518	33	F93	240-265	235/45, 245/45, 255/40, 265/40	incl. Hybrid
	AC-522	25	F93	240-265	235/45	incl. Hybrid
		33	F93	240-265	235/45, 245/45, 255/40, 255/45	incl. Hybrid
	FMI07 Atena	33	F93	240-265	245/40, 245/45, 255/40, 265/40	nur M+S
	FMI11 Elatha	20	F93	240-265	245/40, 245/45	nur M+S
		34	F93	240-265	245/40, 245/45, 255/40, 265/40	nur M+S
	Oxigin 18	28	ZP599F	240-265	235/45, 245/45	
8,5 x 21	B41	VA 30	-	240-265	VA 245/40 + HA 275/35	 Orig.-Verschr.
9,5 x 21		HA 43				
9,5 x 21	B41	31	-	240-265	VA 245/40+HA 275/35	Orig.-Verschr.

Kombinationen

8,5 x 19	B41	35	-	240-265	VA+HA 275/45		Orig.-Verschr., nur M+S
9 x 19		42					
8 x 20	FMI08 Thoe	26	-	240-265	VA 245/45+HA 275/40		Orig.-Verschr., nur M+S
9 x 20		41					
9 x 20	B41	35	-	240-265	VA245/45+HA275/40		Orig.-Verschr.
10,5x20		40					

BMW X5 (siehe Konfigurator)	ab 2014	F15 /X5, XN1	5/120	74,1	e1*2007/46*0421*10-..., e1*2007/46*0454*11-...
-----------------------------	---------	--------------	-------	------	--

BMW X5 M (siehe Konfigurator)	ab 2015	M7X	5/120	74,1	
-------------------------------	---------	-----	-------	------	--

BMW X5	2018	G5X (G05)	5/112	66,7	e1*2007/46*1918*00-14
--------	------	-----------	-------	------	-----------------------

Sensor - Brocksens 1

ACHTUNG! Achslasten beachten!

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 18	B32	44	-	155-250	255/55, 255/60	 Orig.-Verschr., nur Bremse 348mm, incl. M-Paket
	RC34	36	-	155-250	255/55, 255/60, 265/55, 275/50, 285/50	Orig.-Verschr., nicht Bremse 374x36mm
	B32	36	-	155-250	255/55, 255/60	Orig.-Verschr., incl. M-Paket
9 x 18	RC32	32	-	155-250	255/55, 255/60, 265/55	Orig.-Verschr.
	RC32	29	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45	Orig.-Verschr.
8,5 x 19	RC34	26	-	155-250	255/50, 255/55, 265/45, 275/45	Orig.-Verschr.
		29	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45	Orig.-Verschr.
		28+29	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45	Orig.-Verschr., nicht Bremse 395mm
	B41	36+39	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45, 275/50	Orig.-Verschr.
		40	-	155-250	255/50, 255/55, 265/50, 275/45, 275/50	Orig.-Verschr., nicht Bremse 395mm
	B43	45	-	155-250	255/50, 255/55, 275/45	Orig.-Verschr., nicht Bremse 374 u. 395mm
	AC-M10	45	-	155-250	255/50, 255/55, 275/45	Orig.-Verschr., nicht Bremse 348, 374 u. 395mm
	CA 20	45	-	155-250	255/50, 255/55, 275/45	Orig.-Verschr., nicht Bremse 348, 374 u. 395mm
		30	-	155-250	255/50, 255/55, 275/45	nicht Bremse 395mm, incl. M-Paket
	CA 23	45	-	155-250	255/50, 255/55, 275/45	nicht Bremse ab 348mm, incl. M-Paket
		40	F93	155-250	255/50, 255/55, 265/45, 265/50, 275/45, 275/50	nicht Bremse 395mm
	FMI07 Atena	45	F93	155-250	255/50, 255/55, 265/45, 265/50, 275/45	nicht Bremse 374 u. 395mm
		30	-	155-250	255/50, 255/55, 275/45	incl. M-Paket
	Oxigin 28	40	-	155-250	255/50, 255/55, 265/50, 275/45, 275/50	nicht Bremse ab 348mm, incl. M-Paket
		45	-	155-250	255/50, 255/55, 275/45	nicht Bremse ab 348mm, incl. M-Paket
9 x 19	B41	38	-	155-280	255/50, 255/55, 265/45, 265/50, 275/45, 275/50, 285/45	 Orig.-Verschr.
	CA 24	35	ZP599F	155-250	275/45	nicht Bremse 395mm
	RC29	26	-	155-250	265/45	Orig.-Verschr., incl. M-Paket
	RC34	30+33+38	-	155-250	255/45, 265/45	Orig.-Verschr., nur bis 1.600 kg Achslast

8,5 x 20	B41	20	-	155-250	255/45, 265/45		Orig.-Verschr.
		35	-	155-250	255/45, 265/45, 275/45		Orig.-Verschr.
	B43	30+35+ 40	-	155-250	265/45, 275/45		Orig.-Verschr., incl. M-Paket
	AC-M10	30	-	155-250	265/45, 275/45		Orig.-Verschr., incl. M-Paket
	CA 19	45	ZP599F	155-250	255/50		nicht Brembo-Bremse
	FMI07 Atena	39	F93	155-250	255/45, 265/45, 275/45		Radlast 1050kg
9 x 20	B40	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr., incl. M-Paket
	B41	35	-	155-250	275/45		Orig.-Verschr.
				155-280	255/45, 265/40, 265/45, 275/40, 275/45		Orig.-Verschr.
	B43	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr., incl. M-Paket
	BR-IT	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr., nicht Bremse 374mm
	B40	34	ZP599F	183-250	255/50, 275/45, 285/45		
	B41	33	-	155-280	255/45, 265/40, 265/45, 275/40, 275/45		Orig.-Verschr.
		38	-	155-250	255/45, 265/40, 265/45, 275/40, 275/45		Orig.-Verschr.
	B43	42	-	155-250	265/45, 275/40, 275/45, 285/45		Orig.-Verschr., incl. M-Paket
		44	-	155-250	265/45, 275/40, 275/45		Orig.-Verschr., incl. M-Paket
	AC-522	33	F93	155-390	275/45		nur M+S
		40	F93	155-390	255/50, 275/45		incl. Hybrid
	CA 20	35	-	155-250	265/45, 275/40, 275/45, 285/45		Orig.-Verschr., incl. M-Paket
		45	-	155-250	265/45, 275/40, 275/45		Orig.-Verschr., incl. M-Paket, nicht Bremse 348, 374 u. 395mm
	CA 23	45	-	155-250	265/45, 275/40, 275/45		Orig.-Verschr., incl. M-Paket, nicht Bremse 395mm
	FMI07 Atena	33	F93	155-250	255/45, 265/40, 265/45, 275/40, 275/45		
	FMI11 Elatha	34	F93	155-250	255/45, 265/40, 265/45, 275/40, 275/45		
9,5 x 20	CA 17	36	ZP599F	155-390	265/45		
	CA 19	43	ZP599F	155-390	265/45		
10 x 20	Race LS 2	38	14x1,25x30	155-250	275/40, 275/45		
9 x 20	B41	VA 35	-	155-250	VA 275/45+HA 305/40		Orig.-Verschr.
10,5 x 20		HA 40					
8,5 x 21	B41	30+34+ 37+ 40+43	-	155-250	255/40, 255/45		Orig.-Verschr.
9 x 21	B43	36	-	155-250	265/40, 275/40		Orig.-Verschr., incl. M-Paket
	CA 20	37	-	155-250	265/40, 275/40		Orig.-Verschr., incl. M-Paket
		45	-	155-250	265/40, 275/40		Orig.-Verschr., incl. M-Paket, ET45 nicht Bremse 348x36mm, 374 u. 395mm
	FMI07 Atena	40	F93	155-250	255/40, 255/45, 265/35, 265/40, 275/35, 275/40		nicht 4-Kolben Festsattel mit 348x36mm
9,5 x 21	B41	31+36	-	155-280	255/40, 255/45, 265/35, 265/40, 275/35, 275/40, 285/35, 285/40		Orig.-Verschr.
		43	-	155-250	255/40, 255/45, 265/35, 265/40, 275/35, 275/40		Orig.-Verschr.
	B43	36	-	155-250	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., incl. M-Paket, ab 285/35 ✖
	BR-IT	36	-	155-250	265/40, 275/40		Orig.-Verschr., incl. M-Paket
	FMI10 e-Joule	41,5	F93	155-250	255/40, 255/45, 265/35, 265/40, 275/35, 275/40		
9,5 x 21	B41	VA 37	-	155-250	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155-250	VA 275/40+HA 315/35		Orig.-Verschr., incl. M-Paket
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155-250	VA 265/40, 275/40, 285/35, 285/40		Orig.-Verschr., incl. M-Paket
10,5 x 21		HA 43			HA 265/40, 275/40, 285/35, 285/40, 295/35, 305/35, 315/35		
9,5 x 22	B41	VA 37	-	155-250	VA 275/35+HA 315/30		Orig.-Verschr.
10,5 x 22		HA 43					
9,5 x 22	B41	VA 37	-	155-250	VA+HA 265/35, 275/35, 285/30, 285/35		Orig.-Verschr.
10,5 x 22		HA 43					
9,5 x 22	B41	45	-	155-250	265/35, 275/35		Orig.-Verschr.
10 x 22	CA 20	38	-	155-250	265/35, 275/35, 295/30HA		Orig.-Verschr., incl. M-Paket
	FMI07 Atena	31	F93	155-250	265/35, 275/35		
	FMI09 CRATOS	31	-	155-250	265/35, 275/35		Orig.-Verschr.
	Race LS 2	35	14x1,25x30	155-250	275/35, 285/35		
10 x 23	Race LS 3	30	14x1,25x30	155-250	295/30		i.V.

Kombinationen

8,5 x 19	RC34	35	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45, 275/50		Orig.-Verschr.
9 x 19		42					
8,5 x 19	B41	32	-	155-250	255/50, 255/55, 265/45, 265/50, 275/45, 275/50		Orig.-Verschr.
9 x 19		42					
9 x 20	B43	28	-	155-250	VA 265/45		Orig.-Verschr., incl. M-Paket
10 x 20		39			HA 295/40		
10 x 20	Race LS 2	38	14x1,25x30	155-250	VA 275/45+HA 305/40 oder VA 275/40+HA 305/35		
9 x 21	Race LS 2	30+41	14x1,25x30	155-250	VA 265/35+HA 305/30 oder VA 275/35+HA 315/30		
10,5 x 21		44					

9,5 x 21	B41	37	-	155-280	VA+HA 265/35, 265/40, 275/35, 275/40, 285/35, 285/40 od.		Orig.-Verschr.
10,5 x 21		43			VA 275/35+HA 315/30, VA 275/40+HA 315/35		
9 x 22	Race LS 2	30	14x1,25x30	155-250	VA+HA 275/35		
10 x 22		35					
9,5 x 22	AF18	37	F93	155-390	VA 275/35+HA 295/35 od. VA 275/35+HA 315/30		
10,5 x 22		43					
9 x 22	Race LS 2	30	14x1,25x30	155-250	VA 275/35+HA 315/30		
11,5 x 22		43					
10 x 23	Race LS 3	30	14x1,25x30	155-250	VA+HA 295/30		i.V.
11 x 23		30					

BMW X5	NEU	ab Facelift 2023	G5X (G05)	5/112	66,7	e1*2007/46*1918*15-..
Sensor - Brocksens 1						

ACHTUNG! Achslasten beachten!

Dimension	Design	ET	KIT	KW	Reifendimension		Info
9 x 20	CA 20	35	-	183-280	265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
	CA 23	38	-	183-280	265/45, 275/40, 275/45, 285/45		Orig.-Verschr., nicht Bremse 395mm
9 x 21	CA 20	30	-	183-280	265/40, 275/40		Orig.-Verschr., bei 275/40 ✖
		37	-	183-280	265/40, 275/40		Orig.-Verschr.
9,5 x 21	B43	36	-	183-280	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 21	B43	VA 37	-	183-280	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					

Kombinationen

9 x 20	B43	28	-	183-280	VA 265/45		Orig.-Verschr.
10 x 20		39			HA 295/40		

BMW X5 M50 i/d		ab 2019	G5X (G05)	5/112	66,7	e1*2007/46*1918*00-14
Sensor - Brocksens 1						

Dimension	Design	ET	KIT	KW	Reifendimension		Info
9 x 19	B41	38	-	390	275/45, 275/50, 285/45		Orig.-Verschr.
9 x 20	B40	35	-	294, 390	275/40, 275/45 , 285/45		Orig.-Verschr., nur M+S
	B41	35	-	294-390	275/40, 275/45		Orig.-Verschr., nur M+S
	B43	35	-	294, 390	275/40, 275/45 , 285/45		Orig.-Verschr., nur M+S
	BR-IT	35	-	294, 390	275/40, 275/45 , 285/45		Orig.-Verschr., nur M+S
	B40	34	ZP599F	294	275/45		nur M+S
	B41	38	-	294-390	275/40, 275/45		Orig.-Verschr., nur M+S
	CA 20	35	-	294, 390	275/40, 275/45, 285/45		Orig.-Verschr., nur M+S
	FMI07 Atena	33	F93	294-390	275/40, 275/45		nur M+S
	FMI11 Elatha	34	F93	294-390	275/40, 275/45		nur M+S
9 x 21	B43	36	-	294, 390	275/40		Orig.-Verschr., nur M+S
	CA 20	37	-	294, 390	275/40		Orig.-Verschr., nur M+S
	FMI07 Atena	40	F93	294-390	275/40		nur M+S
9,5 x 21	B41	31+36	-	294-390	275/40, 285/35, 285/40		Orig.-Verschr., nur M+S
		43	-	294-390	275/40		Orig.-Verschr., nur M+S
	B43	36	-	294, 390	275/40		Orig.-Verschr., nur M+S
	BR-IT	36	-	294, 390	275/40		Orig.-Verschr., nur M+S
	FMI10 e-Joule	41,5	F93	294-390	275/40		nur M+S
	FMI12 Kari	31+41	F93	294-390	275/40, 285/35, 285/40		nur M+S
9,5 x 21	B41	VA 37	-	294-390	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	294, 390	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 22	B41	VA 37	-	294-390	VA 275/35+HA 315/30		Orig.-Verschr.
10,5 x 22		HA 43					
9,5 x 22	B41	45	-	294-390	275/35		Orig.-Verschr., nur M+S
10 x 22	FMI09 CRATOS	31	-	294-390	275/35		Orig.-Verschr., nur M+S
10 x 23	Race LS 3	30	14x1,25x30	294-390	295/30		i.V.

Kombinationen

9 x 20	B41	35	-	294-390	VA 275/40+HA 275/40, VA 275/45+HA 275/45		Orig.-Verschr., nur M+S
10,5 x 20		40					
9,5 x 21	B41	37	-	294-390	VA+HA 275/40, 285/35, 285/40 od.		Orig.-Verschr., bis 285/40 nur M+S
10,5 x 21		43			VA 275/40+HA 315/35		
10 x 23	Race LS 3	30	14x1,25x30	294-390	VA+HA 295/30		i.V.
11 x 23		30					

BMW X5 M60 i	NEU	ab Facelift 2023	G5X (G05)	5/112	66,7	e1*2007/46*1918*15-..
Sensor - Brocksens 1						

Dimension	Design	ET	KIT	KW	Reifendimension		Info
9 x 19	B41	38	-	390	275/45, 275/50, 285/45		Orig.-Verschr.

9 x 20	CA 20	35	-	390	265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
9 x 21	CA 20	37	-	390	265/40, 275/40		Orig.-Verschr.
9,5 x 21	B43	36	-	390	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 21	B43	VA 37	-	390	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	390	VA 265/40, 275/40, 285/35, 285/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 265/40, 275/40, 285/35, 285/40, 295/35, 305/35, 315/35		

Kombinationen

9 x 20	B43	28	-	390	VA 265/45		Orig.-Verschr.
10 x 20		39			HA 295/40		

BMW X5 M, X5 M Competition				ab 2020	F56XM	5/112	66,7	e1*2007/46*2066*..	
Sensor - Brocksens 1									
Dimension		Design		ET	KIT	KW	Reifendimension		Info

Kombinationen

10,5 x 21	B41	VA31	-	441-460	VA+HA 295/35		Orig.-Verschr., nur M+S
11 x 21		HA 48					
10 x 22	Race LS 2	35	14x1,25x40	441-460	VA 295/30+HA 305/30 od. VA 295/30+HA 315/30		VA mit mindestens 11mm Distanzscheiben - 751126651106
11,5 x 22		43	14x1,25x30				

BMW X5 Plug-in-Hybrid	ab 2020	G5X (G05)	5/112	66,7	e1*2007/46*1918*00-14
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	B40	35	-	155, 210	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr.
	B43	35	-	155, 210	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr.
	BR-IT	35	-	155, 210	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr., nicht Bremse 374mm
	CA 20	35	-	155, 210	265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
	CA 23	38	-	155, 210	265/45, 275/40, 275/45, 285/45		Orig.-Verschr., nicht Bremse 395mm
9 x 21	B43	36	-	155, 210	265/40, 275/40		Orig.-Verschr.
	CA 20	30	-	155, 210	265/40, 275/40		Orig.-Verschr., bei 275/40 ✖
		37	-	155, 210	265/40, 275/40		Orig.-Verschr.
9,5 x 21	B43	36	-	155, 210	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
	BR-IT	36	-	155, 210	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 21	B43	VA 37	-	155, 210	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155, 210	VA 265/40, 275/40, 285/35, 285/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 265/40, 275/40, 285/35, 285/40, 295/35, 305/35, 315/35		

Kombinationen

9 x 20	B43	28	-	155, 210	VA 265/45		Orig.-Verschr.
10 x 20		39			HA 295/40		

BMW X5 Plug-in-Hybrid	NEU	ab Facelift 2023	G5X (G05)	5/112	66,7	e1*2007/46*1918*15-..
Sensor - Brocksens 1						

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	CA 20	35	-	155, 230	265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
9 x 21	CA 20	37	-	155, 230	275/40		Orig.-Verschr.
9,5 x 21	B43	36	-	155, 230	275/40, 285/40		Orig.-Verschr., ab 285/40 ✖
9,5 x 21	B43	VA 37	-	155, 230	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155, 230	VA 265/40, 275/40, 285/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 275/40, 285/40, 295/35, 305/35, 315/35		

Kombinationen

9 x 20	B43	28	-	155, 230	VA 265/45		Orig.-Verschr.
10 x 20		39			HA 295/40		

BMW X6 (siehe Konfigurator)		ab 2015	X6/F16	5/120	VA/HA 74,1	e1*2007/46*0412*08-...	
--	--	---------	--------	-------	------------	------------------------	--

BMW X6M (siehe Konfigurator)		ab 2015	F86	5/120			
---	--	---------	-----	-------	--	--	--

BMW X6 III NEU	ab 2019	G6X (G06)	5/112	66,7	e1*2007/46*2020*...
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 19	B41	38	-	155-250	275/45, 285/45		Orig.-Verschr.
8,5 x 20	CA 19	32	ZP599F	155-390	275/45		nur M+S
	B40	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr.
	B41	35	-	155-250	275/45		Orig.-Verschr.
				155-280	275/45, 285/45		Orig.-Verschr.

9 x 20	B43	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr.
	BR-IT	35	-	155-250	265/45, 275/40, 275/45M+S , 285/45		Orig.-Verschr., nicht Bremse 374mm
	B41	33	-	155-280	265/45		Orig.-Verschr.
	AC-522	33	F93	155-390	275/45		nur M+S
	CA 20	35	-	155-250	265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
	CA 23	38	-	155-250	265/45, 275/40, 275/45, 285/45		Orig.-Verschr., nicht Bremse 395mm
9 x 21	FMI11 Elatha	34	F93	155-250	265/45, 275/40		
	B43	36	-	155-250	265/40, 275/40		Orig.-Verschr.
	CA 20	30	-	155-250	265/40, 275/40		Orig.-Verschr., bei 275/40 ✖
		37	-	155-250	265/40, 275/40		Orig.-Verschr.
		33	F93	155-250	265/40		
9,5 x 21	FMI07 Atena	40	F93	155-250	265/40, 275/40		nicht 4-Kolben Festsattel mit 348x36mm
		36	-	155-280	265/40, 275/40		Orig.-Verschr.
		36	-	155-250	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 21	BR-IT	36	-	155-250	265/40, 275/40, 285/35, 285/40		Orig.-Verschr., ab 285/35 ✖
9,5 x 21	B41	VA 37	-	155-250	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155-250	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	155-250	VA 265/40, 275/40, 285/35, 285/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 265/40, 275/40, 285/35, 285/40, 295/35, 305/35, 315/35		
9,5 x 22	B41	VA 37	-	155-250	VA 275/35+HA 315/30		Orig.-Verschr.
10,5 x 22		HA 43					
10 x 22	CA 20	38	-	155-250	265/35, 275/35, 295/30HA		Orig.-Verschr.
10 x 23	Race LS 3	30	14x1,25x30	155-250	VA+HA 275/35		

Kombinationen

9 x 20	AC-MB6	VA 34	-	155-250	VA 265/45, 275/40, 275/45, 285/45		Orig.-Verschr.
10,5 x 20		HA 39					
9 x 21	Race LS 2	VA 30	14x1,25x30	155-390	VA 275/35+HA 315/30 od. VA 275/40+HA 315/35		
10,5 x 21		HA 44					
9 x 21		VA 41	14x1,25x30	155-390	VA 275/35+HA 315/30 od. VA 275/40+HA 315/35		VA mit mindestens 11mm Distanzscheiben - 751126651106
10,5 x 21		HA 44					
9,5 x 21	B41	VA 37	-	155-280	VA+HA 275/40 od. VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9 x 22	Race LS 2	VA 30	14x1,25x30	155-390	VA+HA 275/35		
10 x 22		HA 35					
9,5 x 22	AF18	VA 31+37	F93	155-390	VA 275/35+HA 315/30		incl. Hybrid
10,5 x 22		HA 43					
10 x 23	Race LS 3	VA 30	14x1,25x30	155-250	VA 275/35+HA 315/30		✖
11 x 23		HA 30					
10 x 23		VA 30	14x1,25x30	155-250	VA 275/35+HA 315/30		✖
11,5 x 23		HA 30					

BMW X6 M50 i/d III NEU			ab 2020	G6X (G06)	5/112	66,7	e1*2007/46*2020*...
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	B40	35	-	294, 390	275/40M+S, 275/45M+S , 285/45		Orig.-Verschr.
	B43	35	-	294, 390	275/40M+S, 275/45M+S , 285/45		Orig.-Verschr.
	BR-IT	35	-	294, 390	275/40M+S, 275/45M+S , 285/45		Orig.-Verschr.
	B41	35	-	294, 390	275/45, 285/45		Orig.-Verschr., nur M+S
	CA 20	35	-	294, 390	275/40M+S, 275/45M+S, 285/45		Orig.-Verschr.
9 x 21	B43	36	-	294, 390	265/40, 275/40		Orig.-Verschr., nur M+S
	CA 20	37	-	294, 390	275/40		Orig.-Verschr., nur M+S
9,5 x 21	B43	36	-	294, 390	275/40, 285/35, 285/40		Orig.-Verschr., nur M+S, ab 285/35 ✖
	BR-IT	36	-	294, 390	275/40, 285/35, 285/40		Orig.-Verschr., nur M+S, ab 285/35 ✖
9,5 x 21	B43	VA 37	-	294, 390	VA 275/40+HA 315/35		Orig.-Verschr.
10,5 x 21		HA 43					
9,5 x 21	B43	VA 37	-	294, 390	VA 275/40, 285/40		Orig.-Verschr.
10,5 x 21		HA 43			HA 315/35		
10 x 23	Race LS 3	30	14x1,25x30	294-390	275/35		

Kombinationen

9 x 20	AC-MB6	VA 34	-	294, 390	VA 275/40, 275/45, 285/45		Orig.-Verschr., nur M+S
10,5 x 20		HA 39					
10 x 23	Race LS 3	VA 30	14x1,25x30	155-250	VA 275/35+HA 315/30		✖
11 x 23		HA 30					
10 x 23		VA 30	14x1,25x30	155-250	VA 275/35+HA 315/30		✖
11,5 x 23		HA 30					

BMW X6 M, X6 M Competition NEU			2020	F56XM	5/112	66,7	e1*2007/46*2066*..
Sensor - Brocksens 1							

Dimension	Design	ET	KIT	KW	Reifendimension	Info
Kombinationen						
10,5 x 21 11 x 21	B41	VA 31 HA 48	-	441-460	VA+HA 295/35	 Orig.-Verschr., nur M+S
10 x 22 11,5 x 22		35 43	14x1,25x40 14x1,25x30	441-460	VA 295/30+HA 305/30 od. VA 295/30+HA 315/30	VA mit mindestens 11mm Distanzscheiben - 751126651106

BMW X7	ab 03.2019	G7X (G07)	5/112	66,7	e1*2007/46*1952*..
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
ACHTUNG!!! Dringend die Achslasten überprüfen!!!						
8,5 x 20	B41	35	-	155-390	VA 255/55+HA 275/50	 Orig.-Verschr.
				155-390	255/50, 255/55, 265/50, 275/45, 275/50, 285/50	Orig.-Verschr., bis 265/50 nur M+S
	B43	35	-	155-250	255/55M+S, 275/50	 275/50 nur bis 250 KW
9 x 20	B41	33	-	155-390	255/50, 255/55, 265/50, 275/45, 275/50, 285/45	Orig.-Verschr., bis 265/50 nur M+S, auch Hybrid
		35+38	-	155-390	255/50, 255/55, 265/50, 275/45, 275/50, 285/45	Orig.-Verschr., bis 265/50 nur M+S
	B43	35	-	155-250	275/50	
				155-390	255/55M+S, 265/50M+S, 275/50M+S	Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-250	255/55M+S, 265/50M+S, 275/50	Orig.-Verschr.
	BR-IT	35	-	155-250	275/50	Orig.-Verschr., mit M-Paket-Verbreiterungen, nicht Bremse 374mm
				155-390	255/55M+S, 265/50M+S, 275/50M+S	
				155-250	255/55M+S, 265/50M+S, 275/50	Orig.-Verschr., nicht Bremse 374mm
	CA 20	35	-	155-250	275/50	Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-390	255/55M+S, 265/50M+S, 275/50M+S	
				155-250	255/55M+S, 265/50M+S, 275/50	Orig.-Verschr.
	FMI07 Atena	33	F93	155-390	255/50M+S, 255/55M+S, 265/50M+S, 275/45, 275/50, 285/45	
8,5 x 21	B41	19	-	155-390	265/45M+S	Orig.-Verschr.
		30+34+37	-	155-390	255/50M+S, 265/45M+S, 275/45	Orig.-Verschr.
	B43	30+34	-	155-250	275/45	Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-390	255/50M+S, 265/45M+S, 275/45M+S	
9 x 21	B43	36	-	155-250	275/45, 285/45	
				155-390	255/50M+S, 265/45M+S, 275/45M+S, 285/45M+S	Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-250	255/50M+S, 265/45M+S, 275/45, 285/45	Orig.-Verschr.
	CA 20	30	-	155-250	275/45	Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-390	255/50M+S, 265/45M+S, 275/45M+S	
				155-250	255/50M+S, 265/45M+S, 275/45	Orig.-Verschr.
	FMI07 Atena	33	F93	155-390	255/50M+S, 265/45M+S, 275/45, 285/45	
9,5 x 21	B41	36	-	155-390	265/45M+S, 275/45, 285/40, 285/45	 Orig.-Verschr.
	B43	36	-	155-390	265/45M+S, 275/45, 285/45	 Orig.-Verschr., mit M-Paket-Verbreiterungen
				155-250	265/45M+S, 275/45, 285/45	 Orig.-Verschr.
	B41	31	-	155-390	265/45M+S, 275/45, 285/40, 285/45	Orig.-Verschr.
	BR-IT	36	-	155-250	275/45	
				155-390	265/45M+S, 275/45M+S, 285/45	 Orig.-Verschr., mit M-Paket-Verbreiterungen
9,5 x 22 10,5 x 22	B41	VA 32 HA 43	-	155-390	VA 275/40+HA 315/35	 Orig.-Verschr., auch für Hybrid
10 x 22	FMI07 Atena	31	F93	155-390	275/40	
	FMI09 CRATOS	31	-	155-390	275/40	Orig.-Verschr.
10 x 23	Race LS 3	30	14x1,25x30	155-390	285/35	
	STC-23	32	-	155-390	275/35	Orig.-Verschr.

Kombinationen						
9 x 20 10,5 x 20	B41	VA 35 HA 40	-	155-390	VA 275/45+HA 275/45, VA 285/45+HA 285/45	Orig.-Verschr.
8,5 x 21 9,5 x 21		VA 30 HA 43	-	155-390	265/45M+S, 275/45	Orig.-Verschr.
9,5 x 21 10,5 x 21	B41	VA 37 HA 43	-	155-390	VA+HA 275/45, 285/40, 285/45 od. VA 275/45+HA 315/40	Orig.-Verschr.
9,5 x 22 10,5 x 22		VA 31+37 HA 43	F93	155-390	VA 275/40+HA 315/35	
9 x 22 11,5 x 22	Race LS 2	VA 30 HA 43	14x1,25x30	155-390	VA 275/40+HA 315/35	
9 x 22 11,5 x 22		VA 35 HA 43	14x1,25x40 14x1,25x30	155-390	VA 275/40+HA 315/35	VA mit 11mm Distanzscheiben - 751126651106
9,5 x 22 10,5 x 22		VA 37 HA 43	-	155-390	VA+HA 275/40, 285/40 VA 275/40+HA 315/35	Orig.-Verschr., auch für Hybrid
10 x 22 11 x 22	CA 17	VA 30 HA 40	ZP593F	155-390	VA 275/40+HA 315/35	✖
10 x 23	Race LS 3	VA 30	14x1,25x30	155-390	VA+HA 285/35	

9 x 20		25		120-250	VA 255/30+HA 275/30		Orig.-Verschr., nur M+S
8,5 x 20	Race GTS	24+35	14x1,25x30	120-250	VA 255/30+HA 275/30		
10 x 20		38					
8,5 x 20	Race GTX	24+35	14x1,25x30	120-250	VA 255/30+HA 275/30		
10 x 20		38					
8,5 x 20	Hibonit	24+35	14x1,25x30	120-250	VA 255/30+HA 275/30		
10 x 20		38					
9 x 20	B43	28	-	120-190	VA 255/30		Orig.-Verschr.
10 x 20		39			HA 275/30		
9 x 20	Oxigin 25	28	ZP599F	120-250	VA 255/30		HA ✖
10,5x20		30			HA 285/30		

BMW Z4 M40i NEU				G4Z (G29)	5/112	66,6	e1*2007/46*1949*..
-----------------	--	--	--	-----------	-------	------	--------------------

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	B42	30	-	250	225/45, 245/40	Orig.-Verschr., nur M+S
	B44	30	-	250	225/45, 245/40	Orig.-Verschr., nur M+S
	AC-M10	30	-	250	225/45, 245/40	Orig.-Verschr., nur M+S
	CA 23 / CA 26	30	ZP599F	250	225/45, 245/40	nur M+S
8 x 19	B40	30	-	250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S
	B43	28	-	250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S
	BR-I	27	-	250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S
8,5 x 19	B32	25	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	B42	30	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	B43	25+29	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	B44	25+30	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	B42	30	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	AC-M10	30	-	250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S
	CA 23	30	ZP593F	250	225/40, 235/35, 245/35, 255/35	nur M+S
	Oxigin 28	30	ZP593F	250	225/40, 235/35, 245/35, 255/35	nur M+S
8 x 20	RC36	27	-	250	245/30	Orig.-Verschr., nur M+S
	B43	27+30	-	250	245/30	Orig.-Verschr., nur M+S
	BR-I	30	-	250	245/30	Orig.-Verschr., nur M+S, nur für Fahrzeuge ohne Kunststoff Verschlusskappen auf den Fahrzeugnaben
8,5 x 20	RC29	26	-	250	245/30, 255/30	Orig.-Verschr., nur M+S
	B32	30	-	250	245/30, 255/30	Orig.-Verschr., nur M+S
	B42 / B43	30	-	250	245/30, 255/30	Orig.-Verschr., nur M+S
	B44	25+30	-	250	245/30, 255/30	Orig.-Verschr., nur M+S
	AC-M10	30	-	250	245/30, 255/30	Orig.-Verschr., nur M+S

Kombinationen

9 x 20	B43	28	-	250	VA 255/30		Orig.-Verschr.
10 x 20		39			HA 275/30		

BYD

Atto 2 NEU				ab 2025	SC3E	5/114,3	60,1	e4*2018/858*00231*..
------------	--	--	--	---------	------	---------	------	----------------------

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	40	-	65 (130)	215/60, 225/55, 235/55	 Orig.-Verschr.
7,5 x 20	RC36	35	-	65 (130)	225/40	Orig.-Verschr.

Atto 3 NEU				im Laufe 2023	SC2E	5/114,3	60,1	e9*2018/858*11147*..
------------	--	--	--	---------------	------	---------	------	----------------------

Sensor - Artikelnr. 101255 (HUF - silbernes Ventil) u. Artikelnr. 101257 (HUF - schwarzes Ventil)

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	40	-	65	215/60, 225/55, 235/55	 Orig.-Verschr.
	RC34	40	-	65	215/60	 Orig.-Verschr.
7 x 17	RC27	35	-	65 (150)	215/60, 225/55, 235/55, 245/50	Orig.-Verschr.
7,5 x 17	B24	38	- +R	65 (150)	215/60, 225/55, 235/55	Orig.-Verschr. + Red.Ringe 72,6-60,1
7 x 18	RC34	40	-	65	215/55, 225/50, 235/50	 Orig.-Verschr.
	FMI06 Koros	40	-		215/55, 235/50	 Orig.-Verschr.
	RC27	35	-	65 (150)	215/55, 225/50, 235/50	Orig.-Verschr.
7,5 x 18	RC30	35	- +R	65 (150)	215/55, 225/50, 235/50, 245/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
	AC-MB6 / AC-M10	35	Artikel Nr. 98502	65 (150)	215/55, 225/50, 235/50, 245/45	Kit mit Artikelnummer 98502
	CA 20	40	-	65	215/55, 225/50, 235/50, 245/45	Orig.-Verschr.
8 x 18	B24	38	- +R	65 (150)	215/55, 225/50, 235/50, 245/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
	B36 / B38	35	- +R	65 (150)	215/55, 225/50, 235/50, 245/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
	B42	30	- +R	65 (150)	215/55, 225/50	Orig.-Verschr. + Red.Ringe 72,6-60,1
		40	- +R	65 (150)	215/55, 225/50, 245/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
	B44	30	- +R	65 (150)	215/55, 225/50	Orig.-Verschr. + Red.Ringe 72,6-60,1
		40	- +R	65 (150)	215/55, 225/50, 245/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
7,5 x 19	B32	40	- +R	65 (150)	215/50, 225/45, 235/45	Orig.-Verschr. + Red.Ringe 72,6-60,1
8 x 19	CA 17	40	ZP574	65	225/45, 235/45	

8,5 x 19	Oxigin 29	40	ZP574	65 (150)	225/45, 235/45, 245/40		
	B32 / B42	35	- +R	65 (150)	225/45, 235/45		Orig.-Verschr. + Red.Ringe 72,6-60,1
	B36	38	- +R	65 (150)	225/45, 235/45		Orig.-Verschr. + Red.Ringe 72,6-60,1
	B44	30	- +R	65 (150)	225/45		Orig.-Verschr. + Red.Ringe 72,6-60,1
		40	- +R	65 (150)	225/45, 235/45		Orig.-Verschr. + Red.Ringe 72,6-60,1
	CA 20	30	ZP574	65 (150)	225/45		
7,5 x 20	8300 - 1973	40	F37C+R	65	225/45, 235/45, 245/40, 255/40		+ Red.Ringe 75,1-60,1
	RC36	35	-	65	225/40		Orig.-Verschr.
	B43	40	ZP580D8F	65 (150)	225/40		Orig.-Verschr., Ausführung S3
8,5 x 20	B42	35	- +R	65 (150)	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe 72,6-60,1
		30	- +R	65 (150)	225/40		Orig.-Verschr. + Red.Ringe 72,6-60,1
	B44	40	- +R	65 (150)	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe 72,6-60,1

Dolphin NEU		Oktober 2023		EM2E, EM2E-1		5/114,3	60,1	e9*2018/858*11468*..., e9*KS18/858*11459*..	
Sensor - Schrader 3103 - Artikelnummer 99199									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6 x 16	RC27	45	-	35	195/60, 205/55, 215/55				Orig.-Verschr.
7 x 16	RC30	40	-	35	195/60, 205/55				Orig.-Verschr.
6,5 x 17	RC27	45	-	35, 65	205/50				Orig.-Verschr.
	RC34	45	-	65	205/50				Orig.-Verschr.
				35-65	195/50, 195/55, 205/50				
	RC27	40	-	35, 65	205/50				Orig.-Verschr.
7 x 17	RC27	35	- +R	35, 65	215/45				Orig.-Verschr. + Red.Ringe 72,6-60,1
		45	- +R	35, 65	205/50, 215/45, 225/45				Orig.-Verschr. + Red.Ringe 72,6-60,1
	CA 26	45	ZP574	35, 65	205/50, 215/45, 225/45				
7,5 x 17	B24	38	- +R	35, 65	215/45				Orig.-Verschr. + Red.Ringe 72,6-60,1
7 x 18	RC27	35	-	35, 65	205/45				Orig.-Verschr.
	RC34	40	-	35-65	205/40, 205/45, 215/40				Orig.-Verschr.
7,5 x 18	RC30	35	- +R	35, 65	205/45				Orig.-Verschr. + Red.Ringe 72,6-60,1
		45	- +R	35, 65	205/45, 215/40				Orig.-Verschr. + Red.Ringe 72,6-60,1
	AC-MB6 / AC-M10	45	Artikel Nr. 98502	35, 65	205/45, 215/40				Kit mit Artikelnummer 98502
	CA 20	40	-	35-65	205/40, 215/40				Orig.-Verschr.
8 x 18	B42	40	- +R	35, 65	215/40				Orig.-Verschr. + Red.Ringe 72,6-60,1
	B44	40	- +R	35, 65	215/40				Orig.-Verschr. + Red.Ringe 72,6-60,1
	CA 24	45	ZP574	35-65	215/40				

Dolphin Surf		NEU i.V.		ab 2025		EQE		4/100		54,1		e4*2018/858*00233*..	
Dimension		Design		ET		KIT		KW		Reifendimension		Info	
5 x 15		RC19		40		-				175/65		Orig.-Verschr., i.V.	
6 x 16		RC34		45		-				185/55		Orig.-Verschr., Ausführung M41, nur in der Farbe SGVP erhältlich, i.V.	

ETP3 NEU					5/120	e9*2018/858*11315*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
!!!Keine Räder in Planung, Fahrzeug ist weder in Österreich noch in Deutschland bestellbar!!! (Info: 26.05.2025)							

Han EV NEU		im Laufe 2023		HC		5/120	64,1	e9*KS18/858*11304*..	
Sensor - Brocksens Universal									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 19	B40	40	-	130 (380)	245/45			Orig.-Verschr.	
8,5 x 19	B32	38	- +R	130 (380)	245/45			Orig.-Verschr. + Red.Ringe 72,6-64,1	
8 x 20	RC36	40	-	130 (380)	245/40			Orig.-Verschr.	

Seal NEU		4. Quartal 2023		EK / EKE		5/120	64,1	e13*KS18/858*00023*..., e13*2018/858*00639*...	
Sensor - Artikelnr. 101255 (HUF - silbernes Ventil) u. Artikelnr. 101257 (HUF - schwarzes Ventil)									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 19	B32	45	-	70	225/45, 235/45				Orig.-Verschr.
8 x 19	RC34	45	-	70-145	235/45, 245/40				Orig.-Verschr.
	FMI06 Koros	45	-		235/45				Orig.-Verschr.
8 x 20	RC36	40	-	70, 145	235/40				Orig.-Verschr.

Seal U NEU		2024		SA3 / SA3-E		5/120	64,1	e9*2018/858*11535*..., e9*KS18/858*11477*..	
Sensor - Schrader 3319 - Artikelnummer 102639									
Dimension		Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 19		RC34	45			235/50			i.V., Lieferzeit August / September
		FMI06 Koros	45	-		235/50			Orig.-Verschr.
		CA 26	45	ZP598 od. OX583	72, 96	235/50, 245/45			Bei einer Direktlieferung muss der Kit OX583 verwendet werden!
8 x 20		RC36	40	-	72, 96	235/45, 245/40, 245/45			Orig.-Verschr.

Seal U Elektro NEU		2024		SA3 / SA3-E		5/120	64,1	e9*2018/858*11535*.., e9*KS18/858*11477*..	
-----------------------------------	--	------	--	-------------	--	-------	------	--	--

Sensor - Schrader 3319 - Artikelnummer 102639							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 19	CA 26	45	ZP598 od. OX583		235/50, 245/45		Bei einer Direktlieferung muss der Kit OX583 verwendet werden!
8 x 20	RC36	40	-	65, 70	235/45, 245/40, 245/45		Orig.-Verschr.

Sealion 7 AWD NEU 2024 UK 5/120 64,1 e9*2018/858*11658*..							
Sensor - Schrader 3319 - Artikelnummer 102639							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 19	RC34	VA 40	-		VA 235/50		Orig.-Verschr., i.V., Lieferzeit August / September
8,5 x 19		HA 40			HA 255/45		
7,5 x 19	FMI06 Koros	VA 40	-		VA 235/50		Orig.-Verschr., i.V.
8,5 x 19		HA 40			HA 255/45		
8 x 20	RC36	40	-	145 (390)	245/45		Orig.-Verschr.

Tang EV NEU im Laufe 2023 STE 5/120 64,1 e9*KS18/858*11108*..							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 20	B40	31	-	130 (380)	255/50		Orig.-Verschr.

Citroen

Citroen		Baujahr	Typ	LK/LZ	Nabe		
Berlingo IV		ab 2018	E	5/108	65,1	e2*2007/46*0624*..., e2*2007/46*0625*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	47	ZP538F	55-96	205/55, 205/60 , 215/55		nicht bei 15" Serie, nicht Bremse 283mm
	RC32	47	ZP538F	55-96	195/55, 195/60, 205/55, 205/60 , 215/50, 215/55, 225/50, 225/55		Serienreifen bis 205/...
					215/65, 215/65C, 225/65C		Serienreifen ab 215/...
	RC34	47	- od. ZP537F	55-96	195/55, 195/60, 205/55, 205/60 , 215/50, 215/55, 225/50, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 20	45	ZP538	55-96	205/55, 205/60, 215/55, 225/50, 225/55		
7 x 17	Pro1	42	-	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55 215/65, 215/65C		Orig.-Verschr., Serienreifen bis 205/.. Orig.-Verschr., Serienreifen ab 215/..
	RC30	50	ZP538F	55-96	205/50, 205/55 , 225/45		nicht bei 16" Serie
	RC34	50	- od. ZP537F	55-96	195/50, 195/55, 205/45, 205/50, 205/55 , 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	50	ZP538F	55-96	205/55		
	RC27	42	- od. ZP537F	55-81	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! für 15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC32	42	ZP538F	55-96	195/50, 195/55, 205/45, 205/50, 205/55, 215/45, 225/45		
	RC34	46	- od. ZP537F	55-96	195/50, 195/55, 205/45, 205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! nicht Bremse 268x12mm HA
7,5 x 17	CA 26	50	ZP538F	55-96	205/50, 205/55, 225/45		
	Pro1	45	-	55-96	205/45, 205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr., Serienreifen bis 205/..
	RC24	44	ZP538F	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
		47	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC29	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC34	44	- od. ZP537F	55-96	205/45, 205/50, 205/55, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	B24	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
7 x 18	AC-518	45	ZP538F+R	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
	RC27	44+48	- od. ZP537F	55-96	205/45, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45		nicht bei 15" Serie
	RC32	49	ZP538F	55-96	215/40, 215/45, 225/40		Serienreifen bis 205/...
				55-96	215/50, 235/45		Serienreifen ab 215/...
	RC34	49	- od. ZP537F	55-96	215/40, 215/45, 225/40		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	B32 / B39	45	ZP538	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	AC-MB6	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-65,1
	RC29	45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie
	8 x 18	RC32	44	ZP538F	55-96	215/40, 215/45	
RC34		44	ZP538F	55-96	215/40, 215/45		
B36		45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie, nicht Bremse 283 u. 304mm
B37 / B38		45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie
AC-M10		42	ZP538F+R	55-96	215/45		+ Red.Ringe 73,1-65,1 , nicht Bremse 283mm
AC-518		45	ZP538F+R	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
AC-521		43	ZP538F+R	55-96	215/45		+ Red.Ringe 73,1-65,1
7,5 x 19	RC32	46	ZP538F	55-96	225/35		
	B32	45	ZP538F	55-81	225/35		nicht bei 16" Serie
	AC-521	42	ZP538F+R	55-81	225/35		+ Red.Ringe 73,1-65,1 , 15 Zoll Serie
e-Berlingo		ab 2021	E	5/108	65,1	e2*2007/46*0624*..., e2*2007/46*0625*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC32	47	ZP538F	57-62	205/60		
	Pro1	42	-	57	205/60, 215/55, 215/60		Orig.-Verschr., Serienreifen bis 205/..
7 x 17	RC34	50	- od. ZP537F	57-62	205/50, 205/55 , 215/50, 225/45, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC32	42	ZP538F	57	205/50, 205/55, 225/45		
	RC34	42	- od. ZP537F	57-62	205/50, 205/55, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		44	- od. ZP537F	57-62	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	Pro1	45	-	57	205/50, 205/55, 215/50, 225/45		Orig.-Verschr.

7,5 x 17	RC34	44	- od. ZP537F	57	205/50, 205/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
8 x 18	RC34	44	ZP538F	57-62	215/45		

Citroen C1 (siehe Konfigurator)	ab 2014	P****	4/100	54,1	e11*2001/116*0238*11...
---------------------------------	---------	-------	-------	------	-------------------------

Citroen C3 III	ab 02.2017	S	4/108	65,1	e2*2007/46*0003*44-..., e2*2007/46*0060*17-..., (FIN: VF7SX, /SY...)
----------------	------------	---	-------	------	---

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	23	ZP402F	50-81	185/65		
				50-85	195/65, 205/60		
	RC30	23	ZP402F	50-81	185/65		
				50-85	195/65, 205/60		
6,5 x 15	RC28	20	ZP402F	50-81	185/65, 195/65, 205/60		
6 x 16	RC30	23	ZP402F	50-85	195/55, 195/60, 205/55		
				50-85	195/55, 195/60, 205/55		
	RC34	20	- od. ZP401F	50-85	185/60, 195/55, 205/50, 205/55		
				50-85	195/55, 195/60, 205/55		
6,5 x 16	RC24	23	ZP402F	50-85	195/55, 195/60		
				50-85	195/55, 195/60		
	RC28	18	ZP402F	50-85	195/55, 195/60		
				50-85	195/55, 195/60		
7 x 17	RC34	25	- od. ZP401F	50-121	195/45, 205/40, 205/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
				50-85	195/45, 195/50, 205/45, 215/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
	B39	18	ZP402F	50-85	215/45		
				50-85	205/40, 205/45		
7,5 x 18	B39	20	ZP402F	50-85	215/35		
7,5 x 19	B39	18	ZP402F	50-85			

Citroen C3 NEU	2024	C	4/108	65,1	e2*2018/858*00035*02-...
----------------	------	---	-------	------	--------------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	74	205/55		

Citroen e-C3 NEU	2024	C	4/108	65,1	e2*2018/858*00035*02-...
------------------	------	---	-------	------	--------------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	53 (83)	205/55		
		38	ZP402F	53 (83)	205/55, 215/55, 225/50		

Citroen C3 Aircross	ab 2017	2	4/108	65,1	e4*2007/46*1241*01
---------------------	---------	---	-------	------	--------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	20	ZP402F	60-96	195/60, 205/55, 205/60, 215/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
	RC34	20	- od. ZP401F	60-96	195/60, 195/65, 205/55, 205/60, 215/55		
		20	ZP402F	60-96	195/60, 205/55, 205/60, 215/55		
	RC24	20	-	60-96	205/45, 205/50, 205/55, 215/50		
6,5 x 17	RC34	20	-	60-96	205/45, 205/50, 205/55, 215/50		Orig.-Verschr.
7 x 17	RC34	20	- od. ZP401F	60-96	205/45, 205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
		25	- od. ZP401F	60-96	205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
	B24	12	ZP402F	60-88	215/45		
	B39	18	ZP402F	60-88	205/50, 205/55, 215/45, 215/50, 225/45		
		15	ZP402F	60-88	215/45		
7,5 x 17	RC28	20	ZP402F	60-96	205/45, 215/40, 215/45, 225/40		
7,5 x 18	B39	20	ZP402F	60-96			

Citroen e-C3 Aircross elektro NEU i.V.	ab 2024	C	4/108	65,1	e2*2018/858*00035*...
--	---------	---	-------	------	-----------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	28	-		215/65		Orig.-Verschr., i.V., Lieferzeit August

DS3 Cabrio	ab 2016	S	4/108	65,1	e2*2007/46*0003*...
------------	---------	---	-------	------	---------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	23	ZP402F	115	185/65, 195/60		
7 x 17	B24	25	ZP402F	115	195/45, 205/45, 215/45		

DS3 FL	ab 04.16	S****, S	4/108	65,1	e2*2007/46*0003*..., (FIN: VF7SA..., VF7SB)
--------	----------	----------	-------	------	---

kein Sensor - indirektes RDKS							
-------------------------------	--	--	--	--	--	--	--

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	23	ZP402F	50-88	185/65		
	RC30	23	ZP402F	50-88	185/65		
6 x 16	RC30	23	ZP402F	50-88	185/55, 195/50, 195/55		
				110-122	195/55		
7 x 17	RC34	25	- od. ZP401F	50-121	205/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
	B39	25	ZP402F	50-122	205/45		

DS3 Crossback NEU		ab 04.2019		U	4/108	65,1	e2*2007/46*0639*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	32	ZP402F	74-114	215/60, 215/65, 225/60			
	RC34	32	- od. ZP401F	74-114	215/60, 215/65		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!	
6,5 x 17	RC34	32	- od. ZP401F	74-114	215/60, 225/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!	
7 x 17	RC34	32	- od. ZP401F	74-114	215/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!	
7,5 x 18	B39	32	ZP402F	74-114	215/50, 215/55, 235/45			

DS3 Crossback e-tense NEU			U		4/108	65,1	e2*2007/46*0639*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7,5 x 18	B39	32	ZP402F	57 (100)	215/50, 215/55, 235/45			
DS3 e-tense NEU i.V.			2021		DS		65,1	e2*2007/46*0639*..
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 17	RC34	32			215/60			 i.V.

DS4 (siehe Konfigurator)		ab 07.11		N	4/108	65,1	
---	--	----------	--	---	-------	------	--

DS4 NEU		ab Jänner 2022		F	5/108	65,1	e2*2007/46*0628*10-...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	42	- od. ZP537F	96-165	205/65, 215/65 , 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	42	ZP538F	96-165	205/65, 215/65 , 225/60		auch Hybrid
	CA 26	42	ZP538F	96-165	205/65, 215/65 , 225/60		
	AC-V51	45	-	96-165	215/65, 225/60, 235/55, 235/60		Orig.-Verschr. von Alufelgen, nicht Bremse 304 u. 330mm
7,5 x 17	RC27	37	ZP538F	96-165	205/65		
	RC29	45	ZP538	96-165	205/65, 215/65, 225/60, 235/55, 235/60		
	B36	45	ZP538	96-165	205/65, 215/65, 225/60, 235/55, 235/60		nicht Bremse 304 u. 330mm
7 x 18	RC27	44+48	- od. ZP537F	96-165	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	96-165	215/55, 215/60, 225/55, 235/50, 235/55		
	AC-MB6	42	ZP538F+R	96-165	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	96-165	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	96-165	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
8 x 18	B37	45	ZP538	96-165	225/55		
	CA 20	45	ZP538	96-165	225/55		nicht Bremse 304 u. 330mm
7 x 19	RC27	41	- od. ZP537F	96-165	205/55, 215/50, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		38	ZP538F	96-165	205/55, 215/50		
7,5 x 19	B32	42	ZP538F	96-165	215/50, 225/50, 235/45, 245/45		nicht Bremse 304mm
	AC-521	42	ZP538F+R	96-165	215/50, 225/50, 235/45, 245/45		+ Red.Ringe 73,1-65,1
	CA 26	45	ZP538	96-165	215/50, 225/50, 235/45, 235/50, 245/45		
8 x 19	RC29	45	ZP538	96-165	225/50, 235/45, 245/45		
	Oxigin 29	45	ZP538	96-165	225/50, 235/45, 245/45		
8,5 x 19	B32	45	ZP538	96-165	235/45		
8 x 20	RC36	50	- od. ZP537F	96-165	235/40, 245/40		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	B43	44	-	96-165	215/45, 235/40, 245/40		Orig.-Verschr. für Alufelgen

e-DS4 NEU i.V.		Herbst 2024					
-------------------------------	--	-------------	--	--	--	--	--

DS5 (siehe Konfigurator)		ab 03.12		K	4/108	65,1	e2*2007/46*0092*..., e2*2007/46*0093*..
---	--	----------	--	---	-------	------	---

DS7 Crossback		ab 2018		J	5/108	65,1	e2*2007/46*0601*...
---------------	--	---------	--	---	-------	------	---------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC34	44	-	96-165	215/65		Orig.-Verschr., nicht Bremse 330x30mm
	RC27	42	- od. ZP537F	96-165	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	42	ZP538F	96, 130	205/65		
	RC32	42	ZP538F	96-165	215/65, 225/60, 225/65, 235/60, 245/55		
	RC34	42+44	- od. ZP537F	96-165	215/65, 225/60, 235/55, 235/60, 245/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		46	- od. ZP537F	96-165	215/65, 225/60, 235/55, 235/60, 245/55, 255/50, 255/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! nicht Bremse 330x30mm VA
	CA 26	42	ZP538F	96-165	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		
7,5 x 17	Pro1	45	-	96-165	215/65, 225/60, 235/55, 235/60, 245/55, 255/50, 255/55		Orig.-Verschr.
	RC24	44	ZP538F	96, 130	205/65		
	RC27	37	ZP538F	96-165	215/65, 225/60, 225/65, 235/60, 245/55		
				205/65, 215/65, 225/60, 225/65			
	RC29	45	ZP538	96-165	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		
	RC34	44	-	96-165	215/65, 225/60, 235/55, 235/60, 245/55		Orig.-Verschr., auch Hybrid
		45	ZP538F	96-165	215/65, 225/60, 235/55, 235/60		
B24	45	ZP538	96, 130	205/65			
			96-165	215/65, 225/60, 225/65, 235/60, 245/55			
B36	45	ZP538	96-165	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		nicht Bremse 304 u. 330mm	
7 x 18	RC27	44	- od. ZP537F	96-165	225/55, 225/60, 235/55, 245/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	Originaldim.	46		96-165	235/55		
	B32 / B39	45	ZP538	96-165	225/55, 225/60, 235/55, 245/50		
	AC-MB6	42	ZP538F+R	96-165	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	96-165	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	96-165	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	96-165	225/55, 235/55, 245/50		
	RC27	45	ZP538	96-165	225/55, 225/60, 235/55		
8 x 18	RC32	44	ZP538F	96-165	235/55		
	RC34	44	ZP538F	96-165	225/55, 235/55		
	B37 / B38	45	ZP538	96-165	225/55, 225/60, 235/55		
	B42 / B44	42	ZP538	96-165	225/55, 225/60, 235/55		
	AC-M10	42	ZP538F+R	96-165	225/55, 225/60, 235/55		+ Red.Ringe 73,1-65,1
	AC-518	45	ZP538F+R	96-165	225/55, 225/60, 235/55		+ Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	96-165	225/55, 225/60, 235/55		+ Red.Ringe 73,1-65,1
8,5 x 18	B32	45	ZP538	96-165	235/55		
		38	ZP538F	96-165	205/55, 235/50		
7 x 19	RC27	41	- od. ZP537F	96-165	205/55, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 19	RC34	38	-	96-165	205/55		Orig.-Verschr.
	RC32	40	ZP538F	96, 133	205/55		
					205/55, 235/45, 245/45		auch für Hybrid
	B32	46	ZP538F	96-165	205/55, 235/45, 235/50, 245/45		
	AC-521	42	ZP538F+R	96-165	235/50, 245/45		+ Red.Ringe 73,1-65,1
	CA 26	45	ZP538	96-165	235/50, 245/45		
8 x 19	RC29	45	ZP538	96-165	235/50, 245/45, 255/45		
	RC34	42	ZP538F	96-165	235/45, 245/45		auch für Hybrid
	B38	45	ZP538	96-165	235/50, 245/45, 255/45		
	AC-518	45	ZP538F+R	96-165	235/50, 245/45, 255/45		+ Red.Ringe 73,1-65,1
	Oxigin 29	45	ZP538	96-165	235/50, 245/45, 255/45		
8,5 x 19	B32	45	ZP538	96-165	235/50, 245/45, 255/45		
	CA 23	45	ZP538	96-165	235/50, 245/45, 255/45		nicht Bremse 304 u. 330mm
8 x 20	B43	44	-	96-165	215/45, 235/45, 245/40		Orig.-Verschr. für Alufelgen
8,5 x 20	B32	45	ZP538	96-165	235/45, 245/40, 255/40		
	AC-518	45	ZP538F+R	96-165	235/45, 245/40, 255/40		+ Red.Ringe 73,1-65,1
9 x 20	CA 23	45	ZP538F	96-165	235/45, 245/40		
	Oxigin 28	40	ZP538	96-165	235/45		

DS7 Crossback e-tense NEU 2020 J 5/108 65,1 e2*2007/46*0601*...

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	133, 147	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	42	ZP538F	133, 147	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Plug-in-Hybrid
	CA 26	42	ZP538F	133, 147	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Plug-in-Hybrid

7,5 x 17	RC27	37	ZP538F	133, 147	205/65, 215/65, 225/60, 225/65		Plug-in-Hybrid
	RC29	45	ZP538	133, 147	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Plug-in-Hybrid
7 x 18	RC27	44	- od. ZP537F	133, 147	225/55, 225/60, 235/55, 245/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	133, 147	225/55, 225/60, 235/55, 245/50		Plug-in-Hybrid
	B39	45	ZP538	133, 147	225/55, 225/60, 235/55, 245/50		Plug-in-Hybrid
	AC-MB6	42	ZP538F+R	133, 147	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	133, 147	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
8 x 18	AC-521	42	ZP538F+R	133, 147	225/55, 225/60, 235/55, 245/50		+ Red.Ringe 73,1-65,1
	B37	45	ZP538	133, 147	225/55, 225/60, 235/55		Plug-in-Hybrid
	B42 / B44	42	ZP538	133, 147	225/55, 225/60, 235/55		
	AC-M10	42	ZP538F+R	133, 147	225/55, 225/60, 235/55		+ Red.Ringe 73,1-65,1
8,5 x 18	AC-521	43	ZP538F+R	133, 147	225/55, 225/60, 235/55		+ Red.Ringe 73,1-65,1
	B32	45	ZP538	133, 147	235/55		
7 x 19	RC27	38	ZP538F	133, 147	205/55, 235/50		Plug-in-Hybrid
		41	- od. ZP537F	133, 147	205/55, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 19	B32	42	ZP538F	133, 147	235/50, 245/45		Plug-in-Hybrid
	AC-521	42	ZP538F+R	133, 147	235/50, 245/45		+ Red.Ringe 73,1-65,1
	CA 26	45	ZP538	133, 147	235/50, 245/45		Plug-in-Hybrid
8 x 19	RC29	45	ZP538	133, 147	235/50, 245/45, 255/45		Plug-in-Hybrid
	Oxigin 29	45	ZP538	133, 147	235/50, 245/45, 255/45		
8,5 x 19	B32	45	ZP538	133, 147	235/50, 245/45, 255/45		Plug-in-Hybrid
8 x 20	B43	44	-	133, 147	215/45, 235/45, 245/40		Orig.-Verschr. für Alufelgen
9 x 20	CA 23	45	ZP538F	133, 147	235/45, 245/40		Plug-in-Hybrid
	Oxigin 28	40	ZP538	133, 147	235/45		

Citroen C4 (siehe Konfigurator)	ab 11.10	N	4/108	65,1	
---------------------------------	----------	---	-------	------	--

Citroen C4 Aircross	ab 2012	B	5/114,3	67,1	e2*2007/46*0117*...
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC32	38	ZP580D6F	84-110	215/65, 215/70, 225/65, 235/60, 235/65	
	RC27	36	ZP580D6F	84-110	215/70, 225/65, 235/60, 235/65	
		38	ZP580	84-110	215/70, 225/65, 235/60, 235/65	
	RC30	38	ZP580	84-110	215/70, 225/65, 235/60, 235/65	
		42	ZP580D6F	84-110	215/70, 225/65, 235/60, 235/65	
6,5 x 17	RC27	40	ZP580D6F	84-110	215/60, 215/65, 225/60, 235/55	
7 x 17	RC27	38+45	ZP580	84-110	215/60, 215/65, 225/60, 235/55	
		40	ZP580D6F	84-110	215/60, 215/65, 225/60, 235/55, 245/55	
	RC30	45	ZP580D6F	84-110	215/60, 215/65, 225/60, 235/55	
	B39	38+45	ZP580	84-110	215/60, 215/65, 225/60, 235/55	
	RC24	45	ZP580	84-110	215/60, 215/65, 225/60	
7,5 x 17	RC27	46	ZP580D6F	84-110	215/60, 215/65, 225/60	
	RC28	45	ZP580	84-110	2015/60, 215/65, 225/60	
	B36	46	ZP580	84-110	215/60, 215/65, 225/60	
	AC-518	40	ZP580D6F +R	84-110	215/60, 215/65, 225/60, 235/55	+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	84-110	215/60	
7 x 18	RC27	38	ZP580D6F	84-110	225/55	
	RC32	38	ZP580D6F	84-110	215/55, 215/60, 225/55, 235/50, 235/55	
	RC27	46	ZP580D6F	84-110	215/55	
7,5 x 18	RC30	45	ZP580	84-110	215/55, 225/50, 225/55	
	B32	35	ZP580	84-110	215/55, 225/50, 225/55, 235/50, 245/50	
	B39	35+45	ZP580	84-110	215/55, 225/50, 225/55	
	Oxigin 18	45	ZP580	84-110	215/55	
7,5 x 19	B32	40	ZP580	84-110	225/45, 235/45, 245/45	
		45	ZP580D6F	84-110	225/45, 235/45, 245/45	
	B39	40+45	ZP580	84-110	225/45, 235/45, 245/45	
	AC-521	45	ZP580D6F +R	84-110	225/45, 235/45, 245/45	+ Red.Ringe 73,1-67,1
	Oxigin 18	40	ZP580	84-110	225/45, 235/45, 245/45	
8 x 20	B38	45	ZP580	84-110	245/40	

weitere Dimensionen/Designs siehe Konfigurator

Citroen C4 Cactus	2014	0	4/108	65,1	e2*2007/46*0440*00
-------------------	------	---	-------	------	--------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 15	RC28	20	ZP402F	55-73	195/65, 205/60	
	RC30	20	ZP402F	55-96	195/55, 195/60, 205/55	 incl. Facelift 2018
6,5 x 16	RC34	20	- od. ZP401F	55-96	195/55, 195/60, 205/55, 215/50, 215/55	 Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!

	RC24	20	ZP402F	55-96	195/55, 195/60, 205/55		
7 x 16	RC28	18	ZP402F	55-73	195/55, 195/60		
				55-81	205/55		
7 x 17	RC34	20	- od. ZP401F	55-96	205/45, 205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
		25	- od. ZP401F	55-96	205/45, 215/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
	B39	18	ZP402F	55-81	205/50, 215/45, 225/45		
7,5 x 19	B39	18	ZP402F	55-81	215/35		

Citroen C4 NEU ab Februar 2021 B 4/108 65,1 e9*2007/46*6816*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	74, 81, 96	215/65		
	RC34	32	- od. ZP401F	74-114	195/70, 205/65, 215/65 , 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
6,5 x 17	RC34	32	- od. ZP401F	74-114	205/60, 215/55, 215/60 , 225/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
7 x 17	RC34	32	- od. ZP401F	74-114	205/60, 215/55, 215/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
6,5 x 18	Originaldim.				keine Felge geplant von Brock da zu selten		
7,5 x 18	B39	32	ZP402F	74-114	205/55		

Citroen e-C4 NEU ab Februar 2021 B 4/108 65,1 e9*2007/46*6816*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	57 (100)	215/65		
	RC34	32	- od. ZP401F	57-62	195/70, 205/65, 215/65 , 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
6,5 x 17	RC34	32	- od. ZP401F	57-62	205/60, 215/55, 215/60 , 225/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
7 x 17	RC34	32	- od. ZP401F	57-62	205/60, 215/55, 215/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP401F für € 32,00!!
6,5 x 18	Originaldim.				keine Felge geplant von Brock da zu selten		
7,5 x 18	B39	32	ZP402F	57 (100)	205/55		

C4 Picasso (siehe Konfigurator) ab 2013 3 5/108 65,1 e2*2007/46*0356*..							
--	--	--	--	--	--	--	--

C5 Aircross ab 02.2019 A 5/108 65,1 e2*2007/46*0642*0-2							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	96-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
	RC30	42	ZP538F	96-133	215/65		incl. Facelift 2022
	RC32	42	ZP538F	96-133	205/65, 215/65 , 225/60, 235/60		
	RC34	42	- od. ZP537F	96-133	205/65, 215/65 , 225/60, 235/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!!
	CA 26	42	ZP538F	96-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60		incl. Facelift 2022
	RC30	42	ZP538F	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2022
		50	ZP538F	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		
	RC34	44+50	- od. ZP537F	96-133	205/65, 215/65, 225/60, 235/60, 245/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! ET44 bei 245/55 ✖
		46	- od. ZP537F	96-133	205/65, 215/65, 225/60, 235/60, 245/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!!
	CA 26	50	ZP538F	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2022, nicht Bremse 330mm
	Pro1	45	-	96-133	205/65, 215/65, 225/60, 235/60		Orig.-Verschr.
7,5 x 17	RC24	44	ZP538F	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		Felge gibt es nur in silber!
	RC29	45	ZP538	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		
	RC34	44	-	96-133	205/65, 215/65, 225/60, 235/60		Orig.-Verschr.
		45	ZP538F	96-133	205/65, 215/65		
	B36	45	ZP538	96-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. FL2022, nicht Bremse 304 u. 330mm
7 x 18	RC27	44+48	- od. ZP537F	96-133	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
7,5 x 18	RC30	49	ZP538F	96-133	215/55, 215/60, 225/55, 235/50, 235/55		incl. FL2022, nicht Bremse 304 u. 330mm
	RC32	49	ZP538F	96-133	215/55, 215/60, 225/55, 235/50, 235/55		
	RC34	49	-	96-133	215/55, 215/60, 225/55 , 235/50, 235/55		Orig.-Verschr.
	B32	45	ZP538	96-133	215/55, 215/60, 225/55, 235/50, 235/55		incl. Facelift 2022
	B39	45	ZP538	96-133	215/55, 215/60, 225/55, 235/50, 235/55		
	AC-MB6	42	ZP538F+R	96-133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1 , incl. Facelift 2022
	AC-M10	42	ZP538F+R	96-133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1 , incl. Facelift 2022
	AC-521	42	ZP538F+R	96-133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1

8 x 18	RC29	45	ZP538	96-133	225/55		
	RC32	44	ZP538F	96-133	215/55, 225/55		
	RC34	44	ZP538F	96-133	215/55, 225/55		
	B37 / B38	45	ZP538	96-133	225/55		
	B42 / B44	42	ZP538	96-133	225/55		
	AC-M10	42	ZP538F+R	96-133	225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	AC-518	45	ZP538F+R	96-133	225/55		+ Red.Ringe 73,1-65,1
7 x 19	AC-521	43	ZP538F+R	96-133	225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	RC27	38	ZP538F	96-133	205/55, 225/50		incl. Facelift 2022
	RC34	38	-	96-133	205/55		Orig.-Verschr.
7,5 x 19	RC27	41	- od. ZP537F	96-133	205/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
	RC32	40	ZP538F	96-133	205/55, 235/45		auch für Hybrid
		46	ZP538F	96-133	205/55, 235/45, 245/45		
	B32	42	ZP538F	96-133	235/45, 245/45		
	AC-521	42	ZP538F+R	96-133	225/50, 235/45, 245/45		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
8 x 19	CA 26	45	ZP538	96-133	225/50, 235/45, 235/50, 245/45		incl. Facelift 2022
	RC29	45	ZP538	96-133	225/50, 235/45, 245/45		incl. Facelift 2022
	RC34	42	ZP538F	96-133	235/45		auch für Hybrid
	B38	45	ZP538	96-133	235/45, 245/45		incl. Facelift 2022, nicht Bremse 304 u. 330mm
	AC-518	45	ZP538F+R	96-133	235/45, 245/45		+ Red.Ringe 73,1-65,1
8,5 x 19	Oxigin 29	45	ZP538	96-133	225/50, 235/45, 245/45		incl. Facelift 2022
	B32	45	ZP538	96-133	235/45, 245/45		incl. Facelift 2022
	CA 23	45	ZP538	96-133	235/45, 245/45		incl. Facelift 2022, nicht Bremse 304 u. 330mm
8 x 20	RC36	50	- od. ZP537F	96-133	215/45, 235/40, 235/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
	B43	44	-	96-133	215/45, 235/40, 235/45, 245/40		Orig.-Verschr. für Alufelgen, incl. FL2022
8,5 x 20	B32	45	ZP538	96-133	235/40, 235/45, 245/40		
	AC-518	45	ZP538F+R	96-133	235/40, 235/45, 245/40		+ Red.Ringe 73,1-65,1
9 x 20	CA 23	45	ZP538F	96-133	235/40, 235/45		incl. Facelift 2022

C5 Aircross Hybrid NEU		ab 2020		A	5/108	65,1	e2*2007/46*0642*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 18	RC27	44+48	- od. ZP537F	133	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
7,5 x 18	B32	45	ZP538	133	215/55, 215/60, 225/55, 235/50, 235/55		incl. Facelift 2022
	B39	45	ZP538	133	215/55, 215/60, 225/55, 235/50, 235/55		
	AC-MB6	42	ZP538F+R	133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	AC-M10	42	ZP538F+R	133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	AC-521	42	ZP538F+R	133	215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
8 x 18	RC29	45	ZP538	133	225/55		
	B37	45	ZP538	133	225/55		
	B42 / B44	42	ZP538	133	225/55		
	AC-M10	42	ZP538F+R	133	225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	AC-521	43	ZP538F+R	133	225/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
7 x 19	RC27	38	ZP538F	133	205/55, 225/50		incl. Facelift 2022
	RC34	38	-	133	205/55		Orig.-Verschr.
	RC27	41	- od. ZP537F	133	205/55, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
7,5 x 19	B32	42	ZP538F	133	235/45, 245/45		
	AC-521	42	ZP538F+R	133	225/50, 235/45, 245/45		+ Red.Ringe 73,1-65,1, incl. Facelift 2022
	CA 26	45	ZP538	133	225/50, 235/45, 245/45		incl. Facelift 2022
8 x 19	RC29	45	ZP538	133	225/50, 235/45, 245/45		incl. Facelift 2022
	Oxigin 29	45	ZP538	133	225/50, 235/45, 245/45		incl. Facelift 2022
8,5 x 19	B32	45	ZP538	133	235/45, 245/45		incl. Facelift 2022
8 x 20	RC36	50	- od. ZP537F	133	215/45, 235/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!! incl. FL2022
	B43	44	-	133	215/45, 235/40, 245/40		Orig.-Verschr. für Alufelgen, incl. FL2022
8,5 x 20	B32	45	ZP538	133	235/40, 245/40		
	AC-518	45	ZP538F+R	133	235/40, 245/40		+ Red.Ringe 73,1-65,1
9 x 20	CA 23	45	ZP538F	133	235/40		incl. Facelift 2022

C5 X		ab 2022		N	5/108	65,1	e9*2018/858*11066*...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	42	- od. ZP537F	96-133	205/65, 215/65 , 225/60			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	96-133	205/65, 215/65 , 225/60			
	RC34	42	- od. ZP537F	96-133	215/65 , 225/60			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	42	ZP538F	96-133	205/65, 215/65 , 225/60			

	RC32	42	ZP538F	96-133	215/65, 225/60		
	RC34	44	- od. ZP537F	96-133	215/65, 225/60, 245/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 17	RC27	37	ZP538F	96-133	205/65		
7,5 x 18	AC-MB6	42	ZP538F+R	96-133	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	96-133	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
8 x 18	RC34	44	ZP538F	96-133	225/55		
7 x 19	RC27	41	- od. ZP537F	96-133	205/55, 215/50, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!!
		38	ZP538F	96-133	205/55, 215/50		
	RC34	38	-	96-133	205/55, 215/50		Orig.-Verschr.
7,5 x 19	RC32	40	ZP538F	96-133	205/55, 215/50, 235/45, 245/45		
8 x 19	RC34	42	ZP538F	96-133	235/45, 245/45		

C5 X Plug-in-Hybrid

ab 2022

N

5/108

65,1

e9*2018/858*11066*...

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	110, 132	205/65, 215/65 , 225/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	132	205/65, 215/65 , 225/60		
	RC34	42	-	96-133	215/65 , 225/60		Orig.-Verschr.
	CA 26	42	ZP538F	110, 132	205/65, 215/65 , 225/60		
	RC34	44	-	96-133	215/65, 225/60, 245/55		Orig.-Verschr.
7,5 x 17	RC27	37	ZP538F	110, 132	205/65		
7,5 x 18	AC-MB6	42	ZP538F+R	110, 132	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	110, 132	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
7 x 19	RC27	41	- od. ZP537F	110, 132	205/55, 215/50, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit Z537F für € 28,00!!
		38	ZP538F	110, 132	205/55, 215/50		
	RC34	38	-	132	205/55, 215/50		Orig.-Verschr.
7,5 x 19	RC32	40	ZP538F	96-133	205/55, 215/50, 235/45, 245/45		

e-Spacetourer FL

NEU i.V.

2. Quartal 2024

Dimension

Design

ET

KIT

KW

Reifendimension

Info

Jumpy III, Space Tourer

ab 2016

V

5/108

65,1

e2*2007/46*0531*..., e2*2007/46*0530*..

Sensor - Brocksens Universal

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC30	46	- od. ZP541F	70-130	215/65, 215/65C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
7 x 17	RC25T	46	- od. ZP541F	70-130	215/60+C, 225/55+C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
			- od. ZP541F	70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
			- od. ZP541F	70-130	215/60+C, 225/55, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	RC30T	46	- od. ZP541F	70-130	215/60+C, 225/55, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!! nicht Bremse 294x22mm HA
	B45	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
			- od. ZP541F	70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
	RC32	42	ZP538F	70-130	215/55, 215/60, 225/55, 225/55C, 235/50		
	RC34	42	- od. ZP537F	57-130	215/55, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!!
		44	- od. ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!!
7 x 17	AC-V51	45	-	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
				70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 17	RC34	44	- od. ZP537F	70-130	215/55, 215/60, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!!
			- od.				Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit

7,5 x 18	RC25T	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45		ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast
	B45	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast
				70-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast
	AC-V51	47	-	70-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC32	44	ZP538F	70-130	235/45, 245/45		
	RC34	44	ZP538F	57-130	235/45, 245/45		

e-Jumpy (III) NEU			2022	V	5/108	65,1	e2*2007/46*0531*11-..
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	RC34	46	- od. ZP537F	57-130	215/60, 215/60C, 225/55		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!! nicht Bremse 294x22mm HA
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	RC32	42	ZP538F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50		
	RC34	42	- od. ZP537F	57-130	215/55, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!!
		44	- od. ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00 netto!!
7,5 x 18	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC34	44	ZP538F	57-130	235/45, 245/45		

e-Jumpy / e-Space Tourer NEU			V	5/108	65,1	e2*2007/46*0531*13-...	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau

Jumper III (5/118)				Y, 250L	5/118	71,1		
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC25T	60	-	74-110	205/65C, 215/60C			Orig.-Verschr., ohne Radhausverbr. ✖
				74-132	215/65, 215/65C, 225/60, 225/60C, 225/65, 225/65C, 225/75C			Orig.-Verschr., ohne Radhausverbr. ✖
7 x 17	B45	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C			Orig.-Verschr., ohne Radhausverbr. ✖
	AC-V51	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C			Orig.-Verschr., ohne Radhausverbr. ✖
7,5 x 18	AC-V51	65	-	74-132	225/60, 235/50, 235/55, 235/60			Orig.-Verschr., ohne Radhausverbr. ✖

Jumper III (5/130)			04.02 - 06.06	Y, 250L	5/130	78,1	e3*2001/116*0234*..
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6.5 x 16	RC25T	60	-	74-130	215/75C, 225/75C, 235/65C		Orig.-Verschr., ✖

	Pro1	58	-	88-130	215/75C, 225/75C		Orig.-Verschr., Serie nur 16Zoll
7 x 17	B45	62	-	74-132	235/60C		Orig.-Verschr., nicht Bremse 300mm HA, ohne Radhausverbr. 

Jumper III (5/130) ab Modelljahr 2014 Y 5/130 78,1 e3*2001/116*0234*.., e3*2007/46*0046*..							
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC25T	60	-	74-132	215/75C, 225/75C, 235/65C		Orig.-Verschr., mit Verbreiter., ab 235/65C 
	Pro1	58	-	96-130	215/75C, 225/75C, 225/75CP, 235/65C, 235/65CP		Orig.-Verschr., ab 225/75C 

Cupra		Baujahr	Typ	LK/LZ	Nabe		
Born electric		ab 2021	K1	5/112	57,1	e9*2018/858*04001*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC32	50	-	70	215/55		Orig.-Verschr.
	RC34	50	-	70	215/55		Orig.-Verschr.
	RC30	49+51	-	70 (150)	215/55, 235/50HA		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	RC32	51	-	70	215/55		Orig.-Verschr.
	RC34	46	-	70	215/55		Orig.-Verschr.
	B32	51	-	70	215/55, 235/50HA		Orig.-Verschr.
	B39	49+51	-	70 (150)	215/55, 235/50HA		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	AC-521	50	-	70	215/55, 235/50HA		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
8 x 18	Oxigin 25	51	ZP560D	70	215/55		
	FMI08 Thoe	49	F31+R	70	215/55		+ Red.Ringe BA25=66,6-57,1
7,5 x 19	RC32	50	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	50	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
	RC32	51	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	48	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
		45,5	ZP560D	70	215/50, 225/45, 235/45		
	AC-521	50	-	70	215/50, 225/45, 235/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
8 x 19	CA 26	51	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
	RC29	49	-	70	215/50, 225/45, 235/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	RC32	50	-	70	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	49+50	-	70	225/45, 235/45		Orig.-Verschr.
	B38	50	-	70	215/50, 225/45, 235/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	B40	49+50	-	70	215/50, 225/45, 235/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	B43	49+50	-	70	215/50, 225/45, 235/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	AC-521	45	-	70 (150)	225/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	CA 19	47	ZP560D	70	225/45		
7,5 x 20	FMI08 Thoe	47	F31+R	70	225/45		+ Red.Ringe BA25=66,6-57,1
	RC36	44	-	70	215/45, 225/40		Orig.-Verschr.
	B43	44	-	70	215/45, 225/40		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
8 x 20	AC-521	44	-	70	215/45		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	RC36	50	-	70, 89	215/45, 235/40		Orig.-Verschr.
				70, 89	215/45, 235/40		Orig.-Verschr.
	B43	50	-	70	225/40		
				70, 89	215/45		
	RC36	47	-	70	225/40		Orig.-Verschr.
	B40	45	-	70 (150)	215/45, 225/40		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
	B43	45	-	70	215/45, 225/40		Orig.-Verschr., für Trommelbremse an der HA, nicht Brembo-Bremse
		47	-	70	225/40		Orig.-Verschr.
70, 89				215/45			
B43	48	ZP560D	70	215/45, 225/40, 235/40		für Trommelbremse an der HA, nicht Brembo-Bremse	
8,5 x 20	FMI08 Thoe	45	F31+R	70	215/45		+ Red.Ringe BA25=66,6-57,1
	B42	48	ZP560D	70 (150)	225/40		für Trommelbremse an der HA, nicht Brembo

Formentor VZ 4drive			ab 2021		KM	5/112	57,1	e9*2007/46*4008*00-19	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 18	RC27	40	-	180, 228	225/50, 235/45, 245/45				Orig.-Verschr., nur M+S
	B38	40	-	228	225/50, 245/45				Orig.-Verschr., nur M+S
	RC29	40	-	180, 228	225/50, 235/45, 245/45				Orig.-Verschr., nur M+S
	B36 / B37	35	ZP560D	180, 228	235/45				nur M+S
	B38	35	ZP560D	228	235/45				nur M+S
	B44	35	ZP560D	180, 228	235/45				nur M+S
	AC-M10	40	- +R	180, 228	225/50, 235/45, 245/45				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, nicht Bremse 370mm
	AC-MB6	39	- +R	180, 228	225/50, 235/45, 245/45				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	180, 228	225/50, 235/45, 245/45				+ Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
	AC-522	40	- +R	180, 228	225/50, 235/45, 245/45				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, nicht Bremse 370mm
8 x 19	AF20	40	- +R	180, 228	225/50, 235/45, 245/45				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, nicht Bremse 370mm
	B40	40	-	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr.
	B43	40	-	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr.
	B40	38	ZP560D	228	225/45M+S, 235/40M+S, 245/40				
	AC-521	35	- +R	180, 228	225/45M+S, 235/40M+S				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI07 Atena	40	- +R	180, 228	245/40				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	180, 228	225/45M+S				mit Radhausverbreiterungen
		39	ZP560D	180, 228	225/45M+S, 235/40M+S, 245/40				mit Radhausverbreiterungen
8,5 x 19	B42	35	ZP560D	180, 228	225/45M+S, 235/40M+S, 245/40				mit Radhausverbreiterungen
	B43	38	ZP568F	180, 228	225/45M+S, 235/40M+S				mit Radhausverbreiterungen
	AC-M10	40	- +R	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	AF20	40	- +R	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	CA 20	40	- +R	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen, nicht Bremse 370mm
	CA 23	40	- +R	180, 228	225/45M+S, 235/40M+S, 245/40				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	Oxigin 28	40	ZP560D	180, 228	225/45M+S, 235/40M+S, 245/40				nicht Bremse 370mm
8 x 20	RC36	38	-	180, 228	225/35, 225/40, 235/35, 245/35				Orig.-Verschr., bis 235/35 nur M+S
	B38	40	-	180, 228	225/35, 225/40, 235/35, 245/35				Orig.-Verschr., bis 235/35 nur M+S, nicht Bremse 370mm
	B40	40	-	228	225/35, 225/40, 235/35, 245/35				Orig.-Verschr., bis 235/35 nur M+S
	B38	35	ZP560D	180, 228	225/35, 225/40, 235/35				nur M+S
	B43	39	ZP560D	180, 228	225/35, 225/40, 235/35, 245/35				bis 235/35 nur M+S
8,5 x 20	RC29	38	-	180, 228	225/35, 225/40, 235/35				Orig.-Verschr., nur M+S
	B43	38	-	180, 228	225/35, 225/40, 235/35				Orig.-Verschr., nur M+S
		40	-	180, 228	225/35, 225/40, 235/35, 245/35				Orig.-Verschr., bis 235/35 nur M+S
	RC29	40	ZP560D	180, 228	225/35, 225/40, 235/35, 245/35				bis 235/35 nur M+S
	B32	40	ZP560D	180, 228	235/35M+S, 245/35				
	B42	35	ZP560D	180, 228	225/35, 225/40				nur M+S
		40	ZP560D	180, 228	225/35, 225/40, 235/35, 245/35				bis 235/35 nur M+S, nicht Bremse 370mm
	B43	40	ZP560D	180, 228	225/35, 225/40, 235/35, 245/35				bis 235/35 nur M+S
	B44	35	ZP560D	180, 228	225/35, 225/40				nur M+S
		40	ZP560D	180, 228	225/35, 225/40, 235/35, 245/35				bis 235/35 nur M+S, nicht Bremse 370mm
	AC-M10	40	- +R	180, 228	225/35, 225/40, 235/35, 245/35				Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, bis 235/35 nur M+S
	9 x 20	CA 23	38	ZP560D	180, 228	225/35, 225/40			
8,5 x 21	B43	40	-	180, 228	245/30				Orig.-Verschr.

Formentor VZ NEU		ab Facelift 2024		KM	5/112	57,1	e9*2007/46*4008*22-..., e9*2007/46*4008*24-...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 20	RC36	38	-	195	245/35		Orig.-Verschr., 2WD, nicht Bremse 374mm	
				245	245/35		Orig.-Verschr., 4WD, nicht Bremse 374mm	
9 x 20	RC36	42	-	195	245/35		Orig.-Verschr., 2WD	
				245	245/35		Orig.-Verschr., 4WD	

Formentor		ab 2021		KM	5/112	57,1	e9*2007/46*4008*00-19	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
	RC27	40	-	110	215/55, 225/55, 235/50			Orig.-Verschr., nur M+S
	RC34	40	-	110	215/55, 225/55			Orig.-Verschr.

7,5 x 17	RC29	35	ZP560D	110	215/55, 225/55		nur M+S
	B24	35	ZP560D	110	215/55, 225/55		nur M+S
	B36	35	ZP560D	110	215/55, 225/55		nur M+S
7,5 x 18	RC34	35	-	110	215/50, 225/50		Orig.-Verschr., nur M+S
	RC30	35	ZP560D	110	215/50, 225/50, 235/45, 245/45		nur M+S
	B39	35	ZP560D	110	215/50, 225/50, 235/45, 245/45		nur M+S
8 x 18	RC27	40	-	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	RC32	40	-	110-228	215/50M+S, 225/50, 245/45, 255/45		Orig.-Verschr.
	RC34	40	-	110-228	215/50M+S, 225/50, 245/45, 255/45		Orig.-Verschr.
	B38	40	-	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	RC29	40	-	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	B36 / B37	35	ZP560D	110, 140	235/45		nur M+S
	B44	35	ZP560D	110, 140	235/45		nur M+S
	AC-M10	40	- +R	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-MB6	39	- +R	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	110, 140	225/50M+S, 235/45M+S, 245/45		+ Red.Ringe BA25=66,6-57,1
	AC-522	40	- +R	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF20	40	- +R	110, 140	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
7,5 x 19	FMI08 Thoe	34	F31+R	110-228	215/50M+S, 225/50M+S, 245/45		+ Red.Ringe BA25=66,6-57,1
	B39	33	ZP560D	110	225/45		nur M+S
	CA 26	40	ZP560D	110	225/45		nur M+S
8 x 19	RC32	40	-	110-228	245/40		Orig.-Verschr.
				110-228	225/45M+S, 245/40		
	RC34	40	-	110-228	245/40		Orig.-Verschr.
				110-245	225/45M+S, 245/40		
	B38	40	-	110, 140	245/40		Orig.-Verschr.
	B40	40	-	110, 140	245/40		Orig.-Verschr.
	B43	40	-	110, 140	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr.
	RC34	38	ZP560D	110-228	225/45M+S, 245/40		
	AC-521	35	- +R	110, 140	225/45M+S, 235/40M+S		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 17	37	ZP560D	110-228	235/40, 245/40		
8,5 x 19	FMI07 Atena	40	- +R	110	245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	110, 140	225/45M+S		mit Radhausverbreiterungen
		39	ZP560D	110, 140	225/45M+S, 235/40M+S, 245/40		mit Radhausverbreiterungen
	B41	39	ZP560D	110-228	245/40		
	B42	35	ZP560D	110, 140	225/45M+S		mit Radhausverbreiterungen
	B43	38	ZP568F	110, 140	225/45M+S, 235/40M+S		mit Radhausverbreiterungen
	AC-M10	40	- +R	110, 140	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	AF20	40	- +R	110, 140	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	CA 20 / CA 23	40	- +R	110, 140	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	Oxigin 28	40	ZP560D	110, 140	225/45M+S, 235/40M+S, 245/40		
8 x 20	RC36	38	-	110, 140	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	B38	40	-	110, 140	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	B40	40	-	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	B38	35	ZP560D	110, 140	225/35, 225/40, 235/35		nur M+S
	B43	39	ZP560D	110, 140	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
8,5 x 20	RC29	38	-	110, 140	225/35, 225/40, 235/35		Orig.-Verschr., nur M+S
	B43	38	-	110, 140	225/35, 225/40, 235/35		Orig.-Verschr., nur M+S
		40	-	110, 140	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	RC29	40	ZP560D	110, 140	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	RC34	38	ZP568F	110-228	245/35		
	B32	40	ZP560D	110, 140	235/35M+S, 245/35		
	B42	35	ZP560D	110, 140	225/35, 225/40		nur M+S
		40	ZP560D	110, 140	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	B43	40	ZP560D	110, 140	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	B44	35	ZP560D	110, 140	225/35, 225/40		nur M+S
		40	ZP560D	110, 140	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
9 x 20	AC-M10	40	- +R	110, 140	225/35, 225/40, 235/35, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, bis 235/35 nur M+S
	CA 23	38	ZP560D	110, 140	225/35, 225/40		nur M+S
8,5 x 21	B43	40	-	110, 140	245/30		Orig.-Verschr.
	B41	40	ZP560D	110-228	245/30		

Formentor NEU		ab Facelift 2024		KM	5/112	57,1	e9*2007/46*4008*20-...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	40	-	110	245/45			Orig.-Verschr.
	AC-MB6	39	- +R	110	245/45			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 19	B43	40	-	110	245/40			Orig.-Verschr.

8 x 20	RC36	38	-	110	245/35		Orig.-Verschr.
	B43	39	ZP560D	110	245/35		
9 x 20	RC36	42	-	110	245/35		Orig.-Verschr.

Formentor e-Hybrid	ab März 2021	KM	5/112	57,1	e9*2007/46*4008*00-19
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC27	40	-	110	215/55, 225/55, 235/50		Orig.-Verschr., nur M+S
	RC29	35	ZP560D	110	215/55, 225/55		nur M+S
	B24	35	ZP560D	110	215/55, 225/55		nur M+S
	B36	35	ZP560D	110	215/55, 225/55		nur M+S
7,5 x 18	RC30	35	ZP560D	110	215/50, 225/50, 235/45, 245/45		nur M+S
	B39	35	ZP560D	110	215/50, 225/50, 235/45, 245/45		nur M+S
8 x 18	RC27	40	-	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	B38	40	-	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	RC29	40	-	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr.
	RC34	40	ZP560D	110-228	215/50M+S, 225/50M+S, 245/45, 255/45		
	B36 / B37	35	ZP560D	110	235/45		nur M+S
	B44	35	ZP560D	110	235/45		nur M+S
	AC-M10	40	- +R	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
	AC-MB6	39	- +R	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	110	225/50M+S, 235/45M+S, 245/45		+ Red.Ringe BA25=66,6-57,1
	AC-522	40	- +R	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
7,5 x 19	AF20	40	- +R	110	225/50M+S, 235/45M+S, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	B39	33	ZP560D	110	225/45		nur M+S
	CA 26	40	ZP560D	110	225/45		nur M+S, nicht Bremse 370mm
	B38	40	-	110	245/40		Orig.-Verschr.
8 x 19	B40	40	-	110	245/40		Orig.-Verschr.
	B43	40	-	110	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr.
	AC-521	35	- +R	110	225/45, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S
	FMI07 Atena	40	- +R	110	245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	110	225/45M+S		mit Radhausverbreiterungen
		39	ZP560D	110	225/45M+S, 235/40M+S, 245/40		mit Radhausverbreiterungen
	B42	35	ZP560D	110	225/45M+S		mit Radhausverbreiterungen
8,5 x 19	B43	38	ZP568F	110	225/45M+S, 235/40M+S		mit Radhausverbreiterungen
	AC-M10	40	- +R	110	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	AF20	40	- +R	110	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	CA 20	40	- +R	110	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen, nicht Bremse 370mm
	CA 23	40	- +R	110	225/45M+S, 235/40M+S, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, mit Verbreiterungen
	Oxigin 28	40	ZP560D	110	225/45M+S, 235/40M+S, 245/40		nicht Bremse 370mm
	RC36	38	-	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	B38	40	-	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
8 x 20	B40	40	-	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	B38	35	ZP560D	110	225/35, 225/40, 235/35		nur M+S
	B43	39	ZP560D	110	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	RC29	38	-	110	225/35, 225/40, 235/35		Orig.-Verschr., nur M+S
8,5 x 20	B43	38	-	110	225/35, 225/40, 235/35		Orig.-Verschr., nur M+S
		40	-	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., bis 235/35 nur M+S
	RC29	40	ZP560D	110	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	B32	40	ZP560D	110	235/35M+S, 245/35		
	B42	35	ZP560D	110	225/35, 225/40		nur M+S
		40	ZP560D	110	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	B43	40	ZP560D	110	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S
	B44	35	ZP560D	110	225/35, 225/40		nur M+S
		40	ZP560D	110	225/35, 225/40, 235/35, 245/35		bis 235/35 nur M+S, nicht Bremse 370mm
	AC-M10	40	- +R	110	225/35, 225/40, 235/35, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, bis 235/35 nur M+S
9 x 20	CA 23	38	ZP560D	110	225/35, 225/40		nur M+S
8,5 x 21	B43	40	-	110	245/30		Orig.-Verschr.

Formentor e-Hybrid NEU	ab Facelift 2024	KM	5/112	57,1	e9*2007/46*4008*21...
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
	RC27	40	-	110	245/45		Orig.-Verschr.

8 x 18	RC27	39	-	110, 130	245/45M+S		Orig.-Verschr.
	AC-MB6	39	- +R	110	245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
				110, 130	245/45M+S		
8 x 19	B43	40	-	110, 130	245/40		Orig.-Verschr.
8 x 20	RC36	38	-	110, 130	245/35		Orig.-Verschr.
	B43	39	ZP560D	110, 130	245/35		
9 x 20	RC36	42	-	110, 130	245/35		Orig.-Verschr.

Cupra Formentor VZ5	ab 2021	KM	5/112	57,1	e9*2007/46*4008*
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	RC32	40	-	287	245/40		Orig.-Verschr., nur M+S
	RC34	40	-	287	245/40		Orig.-Verschr.
	RC29	35	ZP560D	287	245/40		nur M+S
	RC34	38	ZP560D	287	245/40		nur M+S
	B38	35	ZP560D	287	245/40		nur M+S
	AC-521	35	- +R	287	245/40M+S		Orig.-Verschr. + Red.Ringe BA25= 66,6-57,1
	Oxigin 29	32	ZP560D	287	245/40		nur M+S
8,5 x 19	B32	34,5	ZP560D	287	245/40, 255/40		nur M+S
	B37	35	ZP560D	287	245/40, 255/40		nur M+S
	B44	35	ZP560D	287	245/40, 255/40		nur M+S
9 x 19	CA 24	35	ZP560D	287	245/40		nur M+S
8 x 20	B43	30	ZP560D	287	245/35		nur M+S
8,5 x 20	RC36	40	-	287	255/35		Orig.-Verschr.
	B43	40	-	287	245/35M+S, 255/35		Orig.-Verschr.
	RC29	38	-	287	245/35M+S, 255/35		Orig.-Verschr.
	B43	38	-	287	245/35M+S, 255/35		Orig.-Verschr.
	RC29	40	ZP560D	287	245/35M+S, 255/35		
	B43	40	ZP560D	287	245/35M+S, 255/35		
	AC-521	32	-	287	245/35		Orig.-Verschr., nur M+S
	CA 17	40	ZP560D	287	255/35		nicht Brembo Bremse
9 x 20	B37	37	ZP560D	287	245/35		nur M+S
	CA 23	38	ZP560D	287	245/35M+S, 255/35		
	Oxigin 28	35	ZP560D	287	245/35		nur M+S

Cupra Leon Plug-in-Hybrid	ab 2020	KL	5/112	57,1	e9*2007/46*3167*27
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC24	42	-	110	205/50M+S, 215/45M+S, 225/45		Orig.-Verschr., incl. Sportstourer
	RC34	40	ZP560D	110 (180)	225/45		nicht 4-Kolben Festsattel mit 370x32mm
7,5 x 18	B32	46	-	110 (180)	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	RC30	49	-	110 (180)	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	B32	48+49	-	110 (180)	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	B39	49	-	110 (180)	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	RC30	45	ZP560D	110 (180)	225/40		nur M+S, incl. Sportstourer
	B32 / B39	45	ZP560D	110 (180)	225/40		nur M+S, incl. Sportstourer
	AC-521	50	-	110	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer, nicht Bremse 370mm
8 x 18	RC27	46	-	110 (180)	225/40, 235/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	RC29	44+50	-	110 (180)	225/40, 235/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	B38	44+50	-	110 (180)	225/40, 235/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	RC29	45	ZP560D	110 (180)	225/40, 235/40		nur M+S, incl. Sportstourer
	B24	48	ZP560D	110 (180)	225/40, 235/40		nur M+S, incl. Sportstourer
	B42 / B44	45	ZP560D	110	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
	AC-M10	40	- +R	110	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
		45	ZP560D	110	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
	AC-521	45	- +R	110	225/40, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
	AC-522	45	-	110	225/40, 235/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
8,5 x 18	CA 20	45	ZP560D	110 (180)	225/40, 235/40		nur M+S, incl. Sportstourer
	B32	48	ZP560D	110	225/40		incl. Sportstourer
7,5 x 19	B32	43	-	110 (180)	225/35		Orig.-Verschr., nur M+S, incl. Sportstourer
	B39	43	ZP560D	110 (180)	225/35		nur M+S, incl. Sportstourer
	AC-521	50	-	110	225/35		Orig.-Verschr., nur M+S, incl. Sportstourer
	CA 26	40	ZP560D	110	225/35		incl. Sportstourer, nicht Bremse 370mm
	B40	49	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
			-	110	235/35		Orig.-Verschr.
	B43	49	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse

8 x 19				110	225/35M+S, 235/35		370mm
	FMI07 Atena	49	-	110	225/35M+S, 235/35		Orig.-Verschr.
	RC29	49	-	110 (180)	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	RC27	50	-	110 (180)	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	B38	50	-	110 (180)	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	B40	45+50	-	110 (180)	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	B43	45+47+50	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
	AC-518	47	ZP568F	110 (180)	225/35M+S, 235/35		incl. Sportstourer
	AC-521	45	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
8,5 x 19	Oxigin 29	43	ZP560D	110	225/35		incl. Sportstourer
	B36	45	ZP560D	110 (180)	225/35M+S, 235/35		incl. Sportstourer, bei 235/35 ✖
	CA 23	45	ZP560D	110	225/35		incl. Sportstourer
	Oxigin 28	45	ZP560D	110	225/35		incl. Sportstourer
8 x 20	B43	50	-	110	235/30		Orig.-Verschr., nicht Bremse 370mm
	B38	48	ZP560D	110 (180)	235/30		incl. Sportstourer
	B43	48	ZP560D	110	235/30		incl. Sportstourer, nicht Bremse 370mm

Cupra Leon		Plug-in-Hybrid NEU		ab Facelift 2024		KL	5/112	57,1	e9*2007/46*3167*28...
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 18	RC30	49	-	110	225/40			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/40M+S				
	B32	48+49	-	110	225/40			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/40M+S				
	B39	49	-	110	225/40			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/40M+S				
	B32	45	ZP560D	110	225/40			incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/40M+S				
	AC-MB6	45	- +R	110	225/40			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm	
110, 130				225/40M+S					
8 x 18	RC27	46	-	110	225/40, 235/40			Orig.-Verschr., incl. Sportstourer	
				110, 130	225/40M+S, 235/40M+S				
	B37	50	-	110	225/40, 235/40			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/40M+S, 235/40M+S				
7,5 x 19	CA 26	40	ZP560D	110	225/35			incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/35M+S				
8 x 19	RC27	50	-	110	225/35			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/35M+S, 235/35				
	B40	49+50	-	110	225/35			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/35M+S, 235/35				
	B43	45+49+50	-	110	225/35			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
				110, 130	225/35M+S, 235/35				
8 x 20	RC36	47+50	-	110, 130	235/30			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	
	B43	50	-	110, 130	235/30			Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	

Cupra Leon NEU		ab Facelift 2024		KL	5/112	57,1	e9*2007/46*3167*28...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	B32	48+49	-	110	225/40		Orig.-Verschr., incl. Sportstourer
	B39	49	-	110	225/40		Orig.-Verschr., nur M+S, incl. Sportstourer
	B32	45	ZP560D	110	225/40		incl. Sportstourer
	AC-MB6	45	- +R	110	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer
8 x 18	RC27	46	-	110	225/40, 235/40		Orig.-Verschr., nur M+S, für Mehrlenker-HA
					225/40		Orig.-Verschr., für Verbundlenker-HA
	B37	50	-	110	225/40, 235/40		Orig.-Verschr., nur M+S, incl. Sportstourer
7,5 x 19	CA 26	40	ZP560D	110	225/35M+S		incl. Sportstourer
8 x 19	RC27	50	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	B40	49+50	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
	B43	45+49	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
		50	-	110	225/35M+S, 235/35		Orig.-Verschr., incl. Sportstourer
8 x 20	RC36	47+50	-	110, 150	235/30		Orig.-Verschr., incl. Sportstourer
	B43	47+50	-	110	235/30		Orig.-Verschr., incl. Sportstourer

Cupra Leon	ab 2021	KL	5/112	57,1	e9*2007/46*3167*00-27
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
-----------	--------	----	-----	----	-----------------	--	------

Angaben sind ohne Gewähr, für den konkreten Anwendungsfall sind die jeweiligen TÜV- Gutachten maßgeblich! Die Radabdeckung und die Übereinstimmung der EU- Genehmigungsnummer mit den Fahrzeugpapieren ist in jedem Einzelfall zu prüfen!

7,5 x 18	B32	46	-	180-221	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	RC30	49	-	180-221	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	B32	48+49	-	180-221	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	B39	49	-	180-221	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	RC30	45	ZP560D	180-221	225/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
8 x 18	B32 / B39	45	ZP560D	180-221	225/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	AC-MB6	45	- +R	180-221	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	AC-521	50	-	180-221	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S		
	B37	50	-	180-221	225/40, 235/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	B38	44+50	-	180-221	225/40, 235/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	B24	48	ZP560D	180-221	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	B36 / B42	45	ZP560D	180-221	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	B44	45	ZP560D	180-221	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
7,5 x 19	AC-M10	40	- +R	180-221	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
		45	ZP560D	180-221	225/40, 235/40		
				180-228	225/40M+S, 235/40M+S		
	AC-521	45	- +R	180-221	225/40, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	AC-522	45	-	180-221	225/40, 235/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
	CA 20	45	ZP560D	180-221	225/40, 235/40		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/40M+S, 235/40M+S		
8 x 19	AC-521	50	-	180-221	225/35		Orig.-Verschr.
	CA 26	40	ZP560D	180-228	225/35M+S		
				180-221	225/35		
				180-228	225/35M+S		
8 x 19	RC34	49	-	110-228	225/35, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
	B40	49	-	180-228	225/35M+S, 235/35		
	B43	49	-	180-228	225/35M+S, 235/35		
				180-221	225/35		
	B40	50	-	180-221	225/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S, 235/35		
	B43	45+47+50	-	180-221	225/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S, 235/35		
8,5 x 19	AC-521	45	-	180-221	225/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S, 235/35		
	Oxigin 29	43	ZP560D	180-221	225/35		incl. Sportstourer
				180-228	225/35M+S		
	B36	45	ZP560D	180-221	225/35		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S		
	B44	42	ZP560D	180-221	225/35		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S		
8 x 20	CA 23	45	ZP560D	180-221	225/35		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S		
	Oxigin 28	45	ZP560D	180-221	225/35		incl. Sportstourer, nicht Bremse 370mm
				180-228	225/35M+S		
	RC36	50	-	180-228	235/30		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
8 x 20	B43	47+50	-	180-228	235/30		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
		48	ZP560D	180-228	235/30		

Cupra Leon VZ NEU		ab Facelift 2024		KL	5/112	57,1	e9*2007/46*3167*28-...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
	RC30	49	-	221, 245	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm	

7,5 x 18	B32	48+49	-	221, 245	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
	B39	49	-	221, 245	225/40		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370mm
	B32	45	ZP560D	221, 245	225/40		incl. Sportstourer, nicht Bremse 370mm
	AC-MB6	45	- +R	221, 245	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Sportstourer, nicht Bremse 370mm
8 x 18	RC27	46	-	221, 245	225/40, 235/40		Orig.-Verschr., incl. Sportstourer
	B37	50	-	221, 245	225/40, 235/40		Orig.-Verschr., incl. Sportstourer
8 x 19	RC27	50	-	221, 245	225/35, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370 u. 374mm
	B40	49+50	-	221, 245	225/35, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370 u. 374mm
	B43	45+49+50	-	221, 245	225/35, 235/35		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370 u. 374mm
8 x 20	RC36	47+50	-	221, 245	235/30		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370 u. 374mm
	B43	47+50	-	221, 245	235/30		Orig.-Verschr., incl. Sportstourer, nicht Bremse 370 u. 374mm

Tavascan NEU		im Laufe 2024		KR	5/112	57,1	e9*2018/858*11511*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	45	-	89	VA 235/55+HA 255/50		Orig.-Verschr.	
					VA+HA 255/50 od.			
	VA 235/55+HA 255/50							
	B43	45	-	89	VA 235/55+HA 255/50		Orig.-Verschr., mit 20/21 Zoll Serienbereifung	
8 x 20	RC36	38+41+45	-	89	VA 235/50+HA 255/45		Orig.-Verschr., nur M+S, mit 20/21 Zoll Serienbereifung	
	B43	41+45	-	89	VA 235/50+HA 255/45		Orig.-Verschr., nur M+S, mit 20/21 Zoll Serie	
		39	ZP560D	89	VA 235/50+HA 255/45		mit 20/21 Zoll Serienbereifung	
9 x 20	RC36	42	-	77, 89	255/45, 265/45		Orig.-Verschr., mit 20/21 Zoll Serienbereifung	
	B43	42	-	77, 89	255/45		Orig.-Verschr., mit 20/21 Zoll Serienbereifung	
8,5 x 21	B41	40	-	89	255/40		Orig.-Verschr.	

Terramar NEU		2024		KP	5/112	57,1	e9*2018/858*04014*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC34	38	-	110-195	235/55			Orig.-Verschr., nur Bremse 375x36mm VA u. 310x22mm HA
	RC27	40	-	110	235/55			Orig.-Verschr.
	RC32	40	-	110-195	235/50, 235/55, 245/50, 245/55			Orig.-Verschr., nur Bremse 375x36mm VA u. 310x22mm HA
	RC34	40	-	110-195	235/50, 235/55, 245/50, 245/55			Orig.-Verschr., nur Bremse 375x36mm VA u. 310x22mm HA
8,5 x 19	RC34	38	-	110-195	255/45			Orig.-Verschr.
	B43	38	ZP568F	110	255/45			
8 x 20	RC36	38	-	110, 150	235/45, 245/40			Orig.-Verschr.
	B43	30+39	ZP560D	110, 150	235/45, 245/40			
8,5 x 20	RC36	38	-	110, 150	255/40			Orig.-Verschr.
	B43	38	-	110, 150	255/40			Orig.-Verschr.
8,5 x 21	B41	40	-	110-195	245/35, 255/35			Orig.-Verschr., nicht Bremse 375x36mm

Terramar e-Hybrid NEU		2024	KP	5/112	57,1	e9*2018/858*04014*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC27	40	-	110, 130	235/55		Orig.-Verschr.
8,5 x 19	B43	38	ZP568F	110, 130	255/45		nicht Bremse 374mm
8 x 20	RC36	38	-	110, 130	235/45, 245/40		Orig.-Verschr., nicht Bremse 374mm
	B43	39	ZP560D	110, 130	235/45, 245/40		
8,5 x 20	RC36	38	-	110, 130	255/40		Orig.-Verschr.
				130	235/45M+S		
	B43	38	-	110, 130	255/40		Orig.-Verschr.
				130	235/45M+S		

Terramar VZ NEU		2024		KP	5/112	57,1	e9*2018/858*04014*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	40	-	195	235/55			Orig.-Verschr.
8,5 x 19	B43	38	ZP568F	195	255/45			nicht Bremse 374mm

8 x 20	RC36	38	-	195	235/45, 245/40		Orig.-Verschr., nur M+S, nicht Bremse 374mm
	B43	39	ZP560D	195	235/45, 245/40		nur M+S, nicht Bremse 374mm
8,5 x 20	RC36	38	-	195	235/45M+S, 255/40		Orig.-Verschr.
	B43	38	-	195	235/45, 255/40		Orig.-Verschr.

Dacia

Dacia	Baujahr	Typ	LK/LZ	Nabe		
Bigster NEU	2025	DJF	5/114,3	66,1	e19*2007/46*0026*26	
kein Sensor - indirektes RDKS						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	32	-	80, 103	205/65, 215/65 , 225/60	 Orig.-Verschr., 2WD
				96	205/65, 215/65 , 225/60	
	RC34	32	-	80-103	215/65, 225/60	 Orig.-Verschr., 2WD
				96	215/65, 225/60	
6,5 x 18	RC34	32	-	80-103	215/60	 Orig.-Verschr., 2WD
				96	215/60	

Duster II		ab Modell 2018		SR (SR*H..)	5/114,3	66,1	e2*2001/116*0323*43-..., e2*2007/46*0013*12-...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC32	50	-	66-110	215/65, 225/60, 235/60		Orig.-Verschr.	
	RC34	50	-	66-110	215/65, 225/60, 235/60		Orig.-Verschr.	
	RC24	44	ZP581	66-92	215/65, 225/60			
	RC27	44	-	66-110	215/65, 225/60		Orig.-Verschr.	
		45	ZP581	66-92	215/65, 225/60, 235/60			
		50	ZP581	66-110	215/65, 225/60, 235/60			
	RC30	45	ZP581	66-110	215/65, 225/60, 235/60			
		50	ZP581	66-110	215/65, 225/60, 235/60			
CA 20	45	ZP581	66-110	215/65, 225/60, 235/60				
6,5 x 17	RC27	47	-	66-110	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.	
		50	-	66-110	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., ET50 nur in silber erhältlich!	
7 x 17	RC27	40	-	66-110	215/55, 215/60		Orig.-Verschr.	
		45	ZP581	66-110	215/55, 215/60, 225/55			
	RC30	45	-	66-110	215/55, 215/60, 225/55		Orig.-Verschr.	
		45	ZP581	66-110	215/55, 215/60, 225/55			
	B39	45	ZP581	66-110	215/55, 215/60, 225/55			
	AC-V51	45	-	66-110	215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., ohne Radhausverbr. ab 235/50 ✖	
7,5 x 17	RC24	45	ZP581	66-92	215/55, 215/60			
		50	ZP581	66-110	215/55, 215/60, 225/55			
	RC28	45	ZP581	66-92	215/55, 215/60			
	RC29	48	ZP581	66-110	215/55, 215/60, 225/55			
	B24	48	ZP581	66-110	215/55, 215/60, 225/55			
7,5 x 18	RC30	45	ZP581	66-110	215/50, 215/55, 235/45			
		46	-	66-110	215/50, 215/55		Orig.-Verschr.	
	B32	45	ZP581	66-110	215/50, 215/55, 235/45			
	B39	45	ZP581	66-110	215/50, 215/55, 235/45			
	AC-MB6 / AC-M10	45	Artikel Nr. 98478	66-110	215/50, 215/55, 235/45		Kit mit Artikelnummer 98478, ohne Radhausverbreiterungen	
	Oxigin 25	45	ZP581	66-110	215/50, 235/45			
8 x 18	RC29	45	ZP581	66-110	225/50, 235/45, 245/45		ohne Radhausverbr. nur 235/45 auflagenfrei!	
	B38	45	ZP581	66-110	235/45			
		49	ZP581	66-92	225/50, 235/45, 245/45			
	B44	45	ZP581	66-110	225/50, 235/45, 245/45		2WD, ohne Verbreit. nur 235/45 auflagenfrei!	
				80-110	225/50, 235/45, 245/45		4WD, ohne Verbreit. nur 235/45 auflagenfrei!	
	AC-518	40	ZP590F+R	66-110	235/45		+ Red. Ringe 73,1-66,1	
AC-M10	45	ZP590F+R	66-110	225/50, 235/45, 245/45		+ Red. Ringe 73,1-66,1, mit Radhausverbreit.		
7,5 x 19	B32	40	ZP581	66-110	225/45			
	CA 26	45	ZP581	66-110	225/45, 235/45			
	Oxigin 18	40	ZP581	66-92	225/45			
	RC29	48	ZP581	66-92	225/45, 235/40, 235/45			
8 x 19	B24	50	ZP581	66-110	225/45, 235/40, 235/45, 245/40			
	B38	45	ZP581	66-92	225/45, 235/40, 235/45			
	B40	49	ZP590F	66-110	225/45, 235/40, 235/45, 245/40			
	AC-518	40	ZP590F+R	66-110	225/45, 235/40, 235/45		+ Red. Ringe 73,1-66,1, ohne Radhausverbr. ✖	
	CA 19	45	ZP581	66-110	225/45, 235/40, 235/45, 245/40		ohne Radhausverbr. ab 245/40 ✖	
	CA 24	45	ZP581	66-110	225/45			
	Oxigin 29	50	ZP581	66-110	225/45, 235/40, 235/45, 245/40			
	8,5 x 19	B32	45	ZP581	66-110	225/45		
B42		45	ZP581	66-110	225/45			
Oxigin 28		45	ZP581	66-110	225/45, 235/40, 235/45, 245/40		ohne Radhausverbr. ab 235/40 ✖	
8 x 20	RC36	50	-	66-110	225/35, 235/35, 235/40, 245/35		Orig.-Verschr.	
	B38	45	ZP581	66-110	225/35			
		50	ZP581	66-110	225/35, 235/35, 235/40, 245/35			
	B43	45	-	66-110	225/35		Orig.-Verschr., ohne Radhausverbreiterungen	
			66-110	225/35, 235/35		Orig.-Verschr., mit Radhausverbreiterungen		

Duster III NEU	2. Quartal 2024	DJF	5/114,3	66,1	e19*2007/46*0026*22...
----------------	-----------------	-----	---------	------	------------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC34	32	-	67-96	215/70		Orig.-Verschr.
				67-96	215/70, 225/65, 225/70, 235/60, 235/65		
6,5 x 17	RC27	32	-	67-103	215/65, 225/60		Orig.-Verschr., 2WD
				96	215/65, 225/60		Orig.-Verschr., 4WD
	RC34	32	-	67-96	215/65		Orig.-Verschr.
				67-103	215/60, 215/65, 225/60, 235/55		Orig.-Verschr., 2WD
6,5 x 18	RC34	32	-	96	215/60, 215/65, 225/60		Orig.-Verschr., 4WD
				67-103	215/60		Orig.-Verschr.

Dokker	ab 2013	SD	4/100	60,1	e2*2001/116*0314*55-..., e2*2007/46*0030*16-...		
--------	---------	----	-------	------	---	--	--

Sensor - Brocksens 3

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	37	ZP440F	55-85	185/65, 195/60		
		40	ZP440	55-96	185/65, 195/60, 205/55		
	RC30	37	ZP440F	55-96	185/65, 195/60		
		40	ZP440	55-96	185/65, 195/60, 205/55		
6,5 x 15	RC28	35	ZP440	89-85	185/65, 195/60		
6,5 x 16	RC24	38	ZP440	55-96	195/50, 195/55		
		37	-	55-96	185/55, 195/55		Orig.-Verschr.
		45	-	55-96	185/55, 195/55, 205/50		Orig.-Verschr.
7 x 16	RC28	38	ZP440	55-96	195/50, 195/55		
7 x 17	RC34	37	-	55-96	195/45, 205/45		Orig.-Verschr.
	B24	38	ZP440	55-85	205/45		
	B39	38	ZP440	55-96	205/45		

Dokker Stepway II	ab 2017	SD	4/100	60,1	e2*2001/116*0314*..., e2*2007/46*0030*...		
-------------------	---------	----	-------	------	---	--	--

Sensor - Brocksens 3

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC34	37	-	55-96	185/55, 195/55, 205/50, 215/50		Orig.-Verschr.
		45	-	55-96	185/55, 195/55, 205/50		Orig.-Verschr.
7 x 17	RC34	37	-	55-96	195/45, 205/45		Orig.-Verschr.

Jogger NEU	ab März 2022	DJF	4/100	60,1	e19*2007/46*0026*..		
---------------------------	--------------	-----	-------	------	---------------------	--	--

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC34	45	-	67-81	205/60, 215/55, 225/55		Orig.-Verschr.
		37	-	81	205/60, 215/55		Orig.-Verschr.
	RC30	37	-	67-81	205/55, 205/60		Orig.-Verschr.
		38	ZP440	67-81	205/55, 205/60		
7 x 16	RC28	38	ZP440	67-81	205/55, 205/60		
7 x 17	RC34	37	-	67-81	205/55		Orig.-Verschr.
	B24	45	ZP440	67-81	205/50, 205/55, 215/50, 225/45		

Lodgy (siehe Konfigurator)	ab 2012	SD	4/100	60,1	e2*2001/116*0314*49-...		
---	---------	----	-------	------	-------------------------	--	--

Lodgy Stepway II (siehe Konfigurator)	ab 2017	SD	4/100	60,1	e2*2001/116*0314*...		
--	---------	----	-------	------	----------------------	--	--

Logan MCV II (siehe Konfigurator)	ab 2013	SD/SR	4/100	60,1	e2*2001/116*0314*64-... e2*2001/116*0323*31-...		
--	---------	-------	-------	------	---	--	--

Logan MCV II Stepway	2017	SD (7SD../SD*7..)	4/100	60,1	e2*2001/116*0314*82-...		
----------------------	------	-------------------	-------	------	-------------------------	--	--

Sensor - Brocksens 3

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC24	38	ZP440	66, 70	205/55		
	RC30	38	ZP440	66-74	205/55		
	RC34	37	-	66-74	185/55, 185/60, 195/55, 205/50, 215/50		Orig.-Verschr.
		45	-	66-74	185/55, 185/60, 195/55		Orig.-Verschr.
7 x 16	RC28	38	ZP440	66-74	205/55		
	B24	38	ZP440	66, 70	205/55		
7 x 17	RC34	37	ZP440F	66-74	195/45, 195/50, 205/45		
	B24	38	ZP440	66-74	205/45, 205/50, 215/45, 225/45HA		
	B39	38	ZP440	66, 70	205/45, 205/50, 215/45, 225/45HA		

Sandero II (siehe Konfigurator)	ab 2013	5SD/ 5SR	4/100	60,1	e2*2001/116*0314*58-... e2*2001/116*0323*29-... e2*2007/46*0030*20-...		
--	---------	----------	-------	------	--	--	--

Sandero Stepway II (siehe Konfigurator)	ab 2013	5SD/ 5SR	4/100	60,1	e2*2001/116*0314*58-..., e2*2001/116*0323*29-...		
--	---------	----------	-------	------	--	--	--

Sandero III NEU	ab Jänner 2021	DJF	4/100	60,1	e19*2007/46*0026*..		
--------------------------------	----------------	-----	-------	------	---------------------	--	--

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
	RC24	37	ZP440F	49-74	185/60, 185/65, 195/60		

6 x 15	RC30	37	ZP440F	49-74	185/60, 185/65, 195/60		
		40	ZP440	49-74	185/60, 185/65, 195/60, 205/55, 205/60		
6,5 x 16	RC34	45	-	49-67	195/55		Orig.-Verschr.
	RC30	37	-	49-74	185/55, 195/50, 195/55		Orig.-Verschr.
		38	ZP440	49-74	185/55, 195/50, 195/55		
7 x 17	B24	45	ZP440	49-74	195/45, 205/45, 215/40, 215/45		
	B39	44	ZP440	49-74	195/45, 205/45, 215/40, 215/45		
Sandero Stepway III NEU ab Jänner 2021 DJF 4/100 60,1 e19*2007/46*0026*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC34	45	-	67-81	205/60, 215/55, 225/55		Orig.-Verschr.
		37	-	67-81	205/60		Orig.-Verschr.
7 x 17	B24	45	ZP440	67-81	205/50, 205/55, 225/45		
Spring NEU im Laufe 2022 DBG 4/100 60,1 e9*2018/858*11001*..							
Sensor - Brocksens 3							
6 x 15	RC24	37	ZP440F	19 (18,6)	165/60, 165/65		max. Leistung 33kW

Fiat	Baujahr	Typ	LK/LZ	Nabe			
124 Spider (siehe Konfigurator)	ab 07.16	NF	4/100	54,1	e11*2007/46*3320*..., e5*2007/46*1036*..., e3*2007/46*0474*..		
124 Spider Abarth (siehe Konfigurator)	ab 2016	NF, NFM	4/100	54,1	e11*2007/46*3320*..., e5*2007/46*1036*..., e3*2007/46*0474*..		
Fiat 500/-C	ab 07.07	312	4/98	58,1	e3*2001/116*0261*..., e3*2007/46*0064*..., e3*2007/46*0071*...		
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC30	35	ZP404F	44-77	185/55		
					185/55, 195/50		
	RC24	40	ZP404F	73,5-77	185/55		nur innenbelüftete Bremse
		35	ZP402F	44-74	175/60, 195/45		
				44-77	185/55, 195/50		
				77	195/45		
6,5 x 16	RC30	35	ZP404F	44-77	195/45, 205/45		Orig.-Verschr., auch Hybrid, vor Montage eventuelle Zentrierstifte entfernen!
	RC34	35	-	44-77	185/50, 195/40, 195/45, 205/45		
7 x 16	B24	35	ZP404F	44-77	195/45		
7 x 17	RC34	35	-	44-77	195/40, 205/40		Orig.-Verschr., auch Hybrid, vor Montage eventuelle Zentrierstifte entfernen!
	B24 / B39	35	ZP402F	44-77	195/40		nur innenbelüftete Bremse
Fiat 500 Abarth	ab 07.07	312	4/98	58,1	e3*2001/116*0261*..., e3*2007/46*0064*...		
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	35	ZP402F	99-118	195/45, 205/45		nicht 4-Kolben Festsattelbremse
				99-121	195/45, 205/45		
	RC34	35	-	99-121	195/45, 205/45		Orig.-Verschr.
7 x 16	B24	35	ZP402F	99-121	195/45		nicht 4-Kolben Festsattelbremse
7 x 17	RC34	35	-	99-132	195/40, 205/40		Orig.-Verschr., auch Hybrid, vor Montage eventuelle Zentrierstifte entfernen!
	B24	35	ZP402F	99-121	195/40, 205/40		nicht 4-Kolben Festsattelbremse
	B39	35	ZP402F	99-121	195/40, 205/40		nicht 4-Kolben Festsattelbremse
Fiat 500 L VAN	ab 2017	199	5/98	58,1	e3*2001/116*0217*33-..., e3*2001/116*0217*28-..., e3*2007/46*0010*07-...		
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC30	39	ZP538F	59-77	195/65, 205/60		auch Modell Trekking u. Living
					195/65		auch Modell Trekking u. Living
6 x 16	RC30	36,5	ZP538F	59-77	195/60+C, 205/55		Modell Trekking u. Living
6,5 x 16	RC30	39	ZP538F	59-88	195/60, 205/55, 215/55, 225/50		auch Modell Trekking u. Living
	RC32	39	ZP538F	62-88	195/55, 195/60, 205/55, 215/50, 225/50		nur Bremse 284mm
7 x 16	RC28	27	ZP538F	59-77	195/60, 205/55, 215/55, 225/50		Modell Trekking bei 225/50 u. Modell Living ab 205/55 ✖
7 x 17	RC32	41	ZP538F	62-88	205/45, 205/50, 215/45, 225/45		nur Bremse 284mm
	B39	41	ZP538F	59-77	205/45, 205/50, 215/45, 225/45		Modell Trekking u. Living
7,5 x 18	B39	35	ZP538F	59-77	205/45, 215/40, 225/35, 225/40		Modell Trekking u. Living
Fiat 500X	2015	334	5/110	65,1	e3*2007/46*0318*...		
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	40	ZP538F	70-125	215/60, 225/55		nicht Bremse 305mm, nur 2WD!!
	RC24	40	ZP538F	70-125	215/60		
				70-103	215/60, 225/55		
	RC34	40	ZP538F	70-125	215/60		i.V.
7 x 16	RC28	41	ZP538F	81-125	215/60, 225/55		
7 x 17	RC30	40	ZP538F	70-125	215/50, 215/55		Orig.-Verschr.
	RC32	40	ZP538F	70-125	215/50, 215/55, 225/50		
	RC34	40	-	70-125	215/55		
	RC27	37	ZP538F	70-125	215/50, 215/55, 225/50		
		41	ZP538F	81-125	215/50, 215/55, 225/50		nicht Bremse 280mm (innenbelüftet)
7,5 x 17	B24	38	ZP538F	70-125	215/50, 215/55, 235/45		
	AC-518	40	ZP538F	70-125	215/50, 215/55, 235/45		
7 x 18	RC27	40	ZP538F	70-125	215/45, 215/50, 225/45		2WD+4WD, bei 215/50 ✖
	RC32	40	ZP538F	70-125	215/45, 215/50, 225/45		Orig.-Verschr.
	RC34	40	-	70-125	225/45		
7,5 x 18	RC30	37	ZP538F	70-125	215/45, 215/50, 225/45, 235/45		
	B39	38	ZP538F	70-125	215/45, 215/50, 225/45, 235/45		
	B24	35	ZP538F	70-125	215/45, 225/45, 235/40, 235/45		2WD+4WD, ab 235/40 ✖

8 x 18	B38	40	ZP538F	70-125	215/45, 225/45		2WD+4WD
	AC-518	33		70-125	215/45		
		40	ZP538F	70-125	215/45, 225/45		2WD+4WD
7,5 x 19	B39	40	ZP538F	70-125	225/40		
8 x 19	RC29	34	ZP538F	70-125	225/40		
	B24	35	ZP538F	70-125	225/40, 235/35, 235/40		ab 235/35 ✖
	B43	34	ZP538F	70-125	225/40		
8 x 20	RC36	37	ZP538F	70-125	225/35		

Fiat 500e NEU		ab März 2021		FA1	4/98	58,1	e3*2018/858*00001*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC30	40	-	43 (87)	185/60, 185/65 , 195/60			Orig.-Verschr.
	RC24	35	ZP402F	43	185/60, 185/65, 195/60			
	RC30	35	ZP402F	43 (87)	185/60, 185/65, 195/60			
6 x 16	RC34	41	-	43	185/55, 195/50, 195/55 , 205/50, 215/50			Orig.-Verschr.
6,5 x 16	RC34	35	-	43	185/55, 195/50, 195/55			Orig.-Verschr.
6,5 x 17	RC34	41	-	43	205/45			Orig.-Verschr., vor Montage eventuelle Zentrierstifte entfernen
			-	43	185/50, 195/45, 205/45			Orig.-Verschr., vor Montage eventuelle Zentrierstifte entfernen
	RC35	41			205/45			i.V.
7 x 17	RC34	35	-	43	195/45, 205/45			Orig.-Verschr., vor Montage eventuelle Zentrierstifte entfernen
	B24	35	ZP402F	43	195/45			vor Montage eventuelle Zentrierstifte entfernen, mit Trommelbremse an der HA
	B39	35	ZP402F	43	195/45			vor Montage eventuelle Zentrierstifte entfernen, mit Trommelbremse an der HA

Fiat 500e Abarth ^{NEU}			mit 47kW		FA1	4/98	58,1	e3*2018/858*00001*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6 x 16	RC34	41	-			195/55		Orig.-Verschr., i.V.	
6,5 x 17	RC34	41	-	47		205/45		Orig.-Verschr.	

Fiat 600e NEU		ab 2024		FH1	4/108	65,1	e3*2018/858*00078*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	62 (115)	215/65 , 225/60		

Fiat 600 Hybrid NEU		ab 2024		FH1	4/108	65,1	e3*2018/858*00078*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	32	ZP402F	74	215/65 , 225/60		

Doblo NEU		1. Quartal 2024		E	5/108	65,1	e2*2007/46*0624*.., e2*2007/46*0625*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	Pro1	42	-	75-96	205/55, 205/60, 215/55, 215/60		Orig.-Verschr., Serienreifen bis 205/..
7 x 17	Pro1	45	-	75-96	205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr., Serienreifen bis 205/..

e-Doblo NEU i.V.		1. Quartal 2024		E	5/108	65,1	e2*2007/46*0624*18, e2*2007/46*0625*..
------------------	--	-----------------	--	---	-------	------	--

Ducato (5/118) (siehe Konfigurator)		03.02 - 06.06		230, 244	5/118	71,1	
-------------------------------------	--	---------------	--	----------	-------	------	--

Ducato (5/130) (siehe Konfigurator)		03.02 - 06.06		230, 244	5/130	78,1	
-------------------------------------	--	---------------	--	----------	-------	------	--

Ducato (5/118)		ab 2006		250, 250L	5/118	71,1	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC25T	60	-	74-109	205/65C, 215/60C		Orig.-Verschr., ohne Radhausverbr. ✖
				74-132	215/65, 215/65C, 215/75C, 225/60, 225/60C, 225/65, 225/65C, 225/75C		Orig.-Verschr., ohne Radhausverbr. ✖
7 x 17	B45	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C		Orig.-Verschr., ohne Radhausverbr. ✖
	AC-V51	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C		Orig.-Verschr., ohne Radhausverbr. ✖
7,5 x 18	AC-V51	65	-	74-132	225/60, 235/50, 235/55, 235/60		Orig.-Verschr., ohne Radhausverbr. ✖

Ducato (5/130)				ab 07.06	250, 250L	5/130	78,1	
Dimension	Design	ET	KIT	KW	Reifendimension			Info
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!								

6,5 x 16	RC25T	60	-	74-130	215/75C, 225/75C, 235/65C		Orig.-Verschr., ohne Radhausverbr. ✖
	Pro1	58	-	88-130	215/75C, 225/75C, 235/65C		Orig.-Verschr., bei 235/65C ✖
	B45	62	-	74-132	235/60C		Orig.-Verschr., nicht Bremse 300mm HA, ohne Radhausverbr. ✖

Ducato (5/130)		ab Modelljahr 2014		250	5/130	78,1	e3*2001/116*0232*... e3*2007/46*0044*... e3*2007/46*0049*..
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC25T	60	-	74-132	215/75C, 225/75C, 235/65C		Orig.-Verschr., mit Radhausverbreiterungen, ab 235/65C ✖
	Pro1	58	-	88-132	215/75C, 225/75C, 225/75CP, 235/65C, 235/65CP		Orig.-Verschr., ab 225/75C ✖

L200 / Fullback		ab 2015		KT0T		6/139,7		67,1		e1*2007/46*1398*..	
Sensor - Brocksens 4											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!											
7 x 16	RC31	38	-	113-133	215/75, 215/80, 225/75+C, 235/65, 235/70, 245/70+C, 255/65				Orig.-Verschr.		
7 x 17	RC31	38	-	113	225/65, 225/70, 235/65				Orig.-Verschr. wenn Alufelge, ohne Radhausverbr. ab 245/60 ✖		
				113-133	245/60, 245/65						
8 x 18	RC31	38	-	113	235/60				Orig.-Verschr. wenn Alufelge, ohne Radhausverbr. ✖		
				113-133	245/60						

Panda		ab 03.12		312, 312P		4/98		58,1		e3*2007/46*0064*... e3*2007/46*0071*..	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6 x 15	RC30	35	ZP404F	44-70	185/55						
					175/55, 185/50, 185/55						
	RC24	35	ZP402F	44-70	175/55, 185/50, 185/55						
6,5 x 16	RC34	35	-	51-63	195/40, 195/45						
	RC30	35	ZP402F	44-63	195/45						

Panda 4x4 (siehe Konfigurator)		ab 2012		312	4/098	58,1	e3*2007/46*0064*..., e3*2007/46*0071*...
--------------------------------	--	---------	--	-----	-------	------	--

Panda Cross		ab 2014		312	4/098	58,1	e3*2007/46*0064*...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6 x 15	RC24	35	ZP402F	59-70	175/65, 175/70			

Grande Panda NEU i.V.		ab 2025		C	4/108	65,1	e2*2018/858*00035*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
Originaldimensionen:							
7 x 16		42					
7 x 17		42					

Scudo NEU		ab 2022		V		5/108		65,1	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
7 x 16	RC30	46	- od. ZP541F	75-130	215/65C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast	
7 x 17	RC25T	46	- od. ZP541F	75-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast	
			- od. ZP541F	75-130	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast	
			RC30T	46	-		215/60C		
	B45	46	- od. ZP541F	75-130	215/60C, 225/55+C, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast	
			- od. ZP541F	75-130	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast	
			AC-V51	45	-	75-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		
-	75-130	215/60C, 225/55C				Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse			

	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr., geschl. Aufbau
7,5 x 18	RC25T	45	- od. ZP541F	75-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast, nicht für elektr. Parkbremse!
				75-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast, nicht für elektr. Parkbremse!
	B45	45	- od. ZP541F	75-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast
				75-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast
	AC-V51	47	-	75-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		

e-Scudo		NEU	ab 2022		V	5/108	65,1	e2*2007/46*0533/20-...	
kein Sensor - indirektes RDKS									
Dimension		Design		ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T		46	- od. ZP541F	57 (100)	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	RC30T		46	-					Orig.-Verschr., i.V.
	B45		46	- od. ZP541F	57 (100)	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	Pro1		45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr., geschl. Aufbau
7,5 x 18	B45		45	- od. ZP541F	57 (100)	225/50C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20		45	ZP538F	57-130	235/45, 245/45			

Talento		ab 2016		FJL, FFL		5/114,3		66,1		e2*2007/46*0496*...., e2*2007/46*0497*..	
Sensor - Brocksens 3											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
6,5 x 16	RC25T	47	-	66-107	205/65C				Orig.-Verschr., geschl. Aufbau		
				66-125	215/60C, 215/65, 215/65C				Orig.-Verschr., geschl. Aufbau		
	Pro1	45	-	66-125	205/65C, 215/60C, 215/65, 215/65C, 225/60, 225/60C				Orig.-Verschr., geschl. Aufbau		
6,5 x 17	RC27	47	-	66-125	215/60, 215/60C				Orig.-Verschr., geschl. Aufbau		
7 x 17	B45	45	-	66-125	215/60, 215/60C				Orig.-Verschr., geschl. Aufbau		
	AC-V51	45	-	66-125	215/60, 215/60C				Orig.-Verschr., geschl. Aufbau		
	Pro1	45	-	66-125	215/60, 215/60C				Orig.-Verschr., geschl. Aufbau		

Tipo		ab 07.16		356	5/98	58,1	e3*2007/46*0373*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC30	39	ZP538F	70-88	195/65, 205/60, 215/60			
6 x 16	RC30	36,5	ZP538F	70-88	195/55, 195/60, 205/55, 215/50			
6,5 x 16	RC30	39	ZP538F	70-88	195/55, 195/60, 205/55 , 215/50, 225/50			
	RC32	39	ZP538F	70-96	195/55, 195/60, 205/55 , 215/50			
7 x 17	RC32	41	ZP538F	70-96	205/45, 205/50, 215/45, 225/45			
	B39	41	ZP538F	70-88	205/45, 205/50, 215/45, 225/45			
7,5 x 18	B39	35	ZP538F	70-88	205/40, 205/45, 215/40			

Tipo Cross		ab Jänner 2021					
Dimension	Design	ET	KIT	KW	Reifendimension		Info
Kein Fahrzeuganbau vorhanden!							

Ulysse NEU		2. Quartal 2022		V	5/108	65,1	e2*2007/46*0532*18-..., e2*2007/46*0533*20-...
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC30	46	- od. ZP541F	75-130	215/65C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast
			- od. 7P541F	75-130	215/60, 215/60C , 225/55 , 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast

7 x 17	RC25T	46	- od. ZP541F	75-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast
	RC30T	46	-	75-130	215/60C		Orig.-Verschr., geschl. Aufbau
	B45	46	- od. ZP541F	75-130	215/60C, 225/55+C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast
			- od. ZP541F	75-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast
	AC-V51	45	-	75-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
			-	75-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr., geschl. Aufbau
7,5 x 18	RC25T	45	- od. ZP541F	75-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast, nicht für elektr. Parkbremse!
			- od. ZP541F	75-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast, nicht für elektrische Parkbremse!
	B45	45	- od. ZP541F	75-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast
				75-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast
	AC-V51	47	-	75-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		

e-Ulysse NEU		2. Quartal 2022		V	5/108	65,1	e2*2007/46*0532*18-...
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , geschl. Aufbau!
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , geschl. Aufbau
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , geschl. Aufbau

Fisker		Baujahr	Typ	LK/LZ	Nabe		
Ocean NEU		3. Quartal 2023	01, 01-KS	5/114,3	60,1	e9*2018/858*11450*..., e9*KS18/858*11458*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 20	B43	40	-	90, 179	255/50		Orig.-Verschr., Ausführung "S3"
8,5 x 22		40			255/45		Originaldimension

Ford

B-Max (siehe Konfigurator)	ab 2012	JK8	4/108	63,4	e9*2007/46*0092*...
-----------------------------------	----------------	------------	--------------	-------------	---------------------

Bronco NEU i.V.

Capri NEU	2025	DRP	5/112	57,1	e1*2018/858*00368*..
------------------	-------------	------------	--------------	-------------	----------------------

kein Sensor - indirektes RDKS						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 19	RC36	VA 45	-		VA 235/55+HA 255/50	 Orig.-Verschr., i.V.,
8,5 x 19		HA 40				
8 x 20	RC36	VA 45	-		VA 235/50+HA 255/45	 Orig.-Verschr., i.V., Lieferzeit ca. Mai/Juni
9 x 20		HA 35				
8 x 20	B43	VA 45	-	70-109	VA 235/50, 245/45	Orig.-Verschr.
9 x 20		HA 42			HA 255/45, 265/45, 275/40	
9 x 20	RC36	VA+HA 42	-	70-109	VA 245/45+HA 275/40	Orig.-Verschr.
8,5 x 21	B43	VA 40	-	70-109	VA 235/45, 245/40	Orig.-Verschr.
9 x 21		HA 42			HA 255/40, 265/40, 275/35	

C-Max (siehe Konfigurator)	ab 11.10	DXA	5/108	63,4	e13*2007/46*1103*...
-----------------------------------	-----------------	------------	--------------	-------------	----------------------

Grand C-Max (siehe Konfigurator)	ab 11.10	DXA	5/108	63,4	e13*2007/46*1103*...
---	-----------------	------------	--------------	-------------	----------------------

C-Max (siehe Konfigurator)	ab 2015	DXA-LPG	5/108	63,4	e13*2007/46*1288*..
-----------------------------------	----------------	----------------	--------------	-------------	---------------------

EcoSport	ab 2012	JK8	4/108	63,4	e9*2007/46*0092*00-17
-----------------	----------------	------------	--------------	-------------	-----------------------

Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	37,5	ZP422D6F	66-103	195/65	
	RC30	37,5	ZP422D6F	66-103	195/65	
	RC24	37,5	- od. ZP422D6F	66-103	195/65, 205/65, 215/60	 Orig.-Verschr. für Alufelgen
	RC30	37,5	ZP422D6F	66-103	195/65, 205/65, 215/60	
6 x 16	RC30	37,5	ZP422D6F	66-103	195/60, 205/55, 205/60, 215/55, 225/50, 225/55	
6,5 x 16	RC30	37,5	ZP422D6F	66-103	195/60, 205/55, 205/60, 215/55, 225/50, 225/55	
7 x 17	B24	35	ZP422D6F	66-103	205/50, 205/55, 215/50, 225/45	bei 205/55 ✖
	B39	38	ZP422D6F	66-103	205/50, 205/55, 215/50, 225/45, 225/50	bei 205/55 u. 225/50 ✖
7,5 x 18	B39	35	ZP422D6F	66-103	205/45, 215/45, 225/40, 225/45	bei 225/45 ✖
7,5 x 19	B39	38	ZP422D6F	66-103	215/35, 225/35	

EcoSport	ab 2017	JK8	4/108	63,4	e9*2007/46*0092*18-..
-----------------	----------------	------------	--------------	-------------	-----------------------

Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC30	37,5	ZP422D6F	73-103	205/60	
			-	73-103	205/55, 205/60, 215/55, 225/50	 Orig.-Verschr. für Alufelgen
7 x 17	RC34	37,5	ZP422D6F	70-103	205/60	
	RC34	37,5	ZP422D6F	70-103	205/50	
	B24	35	ZP422D6F	73-103	205/50, 205/55, 225/45	
	B39	38	ZP422D6F	73-103	205/50, 205/55, 225/45	
7 x 18	Originaldim.	37,5			215/45	
7,5 x 18	B39	35	ZP422D6F	73-103	205/45	

Edge (siehe Konfigurator)	ab 05/2016	SBF	5/108	63,4	e1*2007/46*1524*00-02
----------------------------------	-------------------	------------	--------------	-------------	-----------------------

Edge	ab MJ2019	SBF	5/108	63,4	e1*2007/46*1524*03-..
-------------	------------------	------------	--------------	-------------	-----------------------

Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 18	RC30	55	-	110-175	235/60, 255/55	 Orig.-Verschr. für Alufelgen
		50,5+ 52,5	-	110-175	235/60, 255/55	Orig.-Verschr. für Alufelgen
	RC32	50+50,5	-	110-175	235/60, 245/55, 255/55	Orig.-Verschr.
	RC34	50	-	110-175	235/60, 245/55, 255/55	Orig.-Verschr.
	B32	50,5+ 52,5	-	110-175	235/60, 255/55	Orig.-Verschr. für Alufelgen
	AC-521	42	AV5	132-155	235/60, 255/55	
	Oxigin 25	52,5	-	110-175	235/60, 245/55, 245/60, 255/55	
8 x 18	RC25	42,5	-	110-175	235/60	Orig.-Verschr. für Alufelgen
	RC29	45	ZP533D13	110-175	235/60, 255/55	
	RC34	42	-	110-175	235/60	Orig.-Verschr.
	B24 / B36 / B37	45	ZP533D13	110-175	235/60, 255/55	
	B42 / B44	42	ZP533D13	110-175	235/60	

	CA 26	45	ZP533D13F+R	110-175	235/60, 255/55		+ Red.Ringe 65,1-63,4
	AC-M10	42	ZP533D13F+R	110-175	235/60		+ Red.Ringe 73,1-63,4
8,5 x 18	B32	45	ZP533D13	110-175	235/60		
7,5 x 19	RC34	47,5+50	-	110-175	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
		50,5	-	110-175	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	B32	50,5	-	110-175	235/55, 255/50, 265/50		Orig.-Verschr. für Alufelgen
		55	-	110-175	235/55, 255/50		Orig.-Verschr. für Alufelgen
8 x 19	AC-521	42	AV5	110-175	235/55, 255/50		
	RC34	52,5	-	110-175	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	RC29	42,5	-	110-175	235/55		Orig.-Verschr. für Alufelgen
		45	ZP533D13	110-175	235/55, 255/50		
	RC32	45	ZP533D13F	110-175	235/50, 235/55, 245/50		
		52,5	ZP533D13F	110-175	235/50, 235/55, 245/50, 255/50		
	RC34	45	-	110-175	235/50, 235/55, 245/50		Orig.-Verschr.
	B24	45	ZP533D13	110-175	235/55, 255/50		
	B40	45+50	- od. ZP533D13CL10F	110-175	235/55, 255/50		Orig.-Verschr. für Alufelgen
		47,5	-	110-175	235/55, 255/50, 265/50		Orig.-Verschr. für Alufelgen
	B43	55	-	110-175	235/55		Orig.-Verschr. für Alufelgen
		45	ZP533D13	110-175	235/55, 245/50, 255/50		
8,5 x 19	Oxigin 29	45	ZP533D13	110-175	235/55, 255/50		
	B37	53	-	110-175	235/55		Orig.-Verschr. für Alufelgen
	B43	45	-	110-175	235/55		Orig.-Verschr. für Alufelgen
	B44	42	-	110-175	235/55		Orig.-Verschr. für Alufelgen
	Oxigin 25	45	ZP533D13	110-175	235/55, 245/50		
8 x 20	B38	45	-	110-175	245/45, 255/45		Orig.-Verschr. für Alufelgen
	B40	45+52,5	-	110-175	245/45, 255/45		Orig.-Verschr. für Alufelgen
	B43	40+45,5+48,5	-	110-175	245/45, 255/45		Orig.-Verschr. für Alufelgen
		50+50,5+52+55	-	110-175	245/45, 255/45		Orig.-Verschr. für Alufelgen
	AC-521	43	AV5	110-175	245/45, 255/45		
8,5 x 20	Originaldim.	52,5			255/45		
	RC29	45+52	-	110-175	245/45, 255/45, 265/45		Orig.-Verschr. für Alufelgen
	B32	45	ZP533D13	110-175	245/45, 255/45, 265/45		
		48	ZP533D13F	110-175	245/45, 255/45, 265/45		
	B41	45+52,5	-	110-175	235/45, 245/45, 255/45, 265/45		Orig.-Verschr., ET52,5 ist original ET
	B42 / B43	45	-	110-175	245/45, 255/45, 265/45		Orig.-Verschr. für Alufelgen
	B44	40	-	110-175	245/45, 255/45		Orig.-Verschr. für Alufelgen
9 x 20	AC-518	45	AV5	110-175	245/45, 255/45, 265/45		
	B37	48	-	110-175	245/45, 255/45, 265/40, 265/45		Orig.-Verschr. für Alufelgen
	B40	46	-	110-175	245/45, 255/45, 265/40, 265/45		Orig.-Verschr. für Alufelgen
	B43	38,5	-	110-175	245/45		Orig.-Verschr. für Alufelgen
8,5 x 21	Oxigin 18	40	ZP533D13	110-175	245/45		
		38,5	-	110-175	245/40		Orig.-Verschr. für Alufelgen
	B43	49,5	-	110-175	245/40, 255/40		Orig.-Verschr. für Alufelgen
9 x 21	Originaldim.	55			265/40		
	B32	38,5	-	110-175	245/40		Orig.-Verschr. für Alufelgen
	B43	38,5	-	110-175	245/40		Orig.-Verschr. für Alufelgen

Explorer		ab 2020		WUJ	5/114,3	70,6	e13*2007/46*2217*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 20	B41	40	-	267	255/55, 265/50, 275/50, 285/50			Orig.-Verschr.
8,5 x 21	B41	40	-	267	255/50, 265/45, 275/45			Orig.-Verschr.

Explorer NEU		August 2024		DRP	5/112	57,1	e1*2018/858*00364*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 19	RC34	VA 45	-	70-109	VA 235/55			Orig.-Verschr.
8,5 x 19		HA 40			HA 255/50			
8 x 19		VA 45	-	70-109	VA 235/55, 245/50, 255/50			Orig.-Verschr.
8,5 x 19		HA 40			HA 255/50, 265/45, 275/45			
9 x 20	RC36	VA+HA 42	-	70-109	VA 245/45+HA 275/40			Orig.-Verschr.

Kombinationen

8 x 19	RC34	VA 45	-	70-109	VA 235/55, 245/50, 255/50		Orig.-Verschr.
8,5 x 19		HA 42			HA 255/50, 265/45, 275/45		
8 x 19	RC32	VA 45	-	70-89	VA 235/55, 245/50, 255/50		Orig.-Verschr.
8,5 x 19		HA 38			HA 255/50, 265/45, 275/45		

8,5 x 20		od. 42			HA 235/50, 245/45, 275/40		
8 x 20	B43	VA 45	-	70-109	VA 235/50, 245/45		Orig.-Verschr.
9 x 20		HA 42			HA 255/45, 265/45, 275/40		
8,5 x 21	B43	VA 40	-	70-109	VA 235/45, 245/40		Orig.-Verschr.
9 x 21		HA 42			HA 255/40, 265/40, 275/35		

Fiesta VII (siehe Konfigurator)		ab MJ2013	JA8 / JR8	4/108	63,4	e9*2001/116*0069*11-..., e9*2007/46*0002*07-..., e13*2007/46*1058*09-...	

Fiesta VIII		ab 09.2017	JHH, JGH	4/108	63,4	e9*2007/46*3142*..., e9*2007/46*3159*..	
--------------------	--	-------------------	-----------------	--------------	-------------	---	--

Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	45	-	51-103	195/60, 205/55, 205/60		Orig.-Verschr. für Alufelgen
	RC30	45	ZP422D6F	51-103	195/60, 205/55, 205/60		auch Typ JGH
	RC24	47,5	- od. ZP422D6F	52-103	195/60, 205/55, 205/60		Orig.-Verschr. für Alufelgen
	RC30	47,5	ZP422D6F	51-103	195/60, 205/55, 205/60		auch Typ JGH
6,5 x 16	RC30	47,5	ZP422D6F	51-103	195/50, 195/55, 205/50		auch Typ JGH
	RC34	47,5	-	52-114	195/55		auch Typ JGH
	RC24	40	-	51-103	195/50, 195/55, 205/50		Orig.-Verschr. für Alufelgen, auch Typ JGH, ✖
7 x 17	RC34	42,5	ZP422D6F	63-114	205/45		nur Typ JHH, auch ET42,5 ist ECE
		47,5	ZP422D6F	52-114	205/45		auch Typ JGH
	B39	47,5	ZP422D6F	51-103	195/45, 205/45, 215/40, 215/45		auch Typ JGH

Fiesta ST VIII	ab 2018	JHH	4/108	63,4	e9*2007/46*3142*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	45	ZP422D6F	147	195/60, 205/55, 205/60		nur M+S
	RC30	45	ZP422D6F	147	195/60		nur M+S
	RC24	37,5	ZP422D6F	147	195/60, 205/55, 205/60		nur M+S
	RC30	37,5	ZP422D6F	147	195/60, 205/55, 205/60		nur M+S
6 x 16	RC30	37,5	ZP422D6F	147	195/50, 195/55, 205/50		nur M+S
6,5 x 16	RC24	40	ZP422D6F	147	195/50, 195/55, 205/50		nur M+S
	RC30	37,5	-	147	195/50, 195/55, 205/50		Orig.-Verschr. für Alufelgen, nur M+S
		40	ZP422D6F	147	195/50, 195/55, 205/50		nur M+S
7 x 16	B24	42	ZP422D6F	147	195/50, 195/55, 205/50, 215/45, 225/45		nur M+S
7 x 17	B39	38	ZP422D6F	147	205/45, 215/40, 215/45		nur M+S
7,5 x 17	RC28	40	ZP422D6F	147	205/45, 215/40, 215/45		nur M+S

Fiesta Active VIII	ab 2018	JHH	4/108	63,4	e9*2007/46*3142*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	45	ZP422D6F	62-103	195/60, 205/55, 205/60		nur M+S, mit Kotflügelverbreiterung
	RC30	45	ZP422D6F	62-103	195/60		nur M+S
	RC24	37,5	ZP422D6F	62-103	195/60, 205/55, 205/60		nur M+S
	RC30	37,5	ZP422D6F	62-103	195/60, 205/55, 205/60		nur M+S, mit Verbreiterung
6,5 x 16	RC24	40	-	62-103	195/50, 195/55, 205/50		Orig.-Verschr. für Alufelgen, nur M+S
	RC30	37,5	-	62-103	195/50, 195/55, 205/50		Orig.-Verschr. für Alufelgen, nur M+S
7 x 16	B24	42	ZP422D6F	62-103	195/50, 195/55, 205/50, 215/45		nur M+S, mit Verbreiterung
7 x 17	RC34	42,5	-	63-103	205/45		Orig.-Verschr., beide ET's sind ECE
		47,5	-	63-103	205/45		
	B39	38	-	62-103	205/45, 215/40, 215/45		Orig.-Verschr. für Alufelgen

Focus (siehe Konfigurator)		ab 04.11	DYB	5/108	63,4	e13*2007/46*1138*...	
-----------------------------------	--	-----------------	------------	--------------	-------------	----------------------	--

Focus ST (siehe Konfigurator)		ab 03.12	DYB	5/108	63,4	e13*2007/46*1138*...	
--------------------------------------	--	-----------------	------------	--------------	-------------	----------------------	--

Focus (siehe Konfigurator)		ab 2014	DYB-LPG	5/108	63,4	e13*2007/46*1289*..	
-----------------------------------	--	----------------	----------------	--------------	-------------	---------------------	--

Focus RS (siehe Konfigurator)		03/2016	DYB, DYB-RS	5/108	63,4	e13*2007/46*1138*..., e13*2007/46*1616*..	
--------------------------------------	--	----------------	--------------------	--------------	-------------	---	--

Focus IV	ab 2018	DEH	5/108	63,4	e13*2007/46*1911*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC24	50	-	63-134	195/60, 195/65, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr. von Alufelgen
	RC27	50	-	63-92	195/60, 195/65, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr. für Alufelgen
	RC30	50	-	63-134	195/60, 195/65, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr. für Alufelgen
	RC32	50	ZP580D6F	63-134	195/65, 205/60, 215/55, 215/60, 225/55, 235/50		
	RC34	47,5	-	63-134	195/65, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr., beide ET's sind ECE
		50	-	63-134	195/65, 205/60, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., beide ET's sind ECE
	CA 20	50	ZP580D6F	63-134	195/65, 205/60		

	Pro 1	45	-	63-134	195/65, 205/60, 215/55, 215/60		Orig.-Verschr.
7 x 17	RC27	50	-	63-134	205/50, 205/55, 215/50 , 225/50		Orig.-Verschr. für Alufelgen, Ausführung "X7"
	RC32	50	-	63-134	195/55, 205/55, 215/50 , 225/50		Orig.-Verschr., auch für Hybrid
	RC34	50	-	63-134	215/50		Orig.-Verschr., auch für Hybrid
	RC30	48,5	-	63-134	205/50, 205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen
		52,5	ZP580D6F	63-134	205/50, 205/55, 215/50, 225/50		
	RC32	45	ZP580D6F	63-134	195/55, 205/55, 215/50		
		47,5	-	63-134	195/55, 205/55, 215/50, 225/50		Orig.-Verschr., auch für Hybrid
	B39	45	-	63-134	205/50, 205/55, 215/50		Orig.-Verschr. für Alufelgen
	CA 26	50	ZP580D6F+ R	63-134	205/50, 205/55, 215/50, 225/50		+ Red.Ringe 65,1-63,4
7,5 x 17	Pro 1	45	-	63-134	205/55, 215/50		Orig.-Verschr.
	RC24	47	ZP532	63-134	205/50, 205/55, 215/50, 235/45		
		55	-	63-134	205/50, 205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr. für Alufelgen
	RC27	47	-	63-134	205/50, 205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr. für Alufelgen
		50,5+ 52,5	-	63-134	205/50, 205/55, 215/50, 215/55, 225/45, 235/45		Orig.-Verschr.
		55	-	63-134	205/50, 205/55, 215/50, 215/55, 225/45, 225/50		Orig.-Verschr.
	RC28 / RC29	45	ZP532	63-134	205/50, 205/55		
	RC32	50,5+ 52,5	-	63-134	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
		55	-	63-134	205/55, 215/50, 235/45, 245/45		Orig.-Verschr.
	RC34	50,5+ 52,5	-	63-134	205/55, 215/50, 225/50, 235/45		Orig.-Verschr.
7,5 x 18	B36	45	ZP532	63-134	205/50, 205/55		
	RC30	46+50,5	-	63-92	205/45, 215/45, 225/40, 225/45		Orig.-Verschr. für Alufelgen
	RC32	50+50,5 + 55	ZP580D6F	63-134	205/45, 205/50, 215/45, 225/45		
	RC34	50	ZP580D6F	63-134	205/45, 205/50, 215/45, 225/45		
		45	ZP532	63-134	205/45, 215/45, 225/40, 225/45		
	B32	50	-	63-134	205/45, 215/45, 225/40, 225/45		Orig.-Verschr. für Alufelgen
		45	ZP532	63-134	205/45, 215/45, 225/40, 225/45		
	B39	45	ZP532	63-134	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	63-134	205/45, 215/45		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	63-134	205/45, 215/45		Kit mit Artikelnummer 98497
	Oxigin 18	45	ZP532	63-134	205/45, 215/40, 215/45		
	Oxigin 25	52,5	-	63-134	205/45, 215/40, 215/45, 225/40, 225/45, 235/45		Orig.-Verschr.
	RC32 / RC34	55	-	63-134	205/45, 215/45, 235/40		Orig.-Verschr.
	RC29	45	ZP532	63-134	215/45, 225/40, 225/45		
	B37 / B38	45	ZP532	63-134	215/45, 225/40, 225/45		
	B42	42	ZP532	63-134	215/45		
	AC-518	45	Artikel Nr. 98497	63-134	215/45, 225/40, 225/45		Kit mit Artikelnummer 98497
		50	Artikel Nr. 98497	63-134	215/45, 225/40, 225/45, 235/40		
	CA 26	45	ZP580D6F+ R	63-134	215/45, 225/40, 225/45		+ Red.Ringe 65,1-63,4
7,5 x 19	RC32	47,5+ 50,5	-	63-134	225/35, 225/40		Orig.-Verschr.
	RC34	47,5+50	-	63-134	225/35, 225/40		Orig.-Verschr.
		50,5	-	63-134	225/35, 225/40		Orig.-Verschr.
	B32	50,5+55	-	63-134	225/35, 225/40		Orig.-Verschr.
8 x 19	CA 26	45	ZP532	63-134	225/35, 225/40		
	RC29	45	ZP532	63-134	225/35, 225/40		
	RC32 / RC34	52,5	-	63-134	225/35, 235/35		Orig.-Verschr.
	B24 / B38	45	ZP532	63-134	225/35, 225/40		
	B40	45	- od. ZP580D6F	63-134	225/35, 225/40		Orig.-Verschr. für Alufelgen
		50	-	63-134	225/35, 225/40, 235/35		Orig.-Verschr. für Alufelgen
	B43	47,5	-	63-134	225/35, 225/40		Orig.-Verschr. für Alufelgen
		55	-	63-134	225/35, 225/40, 235/35, 245/35		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	63-134	225/35, 225/40		Kit mit Artikelnummer 98497
	Oxigin 29	45	ZP532	63-134	225/35, 225/40		
9 x 19	B40	53	-	63-134	225/40		Orig.-Verschr. für Alufelgen
8 x 20	B38	45	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
	B40	52,5	-	63-134	225/30, 225/35, 245/30		auch Turnier
		45,5+50	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
	B43	48,5+50,5	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
		52+55	-	63-134	225/30, 225/35, 245/30		Orig.-Verschr. für Alufelgen

Focus Turnier IV		2018	DEH	5/108	63,4	e13*2007/46*1911*..
Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info

Angaben sind ohne Gewähr, für den konkreten Anwendungsfall sind die jeweiligen TÜV- Gutachten maßgeblich! Die Radabdeckung und die Übereinstimmung der EU- Genehmigungsnummer mit den Fahrzeugpapieren ist in jedem Einzelfall zu prüfen!

6,5 x 16	CA 20	50	ZP580D6F	63-134	195/65, 205/60		
	RC24 / RC27	50	-	63-134	195/60, 195/65, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr. für Alufelgen
	RC30	50	-	63-134	195/60, 195/65, 205/60, 215/55, 215/60, 225/55, 235/50		Orig.-Verschr. für Alufelgen
7 x 17	RC27	50	-	63-134	205/50, 205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen, Ausführung "X7"
	RC34	50	-	63-134	215/50		Orig.-Verschr., auch für Hybrid
	RC30	48,5	-	63-134	205/50, 205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen
		52,5	ZP580D6F	63-134	205/50, 205/55, 215/50, 225/50		
	B39	45	-	63-134	205/50, 205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen, bei 225/50 ✖
	CA 26	50	ZP580D6F+ R	63-134	205/50, 205/55, 215/50, 225/50		+ Red.Ringe 65,1-63,4
	Pro 1	45	-	63-134	205/55, 215/50		Orig.-Verschr.
7,5 x 17	RC24	47	ZP532	63-134	205/50, 205/55, 215/50, 235/45		
		55	-	63-134	205/50, 205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr. für Alufelgen
	RC27	47+50,5	-	63-134	205/50, 205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr. für Alufelgen
	RC28	45	ZP532	63-134	205/50, 205/55		
	RC34	50,5+ 52,5	-	63-134	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
	B24 / B36	45	ZP532	63-134	205/50, 205/55		
	AC-518	45	ZP580D6F+ R	63-134	205/50, 205/55		Kit mit Artikelnummer 98497
7,5 x 18	RC32	50	-	63-134	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	B32	45	ZP532	63-134	205/45, 215/45, 225/40, 225/45		
		50	-	63-134	205/45, 215/45, 225/40, 225/45		Orig.-Verschr. für Alufelgen
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	63-134	205/45, 215/45		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	63-134	205/45, 215/45		Kit mit Artikelnummer 98497
	Oxigin 25	52,5	-	63-134	205/45, 215/40, 215/45, 225/40, 225/45, 235/45		Orig.-Verschr.
8 x 18	RC34	55	-	63-134	205/45, 215/45, 235/40		Orig.-Verschr.
	RC29	45	ZP532	63-134	215/45, 225/40, 225/45		
	RC34	45	-	63-134	205/45, 215/45		Orig.-Verschr.
	B36	45	-	63-134	215/45, 225/40, 225/45		Orig.-Verschr. für Alufelgen
	B37 / B38	45	ZP532	63-134	215/45, 225/40, 225/45		
	B42	42	ZP532	63-134	215/45		
	AC-518	45	Artikel Nr. 98497	63-134	215/45, 225/40, 225/45		Kit mit Artikelnummer 98497
		50		63-134	215/45, 225/40, 225/45, 235/40		
	CA 26	45	ZP580D6F+ R	63-134	215/45, 225/40, 225/45		+ Red.Ringe 65,1-63,4
7,5 x 19	RC32	47,5	-	63-134	225/35, 225/40		Orig.-Verschr.
	RC34	47,5+50	-	63-134	225/35, 225/40		Orig.-Verschr.
		50,5	-	63-134	225/35, 225/40		Orig.-Verschr.
	B32	50,5+55	-	63-134	225/35, 225/40		Orig.-Verschr.
	CA 26	45	ZP532	63-134	225/35, 225/40		
8 x 19	RC29	45	ZP532	63-134	225/35, 225/40		
	B24 / B38	45	ZP532	63-134	225/35, 225/40		
	B40	45	- od. ZP580D6F	63-134	225/35, 225/40		Orig.-Verschr. für Alufelgen
		50	-	63-134	225/35, 225/40, 235/35		Orig.-Verschr. für Alufelgen
	B43	47,5	-	63-134	225/35, 225/40		Orig.-Verschr. für Alufelgen
		55	-	63-134	225/35, 225/40, 235/35, 245/35		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	63-134	225/35, 225/40		Kit mit Artikelnummer 98497
	Oxigin 29	45	ZP532	63-134	225/35, 225/40		
8,5 x 19	B37	53	-	63-134	225/35, 225/40, 235/35		Orig.-Verschr. für Alufelgen
9 x 19	B40	53	-	63-134	225/40		Orig.-Verschr. für Alufelgen
8 x 20	B38	45	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
	B40	45+52,5	ZP580D6F	63-134	225/30, 225/35, 245/30		auch Turnier, ET45 bei 245/30 ✖
	B43	45,5+50	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
		48,5+50,5	-	63-134	225/30, 225/35		Orig.-Verschr. für Alufelgen
		52+55	-	63-134	225/30, 225/35, 245/30		Orig.-Verschr. für Alufelgen

Focus Active		ab 2019		DEH	5/108	63,4	e13*2007/46*1911*03-..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC30	45	ZP580D6F	63-134	215/55, 225/50, 225/55, 235/50			Orig.-Verschr. für Alufelgen, auch Turnier
	RC32	45	ZP580D6F	63-134	215/50, 215/55, 225/50, 235/50			
	RC34	45	-	63-134	215/55			Orig.-Verschr.
	RC30	48,5	-	63-134	215/55, 225/50, 225/55, 235/50			Orig.-Verschr. für Alufelgen, auch Turnier
	B39	45	-	63-134	215/55, 225/50, 225/55, 235/50			Orig.-Verschr. für Alufelgen, auch Turnier
	Pro1	45	-	63-134	215/50, 215/55, 225/50, 235/50			Orig.-Verschr., auch Kombi
	RC24	47	ZP532	63-134	215/55, 225/50, 225/55, 235/50, 245/45			auch Turnier
		47	-	63-134	215/55, 225/50, 225/55, 235/50, 245/45			Orig.-Verschr. für Alufelgen, auch Turnier

7,5 x 17	RC28 / RC29	45	ZP532	63-134	215/55, 225/50, 225/55, 235/50, 245/45		auch Turnier
	B36	45	ZP532	63-134	215/55, 225/50, 225/55, 235/50, 245/45		auch Turnier
	AC-518	45	Artikel Nr. 98497	63-134	215/55, 225/50, 225/55, 235/50, 245/45		Kit mit Artikelnummer 98497, auch Turnier
7 x 18	RC32 / RC34	47,5	-	63-134	215/50		Orig.-Verschr., auch Hybrid
	RC32	45	ZP580D6F	63-134	215/45, 215/50, 225/45, 235/45		
		50	-	63-134	215/45, 215/50, 225/45, 235/45		Orig.-Verschr., auch Turnier
7,5 x 18	RC34	50	-	63-134	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32 / B39	45	ZP532	63-134	215/50, 225/45, 235/45, 245/45		auch Turnier
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	63-134	215/50, 225/45, 235/45, 245/45		Kit mit Artikelnummer 98497, auch Turnier
	AC-521	42	Artikel Nr. 98497	63-134	215/50, 225/45, 235/45, 245/45		Kit mit Artikelnummer 98497
8 x 18	RC25	42,5	-	63-134	215/50, 225/45, 235/45		Orig.-Verschr. für Alufelgen, auch Turnier
	RC29	45	ZP532	63-134	215/50, 225/45, 235/45, 245/40, 245/45		auch Turnier
	RC32	42+45	ZP580D6F	63-134	215/45, 225/45, 235/45, 245/40		
	RC34	45	-	63-134	215/45, 225/45, 235/45, 245/40		Orig.-Verschr.
	B36 / B38	45	ZP532	63-134	215/50, 225/45, 235/45, 245/40, 245/45		auch Turnier
	B42	42	ZP532	63-134	215/50, 225/45, 235/45		auch Turnier
	AC-518	45	Artikel Nr. 98497	63-134	215/50, 225/45, 235/45, 245/40, 245/45		Kit mit Artikelnummer 98497, auch Turnier
7,5 x 19	CA 26	45	ZP580D6F+R	63-134	215/50, 225/45, 235/45, 245/40, 245/45		+ Red.Ringe 65,1-63,4
	RC32	47,5	-	63-134	225/40		Orig.-Verschr.
	RC34	47,5+50	-	63-134	225/40		Orig.-Verschr.
	AC-521	42	Artikel Nr. 98497	63-134	225/40		Kit mit Artikelnummer 98497, auch Turnier
8 x 19	CA 26	45	ZP532	63-134	225/40		
	RC29	42,5	-	63-134	225/40, 235/40		Orig.-Verschr. für Alufelgen, auch Turnier
		45	ZP532	63-134	225/40, 235/40, 245/35, 245/40		auch Turnier
	RC32	45	-	63-134	225/40, 235/40, 245/35		Orig.-Verschr., auch Hybrid
	RC34	42+45	-	63-134	225/40, 235/40, 245/35		Orig.-Verschr., auch Kombi
	B40	45	-	63-134	225/40, 235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen, auch Turnier
	B43	47,5	-	63-134	225/40, 235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen, auch Turnier
	AC-518	45	Artikel Nr. 98497	63-134	225/40, 235/40, 245/35, 245/40		Kit mit Artikelnummer 98497, auch Turnier
8 x 20	Oxigin 29	45	ZP532	63-134	225/40, 235/40, 245/35, 245/40		auch Turnier
	B38 / B40	45	-	63-134	225/35, 235/35, 245/30, 245/35		Orig.-Verschr. für Alufelgen, auch Turnier
	B43	45,5+48,5	-	63-134	225/35, 235/35, 245/30, 245/35		Orig.-Verschr. für Alufelgen, auch Turnier

weitere Dimensionen/Designs siehe Konfigurator

Focus ST		ab 11.2019		DEH	5/108	63,4	e13*2007/46*1911*05-..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	50	-	140, 206	215/50M+S		Orig.-Verschr. für Alufelgen, Ausführung "X7"	
	RC32	50	-	140-206	215/45, 215/50, 225/45		Orig.-Verschr.	
	RC34	50	-	140-206	215/50		Orig.-Verschr.	
	RC30	45	ZP580D6F	140, 206	215/50		Orig.-Verschr. für Alufelgen, nur M+S	
		40,5+ 48,5	-	140, 206	215/50		Orig.-Verschr. für Alufelgen, nur M+S	
		52,5	ZP580D6F	140, 206	215/50		nur M+S	
	RC32	47,5	-	140-206	215/45, 215/50, 225/45		Orig.-Verschr.	
	CA 26	50	ZP580D6F+ R	140, 206	215/50		+ Red.Ringe 65,1-63,4, nur Bremse 330mm	
Pro1	45	-	140-206	215/45, 215/50, 225/45		Orig.-Verschr.		
7,5 x 17	RC24	47	ZP532	140, 206	215/50, 235/45, 245/45		nur M+S	
		47	-	140, 206	215/50, 235/45, 245/45		Orig.-Verschr. für Alufelgen, nur M+S	
	RC27	50,5	-	140, 206	215/50, 235/45, 245/45		Orig.-Versschr., nur M+S, nur Bremse 330mm	
	RC28 / RC29	45	ZP532	140, 206	215/50, 235/45, 245/45		nur M+S	
	RC34	50,5+ 52,5	-	140-206	215/50, 225/45, 235/45, 245/45		Orig.-Verschr.	
	RC32	50,5+ 52,5+55	-	140-206	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.	
	B36	45	ZP532	140, 206	215/50, 235/45, 245/45		nur M+S	
	AC-518	45	Artikel Nr. 98497	140, 206	215/50, 235/45, 245/45		Kit mit Artikelnummer 98497, nur M+S	
7,5 x 18	RC30	46	-	140, 206	215/45, 225/40		Orig.-Verschr. für Alufelgen, nur M+S	
	RC32	45+50,5	ZP580D6F	140-206	215/40, 215/45, 225/40			
		50	-	140-206	215/40, 215/45, 225/40		Orig.-Verschr.	
	RC34	50	-	140-206	215/40, 215/45, 225/40		Orig.-Verschr.	
	B32	45	ZP532	140, 206	215/45, 225/40		nur M+S	
		50	-	140, 206	215/45, 225/40		Orig.-Verschr. für Alufelgen, nur M+S	
B39	45	ZP532	140, 206	215/45, 225/40		nur M+S		

	AC-MB6 / M10	AC-	42	Artikel Nr. 98497	140, 206	215/45, 225/40		Kit mit Artikelnummer 98497, nur M+S
	AC-521		42	Artikel Nr. 98497	140, 206	215/45, 225/40		Kit mit Artikelnummer 98497
8 x 18	RC32 / RC34	55	-	140-206	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.	
	RC27	55	-	140-206	225/40, 235/40		Orig.-Verschr.	
	RC29	45	ZP532	140, 206	215/45M+S, 225/40M+S, 235/40			
	B36 / B38	45	ZP532	140, 206	215/45M+S, 225/40M+S, 235/40			
	B42	42	ZP532	140, 206	215/45, 225/40		nur M+S	
	AC-518	45	ZP580D6F+	140, 206	215/45M+S, 225/40M+S, 235/40		Kit mit Artikelnummer 98497	
		50	R	140, 206	215/45M+S, 225/40M+S, 235/40, 245/40			
	CA 26	45	ZP580D6F+ R	140, 206	215/45M+S, 225/40M+S, 235/40		+ Red.Ringe 65,1-63,4	
7,5 x 19	RC32	47,5+50,5	-	140-206	225/35		Orig.-Verschr.	
	RC34	47,5+50	-	140-206	225/35		Orig.-Verschr.	
		50,5	-	140-206	225/35		Orig.-Verschr.	
	B32	44,5+50,5+55	-	140, 206	225/35M+S		Orig.-Verschr. für Alufelgen	
	AC-521	42	Artikel Nr. 98497	140, 206	225/35M+S		Kit mit Artikelnummer 98497	
8 x 19	CA 26	45	ZP532	140, 206	225/35M+S			
	B43	55	-	140, 206	225/35M+S, 235/35		Orig.-Verschr. für Alufelgen	
	RC27	55	-	140-206	235/35		Orig.-Verschr.	
	RC29	42,5	-	140, 206	225/35M+S		Orig.-Verschr. für Alufelgen	
		45	ZP532	140, 206	225/35M+S, 235/35			
	RC32 / RC34	52,5	-	140-206	225/35, 235/35		Orig.-Verschr.	
	B40	45	-	140, 206	225/35M+S, 235/35		Orig.-Verschr. für Alufelgen	
		50	-	140, 206	225/35M+S, 235/35, 245/35		Orig.-Verschr. für Alufelgen	
	B43	47,5	-	140, 206	225/35M+S, 235/35, 245/35		Orig.-Verschr. für Alufelgen	
	AC-518	45	Artikel Nr. 98497	140, 206	225/35M+S, 235/35		Kit mit Artikelnummer 98497	

weitere Dimensionen/Designs siehe Konfigurator

Galaxy II (siehe Konfigurator)	ab 05.06	WA6	5/108	63,4	e13*2001/116*0185*00-23
--------------------------------	----------	-----	-------	------	-------------------------

Galaxy III	ab 09/2015	WA6 (MK3)	5/108	63,4	e13*2001/116*0185*24-...
------------	------------	-----------	-------	------	--------------------------

Sensor - Brocksens 4

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 17	RC27	52,5	-	88-177	235/55	 Orig.-Verschr., beide ET's original
		55	-	88-177	235/55	 Orig.-Verschr. von Alufelgen
	RC32	52,5+55	-	88-177	235/55	 Orig.-Verschr., beide ET's original
		52,5	ZP533D13F	88-177	235/55	 Orig.-Verschr.
	RC24	55	-	88-177	235/55	 Orig.-Verschr.
	RC29	45	ZP533D13	88-177	235/55, 245/50, 245/55	
	RC28	45	ZP533D13	88-177	235/55, 245/50, 245/55	
	B36	45	ZP533D13	88-177	235/55, 245/50, 245/55	
7,5 x 18	Oxigin 19	45	ZP533	88-177	235/55, 245/50, 255/50	
	RC32	55	ZP533D13F	88-177	235/50, 245/45	 Orig.-Verschr., auch e13*2007/46*2374*..
	RC30	55	-	88-177	235/50, 245/45	 Orig.-Verschr., auch e13*2007/46*2374*..
	RC32	45+50,5 + 52,5	ZP533D13F	88-177	235/50, 245/45	
		50	-	88-177	235/50, 245/45	Orig.-Verschr.
	RC34	45+50	-	88-177	235/50, 245/45	Orig.-Verschr.
	B32	50	-	88-177	235/50, 245/45, 245/50	Orig.-Verschr. für Alufelgen
	B39	45	ZP533D13	88-177	235/50, 245/45, 245/50	
	AC-MB6	42	AV5	88-177	235/50, 245/45	
	AC-521	42	AV5	88-177	235/50, 245/45	
8 x 18	Oxigin 25	52,5	-	88-177	235/50, 245/45	Orig.-Verschr.
	RC27	45	-	88-177	235/50, 245/45, 255/45	Orig.-Verschr.
		55	-	88-177	245/45	
	RC29	45	ZP533D13	88-177	235/50, 245/45, 255/45	245/45 ohne Auflagen
	RC32	45	ZP533D13F	88-177	235/50, 245/45, 255/45	
		55	ZP533D13F	88-177	245/45	
	RC34	45	-	88-177	235/50, 245/45, 255/45	Orig.-Verschr.
		55	-	88-177	245/45	Orig.-Verschr.
	B37 / B38	45	ZP533D13	88-177	235/50, 245/45, 255/45	
	AC-518	45+50	AV5	88-177	235/50, 245/45, 255/45	
	CA 26	45	ZP533D13F +R	88-177	235/50, 245/45, 255/45	+ Red.Ringe 65,1-63,4
	RC32	50,5	ZP533D13F	88-177	235/45, 245/45	
	RC34	47,5+50	ZP533D13F	88-177	235/45	
		50,5	ZP533D13F	88-177	235/45	

7,5 x 19	B32	44,5+55	-	88-177	235/45, 245/45		Orig.-Verschr.
		50,5	-	88-177	235/45, 245/45		Orig.-Verschr.
	B39	55	-	88-177	235/45, 245/45		Orig.-Verschr.
	AC-521	42	AV5	88-177	235/45, 245/45		
	CA 26	45	ZP533D13	88-177	235/45, 245/45		
8 x 19	RC27	55	-	88-177	245/40, 245/45		Orig.-Verschr.
	B43	55	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. von Alufelgen
	RC29	42,5	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
		45	ZP533D13	88-177	235/45, 245/40, 245/45		
	RC32	55	-	88-177	245/45		Orig.-Verschr., i.V.
		52,5	ZP533D13F	88-177	235/40, 235/45, 245/40		
	RC34	45+52,5	ZP533D13F	88-177	235/40, 235/45, 245/40		
	B38	45	ZP533D13	88-177	235/45, 245/40		
	B40	45+50	- od. ZP533D13F	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
	B43	42+47,5	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
	CA 19	45	OX533F-1	88-177	245/40, 245/45		
	CA 24	45	ZP533D13	88-177	245/40, 245/45		
	AC-518	45	AV5	88-177	235/45, 245/40, 245/45		
	Oxigin 29	45	ZP533D13	88-177	235/45, 245/40, 245/45		
8 x 20	B38	45	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr.
	B40	45+52,5	ZP533D13F	88-177	235/40, 245/35, 245/40		
	B43	45,5+50	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
		48,5+50,5+52+55	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
	AC-521	43	AV5	88-177	235/40, 245/35, 245/40		
8,5 x 21	B41	45	-	88-177	245/30, 255/30		Orig.-Verschr.
	B43	49,5	-	88-177	245/35		Orig.-Verschr. für Alufelgen

weitere Dimensionen/Designs siehe Konfigurator

Galaxy Hybrid		ab 2021		WAH6	5/108	63,4	e13*2007/46*2374*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC27	55	-	88-177	235/55		Orig.-Verschr. von Alufelgen
		50,5	-	88-177	235/55, 245/50, 245/55		Orig.-Verschr. von Alufelgen
	B24 / B36	45	ZP533D13	88-177	235/55, 245/50, 245/55		
7,5 x 18	B32	50	-	88-177	235/50, 245/45, 245/50		Orig.-Verschr. für Alufelgen
8 x 18	CA 26	45	ZP533D13F +R	88-177	235/50, 245/45, 255/45		+ Red.Ringe 65,1-63,4
7,5 x 19	CA 26	45	ZP533D13	88-177	235/45, 245/45		
8 x 19	B43	55	-	88-177	245/45		Orig.-Verschr. von Alufelgen
		47,5	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. von Alufelgen
	CA 24	45	ZP533D13	110-121	235/45, 245/40, 245/45		
	Oxigin 29	45	ZP533D13	88-177	235/45, 245/40, 245/45		
8,5 x 19	RC32	45	-	88-177	235/40, 245/40		Orig.-Verschr.
	B41	42	-	88-177	235/40, 245/40		Orig.-Verschr.
	B44	42	-	88-177	235/45		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP533D13F	88-177	235/45, 245/40, 245/45		
	CA 23	45	ZP533D13	88-177	235/45, 245/40, 245/45		
8 x 20	B43	45,5+48,5	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
	AC-521	43	AV5	88-177	235/40, 245/35, 245/40		
8,5 x 20	B43	45+47,5	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen

Ka Plus (siehe Konfigurator)		ab 2016		KAF	4/108	63,3	e13*2007/46*1637*01-
------------------------------	--	---------	--	-----	-------	------	----------------------

Kuga II (siehe Konfigurator)		ab Modell 2013		DM2	5/108	63,4	e13*2001/116*0109*31-...
------------------------------	--	----------------	--	-----	-------	------	--------------------------

Kuga III		NEU	2020		DFK	5/108	63,4	e13*2007/46*2188*..		
Sensor - Brocksens 4										
Dimension		Design	ET	KIT	KW	Reifendimension			Info	
7 x 17		RC27	50	-	88-140	225/65, 235/60, 235/65				Orig.-Verschr. von Alufelgen sonst ZP580D6F, nur Bremse 308mm, Ausführung "X7"
		RC30	50	ZP580D6F	88-140	225/65, 235/60, 235/65				
		RC32	50	-	88-140	225/65, 235/65, 245/60, 255/60				Orig.-Verschr., auch für Hybrid
		RC34	50	-	88-140	225/65				Orig.-Verschr., auch für Hybrid
		RC30	45+48,5	-	88-140	225/65, 235/60, 235/65, 255/55, 255/60				Orig.-Verschr. von Alufelgen
			52,5	ZP580D6F	88-140	225/65, 235/60, 235/65				
		RC32	47,5	-	88-140	225/65, 235/65, 245/60				Orig.-Verschr., auch für Hybrid
		CA 26	50	ZP580D6F+ R	88-140	225/65, 235/60, 235/65				+ Red.Ringe 65,1-63,4 , incl. Facelift 2024
		Pro1	45	-	88-140	225/65, 235/65				Orig.-Verschr., auch für Hybrid

7,5 x 17	RC24	47	ZP580D6F	88-140	225/65, 235/60, 235/65		
	RC27	50,5	ZP580D6F	88-140	225/65, 235/60, 235/65		incl. Facelift 2024
		52,5	-	88-140	225/65, 235/60, 235/65		Orig.-Verschr. von Alufelgen
	RC28 / RC29	45	ZP532	88-140	225/65, 235/60, 235/65, 255/55, 255/60		
	RC34	50,5+52,5	-	88-140	225/65, 235/60, 235/65, 245/60, 255/60		Orig.-Verschr.
	B36	45	ZP532	88-140	225/65, 235/60, 235/65, 255/55, 255/60		
7,5 x 18	CA 20	45	ZP580D6F	88-140	225/65, 235/60, 235/65, 255/55, 255/60		incl. Facelift 2024
	RC32	50	-	88-140	225/60, 235/55, 245/55		Orig.-Verschr., Ausführung "X7"
	RC34	50	-	88-140	225/60, 235/55, 245/55		Orig.-Verschr.
	B32	50	-	88-140	225/60, 235/55		Orig.-Verschr. von Alufelgen
	RC30	50,5+52,5	-	88-140	225/60, 235/55		Orig.-Verschr. von Alufelgen
	RC32	45	-	88-140	225/60, 235/55		Orig.-Verschr.
		50,5	-	88-140	225/60, 235/55, 245/55		Orig.-Verschr.
	RC34	45	-	88-140	225/60, 235/55		Orig.-Verschr.
	B32 / B39	45	ZP532	88-140	225/60, 235/55		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	88-140	225/60, 235/55		Kit mit Artikelnummer 98497
8 x 18	AC-521	42	Artikel Nr. 98497	88-140	225/60, 235/55		Kit mit Artikelnummer 98497
	Oxigin 25	52,5	-	88-140	225/60, 235/55, 235/60		Orig.-Verschr.
	RC29	45	ZP532	88-140	225/60, 235/55		
	RC32	45	-	88-140	225/60		Orig.-Verschr.
	RC34	45	-	88-140	225/60		Orig.-Verschr.
		55	-	88-140	225/60, 235/55, 245/55		Orig.-Verschr.
	B24	45	ZP532	88-140	225/60, 235/55		
	B36 / B37 / B38	45	ZP532	88-140	225/60, 235/55		
	B42 / B44	42	ZP532	88-140	225/60, 235/55		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	88-140	225/60, 235/55		Kit mit Artikelnummer 98497
8,5 x 18	AC-518	45+50	Artikel Nr. 98497	88-140	225/60, 235/55		Kit mit Artikelnummer 98497
	CA 26	45	ZP580D6F+R	88-140	225/60, 235/55		+ Red.Ringe 65,1-63,4
	B32	45	ZP532	88-140	225/60, 235/55		
7 x 19	RC34	47,5	-	88-140	225/55, 235/50, 245/50		Orig.-Verschr.
7,5 x 19	RC32	50	-	88-140	225/55, 235/50, 245/50		Orig.-Verschr.
	RC34	50	-	88-140	225/55, 235/50, 245/50		Orig.-Verschr.
	RC32	47,5	-	88-140	225/55, 235/50		Orig.-Verschr.
	RC34	47,5+50,5	-	88-140	225/55, 235/50		Orig.-Verschr.
	B32	44,5+50,5	-	88-140	225/55, 235/50, 245/50		Orig.-Verschr. für Alufelgen
		55	-	88-140	225/55		Orig.-Verschr. für Alufelgen
	AC-521	42	Artikel Nr. 98497	88-140	225/55, 235/50, 245/50		Kit mit Artikelnummer 98497
	CA 26	45	ZP532	88-140	225/55, 235/50, 245/50		incl. Facelift 2024
	RC29	45	ZP532	88-140	225/55, 235/50, 245/50 , 255/45		
	RC32 / RC34	45	-	88-140	225/55		Orig.-Verschr.
8 x 19	RC32 / RC34	52,5	-	88-140	225/55, 235/50, 245/50 , 255/45		Orig.-Verschr.
		45	ZP532	88-140	225/55, 235/50, 245/50 , 255/45		
	B38	45	ZP580D6F	88-140	225/55, 235/50, 245/50 , 255/45		
	B40	45	-	88-140	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
		50	-	88-140	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B43	47,5	-	88-140	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
		55	-	88-140	225/55		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	88-140	225/55, 235/50, 245/50, 255/45		Kit mit Artikelnummer 98497
	CA 19	45	OX532F-1	88-140	225/55, 235/50, 235/55		incl. Hybrid
	CA 24	45	ZP532	88-140	225/55, 235/50, 235/55		incl. Hybrid
8,5 x 19	Oxigin 29	45	ZP532	88-140	225/55, 235/50, 245/50 , 255/45		
	B42	42	-	88-140	225/55, 235/50		Orig.-Verschr. für Alufelgen
	B36	44	ZP532	88-140	225/55, 235/50		
	B43	45	-	88-140	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B44	42	-	88-140	225/55, 235/50		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP580D6F	88-140	225/55, 235/50, 255/45		incl. Facelift 2024
	CA 23	45	ZP532	88-140	225/55, 235/50, 255/45		
8 x 20	B43	55	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B38	45	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B40	52,5	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B43	45,5+50	-	88-140	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen
		48,5	-	88-140	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen
		50,5	-	88-140	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
		52	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	AC-521	42	Artikel Nr.	88-140	225/45, 245/45		Kit mit Artikelnummer 98497

	RC321	75	98497	88-140	235/45, 245/45		Kit mit Artikelnummer 98497
8,5 x 20	RC29	52,5	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	RC34	45	-	88-140	235/45		Orig.-Verschr.
	B32	48	-	88-140	235/45, 245/45, 255/40, 255/45		Orig.-Verschr. für Alufelgen
	B41	45	-	88-140	235/45		Orig.-Verschr.
		52,5	-	88-140	235/45, 245/45		Orig.-Verschr.
	B42	45	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B43	45	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
		47,5	-	88-140	235/45, 245/45, 255/40, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
9 x 20	B44	40	-	88-140	235/45, 245/45		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	88-140	235/45, 245/45		Kit mit Artikelnummer 98497
8,5 x 21	CA 23	45	ZP580D6F+ R	88-140	235/45, 245/45		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
	B43	49,5	-	88-140	245/40		Orig.-Verschr. für Alufelgen

Kuga III Plug-in-Hybrid							
2020				DFK	5/108	63,4	e13*2007/46*2188*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	50	-	112	225/65, 235/60, 235/65		Orig.-Verschr. für Alufelgen
	RC30	50	-	112	225/65		Orig.-Verschr. für Alufelgen
	RC34	50	ZP580D6F	112	225/65		
	RC30	45	-	112	225/65, 235/60, 235/65, 255/55, 255/60		Orig.-Verschr. für Alufelgen
		52,5	ZP580D6F	112	225/65, 235/60, 235/65		
	CA 26	50	ZP580D6F+ R	111, 112	225/65, 235/60, 235/65		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
7,5 x 17	RC24	47	ZP580D6F	112	225/65, 235/60, 235/65		
	RC27	50,5	ZP580D6F	111, 112	225/65, 235/60, 235/65		incl. Facelift 2024
		52,5	-	112	225/65, 235/60, 235/65		Orig.-Verschr. für Alufelgen
	RC28 / RC29	45	ZP532	112	225/65, 235/60, 235/65, 255/55, 255/60		
	B24 / B36	45	ZP532	112	225/65, 235/60, 235/65, 255/55, 255/60		
	CA 20	45	ZP580D6F	111, 112	225/65, 235/60, 235/65, 255/55, 255/60		incl. Facelift 2024
7,5 x 18	B32	50	-	112	225/60		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
				111, 112	225/60, 235/55		
	RC30	46	-	111, 112	225/60, 235/55		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
		50,5+ 52,5	-	112	225/60, 235/55		Orig.-Verschr. für Alufelgen
	B32 / B39	45	ZP532	112	225/60, 235/55		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	111, 112	225/60, 235/55		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	112	225/60, 235/55		Kit mit Artikelnummer 98497
	Oxigin 25	52,5	-	88-140	225/60, 235/55, 235/60		Orig.-Verschr.
	RC27	45	-	111, 112	225/60, 235/55		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
	RC29	45	ZP532	112	225/60, 235/55		
	B36	45	ZP532	112	225/60, 235/55		
	B24 / B37 / B38	45	ZP532	112	225/60, 235/55		
	B42	42	ZP532	112	225/60, 235/55		
	B44	42	ZP532	111, 112	225/60, 235/55		incl. Facelift 2024
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	111, 112	225/60, 235/55		Kit mit Artikelnummer 98497
	AC-518	45+50	Artikel Nr. 98497	112	225/60, 235/55		Kit mit Artikelnummer 98497
	CA 26	45	ZP580D6F+ R	111, 112	225/60, 235/55		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
8,5 x 18	B32	45	ZP532	112	225/60, 235/55		
7 x 19	RC34	47,5	-	112	225/55, 235/50, 245/50		Orig.-Verschr.
	RC34	50	-	112	225/55		Orig.-Verschr.
7,5 x 19	B32	44,5+ 50,5	-	112	225/55, 235/50, 245/50		Orig.-Verschr. für Alufelgen
		55	-	112	225/55		Orig.-Verschr. für Alufelgen
	AC-521	42	Artikel Nr. 98497	112	225/55, 235/50, 245/50		Kit mit Artikelnummer 98497
	CA 26	45	ZP532	111, 112	225/55, 235/50, 245/50		incl. Facelift 2024
	RC27	55	-	112	225/55		Orig.-Verschr. für Alufelgen
8 x 19	RC29	45	ZP532	112	225/55, 235/50, 245/50 ,255/45		
	B38	45	ZP532	112	225/55, 235/50, 245/50 , 255/45		
	B40	45	ZP580D6F	112	225/55, 235/50, 245/50 , 255/45		
		50	-	112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B43	47,5	-	111, 112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
		55	-	112	225/55		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	112	225/55, 235/50, 245/50, 255/45		Kit mit Artikelnummer 98497

	CA 24	45	ZP532	112	225/55, 235/50, 235/55		
	Oxigin 29	45	ZP532	112	225/55, 235/50, 245/50 , 255/45		
8,5 x 19	B32	45	ZP532	112	225/55, 235/50, 255/45		
			ZP580D6F	112	225/55, 235/50, 255/45		
	B36	44	ZP532	112	225/55, 235/50		
	B42	42	-	112	225/55, 235/50		Orig.-Verschr. für Alufelgen
	B43	45	-	112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B44	42	-	112	225/55, 235/50		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP580D6F	111, 112	225/55, 235/50, 255/45		
8 x 20	CA 23	45	ZP532	112	225/55, 235/50, 255/45		
	B43	55	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B38	45	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B40	52,5	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B43	45,5+50	-	112	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen
		48,5	-	112	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen
		50,5	-	111, 112	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
		52	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
8,5 x 20	AC-521	43	Artikel Nr. 98497	112	235/45, 245/45		Kit mit Artikelnummer 98497
	RC29	52,5	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B32	48	-	112	235/45, 245/45, 255/40, 255/45		Orig.-Verschr. für Alufelgen
	B42	45	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	B43	45	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
		47,5	-	111, 112	235/45, 245/45, 255/40, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
	B44	40	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
9 x 20	AC-518	45	Artikel Nr. 98497	112	235/45, 245/45		Kit mit Artikelnummer 98497
	CA 20	45	ZP580D6F	112	235/45, 245/45		
	CA 23	45	ZP580D6F+ R	111, 112	235/45, 245/45		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
8,5 x 21	B43	49,5	-	112	245/40		Orig.-Verschr. für Alufelgen

Kuga III Hybrid NEU DFHK 5/108 63,4 e13*2018/858*00042*..							
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	CA 26	50	ZP580D6F+ R	111, 112	225/65, 235/60, 235/65		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
7,5 x 17	RC24	47	ZP580D6F	112	225/65, 235/60, 235/65		
	RC27	50,5	ZP580D6F	111, 112	225/65, 235/60, 235/65		incl. Facelift 2024
	RC28	45	ZP532	112	225/65, 235/60, 235/65, 255/55, 255/60		
	B24 / B36	45	ZP532	112	225/65, 235/60, 235/65, 255/55, 255/60		
	CA 20	45	ZP580D6F	111, 112	225/65, 235/60, 235/65, 255/55, 255/60		incl. Facelift 2024
7,5 x 18	Oxigin 25	50	-	112	225/65, 235/60, 235/65		Orig.-Verschr.
	RC30	46	-	111, 112	225/60, 235/55		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
	B32	50	-	111, 112	225/60, 235/55		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	111, 112	225/60, 235/55		Kit mit Artikelnummer 98497
	Oxigin 25	52,5	-	112	225/60, 235/55, 235/60		Orig.-Verschr.
8 x 18	RC27	45	-	111, 112	225/60, 235/55		Orig.-Verschr. für Alufelgen, incl. Facelift 2024
	B36	45	ZP532	112	225/60, 235/55		
	B42	42	ZP532	112	225/60, 235/55		
	B44	42	ZP532	111, 112	225/60, 235/55		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	112	225/60, 235/55		Kit mit Artikelnummer 98497
7,5 x 19	CA 26	45	ZP580D6F+ R	111, 112	225/60, 235/55		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
	CA 26	45	ZP532	111, 112	225/55, 235/50, 245/50		incl. Facelift 2024
	RC27	55	-	112	225/55		Orig.-Verschr. für Alufelgen
	B43	47,5	-	111, 112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
	CA 19	45	OX532F-1	112	225/55, 235/50, 235/55		
8 x 19	CA 24	45	ZP532	112	225/55, 235/50, 235/55		
	Oxigin 29	45	ZP532	112	225/55, 235/50, 245/50 , 255/45		
8,5 x 19	B32	45	-	112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B36	44	ZP532	112	225/55, 235/50		
	B43	45	-	112	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen
	B44	42	-	112	225/55, 235/50		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP580D6F	111, 112	225/55, 235/50, 255/45		
8 x 20	CA 23	45	ZP532	112	225/55, 235/50, 255/45		
	B43	48,5+50	-	112	235/45, 245/45, 255/45		Orig.-Verschr. für Alufelgen
		52	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	AC-521	43	Artikel Nr. 98497	112	235/45, 245/45		Kit mit Artikelnummer 98497
	B42	45	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen

8,5 x 20	B43	45	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
		47,5	-	111, 112	235/45, 245/45, 255/40, 255/45		Orig.-Verschr. für Alufelgen, incl. FL2024
9 x 20	B44	40	-	112	235/45, 245/45		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP580D6F	112	235/45, 245/45		
	CA 23	45	ZP580D6F+R	111, 112	235/45, 245/45		+ Red.Ringe 65,1-63,4, incl. Facelift 2024
8,5 x 21	B43	40	ZP532	112	235/45		
		49,5	-	111, 112	245/40		Orig.-Verschr. für Alufelgen, incl. FL2024

Mondeo V /Turnier V	ab MJ2015	BA7 (MK5)	5/108	63,4	e13*2001/116*0249*26...
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	CA 20	50	ZP580D6F	85-177	215/60	 auch Turnier
	RC24	50	-	85-177	215/60, 225/55	 Orig.-Verschr. für Alufelgen, auch Turnier
	RC27	50	ZP580D6F	85-177	215/60, 225/55	
	RC30	50	ZP580D6F	85-177	215/60	
	RC32	50	-	85-177	215/60, 225/55, 225/60, 235/55	 Orig.-Verschr.
	RC34	50	-	85-177	215/60, 225/55, 225/60, 235/55	 Orig.-Verschr.
7 x 17	RC34	50	-	88-140	215/55	 Orig.-Verschr.
	RC27	50	ZP580D6F	85-177	215/50, 215/55, 225/50, 235/50	
7,5 x 17	RC27	55	-	92-177	235/50	 Orig.-Verschr., von Alufelgen sonst ZP580D6F
	RC32	55	-	85-177	215/50, 215/55, 225/50, 235/45, 235/50, 245/45	 Orig.-Verschr.
	RC24	55	-	85-177	215/55, 225/50, 235/50, 245/45	 Orig.-Verschr. für Alufelgen, auch Turnier
8 x 18	RC27	55	-	85-177	225/45, 235/45	 Orig.-Verschr.
	RC32	55	ZP580D6F	85-177	215/45, 225/45, 235/40, 235/45, 245/40	
	RC34	55	-	85-177	215/45, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr.
8 x 19	RC27	55	-	110-177	235/40	 Orig.-Verschr.
	B43	55	-	110-177	225/40, 235/40, 245/35	 Orig.-Verschr. für Alufelgen, auch Turnier

weitere Dimensionen/Designs siehe Konfigurator
--

Mondeo Hybrid (siehe Konfigurator)	ab 2015	BA7-HEV / BA7H	5/108	63,4	e13*2007/46*1485*...
------------------------------------	---------	----------------	-------	------	----------------------

Mustang (VI)	ab 2015	LAE	5/114,3	70,65	e13*2007/46*1551*00-18
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
9 x 19	B40	VA 45	-	213-338	VA 255/40+HA 275/40	 Orig.-Verschr., incl. Facelift 2018
9,5 x 19		HA 52,5				
9 x 19	RC34	45	-	213-338	255/40, 265/35	 Orig.-Verschr.
	B40	45	-	213-338	255/40, 265/40HA, 275/40HA	 Orig.-Verschr., incl. Facelift 2018
9,5 x 19	B32	45	-	213-338	255/40, 265/40HA, 275/40HA, 285/35HA	Orig.-Verschr., incl. FL2018, bei 285/35 ✖
	B40	40	-	213-338	255/40, 265/35	Orig.-Verschr., incl. Facelift 2018
	Oxigin 18	35	ZP533D13CL 10F+R	233-310	255/40, 265/40HA, 275/40HA, 285/35HA	+ Red.Ringe 72,6-70,6
9 x 20	CA 26	45	ZP533D13C L10F+R	213-338	255/35, 265/30, 265/35, 275/30HA, 275/35HA	+ Red.Ringe 72,6-70,6
	Oxigin 18	38	ZP533D13C L10F+R	213-338	255/35	+ Red.Ringe 72,6-70,6
	Oxigin 20	38	ZP533D13C L10F+R	213-338	255/35	+ Red.Ringe 72,6-70,6
	B37	43	-	213-338	255/35, 265/30, 265/35, 275/30HA, 275/35HA	Orig.-Verschr., incl. Facelift 2018
9 x 21	B32	40	-	213-338	255/30, 265/30, 275/30HA	Orig.-Verschr., incl. Facelift 2018
Kombinationen						
9 x 20	Oxigin 18	VA 38	ZP533D13CL 10F+R	233-310	VA 255/35	+ Red.Ringe 72,6-70,6
10,5 x 20		HA 47		233-310	HA 275/35	✖

Mustang GT (VII) NEU	ab MJ2024	LAE	5/114,3	70,65	e13*2007/46*1551*19...
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
9 x 19	B40	45	-	328	255/40M+S	
				328	255/40, 265/35HA, 265/40HA, 275/35HA, 275/40HA	 Orig.-Verschr., nur M+S, nur Bremse 390mm
9,5 x 19	B40	40	-	328	255/40, 265/35, 265/40, 275/40HA	Orig.-Verschr., nur Bremse 390mm
9 x 19	B40	VA 45	-	328	VA 255/40+HA 275/40	 Orig.-Verschr., nur Bremse 390mm
9,5 x 19		HA 52,5				
9 x 20	B37	43	-	325	275/35	Orig.-Verschr., nur M+S, nur Bremse 390mm
				328	255/35, 265/30, 265/35, 275/30	

Mustang Dark Horse (VII) NEU	ab MJ2024	LAE	5/114,3	70,65	e13*2007/46*1551*19...
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
9,5 x 19	B40	40	-	334	255/40M+S, 265/35, 265/40, 275/40HA	 Orig.-Verschr., nur Bremse 390mm

Mustang Mach-E			Juli 2021		LSK / LSBK		5/108		63,4		e13*2007/46*2387*... e1*2018/858*00365*..	
Sensor - Brocksens 4												
Dimension		Design		ET	KIT	KW	Reifendimension			Info		
7 x 18		RC32	47,5	-	100-130	225/60		Orig.-Verschr.				
		RC34	47,5	-	100-130	225/60		Orig.-Verschr.				
7,5 x 18		RC30	46	ZP533D13F	100	225/60, 235/55						
					100, 124	225/60, 235/55			nur M+S			
		RC32	45	-	100-130	225/60, 235/55			Orig.-Verschr.			
			50	-	100-130	225/60, 235/55, 245/55			Orig.-Verschr.			
		RC34	45	-	100-130	225/60, 235/55			Orig.-Verschr.			
			50	-	100-130	225/60, 235/55, 245/55			Orig.-Verschr.			
		AC-MB6 / AC-M10	42	AV5	100	225/60, 235/55						
					100, 124	225/60, 235/55			nur M+S			
8 x 18		AC-521	42	AV5	100	225/60, 235/55						
					100, 124	225/60, 235/55			nur M+S			
		RC27	45	ZP533D13F	100	225/60						
					100, 124	225/60			nur M+S			
7 x 19		RC32	45	-	100-130	225/60, 235/55			Orig.-Verschr.			
		AC-M10	42	ZP533D13F +R	100	225/60			+ Red.Ringe 73,1-63,4			
					100, 124	225/60M+S						
7 x 19		CA 26	45	ZP533D13F +R	100	225/60			+ Red.Ringe 65,1-63,4			
					100, 124	225/60M+S						
		RC27	47,5	-	100-140	225/55		Orig.-Verschr. für Alufelgen				
					100-140	225/55, 235/50						
7,5 x 19		RC34	47,5	-	92-154	225/55		Orig.-Verschr.				
					100-154	225/55, 235/50, 245/50		Orig.-Verschr.				
		RC32	47,5	-	92-154	225/55, 235/50, 245/50			Orig.-Verschr.			
					50	-	100-154	225/55, 235/50, 245/50			Orig.-Verschr.	
8 x 19		AC-521	42	AV5	100, 124	225/55						
		RC29	45	ZP533D13	100, 124	225/55						
8 x 19		RC32	45	-	100-154	225/55, 235/50, 255/45			Orig.-Verschr.			
					100-154	225/55, 235/50, 255/45			Orig.-Verschr.			
		B40	45	ZP533D13F	124	225/55						
		B43	47,5	-	100-140	225/55			Orig.-Verschr. für Alufelgen			
8 x 20		CA 24	45	ZP533D13	100-154	225/55						
8 x 20		Oxigin 29	45	ZP533D13	100-140	225/55						
		RC36	47,5	-	176, 200	245/45		Orig.-Verschr., nicht Bremse 385mm				
							100-140	235/45		Orig.-Verschr.		
		B40	40+48,5	-	100-140	235/45			Orig.-Verschr.			
8,5 x 20		B43	40	-	100, 124	235/45			Orig.-Verschr. für Alufelgen			
					45,5	-	100, 124	235/45, 245/45			Orig.-Verschr. für Alufelgen	
		AC-521	48,5	-	100-140	235/45			Orig.-Verschr. für Alufelgen			
		RC29	43	AV5	100, 124	235/45, 245/45						
9 x 20		RC36	45	-	92-140	235/45, 245/45			Orig.-Verschr., nicht Bremse 385mm			
		B24	45	ZP533D13	100, 124	235/45, 245/45						
		B41	45	-	92-154	235/45, 245/45			Orig.-Verschr.			
8,5 x 21		B42	45	ZP533D13F	100-140	235/45, 245/45						
9 x 20		B43	45	-	100, 124	235/45, 245/45			Orig.-Verschr.			
8,5 x 21		Oxigin 18	40	ZP533D13	100-154	235/45						
									Orig.-Verschr.			
8,5 x 21		B41	45	-	92-154	245/40						

Mustang Mach-E GT		Juli 2021		LSK		5/108		63,4		e13*2007/46*2387*..	
Sensor - Brocksens 4											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 19	RC34	47,5	-	176-200	225/55, 235/50, 245/50				Orig.-Verschr., nur M+S		
7,5 x 19	RC32	47,5	-	176-200	225/55M+S, 235/50, 245/50				Orig.-Verschr.		
	RC34	47,5	-	176-200	225/55M+S, 235/50, 245/50				Orig.-Verschr.		
8 x 19	CA 24	45	ZP533D13	200	225/55				nur M+S		
8,5 x 20	B41	45	-	176-200	235/45, 245/45				Orig.-Verschr.		
8,5 x 21	B41	45	-	176-200	245/40				Orig.-Verschr.		

Puma		Anfang 2020		J2K	5/108	63,4	e9*2007/46*3165*00-15	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	45	-	70-114	205/65, 215/60, 225/55, 225/60			Orig.-Verschr. von Alufelgen
	RC32	45	-	70-114	205/65, 215/60, 225/55, 225/60			Orig.-Verschr.
	RC34	45	-	70-114	205/65, 215/60			Orig.-Verschr., auch Hybrid
		47,5	-	70-114	205/65, 215/60, 225/55			Orig.-Verschr., auch Hybrid
		50	-	70-114	205/65, 215/60, 225/55, 235/55			Orig.-Verschr., auch Hybrid
	Pro1	45	-	70-114	205/65, 215/60			Orig.-Verschr., auch Hybrid

7 x 17	RC32	47,5	-	70-147	205/55, 205/60, 215/55		Orig.-Verschr., auch Hybrid
	RC34	47,5	-	70-147	215/55		Orig.-Verschr., auch Hybrid
	RC30	45	-	70-114	205/55, 205/60, 215/55		Orig.-Verschr. von Alufelgen
		48,5	-	70-114	205/55, 205/60, 215/55, 225/50, 225/55		Orig.-Verschr. von Alufelgen
	RC32	45	-	70-147	205/55, 205/60		Orig.-Verschr., auch Hybrid
		50	-	70-147	205/55, 205/60, 215/55, 225/55		Orig.-Verschr., auch Hybrid
	CA 26	42	ZP580D6F+ R	70-114	205/55, 205/60		+ Red.Ringe 65,1-63,4
7,5 x 17	Pro1	45	-	70-147	205/55, 205/60		Orig.-Verschr., auch Hybrid
	RC24	47	ZP580D6F	70-114	205/55, 205/60, 215/55, 235/50HA		
	RC28 / RC29	45	ZP532	70-114	205/55, 205/60, 215/55		
	RC34	45	-	70-147	205/55, 205/60, 215/55		Orig.-Verschr.
	B24	45	ZP532	70-114	205/55, 205/60, 215/55		
	B36	45	ZP532	70-114	205/55, 205/60, 215/55		
7 x 18	Oxigin 25	50	-	70-114	215/50, 215/55		Orig.-Verschr.
	RC32	47,5	-	70-114	215/50		Orig.-Verschr., auch Hybrid
7,5 x 18	RC34	47,5	-	70-114	215/50		Orig.-Verschr., auch Hybrid
	RC30	45+46	-	70-114	215/50, 225/45, 235/45		Orig.-Verschr. von Alufelgen
	RC32	45	-	70-114	205/50, 215/45, 225/45		Orig.-Verschr.
		50	-	70-147	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	45	-	70-147	205/50, 215/45, 225/45		Orig.-Verschr.
		50	-	70-147	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32	45	ZP532	70-114	215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	70-114	225/45		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	70-114	225/45		Kit mit Artikelnummer 98497
	RC32 / RC34	45	-	70-147	215/45		Orig.-Verschr.
8 x 18	B36 / B37	45	ZP532	70-114	225/45		
	AC-518	45	Artikel Nr. 98497	70-114	225/45		Kit mit Artikelnummer 98497
	CA 26	45	ZP580D6F+ R	70-114	225/45		+ Red.Ringe 65,1-63,4
	RC32	47,5	-	70-147	205/45, 225/40		Orig.-Verschr., auch Hybrid
7,5 x 19	RC34	47,5	-	70-147	225/40		Orig.-Verschr., auch Hybrid
		50	-	70-147	225/40		Orig.-Verschr.
	B32	44,5	-	70-114	225/40		Orig.-Verschr. für Alufelgen
	AC-521	42	Artikel Nr. 98497	70-114	225/40		Kit mit Artikelnummer 98497
	CA 26	45	ZP532	70-114	225/40		
	RC27	48	-	70-114	225/40, 235/40		Orig.-Verschr. für Alufelgen
8 x 19	B40	45	ZP580D6F	70-114	225/40		Orig.-Verschr. für Alufelgen
	B43	47,5	-	70-114	225/40, 235/40		Orig.-Verschr. für Alufelgen
	AC-518	45	Artikel Nr. 98497	70-114	225/40		Kit mit Artikelnummer 98497
	Oxigin 29	45	ZP532	70-114	225/40		
	B40	45	-	70-114	225/35		Orig.-Verschr. für Alufelgen
8 x 20	B43	45,5	-	70-114	225/35		Orig.-Verschr. für Alufelgen
		48,5	-	70-114	225/35, 235/35		Orig.-Verschr. für Alufelgen

Puma NEU		ab Facelift 2024		J2K	5/108	63,4	e9*2007/46*3165*16-..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 16	RC30	45	-	92	205/65M+S			Orig.-Verschr. für Alufelgen
7 x 17	CA 26	42	ZP580D6F+ R	92	205/55, 205/60			+ Red.Ringe 65,1-63,4
7,5 x 18	RC30	46	-	92, 114	215/50, 225/45, 235/45			Orig.-Verschr. für Alufelgen
8 x 18	CA 26	45	ZP580D6F+ R	92, 114	225/45			+ Red.Ringe 65,1-63,4
7,5 x 19	CA 26	45	ZP532	92, 114	225/40			
8 x 19	B43	47,5	-	92, 114	225/40, 235/40			Orig.-Verschr. für Alufelgen

Puma ST		ab 02/2021		J2K	5/108	63,4	e9*2007/46*3165*00-15	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC34	47,5	ZP580D6F	147	215/55			
	RC30	45	-	147	215/55			Orig.-Verschr. von Alufelgen
	B39	45	ZP580D6F	147	215/55			
7,5 x 17	RC24	47	ZP580D6F	147	215/55, 235/50HA			
	RC28 / RC29	45	ZP532	147	215/55			
	B24	45	ZP532	118, 147	215/55			
	B36	45	ZP532	147	215/55			
	Oxigin 25	50	-	147	215/50, 215/55			Orig.-Verschr.

7,5 x 18	RC30	46	-	118, 147	215/50, 225/45, 235/45		Orig.-Verschr. für Alufelgen
	B39	45	ZP532	147	215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	118, 147	225/45		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	147	225/45		Kit mit Artikelnummer 98497
8 x 18	RC27	45	-	147	225/45		Orig.-Verschr. für Alufelgen
	B37	45	ZP532	147	225/45		
	B36	45	ZP532	118, 147	225/45		
	AC-518	45	Artikel Nr. 98497	147	225/45		Kit mit Artikelnummer 98497
	CA 26	45	ZP580D6F+ R	118, 147	225/45		+ Red.Ringe 65,1-63,4
7,5 x 19	B32	44,5	-	147	225/40		Orig.-Verschr. für Alufelgen
	AC-521	42	Artikel Nr. 98497	147	225/40		Kit mit Artikelnummer 98497
	CA 26	45	ZP532	118, 147	225/40		
8 x 19	RC27	48	-	147	225/40		Orig.-Verschr. von Alufelgen
	B43	47,5	-	118, 147	225/40, 235/40		Orig.-Verschr. von Alufelgen
	B40	45	ZP580D6F	147	225/40		
	AC-518	45	Artikel Nr. 98497	147	225/40		Kit mit Artikelnummer 98497
	Oxigin 29	45	ZP532	70-114	225/40		
8 x 20	B43	45,5	-	147	225/35		Orig.-Verschr. für Alufelgen
		48,5	-	118, 147	225/35, 235/35		Orig.-Verschr. für Alufelgen

Puma ST		ab Facelift 2024		J2K	5/108	63,4	e9*2007/46*3165*16-..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC30	46	-	118	215/50, 225/45, 235/45		Orig.-Verschr. für Alufelgen, nur M+S
	AC-MB6 / AC-M10	42	Artikel Nr. 98497	118	225/45		Kit mit Artikelnummer 98497, nur M+S
8 x 18	CA 26	45	ZP580D6F+ R	118	225/45		+ Red.Ringe 65,1-63,4, nur M+S
7,5 x 19	CA 26	45	ZP532	118	225/40		nur M+S
8 x 19	B43	47,5	-	118	225/40, 235/40		Orig.-Verschr. für Alufelgen

S-Max II		ab 09/2015		WA6 (ab Modell 2016)		5/108		63,4		e13*2001/116*0185*24-...	
Sensor - Brocksens 4											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7,5 x 17	RC27	52,5	-	88-177	235/55				Orig.-Verschr., beide ET's original		
	RC32	52,5+55	-	88-177	235/55				Orig.-Verschr., beide ET's original		
	RC34	52,5	-	88-177	235/55				Orig.-Verschr.		
	RC24	47	-	88-177	235/55, 245/50, 245/55				Orig.-Verschr.		
		55	-	88-177	235/55				Orig.-Verschr.		
	RC29	45	ZP533D13	88-177	235/55, 245/50, 245/55						
	RC28	45	ZP533D13	88-177	235/55, 245/50, 245/55						
	B36	45	ZP533D13	88-177	235/55, 245/50, 245/55						
	AC-518	45	AV5	88-177	235/55, 245/50, 245/55						
	CA 20	45	ZP533D13F	88-177	235/55, 245/50, 245/55						
7,5 x 18	RC30	55	-	88-177	235/50, 245/45				Orig.-Verschr.		
	RC32	55	ZP533D13F	88-177	235/50, 245/45						
	RC30	50,5	-	88-177	235/50, 245/45, 245/50				Orig.-Verschr.		
		52,5	ZP533D13F	88-177	235/50, 245/45						
	RC32	45+50,5 + 52,5	ZP533D13F	88-177	235/50, 245/45						
		50	-	88-177	235/50, 245/45				Orig.-Verschr.		
	RC34	45+50	-	88-177	235/50, 245/45				Orig.-Verschr.		
	B32	50	-	88-177	235/50, 245/45, 245/50				Orig.-Verschr. für Alufelgen		
	B39	45	ZP533D13	88-177	235/50, 245/45, 245/50						
	AC-MB6	42	AV5	88-177	235/50, 245/45						
	AC-521	42	AV5	88-177	235/50, 245/45						
	Oxigin 25	52,5	-	88-177	235/50, 245/45				Orig.-Verschr.		
	RC27	45	-	88-177	235/50, 245/45, 255/45				Orig.-Verschr.		
		55			245/45						
	RC29	45	ZP533D13	88-177	235/50, 245/45, 255/45						
	RC32	45	ZP533D13F	88-177	235/50, 245/45, 255/45						
55		ZP533D13F	88-177	245/45							
RC34	45	-	88-177	235/50, 245/45, 255/45				Orig.-Verschr.			
	55	-	88-177	245/45				Orig.-Verschr.			
B36 / B38	45	ZP533D13	88-177	235/50, 245/45, 255/45							
AC-518	45+50	AV5	88-177	235/50, 245/45, 255/45							

	CA 26	45	ZP533D13F+R	88-177	235/50, 245/45, 255/45		+ Red.Ringe 65,1-63,4
7,5 x 19	RC32	50,5	ZP533D13F	88-177	235/45, 245/45		
	RC34	47,5+50	ZP533D13F	88-177	235/45		
		50,5	ZP533D13F	88-177	235/45		
	B39	55	-	88-177	235/45, 245/45		Orig.-Verschr.
	AC-521	42	AV5	88-177	235/45, 245/45		
	CA 26	45	ZP533D13	88-177	235/45, 245/45		nur M+S
8 x 19	RC27	55	-	88-177	245/40, 245/45		Orig.-Verschr.
	B43	55	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. von Alufelgen sonst ZP533D13F
	RC29	45	ZP533D13	88-177	235/45, 245/40, 245/45		
	RC32	45	ZP533D13F	88-177	235/40, 235/45, 245/40		
		55	-	88-177	245/45		Orig.-Verschr., i.V.
		52,5	ZP533D13F	88-177	235/40, 235/45, 245/40		
	RC34	45+52,5	ZP533D13F	88-177	235/40, 235/45, 245/40		
	B24 / B38	45	ZP533D13	88-177	235/45, 245/40, 245/45		
	B40	45+50	ZP533D13F	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
	B43	42+47,5	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
	AC-518	45	AV5	88-177	235/45, 245/40, 245/45		
	CA 19	45	OX533F-1	88-177	245/40, 245/45		
	CA 24	45	ZP533D13	88-177	245/40, 245/45		
8 x 20	Oxigin 29	45	ZP533D13	88-177	235/45, 245/40, 245/45		
	B38	45	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr.
	B40	45+52,5	ZP533D13F	88-177	235/40, 245/35, 245/40		
	B43	45,5+50	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
		50,5+55	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
	AC-521	43	AV5	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen

weitere Dimensionen/Designs siehe Konfigurator

S-Max Hybrid		ab 2021		WAH6	5/108	63,4	e13*2007/46*2374*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	50,5	-	88-177	235/55, 245/50, 245/55		Orig.-Verschr. für Alufelgen
	B24 / B36	45	ZP533D13	88-177	235/55, 245/50, 245/55		
	CA 20	45	ZP533D13F	88-177	235/55, 245/50, 245/55		
7,5 x 18	B32	50	-	88-177	235/50, 245/45, 245/50		Orig.-Verschr. für Alufelgen
8 x 18	CA 26	45	ZP533D13F+R	88-177	235/50, 245/45, 255/45		+ Red.Ringe 65,1-63,4
7,5 x 19	RC34	47,5	-	88-177	235/45		Orig.-Verschr.
	B32	44,5+55	-	88-177	235/45, 245/45		Orig.-Verschr.
		50,5+55	-	88-177	235/45, 245/45		Orig.-Verschr. für Alufelgen
8 x 19	B43	55	-	88-177	245/45		 Orig.-Verschr. von Alufelgen
	RC27	55	-	88-177	235/45, 245/40, 245/45		 Orig.-Verschr. für Alufelgen
	CA 24	45	ZP533D13	110-121	235/45, 245/40, 245/45		
	Oxigin 29	45	ZP533D13	88-177	235/45, 245/40, 245/45		
8,5 x 19	RC32	45	-	88-177	235/40, 245/40		Orig.-Verschr.
	B41	42	-	88-177	235/40, 245/40		Orig.-Verschr.
	B43	45	-	88-177	235/45, 245/40, 245/45		Orig.-Verschr. für Alufelgen
	B44	42	-	88-177	235/45		Orig.-Verschr. für Alufelgen
	CA 20	45	ZP533D13F	88-177	235/45, 245/40, 245/45		
	CA 23	45	ZP533D13	88-177	235/45, 245/40, 245/45		
8 x 20	B40	45+52,5	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
	B43	45,5+48,5	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
8,5 x 20	RC29	45+52,5	-	88-177	235/40, 245/35, 245/40		Orig.-Verschr. für Alufelgen
8,5 x 21	B43	49,5	-	88-177	245/35		Orig.-Verschr. für Alufelgen

Transit/Tourneo Connect		ab MJ2014		PJ2 / PU2	5/108	63,4	e1*2007/46*0272*04-..., e1*2001/116*0207*16-...
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
ACHTUNG! Befestigung wurde beim Facelift 2018 auf Radmutter M14x1,5 geändert betrifft die Typen "PJ2" ab Nachtrag 28, "PU2" ab Nachtrag 14 und "PJ2-LPG ab Nachtrag 26							

6,5 x 16	CA 20	50	ZP580D6F	55-125	205/60, 215/55		
	RC24	50	-	55-125	205/60, 215/55, 225/55		Orig.-Verschr. für Alufelgen
	RC27	50	-	55-125	205/60, 215/55		Orig.-Verschr. für Alufelgen
	RC30	50	ZP580D6F	55-125	205/60, 215/55		
	RC32	50	ZP580D6F	55-125	205/60, 215/55, 215/60, 225/55, 235/55		ab Modell 2014 bis Facelift 2018
	RC34	50	-	55-125	205/60, 215/55, 215/60, 225/55, 235/55		Orig.-Verschr.

Transit Connect/Tourneo Connect				ab FL2018	PJ2 / PU2	5/108	63,4	e1*2007/46*0272*..., e1*2001/116*0207*...
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension			Info

6,5 x 16	RC30	50	-	55-88	205/60, 215/55		Orig.-Verschr. für Alufelgen
	RC34	50	ZP533D13F	55-88	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		
	RC32	50	ZP533D13F	55-88	205/60, 215/55, 225/55, 235/50		
	RC34	45+47,5	ZP533D13F	55-88	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		
	Pro1	45	-	55-88	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
7 x 17	RC30	45	-	55-88	205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen
	RC32	45+47,5+50	ZP533D13F	55-88	205/50, 205/55, 215/50, 225/45, 225/50		
	Pro1	45	-	55-88	205/50, 205/55, 215/50, 215/55, 225/45, 225/50		Orig.-Verschr.
7,5 x 17	RC28 / RC29	45	ZP533D13	55-88	205/55, 215/50, 235/45		
	RC32	50,5	ZP533D13F	55-88	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45		
7,5 x 18	RC32	45+50+50,5	ZP533D13F	55-88	215/45, 225/40		
	RC34	45+50	ZP533D13F	55-88	215/45, 225/40, 225/45		
	B32	50	ZP533D13F	55-88	215/45, 225/45		
	AC-MB6	42	AV5	55-88	215/45, 225/45		
	AC-521	42	AV5	55-88	215/45, 225/45		
8 x 18	RC32	45	ZP533D13F	55-88	215/45, 225/40		
	RC34	45	ZP533D13F	55-88	215/45, 225/40		
	B42 / B44	42	ZP533D13	55-88	215/45, 225/45		
	AC-M10	42	ZP533D13F+R	55-88	215/45, 225/45		+ Red.Ringe 73,1-63,4
7,5 x 19	RC34	47,5+50	ZP533D13F	55-88	225/40		
		50,5	ZP533D13F	55-88	225/40		
8 x 19	RC32	45	ZP533D13F	55-88	225/40		

Tourneo Connect NEU		ab März / April 2022		SK/SKN	5/112	57,1	e13*2018/858*00270*..., e13*2018/858*00342*..	
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC30	47	-	55, 75	205/65, 215/65, 225/60		Orig.-Verschr., nur Bremse 288mm	
	RC24	43	-	55, 75	205/65, 215/65		Orig.-Verschr., nur Bremse 288mm	
		47	-	55, 75	205/65, 215/65, 225/60		Orig.-Verschr., nur Bremse 288mm	
		RC30	43	-	55, 75	205/65, 215/65		Orig.-Verschr., nur Bremse 288mm
6 x 16	RC30	48	-	55, 75	205/60, 215/55, 215/60, 225/55		Orig.-Verschr.	
6,5 x 16	RC30	48	-	55-90	205/60		Orig.-Verschr.	
	RC24	46+50	-	55-90	205/60, 215/55, 215/60		Orig.-Verschr.	
	RC27	46+50	-	55-90	205/60, 215/55, 215/60		Orig.-Verschr.	
	RC30	42	-	55-90	205/60		Orig.-Verschr.	
	CA 20	45	ZP560D	55-90	205/60			
	Pro1	48	ZP562D	55-90	205/60, 205/65, 215/55, 215/60			
6,5 x 17	RC27	49	-	55-90	205/55, 215/50, 215/55		Orig.-Verschr.	
		48,5	-	55-90	205/55, 215/50, 215/55		Orig.-Verschr.	
7 x 17	RC27	45+47	-	55-90	205/55		Orig.-Verschr.	
	RC30	49	-	55-90	205/55		Orig.-Verschr.	
	B39	49	-	55-90	205/55		Orig.-Verschr.	
7,5 x 17	B24	47	ZP560D	55-90	205/55			
	CA 20	47	ZP560D	55-90	205/55			
7 x 18	RC27	45	-	55-90	215/45, 225/45		Orig.-Verschr.	
7,5 x 18	B32	48	-	55-90	215/45, 225/45		Orig.-Verschr.	
		49	-	55-90	215/45		Orig.-Verschr.	
	B39	49	-	55-90	215/45		Orig.-Verschr.	
	RC30	45	ZP560D	55-90	215/45			
	B39	45	ZP560D	55-90	215/45			
8 x 18	B24	48	ZP560D	55-90	215/45			
	FMI08 Thoe	49	F31+R	55-90	215/45		+ Red.Ringe BA25=66,6-57,1	

Transit/Tourneo Custom				FAC / FCC		5/160	65,1	e11*2007/46*0676*.., e1*2007/46*1005*.., e5*2007/46*1034*..	
Sensor - Brocksens 4									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!									
6,5 x 16	RC25T	60	-	74-136	215/65C			Orig.-Verschr., incl. Facelift 2018	
	AC-V51	50	-	74-136	215/60C, 215/65+C			Orig.-Verschr., incl. Facelift 2018	
			-	77-136	215/65+C, 225/60+C, 235/60		Orig.-Verschr., incl. Facelift 2018, mit Radhausverbreiterungen		
	Pro1	60	-	62-136	195/65C, 205/65, 205/65C, 215/60, 215/60C, 215/65, 215/65C			Orig.-Verschr., ohne Radhausverbreiterungen	
			-	77-136	215/60C, 215/65, 215/65C, 225/60, 225/60C, 225/65, 225/65C			Orig.-Verschr., mit Radhausverbreiterungen	
								Orig.-Verschr., incl. Facelift 2018, nicht für einen	

7 x 17	RC25T	55	-	74-136	215/60, 215/60C , 225/55, 225/55C		Orig.-Verschr., incl. Facelift 2018, nicht für reines Elektrofahrzeug und nicht für Plug-in-Hybrid Modelle!
			-	77-136	215/60, 215/60C , 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr., incl. Facelift 2018, mit Radhausverbreiterungen, nicht für reines Elektrofahrzeug und nicht für Plug-in-Hybrid Modelle!
7,5 x 18	Originaldim.	56			235/50		
	RC25T	50	-	74-136	215/55, 225/50, 235/50, 245/45		Orig.-Verschr., incl. FL2018, ohne Radhausverbr. ✖
					235/50, 245/45		Orig.-Verschr., nur 245/45 auflagenfrei!
	B45	50	-	74-136	215/55, 225/50, 225/50C, 235/50, 245/45		Orig.-Verschr., incl. Facelift ab 2018, ohne Radhausverbreiterungen ✖
				77-136	225/50C, 235/50, 245/45		Orig.-Verschr., incl. Facelift ab 2018, mit Radhausverbreiterungen, bei 235/50 ✖
	AC-V51	50	-	74-136	245/45		Orig.-Verschr., incl. Facelift ab 2018, ohne Radhausverbreiterungen ✖
	CA 20	50	-	74-136	245/45		Orig.-Verschr.

Transit	FAD / FCD	5/160	65,1	e11*2007/46*0801*.., e1*2007/46*1100*.., e5*2007/46*1032*..
---------	-----------	-------	------	---

Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC25T	60	-	74-125	215/65C, 235/65C		Orig.-Verschr., Typ FAD
				74-136	215/65C, 235/65C		Orig.-Verschr., Typ FCD
	Pro1	60	-	74-125	215/60C, 215/65, 215/65C, 215/70, 225/60, 225/60C, 225/65, 225/65C, 235/65, 235/65C		Orig.-Verschr., Serie Sommerreifen 215/..
				74-136	235/65C		
7 x 17	RC25T	55	-	74-125	215/60C, 225/55+C, 235/55, 235/60C		Orig.-Verschr., mit Kotflügelverbreiterung
	AC-V51	55	-	74-125	235/60C		Orig.-Verschr., Typ FAD, mit Verbreiterungen
				74-136	235/60C		Orig.-Verschr., Typ FCD, mit Verbreiterungen
7,5 x 18	RC25T	50	-	74-136	235/50, 235/55		Orig.-Verschr., mit Kotflügelverbreiterung
	B45	50	-	74-125	225/50C, 235/50, 235/55		Orig.-Verschr., Typ FAD, mit Verbreiterungen
				74-136	225/50C, 235/50, 235/55		Orig.-Verschr., Typ FCD, mit Verbreiterungen
	CA 20	50	-	74-125	225/55, 235/50		Orig.-Verschr.
8 x 20	B45	50	-	74-125	235/45C		Orig.-Verschr., Typ FAD, mit Verbreiterungen
				74-136	235/45C		Orig.-Verschr., Typ FCD, mit Verbreiterungen

Transit	FDD	5/160	65,1	e1*2007/46*1098*
---------	-----	-------	------	------------------

Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC25T	60	-	74-125	235/65C		Orig.-Verschr., Frontantrieb, mit Verbreiter.
7 x 17	RC25T	55	-	74-125	235/60C		Orig.-Verschr., mit Kotflügelverbreiterung
	AC-V51	55	-	74-125	235/60C		Orig.-Verschr., mit Kotflügelverbreiterung
8 x 20	B45	50	-	74-125	235/45C		Orig.-Verschr., Frontantrieb, mit Verbreiter.

Transit Tourneo Custom	NEU	4. Quartal 2023	NRN / NXN	6/120	74,6	e5*2018/858*00192*.., e5*2018/858*00191*..
------------------------	-----	-----------------	-----------	-------	------	--

Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC35	50	-	81-125	215/65C		Orig.-Verschr., ohne Radhausverbreiterung
				100-125	215/65		Orig.-Verschr., mit Radhausverbreiterung
				81-125	215/65, 215/65C, 225/60, 225/60C, 225/65C, 235/60		Orig.-Verschr.
	Pro2	50	-	81-125	215/65C , 225/60, 225/60C, 235/60		Orig.-Verschr., mit Serie 215/65R16C od. 215/60R17C
				100-125	215/65C , 215/70C, 225/65, 225/65CP, 235/60, 235/65, 235/65C, 235/65CP		Orig.-Verschr., Ausstattung Sport, 19Zoll Serie, ww. Serie 215/65R16C od. 215/60R17C
				100-125	215/70C, 235/65, 235/65C, 235/65CP		Orig.-Verschr., Ausstattung Sport und NUR 19Zoll Serie
7 x 16	RC31	45	-	81-125	215/65C, 225/60, 225/60C		Orig.-Verschr., mit Serie 215/65R16C od. 215/60R17C
				100-125	215/65C, 215/70C, 225/65, 225/65C, 225/65CP		Orig.-Verschr., Ausstattung Sport, 19Zoll Serie, ww. Serie 215/65R16C od. 215/60R17C
				100-125	215/70C		Orig.-Verschr., Ausstattung Sport und NUR 19Zoll Serie
6,5 x 17	RC35	50	-	81-125	215/60C		Orig.-Verschr., ohne Radhausverbreiterung
				100-125	215/60C		Orig.-Verschr., mit Radhausverbreiterung
				81-125	215/60C, 215/65, 215/65C, 225/55, 225/55C, 225/60, 225/60C, 235/55, 235/60, 235/60C		Orig.-Verschr.
	RC31	45	-	81-125	215/55, 215/60, 215/60C, 225/55, 225/55C		Orig.-Verschr., mit Serie 215/65R16C od. 215/60R17C
				100-125	215/60C, 215/65C, 225/55C, 225/60, 225/65C		Orig.-Verschr., Ausstattung Sport, 19Zoll Serie, ww. Serie 215/65R16C od. 215/60R17C
				100-125	215/65C, 225/60, 225/65C		Orig.-Verschr., Ausstattung Sport und NUR 19Zoll

7 x 17	B45	45	-	100-125	215/60C, 215/65, 215/65C, 225/55, 225/55C, 225/60, 225/60C, 235/55, 235/60, 235/60C		Serie
				81-125	215/60C, 215/65, 215/65C, 225/55, 225/55C, 225/60, 225/60C, 235/55, 235/60, 235/60C		Orig.-Verschr., Typ NRN, nur Bremse 308mm
	Pro2	48	-	81-125	215/55, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr., mit Serie 215/65R16C od. 215/60R17C
				100-125	215/60C, 215/65C, 225/55C, 225/60, 225/65C, 235/55, 235/60, 235/60C		Orig.-Verschr., Ausstattung Sport, 19Zoll Serie, ww. Serie 215/65R16C od. 215/60R17C
				100-125	215/65C, 225/60, 225/65C, 235/60, 235/60C		Orig.-Verschr., Ausstattung Sport und NUR 19Zoll Serie
7,5 x 18	B45	48	-	81-125	215/60, 225/50C, 225/55, 235/50, 235/55, 235/55C		Orig.-Verschr., nur Bremse 308mm, Typ NRN
				100-125	215/60, 225/50C, 225/55, 235/50, 235/55, 235/55C		Orig.-Verschr., nur Bremse 308mm, Typ NXN
8 x 18	RC31	51	-	81-125	225/50, 235/45, 245/45, 255/45		Orig.-Verschr., mit Serie 215/65R16C od. 215/60R17C
				87-125	225/55, 235/55, 255/45		Orig.-Verschr., Ausstattung Sport, 19Zoll Serie, ww. Serie 215/65R16C od. 215/60R17C
				87-125	225/55, 235/55		Orig.-Verschr., Ausstattung Sport und NUR 19Zoll Serie
8 x 20	B45	45	-	81-125	235/45, 235/45C, 245/40		Orig.-Verschr., Typ NRN
				81-125	235/45C		Orig.-Verschr., Typ NXN

Transit/Tourneo Custom PHEV NEU				Okt.23	NRN / NXN	6/120	74,6	e5*2018/858*00192*..., e5*2018/858*00191*..
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC35	50	-	87	215/65C			Orig.-Verschr., Plug-in-Hybrid
6,5 x 17	RC35	50	-	87	215/60C			Orig.-Verschr., Plug-in-Hybrid
7,5 x 18	B45	48	-	87	225/50C, 235/55, 235/55C			Orig.-Verschr., Plug-in-Hybrid, nur Typ NRN
				87	215/60, 225/50C, 225/55, 235/55, 235/55C			Orig.-Verschr., Plug-in-Hybrid, nur Typ NXN
8 x 20	B45	45	-	87	235/45C			Orig.-Verschr., Plug-in-Hybrid

Transit/Tourneo Custom E PHEV NEU				Okt.23	NRN / NXN	6/120	74,6	e5*2018/858*00192*..., e5*2018/858*00191*..
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC35	50	-	63-85	215/65C			Orig.-Verschr., Elektro
6,5 x 17	RC35	50	-	63-85	215/60C			Orig.-Verschr., Elektro
7,5 x 18	B45	48	-	63-85	225/50C, 235/55C			Orig.-Verschr., Elektro
8 x 20	B45	45	-	63-85	235/45C			Orig.-Verschr., Elektro

Transit Courier			ab 2014		JN8 / JU2	4/108	63,4	e13*2007/46*1349*..., e1*98/14*0194*26-...	
Sensor - Brocksens 4									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6 x 15	RC30	37,5	ZP422D6F	55-74	185/60, 195/55, 195/60				Orig.-Verschr. für Alufelgen
	RC24	37,5	- od. ZP422D6F	55-74	185/60, 185/65, 195/60, 205/55				
6,5 x 15	RC28	40	ZP422D6F	55-74	185/60, 195/55, 195/60+C				
6 x 16	RC30	37,5	ZP422D6F	55-74	185/55, 195/50, 195/55, 205/50				
6,5 x 16	RC30	40	ZP422D6F	55-74	185/55, 195/50, 195/55				
7 x 17	B39	38	ZP422D6F	55-74	195/45, 205/45				
7,5 x 17	RC28	40	ZP422D6F	55-74	195/45				

Tourneo Courier NEU					ab 2024	N1P	5/108	63,4	e13*2018/858*00648*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
6,5 x 16	RC30	45	-	92	205/65				Orig.-Verschr. für Alufelgen	
8,5 x 20	B43	47,5	-	92	225/35, 235/35				Orig.-Verschr. für Alufelgen	

Transit/Tourneo Courier NEU ab 2024				N3P	5/108	63,4	e13*2018/858*00649*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	45	-	73-92	205/65			Orig.-Verschr. für Alufelgen, mit 16/17 Zoll Serienbereifung
8,5 x 20	B43	47,5	-	73, 74	225/35, 235/35			Orig.-Verschr. für Alufelgen, nur mit 15" Serie
				73-92	225/35, 235/35			Orig.-Verschr. für Alufelgen, mit 16/17" Serie

Ranger				ab 2012	2AB	6/139,7	93,1	e11*2007/46*0154*..., e5*2007/46*0080*...	
Sensor - Brocksens 4									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!									
6,5 x 16	RC35	55	-	92-157	255/70				Orig.-Verschr., mit Trommelbremse an HA
	RC31	55	ZP600F	92-157	255/70, 265/70+C, 265/75				auch e5*2007*...
7 x 16	RC31	55	-	92-157	255/65, 255/70, 265/70				Orig.-Verschr.
	B45	55	-	92-157	255/65, 255/70				Orig.-Verschr., incl. Facelift 2019, mit

	B45	55	-	92-157	255/65, 255/70, 265/65		Trommelbremse an HA
7,5 x 17	RC35	55	-	92-157	255/65, 255/70, 265/65		Orig.-Verschr.
	RC14-6S	50	ZP600F	92-157	255/65, 255/70, 265/65		nur Allrad, ET55 Orig.-ET -> ✖ ?
8,5 x 17	8400 Bluster	50	-	92-157	255/65, 255/70, 265/65, 265/70, 275/60, 275/65		Orig.-Verschr., ✖
7,5 x 18	B45	55	-	92-157	255/60, 265/60		Orig.-Verschr., incl. Facelift 2019, mit Trommelbremse an HA
8 x 18	RC31	55	-	92-110	235/60, 235/65, 245/60		Orig.-Verschr., nicht Allrad, nicht e5*2007*...
				92-147	255/55, 255/60, 265/60		Orig.-Verschr., nicht e5*2007*...
	8400 Bluster	50	-	92-157	255/60, 255/65, 265/60, 265/65, 275/60, 285/55		Orig.-Verschr., ✖
8 x 20	B45	55,1	-	92-157	255/50, 265/50		Orig.-Verschr., incl. Facelift 2019, mit Trommelbremse an HA
9 x 20	8400 Bluster	48	-	92-157	255/50, 265/50, 275/45, 275/50, 285/45		Orig.-Verschr., ✖

Ranger NEU		ab Modelljahr 2022			2AB	6/139,7	93,1	e5*2007/46*0080*09-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!									
6,5 x 16	RC35	55					i.V.		
7 x 17	B45	55	-	125	255/65, 255/70		Orig.-Verschr.		
7,5 x 17	RC35	55	-	125	255/65, 255/70 , 265/65, 275/60, 275/65		Orig.-Verschr.		
8,5 x 17	8400 Bluster	50	-	125	255/65, 255/70, 265/65, 275/60, 275/65		Orig.-Verschr., ab 275/60	✖	
7,5 x 18	B45	55	-	125-177	255/65 , 265/60		Orig.-Verschr.		
				125	255/60				
8 x 18	8400 Bluster	50	-	125-177	255/60, 255/65, 265/55, 265/60, 275/60, 285/55		Orig.-Verschr., ab 275/60	✖	
8 x 20	B45	55,1	-	125	255/50		Orig.-Verschr.		
				125-177	255/55				
9 x 20	8400 Bluster	48	-	125-177	255/50, 255/55, 265/50, 275/45, 275/50, 285/45		Orig.-Verschr., nur 275/45 auflagenfrei!		

Ranger Raptor i.V.		ab September 2022			2AB	6/139,7	93,1	e11*2007/46*0154*18-...; e5*2007/46*0080*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 17	Originaldim.	55		157		<u>285/70</u>			

Great Wall

Ora 03 Funky Cat / Funky Cat GT NEU				2023	ES11	5/114,3	66,6	e13*2018/858*00266*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 17	RC27	47	-	60 (126)	205/55, 215/50, 215/55, 225/50, 235/50				Orig.-Verschr., Ausführung GW1 , 17 Zoll Serie, ohne Radhausverbreiterungen
	RC34	47	-	60	205/55, 215/55, 225/50, 235/50				Orig.-Verschr., i.V., Ausführung GW1
7 x 17	CA 26	45	ZP569	60 (126)	205/55, 215/50, 215/55, 225/50, 235/50				17 Zoll Serie
7,5 x 17	CA 20	48	ZP569	60 (126)	205/55, 215/50, 215/55, 225/50, 235/45, 245/45				17 Zoll Serie
7 x 18	RC32	39	-	60	215/45, 215/50, 225/45			Orig.-Verschr., Ausführung GW1	
					215/50			Orig.-Verschr., Ausführung GW1, nur GT	
	RC34	39	-	60	215/50			Orig.-Verschr., i.V., Ausführung GW1	
7,5 x 18	CA 20	40	ZP568	60	215/45, 215/50, 225/45, 235/45				
					215/50, 235/45, 245/45			nur GT	
8 x 18	CA 20 / CA 23 / CA 26	45	ZP569	60 (126)	215/50, 225/45, 235/45, 245/40, 245/45			18 Zoll Serie	
				60 (126)	215/45, 215/50, 225/45, 235/40, 235/45, 245/40			17 Zoll Serie	
8 x 19	CA 19	45	ZP569	60 (126)	225/40, 235/35, 235/40, 245/35, 245/40			18 Zoll Serie	
				60 (126)	225/40, 235/35, 235/40, 245/35			17 Zoll Serie	
	Oxigin 29	40	ZP569	60 (126)	225/40, 235/35, 235/40, 245/35, 245/40			18 Zoll Serie, ohne Radhausverbreiterungen ab 235/35 ✖	
				60 (126)	225/40			17 Zoll Serie	
8,5 x 19	CA 20	45	ZP569	60 (126)	225/40, 235/35, 235/40				
7,5 x 20	RC36	40+45	-	60 (126)	225/35			Orig.-Verschr.	

Ora 07 NEU		EC24			5/114,3	66,6	e9*2018/858*11531*..		
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 18	CA 20	40	ZP568	66	235/45, 235/50, 245/45				

Wey Coffee 01 NEU		2023			V71 / V61	5/114,3	66,6	e9*2018/858*11205*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 21	B41	45	-	150	235/45, 245/45, 255/45, 265/45		Orig.-Verschr., i.V., Ausführung GW1		
8 x 19	CA 19	45	ZP569	150	235/55, 245/50				
9 x 20	CA 23 / CA 26	45	ZP569	150	235/55, 255/50, 265/50, 275/45, 285/45		Variante MF4		

Wey Coffee 03 / Coffee 02 PHEV NEU				2023	V71 / V61	5/114,3	66,6	e9*2018/858*11205*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 19	CA 20	45	ZP569	150	235/55				Variante 1F4 + 1F2
		45	-	150	235/50, 245/45				Orig.-Verschr., Variante 1F4 + 1F2
		40	-	150	235/50, 245/45				Orig.-Verschr., Variante 1F4 + 1F2
7,5 x 20	RC36	45	ZP569	150	235/55				Variante 1F4 + 1F2
		45	-	150	235/50, 245/45				Orig.-Verschr., Variante 1F4 + 1F2
		40	-	150	235/50, 245/45				Orig.-Verschr., Variante 1F4 + 1F2

9 x 20	CA 23 / CA 26	45	ZP569	150	235/50, 245/45, 255/45		Variante 1F4 + 1F2
Wey Coffee 05 ^{NEU} 2023 V71 / V61 5/114,3 66,6 e9*2018/858*11205*..							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 20	RC36	45	-	150	235/55, 245/50, 255/50, 265/50		Orig.-Verschr., Variante MF4, Plug-in Hybrid
		40	-	150	235/55, 245/50, 255/50, 265/50		Orig.-Verschr., Variante MF4, Plug-in Hybrid

Honda

Honda		Baujahr		Typ		LK/LZ		Nabe	
Civic X		ab 03.2017		FC, FK		5/114,3		64,1	
kein Sensor - indirektes RDKS								e11*2007/46*3633*... neu Typ FK e6*2007/46*0256*...	
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
7 x 16	RC30	45	-	88-134	215/55			Orig.-Verschr.	
	RC24	45	ZP576D6	88-134	215/55, 225/50, 235/50				
	RC28	45	ZP576D6	92-134	215/55, 225/50, 235/50				
7 x 17	RC32	45	-	88-134	215/45, 215/50, 225/45			Orig.-Verschr.	
	RC27	45	ZP576D6	88-134	215/45, 215/50, 225/45, 235/45			Limousine nicht 235/45	
	RC30	45	-	88-134	215/45, 215/50, 225/45, 235/45			Limousine nicht 235/45	
	B39	45	ZP576D6	95-134	215/45, 215/50, 225/45, 235/45			5-Türer	
				92-134	215/45, 215/50, 225/45			Limousine	
7,5 x 17	RC24	50	ZP576D6	88-134	215/45, 215/50, 225/45, 235/45				
	RC27	50	-	88-134	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.		
	RC29	38	ZP576D6	88-134	215/45, 215/50, 225/45, 235/45				
		48	ZP576D6	88-134	215/45, 215/50, 225/45, 235/45, 245/45				
	RC32	45	-	88-134	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr., 4-türig		
				88-134	215/45, 215/50, 225/45, 235/45		Orig.-Verschr., 5-türig		
	B36	38	ZP576D6	92-134	215/45, 215/50, 225/45, 235/45				
		46	ZP576D6	88-134	215/45, 215/50, 225/45, 235/45, 245/45				
	AC-518	40	ZP580D6+ F	88-134	215/45, 215/50, 225/45, 235/45		5-Türer		
				88-134	215/45, 215/50, 225/45, 235/45		Limousine		
7,5 x 18	RC30	45	ZP576D6	88-134	215/40, 215/45, 225/40				
	B32	45	ZP576D6	88-134	215/40, 215/45, 225/40				
	B39	35+45	ZP576D6	88-134	215/40, 215/45, 225/40				
	AC-MB6	45	Artikel Nr. 98498	88-134	215/40, 215/45, 225/40		Kit mit Artikelnummer 98498		
	AC-521	45	ZP580D6+ F	88-134	215/40, 215/45, 225/40		+ Red.Ringe 73,1-64,1		
8 x 18	RC27	50	-	88-134	235/40			Orig.-Verschr.	
	RC29	45	ZP576D6	88-134	215/40, 215/45, 225/40, 235/40, 245/35				
	B38	45	ZP576D6	88-134	215/40, 215/45, 225/40, 235/40, 245/35		Limousine nicht 245/35		
		49	ZP576D6	88-134	215/40, 215/45, 225/40, 235/40				
	B42 / B44	45	ZP576D6	88-134	215/40, 215/45, 225/40, 235/40, 245/35		Limousine nicht 245/35		
	AC-518	40	ZP580D6+ F	88-134	215/40, 215/45, 225/40		5-Türer		
				88-134	215/40, 215/45, 225/40, 235/40		Limousine		
	AC-M10	45	ZP580D6+ F	88-134	215/40, 215/45, 225/40, 235/40, 245/35		5-Türer, + Red.Ringe 73,1-64,1		
7,5 x 19	RC32 / RC34	45	-	88-134	215/35, 225/35		Orig.-Verschr.		
	B32	40	ZP576D6	88-134	215/35, 225/35		auch Typ FK		
	B39	40+45	ZP576D6	92-134	215/35, 225/35				
8 x 19	RC29	38	ZP576D6	88-134	215/35, 225/35				
		48	ZP576D6	88-134	215/35, 225/35, 235/35		5-Türer		
	B24	50	ZP576D6	88-134	215/35, 225/35		5-Türer		
	B38	45	ZP576D6	88-134	215/35, 225/35, 235/35		5-Türer		
				88-134	215/35, 225/35		Limousine		
8 x 20	AC-518	40	ZP580D6+ F	88-134	215/35, 225/35		5-Türer		
				88-134	215/35, 225/35, 235/35		Limousine		
	B38	45	ZP576D6	88-134	225/30		Limousine		
				88-134	225/30, 235/30		5-Türer		
B40	35	ZP576D6	88-134	225/30		5-Türer			
AC-521	45	ZP580D6+ F	88-134	225/30		Limousine			
			88-134	225/30, 235/30		5-Türer			
weitere Dimensionen/Designs siehe Konfigurator									

Civic Hybrid		NEU	2. Halbjahr 2022		FE	5/114,3	64,1	e6*2018/858*00064*..	
kein Sensor - indirektes RDKS									
Dimension	Design		ET	KIT	KW	Reifendimension		Info	
7 x 17	RC32		45	-	105	215/45, 215/50, 225/45			Orig.-Verschr.
	CA 26		45	ZP576D6	105	215/45, 215/50, 225/45			
7,5 x 17	RC24		50	ZP576D6	105	215/45, 215/50, 225/45, 235/45, 245/45			
	RC32		45	-	105	215/45, 215/50, 225/45, 235/45, 245/45			Orig.-Verschr.
	B24		48	ZP576D6	105	215/45, 215/50, 225/45, 235/45, 245/45			
	B36		46	ZP576D6	105	215/45, 215/50, 225/45, 235/45, 245/45			
7 x 18	RC27		45+50	-	105	215/40, 215/45			Orig.-Verschr.
7,5 x 18	B32		45	ZP576D6	105	215/40, 215/45, 225/40, 235/40			
	AC-MB6 / M10	AC-	35	Artikel Nr. 98498	105	215/40, 215/45, 225/40			Kit mit Artikelnummer 98498
			45	Artikel Nr. 98498	105	215/40, 215/45, 225/40, 235/40			Kit mit Artikelnummer 98498
	CA 20		40	ZP576D6	105	215/45, 225/40			

	Oxigin 25	45	ZP576D6	95-134	225/40		mit Radhausverbreiterungen
8 x 18	RC27	50	-	105	235/40		Orig.-Verschr.
	B24	48	ZP576D6	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		
	B36	45	ZP576D6	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		
	B42	40	ZP576D6	105	215/40, 215/45, 225/40, 235/40		
		45	ZP576D6	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		
	B44	40	ZP576D6	105	215/40, 215/45, 225/40, 235/40		
		45	ZP576D6	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		
	AC-M10	45	Artikel Nr. 98498	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		Kit mit Artikelnummer 98498
	CA 20	45	ZP576D6	105	215/40, 215/45, 225/40, 235/40, 245/35, 245/40		
7,5 x 19	CA 26	45	ZP576D6	105	225/35		
8 x 19	RC29	48	ZP576D6	105	225/35, 235/35		
	B38	45	ZP576D6	105	225/35, 235/35		
	CA 19	45	ZP576D6	105	225/35, 235/35		
	CA 24	45	ZP576D6	95-134	225/35, 235/35		
	Oxigin 29	50	ZP576D6	105	225/35, 235/35		
8,5 x 19	B32	45	ZP576D6	105	225/35, 235/35		
	B36	44	ZP576D6	105	225/35, 235/35		
	B37 / B42	45	ZP576D6	105	225/35, 235/35		
	B44	40	ZP576D6	105	225/35		
8,5 x 20	B42	45	ZP576D6	105	235/30		

Civic Type R NEU i.V.		im Laufe 2023		FE	5/114,3	64,1		
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
9,5 x 19	B40	60	-	242	255/30, 265/30, 275/30			Orig.-Verschr.
Civic (IX) R (siehe Konfigurator)		ab 2015		FK2	5/120	64,1	e11*2001/116*0256*14-..	

Civic (X) R		ab 2017		FC, FK		5/120		64,1		e11*2007/46*3633*..., e6*2007/46*0256*01-...	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8 x 18	RC32	55	-	235	235/40, 245/40					Orig.-Verschr.	
8 x 19	B40	45	-	235	235/35, 245/30, 245/35					Orig.-Verschr.	
CR-V IV (siehe Konfigurator)		ab FL 2015		RE5/RE6		5/114,3		64,1		e11*2001/116*0301*10-..., e11*2001/116*0302*11-...	

CR-V (V)		ab 2018		RW	5/114,3	64,1	e6*2007/46*0265*...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC32	45	-	127	235/65, 245/60		Orig.-Verschr.	
	B37 / B38	45	ZP576D6	127	235/65, 255/60			
	B36	46	ZP576D6	127	235/65			
	AC-518	40	ZP580D6F +R	127	235/65		+ Red.Ringe 73,1-64,1	
7,5 x 18	RC34	45	-	107-142	235/60		Orig.-Verschr.	
	B32	35	ZP576D6	107-142	235/60, 255/55		bei 255/55 ✖	
		45	ZP576D6	107-142	235/60, 255/55		bei 255/55 ✖	
	B39	45	ZP576D6	107-142	235/60			
	AC-MB6 / AC-M10	45	Artikel Nr. 98498	107-142	235/60		Kit mit Artikelnummer 98498	
8 x 18	CA 20	40	ZP576D6	107-142	235/60			
	RC29	45	ZP576D6	107-142	235/60			
	B37 / B38	45	ZP576D6	107-142	235/60			
	B36	45	ZP576D6	107-142	235/60			
	B42	40+45	ZP576D6	107-142	235/60			
	B44	40+45	ZP576D6	107-142	235/60			
	AC-518	40	ZP580D6F +R	107-142	235/60		+ Red.Ringe 73,1-64,1	
	AC-M10	45	ZP580D6F +R	107-142	235/60		+ Red.Ringe 73,1-64,1	
8,5 x 18	B32	45	ZP576D6	127, 142	235/60			
7,5 x 19	RC32	45	-	107-142	235/50, 235/55, 245/50		Orig.-Verschr.	
	RC34	45	-	107-142	235/50, 235/55, 245/50		Orig.-Verschr.	
	B32	40	ZP576D6	107-142	235/50, 235/55			
	B39	45	ZP576D6	107-142	235/50, 235/55, 245/50			
	CA 26	45	ZP576D6	107-142	235/50, 235/55, 245/50			
8 x 19	B38	45	ZP576D6	107-142	235/50, 235/55, 245/50			
	AC-518	40	ZP580D6F +R	107-142	235/50		+ Red.Ringe 73,1-64,1	
	CA 19	45	ZP576D6	107-142	235/50, 235/55, 245/50			

8,5 x 19	CA 24	45	ZP576D6	107-142	235/55		
	Oxigin 29	40	ZP576D6	107-142	235/50, 235/55		
	B32	45	ZP576D6	107-142	235/50, 235/55		
	B36	44	ZP576D6	107-142	235/50, 235/55		
	B37 / B42	45	ZP576D6	107-142	235/50, 235/55		
8 x 20	B38	45	ZP576D6	107-142	235/45, 235/50, 245/45, 255/45		
	B40	35	ZP576D6	107-142	235/45		
	AC-521	45	ZP580D6F +R	107-142	235/45, 235/50, 245/45, 255/45		+ Red.Ringe 73,1-64,1
8,5 x 20	RC29	45	ZP576D6	107-142	235/45, 235/50, 245/45, 255/45		
	B24	42	ZP576D6	107-142	235/45, 245/45		
	B32	40	ZP576D6	107-142	235/45, 245/45		
	B42	45	ZP576D6	107-142	235/45, 235/50, 245/45, 255/45		
	B44	40	ZP576D6	107-142	235/45, 245/45		
	AC-518	40	ZP580D6F +R	107-142	235/45, 245/45		+ Red.Ringe 73,1-64,1
9 x 20	CA 23	45	ZP576D6	107-142	235/45, 245/45		
8,5 x 21	B41	47	ZP576D6	107-142	245/40, 255/40		

CR-V Hybrid		ab 02.2019		RW	5/114,3	64,1	e6*2007/46*0265*...	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC34	45	-	107-142	235/60			Orig.-Verschr.
	CA 20	40	ZP576D6	107-142	235/60			
7,5 x 19	RC32	45	-	107-142	235/55			Orig.-Verschr.
	RC34	45	-	107-142	235/50, 235/55, 245/50			Orig.-Verschr.
8,5 x 20	B32	40	ZP576D6	107-142	235/45, 235/50, 245/45, 255/45			bei 235/50 u. 255/45 ✖

CR-V NEU		ab 2023		RS	5/120	64,1	e6*2018/858*00267*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC30	40	-	109	235/60, 245/55, 255/55		Orig.-Verschr.
8 x 19	B40	40	ZP533D13F	109	235/50, 235/55, 245/50		
		35	ZP533D13F	109	235/50, 235/55		
8,5 x 19	B32	38	ZP533D13F +R	109	235/50, 235/55		+ Red.Ringe 72,6-64,1
8 x 20	RC36	40	ZP533D13F	109	235/45, 235/50, 245/45, 255/45		
	B40	31	ZP533D13F	109	235/45, 245/45		

Honda e		ab 2020		ZC	5/114,3	64,1	e6*2007/46*0425*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 16	RC30	VA 50	-	60	VA 185/60, 195/55, 205/55			Orig.-Verschr.
7 x 16		HA 45			HA 205/55, 225/50			
7 x 17	RC27	45	ZP576D6	60	VA 205/45 + HA 225/45			
	RC30	45	-	60	VA 205/45 + HA 225/45			Orig.-Verschr., Felge gibt es nur in SG
	RC32	45	-	60	205/45, 215/45			Orig.-Verschr.
	B39	45	ZP576D6	60	VA 205/45 + HA 225/45			
	CA 26	45	ZP576D6	60	VA 205/45 + HA 225/45			
7,5 x 17	RC27	50	-	60	VA 205/45 + HA 225/45			Orig.-Verschr.
	RC32	45	-	60	VA 205/45 + HA 225/45			Orig.-Verschr.
	B24	48	ZP576D6	60	VA 205/45 + HA 225/45			
	B36	46	ZP576D6	60	VA 205/45 + HA 225/45			
7,5 x 18	RC30	45	ZP576D6	60	VA 205/40 + HA 225/40			
	B32	45	ZP576D6	60	VA 205/40 + HA 225/40			
	AC-MB6 / AC-M10	45	Artikel Nr. 98498	60	VA 205/40 + HA 225/40			Kit mit Artikelnummer 98498
	AC-521	45	ZP580D6F +R	60	VA 205/40 + HA 225/40			+ Red.Ringe 73,1-64,1
8 x 18	B36 / B44	45	ZP576D6	60	VA 205/40 + HA 225/40			VA ✖
	AC-M10	45	ZP580D6F +R	60	VA 205/40 + HA 225/40			+ Red.Ringe 73,1-64,1, VA ✖

Honda e:Ny1 NEU				RSA	5/114,3	64,1	e6*2018/858*00269*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	AC-MB6 / AC-M10	45	Artikel Nr. 98498	60 (150)	235/45		Kit mit Artikelnummer 98498
	RC30	45	ZP576D6	60 (150)	235/45		
8 x 18	RC27	50	-	60 (150)	225/50, 235/45, 245/45		Orig.-Verschr.
	B24	48	ZP576D6	60 (150)	235/45		
7,5 x 19	CA 26	45	ZP576D6	60 (150)	225/45		
8 x 19	CA 19	45	ZP576D6	60 (150)	225/45		
	Oxigin 29	50	ZP576D6	60 (150)	225/45, 235/40, 245/40		

HR-V		ab 06.2015		RU	5/114,3	64,1	e6*2007/46*0158*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 16	RC30	55	-	88, 96	215/60, 225/55			Orig.-Verschr.
	RC30	55	-	88, 96	215/60, 225/55			Orig.-Verschr.
	RC28	45	ZP576D6	88, 96	215/60			
7 x 17	RC30	55	-	88, 96 96, 134	215/55, 225/50, 235/50 215/55, 225/55, 235/50, 245/50		 	Orig.-Verschr.
	RC27 / RC30	45	ZP576D6	88, 96	215/55, 225/50, 235/50			ab 225/50 ✖
	B39	45	ZP576D6	88, 96	215/55			
7,5 x 17	RC24	50	ZP576D6	88, 96	215/55, 225/50, 235/50, 245/45			ab 225/50 ✖
	RC29	48	ZP576D6	88, 96 96, 134	215/55 215/55, 225/55			
	RC27	50	-	88, 96 96, 134	215/55 215/55, 225/55, 235/50			Orig.-Verschr.
	Oxigin 19	48	ZP576D6	88-96	205/55, 215/50, 215/55, 225/50, 235/45, 235/50			ab 215/50 ✖
7 x 18	RC27	55	-	88-96	215/50, 225/45			Orig.-Verschr.
7,5 x 18	RC30	45	ZP576D6	88, 96	215/45, 225/45			
	RC32	55	-	88-96	215/45, 225/45, 235/45			Orig.-Verschr.
	B32	45	ZP576D6	88, 96 96, 134	215/45, 225/45 215/50, 235/45			
	B39	45	ZP576D6	88, 96	215/45, 225/45			
	AC-521	45	ZP580D6F +R	88, 96 96, 134	215/45, 225/45 215/50, 235/45			+ Red.Ringe 73,1-64,1
7,5 x 19	RC32 / RC34	45	-	88-96	225/35			Orig.-Verschr., ✖
	B39	45	ZP576D6	88, 96	225/40			
8 x 19	RC29	48	ZP576D6	88, 96	225/40, 235/40, 245/35			ab 235/40 ✖
	B24	50	ZP576D6	88, 96 96, 134	225/40, 235/40 225/40, 225/45, 235/40, 245/40			
8 x 20	B38	50	ZP576D6	88-134	225/35, 235/35			
weitere Dimensionen/Designs siehe Konfigurator								

HR-V NEU		ab 2021		RV	5/114,3	64,1	e6*2018/858*00063*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC32	55	-	79	225/50, 235/45, 245/45			Orig.-Verschr.
	B32	45	ZP576D6	79	225/50, 235/45			
	AC-MB6 / AC-M10	45	Artikel Nr. 98498	79	225/50, 235/45			Kit mit Artikelnummer 98498
	AC-521	45	ZP580D6F +R	79	225/50, 235/45			+ Red.Ringe 73,1-64,1
8 x 18	B24	48	ZP576D6	79	225/50, 235/45, 245/45			
	B36 / B42	45	ZP576D6	79	235/45			
	B44	45	ZP576D6	79	235/45			
	AC-M10	45	ZP580D6F +R	79	235/45			+ Red.Ringe 73,1-64,1
7,5 x 19	RC34	45	-	79	225/45			Orig.-Verschr.
	CA 26	45	ZP576D6	79	225/40, 225/45			
8 x 19	RC29	48	ZP576D6	79	225/40, 225/45, 235/40			
	B38	45	ZP576D6	79	225/40, 225/45			
	CA 19	45	ZP576D6	79	225/40, 225/45			
	CA 24	45	ZP576D6	79	225/45			
	Oxigin 29	50	ZP576D6	79	225/40, 225/45, 235/40			
8,5 x 19	B32 / B42	45	ZP576D6	79	225/40, 225/45			
	B36	44	ZP576D6	79	225/40, 225/45			
8 x 20	AC-521	45	ZP580D6F +R	79	225/35			+ Red.Ringe 73,1-64,1
8,5 x 20	RC29	45	ZP576D6	79	225/35			
	B42	45	ZP576D6	79	225/35			

Jazz (siehe Konfigurator)		ab 2015		GK	4/100	56,1	e6*2007/46*0162*..	
---------------------------	--	---------	--	----	-------	------	--------------------	--

Jazz Hybrid		Mitte 2020		GR	4/100	56,1	e6*2007/46*0415*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC30	50	-	72	185/60			Orig.-Verschr.
6 x 16	RC30	50	-	72, 79	185/55, 195/50			Orig.-Verschr.
	RC34	50	-	72-79	185/55, 195/50, 205/50			Orig.-Verschr.
		45	-	72-79	185/55			Orig.-Verschr.
6,5 x 16	RC24 / RC30	48	ZP428	72	185/55			

Jazz Crosstar Hybrid	ab 2020	GR	4/100	56,1	e6*2007/46*0415*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 16	RC34	45	-	72-79	185/60 , 195/55, 205/55, 215/50, 225/50	 Orig.-Verschr.
6,5 x 16	RC24	38	ZP428	72	185/60, 195/55	
7 x 17	B24	38	ZP428	72	205/45	
	B39	38	ZP428	72	205/45	

ZR-V e:HEV NEU	2023	RZ	5/114,3	64,1	e6*2018/858*00266*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	50	-	105	215/60 , 225/55, 225/60, 235/55	 Orig.-Verschr.
7,5 x 17	B24	48	ZP576D6	105	215/60, 225/55, 225/60, 235/55	
	CA 20	48	ZP576D6	105	215/60, 225/55, 225/60, 235/55	
7 x 18	RC27	50	-	105	215/55, 225/50, 225/55 , 235/50, 245/50	 Orig.-Verschr.
		45	-	105	215/55, 225/50, 225/55, 235/50	Orig.-Verschr.
7,5 x 18	B32	45	ZP576D6	105	215/55, 225/50, 225/55, 235/50	
	AC-M10	45	ZP580D6F +R	105	215/55, 225/50, 225/55, 235/50	+ Red.Ringe 73,1-64,1
	Oxigin 25	45	ZP576D6	105	215/55, 225/55, 245/45	mit Radhausverbreiterungen
8 x 18	RC27	50	-	105	225/50, 225/55, 235/50, 255/45	Orig.-Verschr.
	B24	48	ZP576D6	105	225/50, 225/55, 235/50, 255/45	
	B36 / B42	45	ZP576D6	105	225/50, 225/55	
	B44	45	ZP576D6	105	225/50, 225/55	
	AC-M10	45	ZP580D6F +R	105	225/50, 225/55	+ Red.Ringe 73,1-64,1
	CA 20	45	ZP576D6	105	225/50, 225/55	
7,5 x 19	CA 26	45	ZP576D6	105	215/50, 225/45, 225/50, 235/45, 245/45	
8 x 19	CA 17	40	ZP576D6	105	225/45	
	CA 19	45	ZP576D6	105	225/45, 225/50, 235/45, 245/40, 245/45	
	Oxigin 29	40	ZP576D6	105	225/45, 235/45	
		50	ZP576D6	105	225/45, 225/50, 235/45, 245/40, 245/45	
8,5 x 19	B32 / B42	45	ZP576D6	105	225/45, 235/45	
	B36	44	ZP576D6	105	225/45, 235/45	
	B44	40	ZP576D6	105	225/45	
8,5 x 20	B42	45	ZP576D6	105	225/40, 235/40	
	B44	40	ZP576D6	105	225/40	
9 x 20	CA 23	45	ZP576D6	105	225/40	

Hyundai

Hyundai		Baujahr	Typ	LK/LZ	Nabe		
Bayon		ab 2021	BC3	4/100	54,1	e5*2007/46*0121*..	
Sensor - Brocksens 5							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC30	47	ZP422D6F	62-88	185/65, 195/60, 205/55, 205/60, 225/50		15/16 Zoll Serie
	RC24	40	ZP422	62-88	185/65, 195/60, 205/55, 205/60		15/16 Zoll Serie
	RC30	46	ZP422D6F	62-88	185/65, 195/60, 205/55, 205/60		15/16 Zoll Serie
6 x 16	RC30	50	ZP422D6F	62-88	185/55, 185/60, 195/55, 205/50		15/16 Zoll Serie
	RC34	50	-	62-88	185/60, 195/50, 195/55, 205/50, 205/55, 215/50, 225/50		Orig.-Verschr., auch Hybrid
	RC30	45	ZP422D6F	62-88	185/55, 185/60, 195/55, 205/50		15/16 Zoll Serie
	RC34	45	-	58-88	185/60, 195/50, 195/55, 205/50, 205/55, 215/50		Orig.-Verschr., auch Hybrid
6,5 x 16	RC24	48	ZP422	62-88	185/55, 185/60, 195/55, 205/50		15/16 Zoll Serie
	RC30	45	ZP422D6F	62-88	185/55, 185/60, 195/55, 205/50		15/16 Zoll Serie
	RC34	45	-	62-88	185/60, 195/50, 195/55, 205/50, 205/55, 215/50		Orig.-Verschr., auch Hybrid
		48	-	58-88	185/60, 195/50, 195/55, 205/50, 205/55, 215/50		Orig.-Verschr., auch Hybrid
6,5 x 17	RC34	50	-	74-88	205/55		Orig.-Verschr., auch Hybrid
				58-88	185/50, 195/50, 205/45		
		43	-	58-88	185/50, 195/50, 205/45		Orig.-Verschr., auch Hybrid
				74-88	205/55		Orig.-Verschr., auch Hybrid
	RC14 EL	45	ZP422D6F	62-88	195/45, 205/45		15/16 Zoll Serie, RLP, SVR
				73-88	205/50, 205/55		17 Zoll Serie, RLP, SVR
7 x 17	RC34	50	-	62-88	195/50, 205/45, 215/45		Orig.-Verschr., auch Hybrid
	B24	45	ZP422	62-88	195/45, 205/45, 215/40, 215/45		15/16 Zoll Serie
				73-88	205/50, 205/55, 225/45		17 Zoll Serie
	B39	44	ZP422	62-88	195/45, 205/45, 215/40, 215/45		15/16 Zoll Serie
7,5 x 18	B39	45	ZP422	62-88	205/40, 215/35		15/16 Zoll Serie
				73-88	205/45, 215/45		17 Zoll Serie
Genesis (siehe Konfigurator)							
		2014	DH		5/114,3	67,1	e4*KS07/46*0018*..

Genesis GV60 (siehe Konfigurator)	im Laufe 2023	JW	5/114,3	67,1	e4*2018/858*00060*..
-----------------------------------	---------------	----	---------	------	----------------------

I10 (siehe Konfigurator)	ab 2013	IA	4/100	54,1	e11*2007/46*1008*...., e13*2007/46*1602*..., e5*2007/46*1086*..
--------------------------	---------	----	-------	------	---

I10 (III) NEU	ab 02.2020	AC3	4/100	54,1	e5*2007/46*0090*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
5,5 x 15	RC19	36	ZP422D6F	49-74	175/55, 185/55	incl. N-Line
6 x 15	RC24	40	ZP422	49-74	175/55, 185/55	incl. N-Line
		42+46	ZP422D6F	49-74	175/55, 185/55, 195/50	incl. N-Line
		46	ZP422D6F	49-74	175/55, 185/55, 195/50	incl. N-Line
	RC30	47	ZP422D6F	49-74	175/55, 185/55	
6 x 16	RC30	45	ZP422D6F	49-74	175/50, 195/45	incl. N-Line
	RC34	45+49+50	-	49-62	175/50, 195/45	Orig.-Verschr., auch N-Line
6,5 x 16	RC34	48	-	46-74	195/45	 Orig.-Verschr., auch N-Line
				46-74	195/45, 205/45	
	RC24	48	ZP422	49-74	195/45	 incl. N-Line
	RC30	48	ZP422D6	49-74	195/45	 incl. N-Line
6,5 x 17	RC34	45	ZP422D6F	49-74	195/45, 205/45	incl. N-Line
		43	-	46-74	195/40	Orig.-Verschr., auch N-Line
	RC14 EL	45	ZP422D6F	49-74	195/40	incl. N-Line, RLP, SVR
7 x 17	RC34	50	-	49-74	195/40	Orig.-Verschr.
	B24	45	ZP422	49-74	195/40	
	B39	44	ZP422	49-62	195/40	

I20 (siehe Konfigurator)	ab 2014	GB	4/100	54,1	e11*2007/46*1600*...., e13*2007/46*1603*..., e5*2007/46*1087*..
--------------------------	---------	----	-------	------	---

I20 Active (siehe Konfigurator)	ab 01/2016	GB, GB-HME	4/100	54,1	e11*2007/46*1600*...., e13*2007/46*1603*..., e5*2007/46*1087*..
---------------------------------	------------	------------	-------	------	---

I20 III	ab 2020	BC3	4/100	54,1	e5*2007/46*0121*...
Sensor - Brocksens 5					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC30	47	ZP422D6F	61-88	185/65	
	RC24	40	ZP422	61-88	185/65	
	RC30	46	ZP422D6F	61-88	185/65, 195/60	
6 x 16	RC30	50	ZP422D6F	61-88	185/55, 195/55, 205/50	 Orig.-Verschr.
	RC34	50	-	62-88	185/55, 185/60, 195/55, 205/50, 215/50	
	RC34	45	-	58-88	185/55, 185/60, 195/55, 205/50	Orig.-Verschr.
		49	-	62-88	185/55, 185/60, 195/55, 205/50, 215/50	Orig.-Verschr.
	RC24	48	ZP422	61-88	185/55, 195/55	

6,5 x 16	RC30	45	ZP422D6F	61-88	185/55, 195/55		
		48	ZP422	61-88	185/55, 195/55		
	RC34	45	-	62-88	185/55, 185/60, 195/55		Orig.-Verschr.
		48	-	58-88	185/55, 185/60, 195/55, 205/50		Orig.-Verschr.
6,5 x 17	RC34	43	-	58-88	185/50, 205/45		Orig.-Verschr.
		50	-	58-88	185/50, 195/50, 205/45		Orig.-Verschr.
	RC14 EL	45	ZP422D6F	61-88	195/45, 205/45		R.LP, SVR
7 x 17	RC34	50	-	62-88	195/50, 205/45, 215/45		Orig.-Verschr.
	B24	45	ZP422	61-88	195/45, 205/45		
	B39	44	ZP422	61-88	195/45		

I20 N		ab April 2021		BC3	5/114,3	67,1	e5*2007/46*0121*...	
Sensor - Brocksens 5								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC30	53	ZP580D8F	150	215/40			
	B32	53	ZP580D6F	150	215/40			es sind nur spezielle Gewebeschneeketten zulässig!
	RC30	49,5+ 50,5	ZP580D6F	150	215/40			
	RC32	51+52	-	150	215/40			Orig.-Verschr.
7,5 x 19	RC32	50,5+51	-	150	215/35			Orig.-Verschr.
		53	-	150	215/35			Orig.-Verschr.
	RC34	49,5	-	150	215/35			Orig.-Verschr.
		51+54,5	-	150	215/35			Orig.-Verschr.
	B32	53	ZP580D6F	150	215/35			

I30		ab 02.2017		PDE	5/114,3	67,1	e11*2007/46*3807*..., e5*2007/46*1075*..		
Sensor - Brocksens 5									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
6 x 15	RC30	46	ZP580D6F	70-103	195/65, 205/60, 215/60			nicht für elektr. Parkbremse, nur Bremse 280mm auch e5*2007/46*1075*..	
	RC24	45	ZP580	70-117	195/65, 205/60, 215/60			incl. Facelift 2020, nicht für elektr. Parkbremse, nur Bremse 280mm	
	RC27	43	ZP580D6F	70-103	195/65, 205/60, 215/60			nicht für elektr. Parkbremse, nur Bremse 280mm	
	RC30	48	ZP580D6F	70-103	195/65, 205/60, 215/60			nicht für elektr. Parkbremse, nur Bremse 280mm	
6,5 x 15	RC28	45	ZP580	70-103	195/65, 205/60, 215/60			nicht für elektr. Parkbremse, nur Bremse 280mm	
	RC27	50	ZP580D6F	70-117	195/55, 195/60, 205/55, 215/50, 225/50			incl. Facelift 2020	
6,5 x 16	RC30	50	ZP580D6F	70-118	205/55			incl. Facelift 2020	
	RC32	50	-	70-117	195/55, 195/60, 205/55, 215/50			Orig.-Verschr., auch für Hybrid	
	RC34	50	-	70-118	195/55, 195/60, 205/55, 215/50			Orig.-Verschr., auch für Hybrid	
	RC24	47	ZP580D6F	70-117	195/55, 195/60, 205/55, 215/50			incl. Facelift 2020	
		48	ZP580	70-117	195/55, 195/60, 205/55, 215/50, 225/50			incl. Facelift 2020	
		50	ZP580D6F	70-118	195/55, 195/60, 205/55, 215/50, 225/50			incl. Facelift 2020, nicht Bremse 305mm, ET50 gibt es nur in SKM	
	RC27	45	ZP580	70-117	195/55, 195/60, 205/55, 215/50			incl. Facelift 2020	
	RC30	47	ZP580D6F	70-103	195/55, 195/60, 205/55, 215/50				
		48	ZP580D6F	70-117	195/55, 195/60, 205/55, 215/50, 225/50			incl. Facelift 2020	
	6,5 x 17	RC32	45	-	70-118	195/55, 195/60, 205/55			Orig.-Verschr.
			47,5	-	70-103	195/55, 195/60, 205/55, 215/50			Orig.-Verschr.
		RC34	44+45	-	70-118	195/55, 195/60, 205/55			Orig.-Verschr.
		RC27	51	ZP580D6F	70-117	205/50			incl. Facelift 2020, nicht Bremse 305mm
7 x 17	RC32	53	-	70-118	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
	RC34	53	-	70-118	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
	RC27	45	ZP580	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	
		47	ZP580D6F	70-117	205/50, 215/45, 225/45			incl. Facelift 2020	
		50	ZP580D6F	70-103	205/50, 215/45, 225/45				
	RC30	47	ZP580D6F	70-117	205/50, 215/45, 225/45			incl. Facelift 2020	
		50+51	ZP580D6F	70-117	205/50, 215/45, 225/45			incl. Facelift 2020, ET51 nicht Bremse 305mm	
	RC32	47	-	70-118	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
		48,5	-	70-117	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
		50	-	70-118	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
	RC34	47+50	-	70-118	195/50, 205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
	B39	45	ZP580	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	
		50	ZP580D6F	70-118	205/50, 215/45, 225/45			incl. Facelift 2020, nur Bremse 304mm	
	RC24	45	ZP580	70-103	215/45				
		50	ZP580	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	
			ZP580D6F	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	
	RC27	46	ZP580D6F	70-103	205/45, 215/45				
		52,5	ZP580D6F	70-117	205/50, 215/45, 225/45			incl. Facelift 2020	
	RC28	45	ZP580	70-118	215/45			incl. Facelift 2020	
	RC29	48	ZP580	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	
	RC32	46	-	70-118	205/45, 215/45				
		52,5	-	70-103	205/45, 205/50, 215/45, 225/45			Orig.-Verschr.	
	B24	48	ZP580	70-118	205/50, 215/45, 225/45			incl. Facelift 2020	

7 x 18	B36	46	ZP580	70-118	215/45		incl. Facelift 2020
	RC32	45	-	70-118	205/40, 205/45, 215/40		Orig.-Verschr., auch für Hybrid
		48,5	-	70-117	205/40, 205/45, 215/40		Orig.-Verschr., auch für Hybrid
		51	-	70-117	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC30	53	ZP580D6F	70-118	225/40		nicht Bremse 305mm
	RC32	55	-	74-118	225/40		Orig.-Verschr., ET55 ist nur in den Farben SBM u. HGVP erhältlich!
			-	70-103	205/40, 205/45, 215/40, 225/35, 225/40		
	B32	53	ZP580D8F	70-118	205/45, 215/40, 225/35, 225/40		incl. Facelift 2020, nicht Bremse 305mm
		55	ZP580D6F	70-103	205/45, 215/40, 225/35, 225/40		nur Bremse 304mm
	RC30	50,5	ZP580D6F	70-118	205/45, 215/40, 225/35, 225/40		incl. Facelift 2020
		50+52,5	ZP580D6F	70-103	205/45, 215/40, 225/35, 225/40		
		55	ZP580D6F	70-103	205/45, 215/40, 225/35, 225/40		nicht Bremse 305mm
	RC32	51+52	-	70-118	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	RC34	49,5	-	71-118	225/40		Orig.-Verschr.
		53	-	71-118	225/40		Orig.-Verschr.
	B32	49,5	ZP580D6F	70-117	205/45, 215/40, 225/35, 225/40		incl. Facelift 2020
7,5 x 19	RC32	50,5+51+53	-	70-118	225/35		Orig.-Verschr.
	RC34	49,5+51	-	71-118	225/35		Orig.-Verschr.
		54,5	-	70-118	225/35		Orig.-Verschr.
	B32	49,5	ZP580D6F	70-118	225/35		incl. Facelift 2020
		53	ZP580D6F	70-118	225/35		nur Bremse 305mm
	B39	50	ZP580D6F	70-103	225/35		nur Bremse 304mm
	B39	50	ZP580D6F	70-103	225/35		nur Bremse 304mm

weitere Dimensionen/Designs siehe Konfigurator

I30 N		ab 2017		PDE		5/114,3		67,1		e11*2007/46*3807*..., e5*2007/46*1075*..	
Sensor - Brocksens 5											
Dimension		Design	ET	KIT	KW	Reifendimension			Info		
7,5 x 18	RC30		53	ZP580D8F	184	225/40				incl. Facelift 2020, auch Fastback	
	B32		53	ZP580D8F	184	225/40				incl. Facelift 2020, auch Fastback	
	RC30	50+50,5	ZP580D6F	184	225/40				incl. Facelift 2020, auch Fastback		
		49,5+55	ZP580D6F	184	225/40				incl. Facelift 2020, auch Fastback		
	RC32		52+55	-	184	225/40				Orig.-Verschr., ET55 auch Fastback, ET55 ist nur in den Farben SBM u. HGVP erhältlich!	
	B32	49,5	ZP580D6F	184	225/40				incl. Facelift 2020, auch Fastback		
		50,5	ZP580D6F	184	225/40						
		55	ZP580D6F	184	225/40				auch Fastback		
	B39	45	ZP580	184	225/40				auch Fastback		
		50	ZP580D6F	184	225/40				incl. Facelift 2020, auch Fastback		
	AC-MB6		45	Artikel Nr. 98499	184	225/40				incl. Facelift 2020, Kit mit Artikelnummer - 98499	
	AC-521		45	ZP580D6F +R	184	225/40				incl. Facelift 2020, + Red.Ringe 73,1-67,1 , auch Fastback	
8 x 18	RC34		50	-	184	225/40				Orig.-Verschr., auch Fastback	
	B24		48	ZP580	184	225/40				incl. Facelift 2020, auch Fastback	
	B38		49	ZP580	184	225/40				incl. Facelift 2020, auch Fastback	
7,5 x 19	RC32		50,5+51+53	-	184	225/35				Orig.-Verschr., auch Fastback	
	RC34	49,5	-	184	225/35				Orig.-Verschr., auch Fastback		
		51+54,5	-	184	225/35				Orig.-Verschr., auch Fastback		
	B32	45	ZP580D6F	184	225/35				incl. Facelift 2020, auch Fastback		
		49,5+53	ZP580D6F	184	225/35				incl. Facelift 2020, auch Fastback		
	AC-521		45	ZP580D6F +R	184	225/35				incl. Facelift 2020, + Red.Ringe 73,1-67,1 , auch Fastback	
8 x 19	RC32		55	ZP580D6F	184	225/35, 235/35				i.V.	
	RC34		55	-	184	225/35, 235/35				Orig.-Verschr., auch Fastback	
	B24		50	ZP580	184	225/35				auch Fastback	
	B40		53	ZP580D6F	184	225/35				incl. Facelift 2020, auch Fastback	
	B43		55	ZP580D6F	184	225/35, 235/35				incl. Facelift 2020, auch Fastback	
	Oxigin 29		50	ZP580	184	225/35, 235/35				incl. Facelift 2020, auch Fastback	

I30 N Performance		ab 2017		PDE	5/114,3	67,1	e11*2007/46*3807*...., e5+2007/46+1075+...	
Sensor - Brocksens 5								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
	RC30	53	ZP580D8F	202, 206	225/40M+S			incl. Facelift 2020, auch Fastback
	B32	53	ZP580D8F	202, 206	225/40 M+S			incl. Facelift 2020, auch Fastback
		50+52,5	ZP580D6F	202	225/40			nur M+S

7,5 x 18	RC30	50,5	ZP580D6F	202, 206	225/40		nur M+S, incl. Facelift 2020
		49,5+55	ZP580D6F	202, 206	225/40		nur M+S, incl. Facelift 2020
	RC32	52+55	-	202	225/40		Orig.-Verschr., ET55 auch Fastback, ET55 ist nur in den Farben SBM u. HGVP erhältlich!
	B32	49,5	ZP580D6F	202	225/40		incl. Facelift 2020, nur M+S, auch Fastback
		50,5	ZP580D6F	202	225/40		nur M+S, auch Fastback
		55	ZP580D6F	202	225/40		nur M+S, auch Fastback
	B39	45	ZP580	202, 206	225/40		incl. Facelift 2020, nur M+S, auch Fastback
		50	ZP580D6F	202, 206	225/40		incl. Facelift 2020, nur M+S, auch Fastback
	AC-MB6	45	Artikel Nr. 98499	202, 206	225/40		incl. Facelift 2020, nur M+S, Kit mit Artikelnummer - 98499
	AC-521	45	ZP580D6F +R	202, 206	225/40		incl. Facelift 2020, nur M+S, + Red.Ringe 73,1-67,1 , auch Fastback
8 x 18	RC34	50	-	202	225/40		Orig.-Verschr., auch Fastback
	B24	48	ZP580	202	225/40		incl. Facelift 2020, nur M+S, auch Fastback
	B38	49	ZP580	202	225/40		incl. Facelift 2020, auch Fastback
7,5 x 19	RC32	50,5+51+53	-	202-206	225/35		Orig.-Verschr., auch Fastback
	RC34	49,5	-	202-206	225/35		Orig.-Verschr., auch Fastback
		51+54,5	-	202-206	225/35		Orig.-Verschr., auch Fastback
	B32	45	ZP580D6F	202, 206	225/35		incl. Facelift 2020, auch Fastback
		49,5+53	ZP580D6F	202, 206	225/35		incl. Facelift 2020, auch Fastback
	B39	45	ZP580	202	225/35		nur Bremse 345mm
		50	ZP580D6F	202	225/35		nur Bremse 345mm
	AC-521	45	ZP580D6F +R	202, 206	225/35		incl. Facelift 2020, nur M+S, + Red.Ringe 73,1-67,1 , auch Fastback
8 x 19	RC32	55	-	202-206	225/35, 235/35		Orig.-Verschr., auch Fastback
	RC34	55	-	202-206	225/35, 235/35		Orig.-Verschr., auch Fastback
	B43	55	ZP580D6F	202, 206	235/35		auch Fastback, incl. FL2020
	B24	50	ZP580	202	225/35M+S, 235/35		auch Fastback
	B40	53	ZP580D6F	202	225/35M+S, 235/35		incl. Facelift 2020, auch Fastback
	Oxigin 29	50	ZP580	202, 206	225/35M+S, 235/35		incl. Facelift 2020, auch Fastback

I30 Fastback	ab 2017	PDE	5/114,3	67,1	e11*2007/46*3807*03-..., e5+2007/46+1075+...
Sensor - Brocksens 5					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	50	ZP580D6F	85-117	205/55, 215/50, 225/50	 incl. Facelift 2020
	RC30	50	ZP580D6F	85-118	205/55	 incl. Facelift 2020
	RC24	47	ZP580D6F	85-117	205/55, 215/50	incl. Facelift 2020
		48	ZP580	85-117	205/55, 215/50	incl. Facelift 2020
		50	ZP580D6F	85-118	205/55, 215/50, 225/50	 incl. Facelift 2020, nicht Bremse 305mm, ET50 gibt es nur in SKM
	RC27	45	ZP580	85-117	205/55	incl. Facelift 2020
		50	ZP580	85-118	205/55, 215/50, 225/50	incl. Facelift 2020
	RC30	47	ZP580D6F	88, 103	205/55, 215/50	
		48	ZP580D6F	85-117	205/55, 215/50	incl. Facelift 2020
		50	ZP580 od. ZP580D6F	85-103	205/55, 215/50, 225/50	
	RC34	45	-	70-118	195/55, 195/60, 205/55	Orig.-Verschr.
		50	-	70-118	195/55, 195/60, 205/55, 215/50	 Orig.-Verschr.
6,5 x 17	RC27	51	ZP580D6F	85-117	205/50	incl. Facelift 2020, nicht Bremse 305mm
7 x 17	RC27	45	ZP580	85-118	205/50, 215/45, 225/45	incl. Facelift 2020
		47	ZP580D6F	85-117	205/50, 215/45, 225/45	incl. Facelift 2020
		50	ZP580D6F	85-103	205/50, 215/45, 225/45	ET50 nicht Bremse 305mm
	RC30	47+51	ZP580D6F	85-117	205/50, 215/45, 225/45	incl. Facelift 2020, ET51 nicht Bremse 305mm
		50	ZP580D6F	85-117	205/50, 215/45, 225/45	incl. Facelift 2020
	RC32	47	-	70-117	195/50, 205/45, 205/50, 215/45, 225/45	Orig.-Verschr.
	B39	45	ZP580	85-118	205/50, 215/45, 225/45	incl. Facelift 2020
		50	ZP580D6F	85-118	205/50, 215/45, 225/45	incl. Facelift 2020, nicht Bremse 305mm
7,5 x 17	RC24	45	ZP580	88, 103	215/45	
		50	ZP580	85-118	205/50, 215/45, 225/45	incl. Facelift 2020
			ZP580D6F	85-118	205/50, 215/45, 225/45	incl. Facelift 2020
	RC28	45	ZP580	85-118	215/45	incl. Facelift 2020
	RC27	52,5	ZP580D6F	85-117	205/50, 215/45, 225/45	incl. Facelift 2020
	RC29	48	ZP580	85-118	205/50, 215/45, 225/45	incl. Facelift 2020
	RC30	47	-	88-103	205/50, 215/45, 225/45	Orig.-Verschr.
	RC32	52,5	-	70-103	205/45, 205/50, 215/45, 225/45	Orig.-Verschr.
	B24	48	ZP580	85-118	205/50, 215/45, 225/45	
7 x 18	B36	46	ZP580	85-118	215/45	incl. Facelift 2020
	RC32	45+51	-	70-103	205/40, 205/45, 215/40	Orig.-Verschr.
	RC30	53	ZP580D6F	85-118	225/40	 incl. Facelift 2020, nicht Bremse 305mm
		55	ZP580D6F	85-103	205/45, 215/40, 225/35, 225/40	 nicht Bremse 305mm, incl FL2020
	B32	53	ZP580D8F	85-118	205/45, 215/40, 225/35, 225/40	 incl. Facelift 2020, nicht Bremse 305mm
	RC30	49,5+50	ZP580D6F	85-118	205/45, 215/40, 225/35, 225/40	incl. Facelift 2020

7,5 x 18	RC32	55	-	88-103	225/40		Orig.-Verschr., ET55 ist nur in den Farben SBM u. HGVP erhältlich!
	B32	49,5	ZP580D6F	85-117	205/45, 215/40, 225/35, 225/40		
		50,5	ZP580D6F	85-103	205/45, 215/40, 225/35, 225/40		
		55	ZP580D6F	85-103	205/45, 215/40, 225/35, 225/40		nicht Bremse 305mm
	B39	45	ZP580	85-118	205/45, 215/40		incl. Facelift 2020
		50	ZP580D6F	85-118	205/45, 215/40, 225/35, 225/40		incl. Facelift 2020
	AC-MB6	45	Artikel Nr. 98499	85-118	205/45, 215/40		incl. Facelift 2020, Kit mit Artikelnummer - 98499
8 x 18	AC-521	45	ZP580D6F +R	85-118	205/45, 215/40		incl. Facelift 2020, + Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	70-118	205/40, 205/45		
	RC34	50	-	70-117	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 19	B24	48	ZP580	85-103	215/40		
	B38	49	ZP580	88, 103	215/40, 225/35, 225/40, 235/35		ab 225/35 ✖
	RC32	53	-	88-103	225/35		Orig.-Verschr.
8 x 19	B40	49,5	ZP580D6F	85-118	225/35		incl. Facelift 2020
		53	ZP580D6F	85-117	225/35		incl. Facelift 2020, nicht Bremse 305mm

Inster NEU		2025		AX1	4/100	54,1	e4*2018/858*00225*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	45	ZP422D6F	24, 28	185/55, 185/60		
6,5 x 17	RC34	43+49	-	24-28	185/50, 195/45, 205/45		Orig.-Verschr.

Ioniq Hybrid/Elektro (siehe Konfigurator)		ab 04.2016	AE	5/114,3	67,1	e4*2007/46*1157*..
---	--	------------	----	---------	------	--------------------

Ioniq Elektro		ab MJ 2020		AE	5/114,3	67,1	e4*2007/46*1157*10-..	
Sensor - Continental - Artikelnummer 97318								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC27	50	ZP580D6F	25 (100)	205/55, 205/60, 215/55			
	RC30	50	ZP580D6F	25 (100)	205/60			Ausführung "M3N"
	RC34	50	-	25 (100)	205/60, 215/55			Orig.-Verschr.
	RC24	48	ZP580	25 (100)	205/55, 205/60, 215/55			
		47+50	ZP580D6F	25 (100)	205/55, 205/60, 215/55			ET50 ist original ET
	RC27	45	ZP580	25 (100)	205/55, 205/60			
		50	ZP580	25 (100)	205/55, 215/50, 225/50			
	RC30	45	ZP580D6F	25 (100)	205/55, 205/60			
			ZP580	25 (100)	205/55, 205/60			
	RC32	48	ZP580D6F	25 (100)	205/55, 205/60, 215/55			
		47,5	-	25 (100)	205/55, 215/50			Orig.-Verschr.
	RC34	50	-	25 (100)	205/55, 215/50			Orig.-Verschr.
7 x 17		45	-	25 (100)	205/55		Orig.-Verschr.	
6,5 x 17	RC27	51	ZP580D6F	25 (100)	205/50, 205/55			
	RC27	45	ZP580	25 (100)	205/50, 205/55, 225/45			
		47+50	ZP580D6F	25 (100)	205/50, 205/55			
	RC30	45	ZP580D6F	25 (100)	205/50, 205/55, 225/45			
			ZP580	25 (100)	205/50, 205/55, 225/45			
	RC32	47+50+51	ZP580D6F	25 (100)	205/50, 205/55, 225/45			
		47	-	25 (100)	205/50, 215/45, 225/45			Orig.-Verschr.
	RC34	50	-	25 (100)	205/50, 225/45			Orig.-Verschr.
		50	-	25	215/45, 225/45			Orig.-Verschr.
	B39	45	ZP580	25 (100)	205/50, 205/55, 225/45			
		50	ZP580D6F	25 (100)	205/50, 205/55, 225/45			
	7,5 x 17	RC24	50	ZP580	25 (100)	205/50, 205/55, 225/45		
50			ZP580D6F	25 (100)	205/50, 205/55, 225/45			
7 x 18	RC29	48	ZP580	25 (100)	205/50, 205/55, 225/45			
	RC32	45+48,5	-	25 (100)	215/40			Orig.-Verschr.
7,5 x 18	RC30	49,5	ZP580D6F	25 (100)	205/45, 215/40, 215/45, 225/40			
	B32	45	ZP580	25 (100)	205/45, 215/40, 215/45			
		49,5+50,5	ZP580D6F	25 (100)	205/45, 215/40, 215/45, 225/40			
	B39	45	ZP580	25 (100)	205/45, 215/40, 215/45			
		50	ZP580D6F	25 (100)	205/45, 215/40, 215/45, 225/40			
	AC-521	45	ZP580D6F+R	25 (100)	205/45, 215/40, 215/45			+ Red.Ringe 73,1-67,1
8 x 18	B38	49	ZP580	25 (100)	215/40, 215/45			
7,5 x 19	B32	49,5	ZP580D6F	25 (100)	225/35			

Ioniq 5				ab Juni 2021	NE	5/114,3	67,1	e9*2018/858*11054*..
Sensor - Brocksens 7								
Dimension	Design	ET	KIT	KW	Reifendimension			Info

7,5 x 19	RC32	49,5	-	42-81	235/55, 245/50		Orig.-Verschr.
	RC34	49,5	-	42-81	235/55, 245/50		Orig.-Verschr.
	RC32	51	-	42-81	235/55, 245/50		Orig.-Verschr.
		53	-	42-81	235/55, 245/50, 255/50		Orig.-Verschr.
	RC34	49,5+51	-	42-81	235/55, 245/50		Orig.-Verschr.
		54,5	-	42-76	235/55, 245/50, 255/50		Orig.-Verschr.
	B32	45	ZP580D6F	42-76	235/50, 235/55		
8 x 19	AC-521	45	ZP580D6F +R	42-81	235/50, 235/55		+ Red.Ringe 73,1-67,1
	RC27	47	ZP580D6F	42-76	235/50, 235/55		
	RC29	48	ZP580	42-81	235/50, 235/55		
	RC32	55	-	42-76	235/55, 245/50		Orig.-Verschr.
	RC34	55	-	42-81	235/55, 245/50		Orig.-Verschr.
8,5 x 20	Oxigin 29	50	ZP580	42-81	235/50, 235/55, 245/50		
	B43	54,5	ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45, 265/45		
	RC29	45	ZP580	42-76	235/45, 245/45		
	RC36	54	ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45, 265/45		
9 x 20	B43	53,5	ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45, 265/45		
	B37	43	ZP580	42-76	235/45		
	B40	46	ZP580D6F	42-81	235/45		
	CA 20 / CA 23	45	ZP580	42-81	235/45		
8,5 x 21	B41	43,5	-	42-81	235/45		Orig.-Verschr.
		47	ZP580	42-81	235/45		
	B43	43,5	ZP580D6F	42-81	235/45		

Ioniq 5 N
NEU
Frühjahr 2024
NE
5/114,3
67,1
e9*2018/858*11054*..

Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 21	B43	45	-	159 (478)	275/35, 285/30		Orig.-Verschr.

Ioniq 6
NEU
4. Quartal 2022
CE
5/114,3
67,1
e4*2018/858*00145*..

Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC32	51	-	37-81	225/55, 235/50		Orig.-Verschr.
	RC34	51	-	37-81	225/55		Orig.-Verschr.
	RC32	52	-	37-81	225/55, 235/50, 245/50		Orig.-Verschr.
	RC34	45	-	37-81	225/55		Orig.-Verschr.
		53	-	37-81	225/55, 235/50, 245/50		Orig.-Verschr.
	B32	45	ZP580	37-81	225/55		
		50,5	ZP580D6F	37-81	225/55, 235/50		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	37-81	225/55		Kit mit Artikelnummer 98499
8 x 18	Oxigin 25	45	ZP580	37-81	225/55		
	RC34	50	-	37-81	225/55		Orig.-Verschr.
7,5 x 19	B24	48	ZP580	37-81	225/55		
	RC32	45+50,5	-	37-81	225/50, 235/45, 245/45		Orig.-Verschr.
		53	-	37-81	225/50, 235/45, 245/45		Orig.-Verschr.
8 x 19	RC34	49,5+51	-	37-81	225/50, 235/45, 245/45		Orig.-Verschr.
	RC34	55	-	37-81	225/50, 235/45, 245/45		Orig.-Verschr.
	RC29	48	ZP580	37-81	225/45, 225/50, 235/45, 245/45		
	CA 19	45	ZP580	37-81	235/45		
	CA 24	45	ZP580	37-81	235/45		
8,5 x 19	Oxigin 29	50	ZP580	37-81	225/45, 225/50, 235/45, 245/45		
	B37	45	ZP580	37-81	225/45		
	B43	46,5	ZP580D6F	37-81	225/45, 235/45		
8,5 x 20	CA 20	45	ZP580	37-81	225/45		
	B43	53,5	ZP580D6F	37-81	235/40, 245/40, 255/35, 255/40		Orig.-Verschr.
	RC36	54	ZP580D6F	37-81	235/40, 245/40, 255/35, 255/40		
	B43	54	ZP580D6F	37-81	235/40, 245/40, 255/35, 255/40		

Kona
ab 10.2017
OS
5/114,3
67,1
e4*2007/46*1259*..

Sensor - Brocksens 5							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
	RC30	44	-	85-146	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., Bremse max. 280mm, incl. Facelift 2021
	RC32	44	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., nicht Bremse 320x28mm, auch für Hybrid
	RC34	44	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., nicht Bremse 320x28mm, auch für Hybrid, Frontantrieb
			-	100-146	205/60, 215/60, 225/55, 235/55		Orig.-Verschr., Allrad, nicht Bremse 320x28mm
			ZP580	85-100	205/60, 215/55, 215/60, 225/55		Frontantrieb, Bremse max. 280mm
	RC24	47	-	85-146	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., incl. Facelift 2021, ET47 gibt es nur in silber!
		48	ZP580	85-146	205/60, 215/55, 215/60, 225/55		incl. Facelift 2021

6,5 x 16		50	-	85-146	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., incl. Facelift 2021, ET50 gibt es nur in SKM!
	RC27	45	ZP580	85-100	205/60, 215/55, 215/60, 225/55		Front- u. Allradantrieb
		47	-	85-100	205/60, 215/55, 215/60, 225/55		Orig.-Verschr.
		50	ZP580	85-146	205/60, 215/55, 215/60, 225/55		incl. Facelift 2021
	RC32	45	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb, nicht Bremse 320x28mm
				100-146	215/60, 225/55, 235/55		Orig.-Verschr., Allrad, nicht Bremse 320x28mm
		47,5	-	77-130	205/60, 205/65, 215/55, 215/60, 225/55, 235/55		Orig.-Verschr., Frontantrieb
		50	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., Frontantrieb, auch für Hybrid, nicht Bremse 320x28mm,
	RC34	45	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb, auch für Hybrid, nicht Bremse 320x28mm,
			-	100-146	215/60, 225/55, 235/55		Orig.-Verschr., Allrad, auch für Hybrid, nicht Bremse 320x28mm,
50		-	77-146	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr. Frontantrieb, nicht Bremse 320x28mm	
	CA 20	45	ZP580	85-146	205/60, 215/55, 215/60, 225/55		
6,5 x 17	RC27	51	-	85-130	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., auch Allrad
7 x 17	RC27		-	85-146	215/55		Orig.-Verschr., incl. Facelift 2021, auch Allrad
		50	-	85-146	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2021, Frontantrieb
	RC30		-	85-146	205/55, 215/50, 215/55, 225/50, 235/60		Orig.-Verschr., incl. Facelift 2021, Allrad
		50	-	85-130	215/50, 215/55 , 225/50, 235/50		Orig.-Verschr., auch Allrad
	RC32		-	85-100	205/55		Orig.-Verschr., auch Allrad
			-	85-146	215/55		Orig.-Verschr.
		50	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Frontantrieb
		-	100-146	215/50, 215/55, 225/50	Orig.-Verschr., Allrad		
	RC34		-	85-146	215/55		Orig.-Verschr.
		50	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Frontantrieb
			-	100-146	215/50, 215/55, 225/50		Orig.-Verschr., Allrad
	B39		-	85-130	215/50, 215/55 , 225/50		
		50	-	85-100	205/55		Orig.-Verschr., Frontantrieb
			-	100, 130	215/50, 215/55 , 225/50, 235/50		
			-	100	205/55		Orig.-Verschr., Allrad
	RC27	47	-	88	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Frontantrieb
			-	130	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Allrad
	RC30	47+51	-	85-130	215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2021
	RC32	43,5+45	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Frontantrieb
		+47	-	100-146	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., Allrad
48,5		-	77-130	205/50, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Frontantrieb	
		-	100-130	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Allrad, ET45 bei 235/50 ✖	
RC34	47	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Frontantrieb	
		-	100-146	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Allrad	
7,5 x 17	RC24	50	-	85-146	205/55, 215/50, 215/55, 225/50, 235/45		Orig.-Verschr., incl. Facelift 2021, auch Allrad
		50	ZP580	85-146	205/55, 215/50, 215/55, 225/50, 235/45		incl. Facelift 2021
	RC27	46	ZP580D6F	85-130	205/50, 205/55, 205/60, 215/50, 215/55, 235/45		
		52,5	-	85-130	205/50, 205/55, 205/60, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC28	45	ZP580	85-146	205/55, 215/50, 215/55, 235/45		incl. Facelift 2021, Frontantrieb
			-	100-146	215/50, 215/55, 225/50, 235/45		incl. Facelift 2021, Allrad
	RC29	48	ZP580	85-146	205/55, 215/50, 215/55, 225/50, 235/45		incl. Facelift 2021
	RC32	46	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr., Frontantrieb, auch für Hybrid
			-	100-146	205/55, 215/50, 215/55, 225/50, 245/45		Orig.-Verschr., Allrad, auch für Hybrid
	B36	46	ZP580	85-146	205/55, 215/50, 215/55, 235/45		incl. Facelift 2021, Frontantrieb
		-	100-146	205/55, 215/50, 215/55, 225/50, 235/45		incl. Facelift 2021, Allrad	
AC-518	40	ZP580D6F +R	100, 130	215/50, 215/55, 235/45		+ Red. Ringe 73,1-67,1, Allrad	
7 x 18	Oxigin 25	55	ZP580	77-146	205/50, 205/55, 205/60, 215/50, 215/55, 235/45		nicht Bremse 320mm
	RC27	50	-	85-130	225/45		Orig.-Verschr., auch Allrad
		45+48,5	-	77-146	205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr., Frontantrieb, auch Hybrid
	RC32		-	100-146	215/45, 215/50, 225/45		Orig.-Verschr., Allrad, auch Hybrid
		51	-	77-130	205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr., Frontantrieb
7,5 x 18	RC32		-	100-130	215/45, 215/50, 225/45		Orig.-Verschr., Allrad
		52	-	85-146	205/45, 205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., Frontantrieb
		-	100-146	215/45, 215/50, 225/45, 235/45	Orig.-Verschr., Allrad		
	RC30	45	ZP580	85-146	215/45, 225/45, 235/45		incl. Facelift 2021, auch Allrad
		49,5+50	-	85-146	215/45, 225/45, 235/45		Orig.-Verschr., incl. Facelift 2021, auch Allrad
		50,5	-	85-146	215/45, 225/45, 235/45		Orig.-Verschr., incl. Facelift 2021, auch Allrad
	RC32	51	-	77-146	205/45, 205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., Frontantrieb
			-	100-146	205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., Allrad
	B32	45	ZP580	85-146	215/45, 225/45, 235/45		incl. Facelift 2021, auch Allrad
		49,5+50,5	-	85-130	215/45, 225/45, 235/45		Orig.-Verschr., auch Allrad
45		ZP580	85-130	215/45, 225/45, 235/45		auch Allrad	

8 x 18		50	-	85-146	215/45, 225/45, 235/45		Orig.-Verschr., incl. Facelift 2021, auch Allrad
	AC-MB6	45	Artikel Nr. 98499	85-146	215/45, 225/45, 235/45		incl. Facelift 2021, Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	85-146	215/45, 225/45, 235/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
	Oxigin 18	45	ZP580	85-130	225/40, 225/45, 235/45		
	Oxigin 25	45	ZP580	77-146	225/40, 225/45, 235/45		
	RC27	46	ZP580D6F	85-130	225/40, 225/45		auch Allrad
	RC29	45	ZP580	85-146	215/45, 225/45		incl. Facelift 2021, Frontantrieb
				100-146	215/45, 225/45, 235/40, 235/45		incl. Facelift 2021, Allrad
	RC34	50	-	77-130	205/45, 215/45, 225/45, 235/40, 235/45		Orig.-Verschr., Frontantrieb
				100-130	215/45, 225/45, 235/45		Orig.-Verschr., Allrad
	B24	48	ZP580	85-130	215/45, 225/45, 235/40, 235/45		auch Allrad
	B36 / B37	45	ZP580	85-146	215/45, 225/45		incl. Facelift 2021, Frontantrieb
				100-146	215/45, 225/45, 235/40, 235/45		incl. Facelift 2021, Allrad
	B38	45	ZP580	88, 130	215/45, 225/45, 235/40, 235/45		auch Allrad
		49	ZP580	85-130	215/45, 225/45, 235/40, 235/45		auch Allrad
B42 / B44	45	ZP580	85-146	215/45, 225/45		incl. Facelift 2021, Frontantrieb	
			100-146	215/45, 225/45, 235/40, 235/45		incl. Facelift 2021, Allrad	
AC-M10	45	ZP580D6F +R	85-146	215/45, 225/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021	
7,5 x 19	RC32	45+50,5	-	85-130	205/45, 225/35, 225/40		Orig.-Verschr., Frontantrieb
				100-130	225/40		Orig.-Verschr., Allrad
	RC34	49,5+51	-	77-146	225/35, 225/40		Orig.-Verschr., Frontantrieb
				100-146	225/40		Orig.-Verschr., Allrad
	B32	45+49,5	-	85-146	225/40		Orig.-Verschr., incl. Facelift 2021, auch Allrad
	B39	45	ZP580	88-130	225/40		auch Allrad
		50	-	88-130	225/40		Orig.-Verschr., auch Allrad
	AC-521	45	ZP580D6F +R	85-146	225/40		+ Red. Ringe 73,1-67,1, incl. Facelift 2021
8 x 19	RC27	47	-	85-130	225/35, 225/40, 235/35, 235/40		Orig.-Verschr., auch Allrad
	RC29	48	ZP580	85-146	225/40, 235/35, 235/40		auch Allrad, incl. Facelift 2021, bei 235/40 ✖
	B24	50	ZP580	85-130	225/40, 235/35, 235/40		nicht Bremse 280mm
	B38	45	ZP580	85-130	225/40		Frontantrieb
				100, 130	225/40, 235/35		Allrad
	AC-518	40	ZP580D6F +R	100-146	225/40		+ Red. Ringe 73,1-67,1, incl. Facelift 2021, nur Allrad
	CA 19	45	ZP580	85-146	225/40		incl. Facelift 2021, Frontantrieb
				100-146	225/40, 235/35		incl. Facelift 2021, Allrad
CA 24	45	ZP580	77-146	225/35, 225/40			
Oxigin 29	50	ZP580	85-146	225/40, 235/35, 235/40		incl. Facelift 2021, Frontantrieb	
			100-146	225/40, 235/35, 235/40		incl. Facelift 2021, Allrad	
8 x 20	B38	45	ZP580	85-130	225/35		auch Allrad
		50	ZP580	85-146	225/35		incl. Facelift 2021, auch Allrad

weitere Dimensionen/Designs siehe Konfigurator

Kona electric		2018	OS, OSE		5/114,3	67,1	e4*2007/46*1259*01-..., e4*2007/46*1522*...	
Sensor - Brocksens 5								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	50	ZP580D8F	26, 28	215/50, 215/55 , 225/50			incl. Facelift 2021
	RC30	50	ZP580D6F	26, 28	215/50, 215/55 , 225/50			
	RC32	50	-	26-28	215/50, 215/55 , 225/50			Orig.-Verschr.
	RC34	50	-	26-28	215/50, 215/55 , 225/50			Orig.-Verschr.
	RC27	45	ZP580D6F	26, 28	215/50, 215/55			incl. Facelift 2021
		47	ZP580D8F	26, 28	215/50, 215/55, 225/50			
	RC30	45	ZP580D6F	26, 28	215/50, 215/55			incl. Facelift 2021
		47	-	26, 28	215/50, 215/55, 225/50			Orig.-Verschr., incl. Facelift 2021
	RC32	45	-	26-28	215/50, 215/55, 225/50			Orig.-Verschr.
		43,5+47	-	26-28	215/50, 215/55, 225/50, 235/50			Orig.-Verschr.
7,5 x 17	RC34	47	-	26-28	215/50, 215/55, 225/50, 235/50			Orig.-Verschr.
		45	ZP580	26, 28	215/50, 215/55			
	B39	50	ZP580D6F	26, 28	215/50, 215/55, 225/50			
		45	ZP580	26, 28	215/50, 215/55			incl. Facelift 2021
	RC24	50	ZP580	26, 28	215/50, 215/55, 225/50			
		50	ZP580D6F	26, 28	215/50, 215/55, 225/50			Ausführung "M3"
		46	ZP580D6F	26-28	205/50, 205/55, 205/60, 215/50, 215/55, 235/45			
	RC27	52,5	-	26-28	205/50, 205/55, 205/60, 215/50, 215/55, 225/50, 235/45, 245/45			Orig.-Verschr.
		45	ZP580	26, 28	215/50, 215/55			incl. Facelift 2021
	RC29	48	ZP580	26, 28	215/50, 215/55			incl. Facelift 2021
	RC32	46	-	26-28	215/50, 215/55, 225/50, 235/50, 245/45			Orig.-Verschr.
	B24	48	ZP580	26, 28	215/50, 215/55			
	B36	46	ZP580	26, 28	215/50, 215/55			incl. Facelift 2021
	Oxigin 25	55	ZP580	26-28	205/50, 205/55, 205/60, 215/50, 215/55, 235/45			

7 x 18	RC27	50	-	26, 28	225/45		Orig.-Verschr.
	RC32	45+51	-	26-28	215/45, 215/50, 225/45		Orig.-Verschr.
		48,5	-	26-28	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC30	45	ZP580	26, 28	215/45, 225/45		incl. Facelift 2021
		49,5+50+50,5	ZP580D6F	26, 28	215/45, 225/45		incl. Facelift 2021 u. auch Typ OSE
	RC32	51	-	26-28	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32	45	ZP580	26, 28	215/45, 225/45		
		49,5+50,5	ZP580D6F	26, 28	215/45, 225/45		
	B39	45	ZP580	26, 28	215/45, 225/45		incl. Facelift 2021
		50	ZP580D6F	26, 28	215/45, 225/45		incl. Facelift 2021
	AC-MB6	45	Artikel Nr. 98499	26, 28	215/45, 225/45		incl. Facelift 2021, Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	26, 28	215/45, 225/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
	Oxigin 25	45	ZP580	26-28	225/40, 225/45, 235/45		
8 x 18	RC27	46	ZP580D6F	26-28	225/40, 225/45		
	RC29	45	ZP580	26, 28	215/45, 225/45		incl. Facelift 2021
	RC34	50	-	26-28	215/45, 225/45, 235/45		Orig.-Verschr., auch Typ OSE
	B24	48	ZP580	26, 28	215/45, 225/45		
	B36	45	ZP580	26, 28	215/45, 225/45		incl. Facelift 2021
	B37 / B38	45	ZP580	26, 28	215/45, 225/45		
	B42 / B44	45	ZP580	26, 28	215/45, 225/45		incl. Facelift 2021
	AC-M10	45	ZP580D6F +R	26, 28	215/45, 225/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
7,5 x 19	RC32	50,5	-	26-28	225/40		Orig.-Verschr.
	RC34	49,5	-	26-28	225/40		Orig.-Verschr.
	B32	45+49,5	ZP580D6F	26, 28	225/40		incl. Facelift 2021, auch Typ OSE
	AC-521	45	ZP580D6F +R	26, 28	225/40		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
8 x 19	RC27	47	-	26-28	225/35, 225/40, 235/35, 235/40		Orig.-Verschr.
	RC29	48	ZP580	26, 28	225/40		incl. e4*2007/46*1522*.. u. Facelift 2021
	B24	50	ZP580	26, 28	225/40		
	B38	45	ZP580	26, 28	225/40		
	CA 19	45	ZP580	26, 28	225/40		incl. Facelift 2021
	CA 24	45	ZP580	26-28	225/35, 225/40		
	Oxigin 29	50	ZP580	26, 28	225/40		incl. Facelift 2021
8 x 20	B38	45+50	ZP580	26, 28	225/35		ET50 incl. Facelift 2021

Kona N		ab Juni 2021		OS	5/114,3	67,1	e4*2007/46*1259*14-...	
Sensor - Brocksens 5								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
7,5 x 18	RC30	53	ZP580D6F	206	225/45			
	B32	53	ZP580D6F	206	225/45			
	RC30	45	ZP580	206	225/45, 235/45			
		49,5+50,5	ZP580D6F	206	225/45, 235/45			
	RC32	51+52	-	206	225/45, 235/45, 245/45		Orig.-Verschr.	
	B32	50,5	ZP580D6F	206	225/45, 235/45			
	B39	45	ZP580	206	225/45, 235/45			
		50	ZP580D6F	206	225/45, 235/45			
	AC-MB6	45	Artikel Nr. 98499	206	225/45, 235/45		incl. Facelift 2021, Kit mit Artikelnummer 98499	
AC-521	45	ZP580D6F +R	206	225/45, 235/45		+ Red.Ringe 73,1-67,1		
8 x 18	RC27	46	ZP580D6F	206	225/45			
	B24	48	ZP580	206	225/45, 235/45			
	B38	45	ZP580	206	225/45			
		49	ZP580	206	225/45, 235/45			
	B42 / B44	45	ZP580	206	225/45			
AC-M10	45	ZP580D6F +R	206	225/45		+ Red.Ringe 73,1-67,1		
7,5 x 19	RC32	49,5+51	-	206	225/40		Orig.-Verschr.	
	RC34	49,5+54,5	-	206	225/40		Orig.-Verschr.	
	B32	45+49,5+53	ZP580D6F	206	225/40			
	AC-521	45	ZP580D6F +R	206	225/40		+ Red.Ringe 73,1-67,1	
8 x 19	B43	55	ZP580D6F	206	225/40, 235/40			
	RC29	48	ZP580	206	225/40, 235/40			
	RC32	55	-	206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.	
	RC34	55	-	206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.	
	B40	53	ZP580D6F	206	225/40, 235/40, 245/35			
	CA 19	45	ZP580	206	225/40			

	Oxigin 29	50	ZP580	206	225/40, 235/40		
8 x 20	B38	50	ZP580	206	235/35		
8,5 x 20	B41	54	-	206	235/35		Orig.-Verschr.
Kona Hybrid							
Sensor - Brocksens 5		ab 2019	OS	5/114,3	67,1	e4*2007/46*1259*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	44	ZP580D6F	77	205/60, 215/55, 215/60, 225/55		
	RC32	44	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., nicht Bremse 320x28mm
	RC34	44	-	77-146	205/60		Orig.-Verschr.
	RC24	44	ZP580	77	205/60, 215/55, 215/60, 225/55		
	RC27	45	ZP580	77	205/60, 215/55, 215/60, 225/55		
		50	ZP580	77	205/60, 215/55, 215/60		incl. Facelift 2021
	RC30	45	ZP580D6F	77	205/60, 215/55, 215/60, 225/55		
			ZP580	77	205/60, 215/55, 215/60, 225/55		
	RC32	50	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., Frontantrieb, auch Hybrid Fahrzeuge, nicht Bremse 320x28mm,
	RC34	50	-	77-146	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., Frontantrieb, auch Hybrid Fahrzeuge, nicht Bremse 320x28mm,
7 x 17	RC32	50	-	77-146	205/50, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	50	-	85-146	215/55		Orig.-Verschr.
	RC27	45	ZP580	77	205/55, 215/50		incl. Facelift 2021
		47	ZP580D6F	77	205/55, 215/50		
		50	ZP580D6F	77	205/55, 215/50		incl. Facelift 2021
	RC30	47	ZP580D6F	77	205/55, 215/50		incl. Facelift 2021
		50	ZP580D6F	77	205/55, 215/50		
	B39	45	ZP580	77	205/55, 215/50		
		50	ZP580D6F	77	205/55, 215/50		
7,5 x 17	RC24	45	ZP580	77	205/55, 215/50, 235/45		incl. Facelift 2021
	RC27	46	ZP580D6F	77	205/55, 215/50, 235/45		incl. Facelift 2021
	RC28	45	ZP580	77	205/55, 215/50, 235/45		incl. Facelift 2021
	RC29	48	ZP580	77	205/55, 215/50, 235/45		incl. Facelift 2021
	B36	46	ZP580	77	205/55, 215/50, 235/45		incl. Facelift 2021
7,5 x 18	RC30	50	ZP580D6F	77	225/45		
		49,5	ZP580D6F	77	215/45, 225/45		incl. Facelift 2021
	B32	49,5+50,5	ZP580D6F	77	215/45, 225/45		
	B39	45	ZP580	77	215/45, 225/45		incl. Facelift 2021
		50	ZP580D6F	77	215/45, 225/45		incl. Facelift 2021
	AC-MB6	45	Artikel Nr. 98499	77	215/45, 225/45		incl. Facelift 2021, Kit mit Artikelnummer 98499
8 x 18	AC-521	45	ZP580D6F +R	77	215/45, 225/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
	RC29	45	ZP580	77	215/45, 225/45		incl. Facelift 2021
	B36 / B37	45	ZP580	77	215/45, 225/45		incl. Facelift 2021
	B42 / B44	45	ZP580	77	215/45, 225/45		incl. Facelift 2021
7,5 x 19	AC-M10	45	ZP580D6F +R	77	215/45, 225/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
	B32	45+49,5	ZP580D6F	77	225/40		incl. Facelift 2021
	AC-521	45	ZP580D6F +R	77	225/40		+ Red.Ringe 73,1-67,1, incl. Facelift 2021
8 x 19	RC29	48	ZP580	77	225/40		incl. Facelift 2021
	CA 19	45	ZP580	77	225/40		incl. Facelift 2021
8 x 20	B38	45	ZP580	77	225/35		

Kona NEU							
kein Sensor - indirektes RDKS		im Laufe 2023	SX2	5/114,3	67,1	e4*2018/858*00153*	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	44	-	74, 88	205/65		Orig.-Verschr., nicht Bremse 325mm
	RC34	44	-	69-88	205/65		Orig.-Verschr.
				69-88	205/65, 215/60, 215/65		
7 x 16	RC32	45	-	77-88	205/65, 215/60, 215/65		Orig.-Verschr., mit Verbundlenker-HA
	RC30	40	-	88	205/65, 205/70		Orig.-Verschr., mit Verbundlenker-HA
6,5 x 17	RC27	40	-	88	205/60, 215/60		Orig.-Verschr.
	RC27	50	-	88, 146	215/60, 225/55, 235/55		Orig.-Verschr.
				146	215/60, 225/55, 235/55		Orig.-Verschr., Allrad
	RC32	50	-	69-146	215/60		Orig.-Verschr.
				69-146	215/55, 215/60, 225/55		Orig.-Verschr., mit Verbundlenker-HA
				69-146	205/55, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., mit Einzelradaufhängung an HA
	RC34	50	-	88	215/60		Orig.-Verschr.
				146	215/60		
				77-88	215/55, 215/60, 225/55		Orig.-Verschr., mit Verbundlenker-HA

7 x 17				146	215/60, 225/55, 235/55		Orig.-Verschr., mit Einzelradaufhängung an HA
	RC27	45	ZP580	88	205/60		
				88, 146	215/60		
				146	215/60		Allrad
	RC32	45	-	69-146	205/60, 205/65, 215/55, 215/60		Orig.-Verschr., mit Verbundlenker-HA
				69-146	205/55, 205/60, 205/65, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., mit Einzelradaufhängung an HA
		47	-	77-88	205/60, 215/55, 215/60		Orig.-Verschr., mit Verbundlenker-HA
				146	215/60, 225/55		Orig.-Verschr., mit Einzelradaufhängung an HA
	RC34	47	-	77-88	205/60, 215/55, 215/60		Orig.-Verschr., mit Verbundlenker-HA
				146	215/60, 225/55		Orig.-Verschr., mit Einzelradaufhängung an HA
	B39	50	-	88	205/60		
				88, 146	215/60, 225/55, 235/55		
				146	215/60, 225/55, 235/55		Allrad
7,5 x 17	RC27	46	-	74-146	205/60, 215/60		
				125, 146	215/60		4WD
				88	205/60		Orig.-Verschr.
				88, 146	215/60		Orig.-Verschr., Allrad
	B24	48	ZP580	146	215/60		
				88	205/60		
				88, 146	215/60, 225/55		
				146	215/60, 225/55		Allrad
	CA 20	48	ZP580	74-146	205/60, 215/60, 225/55		
				125, 146	215/60, 225/55		4WD
7 x 18	RC27	50	-	74-146	215/55		Orig.-Verschr., mit Verbundlenker-HA
				125, 146	215/55		Orig.-Verschr., mit Mehrlenker-HA
		46	-	146	215/55, 225/50		Orig.-Verschr., Allrad
				69-146	205/50, 205/55, 215/50, 215/55, 225/45		Orig.-Verschr., mit Verbundlenker-HA
	RC32	45	-	69-146	205/50, 205/55, 215/50, 215/55, 225/45, 225/50		Orig.-Verschr., mit Einzelradaufhängung an HA
				77-88	205/50, 205/55, 215/50, 215/55, 225/45		Orig.-Verschr., mit Verbundlenker-HA
	RC34	45	-	146	215/55, 225/50		Orig.-Verschr., mit Einzelradaufhängung an HA
				69-146	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., mit Verbundlenker-HA
	RC34	45	-	69-146	205/50, 205/55, 215/50, 215/55, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				69-88	205/50, 205/55, 215/50, 215/55, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-HA
				146	215/55, 225/50, 245/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				74-146	205/55, 215/55		
		50,5	-	125, 146	215/55		
				74-146	205/55, 215/55, 225/50, 245/45		Orig.-Verschr.
				125, 146	215/55, 225/50, 245/45		
				74-146	205/55, 215/55		
7,5 x 18	AC-MB6 / AC-M10	45	Artikel Nr. 98499	125, 146	215/55		Kit mit Artikelnummer 98499
				74-146	205/55, 215/55		
				125, 146	215/55		
				69-146	215/50, 215/55, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-HA
	RC34	50	-	69-146	215/50, 215/55, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				88, 146	215/55		mit Verbundlenker-HA
				146	215/55		mit Einzelradaufhängung
				88, 146	215/50, 225/45		Orig.-Verschr.
	RC27	45	-	146	215/50, 225/45		Orig.-Verschr., Allrad
				77-88	205/45, 205/50, 225/40, 225/45		Orig.-Verschr., mit Verbundlenker-HA, Frontantr.
				146	215/50, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				77-88	205/45, 205/50, 225/40, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-HA, Frontantr.
7,5 x 19	RC32	45	-	146	215/50, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				77-88	205/45, 205/50, 225/40, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-HA, Frontantr.
		50,5	-	146	215/50, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				69-88	225/40, 225/45		Orig.-Verschr., mit Verbundlenker-HA, Frontantr.
	RC34	49,5	-	146	215/50, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				69-88	215/50, 225/40, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-HA, Frontantr.
		51	-	146	215/50, 225/45, 235/45		Orig.-Verschr., mit Einzelradaufhängung an HA
				74-146	215/50, 225/45, 235/45		
	CA 26	50	ZP580D6F	125, 146	215/50, 225/45, 235/45		
				88, 146	225/45, 235/40, 235/45		Orig.-Verschr.
				146	225/45, 235/40, 235/45		Orig.-Verschr., Allrad
				88, 146	225/45		
8 x 19	RC27	45	-	146	225/45, 235/40, 235/45		Allrad
				88, 146	225/45		
				146	225/45		
				88, 146	225/45, 235/40, 235/45		Allrad
	CA 19	45	ZP580	146	225/45, 235/40, 235/45		
				88, 146	225/45, 235/40, 235/45		
				146	225/45, 235/40, 235/45		
				88, 146	225/45, 235/40, 235/45		Allrad
	Oxigin 29	50	ZP580	146	225/45, 235/40, 235/45		
				88, 146	225/45, 235/40, 235/45		
				146	225/45, 235/40, 235/45		
				88, 146	225/45, 235/40, 235/45		Allrad

Kona Elektro NEU		im Laufe 2023		SX2E	5/114,3	67,1	e4*2018/858*00168*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
	RC27	50	-	38-54	215/60, 225/55, 235/55			Orig.-Verschr.
	RC32	50	-	33-53	215/60, 225/55, 235/55			Orig.-Verschr.

7 x 17	RC34	50	-	33-53	215/60, 225/55, 235/55		Orig.-Verschr.
	RC27	45	ZP580	38-54	215/60		
	RC32	45+47	-	38-53	215/60, 225/55		Orig.-Verschr.
	RC34	47	-	38-53	215/60, 225/55		Orig.-Verschr.
	B39	50	-	38-54	215/60, 225/55, 235/55		Orig.-Verschr.
		45	ZP580	38-54	215/60		
7,5 x 17	CA 26	45	ZP580	33-54	215/60		
	RC27	46	-	38-54	215/60		Orig.-Verschr.
	B24	48	ZP580	38-54	215/60, 225/55		
7 x 18	CA 20	48	ZP580	33-54	215/60, 225/55		
	RC27	46	-	38-54	215/55, 225/50		Orig.-Verschr.
7,5 x 18	RC32	45	-	33-53	215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC34	45	-	33-53	215/55		Orig.-Verschr.
		49,5	-	33-53	215/55, 225/50, 245/45		Orig.-Verschr.
	B32	45	ZP580	33-54	215/55		
		50,5	-	33-54	215/55, 225/50, 245/45		Orig.-Verschr.
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	33-54	215/55		Kit mit Artikelnummer 98499
8 x 18	RC34	50	-	38-53	215/55, 225/50, 245/45		Orig.-Verschr.
	B24	48	ZP580	38-54	215/55		
7 x 19	RC27	45	-	38-54	215/50, 225/45		Orig.-Verschr.
7,5 x 19	RC32	51	-	50-53	235/45		Orig.-Verschr.
	RC34	51	-	50-53	235/45		Orig.-Verschr.
				33-53	215/50, 225/45, 235/45		Orig.-Verschr.
		49,5	-	33-53	215/50, 225/45, 235/45		Orig.-Verschr.
	RC32	45+50,5	-	38-53	215/50, 225/45, 235/45		Orig.-Verschr.
	CA 26	50	ZP580D6F	33-54	215/50, 225/45, 235/45		
8 x 19	RC27	47	-	38-54	225/45, 235/45		Orig.-Verschr.
	CA 19	45	ZP580	38-54	225/45		
	Oxigin 29	50	ZP580	38-54	225/45, 235/45		

Kona Hybrid NEU		im Laufe 2023		SX2	5/114,3	67,1	e4*2018/858*00153*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	44	-	69, 77	205/65		Orig.-Verschr.	
	RC34	44	-	77-88	205/65		Orig.-Verschr.	
	RC32	42,5	-	77-88	205/65, 205/70, 215/60, 215/65		Orig.-Verschr.	
7 x 16	RC30	40	-	77	205/65, 205/70		Orig.-Verschr.	
6,5 x 17	RC27	40	-	77	205/60, 215/60		Orig.-Verschr.	
7 x 17	RC27	50	-	77	205/60, 215/60, 225/55, 235/55		Orig.-Verschr.	
		45	ZP580	77	205/60, 215/60			
	B39	45	ZP580	77	205/60, 215/60			
		50	-	77	205/60, 215/60, 225/55, 235/55		Orig.-Verschr.	
	CA 26	45	ZP580	69, 77	205/60, 215/60			
7,5 x 17	B24	48	ZP580	77	205/60, 215/60, 225/55			
	CA 20	48	ZP580	69, 77	205/60, 215/60, 225/55			
7 x 18	RC27	50	-	69, 77	215/55		Orig.-Verschr.	
		46	-	77	205/55, 215/55, 225/50		Orig.-Verschr.	
7,5 x 18	B32	45	ZP580	69, 77	205/55, 215/55			
		50,5	-	69, 77	205/55, 215/55, 225/50, 245/45		Orig.-Verschr.	
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	69, 77	205/55, 215/55		Kit mit Artikelnummer 98499	
8 x 18	B24	48	ZP580	77	215/55			
7 x 19	RC27	45	-	77	215/50, 225/45		Orig.-Verschr.	
7,5 x 19	CA 26	50	ZP580D6F	69, 77	215/50, 225/45, 235/45			
8 x 19	RC27	47	-	77	225/45, 235/40, 235/45		Orig.-Verschr.	
	CA 19	45	ZP580	77	225/45			
	Oxigin 29	50	ZP580	77	225/45, 235/40, 235/45			

Nexo		2018		FE	5/114,3	67,1	e9*2007/46*6592*..
Sensor - Brocksens 5							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	40	ZP580D6F	32 (120)	225/55, 225/60		
		45	ZP580	32 (120)	225/55, 225/60, 235/55		
		47	ZP580D6F	32 (120)	225/55, 225/60, 235/55		
	RC30	45	ZP580 od. ZP580D6F	32 (120)	225/55, 225/60, 235/55		
		47	-	32 (120)	225/55, 225/60, 235/55		
	B36	46	ZP580	32 (120)	225/55, 225/60, 235/55		
	B39	38	ZP580	32 (120)	225/55, 225/60		
		45	ZP580	32 (120)	225/55, 225/60, 235/55		
	RC24	45	ZP580	32 (120)	225/55, 225/60, 235/55		
	RC28	45	ZP580	32 (120)	225/55, 225/60, 235/55		

7,5 x 17	RC29	48	ZP580	32 (120)	225/55, 225/60		
	B24	48	ZP580	32 (120)	225/55, 225/60		
	AC-518	40	ZP580D6F +R	32 (120)	225/55, 225/60		+ Red.Ringe 73,1-67,1
7,5 x 18	RC30	45	ZP580	32 (120)	225/50, 225/55, 235/50		
		49,5+50	ZP580D6F	32 (120)	225/50, 225/55		
		45	ZP580	32 (120)	225/50, 225/55, 235/50		
	B32	49,5+50,5	ZP580D6F	32 (120)	225/50, 225/55		
		45	ZP580	32 (120)	225/50, 225/55, 235/50		
	B39	50	ZP580D6F	32 (120)	225/50, 225/55		
8 x 18	RC29	45	ZP580	32 (120)	225/50, 225/55		
	B24	48	ZP580	32 (120)	225/50, 225/55		
	B37 / B38	45	ZP580	32 (120)	225/50, 225/55		
7,5 x 19	B32	45+49,5	ZP580D6F	32 (120)	225/45, 235/45, 245/45		
	AC-521	45	ZP580D6F +R	32 (120)	225/45, 235/45, 245/45		+ Red.Ringe 73,1-67,1
8 x 19	RC29	38	ZP580	32 (120)	225/45, 235/45		
		48	ZP580	32 (120)	225/45, 235/45, 245/45		
	B38	45	ZP580	32 (120)	225/45, 235/45, 245/45		
	AC-518	40	ZP580D6F +R	32 (120)	225/45, 235/45		+ Red.Ringe 73,1-67,1
8 x 20	B38	45	ZP580	32 (120)	225/40, 235/40, 245/35, 245/40		
	B40	35	ZP580	32 (120)	225/40		
8,5 x 20	RC29	45	ZP580	32 (120)	225/40, 235/40, 245/35, 245/40		
	B32	45	ZP580	32 (120)	235/40, 245/35, 245/40		
	AC-518	40	ZP580D6F +R	32 (120)	225/40		+ Red.Ringe 73,1-67,1

Grand Santa Fé	(siehe Konfigurator)	ab 2013	DM	5/114,3	67,1	e11*2007/46*0633*...
----------------	----------------------	---------	----	---------	------	----------------------

Santa Fé IV	2018	TM	5/114,3	67,1	e4*2007/46*1318*..
-------------	------	----	---------	------	--------------------

Sensor - Brocksens 5							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	47	ZP580D8F	110-147	235/60, 235/65 , 255/55, 255/60		nicht Bremse 340mm
	RC30	47	-	110-147	235/60, 235/65 , 255/55, 255/60		Orig.-Verschr., nicht Bremse 340mm
	RC34	47	-	110-147	235/65 , 245/60		Orig.-Verschr., nicht Bremse 340x30mm
	RC30	45	ZP580 od. ZP580D6F	110-147	235/60, 235/65		nicht Bremse 340mm
		50	ZP580D6F	110-147	235/60, 235/65, 255/55, 255/60		nicht Bremse 340mm
	RC32	45	-	110-147	235/65		Orig.-Verschr.
		50	-	110-147	235/65, 245/60, 255/60		Orig.-Verschr.
CA 26	45	ZP580	110-147	235/60, 235/65		nicht Bremse 340mm	
7,5 x 17	RC27	46	ZP580D6F	110-147	235/65		nicht Bremse 340mm
	RC28	45	ZP580	110-147	235/60		nicht Bremse 340mm
	RC29	48	ZP580	110-147	235/60, 235/65		nicht Bremse 340mm
	RC32	52,5	-	110-147	235/65, 245/60, 255/60		Orig.-Verschr.
	B24	48	ZP580	110-147	235/60, 235/65		nicht Bremse 340mm
	B36	46	ZP580	110-147	235/60, 235/65		nicht Bremse 340mm
7 x 18	RC32	45	-	110-147	235/60		Orig.-Verschr.
		48,5+51	-	110-147	235/60, 245/55, 255/55		Orig.-Verschr.
7,5 x 18	RC34	49,5	-	110-147	235/55, 235/60		Orig.-Verschr.
	B32	49,5	ZP580D6F	110-147	235/55, 235/60		
	RC30	45	ZP580	110-147	235/55, 235/60		
		49,5	ZP580D6F	110-147	235/55, 235/60		
		50	ZP580D6F	110-147	235/55, 235/60		
	RC32	51+52	-	110-147	235/60, 245/55, 255/55		Orig.-Verschr.
	B32	45	ZP580	110-147	235/55, 235/60		
		50,5	ZP580D6F	110-147	235/55, 235/60		
	B39	45	ZP580	110-147	235/55, 235/60		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	110-147	235/55, 235/60		Kit mit Artikelnummer 98499
8 x 18	AC-521	45	ZP580D6F +R	110-147	235/55, 235/60		+ Red.Ringe 73,1-67,1
	RC29	45	ZP580	110-147	235/55, 235/60		
	RC34	50	-	110-147	235/60		Orig.-Verschr.
	B24	48	ZP580	110-147	235/55, 235/60		
	B36	45	ZP580	110-147	235/55		
	B37 / B42	45	ZP580	110-147	235/55, 235/60		
	B44	45	ZP580	110-147	235/55, 235/60		
	RC32	45	ZP580D6F +R	110-147	235/55, 235/60		+ Red.Ringe 73,1-67,1
		45	-	110-147	235/50, 235/55		Orig.-Verschr.
		50,5	-	110-147	235/50, 235/55, 245/50		Orig.-Verschr.
		53	-	110-147	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.

7,5 x 19	RC34	49,5+51	-	110-147	235/50, 235/55, 245/50		Orig.-Verschr.
	B32	49,5	ZP580D6F	110-147	235/50, 235/55, 245/50		
	AC-521	45	ZP580D6F +R	110-147	235/50, 235/55		+ Red.Ringe 73,1-67,1
8 x 19	RC27	47	-	110-147	235/55		Orig.-Verschr.
	RC34	55	-	110-147	235/50, 235/55, 245/50		Orig.-Verschr.
	RC29	48	ZP580	110-147	235/50, 235/55, 255/45		
	CA 19	45	ZP580	110-147	235/50, 235/55, 255/45		
	Oxigin 29	50	ZP580	110-147	235/50, 235/55, 255/45		
8,5 x 20	B43	54 54,5	ZP580D6F	132-148	255/45		beide ETs sind ECE
	B24	50	ZP580	110-147	235/45, 235/50, 245/45, 255/40, 255/45		
	B32	40	ZP580	110-147	235/45		
	B41	54	-	110-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B42	45	ZP580	110-147	235/45, 245/45		
	B44	40	ZP580	110-147	235/45		
	AC-518	40	ZP580D6F +R	110-147	235/45		+ Red.Ringe 73,1-67,1
9 x 20	B37	43	ZP580	110-147	235/45		
	B40	46	ZP580D6F	110-147	235/45, 245/45		
	CA 23	45	ZP580	110-147	235/45		
8,5 x 21	B41	47	ZP580	110-147	245/40		
	B43	43,5	ZP580D6F	110-147	245/40		

Santa Fé IV							
ab Facelift 2020				TM	5/114,3	67,1	e4*2007/46*1318*03-..
Sensor - Brocksens 5							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC30	47	ZP580D6F	132-148	235/65		nicht Bremse ab 345mm
		50	ZP580D6F	132-148	235/60, 235/65, 255/60		nicht Bremse ab 345mm
	CA 26	45	ZP580	132-148	235/60		nicht Bremse ab 345mm
7,5 x 17	RC27	46	ZP580D6F	132-148	235/60, 235/65		nicht Bremse ab 345mm
	RC29	48	ZP580	132-148	235/60, 235/65, 255/60		nicht Bremse ab 345mm
	B36	46	ZP580	132-148	235/60, 235/65		nicht Bremse ab 345mm
7,5 x 18	RC30	50	ZP580D6F	132-148	235/60		
		49,5	ZP580D6F	132-148	235/55, 235/60, 255/50, 255/55		
	RC34	45	-	132-148	235/60		Orig.-Verschr.
		49,5	-	132-148	235/60, 245/55		Orig.-Verschr.
		53	-	132-148	245/55, 255/55		Orig.-Verschr.
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	132-148	235/55, 235/60		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	132-148	235/55, 235/60		+ Red.Ringe 73,1-67,1
8 x 18	RC29	45	ZP580	132-148	235/55, 235/60		
	RC34	50	-	132-148	235/60		Orig.-Verschr.
	B37	45	ZP580	132-148	235/55		
	AC-M10	45	ZP580D6F +R	132-148	235/55, 235/60		+ Red.Ringe 73,1-67,1
7,5 x 19	B32	49,5	ZP580D6F	132-148	235/50, 235/55, 245/50, 255/50		
	RC32	50,5	-	132-148	235/50, 235/55, 245/50		Orig.-Verschr.
		53	-	132-148	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	RC34	49,5	-	132-148	235/50, 235/55, 245/50		Orig.-Verschr.
		51	-	132-148	235/50, 235/55, 245/50		Orig.-Verschr.
	B32	45	ZP580D6F	132-148	235/50, 235/55, 245/50		
8 x 19	AC-521	45	ZP580D6F +R	132-148	235/50, 235/55, 245/50		+ Red.Ringe 73,1-67,1
	RC27	47	ZP580D6F	132-148	235/50, 235/55, 255/45		
	RC29	48	ZP580	132-148	235/50, 235/55, 245/50, 255/45		
	RC34	55	-	110-147	235/50, 235/55, 245/50		Orig.-Verschr.
	CA 19	45	ZP580	132-148	235/50, 235/55, 255/45		
	Oxigin 29	50	ZP580	132-148	235/50, 235/55, 245/50, 255/45		
8,5 x 19	B32	45	ZP580	132-148	235/50, 235/55, 255/45		
	B43	46,5	ZP580D6F	132-148	235/50, 235/55, 255/45		
	Oxigin 28	45	ZP580	132-148	235/50, 235/55, 255/45		
8,5 x 20	RC36	54	-	132-148	235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr.
	B41	54	-	132-148	255/45		Orig.-Verschr.
				132-148	235/45, 235/50, 245/45, 255/45		
	B42	45	ZP580	132-148	235/45, 235/50, 245/45, 255/40, 255/45		
	B43	53,5	ZP580D6F	132-148	235/45, 235/50, 245/45, 255/40, 255/45		
		54+54,5	ZP580D6F	132-148	235/45, 235/50, 245/45, 255/40, 255/45		
9 x 20	AC-518	40	ZP580D6F +R	132-148	235/45		+ Red.Ringe 73,1-67,1
	B37	43	ZP580	132-148	235/45		
	B40	46	ZP580D6F	132-148	235/45, 245/45		
	CA 23	45	ZP580	132-148	235/45, 245/45		

8,5 x 21	B41	47	ZP580	132-148	235/45, 245/40		
	B43	43,5	ZP580D6F	132-148	245/40		

Santa Fé V NEU		2024		MX5	5/114,3	67,1	e4*2018/858*00188*..	
Sensor - Brocksens 7								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC34	49,5	-	118	235/60		Orig.-Verschr.	
				118	235/60, 245/55, 255/55			
	RC32	52	-	118	235/60, 245/55, 255/55		Orig.-Verschr.	
				118	235/60		Orig.-Verschr.	
	RC34	45	-	118	245/55, 255/55		Orig.-Verschr.	
				53	118	235/60, 245/55		Orig.-Verschr.
	B32	50,5	ZP580	117-132	235/60, 245/55		Orig.-Verschr.	
ZP580D6F				117-132	235/60, 245/55, 255/55		Orig.-Verschr.	
AC-MB6 / AC-M10	45	Artikel Nr. 98499	117-132	235/60, 245/55		Kit mit Artikelnummer 98499		
8 x 18	RC34	50	-	118	235/60, 245/55		Orig.-Verschr.	
7,5 x 19	RC32	53	-	118	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.	
	RC34	49,5+51	-	118	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.	
8 x 19	RC34	55	-	118	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.	
8,5 x 20	RC36	54	-	117-132	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.	
	B41	54	-	118	255/45		Orig.-Verschr.	
				118	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr.	
	B43	54	-	117-132	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.	
9 x 20	CA 23	45	ZP580	117-132	235/45, 245/45			
8,5 x 21	B43	43,5	ZP580D6F	117-132	235/45, 245/40			

Staria NEU				US4	6/139,7	92,4	e4*2018/858*00055*..., e4*2018/858*00056*..	
Sensor - Brocksens 7								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC35	48	ZP600D6F	118, 130	215/65		nicht Bremse 345mm	
				130	215/65, 215/65C, 225/60C			
7,5 x 18	B45	50	ZP600D6F	130	235/55			
8 x 18	RC31	48	ZP600D6F	118-130	235/55			
8 x 20	B45	45	ZP600D6F	118, 130	235/45C			

Tucson (siehe Konfigurator)		ab 2015		TLE	5/114,3	67,1	e11*2007/46*2711*..., e11*2007/46*2724*..., e13*2007/46*1612*..., e5*2007/46*1076*..., e5*2007/46*1084...
--	--	---------	--	-----	---------	------	---

Tucson		ab 2021		NX4e		5/114,3		67,1		e5*2018/858*00001*..	
Sensor - Brocksens 5											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 17	RC32	43,5	-	85-132	215/65, 225/60, 225/65, 235/60				Orig.-Verschr., auch für Hybrid		
	RC27	45	ZP580	85-132	215/65, 225/60, 235/60						
		50	ZP580D6F	85-132	215/65, 225/60, 235/60, 245/55						
	RC30	45+47	ZP580D6F	85-132	215/65, 225/60, 235/60						
	RC32	45+47+53	-	85-132	215/65, 225/60, 225/65, 235/60, 245/55, 245/60				Orig.-Verschr., auch für Hybrid		
		47	-	85-132	215/65, 225/60, 225/65, 235/60, 245/55, 245/60				Orig.-Verschr., auch für Hybrid		
	RC34	50	-	85-132	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55				Orig.-Verschr., auch für Hybrid		
		B39	45	ZP580	85-132	215/65, 225/60, 235/60					
CA 26	45	ZP580	85-132	215/65, 225/60, 235/60				incl. Facelift 2024			
7,5 x 17	RC24	45	ZP580	85-132	215/65, 225/60						
	RC27	46	ZP580D6F	85-132	215/65, 225/60						
	RC28	45	ZP580	85-132	215/65, 225/60						
	RC29	48	ZP580	85-132	215/65, 225/60, 235/60						
	RC32	46	-	85-132	215/65, 225/60, 225/65, 235/60				Orig.-Verschr., auch für Hybrid		
	B24	48	ZP580	85-132	215/65, 225/60, 235/60						
	B36	46	ZP580	85-132	215/65, 225/60						
7 x 18	RC27	46	ZP580D6F	85-132	215/60, 225/55, 235/55				auch für Hybrid		
		50	ZP580D6F	85-132	215/60, 225/55, 235/55, 245/50				auch für Hybrid		
	RC32	45	-	85-132	215/60, 225/55, 235/55, 245/50				Orig.-Verschr., auch für Hybrid		
		48,5	-	85-132	215/60, 225/55, 235/55, 245/50, 255/50				Orig.-Verschr., auch für Hybrid		
		51	-	85-132	215/60, 225/55, 235/55, 245/50				Orig.-Verschr., auch für Hybrid		
7,5 x 18	RC32	51	-	85-132	215/60, 225/55, 235/55, 245/50				Orig.-Verschr., auch für Hybrid		
	RC34	51	-	85-132	235/55				Orig.-Verschr., auch für Hybrid		
	RC30	49,5+50	ZP580D6F	85-132	215/60, 225/55, 235/55						
	RC32	52	-	85-132	215/60, 225/55, 235/55, 245/50				Orig.-Verschr., auch für Hybrid		
	B32	49,5	ZP580D6F	85-132	215/60, 225/55, 235/55						
		50,5	ZP580D6F	85-132	215/60, 225/55, 235/55				bei ET50,5 sind nur spezielle Gewebeschneeketten zulässig!		
	B39	45	ZP580	85-132	215/60, 225/55						
		50	ZP580D6F	85-132	215/60, 225/55, 235/55						
	AC-MB6 / AC-	45	Artikel Nr.	85-132	215/60, 225/55				Kit mit Artikelnummer 98499		

	M10	70	98499	85-132	215/60, 225/55		Rad mit Faceliftnummer: 00499
	AC-521	45	ZP580D6F +R	85-132	215/60, 225/55		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	85-132	215/55, 215/60, 225/55, 225/60		
8 x 18	RC27	46	ZP580D6F	85-132	225/55		
	RC34	45	-	85-132	225/55, 235/55, 245/50		Orig.-Verschr., auch für Hybrid
	B38	49	ZP580	85-132	225/55		
7 x 19	RC27	45	ZP580D6F	85-132	215/50, 225/50, 235/50		
	RC34	45	-	85-132	215/50, 225/50, 235/50		Orig.-Verschr., auch für Hybrid
7,5 x 19	RC32	51	-	85-132	215/50, 225/50, 235/50 , 245/45		Orig.-Verschr.
	RC34	49,5+51	-	85-132	215/50, 225/50, 235/50 , 245/45		Orig.-Verschr., beide ET's sind ECE
	RC32	45	-	85-132	215/50, 225/50, 235/50, 245/45		Orig.-Verschr.
		49,5+ 50,5+53	-	85-132	215/50, 225/50, 235/50, 245/45		Orig.-Verschr., ET49,5 ist nur in den Farben SBM u. HGVP erhältlich!
	RC34	49,5	-	85-132	215/50, 225/50, 235/50, 245/45		Orig.-Verschr.
	B32	45	ZP580D6F	85-132	215/50, 225/50, 245/45		
		49,5	ZP580D6F	85-132	215/50, 225/50, 235/50, 245/45		
	B39	45	ZP580	85-132	215/50, 225/50, 245/45		
		50	ZP580D6F	85-132	215/50, 225/50, 235/50, 245/45		
	AC-521	45	ZP580D6F +R	85-132	215/50, 225/50, 245/45		+ Red.Ringe 73,1-67,1
8 x 19	CA 26	50	ZP580D6F	85-132	215/50, 225/50, 235/50, 245/45		incl. Facelift 2024
	RC27	47	ZP580D6F	85-132	225/50, 245/45		
	RC29	48	ZP580	85-132	225/50, 245/45		
	CA 24	45	ZP580	85-132	235/45, 245/45		
	Oxigin 29	50	ZP580	85-132	225/50, 235/50, 245/45, 255/45		
8 x 20	B38	50	ZP580	85-132	215/45, 235/45, 245/40		
8,5 x 20	B42	45	ZP580	85-132	235/45		
8,5 x 21	B41	47	ZP580	85-132	245/35		auch für Hybrid

Tucson Plug-in-Hybrid NEU		ab 2021		NX4e		5/114,3		67,1		e5*2018/858*00001*...	
Sensor - Brocksens 5											
Dimension		Design		ET	KIT		KW		Reifendimension		Info
7,5 x 19		RC32		51					235/50		 i.V.
		RC34		51	-		85-132		235/50		 Orig.-Verschr.

Ineos	Baujahr	Typ	LK/LZ	Nabe		
Grenadier NEU	ab 2022	GM / GN	6/130	84,1	e9*2018/858*11384*..., e9*2018/858*11385*..	
Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	RC31	55	-	183-210	255/65, 255/70, 265/65, 275/60, 275/65	Orig.-Verschr., Ausführung "P6"

Infiniti		Baujahr		Typ		LK/LZ		Nabe	
QX30 AWD		ab 05.16		H15		5/112		66,6	
Sensor - Brocksens 3									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 17	RC27	38	-	125, 155	215/60, 225/55, 225/60, 235/55				Orig.-Verschr.
7 x 17	RC27	34	-	125, 155	215/60, 225/55, 225/60				Orig.-Verschr.
		37	-	125, 155	215/60, 225/55, 225/60, 235/55				Orig.-Verschr.
		B39	35	ZP568F	125, 155	215/60, 225/55, 225/60			
	CA 26	42	ZP568F	125, 155	215/60, 225/55, 225/60, 235/55				
7,5 x 17	RC24	35	ZP568F	125, 155	215/60, 225/55, 225/60				
		42	ZP568F	125, 155	215/60, 225/55, 225/60, 235/55				
	RC28	35	ZP568F	125, 155	215/60, 225/55, 225/60				
	RC29	35	ZP568F	125, 155	215/60, 225/55, 225/60				
7,5 x 18	B32	33	-	125, 155	215/50, 215/55				Orig.-Verschr.
		35	ZP568F	125, 155	215/50, 215/55, 225/50				
		40+42	-	125, 155	215/50, 215/55, 225/50, 235/50, 245/45				Orig.-Verschr.
	B39	35	ZP568F	125, 155	215/50, 215/55, 225/50				
8 x 18	D17	40	-	125, 155	225/50, 245/45				Orig.-Verschr.
	AC-M10	40	AV1	125, 155	225/50, 245/45				
	AC-522	40	AV1	125, 155	225/50, 245/45				
	AF18 / AF20	40	AV1	125, 155	225/50, 245/45				
	FMI12 Kari	34+45	-	125-155	215/55, 225/50, 245/45				Orig.-Verschr.
7,5 x 19	B39	33	ZP568F	125, 155	225/45, 235/45				
	CA 26	32	ZP568F	125, 155	225/45, 235/45				
8 x 19	RC29	35	ZP568F	125, 155	225/45, 235/40, 235/45				
		39	-	125, 155	225/45, 235/40, 235/45, 245/40, 245/45				Orig.-Verschr.
	B24	35	ZP568F	125, 155	225/45, 235/40, 235/45				
	B38	35	ZP568F	125, 155	225/45, 235/40, 235/45				
		39	-	125, 155	225/45, 235/40, 235/45, 245/40, 245/45				Orig.-Verschr.
	B43	34	ZP568F	125, 155	225/45, 235/40, 235/45				
		38	ZP568F	125, 155	225/45, 235/40, 235/45, 245/40				
	AC-518	38	-	125, 155	225/45, 235/40, 235/45, 245/40, 245/45				Orig.-Verschr.
	AC-521	35	AV1	125, 155	225/45, 235/40, 235/45				
	CA 17	43	ZP568F	80-155	235/45				nicht Bremse 295mm
		45	ZP568F	125	235/45				
	CA 24	43	ZP568F	125	235/45				
Oxigin 29	39	ZP568F	125, 155	225/45, 235/40, 235/45, 245/40					
8,5 x 19	B43	40	ZP568F	125, 155	225/45, 235/40, 235/45				
	B44	42	ZP568F	125, 155	225/45, 235/40, 235/45				
	AC-M10	40	AV1	125, 155	225/45, 235/40, 235/45				
	AF18 / AF20	40	AV1	125, 155	225/45, 235/40, 235/45				
	CA 23	40	-	125, 155	225/45, 235/40, 235/45				Orig.-Verschr.
	Oxigin 20	45	ZP568F	80-155	225/45				
Oxigin 28	40	ZP568F	125, 155	225/45, 235/40, 235/45					
8 x 20	B38	35	ZP568F	125, 155	215/45, 235/35, 235/40				
	B40	39	-	125, 155	215/45, 235/35, 235/40, 245/35				Orig.-Verschr.
	B43	39	ZP568F	125, 155	215/45, 235/35, 235/40, 245/35				
8,5 x 20	RC29	40	ZP568F	125, 155	235/35, 235/40				
	B43 / B44	40	ZP568F	125, 155	235/35, 235/40				
	AC-M10	40	AV1	125, 155	235/35, 235/40				
9 x 20	AF18	40	AV1	125, 155	235/35, 235/40				

Q50	ab 2013		V37	5/114,3	66,1	e13*2007/46*1378*..	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC32	35	ZP578D2F	125	225/55, 235/50		nicht Bremse 352x32mm, Ausführung N22
		40	ZP578D2F	125	225/55, 235/50, 245/50		nicht Bremse 352x32mm
		43	ZP578D2F	125	225/55, 235/50, 245/50, 255/50		nicht Bremse 352x32mm
	RC34	43	ZP578D2F	125	225/55, 235/50, 245/50, 255/50		nicht Bremse 352x32mm, Ausführung N42
	Pro1	45	ZP578D2F	125	225/55, 235/50, 245/50, 255/50		nicht Bremse 352x32mm
7,5 x 17	Oxigin 14	42	ZP578	125-225	225/55, 225/60, 225/65		
	Oxigin 19	48	ZP578	125-225	225/55, 225/60, 225/65, 235/50, 235/55, 235/60, 245/50, 245/55		
	Oxigin 25	45	ZP578	125-225	225/55, 225/60, 25/65		nicht Bremse 335x32mm
7 x 18	RC32	35+40+45	ZP578D2F	125	225/50		nicht Bremse 352x32mm

7,5 x 18	RC32	46	ZP578D2F	125-225	225/50, 235/45, 245/45		
	Oxigin 18	45	ZP578	125-225	225/50, 225/60, 235/50, 235/55, 245/45, 245/50		nicht Bremse 335x32mm
7,5 x 19	RC34	35	ZP578D2F	125-225	225/45		
	Oxigin 18	40+50	ZP578	125-225	225/45, 235/45, 235/50, 245/45		ET50 nur 235/50, nicht Bremse 335x32mm
8 x 19	RC27	42	-	125-225	225/45, 235/40, 235/45		Orig.-Verschr., nicht Bremse 335mm
	CA 24	45	ZP578	125-225	235/40, 235/45, 245/40, 245/45		nicht Bremse 335x32mm
	FMI08 Thoe	40	-	125-225	225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 352x32mm
8,5 x 19	Oxigin 20	42	ZP578	125-225	225/45		nicht Bremse 335mm

Q60		ab 2016		V37	5/114,3	66,1	e13*2007/46*1378*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7,5 x 19	Oxigin 18	50	ZP578	125-225	235/50			nicht Bremse 335mm

Isuzu

		Baujahr	Typ	LK/LZ	Nabe		
D-Max		ab 2012	ATFR, ATFS	6/139,7	100,1	e4*2007/46*0411*..., e4*2007/46*0413*...	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC31	33	ZP600F	120	245/70+C, 245/75, 255/70, 265/70C		
7 x 17	RC31	33	-	120	245/65, 255/65		Orig.-Verschr. wenn Alufelge
8 x 18	RC31	25	-	120	245/60, 255/60		Orig.-Verschr., I1 Ausführung
9 x 20	8400 Bluster	25	-	120	255/50, 265/45, 275/45		Orig.-Verschr.

D-Max		2008 - 2012	TF	6/139,7	100,1	N051	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC31	33	ZP600F	100-120	225/75C, 235/65C, 245/70C		
7 x 17	RC31	33	ZP600F	100-120	225/70C, 235/60C		

D-Max NEU		ab 2021	BTF / WTF		6/139,7	100,1	e13*2007/46*2324*..., e1*2018/858*00269*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 16	RC31	33	ZP600F	120	215/75C, 225/75C			✖
7 x 17	RC31	33	ZP600F	120	225/70C, 235/65+C, 245/60, 255/55, 255/60			✖
7,5 x 18	B45	33	-	120	265/60, 275/60			Orig.-Verschr., auch V-Cross, nur Bremse 320mm
8 x 18	RC31	25	-	120	265/60, 275/60			Orig.-Verschr., 4WD
8 x 20	B45	25	-	120	265/50, 275/50			Orig.-Verschr., auch V-Cross, nur Bremse 320mm
9 x 20	8400 Bluster	25	-	120	265/50, 275/50, 285/45			Orig.-Verschr., nur 285/45 auflagenfrei!

Jaguar

	Baujahr	Typ	LK/LZ	Nabe	
E-Pace	2018	DF	5/108	63,4	e11*2007/46*4161*..., e5*2007/46*1050*...
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC32	45	ZP533D13F	110-221	225/65, 225/70, 235/65, 245/60, 245/65	 auch für Hybrid, nur belüftete Bremsscheibe mit 325x30mm
	Pro1	45	-	110-221	225/65, 225/70, 235/65, 245/60, 245/65	 Orig.-Verschr., nicht Bremse 350x34mm
7,5 x 17	RC34	45	ZP533D13F	110-183	225/65, 225/70, 235/65, 245/60	
7,5 x 18	RC32	45	ZP533D13F	110-183	225/60, 225/65, 235/60, 245/55	nicht belüftete Bremsscheibe mit 325x30mm
	RC34	45	ZP533D13F	110-221	225/60, 225/65, 235/60, 245/55	
	Oxigin 18	45	ZP533D13	110-221	225/60, 225/65, 235/55, 235/60	
8 x 18	RC27	45	-	110-221	225/60, 225/65, 235/55, 235/60	 Orig.-Verschr.
	RC32	45	ZP533D13F	110-221	225/60, 225/65, 235/60	 nur belüftete Bremsscheibe mit 325x30mm
	RC34	45	ZP533D13F	110-221	225/60, 225/65, 235/60	 nur belüftete Bremsscheibe mit 325x30mm
	RC27	42,5	-	110-221	225/60, 225/65, 235/55, 235/60	Orig.-Verschr.
	RC32	42	ZP533D13F	110-221	225/60, 225/65, 235/60, 245/55	nur belüftete Bremsscheibe mit 325x30mm
	RC34	42	ZP533D13F	110-221	225/60, 225/65, 235/60, 245/55	
7,5 x 19	Oxigin 18	45	ZP533D13	110-221	225/55, 235/50, 235/55	
8 x 19	RC27	42,5	ZP533D13F	110-221	225/55, 235/50, 235/55, 255/45	
		45	ZP533D13F	110-221	225/55	
	RC34	42	ZP533D13F	110-221	225/55, 235/50, 235/55	nur belüftete Bremsscheibe mit 325x30mm
		45	ZP533D13F	110-221	225/55, 235/50	nur belüftete Bremsscheibe mit 325x30mm
	CA 19	45	OX533F-1	110-221	225/55, 235/55	
	CA 24	45	ZP533D13	110-221	225/55, 235/55	
		45	ZP533D13	110-221	225/55, 235/55	
8,5 x 19	B41	42	ZP533D13F	110-221	235/50, 235/55	
8 x 20	B38	45	ZP533D13F	110-221	235/45, 245/45	
8,5 x 20	RC34	45	ZP533D13F	110-221	235/45, 245/45	nur belüftete Bremsscheibe mit 325x30mm
	B41	45	ZP533D13F	110-221	235/45, 245/45	nur belüftete Bremsscheibe mit 325x30mm
8,5 x 21	B41	38,5	ZP533D13F	110-221	235/45, 245/40, 245/45	

F-Pace	ab 04.16	DC	5/108	63,4	e11*2007/46*3324*..., e5*2007/46*1047*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 18	RC32	45	ZP533D13F	120-280	235/65, 245/60, 255/60, 265/55, 265/60	
	RC34	45	ZP533D13F	120-280	235/65, 245/60, 255/60, 265/55, 265/60	 nicht Bremse 380mm
	B32	45	ZP533D13	120-132	235/65, 245/60	
				120-280	255/60, 265/60	
	AC-MB6 / AC-M10	42	AV5	120-132	235/65, 245/60	
				120-280	255/60, 265/60	
	AC-521	42	AV5	120-132	235/65, 245/60	
				120-280	255/60, 265/60	
8 x 18	RC25	42,5	ZP533D13F	120-132	235/65, 245/60	
				120-280	255/60, 265/60	
	RC27	42,5+45	ZP533D13F	120-132	235/65	
				120-280	255/60	
	RC34	42	ZP533D13F	120-250	235/65, 245/60, 255/60	
				120-132	245/60	
	AC-MB6 / AC-M10	42	ZP533D13F+R	120-132	235/65, 245/60	+ Red.Ringe 73,1-63,4
				120-280	255/60, 265/60	
7,5 x 19	AC-521	42	AV5	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55, 275/50	
	CA 26	45	ZP533D13	120-132	235/55, 245/55	
8 x 19	RC27	45	ZP533D13F	120-280	245/55, 255/55	
				120-132	235/55, 245/55	
	RC29	45	ZP533D13	120-280	255/55, 265/50, 265/55	
				120-132	235/55, 245/55	
	RC34	42	ZP533D13F	120-280	235/55, 245/55, 255/55, 265/50, 265/55	
				120-280	235/55, 245/55, 255/55, 265/55	
	B24	45	ZP533D13	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55	
	B40	45	ZP533D13F	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55	
	B43	42	ZP533D13F	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55	
	AC-518	45	AV5	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55	
	CA 24	45	ZP533D13	120-280	245/55, 255/55	
	Oxigin 29	45	ZP533D13	120-132	235/55, 245/55	
				120-280	255/55, 265/50, 265/55	
	RC32	45	ZP533D13F	120-280	255/55	
	B43	45	ZP533D13F	120-280	255/55	
				120-132	235/55, 245/55	

8,5 x 19	CA 20	45	533D13F	120-280	255/55		nur X4 Felge fix gebohrt auf 63,4 nehmen!
				120-132	235/55, 245/55		
				120-280	255/55		
	CA 26	45	533D13F	120-280	255/55		
	B32	45	533D13F	120-132	235/55, 245/55		
				120-280	255/55		
	B41	42	533D13F	120-280	235/55, 245/55, 255/55		
	CA 23	45	533D13	120-132	235/55, 245/55		
8 x 20				120-280	255/55		
	Oxigin 18	45	533	120-132	235/55		
	Oxigin 19 / 25	45	533	120-280	245/55, 255/55		
	Oxigin 28	38	533D13	120-132	235/55, 245/55		
				120-280	255/55		
	B40	45	533D13F	120-132	235/55, 245/50		
				120-280	255/50, 265/50		
	B43	40	533D13F	120-132	235/55, 245/50		
8,5 x 20				120-280	255/50, 265/50		auch für Hybrid, nicht Bremse 380mm
	AC-521	43	AV5	120-132	235/55, 245/50		
				120-280	255/50, 265/50		
	B43	45	533D13F	120-280	255/50		
	RC29	45	533D13F	120-280	255/50		
	RC34	45	533D13F	120-280	235/55, 245/50, 255/50, 265/45, 275/45		
	FMI07 Atena	45	F60C	120-280	255/50		
	RC29	45	533D13F	132	235/55, 245/50		
				132-280	255/50, 265/45, 275/45		
	B24	45	533D13	120-132	235/55, 245/50		
				120-280	255/50, 265/45, 275/45		
	B32	45	533D13	120-132	235/55, 245/50		
				120-280	255/50, 265/45, 275/45		
	B41	45	533D13F	120-294	235/55, 245/50, 255/50, 265/45, 275/45		
8,5 x 21	B42 / B43	45	533D13F	120-132	235/55, 245/50		
				120-280	255/50, 265/45, 275/45		
	B44	40	533D13F	120-280	265/45		
	AC-518	45	AV5	120-132	235/55, 245/50		
				120-280	255/50, 265/45, 275/45		

i-Pace (elektro)		2018		DH		5/108		63,4		e11*2007/46*4311*..	
Sensor - Brocksens Universal											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7,5 x 18	RC32	45	ZP533D13F	172	235/65, 245/60, 255/60						
	RC34	45	ZP533D13F	172	235/65, 245/60, 255/60						
8 x 18	RC27	42+42,5	-	172	235/60, 235/65, 245/60				Orig.-Verschr.		
		45	-	172	235/60, 235/65, 245/60, 255/55, 255/60				Orig.-Verschr.		
	RC32 / RC34	42	ZP533D13F	172	235/65, 245/60						
		45	ZP533D13F	172	235/65, 245/60, 255/60						
8 x 19	RC27	45	-	172	235/55, 245/55, 255/50, 255/55				Orig.-Verschr.		
	RC34	42	ZP533D13F	172	235/55, 245/55						
		45	ZP533D13F	172	235/55, 245/55, 255/50, 255/55						
	CA 19	45	OX533F-1	172	235/55, 235/60, 245/55, 255/50, 255/55						
	CA 24	45	ZP533D13	172	235/55, 235/60, 245/55, 255/50, 255/55						
8,5 x 19	B41	42	ZP533D13F	172	235/55						
	Oxigin 14	42	ZP533	172	235/55, 245/55						
	Oxigin 19 / 25	45	ZP533	172	245/55						
8,5 x 20	RC34	45	ZP533D13F	172	235/50, 235/55, 245/50						
	B41	45	ZP533D13F	172	235/50, 235/55, 245/50, 265/45						
8,5 x 21	B41	38,5	ZP533D13F	172	235/45, 245/45						
		45	ZP533D13F	172	235/45, 245/45, 255/45						

F-Type		ab 2020		QQ6		5/108		63,4		e5*2001/116*1000*03	
Sensor - Brocksens Universal											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
Kombinationen											
8,5 x 19		B32		45			VA 245/40, 255/35, 255/40				
9,5 x 19				27			HA 275/35, 285/30, 285/35				

XE		ab 05.2015		JA		5/108		63,4		e11*2007/46*2150*...	
Sensor - Brocksens Universal											
Dimension		Design		ET		KIT		KW		Reifendimension	
		RC30		48,5		ZP580D6F		120-132		205/55, 215/50	
								120-184		225/50, 235/50	
										nicht Bremse 350mm	

7 x 17	RC27	50	ZP580D6F	120-132	205/55, 215/50		
				120-177	225/50, 235/50		
	RC32	45	ZP580D6F	120-184	205/55		
	B39	45	ZP580D6F	120-132	205/55, 215/50		
7,5 x 17				120-177	225/50, 235/50		bei 235/50 ✖
	RC24	47	ZP580D6F	120-132	205/55, 215/50		nicht Bremse 350mm
				120-184	225/50, 235/45, 235/50, 245/45		ab 235/50 ✖
	RC28	45	ZP532	120-132	205/55, 215/50		
				120-184	235/45		nicht Bremse 350mm
	B36	45	ZP532	120-132	205/55, 215/50		
				120-177	225/50, 235/45, 235/50, 245/45		nur 235/45 auflagenfrei! ✖
	AC-518	45	ZP580D6F+R	120-132	205/55, 215/50		+ Red. Ringe 73,1-63,4, nicht Bremse 350mm
7,5 x 18				120-184	235/45		
	RC30	46	ZP580D6F	120-177	225/40, 225/45, 235/45		
				120-132	215/45		
	RC32	45	ZP580D6F	120-221	225/45		
	RC34	45	ZP580D6F	132-221	225/45		
	B32 / B39	45	ZP532	120-132	215/45		
				120-177	225/40, 225/45, 235/45		
	AC-521	45	ZP580D6F+R	120-132	215/45		nicht Bremse 350mm, + Red.Ringe 73,1-63,4
8 x 18				120-184	225/40, 225/45, 235/45		
	Oxigin 18	45	ZP532	120-280	225/45		
				120-132	215/45		
	RC29	45	ZP532	120-177	225/40, 225/45, 235/40, 235/45, 245/40		bei 235/40 u. 245/40 ✖
	RC32	42	ZP580D6F	120-280	225/50, 235/45, 245/45, 255/45		
	RC34	45	ZP580D6F	120-221	225/45		Heckantrieb
				132-221	225/45, 245/40		Allrad
	B38	45	ZP532	120-177	225/40, 225/45, 235/40, 235/45, 245/40		bei 235/40 u. 245/40 ✖
7,5 x 19	AC-518	50	ZP580D6F+R	120-132	215/45		nicht Bremse 350mm, + Red.Ringe 73,1-63,4
				120-184	225/40, 225/45, 235/40, 235/45, 245/40		
	B32	44,5 + 50,5	ZP580D6F	120-177	225/40		
	AC-521	42	ZP580D6F+R	120-184	225/40		nicht Bremse 350mm, + Red.Ringe 73,1-63,4
8 x 19				120-132	215/45		
	RC29	42,5	ZP580D6F	120-177	225/40, 235/35, 235/40, 245/35		ab 235/35 ✖
		45	ZP532	120-177	225/40, 235/35, 235/40, 245/35		ab 235/35 ✖
	B24	45	ZP532	120-177	225/40, 235/35, 235/40, 245/35		ab 235/35 ✖
	B43	47,5	ZP580D6F	120-184	225/40, 235/35, 235/40		nicht Bremse 350mm
8 x 20	B40	45+50	ZP580D6F	120-184	225/40, 235/35, 235/40, 245/35		nicht Bremse 350mm, ET45 ab 235/35 ✖
	B38 / B40	45	ZP580D6F	120-184	235/35		nicht Bremse 350mm
				120-132	215/45		nicht Bremse 350mm
	B43	45,5+50	ZP580D6F	120-184	235/35		nicht Bremse 350mm
		50,5	ZP580D6F	120-184	235/35		nicht Bremse 350mm

weitere Dimensionen/Designs siehe Konfigurator

XF		ab 2015		JB	5/108	63,4	e11*2007/46*2981*...	
Sensor - Brocksens Universal								
Dimension		Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC34	45	ZP580D6F	120-221	225/55			
	RC24	47	ZP532	120-221	225/55, 235/50, 235/55, 245/50, 255/50HA			
	RC28 / RC29	45	ZP532	120-221	225/55, 235/50, 235/55, 245/50			
	B24	45	ZP532	120-221	225/55, 235/50, 235/55, 245/50, 255/50			bei 255/50 ✖
	B36	45	ZP532	120-177	225/55, 235/50, 235/55, 245/50, 255/50			bei 255/50 ✖
	AC-518	45	Artikel Nr. 98497	120-221	225/55, 235/50, 235/55, 245/50			Kit mit Artikelnummer 98497
7,5 x 18	RC30	46	ZP580D6F	120-177	225/50, 235/45, 245/45			
	RC32 / RC34	45	ZP580D6F	120-221	225/50, 235/45, 245/45			
	B32 / B39	45	ZP532	120-221	225/50, 235/45, 245/45			
	AC-MB6	42	Artikel Nr. 98497	120-221	225/50, 235/45, 245/45			Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	120-221	225/50, 235/45, 245/45			Kit mit Artikelnummer 98497
8 x 18	RC27	45	ZP580D6F	120-280	245/45			Orig.-Verschr.
			ZP580D6F	120-184	235/50			
				120-280	245/45, 255/45			
	RC32	45	ZP580D6F	120-280	225/50, 235/45, 245/45, 255/45			
	RC34	45	ZP580D6F	120-280	225/50, 235/45, 245/45, 255/45			
	RC29	45	ZP532	120-177	225/50, 235/45			
				120-280	245/45, 255/45			
	B36	45	ZP532	120-177	225/50, 235/45			
				120-280	245/45, 255/45			
				120-221	225/50, 235/45			
	B42 / B44	42	ZP532	120-280	245/45, 255/45			

	AC-MB6 / AC-M10	42	Artikel Nr. 98497	120-221	225/50, 235/45		Kit mit Artikelnummer 98497
				120-280	245/45, 255/45		
	AC-518	45	Artikel Nr. 98497	120-221	225/50, 235/45		Kit mit Artikelnummer 98497
				120-280	245/45, 255/45		
	CA 26	45	ZP580D6F+R	120-221	225/50, 235/45		
				120-280	245/45, 255/45		
7,5 x 19	B32	44,5	ZP580D6F	120-221	225/45		Kit mit Artikelnummer 98497
	AC-521	42	Artikel Nr. 98497	120-221	225/45		
	CA 26	45	ZP532	120-221	225/45		
8 x 19	RC27	45	-	132-280	245/40		Orig.-Verschr.
	RC34	45	ZP580D6F	120-280	225/40, 225/45, 235/40, 245/40		
	B40	45	ZP580D6F	120-280	245/40		
			ZP580D6F	120-221	225/45, 235/40		
	CA 19	45	OX532F-1	132-280	245/40		
	RC27	42,5	ZP580D6F	120-280	245/40		
	RC29	45	ZP532	120-177	225/45, 235/40		
				120-280	245/40		
	RC34	42	ZP580D6F	120-280	225/40, 225/45, 235/40, 245/40		
	B24 / B38	45	ZP532	120-177	225/45, 235/40		
				120-280	245/40		
	B43	42+47,5	ZP580D6F	120-221	225/45, 235/40		
				120-280	245/40		
	AC-518	45	Artikel Nr. 98497	120-221	225/45, 235/40		Kit mit Artikelnummer 98497
				120-280	245/40		
	CA 24	45	ZP532	120-280	245/40		
	Oxigin 29	45	ZP532	120-221	225/45, 235/40		
				120-280	245/40		
8 x 20	B38 / B40	45	ZP580D6F	120-280	245/35		
	B43	40+45,5 +48,5	ZP580D6F	120-280	245/35		
	AC-521	43	Artikel Nr. 98497	120-280	245/35		Kit mit Artikelnummer 98497
8,5 x 20	RC29	45	ZP580D6F	120-280	245/35, 255/35		
	B24	45	ZP532	120-280	245/35, 255/35		
	B32	48	ZP580D6F	120-280	245/35, 255/35		
		45	ZP532				
	B41	45	ZP580D6F	120-280	235/35, 245/35, 255/35		Heckantrieb
				132-280	245/35, 255/35		Allrad
	B42 / B43	45	ZP580D6F	120-280	245/35, 255/35		
	AC-518	40	Artikel Nr. 98497	120-280	245/35, 255/35		Kit mit Artikelnummer 98497

weitere Dimensionen/Designs siehe Konfigurator

XF Sportbrake		ab 2017		JB	5/108	63,4	e11*2007/46*2981*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC32	45	ZP580D6F	120-221	225/50, 235/45, 245/45			auch Allrad
	RC34	45	ZP580D6F	120-221	225/50, 235/45, 245/45			
8 x 18	RC32	45	ZP580D6F	120-280	225/50, 235/45, 245/45 , 255/45			auch Allrad
	RC34	45	ZP580D6F	120-280	225/50, 235/45, 245/45 , 255/45			
8 x 19	RC34	45	ZP580D6F	120-280	225/40, 225/45, 235/40, 245/40			
	CA 19	45	OX532F-1	132-221	245/40			
	RC34	42	ZP580D6F	120-280	225/40, 225/45, 235/40, 245/40			
8,5 x 19	B41	42	ZP580D6F	120-280	225/40, 225/45, 235/40, 245/40, 255/40			
8,5 x 20	B41	45	ZP580D6F	120-280	235/35, 245/35, 255/35			Heckantrieb
				132-280	245/35, 255/35			Allrad
8,5 x 21	B41	45	ZP580D6F	120-280	255/30			

Jeep

Jeep	Baujahr	Typ	LK/LZ	Nabe			
Avenger elektro NEU	März 2023	FH1	4/108	65,1	e3*2018/858*00078*..		
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	32	ZP402F	62 (115)	215/65, 225/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
	RC34	32	- od. ZP401F	62	215/65, 225/60, 225/65		
6,5 x 17	RC34	32	- od. ZP401F	62	215/60, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 17	RC34	32	- od. ZP401F	62	215/60, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7,5 x 18	B39	32	ZP402F	62 (115)	215/50, 215/55		

Avenger NEU		2024		FH1		4/108		65,1		e3*2018/858*00078*..	
kein Sensor - indirektes RDKS											
Dimension		Design	ET	KIT	KW	Reifendimension			Info		
6,5 x 16		RC30	32	ZP402F	74, 100	215/65, 225/60					
7,5 x 18		B39	32	ZP402F	74, 100	215/50, 215/55					

Cherokee		ab 2014		KL	5/110	65,1	e4*2007/46*0783*...	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	41	-	103-200	215/60, 225/60		Orig.-Verschr.	
	RC34	41	-	103-200	215/70, 225/60		Orig.-Verschr.	
	RC27	37	ZP538F	103-200	215/60M+S, 225/60			
	RC30	40	-	103-200	215/60M+S, 225/60, 235/55		Orig.-Verschr.	
	RC32	40	-	103-200	225/60		Orig.-Verschr.	
	RC34	37,5+40	-	103-200	225/60		Orig.-Verschr.	
7,5 x 17	RC27	31	-	200	245/65		Orig.-Verschr.	
				103-200	225/60, 225/65, 235/55, 235/60		Orig.-Verschr. ✖	
7 x 18	AC-518	40	ZP538F	103-200	215/60M+S, 225/60			
	RC27	40	ZP538F	103-200	225/55			
7,5 x 18	RC32	40	-	103-200	225/50, 225/55		Orig.-Verschr.	
	B32	41	-	103-200	225/55, 235/50		Orig. Verschr. bei 235/50 ✖	
8 x 18	B39	38	-	103-200	215/55, 225/55, 235/50, 245/50		Orig. Verschr. ab 235/50 ✖	
	B37	40	ZP538F	103-200	225/55, 235/50, 255/45		✖	
7,5 x 19	B38	40	-	103-200	225/55, 235/50, 255/45		Orig.-Verschr. ✖	
	RC32	40	ZP538F	103-200	225/45, 235/45, 245/45		Orig.-Verschr.	
	RC34	40	-	103-200	225/45, 235/45, 245/45		Orig.-Verschr.	
	B39	40	-	103-200	225/45, 235/45, 245/45		Orig.-Verschr.	
8 x 19	RC29	34	-	103-200	225/45		Orig.-Verschr.	
	B24	35	-	103-200	225/45, 235/45, 245/45		Orig.-Verschr., ab 235/45 ✖	
	B38	33	-	103-200	225/45, 235/45, 245/45		Orig.-Verschr. ✖	
	B43	34	ZP538F	103-200	225/45			
weitere Dimensionen/Designs siehe Konfigurator								

weitere Dimensionen/Designs siehe Konfigurator

Cherokee Trailhawk		ab 2014		KL	5/110	65,1	e4*2007/46*0783*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC27	31	ZP538F	200	245/65			
9 x 21	B32	30	ZP538F	200	245/40, 255/40, 265/40			ab 255/40 HA ✖

Grand Cherokee (inkl. Facelift ab 07.2013)			ab 2010	WK	5/127	71,6	e4*2007/46*0186*...	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7,5 x 18	B45	44,45	-	140-259	265/60			Orig.-Verschr., incl. Facelift 2013
8 x 18	RC25	56,4	ZP597F	140-259	265/60			incl. Facelift 2013
8,5 x 19	RC25	50	ZP597F	140-259	265/50, 265/55, 275/50			incl. Facelift 2013, bei 275/50 ✖
8 x 20	B40	56,4	-	140-259	265/50			Orig.-Verschr., incl. Facelift 2013
8,5 x 20	RC29	56	ZP597F	140-259	265/50, 275/45			incl. Facelift 2013
	B32	56	ZP597F	140-259	265/50, 275/45			incl. Facelift 2013
	B41	50	ZP597F	140-259	265/50, 275/45			
9 x 20	B37	51	ZP597F	140-259	265/50, 275/45			incl. Facelift 2013
9 x 21	B32	55	ZP597F	140-259	265/40, 265/45, 275/40			

Grand Cherokee SRT8 (inkl. Facelift 2013)		ab 2013	WK	5/127	71,6	e4*2007/46*0186*...	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
10,5x20	B32	45	ZP597F	344	295/45		✖
	B40	45	-	344	295/45		Orig.-Verschr., incl. Facelift 2013, ✖

Grand Cherokee NEU	2021	WL	5/127	71,6	e9*2018/858*11257*..
---------------------------	-------------	-----------	--------------	-------------	----------------------

Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 21	FMI05 Makhai	50	-		275/45		Orig.-Verschr.,

Compass	ab 08.2017	MX	5/110	65,1	e11*2007/46*4037*..., e4*2007/46*1410*...		
---------	------------	----	-------	------	---	--	--

Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC24	40	ZP538F	88-125	215/65, 215/70, 225/65		
	RC30	40	-	88-125	215/65		Orig.-Verschr.
			ZP538F	88-125	215/65, 215/70, 225/65		
	RC34	40	-	88-125	215/65, 215/70, 225/60, 225/65, 235/60, 235/65		Orig.-Verschr.
6,5 x 17	RC34	40	-	88-125	215/55, 215/60, 215/65, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
7 x 17	RC30	40	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
	RC32	40	-	88-125	215/55, 215/60, 215/65, 225/55, 225/60		Orig.-Verschr.
	RC34	40	-	88-125	215/55, 215/60, 215/65, 225/55, 225/60		Orig.-Verschr.
	RC27	37	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
	RC34	37,5	-	88-125	215/55, 215/60, 215/65, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
7,5 x 17	B24	38	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
7 x 18	RC27	40	ZP538F	88-125	225/55		
	RC32	40	-	88-125	215/50, 215/55, 225/50, 225/55, 235/50		Orig.-Verschr.
	RC34	40	-	88-125	225/55		Orig.-Verschr.
7,5 x 18	RC30	37	ZP538F	88-125	215/55, 225/50, 225/55, 245/45		
	B39	38	ZP538F	88-125	215/55, 225/50, 225/55, 245/45		
8 x 18	B38	33	ZP538F	88-125	225/50, 225/55, 245/45		
	AC-518	33	ZP538F	88-125	225/50, 225/55, 245/45		
7,5 x 19	RC32	40	ZP538F	88-125	225/45, 235/45, 245/45		
	RC34	40	-	88-125	225/45, 235/45, 245/45		Orig.-Verschr.
8 x 19	RC29	34	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
	B24	35	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
	B38 / B40	33	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
	B43	34	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
	AC-518	33	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
8,5 x 19	B32	35	ZP538F	88-125	225/45, 235/45		
8 x 20	RC36	37	ZP538F	88-125	215/45, 235/40		

Compass	ab 2021	MP	5/110	65,1	e3*2007/46*0508*...		
---------	---------	----	-------	------	---------------------	--	--

Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	40	-	88-125	215/65		Orig.-Verschr.
6,5 x 17	RC34	40	-	125	225/60		Orig.-Verschr., auch Hybrid
			-	88-125	205/60, 205/65, 215/60, 215/65, 225/55, 225/60, 235/55, 235/60		Orig.-Verschr., auch Hybrid
7 x 17	RC30	40	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
	RC34	40	-	125	225/60		Orig.-Verschr.
				88-132	205/60, 205/65, 215/60, 215/65, 225/55, 225/60		Orig.-Verschr.
				88-125	215/60, 235/60		Orig.-Verschr.
		37,5	-	88-132	205/60, 205/65, 215/60, 215/65, 225/55, 225/60, 235/55, 235/60		Orig.-Verschr.
	RC27	37	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
	RC32	40	-	88-125	215/55, 215/60, 215/65, 225/55, 225/60		Orig.-Verschr.
7,5 x 17	B24	38	ZP538F	88-125	215/60, 215/65, 225/55, 225/60		
7 x 18	RC27	40	-	88-125	225/55		Orig.-Verschr.
	RC32	40	-	88-125	215/50, 215/55, 225/50, 225/55, 235/50		Orig.-Verschr.
	RC34	40	-	88-125	225/55		Orig.-Verschr.
7,5 x 18	RC30	37	ZP538F	88-125	215/55, 225/50, 225/55, 245/45		
8 x 18	RC27	33	-	88-125	225/50, 225/55, 245/45		Orig.-Verschr.
	B24	35	ZP538F	88-125	225/50, 225/55, 245/45		
7,5 x 19	RC32	40	ZP538F	88-132	205/50, 205/55, 215/50, 225/45, 235/45		
	RC34	40	-	88-132	205/55, 215/50, 225/45, 235/45		Orig.-Verschr.
8 x 19	B38 / B40	33	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
	B43	34	ZP538F	88-125	225/45, 235/45, 245/40, 245/45		
8 x 20	RC36	37	ZP538F	88-125	215/45, 235/40		

Compass Hybrid	1. Quartal 2022	MP	5/110	65,1	e3*2007/46*0508*...		
----------------	-----------------	----	-------	------	---------------------	--	--

Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC34	37,5	-	88-132	215/60, 235/60		Orig.-Verschr.
					205/60, 205/65, 215/60, 215/65, 225/55, 225/60, 235/55, 235/60		Orig.-Verschr.
		40	-	125	225/60		Orig.-Verschr.
				88-132	205/60, 205/65, 215/60, 215/65, 225/55, 225/60		Orig.-Verschr.
7 x 18	RC34	37,5	-	88-132	225/55, 235/55		Orig.-Verschr.

7,5 x 19	RC32	40	ZP538F	88-132	205/50, 205/55, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	40	-	88-132	205/55, 215/50, 225/45, 235/45		
Gladiator		ab Jänner 2021		JT	5/127	71,5	e4*2007/46*1532*...
Sensor - Brocksens 3							

auf Anfrage						
Renegade	2014	BU	5/110	65,1	e3*2007/46*0300*...	
Sensor - Brocksens Universal						

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC24	40	ZP538F	77-125	215/65		nur 2WD!! Nicht Bremse 305mm
			ZP538F	81-103	215/65, 215/70, 225/65		
	RC30	40	ZP538F	81-125	215/65 , 215/70, 225/65		Orig.-Verschr.
			-	70-132	215/65 , 215/70 , 225/65, 235/60, 235/65		
7 x 16	RC28	41	ZP538F	81-125	215/65		nicht Bremse 305mm
6,5 x 17	RC34	40	-	84-132	215/60		Orig.-Verschr.
				70-132	215/55, 215/60, 215/65, 225/55, 225/60, 235/50, 235/55		
7 x 17	RC30	40	ZP538F	81-125	215/60 , 215/65, 225/55, 225/60		Orig.-Verschr.
	RC32	40	ZP538F	70-132	215/55, 215/60 , 215/65, 225/55, 225/60		
	RC34	40	-	70-132	215/55, 215/60 , 215/65, 225/55, 225/60		
	RC34	37,5	-	70-132	215/55, 215/60, 215/65, 225/55, 225/60, 235/50, 235/55		
7,5 x 17	B24	38	ZP538F	81-125	215/60, 215/65, 225/55, 225/60		
	AC-518	40	ZP538F	81-125	215/65, 225/60		
7 x 18	RC27	40	ZP538F	70-132	225/55		Orig.-Verschr.
	RC32	40	ZP538F	70-132	215/50, 215/55, 225/50, 225/55 , 235/50		
	RC34	40	-	70-132	225/55		
	RC27	33	ZP538F	77-125	225/50, 235/45		
7,5 x 18	RC30	37	ZP538F	81-125	215/55, 225/50, 225/55		
	B39	38	ZP538F	81-125	215/55, 225/50, 225/55		
8 x 18	RC27	33	ZP538F	70-125	225/50, 235/45		✖
	B24	35	ZP538F	81-125	225/50, 225/55, 245/45		✖
7,5 x 19	RC32	40	ZP538F	84-132	235/45		Orig.-Verschr.
				70-132	225/45, 235/45		
	RC34	40	-	84-132	235/45		
				70-132	225/45, 235/45		
8 x 19	B39	40	ZP538F	81-125	225/45, 235/45		ab 245/40 ✖
	RC29	34	ZP538F	81-125	225/45		
	B24	35	ZP538F	81-125	225/45, 235/45, 245/40, 245/45		
	B43	34	ZP538F	81-125	225/45		
8 x 20	AC-518	33	ZP538F	81-125	225/45		
	RC36	37	ZP538F	81-125	215/45, 235/40		

Wrangler & Unlimited		ab 03.07		JK	5/127	71,6	e4*2001/116*0116*00-25	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7,5 x 17	RC25	40	ZP595F	130-209	235/65, 235/70, 245/65, 245/70, 245/75, 255/65, 255/75			
		44,5	-	130-209	235/65, 235/70, 245/65, 245/70, 245/75, 255/65, 255/75			Orig.-Verschr., bis 245/70M+S
8,5 x 17	8400 Bluster	37	-	130-147	255/70, 255/75, 265/65, 265/70			Orig.-Verschr.
7,5 x 18	B45	44,45	ZP595F	130-209	235/60M+S, 235/65M+S, 255/60, 255/70			
8 x 18	8400 Bluster	35	-	130-147	255/65, 255/70, 265/60, 265/65, 275/60, 275/65			Orig.-Verschr., ab 275/60 ✖
8,5 x 20	B32	35	ZP595F	130-209	255/50, 255/55, 265/50			
9 x 20	8400 Bluster	35	-	130-147	255/55			Orig.-Verschr.

Wrangler (IV) NEU				JK	5/127	71,6	e4*2001/116*0116*26-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC25	44,5	-	147, 200	245/75, 255/70, 255/75		Orig.-Verschr.
7,5 x 18	B45	44,5	-	147, 200	255/70		Orig.-Verschr., Ausführung C7
8 x 18	8400 Bluster	35	-	147-200	255/70, 265/65, 275/60, 275/65, 285/60		Orig.-Verschr., ✖

Kia		Baujahr	Typ	LK/LZ	Nabe	
Cee'd (siehe Konfigurator)		ab 06.12	JD	5/114,3	67,1	e4*2007/46*0496*..., e4*2007/46*0497*...
Pro Cee'd (siehe Konfigurator)		ab 2013	JD	5/114,3	67,1	e4*2007/46*0496*...
Cee'd		2018	CD	5/114,3	67,1	e4*2007/46*1299*..
Sensor - Brocksens 7 od. HUFRDE215 - Artikelnummer 88086						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC30	46	ZP580D6F	73-103	195/65, 205/60, 215/60	 nicht für elektr. Parkbremse, nur Bremse 280mm
	RC24	45	ZP580	73-103	195/65, 205/60, 215/60	 nicht für elektr. Parkbremse, nur Bremse 280mm
	RC27	43	ZP580D6F	73-103	195/65, 205/60, 215/60	 nicht für elektr. Parkbremse, nur Bremse 280mm
6,5 x 16	RC27	50	ZP580D6F	73-103	195/55, 195/60, 205/55, 215/50, 225/50	
	RC30	50	ZP580D6F	73-118	205/55	
	RC32	50	-	73-103	195/55, 195/60, 205/55, 215/50, 225/50	 Orig.-Verschr.
	RC34	50	-	73-118	195/55, 195/60, 205/55, 215/50, 225/50	 Orig.-Verschr.
	RC24	44	ZP580	73-103	195/55, 195/60, 205/55	
		48	ZP580	73-103	195/55, 195/60, 205/55, 215/50, 225/50	
	RC27	50	ZP580	73-118	195/55, 195/60, 205/55, 215/50, 225/50	
	RC30	47+48	ZP580D6F	73-103	195/55, 195/60, 205/55, 215/50	
		50	ZP580 od. ZP580D6F	73-103	195/55, 195/60, 205/55, 215/50, 225/50	
	RC32	40+44	-	73-103	195/55, 195/60	Orig.-Verschr.
		45	-	73-118	195/55, 195/60, 205/55, 215/50	Orig.-Verschr.
		47,5	-	73-103	195/55, 195/60, 205/55, 215/50	Orig.-Verschr.
	RC34	44	-	73-118	195/55, 195/60, 205/55	Orig.-Verschr.
		45+46	-	73-118	195/55, 195/60, 205/55, 215/50	Orig.-Verschr.
	CA 20	45	ZP580	73-118	195/55, 195/60, 205/55, 215/50	
6,5 x 17	RC27	51	ZP580D6F	73-103	205/50	nicht Bremse 305mm
	RC32	53	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45	 Orig.-Verschr.
	RC34	53	-	73-118	225/45	 Orig.-Verschr.
	RC27	47	ZP580D6F	73-103	205/50	
				75-103	215/45, 225/45	
		50	ZP580D6F	73-118	205/50, 215/45, 225/45	
	RC30	45+47	ZP580D6F	73-103	205/50, 215/45, 225/45	
		50+51	ZP580D6F	73-103	205/50, 215/45, 225/45	ET51 nicht Bremse 305mm, auch SW
	RC32	47	-	73-118	195/50, 205/45, 205/50, 215/45	Orig.-Verschr.
		48,5	-	73-103	195/50, 205/45, 205/50	Orig.-Verschr.
		45+50	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45	Orig.-Verschr.
	RC34	47+50	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45	Orig.-Verschr.
	B39	45	ZP580	73-103	205/50, 215/45, 225/45	
		50	ZP580D6F	73-103	205/50, 215/45, 225/45	nicht Bremse 305mm
	CA 26	45	ZP580	73-118	205/50, 215/45, 225/45	
7 x 18	RC27	46	ZP580D6F	73-118	205/45, 215/40	
	RC32	45	-	73-118	205/40, 205/45, 215/40	Orig.-Verschr.
		48,5+51	-	73-103	205/40, 205/45, 215/40	Orig.-Verschr.
	RC34	45	-	73-118	205/40, 205/45, 215/40	Orig.-Verschr.
7,5 x 18	RC30	55	ZP580D6F	73-150	225/40	 nicht Bremse 305mm
				73-103	205/45, 215/40, 225/35, 225/40	 nicht Bremse 305mm
	RC32		-	74-150	225/40	 Orig.-Verschr., ET55 ist nur in den Farben SBM und HGVP erhältlich!
				73-103	205/40, 205/45, 215/40, 225/35, 225/40	
	B32	55	ZP580D6F	73-150	225/40	
				73-103	205/45, 215/40, 225/35	 nicht Bremse 305mm
	RC30	49,5+50,5	ZP580D6F	73-150	225/40	
				73-118	205/45, 215/40, 225/35	
				73-108	205/45, 215/40, 225/35, 225/40	
	RC32	51	-	73-118	205/40, 205/45, 215/40, 225/35, 225/40	Orig.-Verschr.
		52	-	73-103	205/40, 205/45, 215/40, 225/35, 225/40	Orig.-Verschr.
	B32	50,5+53	ZP580D6F	73-103	205/45, 215/40, 225/35	ET53 nicht Bremse 305mm
8 x 18				73-150	225/40	
	B39	50	ZP580D6F	73-118	205/45, 215/40, 225/35	
				73-150	225/40	
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	73-118	205/45, 215/40	Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	73-118	205/45, 215/40	+ Red.Ringe 73,1-67,1
	RC34	50	-	73-118	205/40, 205/45, 215/40, 225/35, 225/40	Orig.-Verschr.
				150	225/40	Orig.-Verschr.
	B24	48	ZP580	73-103	215/40	
	B38	49	ZP580	73-103	215/40, 225/35	
				73-150	225/40	
7,5 x 19	RC32	49,5+50,5+51	-	73-150	225/35	Orig.-Verschr.
		50+53	-	73-150	225/35	Orig.-Verschr.
	RC34	49,5	-	73-150	225/35	Orig.-Verschr.
		51+54,5	-	73-150	225/35	Orig.-Verschr.

8 x 19	B32	49,5+53	ZP580D6F	73-150	225/35		ET53 nicht Bremse 305mm
	CA 26	50	ZP580D6F	73-150	225/35		nicht Bremse 305mm
	B40	53	ZP580D6F	73-150	225/35		
	Oxigin 29	50	ZP580	73-150	225/35		

ProCee'd III	2018	CD	5/114,3	67,1	e4*2007/46*1299*..		
--------------	------	----	---------	------	--------------------	--	--

Sensor - Brocksens 7 od. HUFRDE215 - Artikelnummer 88086

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC32	50	-	73-103	195/55, 195/60, 205/55 , 215/50, 225/50		Orig.-Verschr.
	RC34	50	-	73-118	195/55, 195/60, 205/55 , 215/50, 225/50		Orig.-Verschr.
	RC32	42,5+44	-	73-103	195/55, 195/60, 205/55		Orig.-Verschr.
		45	-	73-118	195/55, 195/60, 205/55, 215/50		Orig.-Verschr.
7 x 17	RC34	45+46	-	73-118	195/55, 195/60, 205/55, 215/50		Orig.-Verschr.
	RC32	53	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	53	-	73-118	225/45		Orig.-Verschr.
	RC27	47	ZP580D6F	88-103	225/45		
		50	ZP580D6F	88-118	225/45		
	RC30	47	ZP580D6F	88-103	225/45		
	RC32	47	-	73-118	195/50, 205/45, 205/50, 215/45		Orig.-Verschr.
		50	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
7 x 18	RC34	47+50	-	73-118	195/50, 205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	B39	50	ZP580D6F	88-103	225/45		nicht Bremse 305mm
	CA 26	45	ZP580	88-118	225/45		
	RC32	45+48,5+51	-	73-103	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC32	55	-	74-150	225/40		Orig.-Verschr.
	B32	55	ZP580D6F	88-150	225/40		nicht Bremse 305mm
	RC30	49,5	ZP580D6F	88-150	225/40		
	RC32	55	ZP580D6F	88-150	225/40		nicht Bremse 305mm
		51	-	73-118	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	B32	50,5	ZP580D6F	88-150	225/40		
		53	ZP580D6F	88-150	225/40		nicht Bremse 305mm
8 x 18	B39	50	ZP580D6F	88-150	225/40		
	RC34	50	-	73-118	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
				150	225/40		Orig.-Verschr.
	B38	49	ZP580	88-150	225/40		
7,5 x 19	RC32	49,5+51	-	73-150	225/35		Orig.-Verschr.
	RC34	49,5	-	73-150	225/35		Orig.-Verschr.
		51+54,5	-	73-150	225/35		Orig.-Verschr.
	B32	49,5+53	ZP580D6F	88-150	225/35		ET53 nicht Bremse 305mm
	CA 26	50	ZP580D6F	88-150	225/35		nicht Bremse 305mm
8 x 19	B40	53	ZP580D6F	88-150	225/35		
	Oxigin 29	50	ZP580	88-150	225/35		

Cee'd SW Plug-in Hybrid	ab 2019	CD	5/114,3	67,1	e4*2007/46*1299*..		
-------------------------	---------	----	---------	------	--------------------	--	--

Sensor - Brocksens 7 od. HUFRDE215 - Artikelnummer 88086

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC27	50	ZP580D6F	77	205/55 , 215/50		
	RC30	50	ZP580D6F	77	205/55		
	RC24	47	ZP580D6F	77	205/55, 215/50		
		48	ZP580	77	205/55, 215/50		
	RC30	48	ZP580D6F	77	205/55, 215/50		
7 x 17	CA 20	45	ZP580	77	205/55, 215/50		
	RC27	47+50	ZP580D6F	77	205/50, 215/45, 225/45		
	RC30	45	ZP580D6F	77	205/50, 215/45, 225/45		
			ZP580	77	205/50, 215/45, 225/45		
		47+50	ZP580D6F	77	205/50, 215/45, 225/45		
	B39	45	ZP580	77	205/50, 215/45, 225/45		
7 x 18	CA 26	45	ZP580	77	205/50, 215/45, 225/45		
	RC27	46	ZP580D6F	77	205/45, 215/40		
7,5 x 18	RC30	49,5	ZP580D6F	77	205/45, 215/40, 225/35, 225/40		
	B32	49,5+50,5	ZP580D6F	77	205/45, 215/40, 225/35, 225/40		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	77	205/45, 215/40		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F+R	77	205/45, 215/40		+ Red.Ringe 73,1-67,1
8 x 18	B38	49	ZP580	77	215/40, 225/35, 225/40		

Xcee'd	ab 10.2019	CD	5/114,3	67,1	e4*2007/46*1299*07..		
--------	------------	----	---------	------	----------------------	--	--

Sensor - Brocksens 7 od. HUFRDE215 - Artikelnummer 88086

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
	RC32	40	-	77-150	205/60 , 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., nicht Bremse 320x28mm - 1 Kolben Faustsattel
	RC34	40	-	77-150	205/60 , 215/55, 225/55		Orig.-Verschr., nicht Bremse 320x28mm - 1 Kolben

6,5 x 16							Faustsattel
	RC24	42	ZP580D6F	85-103	205/60, 215/60, 225/55		
		38+44	ZP580	85-103	205/60, 215/60, 225/55		
	RC27	36	ZP580D6F	85-103	205/60, 215/60		
		38	ZP580	85-150	205/60, 215/60, 225/55		
		45	ZP580	85-103	205/60, 215/60, 225/55		
	RC30	38	ZP580	85-103	205/60, 215/60, 225/55		
		42+44	ZP580D6F	85-103	205/60, 215/60, 225/55		
		45	ZP580	85-103	205/60, 215/60, 225/55		
			ZP580D6F	85-103	205/60, 215/60, 225/55		
7 x 17	RC32	42,5	-	77-150	205/60, 215/55, 225/55, 235/50		Orig.-Verschr.
		44+45	-	85-150	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
	RC34	44+45+46	-	77-150	205/60, 215/55, 225/55, 235/50		Orig.-Verschr., nicht Bremse 320x28mm - 1 Kolben Faustsattel
	CA 20	45	ZP580	85-150	205/60, 215/60, 225/55		nicht Bremse 320mm
	RC27	40	ZP580D6F	85-103	205/55, 215/50, 215/55		
		45	ZP580	85-150	205/55, 215/50, 215/55, 225/50		
	RC30	38	ZP580	85-103	205/55, 215/50, 215/55, 225/50		
		45	ZP580D6F	85-150	205/55, 215/50, 215/55, 225/50		
			ZP580	85-103	205/55, 215/50, 215/55, 225/50		
	RC32	43,5+45+47	-	77-150	205/50, 215/50, 225/45		Orig.-Verschr.
7 x 18	RC34	47	-	77-150	205/50, 215/50, 225/45		Orig.-Verschr.
		38	ZP580	85-103	205/55, 215/50, 215/55		
	B39	45	ZP580	85-103	205/55, 215/50, 215/55, 225/50		
		45	ZP580	85-150	205/55, 215/50, 215/55, 225/50		
	CA 26	45	ZP580	85-150	205/55, 215/50, 215/55, 225/50		
	RC32	45	-	75-150	205/45, 215/45		Orig.-Verschr.
	RC34	45	-	75-150	205/45, 215/45		Orig.-Verschr.
	RC32	45	-	77-150	205/45, 215/45, 225/40, 235/45		Orig.-Verschr., ET45 ist nur in den Farben SBM u. HGVP erhältlich!, auch für Hybrid
		45	-	75-150	235/45		Orig.-Verschr.
	RC30	45	ZP580	85-150	215/45, 215/50, 225/45, 235/45		
7,5 x 18	B32	45	ZP580	85-103	215/45, 215/50, 225/45		
		45	ZP580	85-150	235/45		
	B39	45	ZP580	85-150	215/45, 215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	85-150	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	85-150	215/45, 215/50, 225/45, 235/45		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	77-150	235/45, 245/45		
	B42	40	ZP580	85-150	215/45, 225/45		
		45	ZP580	85-150	215/45, 225/45, 235/45		
	B44	40	ZP580	85-150	215/45, 225/45		
		45	ZP580	85-150	215/45, 225/45, 235/45		
	AC-M10	45	ZP580D6F +R	85-150	215/45, 225/45, 235/45		+ Red.Ringe 73,1-67,1
7,5 x 19	RC32	45	-	77-150	205/45, 225/35, 225/40		Orig.-Verschr.
	B32	40	ZP580	85-150	225/40		
		45	ZP580D6F	85-150	225/40		
	AC-521	45	ZP580D6F +R	85-150	225/40		+ Red.Ringe 73,1-67,1, mit Verbreiterungen
8 x 19	AC-518	40	ZP580D6F +R	85-103	225/40		+ Red.Ringe 73,1-67,1, mit Verbreiterungen
	CA 24	45	ZP580	77-150	235/35, 235/40		
	Oxigin 29	40	ZP580	85-150	225/40		mit Verbreiterungen
8 x 20	B38	45	ZP580	85-150	225/35, 235/35		

Xcee'd Plug-in-Hybrid			ab 2020		CD	5/114,3	67,1	e4*2007/46*1299*07-..	
Sensor - Brocksens 7 od. HUFRDE215 - Artikelnummer 88086									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
6,5 x 16	RC34	40	ZP580D6F	77	205/60			i.V.	
	RC24	42	ZP580D6F	77	205/60, 215/60, 225/55				
		RC27	38+44	ZP580	77	205/60, 215/60, 225/55			
	38		ZP580	77	205/60, 215/60, 225/55				
	45		ZP580	77	205/60, 215/60, 225/55				
	RC30	42+44	ZP580D6F	77	205/60, 215/60, 225/55				
		45	ZP580	77	205/60, 215/60, 225/55				
			ZP580D6F	77	205/60, 215/60, 225/55				
	CA 20	45	ZP580	77	205/60, 215/60, 225/55				
	7 x 17	RC27	40	ZP580D6F	77	205/50, 215/50, 215/55			
45			ZP580	77	205/50, 215/50, 215/55, 225/50				
RC30		38	ZP580	77	205/55, 215/50, 215/55				
		45	ZP580D6F	77	205/55, 215/50, 215/55, 225/50				
			ZP580	77	205/55, 215/50, 215/55, 225/50				
RC34		38	ZP580	77	205/55, 215/50, 215/55				
		45	ZP580	77	205/55, 215/50, 215/55				

		45	ZP580	77	205/55, 215/50, 215/55, 225/50		
	CA 26	45	ZP580	77	205/55, 215/50, 215/55, 225/50		
7,5 x 18	RC30	45	ZP580	77	215/45, 215/50, 225/45, 235/45		
	B32	45	ZP580	77	215/45, 215/50, 225/45, 235/45		
	B39	45	ZP580	77	215/45, 215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	77	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	77	215/45, 215/50, 225/45, 235/45		+ Red.Ringe 73,1-67,1
8 x 18	RC29	45	ZP580	77	215/45, 225/45, 235/45		
	B37 / B38	45	ZP580	77	215/45, 225/45, 235/45		
	B42	40	ZP580	77	215/45, 225/45		
		45	ZP580	77	215/45, 225/45, 235/45		
	B44	40	ZP580	77	215/45, 225/45		
		45	ZP580	77	215/45, 225/45, 235/45		
	AC-518	40	ZP580D6F +R	77	215/45, 225/45		+ Red. Ringe 73,1-67,1, mit Verbreiterungen
	AC-M10	45	ZP580D6F +R	77	215/45, 225/45, 235/45		+ Red. Ringe 73,1-67,1, mit Verbreiterungen
7,5 x 19	B32	40	ZP580	77	225/40		
		45	ZP580D6F	77	225/40		
	AC-521	45	ZP580D6F +R	77	225/40		+ Red.Ringe 73,1-67,1, mit Verbreiterungen
8 x 19	AC-518	40	ZP580D6F +R	77	225/40		+ Red. Ringe 73,1-67,1, mit Verbreiterungen
	Oxigin 29	40	ZP580	77	225/40		mit Verbreiterungen
8 x 20	B38	45	ZP580	77	225/35, 235/35		

e-Niro		ab 2019		DE	5/114,3	67,1	e4*2007/46*1139*...	
Sensor - Brocksens 5								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	50	ZP580D6F	27-29	215/55, 225/50			
	RC30	50	ZP580D6F	27-29	215/55, 225/50			
	RC32	50	-	27-29	215/55			Orig.-Verschr.
	RC34	50	-	27-29	215/50, 215/55			Orig.-Verschr.
	RC27	47	ZP580D6F	27-29	215/55, 225/50			
	RC32	43,5+45 +47	-	27-29	215/50			Orig.-Verschr.
	RC34	47	-	27-29	215/50			Orig.-Verschr.
7,5 x 17	B39	50	ZP580D6F	27-29	215/55, 225/50			
	RC24	50	ZP580	27-29	215/55, 225/50			
			ZP580D6F	27-29	215/55, 225/50			Ausführung "M3"
	RC29	48	ZP580	27-29	215/55, 225/50			
	RC32	46	-	27-29	215/50, 215/55, 225/50, 245/45			Orig.-Verschr.
7 x 18	B24	48	ZP580	27-29	215/55, 225/50			
	RC32	45+48,5 +51	-	27-29	215/45, 215/50, 225/45			Orig.-Verschr.
7,5 x 18	RC30	49,5+55	ZP580D6F	27-29	225/45			
	RC32	45	-	27-29	215/45, 215/50, 225/45, 235/45			Orig.-Verschr., ET45 nur in SBM u. HGVP
		51	-	27-29	215/45			Orig.-Verschr.
	B32	45	ZP580	27-29	225/45			
		49,5	ZP580D6F	27-29	225/45			
		50,5	ZP580D6F	27-29	225/45			
	B39	45	ZP580	27-29	225/45			
		50	ZP580D6F	27-29	225/45			
	AC-MB6	45	Artikel Nr. 98499	27-29	225/45			Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	27-29	225/45			+ Red.Ringe 73,1-67,1
8 x 18	RC27	46	ZP580D6F	27-29	215/45, 225/45			bei 225/45 ✖
	RC29	45	ZP580	27-29	225/45			
	RC34	50	-	27-29	215/45			Orig.-Verschr.
	B24	48	ZP580	27-29	225/45			
	B36	45	ZP580	27-29	225/45			
	B38	45+49	ZP580	27-29	225/45			
	B42 / B44	45	ZP580	27-29	225/45			
8,5 x 18	AC-M10	45	ZP580D6F +R	27-29	225/45			+ Red.Ringe 73,1-67,1
	B32	45	ZP580	27-29	225/45			
7,5 x 19	RC32	45+50,5	-	27-29	225/40			Orig.-Verschr.
	B32	45+49,5	ZP580D6F	27-29	225/40			
	AC-521	45	ZP580D6F +R	27-29	225/40			+ Red.Ringe 73,1-67,1
8 x 19	RC27	47	-	27-29	225/40			Orig.-Verschr., ✖
	RC29	48	ZP580	27-29	225/40			
	B24	50	ZP580	27-29	225/40			

8 x 19	B38	45	ZP580	27-29	225/40		
	CA 19	45	ZP580	27-29	225/40		
	Oxigin 29	50	ZP580	27-29	225/40		
8,5 x 19	B32 / B37	45	ZP580	27-29	225/40		
	B42	45	ZP580	27-29	225/40		
	B43	46,5	ZP580D6F	27-29	225/40		
	Oxigin 28	45	ZP580	27-29	225/40		
8 x 20	B38	50	ZP580	27-29	225/35		

Niro (Hybrid)		ab 05.2016		DE	5/114,3	67,1	e4*2007/46*1139*..	
Sensor - Continental - Artikelnummer 97318								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	45	-	77-78	205/60			Orig.-Verschr., Plug-in-Hybrid mit Kit ZP580D6F
	RC32	45	-	77	205/60, 205/65, 215/55, 215/60, 225/55, 235/50			Orig.-Verschr.
	RC34	45	-	77	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55			Orig.-Verschr., nicht Bremse 300x10mm HA
	RC24	42	-	77-78	205/60, 215/55			Orig.-Verschr., Plug-in-Hybrid mit Kit ZP580D6F
		48	ZP580	77-78	205/60, 215/55, 225/55			
	RC27	45	ZP580	77-78	205/60, 215/55, 225/55			auch Plug-In-Hybrid
		50	-	77-78	205/60, 215/55, 225/55			Orig.-Verschr.
			ZP580	77-78	205/60, 215/55, 225/55			
	RC30	45	ZP580	77-78	205/60, 215/55, 225/55			auch Plug-In-Hybrid
		47	-	77-78	205/60, 215/55, 225/55			Orig.-Verschr.
	RC32	42,5+44+47,5	-	77	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55			Orig.-Verschr.
		50	-	77	205/60, 205/65, 215/55, 215/60, 225/55			Orig.-Verschr.
		40+50	-	77	205/60, 205/65, 215/55, 215/60, 225/55			Orig.-Verschr.
	RC34	44+46	-	77	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55			Orig.-Verschr., nicht Bremse 300x10mm HA
7 x 17	CA 20	45	ZP580	77-78	205/60, 215/55, 225/55			
	RC24	50	-	77,2	205/50, 205/55, 225/45			Orig.-Verschr.
	RC27	45	ZP580	77-78	205/50, 205/55, 215/50, 225/45			auch Plug-In-Hybrid
		47	-	77-78	205/50, 205/55, 215/50, 225/45, 225/50			Orig.-Verschr.
		50	-	77-78	205/50, 205/55, 215/50, 225/45			Orig.-Verschr.
	RC30	45	ZP580	77-78	205/50, 205/55, 215/50, 225/45			auch Plug-In-Hybrid
		-	77-78	205/50, 205/55, 215/50, 225/45			Orig.-Verschr.	
		47	-	77-78	205/50, 205/55, 215/50, 225/45, 225/50			Orig.-Verschr.
		50	-	77-78	205/50, 205/55, 215/50, 225/45			Orig.-Verschr.
	RC32	45	-	77	205/50, 205/55, 215/50, 215/55, 225/45, 225/50			Orig.-Verschr.
		48,5	-	77	205/50, 205/55, 215/50, 215/55, 225/45			Orig.-Verschr.
		43,5+47+50	-	77	205/50, 205/55, 215/50, 215/55, 225/45, 225/50			Orig.-Verschr.
	RC34	47	-	77	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/50			Orig.-Verschr.
		50	-	77	205/50, 205/55, 215/50, 215/55, 225/45, 225/50			Orig.-Verschr.
	B39	45	ZP580	77,2	205/50, 205/55, 215/50, 225/45			auch Plug-In-Hybrid
50		-	77,2	205/50, 205/55, 215/50, 225/45			Orig.-Verschr.	
7,5 x 17	RC28	45	ZP580	77-78	205/50, 205/55, 225/45			auch Plug-In-Hybrid
	RC27	46	ZP580D6F	77	205/50, 205/55, 215/50, 215/55, 235/45			bei 205/55 u. 215/55 ✖
	RC29	48	ZP580	77-78	205/50, 205/55, 215/50, 225/45, 225/50			
	RC32	46	-	77	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/45, 245/45			Orig.-Verschr.
	B36	46	ZP580	77-78	205/50, 205/55, 215/50, 225/45, 235/45			
7 x 18	RC32	45	-	77	205/45, 215/45, 215/50, 225/45			Orig.-Verschr.
		48,5	-	77	205/45, 215/45, 225/45			Orig.-Verschr.
7,5 x 18	RC30	49,5	-	77-78	225/45			Orig.-Verschr.
		50	-	77,2	225/45			Orig.-Verschr.
			77-78	205/45, 215/45, 225/40, 225/45				
	B39	50	-	77,2	205/45, 215/45, 225/40, 225/45			Orig.-Verschr.
	RC30	50,5	-	77,2	205/45, 215/45, 225/40, 225/45			Orig.-Verschr.
	RC32	45	-	77	205/45, 215/45, 225/40, 225/45, 235/45			Orig.-Verschr., ET45 ist nur in den Farben SBM u. HGVP erhältlich!
	B32	45	ZP580	77,2	205/45, 215/45, 225/40, 225/45			
		50,5	-	77,2	205/45, 215/45, 225/40, 225/45			Orig.-Verschr.
	AC-MB6	45	Artikel Nr. 98499	77-78	205/45, 215/45, 225/40, 225/45			Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F+R	77-78	205/45, 215/45, 225/40, 225/45			+ Red.Ringe 73,1-67,1, auch Plug-in-Hybrid
8 x 18	Oxigin 18	45	ZP580	77	205/45, 215/45, 225/40			
	RC29	45	ZP580	77-78	215/45, 225/40, 225/45			auch Plug-In-Hybrid
	RC34	50	-	77	205/45, 215/45, 225/40, 225/45			Orig.-Verschr.
	B38	45	ZP580	77-78	215/45, 225/40, 225/45			auch Plug-In-Hybrid
		49	ZP580	77,2	215/45, 225/40, 225/45			
B42 / B44	45	ZP580	77-78	215/45, 225/40, 225/45			auch Plug-In-Hybrid	
	RC32	45	-	77	225/35, 225/40			Orig.-Verschr.
50		-	69-77	225/40			Orig.-Verschr.	

7,5 x 19	RC34	49,5	-	77	225/35, 225/40		Orig.-Verschr.
	B32	45	-	77,2	225/35, 225/40		Orig.-Verschr.
		49,5	-	77-78	225/35, 225/40		Orig.-Verschr.
	B39	50	-	77,2	225/35, 225/40		Orig.-Verschr.
8 x 19	AC-521	45	ZP580D6F +R	77-78	225/35		+ Red.Ringe 73,1-67,1, auch Plug-in-Hybrid
	RC27	47	-	77	225/35		Orig.-Verschr.
	RC29	48	ZP580	77,2	225/35		
	B38	45	ZP580	77,2	225/35, 225/40		

Niro Hybrid NEU Sommer 2022 SG2 5/114,3 67,1 e9*2018/858*11241*..							
Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC34	46	-	77	205/60		Orig.-Verschr., nur in den Farben SG u. SGVP erhältlich!
				69-77	205/60, 215/60, 225/55		
	RC24	48	ZP580	77	205/60, 215/55, 225/55		
		50	-	77	205/60, 215/55, 225/55		Orig.-Verschr. für Alufelgen, ET50 gibt es nur in SKM!
	RC27	50	ZP580	77	205/60, 215/55, 225/55		auch Plug-in-Hybrid
	RC32	42,5+45	-	77	205/60, 215/60		Orig.-Verschr.
		47,5	-	77	205/60, 215/60, 225/55		Orig.-Verschr.
		50	-	77	215/60, 225/55, 235/55		Orig.-Verschr.
	CA 20	45	ZP580	77	205/60, 215/55		
	RC27	45	ZP580	77	205/55		auch Plug-in-Hybrid
7 x 17	RC32	45	-	69-77	205/55, 215/50		Orig.-Verschr.
		47	-	69-77	205/55, 215/50		Orig.-Verschr.
		50	-	77	205/55, 215/50, 225/50		Orig.-Verschr.
	RC34	47	-	69-77	205/55, 215/50		Orig.-Verschr.
		50+52	-	77	205/55, 215/50, 225/50		Orig.-Verschr.
	B39	45	ZP580	77	205/55		auch Plug-in-Hybrid
		50	-	77	205/55, 215/50, 225/50		Orig.-Verschr. für Alufelgen, auch Plug-in-Hybrid
	CA 26	45	ZP580	77	205/55		auch Plug-in-Hybrid
	RC24	50	ZP580	77	205/55, 215/50, 235/45		
		50	-	77	205/55, 215/50, 235/45		Orig.-Verschr. für Alufelgen
7,5 x 17	RC28	45	ZP580	77	205/55		
	RC32	46	-	77	205/55		Orig.-Verschr.
		52,5	-	77	205/55, 215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
	B24	48	ZP580	77	205/55		
	B36	46	ZP580	77	205/55		
	RC27	46+50	-	77	215/45, 225/45		Orig.-Verschr. für Alufelgen
		45	-	69-77	215/45, 225/45		Orig.-Verschr.
	RC34	45	-	69-77	215/45, 225/45		Orig.-Verschr.
7,5 x 18	RC32	52	-	77	225/45		Orig.-Verschr.
				69-77	215/45, 225/45		
	RC34	45+51	-	77	215/45, 225/45		Orig.-Verschr.
		45	-	77	215/45, 225/45		Orig.-Verschr.
	RC34	49,5+51	-	69-77	215/45, 225/45		Orig.-Verschr.
		49,5+50,5	-	77	215/45, 225/45		Orig.-Verschr. für Alufelgen
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	77	215/45		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	77	215/45		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	77-78	205/45		
	RC27	46	-	77	215/45		Orig.-Verschr. für Alufelgen
8 x 18	RC34	50	-	69-77	215/45, 225/45, 235/40		Orig.-Verschr.
	B24	48	ZP580	77	215/45, 225/45		
	B36 / B42 / B44	45	ZP580	77	215/45		
	AC-M10	45	ZP580D6F +R	77	215/45		+ Red.Ringe 73,1-67,1
7,5 x 19	RC32	45+49,5	-	77	225/40		Orig.-Verschr.
		50,5+51	-	77	225/40		Orig.-Verschr.
		53	-	69-77	225/40		Orig.-Verschr.
	RC34	49,5	-	69-77	225/40		Orig.-Verschr.
		51	-	77	225/40		Orig.-Verschr.
	CA 26	50	ZP580D6F	77	225/35, 225/40		
8 x 19	RC32	53,5	-	77	225/40, 235/35		Orig.-Verschr.
	Oxigin 29	50	ZP580	77	225/35, 225/40		

Niro-EV elektro NEU Sommer 2022 SG2 5/114,3 67,1 e9*2018/858*11241*..							
Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC34	52	-	50	215/55		Orig.-Verschr.
	RC27	45	ZP580	50 (150)	215/55		
	B39	45	ZP580	50 (150)	215/55		

7,5 x 17		50	-	50 (150)	215/55, 225/50		Orig.-Verschr. für Alufelgen
	CA 26	45	ZP580	50 (150)	215/55		
	RC24	50	-	50 (150)	215/55		Orig.-Verschr. für Alufelgen
		50	ZP580	50 (150)	215/55		
		48	ZP580	50 (150)	215/55		
7 x 18	CA 20	48	ZP580	50 (150)	215/55		
	RC27	46+50	-	50 (150)	215/45, 215/50, 225/45		Orig.-Verschr. für Alufelgen
7,5 x 18	B32	49,5+50,5	-	50 (150)	215/45, 215/50, 225/45, 235/45		Orig.-Verschr. für Alufelgen
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	50 (150)	215/45, 225/45		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	50 (150)	215/45, 225/45		+ Red.Ringe 73,1-67,1
8 x 18	RC27	46	-	50 (150)	215/45, 225/45		Orig.-Verschr. für Alufelgen
	B24	48	ZP580	50 (150)	215/45, 225/45		
	B36 / B42	45	ZP580	50 (150)	215/45		
	B44	45	ZP580	50 (150)	215/45		
	AC-M10	45	ZP580D6F +R	50 (150)	215/45		+ Red.Ringe 73,1-67,1
7,5 x 19	AC-521	45	ZP580D6F +R	50 (150)	225/40		+ Red.Ringe 73,1-67,1
	CA 26	50	ZP580D6F	50 (150)	225/40		
8 x 19	RC29	48	ZP580	50 (150)	225/40		
	Oxigin 29	50	ZP580	50 (150)	225/40		
8 x 20	B38	50	ZP580	50 (150)	225/35		

Kia EV3 NEU		2024			SV1	5/114,3	67,1	e6*2018/858*00331*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC34	48	-	50	215/60				Orig.-Verschr.
	RC32	45	-	50	215/60				Orig.-Verschr.
7,5 x 17	CA 20	48	ZP580	50 (150)	215/60				
7 x 18	RC32	45	-	50	215/50, 215/55				Orig.-Verschr.
	RC34	45	-	50	215/50, 215/55				Orig.-Verschr.
7,5 x 18	RC32	52	-	50	215/50, 215/55, 225/50, 225/55, 235/50, 245/45				Orig.-Verschr.
	RC34	45	-	50	215/50, 215/55				Orig.-Verschr.
8 x 18	RC34	50	-	50	215/50, 215/55				Orig.-Verschr.
7,5 x 19	RC32	50	-	50	215/50				Orig.-Verschr.
				50	215/45, 215/50, 225/45, 235/45, 245/45				
8 x 19	CA 26	50	ZP580D6F	50 (150)	215/50				
	RC27	47	-		225/45				Orig.-Verschr., i.V.

Kia EV6 elektro NEU		ab 2021	CV	5/114,3	67,1	e9*2018/858*11073*..
Sensor - Brocksens 7						

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 19	RC32	54,5	-	42-81	235/55		Orig.-Verschr., Felge ist nur in der Farbe HGVP erhältlich!
	RC34	54,5	-	42-81	235/55, 245/50		Orig.-Verschr.
	RC32	49,5+50,5+51	-	42-81	235/55		Orig.-Verschr., ET49,5 ist nur in den Farben SBM u. HGVP erhältlich!
		50	-	42-81	235/50, 235/55		Orig.-Verschr.
		53	-	42-81	235/50, 235/55, 245/50		Orig.-Verschr.
	RC34	49,5+51	-	42-81	235/55		Orig.-Verschr.
	B32	45	ZP580D6F	42-81	235/50, 235/55		
	AC-521	45	ZP580D6F +R	42-81	235/50, 235/55		+ Red.Ringe 73,1-67,1
8 x 19	RC29	48	ZP580	42-81	235/50, 235/55		
	RC32	53,5	-	42-81	235/50, 235/55		Orig.-Verschr.
		55	-	42-81	235/55, 245/50		Orig.-Verschr.
	RC34	55	-	42-81	235/55, 245/50		Orig.-Verschr.
	Oxigin 29	50	ZP580	42-81	235/50, 235/55		
8 x 20	B43	57	ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45		
8,5 x 20	RC29	45	ZP580	42-81	235/45		
	RC36	54	-	42-81	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., incl. Facelift 2025
	B43	53,5	ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45, 265/45		
54+54,5		ZP580D6F	42-81	235/45, 235/50, 245/45, 255/45, 265/45			
9 x 20	B40	46	ZP580D6F	42-81	235/45		
	CA 20 / CA 23	45	ZP580	42-81	235/45		
8,5 x 21	B41	47	ZP580	42-81	235/45		

Kia EV6 GT elektro NEU			ab 2022			CV	5/114,3	67,1	e9*2018/858*11073*..		
Sensor - Brocksens 7											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8,5 x 21	B41	43,5	-	143	255/40					Orig.-Verschr., nur FG und SG	
	B43	43,5	-	143 (430)	255/40					Orig.-Verschr.	

Kia EV9 NEU		2.Quartal 2023			MV1	5/114,3	67,1	e4*2018/858*00178*..	
-------------	--	----------------	--	--	-----	---------	------	----------------------	--

Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 19	RC32	53,5	-	53-113	255/60, 265/55, 275/55		Orig.-Verschr.
8,5 x 20	B41	54	-	53-113	265/50		Orig.-Verschr.
8,5 x 21	B41	47	ZP580	53-113	265/45		
	B43	43,5	ZP580D6F	53-113	265/45		

Optima	(siehe Konfigurator)	ab 12.2015	JF	5/114,3	67,1	e4*2007/46*1018/00-06
--------	----------------------	------------	----	---------	------	-----------------------

Optima Hybrid	(siehe Konfigurator)	ab 2016	JF	5/114,3	67,1	e4*2007/46*1018*...
---------------	----------------------	---------	----	---------	------	---------------------

Optima SW	(siehe Konfigurator)	Facelift 2018	JF	5/114,3	67,1	e4*2007/46*1018*...
-----------	----------------------	---------------	----	---------	------	---------------------

Optima GT / Sportswagon GT	(siehe Konfigurator)		JF	5/114,3	67,1	e4*2007/46*1018*...
----------------------------	----------------------	--	----	---------	------	---------------------

Picanto III	(siehe Konfigurator)	ab 04.2017	JA	4/100	54,1	e11*2007/46*3848*..
-------------	----------------------	------------	----	-------	------	---------------------

Picanto III X-Line	NEU	ab 2018	JA	4/100	54,1	e11*2007/46*3848*..., e5*2007/46*1078*..
--------------------	-----	---------	----	-------	------	--

Sensor - Continental VDO - Artikelnummer 74441							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC24	42	ZP422D6F	49-74	175/55, 175/60		incl. Facelift 2020
		46	ZP422D6F	49-74	175/55, 175/60, 185/55		incl. Facelift 2020
	RC30	46	ZP422D6F	49-74	175/55, 175/60, 185/55		incl. Facelift 2020
		47	ZP422D6F	49-74	175/55, 175/60, 185/55		
6 x 16	RC30	45+50	ZP422D6F	62, 74	175/50, 195/45		incl. Facelift 2020
6,5 x 16	RC24	48	ZP422	49-74	195/45		
	RC30	48	ZP422	49-74	195/45		incl. Facelift 2020
7 x 17	B24	45	ZP422	49-74	195/40		✖
	B39	44	ZP422	62, 74	195/40		✖

Kia Rio	(siehe Konfigurator)	ab 09.11	UB	4/100	54,1	e11*2007/46*0195*...
---------	----------------------	----------	----	-------	------	----------------------

Kia Rio		ab 02.2017	YB	4/100	54,1	e11*2007/46*3777*..., e5*2007/46*1077*..
---------	--	------------	----	-------	------	--

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC24	46	ZP422D6F	57-89	185/60, 185/65 , 195/60		
	RC30	46	ZP422D6F	57-89	185/60, 185/65 , 195/60		incl. Facelift 2020, ET46 ist nur in SG erhältlich!
	RC24	42	ZP422D6F	57-89	185/60, 185/65, 195/60, 205/55, 205/60		ab 205/55 ✖
	RC30	40	ZP422	57-89	185/60, 185/65		
		47	ZP422D6F	57-89	185/60, 185/65, 195/60		
6 x 16	RC34	49	-	62-88	185/55, 185/60, 195/50, 195/55 , 205/50		Orig.-Verschr.
	RC30	45+50	ZP422D6F	57-89	185/55, 195/50, 195/55		incl. Facelift 2020
		45	-	57-88	185/55, 195/50, 195/55		Orig.-Verschr.
		50	-	57-88	185/55, 185/60, 195/50, 195/55, 205/50		Orig.-Verschr.
6,5 x 16	RC24	48	ZP422	57-89	185/55, 195/50, 195/55		nicht für belüftete Scheibenbremsen mit 256mm
	RC30	45	ZP422D6F	57-89	185/55, 195/50, 195/55		incl. Facelift 2020
		48	ZP422	57-89	185/55, 195/50, 195/55		incl. Facelift 2020
7 x 16	RC28	45	ZP422	57-89	195/50, 195/55		✖
6,5 x 17	RC34	49	-	62-88	185/45, 185/50, 195/45, 205/45		Orig.-Verschr.
				58-100	205/45		Orig.-Verschr., mit Serienreifen in 15 Zoll
		43	-	57-88	185/45, 195/45		Orig.-Verschr.
	RC14 EL	45	ZP422D6F	57-89	195/45, 205/45		incl. Facelift 2020, RLP, SVR , nicht für belüftete Scheibenbremsen mit 256mm

Sorento IV	(siehe Konfigurator)	ab 2015	UM	5/114,3	67,1	e4*2007/46*0894*..
------------	----------------------	---------	----	---------	------	--------------------

Sorento IV		ab 2020	MQ4	5/114,3	67,1	e4*2007/46*1530*...
------------	--	---------	-----	---------	------	---------------------

Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	47	-	132-148	235/60, 235/65		Orig.-Verschr., nur KS silber
	RC30	47	-	132-148	235/60, 235/65		Orig.-Verschr., nicht Bremse ab 345mm
	RC34	47	-	118-148	235/65 , 245/60		Orig.-Verschr., nicht Bremse 345x30mm
	RC30	45	-	132-148	235/60, 235/65		Orig.-Verschr., nicht Bremse ab 345mm
		43,5	-	132-148	235/65, 245/60		Orig.-Verschr., nicht Bremse 345x30mm
	RC32	50	-	132-148	235/65, 245/60, 255/60		Orig.-Verschr., nicht Bremse 345x30mm
7,5 x 17	CA 26	45	-	117-148	235/60		Orig.-Verschr., incl. FL2024, nicht Bremse ab 345mm
	RC27	46	-	132-148	235/60, 235/65		Orig.-Verschr., nicht Bremse ab 345mm
	RC29	48	ZP580	132-148	235/60, 235/65		incl. Facelift 2017, nicht Bremse ab 345mm
	RC32	46	-	132-148	235/65, 245/60		Orig.-Verschr.
		52,5	-	132-148	235/65, 245/60, 255/60		Orig.-Verschr., nicht Bremse 345x30mm
	B36	46	ZP580	132-148	235/60		nicht Bremse ab 345mm
	CA 20	48	ZP580	117-148	235/60, 235/65		incl. FL2024, nicht Bremse ab 345mm
	RC27	46	-	132-148	235/55, 235/60		Orig.-Verschr.
		50	-	132-148	235/55, 235/60, 255/50, 255/55		Orig.-Verschr.

7 x 18	RC32	45	-	118-148	235/60		Orig.-Verschr.
		51	-	132-148	235/60		Orig.-Verschr.
		48,5	-	132-148	235/60, 255/55		Orig.-Verschr.
	RC34	45	-	118-148	235/60		Orig.-Verschr.
7,5 x 18	RC30	49,5	-	132-148	235/55, 235/60		Orig.-Verschr., nur SG schwarz glanz
		50	-	132-148	235/60		Orig.-Verschr.
	B32	49,5	-	132-148	235/55, 235/60		Orig.-Verschr., auch für Hybrid
	RC32	51+52	-	118-148	235/60, 255/55		Orig.-Verschr.
	RC34	45	-	118-148	235/60		Orig.-Verschr.
		51	-	118-148	235/60, 255/55		Orig.-Verschr.
	B32	45	ZP580	117-148	235/55, 235/60		incl. Facelift 2024
		50,5	-	117-148	235/55, 235/60		Orig.-Verschr., incl. Facelift 2024
	B39	45	ZP580	132-148	235/55, 235/60		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	117-148	235/55, 235/60		incl. Facelift 2024, Kit mit Artikelnummer 98499
8 x 18	AC-521	45	ZP580D6F +R	132-148	235/55, 235/60		+ Red.Ringe 73,1-67,1
8 x 18	RC27	46	-	132-148	235/55, 235/60		Orig.-Verschr.
	RC34	50	-	118-148	235/60		Orig.-Verschr.
7,5 x 19	B32	49,5	-	132-148	235/50, 235/55 , 245/50		Orig.-Verschr.
		49,5	-	132-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid, nur SBM und HGVP
	RC34	49,5	-	132-148	235/55		Orig.-Verschr., auch für Hybrid
				118-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
	RC32	49,5	-	132-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid, nur SBM und HGVP
		50+51	-	132-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
		45	-	132-148	235/55		Orig.-Verschr., auch für Hybrid
		53	-	118-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
	RC34	51+54,5	-	132-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
	B39	45	ZP580	132-148	235/50, 235/55		
	AC-521	45	ZP580D6F +R	132-148	235/50, 235/55		+ Red.Ringe 73,1-67,1
8 x 19	RC27	47	-	132-148	235/50, 235/55, 255/45		Orig.-Verschr.
	RC29	48	ZP580	132-148	235/50, 235/55, 255/45		
	RC32	53,5+55	-	132-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
	RC34	55	-	118-148	235/55, 255/50		Orig.-Verschr., auch für Hybrid
	Oxigin 29	50	ZP580	132-148	235/50, 235/55, 255/45		
8,5 x 20	RC36	54	-	117-148	235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr., incl. Facelift 2024
	B41	54	-	142-148	255/45		Orig.-Verschr.
				118-148	235/50, 255/45, 265/45		Orig.-Verschr., auch für Hybrid
	B43	54	ZP580D6F	117-148	235/45, 235/50, 245/45, 255/40, 255/45		beide ETs sind ECE, ET54 incl. Facelift 2024
		54,5	ZP580D6F	132-148	235/45, 235/50, 245/45, 255/40, 255/45		
	RC29	45	ZP580	132-148	235/45, 245/45		
	B32 / B42	45	ZP580	132-148	235/45, 245/45		
	B43	53,5	ZP580D6F	132-148	235/45, 235/50, 245/45, 255/40, 255/45		
9 x 20	B37	43	ZP580	132-148	235/45		
	CA 23	45	ZP580	132-148	235/45		
8,5 x 21	B41	43,5	-	132-148	235/45, 245/40		Orig.-Verschr.
		47	ZP580	132-148	235/45, 245/40, 255/40		auch für Hybrid

Sorento PHEV NEU		ab Jänner 2021		MQ4	5/114,3	67,1	e4*2007/46*1530*..
Sensor - Brocksens 7							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC30	45	ZP580	132 (195)	235/55, 235/60		
		49,5+50,5	-	132 (195)	235/55, 235/60		Orig.-Verschr.
	B32	45	ZP580	117-132	235/55, 235/60		incl. Facelift 2024
		50,5	-	117-132	235/55, 235/60		Orig.-Verschr., incl. Facelift 2024
	B39	45	ZP580	132 (195)	235/55, 235/60		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	117-132	235/55, 235/60		incl. Facelift 2024, Kit mit Artikelnummer 98499
8 x 18	AC-521	45	ZP580D6F +R	132 (195)	235/55, 235/60		+ Red.Ringe 73,1-67,1
	RC27	46	-	132 (195)	235/55, 235/60		Orig.-Verschr.
7,5 x 19	B24	48	ZP580	132 (195)	235/55, 235/60		
	B32	49,5	-	132 (195)	235/50, 235/55 , 245/50		Orig.-Verschr.
		45	-	132 (195)	235/50, 235/55		Orig.-Verschr.
	B39	45	ZP580	132 (195)	235/50, 235/55		
	AC-521	45	ZP580D6F +R	132 (195)	235/50, 235/55		+ Red.Ringe 73,1-67,1
8 x 19	RC27	47	-	132 (195)	235/50, 235/55, 255/45		Orig.-Verschr.
	RC29	48	ZP580	132 (195)	235/50, 235/55, 255/45		
	Oxigin 29	50	ZP580	132 (195)	235/50, 235/55, 255/45		
8,5 x 20	RC29	45	ZP580	132 (195)	235/45, 245/45		
	RC36	54	-	117-132	235/45, 235/50, 245/45, 255/40, 255/45		Orig.-Verschr., incl. Facelift 2024
	B32 / B42	45	ZP580	132 (195)	235/45, 245/45		
		53,5	ZP580D6F	132 (195)	235/45, 235/50, 245/45, 255/40, 255/45		

9 x 20	B43	54	ZP580D6F	117-132	235/45, 235/50, 245/45, 255/40, 255/45		incl. Facelift 2024
		54,5	ZP580D6F	132 (195)	235/45, 235/50, 245/45, 255/40, 255/45		
	B37	43	ZP580	132 (195)	235/45		
	CA 23	45	ZP580	132-148	235/45		

Soul	ab 2014	PS	5/114,3	67,1	e4*2007/46*0825*...
------	---------	----	---------	------	---------------------

Sensor - Brocksens 5

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	47	-	91-113	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr. für Alufelgen
	RC24	42	ZP580D6F	91-113	205/60, 205/65, 215/55, 215/60, 225/55		ohne Radhausverbreiterung ✖
	RC27	45+50	ZP580	91-113	205/60, 205/65, 215/55, 215/60, 225/55		
	RC30	48	-	91-113	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr.
		45+50	ZP580	91-113	205/60, 205/65, 215/55, 215/60, 225/55		ET45 bei 225/55 ✖
	RC32	44	-	91-113	205/60, 205/65, 215/55, 215/60		Orig.-Verschr., nicht Bremse 280mm
		45	-	91-113	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., nicht Bremse 280mm
		50	-	91-113	205/60, 205/65, 215/55, 215/60, 225/55, 235/50		Orig.-Verschr., nicht Bremse 280mm
6,5 x 17	RC27	51	ZP580D6F	91-113	215/55		
7 x 17	RC27	45+50	ZP580D6F	91-113	205/55, 215/50, 215/55, 225/50		ET45 ohne Radhausverb. ✖
	RC30	47+50	ZP580D6F	91-113	205/55, 215/50, 215/55, 225/50		ab 225/50 ✖
	RC32	47+50	-	91-150	205/50, 205/55, 215/50, 215/55, 225/45, 225/50		Orig.-Verschr., nicht Bremse 280mm
		48,5	-	91-150	205/50, 205/55		Orig.-Verschr., nicht Bremse 280mm
		53	-	91-150	205/50, 205/55, 215/50, 215/55, 225/45, 225/50		Orig.-Verschr., nicht Bremse 280mm
	B39	50	-	91-113	205/55, 215/50, 215/55, 225/50		Orig.-Verschr. für Alufelgen, ohne Verbr. 225/50 ✖
7 x 18	RC32	45+48,5 +51	-	91-150	205/45, 215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC30	55	ZP580D6F	91-113	215/45, 215/50, 225/45, 235/45		
	RC32	55	-	91-150	235/45		Orig.-Verschr.
	B32	55	-	91-150	235/45		Orig.-Verschr. für Alufelgen
		55	ZP580D6F	91-113	215/45, 215/50, 225/45, 235/45		

weitere Dimensionen/Designs siehe Konfigurator

Soul Elektro (siehe Konfigurator)	ab 2014	PSEV	5/114,3	67,1	e9*2007/46*6160*...
-----------------------------------	---------	------	---------	------	---------------------

e-Soul	ab 2019	SK3	5/114,3	67,1	e4*2007/46*1365*..
--------	---------	-----	---------	------	--------------------

Sensor - Continental - Artikelnummer 97318

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	50	ZP580D6F	27-29	215/55, 225/50		
	RC32	50	-	27-29	215/55		Orig.-Verschr.
	RC34	50	-	27-29	215/55		Orig.-Verschr.
	RC27	47	ZP580D6F	27-29	215/55, 225/50		
	RC30	47	ZP580D6F	27-29	215/55		
		50	ZP580D6F	27-29	215/55, 225/50		
	RC32	45	-	27-29	215/55, 225/50, 235/50		Orig.-Verschr.
		43,5+47	-	27-29	215/55, 225/50		Orig.-Verschr.
	RC34	47	-	27-29	215/55, 225/50		Orig.-Verschr.
		52	-	27-29	215/55		Orig.-Verschr.
7,5 x 17	B39	45	ZP580	27-29	215/55		
	RC24	50	ZP580	27-29	215/55, 225/50		
			ZP580D6F	27-29	215/55, 225/50		Ausführung "M3"
7 x 18	RC29	48	ZP580	27-29	215/55		
	RC27	50	-	27-29	215/45, 215/50, 225/45		Orig.-Verschr.
	RC32	45+51	-	27-29	215/45, 215/50, 225/45		Orig.-Verschr.
48,5		-	27-29	215/45, 215/50, 225/45		Orig.-Verschr.	
7,5 x 18	RC30	49,5+55	ZP580D6F	27-29	215/50, 225/45		
	RC32	45+51	-	27-29	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32	45	ZP580	27-29	215/50, 225/45		bei 215/50 ✖
		49,5	ZP580D6F	27-29	215/50, 225/45		
		50,5	ZP580D6F	27-29	215/50, 225/45		
	B39	50	ZP580D6F	27-29	215/50, 225/45		
	AC-521	45	ZP580D6F +R	27-29	225/45		+ Red.Ringe 73,1-67,1
8 x 18	RC27	46	ZP580D6F	27-29	215/45, 225/45		
	RC29	45	ZP580	27-29	225/45		✖
	RC34	50	-	27-29	215/45, 225/45		Orig.-Verschr.
	B38	49	ZP580	27-29	225/45		
7,5 x 19	RC32	45+49,5	-	27-29	225/40		Orig.-Verschr.
		50,5+51	-	27-29	225/40		Orig.-Verschr.
	RC34	49,5+51	-	27-29	225/40		Orig.-Verschr.
	B32	45+49,5	ZP580D6F	27-29	225/40		
	AC-521	45	ZP580D6F +R	27-29	225/40		+ Red.Ringe 73,1-67,1
8 x 19	RC27	47	-	27-29	225/40		Orig.-Verschr.
	RC29	48	ZP580	27-29	225/40		
	Oxigin 29	50	ZP580	27-29	225/40		
7,5 x 20	B43	45	ZP580D6F	27-29	225/35		
8 x 20	B38	50	ZP580	27-29	225/35		

8,5 x 20	B24	50	ZP580	27-29	225/35		
----------	-----	----	-------	-------	--------	--	--

Sportage		ab 01.16		QLE		5/114,3		67,1		e11*2007/46*3144*...., e11*2007/46*3139*...	
Sensor - Brocksens 5											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 16	RC32	42,5	-	85-136	215/65, 215/70 , 225/65				Orig.-Verschr., nicht für elektr. Parkbremse		
	RC34	45	-	114-136	215/65, 215/70 , 225/65				Orig.-Verschr., nicht für elektr. Parkbremse u. nicht Bremse 320x28mm, ECE nur Typ QL		
	RC24	42	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr. für Alufelgen, incl. Facelift 2018, auch Typ QLE-KMD, nicht für elektr. Parkbremse		
	RC27	45	ZP580	85-136	215/65, 215/70, 225/65, 235/60, 235/65				nicht für elektr. Parkbremse		
		50	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr., nicht für elektr. Parkbremse		
	RC30		ZP580	85-136	215/65, 215/70, 225/65, 235/60, 235/65				nicht für elektr. Parkbremse		
		45	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr., nicht für elektr. Parkbremse		
			ZP580	85-136	215/65, 215/70, 225/65, 235/60, 235/65				nicht für elektr. Parkbremse		
		50	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr., nicht für elektr. Parkbremse		
	RC32	47,5+50	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr., nicht für elektr. Parkbremse		
RC34		44	-	85-136	215/65, 215/70, 225/65				Orig.-Verschr., nicht für elektr. Parkbremse u. nicht Bremse 320x28mm		
		46+50	-	85-136	215/65, 215/70, 225/65, 235/60, 235/65				Orig.-Verschr., nicht für elektr. Parkbremse u. nicht Bremse 320x28mm		
6,5 x 17	RC27	51	-	85-136	215/60, 215/65, 225/55, 225/60, 235/55, 235/60						
7 x 17	RC32	48,5	-	85-136	225/60, 235/60				Orig.-Verschr.		
	RC34	48,5	-	85-136	225/60, 235/60				Orig.-Verschr.		
	RC27	47	- od. ZP580D6F	85-136	215/60, 215/65, 225/55, 225/60, 235/55, 235/60				incl. Facelift 2018		
		50	-	85-136	215/60, 215/65, 225/55, 225/60				Typ QL mit Kit ZP580D6F, incl. Facelift 2018		
	RC30	47	-	85-136	215/60, 215/65, 225/55, 225/60, 235/55, 235/60				Orig.-Verschr., incl. Facelift 2018, auch QLE-KMD		
			ZP580D6F	114-136	225/55, 225/60, 235/55, 235/60				incl. Facelift 2018, Typ QL		
		50	-	85-136	215/60, 215/65, 225/55, 225/60				Orig.-Verschr. für Aluf., incl. FL2018, auch QLE-KMD		
			ZP580D6F	114-136	225/55, 225/60				incl. Facelift 2018, Typ QL		
	RC32	45+47	-	85-136	215/60, 215/65, 225/60				Orig.-Verschr.		
		50	-	85-136	215/60, 215/65, 225/60, 235/55, 235/60				Orig.-Verschr.		
	53	-	85-136	215/60, 215/65, 225/60, 235/55, 235/60, 245/55				Orig.-Verschr.			
	RC34	50	-	85-136	215/60, 215/65, 225/60, 235/55, 235/60				Orig.-Verschr.		
	B39	50	-	85-136	215/60, 225/55, 225/60				Orig.-Verschr. für Alufelgen, incl. Facelift 2018		
7 x 18	RC32	48,5	-	85-136	215/55, 215/60, 225/50, 225/55 , 235/50, 235/55				Orig.-Verschr.		
	RC27	46	ZP580D6F	85-136	215/55, 215/60, 225/55, 235/50						
		50	ZP580D6F	85-136	215/55, 215/60						
	RC32	45	-	85-136	215/55, 215/60, 225/50, 225/55				Orig.-Verschr.		
51		-	85-136	215/55, 215/60, 225/50, 225/55, 235/50, 235/55				Orig.-Verschr.			
7,5 x 18	RC30	49,5+50	-	85-136	215/55, 225/50, 225/55				Orig.-Verschr.		
		50,5	-	85-136	215/55, 225/50, 225/55				Orig.-Verschr.		
	RC32	51	-	85-136	215/55, 215/60, 225/50, 225/55, 235/50				Orig.-Verschr.		
		55	-	85-136	215/55, 215/60, 225/50, 225/55				Orig.-Verschr.		
	B32	49,5+	-	85-136	215/55, 225/50, 225/55				Orig.-Verschr., incl. Facelift 2018		
		50,5	ZP580D6F	114-136	225/50, 225/55				Typ QL		
	B39		-	85-136	215/55, 225/50, 225/55				Orig.-Verschr. für Alufelgen, incl. Facelift 2018		
		50	ZP580D6F	114-136	225/50, 225/55				incl. Facelift 2018, Typ QL		
AC-521	45	ZP580D6F +R	85-136	215/55, 225/50, 225/55				incl. Facelift 2018, + Red.Ringe 73,1-67,1			
			114-136	225/50, 225/55				incl. Facelift 2018, + Red.Ringe 73,1-67,1 , Typ QL			
7,5 x 19	Oxigin 18	45	ZP580	85-136	215/55, 215/60, 225/55, 235/50						
	RC32	50,5	-	85-136	225/45, 235/45, 245/45				Orig.-Verschr.		
		51	-	85-136	225/45, 235/45, 245/45				Orig.-Verschr.		
	RC34	49,5+51	-	85-136	225/45, 235/45, 245/45				Orig.-Verschr.		
		54,5	-	85-136	225/45, 235/45				Orig.-Verschr.		
	B32	45+49,5	-	85-136	225/45, 235/45, 245/45				Orig.-Verschr., für Alufelgen, incl. FL2018		
	B39	50	-	85-136	225/45, 235/45, 245/45				Orig.-Verschr., für Alufelgen		
	AC-521	45	ZP580D6F +R	85-136	225/45, 235/45, 245/45				incl. Facelift 2018, + Red.Ringe 73,1-67,1		
			114-136	225/45, 235/45, 245/45				incl. Facelift 2018, + Red.Ringe 73,1-67,1 , Typ QL			
8 x 19	Oxigin 18	50	ZP580	85-136	225/45, 235/45, 245/45						
	RC27	46	ZP580D6F	85-136	225/45, 235/45						
		47	-	85-136	225/45, 235/45				Orig.-Verschr.		
	RC29	48	ZP580	85-136	225/45, 235/45, 245/45						
	RC32	53,5+55	-	85-136	225/45, 235/45				Orig.-Verschr.		
	RC34	55	-	85-136	225/45, 235/45				Orig.-Verschr.		
	B38	45	ZP580	85-136	225/45, 235/45, 245/45						
	AC-518	40	ZP580D6F +R	85-136	225/45, 235/45				incl. Facelift 2018, auch Typ QL u. QLE-KMD, + Red.Ringe 73,1-66,1		

Sportage V NEU		ab 2022	NQ5e	5/114,3	67,1	e4*2018/858*00079*..
Sensor - Brocksens 5						

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC32	43,5	-	85-132	215/60, 215/65 , 225/60, 225/65, 235/55, 235/60		Orig.-Verschr.
	RC27	45	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
	RC30	45	ZP580D6F	85-132	215/65, 225/60, 235/60, 245/55		
	RC32	45	-	85-132	215/60, 215/65, 225/60, 225/65, 235/55, 235/60, 245/55, 245/60		Orig.-Verschr., auch Hybrid
		47	-	85-132	215/60, 225/60, 225/65, 235/55, 235/60, 245/55, 245/60		Orig.-Verschr., auch Hybrid
		50	-	85-132	225/60, 235/55, 235/60, 245/55, 245/60, 255/50, 255/55		Orig.-Verschr., auch Hybrid
	RC34	47	-	85-132	215/60, 225/60, 225/65, 235/55, 235/60, 245/55, 245/60		Orig.-Verschr., auch Hybrid
		50	-	85-132	225/60, 235/55, 235/60, 245/55, 245/60, 255/50, 255/55		Orig.-Verschr., auch Hybrid
	B39	45	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
7,5 x 17	CA 26	45	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
	RC24	45	ZP580	85-132	215/65, 225/60, 235/60		
	RC28	45	ZP580	85-132	215/65, 225/60, 235/60		
	RC29	48	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
	RC32	46	-	85-132	215/60, 215/65, 225/60, 225/65, 235/55, 235/60		Orig.-Verschr., auch Hybrid
		52,5	-	85-132	235/55, 235/60, 245/55, 245/60		Orig.-Verschr., auch Hybrid
	B24	48	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
	B36	46	ZP580	85-132	215/65, 225/60, 235/60		
	CA 20	45	ZP580	85-132	215/65, 225/60, 235/60, 245/55		
7 x 18	RC27	46+50	ZP580D6F	85-132	215/60, 225/55, 235/55, 245/50		
	RC32	45	-	85-132	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
	RC34	45	-	85-132	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
7,5 x 18	RC32	51	-	85-132	215/55, 225/55, 235/50, 235/55 , 245/50		Orig.-Verschr., auch Hybrid
	RC34	51	-	85-132	235/55		Orig.-Verschr., auch Hybrid
	RC30	45	ZP580	85-132	215/60, 225/55, 235/55		
		50,5	ZP580D6F	85-132	215/60, 225/55, 235/55, 245/50		
	RC32	45	-	85-132	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., auch Hybrid
		52	-	85-132	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
	RC34	49,5	-	85-132	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
	B32	50,5	ZP580D6F	85-132	215/60, 225/55, 235/55, 245/50		
	B39	45	ZP580	85-132	215/60, 225/55, 235/55		
		50	ZP580D6F	85-132	215/60, 225/55, 235/55, 245/50		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	85-132	215/60, 225/55, 235/55		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	85-132	215/60, 225/55, 235/55		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	85-133	215/55, 215/60, 225/55		
8 x 18	RC27	46	ZP580D6F	85-132	225/55, 235/55		
	RC34	50	-	85-132	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
	B24	48	ZP580	85-132	225/55, 235/55		
	B36 / B42	45	ZP580	85-132	225/55		
	B44	45	ZP580	85-132	225/55		
	AC-M10	45	ZP580D6F +R	85-132	225/55		+ Red.Ringe 73,1-67,1
7 x 19	RC27	45	ZP580D6F	85-132	215/50, 225/50, 235/50		
	RC34	45	-	85-132	235/50		Orig.-Verschr., auch Hybrid
7,5 x 19	RC32	51	-	85-132	235/50		Orig.-Verschr., auch Hybrid
	RC34	51	-	85-132	235/45, 235/50 , 245/45		Orig.-Verschr., auch Hybrid
	RC32	45+49,5	-	85-132	235/45, 235/50, 245/45		Orig.-Verschr., auch Hybrid
		50,5+51	-	85-132	235/45, 235/50, 245/45		Orig.-Verschr., auch Hybrid
		50+53	-	85-132	235/45, 235/50, 245/45		Orig.-Verschr., auch Hybrid
	RC34	49,5	-	85-132	235/45, 235/50, 245/45		Orig.-Verschr., auch Hybrid
	B32	45+49,5	ZP580D6F	85-132	215/50, 225/50, 235/50, 245/45		
	AC-521	45	ZP580D6F +R	85-132	215/50, 225/50, 235/50, 245/45		+ Red.Ringe 73,1-67,1
8 x 19	CA 26	50	ZP580D6F	85-132	215/50, 225/50, 235/50, 245/45		
	RC29	48	ZP580	85-132	225/50, 235/50, 245/45, 255/45		
	CA 19	45	ZP580	85-132	225/50, 245/45		
	CA 24	45	ZP580	85-133	235/45		
	Oxigin 29	50	ZP580	85-132	225/50, 235/50, 245/45, 255/45		
8,5 x 19	B42	45	ZP580	85-132	245/45		
	Oxigin 28	45	ZP580	85-132	245/45		
8 x 20	B38	45+50	ZP580	85-132	215/45, 235/45, 245/40		
	RC29	45	ZP580	85-132	235/45, 245/40		
8,5 x 20	B42	45	ZP580	85-132	235/45, 245/40		
	B37	43	ZP580	85-132	235/45		
9 x 20	B40	46	ZP580D6F	85-132	235/45		
	CA 20 / CA 23	45	ZP580	85-132	235/45		
8,5 x 21	B41	47	ZP580	85-132	245/35		
Stinger GT							
		ab 2017		CK	5/114,3	67,1	e11*2007/46*4002*..., e5*2007/46*1079*..

Sensor - Brocksens 5

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 19	B43	VA 34	ZP580D6F	269, 272	VA 225/40 + HA 255/35	
8,5 x 19		HA 46,5				
8,5 x 19	B42	35	ZP580	269, 272	VA 225/40 + HA 255/35	HA ✖
8,5 x 20	RC29	35	ZP580	269, 272	VA 225/35 + HA 255/30	nur für Allradantrieb, HA ✖
	B24	35	ZP580	269, 272	VA 225/35 + HA 255/30	nur für Allradantrieb, HA ✖

Kombinationen

8 x 19	B40	VA 35	ZP580D6F	269, 272	VA 225/40	
9 x 19		HA 46			HA 255/35	
8 x 20	B40	VA 35	ZP580D6F	269, 272	VA 225/35	
9 x 20		HA 46			HA 255/30	
8,5 x 19	B32	VA 35	ZP580	269, 272	VA 225/40	
		HA 45			HA 255/35	

Stonic ab 10.2017 YB 4/100 54,1 e1*2007/46*2094*..., e5*2007/46*1077*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	46	ZP422D6F	61-100	185/65, 195/60, 205/55, 205/60	 15/16 Zoll Serie, incl. Facelift 2020
	RC30	46	ZP422D6F	61-100	185/65	 incl. Facelift 2020, ET46 ist nur in schwarz erhältlich!
				61-100	185/65, 195/60, 205/55, 205/60	
	RC24	40	ZP422	61-100	185/65, 195/60, 205/55, 205/60	15 Zoll Serie
		42	ZP422D6F	61-100	185/65, 195/60, 205/55, 205/60	15/16 Zoll Serie, incl. Facelift 2020
	RC30	40	ZP422	61-100	185/65, 195/60, 205/55, 205/60	15 Zoll Serie
6 x 16	RC34	49	-	62-74	195/55, 205/50, 215/50	 Orig.-Verschr., 15 Zoll Serie
	RC34	45+50	-	62-100	195/55, 205/50, 215/50	Orig.-Verschr., 15 Zoll Serie
	6,5 x 16	RC24	48	ZP422	61-100	185/55, 185/60, 195/55, 205/50
RC30		38	ZP422	61-88	185/55, 185/60, 195/55	15 Zoll Serie
		45	ZP422D6F	61-100	185/55, 185/60, 195/55, 205/50, 215/50	15 Zoll Serie, incl. FL2020
		48	ZP422	61-100	185/55, 185/60, 195/55, 205/50	15 Zoll Serie, incl. FL2020
6,5 x 17	RC34	49	-	73-100	205/55	 Orig.-Verschr.
	RC14 EL	45	ZP422D6F	61-100	195/45, 205/45	15 Zoll Serie, incl. FL2020, RLP, SVR
				73-100	205/50, 205/55, 215/50	17 Zoll Serie, incl. FL2020, RLP, SVR
7 x 17	B24	45	ZP422	61-100	195/45, 205/45, 215/40, 215/45	15 Zoll Serie, incl. FL2020
				73-100	205/50, 205/55, 225/45	17 Zoll Serie, incl. FL2020
	B39	38	ZP422	61-88	195/45, 205/45	15 Zoll Serie
		44	ZP422	61-100	195/45, 205/45, 215/40, 215/45	15 Zoll Serie
				73-100	205/50, 205/55, 225/45	17 Zoll Serie
7,5 x 17	RC28	45	ZP422	61-88	195/45, 205/45, 215/40, 215/45	15 Zoll Serie
7,5 x 18	B39	38	ZP422	61-88	205/40	15 Zoll Serie
				73-88	205/45	17 Zoll Serie
		45	ZP422	61-100	205/45, 215/35	15/16 Zoll Serie, incl. Facelift 2020
				73-100	205/45, 215/45	17 Zoll Serie, incl. Facelift 2020

Lamborghini

	Baujahr	Typ	LK/LZ	Nabe
Gallardo		140	5/112	57,1

Sensor - Brocksens Universal

Dimension	Design	ET	KIT	KW	Reifendimension	Info
<u>Kombinationen</u>						
9 x 20	Oxigin 18	28	ZP560D	368-412	235/30, 245/30	+5mm Spurverbreiterung (HR 1055571)
10,5 x 20		30			295/25, 305/25	

Urus

	2018	636	5/130	71,6	e3*KS07/46*0481*.., e3*2007/46*0616*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info
10 x 23	STC-23	VA 28	-		VA 285/35	 Orig.-Verschr.
11,5x23		HA 22			HA 325/30	

Landrover

Landrover

	Baujahr	Typ	LK/LZ	Nabe		
Defender 90	ab 2021	LE	5/120	72,6	e5*2007/46*0092*..., e5*2007/46*0125*...	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	8400 Bluster	41,5	-	147-221	255/70, 265/65, 275/65	Orig.-Verschr., nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm
8,5 x 19	B41	38	-	147-294	255/65, 285/55	Orig.-Verschr.
8,5 x 20	B41	41,5	-	147-386	255/60, 275/55	Orig.-Verschr., nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm
9,5 x 22	B41	42,5	ZP533D13F	147-294	275/45, 285/45	
10 x 22	FMI09 CRATOS	42	-	147-294	275/45, 285/45, 295/40	Orig.-Verschr.
10 x 23	STC-23	40	ZP533D13F	147-386	275/40	nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm

Defender 110 / 130		NEU	im Laufe 2023		LE	5/120	72,6	e5*2007/46*0092*..., e5*2007/46*0125*..	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 18	8400 Bluster	41,5	-	147-386	255/70			Orig.-Verschr., nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm	
				147-221	255/70, 265/65, 275/65				
8,5 x 20	B41	41,5	-	147-386	255/60, 275/55			Orig.-Verschr., nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm	
9 x 20	8400 Bluster	35	-	147-386	255/60, 275/55			Orig.-Verschr., nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm	
10 x 23	STC-23	40	ZP533D13F	147-386	275/40, 285/40			nicht geprüft bei Fahrzeugen mit Bremsscheibe 363mm	

Discovery 5		ab 2018		LR	5/120	72,6	e11*2007/46*3784*..., e11*2007/46*4189*..., e5*2007/46*1054*..., e5*2007/46*1055*...	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B41	38	-	132-265	235/65, 255/55, 255/60, 265/55			Orig.-Verschr., ✖
8,5 x 20	B41	47	-	132-265	235/55, 235/60, 255/50, 255/55 , 265/50, 275/50			Orig.-Verschr., auch Hybrid
		41,5	-	132-265	235/55, 235/60, 255/50, 255/55, 265/50, 275/50			Orig.-Verschr., auch Hybrid
	B32	47	-	132-250	235/60, 255/50, 255/55, 265/50, 275/50			Orig.-Verschr.
9,5 x 21	B41	49	-	132-265	255/45, 265/45, 275/45 , 285/40, 285/45			Orig.-Verschr. auch Hybrid
10 x 21	FMI07 Atena	41	-	132-265	265/45, 275/45			Orig.-Verschr.
9,5 x 22	B41	42,5	ZP533D13F	132-265	255/45, 265/40, 275/40, 285/35, 285/40			
		49	-	132-265	255/45, 265/40, 275/40, 285/35, 285/40			Orig.-Verschr.
10 x 22	FMI09 CRATOS	42	-	132-265	265/40, 275/40			Orig.-Verschr.
	Oxigin 14	40	ZP533F+R	132-250	275/40, 285/40, 295/35			+ Red.Ringe 76,9-72,6 ✖

Discovery Sport			ab 02.15		LC		5/108		63,4		e11*2007/46*1659*...., e5*2007/46*1058*...	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353												
Dimension		Design	ET	KIT	KW	Reifendimension				Info		
7 x 17	RC30		45	ZP533D13F	110-177	225/65, 225/70, 235/65, 255/60						
	RC32		45	ZP533D13F	110-183	225/65, 225/70, 235/60, 235/65, 245/60, 255/55, 255/60						
	RC34		45	ZP533D13F	110-183	225/65, 235/65						
	B39		45	ZP533D13F	110-177	225/65, 225/70, 235/65, 255/60						
	Pro1		45	-	110-183	225/65, 225/70, 235/60, 235/65, 245/60, 255/55, 255/60					Orig.-Verschr., nicht Bremse 349x34mm	
7,5 x 17	RC34		45	ZP533D13F	110-177	235/65					nicht Bremse 349x34mm	
7,5 x 18	RC32 / RC34		45	ZP533D13F	110-183	225/55, 225/60, 235/55, 235/60, 245/50, 245/55, 255/50						
	B32 / B39		45	ZP533D13	110-177	225/60, 225/65, 235/60						
	AC-518		42	AV5	110-177	225/60, 225/65, 235/60						
8 x 18	RC27		45	-	110-213	225/60, 225/65, 235/60					Orig.-Verschr.	
	RC32		45	ZP533D13F	110-213	225/55, 225/60, 235/55, 235/60, 245/50, 245/55						
	RC34		45	ZP533D13F	110-227	225/55, 225/60, 235/55, 235/60, 245/50, 245/55						
	RC29		45	ZP533D13	110-177	225/60, 225/65, 235/60						
	B36		45	ZP533D13	110-177	225/60, 225/65						
					110-213	235/60						
	B37 / B38		45	ZP533D13	110-177	225/60, 225/65, 235/60						
	B42 / B44		42	ZP533D13	110-177	225/60, 225/65						
					110-213	235/60						
AC-MB6 / AC-M10		42	ZP533D13F +R	110-177	225/60, 225/65					+ Red.Ringe 73,1-63,4		
AC-518		45	AV5	110-177	225/60, 225/65, 235/60							
7,5 x 19	Oxigin 18		45	ZP533	110-213	225/55, 235/55						
	RC27		45	ZP533D13F	110-213	225/55, 235/55					Orig.-Verschr.	
	RC32		45	ZP533D13F	110-213	225/55, 235/50, 235/55, 245/45, 245/50, 255/45					auch für Hybrid Fahrzeuge	
	RC34		45	ZP533D13F	110-213	225/55, 235/50, 235/55, 245/45, 245/50, 255/45						
	B40		45	ZP533D13F	110-177	225/55, 235/50, 235/55, 245/50						

8 x 19	CA 19	45	OX533F-1	110-213	235/55		
	RC29	45	ZP533D13	110-177 110-213	225/55 235/50, 235/55, 245/50		
	B38	45	ZP533	110-177	225/55, 235/50, 235/55, 245/50		
	B43	42	ZP533D13F	110-177 110-213	225/55 235/50, 235/55		
	AC-518	45	AV5	110-177	225/55, 235/50, 235/55, 245/50		
	CA 24	45	ZP533D13	110-227	225/55, 235/55		
	Oxigin 29	45	ZP533D13	110-177 110-213	225/55 235/50, 235/55, 245/50		
8 x 20	B40	45	ZP533D13F	110-177	235/45, 245/45, 255/45		
	RC36	40	ZP533D13F	110-213	235/45, 245/45, 255/45		
	B38	45	ZP533D13F	110-213	235/45, 245/45, 255/45		
	B43	40	ZP533D13F	110-213	235/45, 245/45, 255/45		
	AC-521	43	AV5	110-213	235/45, 245/45, 255/45		

weitere Dimensionen/Designs siehe Konfigurator

Discovery Sport		ab Modelljahr 2020		LC	5/108	63,4	e5*2007/46*1058*01..	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7 x 17	CA 26	42	ZP533D13F +R	120-150	225/65, 235/65, 245/65			+ Red.Ringe 65,1-63,4
7,5 x 17	RC28	45	ZP533D13	120-150	225/65, 235/65			
	B24 / B36	45	ZP533D13	120-150	225/65, 235/65			
	CA 20	45	ZP533D13F	120-150	225/65, 235/65			
7,5 x 18	AC-MB6	42	AV5	120-150	225/60, 225/65, 235/60			
	AC-M10	42	AV5	120-150	225/60, 225/65, 235/60			
	AC-518	42	AV5	120-150	225/60, 225/65, 235/60			
8 x 18	RC27	45	ZP533D13F	120-213	235/60			
	B36	45	ZP533D13	120-150	225/60			
				120-213	235/60			
	B42 / B44	42	ZP533D13	120-150	225/60, 225/65			
				120-213	235/60			
	AC-MB6 / AC-M10	42	ZP533D13F +R	120-150	225/60, 225/65			+ Red.Ringe 73,1-63,4
	CA 26	45	ZP533D13F +R	120-150	225/60			+ Red.Ringe 65,1-63,4
120-213				235/60				
7,5 x 19	AC-521	42	AV5	120-150	225/55, 235/55			
8,5 x 19	Oxigin 28	38	ZP533D13	120-213	235/55			
8 x 20	RC36	40	ZP533D13F	120-213	235/50, 245/45, 255/45			
	B43	40	ZP533D13F	120-213	235/50, 245/45, 255/45			
	B45	40	ZP533D13F	120-213	235/50			
	B38	45	ZP533D13F	120-213	245/45			
	AC-521	43	AV5	120-213	245/45			
8,5 x 20	B44	40	ZP533D13F	120-213	245/45			
9 x 20	B43	38,5	ZP533D13F	120-213	245/45			
	Oxigin 28	40	ZP533D13	120-213	245/45			
8,5 x 21	B43	38,5	ZP533D13F	120-213	235/45, 245/40, 245/45, 255/40			
9 x 21	B43	38,5	ZP533D13F	120-213	245/40, 245/45			

Range Rover Sport		ab 2013		LW	5/120	72,6	e11*2007/46*0909*.., e5*2007/46*1056*..	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 19	B32	44,5	-	155-280	235/65		Orig.-Verschr., nicht Bremse 349mm	
					235/65, 255/60, 265/55, 275/55			
8,5 x 19	RC25	38	-	155-280	235/65, 255/60, 265/55, 275/55, 285/55		Orig.-Verschr., ab 265/55 ✖	
		50	-	155-280	235/65, 255/60		Orig.-Verschr.	
8,5 x 20	B41	38	-	155-386	235/65, 255/55, 255/60, 265/55, 275/50, 275/55		Orig.-Verschr., ab 265/55 ✖	
	B41	47	-	155-405	235/55, 255/50, 255/55, 265/50, 275/45, 275/50		Orig.-Verschr., auch Hybrid	
	B43	47	-	155-386	255/55, 265/50, 275/50		Orig.-Verschr., nicht Bremse 349mm	
	RC29	47	-	155-386	255/55, 265/50, 275/50		Orig.-Verschr., nicht Bremse 349mm	
	B32	47	-	155-386	255/55, 265/50, 275/50		Orig.-Verschr., nicht Bremse 349mm	
	B41	41,5	-	155-405	235/55, 255/50, 255/55, 265/50, 275/45		Orig.-Verschr., auch Hybrid	
9 x 20	B37	47	-	155-386	255/55, 265/50		Orig.-Verschr., nicht Bremse 349mm	
9 x 21	B32	48	-	155-386	255/50, 265/45, 275/45, 285/45		Orig.-Verschr., nicht Bremse 349mm	
9,5 x 21	B41	49	-	155-423	265/45, 275/45		Orig.-Verschr., auch Hybrid	
10 x 21	FMI07 Atena	41	-	155-423	265/45		Orig.-Verschr.	
9,5 x 22	B41	49	-	155-405	275/40		Orig.-Verschr.	
		42,5	ZP533D13F	155-423	265/40, 275/40, 285/35, 285/40			
10 x 22	B32	46	-	155-386	265/40, 275/40		Orig.-Verschr., nicht Bremse 349mm	
	FMI07 Atena	42,5	-	155-405	295/40		Orig.-Verschr.	
	FMI09 Cratos	42,5	-	155-423	265/40, 275/40		Orig.-Verschr.	

Range Rover Evoque (siehe Konfigurator)		ab 09.11		LV / LV-A	5/108	63,4	e11*2007/46*0223*..., e3*2001/116*0221*..	
---	--	----------	--	-----------	-------	------	---	--

Range Rover Evoque Cabrio			ab 04.2016		LV, LV-A		5/108		63,4		e11*2007/46*0223*...., e3*2007/46*0221*...		
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353													
Dimension		Design		ET	KIT	KW	Reifendimension				Info		
7 x 17	RC30		45	ZP533D13F	110-177	225/65, 235/60, 235/65							
	RC32		45	ZP533D13F	110-177	225/65, 225/70, 235/60, 235/65, 245/60, 255/55, 255/60							
	RC34		45	ZP533D13F	110-177	225/65							
	B39		45	ZP533D13F	110-177	225/65, 235/60, 235/65							
8 x 18	RC27		45	ZP533D13F	110-213	235/60							
	RC32		45	ZP533D13F	110-213	225/60, 235/55, 235/60, 245/55, 255/50, 255/55							
	RC34		45	ZP533D13F	110-213	225/60, 235/55, 235/60, 245/55, 255/50, 255/55							
	B36 / B37		45	ZP533D13	110-177	225/60							
					110-213	235/55, 235/60							
			B38	45	ZP533	110-177	225/60, 235/55, 235/60						
			AC-518	45	AV5	110-177	225/60, 235/55, 235/60						
8 x 19	RC32		45	ZP533D13F	110-213	235/55							
	RC34		45	ZP533D13F	110-213	225/55, 235/50, 235/55, 245/50, 255/45, 255/50							
	CA 19		45	OX533F-1	110-213	235/50, 235/55, 245/45, 255/45							
	B38		45	ZP533D13	110-177	235/50, 235/55, 255/45							
	B40		45	ZP533D13F	110-177	235/50, 235/55, 255/45							
	AC-518		45	AV5	110-177	235/50, 235/55, 255/45							
	CA 24		45	ZP533D13	110-213	235/50, 235/55, 245/45, 255/45							
	Oxigin 29		45	ZP533D13	110-213	235/50, 235/55, 255/45							
weitere Dimensionen/Designs siehe Konfigurator													

Evoque		ab 04.2019		LZ	5/108	63,4	e5*2007/46*0076*...	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC30	45	ZP533D13F	110-147	225/65, 235/65, 245/65			
	RC32	45	ZP533D13F	110-177	225/65, 225/70, 235/60, 235/65, 245/60, 245/65, 255/55, 255/60			
	RC34	45	ZP533D13F	110-177	225/65, 235/65		nicht Bremse 349x34mm	
	CA 26	42	ZP533D13F +R	110-147	225/65, 235/65, 245/65, 255/60		+ Red.Ringe 65,1-63,4, nicht Bremse 349mm	
	Pro1	45	-	110-177	225/65, 225/70, 235/60, 235/65, 245/60, 245/65, 255/55, 255/60		Orig.-Verschr., nicht Bremse 349x34mm	
7,5 x 17	RC28 / RC29	45	ZP533D13	110-147	225/65, 235/65		nicht Bremse 349mm	
	RC34	45	ZP533D13	110-177	225/65, 225/70, 235/60, 235/65, 245/60		nicht Bremse 349mm	
	B36	45	ZP533D13	110-147	225/65, 235/65		nicht Bremse 349mm	
7,5 x 18	RC32 / RC34	45	ZP533D13F	110-177	225/60, 225/65, 235/55, 235/60, 245/55			
	B32 / B39	45	ZP533D13	110-147	225/60, 235/60			
	AC-MB6	42	AV5	110-147	225/60, 235/60, 245/60			
	AC-M10	42	AV5	110-147	225/60, 235/60, 245/60			
	AC-521	42	AV5	110-147	225/60, 235/60, 245/60			
8 x 18	RC27	45	ZP533D13F	110-221	225/60, 225/65, 235/55, 235/60, 235/65			
	RC32	45	ZP533D13F	110-221	225/60, 225/65, 235/55, 235/60			
	RC34	45	ZP533D13F	110-227	225/60, 225/65, 235/55, 235/60			
	RC27	42+42,5	ZP533D13F	110-221	225/60, 225/65, 235/55, 235/60, 235/65, 245/55, 245/60			
	RC32	42	ZP533D13F	110-221	225/60, 225/65, 235/55, 235/60, 235/65			
	RC34	42	ZP533D13F	110-227	225/60, 225/65, 235/55, 235/60, 245/55			
	B36 / B37	45	ZP533D13	110-147	225/60			
				110-221	235/60			
	B42 / B44	42	ZP533D13	110-147	225/60			
				110-221	235/60			
	AC-MB6 / AC-M10	42	ZP533D13F +R	110-147	225/60		+ Red.Ringe 73,1-63,4	
				110-221	235/60			
	CA 26	45	ZP533D13F +R	110-147	225/60		+ Red.Ringe 65,1-63,4	
				110-221	235/60			
	8,5 x 18	Oxigin 20	45	ZP533D13F	110-221	235/55, 235/60, 235/65		
7,5 x 19	AC-521	42	AV5	110-147	225/55, 235/55, 245/50			
	CA 26	45	ZP533D13	110-147	225/55, 235/55			
8 x 19	RC27	42,5	ZP533D13F	110-221	225/55, 235/50, 235/55, 245/50, 245/55, 255/45			
		45	ZP533D13F	110-221	225/55, 235/50, 235/55, 255/45			
	RC29	42,5	ZP533D13F	110-147	225/55			
				110-221	235/55			
	RC32	45	ZP533D13F	110-227	225/55, 235/50, 235/55, 255/45		auch für Hybrid Fahrzeuge	
	RC34	42	ZP533D13F	110-227	225/55, 235/50, 235/55, 245/50, 255/45			
		45	ZP533D13F	110-227	225/55, 235/50, 235/55, 255/45			

	B40	45	ZP533D13F	110-147 110-221	225/55 235/55		
	B43	42	ZP533D13F	110-147 110-221	225/55 235/55		
	AC-518	45	AV5	110-147 110-221	225/55 235/55		
	CA 24	45	ZP533D13	110-227	225/55, 235/50, 235/55, 255/45		
	Oxigin 29	45	ZP533D13	110-147 110-221	225/55 235/55		
8,5 x 19	B32	45	ZP533D13F	110-221	235/50, 255/45		
	B41	42	ZP533D13F	110-227	235/50, 235/55, 255/45, 265/45		
	B42 / B44	42	ZP533D13F	110-221	235/55		
	Oxigin 25	45	ZP533D13	110-221	235/50, 235/55, 255/45		
	Oxigin 28	38	ZP533D13	110-221	235/55		
8 x 20	RC36	40	ZP533D13F	110-221	235/50 , 245/45, 255/45		
	B43	40	ZP533D13F	110-221	235/50 , 245/45, 255/45		
	B45	40	ZP533D13F	110-221	235/50		
	B40	45	ZP533D13F	110-221	235/50, 245/45		
	AC-521	43	AV5	110-221	235/50, 245/45		
8,5 x 20	RC34	45	ZP533D13F	110-227	235/45, 245/45, 255/40		
	B41	45	ZP597F	110-227	235/45, 245/45, 255/40		auch für Hybrid
	B44	40	ZP533D13F	110-221	235/50, 245/45, 255/45		
9 x 20	B37 / B40	38,5	ZP533D13F	110-221	235/50, 245/45, 255/45		
	B43	38,5	ZP533D13F	110-221	235/50, 245/45, 255/45		
	Oxigin 18	40	ZP533D13	110-227	235/45, 245/45, 255/40, 255/45, 265/40, 265/45		nicht Bremse 349mm
	Oxigin 28	40	ZP533D13	110-221	235/50, 245/45, 255/45		
8 x 21	Originaldim.	40		132-221	245/45		
8,5 x 21	B41	38,5	ZP533D13F	110-227	245/40, 245/45, 255/35		
	B43	38,5	ZP533D13F	110-221	235/45, 245/40, 245/45, 255/40		
9 x 21	B32	38,5	ZP533D13F	110-221	245/40, 245/45, 255/40		
	B43	38,5	ZP533D13F	110-221	245/40, 245/45, 255/40		

Range Rover IV		ab 2018		LG		5/120		72,6		e11*2007/46*0649*.., e5*2007/46*1053*..	
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7,5 x 19	B32	44,5	-	155-294	235/65				Orig.-Verschr., nicht Bremse 380mm		
					235/65, 255/55, 265/55						
8,5 x 19	RC25	38	-	183, 190	235/65, 255/55, 265/55, 275/50, 275/55				Orig.-Verschr., nur Bremse 380mm, ab 265/55 ✖		
	B41	38	-	155-294	235/65				Orig.-Verschr.		
8,5 x 20	B41	47	-	155-415	235/55, 255/50, 255/55, 265/50, 275/45, 275/50				Orig.-Verschr., auch Hybrid		
	B43	47	-	155-405	255/50, 255/55, 265/50				Orig.-Verschr., auch Hybrid, nur Bremse 380mm		
	RC29	47	-	155-405	255/55				Orig.-Verschr., nur Bremse 380mm		
	RC29	47	-	155-294	235/55				Orig.-Verschr., nur Bremse 380mm		
				155-405	255/50, 255/55, 265/50						
	B32	47	-	155-294	235/55				Orig.-Verschr., nur Bremse 380mm, Ausführung W13		
				155-405	255/50, 255/55, 265/50						
B41	41,5	-	155-415	235/55, 255/50, 255/55, 265/50, 275/45				Orig.-Verschr., auch Hybrid			
9 x 20	B37	47	-	155-405	255/50, 255/55				Orig.-Verschr., nur Bremse 380mm		
9 x 21	B32	48	-	155-405	255/50, 265/45, 275/45				Orig.-Verschr., nur Bremse 380mm		
9,5 x 21	B41	49	-	155-415	265/45, 275/45				Orig.-Verschr., auch Hybrid		
9,5 x 22		49	-	155-415	275/40				Orig.-Verschr.		
		42,5	ZP533D13F	155-415	265/40, 275/40, 285/35, 285/40						
10 x 22	B32	46	-	155-405	265/40				Orig.-Verschr., nur Bremse 380mm		
				155-415	275/40						
	FMI09 CRATOS	42	-	155-415	265/40				Orig.-Verschr.		

Range Rover V		ab 2022		LK	5/120	72,6	e9*2018/858*11120*...	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	B45	39,5	- (W14)	183-294	255/60, 275/55			Orig.-Verschr., nur Bremse 380mm
8,5 x 20	B41	43,5	- (W14)	183-390	255/55, 275/55			Orig.-Verschr.
	B43	43,5	- (W14)		275/55			Orig.-Verschr., Felge u. TÜV i.V.
8,5 x 21	B41	43,5	- (W14)	183-390	275/50			Orig.-Verschr.
				183-452	255/50, 275/45, 275/50			
	B43	43,5	- (W14)	183-294	255/50, 275/50			Orig.-Verschr., nur Bremse 380mm
9,5 x 22	B41	42,5	-	183-294	255/45, 275/45, 285/40, 285/45			Orig.-Verschr., nicht Bremse 400mm VA u. 370mm HA
10 x 23	STC-23	40	-	183-452	275/40, 285/40			Orig.-Verschr.

Range Rover V PHEV NEU					LK	5/120	72,6	e9*2018/858*11120*...	
Sensor - Brocksens Universal									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 21	B43	43,5	- (W14)	294	275/50				Orig.-Verschr., nur Bremse 380mm

Range Rover Sport			NEU	2022		L1	5/120	72,6	e9*2018/858*11229*...	
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
8,5 x 20	B41	43,5	-	183-390	255/55, 265/50, 275/55				Orig.-Verschr.	
8,5 x 21	B41	43,5	-	183-390	255/50, 275/45, 275/50				Orig.-Verschr., ECE i.V.	

Range Rover Velar			ab Mitte 2017		LY	5/108	63,4	e11*2007/46*3954*, e5*2007/46*1057*...		
Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
7,5 x 18	RC32	45	ZP533D13F	132-280	235/65, 255/60, 255/65, 265/55, 265/60, 275/60					
	RC34	45	ZP533D13F	132-280	255/60, 255/65, 265/55, 265/60, 275/60					
	B32	45	ZP533D13	132, 177	235/65, 245/60					
				132-280	255/60, 265/60					
	AC-MB6 / AC-M10	42	AV5	132-184	235/65, 245/60				nicht Bremse 370mm	
				132-280	255/60, 265/60					
8 x 18	AC-521	42	AV5	132-184	235/65, 245/60				nicht Bremse 370mm	
				132-280	255/60, 265/60					
	RC27	42+	ZP533D13F	132-177	235/65					
		42,5		132-280	245/60, 255/60, 265/55, 265/60					
		45	ZP533D13F	132-177	235/65					
				132-280	245/60, 255/60					
	RC29	45	ZP533	132,177	235/65, 245/60					
				132-280	255/60					
	RC32	42+45	ZP533F	132-280	255/60, 255/65, 265/55, 265/60, 275/60					
	RC34	42+45	ZP533D13F	132-280	255/60, 255/65, 265/55, 265/60, 275/60					
	B37	45	ZP533D13	132, 177	235/65, 245/60					
				132-280	255/60					
7,5 x 19	AC-M10	42	ZP533D13F +R	132-184	235/65, 245/60				+ Red.Ringe 73,1-63,4, nicht Bremse 370mm	
				132-280	255/60, 265/60					
	AC-518	45	AV5	132, 177	235/65, 245/60					
				132-280	255/60					
	CA 26	45	ZP533D13F +R	132-184	235/65, 245/60				+ Red.Ringe 65,1-63,4	
				132-280	255/60					
8 x 19	AC-521	42	AV5	132-184	235/55, 245/55					
				132-280	255/55, 265/50, 265/55					
	CA 26	45	ZP533D13	132-184	235/55, 245/55					
				132-280	265/50					
	RC27	42,5	ZP533D13F	132-280	255/55, 265/50, 265/55					
		45	-	132-280	255/55				Orig.-Verschr.	
	RC34	42	ZP533D13F	132-280	255/55, 255/60, 265/50, 265/55, 275/50, 275/55					
		45	ZP533D13F	132-280	255/55, 255/60, 265/50, 265/55, 275/50					
	B40	45	ZP533D13F	132, 177	235/55, 245/55					
				132-280	255/55					
8,5 x 19	B43	42	ZP533D13F	132-184	235/55, 245/55					
				132-280	255/55, 265/50					
	AC-518	45	AV5	132, 177	235/55, 245/55					
				132-280	255/55					
	CA 19	45	OX533F-1	132-280	255/55					
	CA 24	45	ZP533D13	132-280	255/55					
	Oxigin 29	45	ZP533D13	132-184	235/55, 245/55					
				132-280	255/55					
	RC32	45	ZP533D13F	132-280	255/55					
	B43	45	ZP533D13F	132-294	255/55					
8 x 20	CA 20	45	ZP533D13F	132-184	235/55, 245/55					
				132-184	235/55, 245/55					
				132-294	255/55					
	CA 26	45	ZP533D13F	132-294	255/55					
	B32	45	ZP533F	132, 177	235/55, 245/55					
				132-280	255/55					
	B41	42	ZP533D13F	132-294	255/55, 255/60, 265/50, 265/55					
	CA 23	45	ZP533D13	132-184	235/55, 245/55					
				132-294	255/55					
	Oxigin 25	45	ZP533	132-280	255/55					
8 x 20	Oxigin 28	38	ZP533D13	132-184	235/55, 245/55					
				132-294	255/55					
	RC36	40	ZP533D13F	132-184	235/55, 245/50					
				132-280	255/50, 265/50					
	B40	45	ZP533F	132, 177	235/55, 245/50					
				132-280	255/50					
8 x 20	B43	40	ZP533D13F	132-184	235/55, 245/50					
				132-280	255/50, 265/50					
	AC-521	43	AV5	132-184	235/55, 245/50					
				132-280	255/50, 265/50					

8,5 x 20	B43	45	ZP533D13F	132-294	255/50		nicht Hybrid
	RC29	45	ZP533F	132-294	255/50		
	RC34	45	ZP533D13F	132-294	255/50, 255/55, 265/45, 265/50, 275/45		
	RC36	45	ZP533D13F	132-294	255/50		
			ZP533D13F	132-184	235/55, 245/50		
				132-294	255/50, 265/45, 275/45		
	FMI07 Atena	45	F60C	132-280	255/50		
	B32	45	ZP533D13	132, 177	235/55, 245/50		
				132-280	255/50, 265/45, 275/45		
	B37	38,5	ZP533D13F	132-294	265/45		
	B43	38,5	ZP533D13F	132-294	265/45		
	B41	45	ZP597F	132-294	255/50, 255/55, 265/45, 265/50, 275/45		
	B42	45	ZP533D13F	132-184	235/55, 245/50		
				132-294	255/50, 265/45, 275/45		
	B43	45	ZP533D13F	132-184	235/55, 245/50		
				132-294	255/50, 265/45, 275/45		
	AC-518	45	AV5	132, 177	235/55, 245/50		
				132-280	255/50, 265/45, 275/45		
9 x 20	Oxigin 18 / 28	40	ZP533D13	132-294	255/50, 265/45, 275/45		
8,5 x 21	B41	45	ZP533D13F	132-294	255/45, 255/50, 265/45, 275/45		auch für Hybrid
		38,5	ZP533D13F	132-280	255/45, 255/50, 265/45, 275/45		
	B43	38,5	ZP533D13F	132-294	265/45		
9 x 21	B32	38,5	ZP533D13F	132-280	265/40, 265/45		
	B43	38,5	ZP533D13F	132-294	265/40, 265/45		

Range Rover Velar
Plug-in-Hybrid
ab 2021
LY
5/108
63,4
e5*2007/46*1057*..

Sensor - Brocksens Universal od. HUF RDE229 - Artikelnummer 93353

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 19	CA 26	45	ZP533D13F	221	255/55	
	CA 20	45	ZP533D13F	221	255/55	
	CA 23	45	ZP533D13	221	255/55	
	Oxigin 28	38	ZP533D13	221	255/55	
8,5 x 20	B43	45	ZP533D13F	221	255/50, 265/45, 275/45	
	RC29	45	ZP533D13F	221	255/50, 265/45, 275/45	
	RC36	45	ZP533D13F	221	255/50, 265/45, 275/45	
9 x 20	B37	38,5	ZP533D13F	221	265/45	
	B43	38,5	ZP533D13F	221	265/45	
	Oxigin 18 / 28	40	ZP533D13	221	255/50, 265/45, 275/45	
8,5 x 21	B43	38,5	ZP533D13F	221	265/45	
9 x 21	B43	38,5	ZP533D13F	221	265/40, 265/45	
10 x 22	CA 20	40	ZP533D13	221	265/35, 265/40	

Lexus		Baujahr	Typ	LK/LZ	Nabe		
ES 300h		XZ1L(EU,M), -/TMG		5/114,3	60,1	e6*2007/46*0250*..., e13*2007/46*1962*..	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC32	40	ZP580D6F	131	215/50, 215/55 , 225/50, 235/50, 245/45		
	RC34	40	ZP580D6F	131	215/55		
	RC24	38+45	ZP574	131	215/55, 225/50, 235/50, 245/45		
	RC29	38	ZP574	131	215/55, 225/50, 235/50, 245/45		
	AC-518	40	Artikel Nr. 98502	131	215/55, 225/50, 235/50, 245/45		Kit mit Artikelnummer 98502
7,5 x 18	RC32	45	ZP580D6F	131	215/45, 215/50, 225/45, 235/45, 245/45		
	B32	35	ZP574	131	215/45, 215/50, 225/45, 235/45		
	B39	35+45	ZP574	131	215/45, 215/50, 225/45, 235/45		
	AC-MB6	35	Artikel Nr. 98502	131	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	AC-521	45	Artikel Nr. 98502	131	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
8 x 18	RC32	45	ZP580D6F	131	215/45, 225/45, 235/45 , 245/40, 245/45		
	B36	35+45	ZP574	131	215/45, 225/45, 235/45, 245/40		ET45 original ET
	B37 / B38	35+45	ZP574	131	215/45, 225/45, 235/45, 245/40		ET45 original ET
	B42	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	B44	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	AC-518	40	Artikel Nr. 98502	131	215/45, 225/45, 235/45, 245/40		Kit mit Artikelnummer 98502
	AC-M10	45	Artikel Nr. 98502	131	215/45, 225/45, 235/45, 245/40		Kit mit Artikelnummer 98502
	CA 24	45	ZP574	131	225/45, 235/45, 245/40, 245/45		
8 x 19	RC29	38	ZP574	131	225/40, 235/40, 245/35		
	B24	38	ZP574	131	225/40, 235/40, 245/35		
	AC-518	40	Artikel Nr. 98502	131	225/40, 235/40, 245/35		Kit mit Artikelnummer 98502
	CA 17	40	ZP574	131	225/40, 235/40, 245/35		
	CA 19	45	ZP574	131	225/40, 235/40, 245/35		
	CA 24	45	ZP574	131	225/40, 235/40, 245/35		
	Oxigin 29	40	ZP574	131	225/40, 235/40, 245/35		
	8 x 20	B38	35	ZP574	131	235/35	
45			ZP574	131	235/35, 245/30		
B43		35	-	131	235/35		Orig.-Verschr.
weitere Dimensionen/Designs siehe Konfigurator							

GS 250/200t/300 (siehe Konfigurator)	ab Modell 2013	S19(a)	5/114,3	60,1	e6*2001/116*0103*06*..
--------------------------------------	----------------	--------	---------	------	------------------------

GS 300H / 450H (siehe Konfigurator)	ab Modell 2013	HS19(a)	5/114,3	60,1	e6*2001/116*0106*08*..
-------------------------------------	----------------	---------	---------	------	------------------------

IS 250 / 300H (siehe Konfigurator)		XE2(a)	5/114,3	60,1	e11*2001/116*0206*10*..., e6*2007/46*0346*..., e13*2007/46*1936
------------------------------------	--	--------	---------	------	---

LBX NEU i.V.	ab 2024	AYH1(M)	5/114,3	60,1	e6*2018/858*00295*..
--------------	---------	---------	---------	------	----------------------

Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
Noch kein Fahrzeuganbau vorhanden - Info Thorsten (Stand:20.01.2025)							

NX200T (siehe Konfigurator)	2015	AZ1	5/114,3	60,1	e6*2007/46*0111*...
-----------------------------	------	-----	---------	------	---------------------

NX300H		2014-2015	AZ1 / AZ1-TMG	5/114,3	60,1	e6*2007/46*0111*..., e13*2007/46*1536*...	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	35	ZP580D6F	114, 175	225/65, 235/60, 255/55		incl. Hybrid
	RC34	35	ZP580D6F	114-175	225/60, 225/65, 235/60, 245/60		
	RC27	38	ZP574	114, 175	225/65, 235/60, 255/55		incl. Hybrid
	RC30	38	ZP574	114	225/65, 235/60, 255/55		
	RC32	39	ZP580D6F	114-175	225/60, 225/65		
7,5 x 17	B39	38	ZP574	114	225/65, 235/60, 255/55		
	RC24	38	ZP574	114, 175	225/65, 235/60		incl. Hybrid
	RC29	38	ZP574	114, 175	225/65, 235/60		incl. Hybrid
	B36	38	ZP574	114, 175	225/65, 235/60		incl. Hybrid
7,5 x 18	RC30	35	ZP574	114	225/55, 225/60, 235/55, 245/50, 245/55, 255/50		
	B32 / B39	35	ZP574	114, 175	225/55, 225/60, 235/55, 245/50, 255/50		incl. Hybrid
	Oxigin 18	35	ZP574	114-175	225/60, 235/55		
8 x 18	RC25 / RC29	35	ZP574	114, 175	225/55, 225/60, 235/55, 245/50		incl. Hybrid
	B36	38	ZP574	114	225/55, 225/60, 235/55, 245/50		
	B37	35	ZP574	114, 175	225/55, 225/60, 235/55, 245/50		incl. Hybrid

8,5 x 18	B38	35	ZP574	114, 175	225/55, 225/60, 235/55, 245/50		
	AC-518	40	ZP580D6F+R	114, 175	225/55, 225/60, 235/55		+ Red.Ringe 73,1-60,1
8,5 x 18	B32	35	ZP574	114, 175	225/60, 235/55, 245/50		incl. Hybrid
	Oxigin 18	35	ZP574	114	225/60, 235/55, 245/50, 245/55		
7,5 x 19	B32	40	ZP574	114, 175	225/55, 235/50, 245/45, 245/50		incl. Hybrid
	B39	40	ZP574	114	225/55, 235/50, 245/45, 245/50		
8 x 19	RC29	30	ZP580D6F	114	225/55, 235/50, 245/45, 255/45		
		38	ZP574	114, 175	225/55, 235/50, 245/45, 255/45		incl. Hybrid
	B24	38	ZP574	114, 175	225/55, 235/50, 245/45, 255/45		incl. Hybrid
	B38	38	ZP574	114	225/55, 235/50, 245/45, 255/45		
	AC-518	40	ZP580D6F+R	114, 175	225/55, 235/50, 245/45, 255/45		+ Red.Ringe 73,1-60,1
8 x 20	B38	35	ZP574	114, 175	235/45, 245/40, 245/45		incl. Hybrid
	B40	30	ZP580D6F	114, 175	235/45, 245/40, 245/45		incl. Hybrid
		35	ZP574	114, 175	235/45, 245/40, 245/45		incl. Hybrid
	B43	35	-	114, 175	235/45, 245/40, 245/45		Orig.-Verschr., incl. Hybrid

weitere Dimensionen/Designs siehe Konfigurator

NX350h NEU		ab Jänner 2022		AZ2 (M)	5/114,3	60,1	e6*2018/858*00081*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	B32	35	ZP534	140	235/60, 245/55, 255/55		
	AC-MB6	35	ZP568F+R	140	235/60, 245/55, 255/55		+ Red.Ringe 73,1-60,1
8 x 18	B36	35	ZP534	140	235/60, 245/55		
	B42 / B44	30	ZP534	140	235/60		
8,5 x 19	B32 / B37	35	ZP534	140	235/55		
	B42	35	ZP534	140	235/55		
7,5 x 20	RC36	35	ZP568F	140	235/50, 245/45		
	B43	35	ZP568F	140	235/50, 245/45		
8 x 20	B38	35	ZP534	140	235/50, 245/45, 255/45		
	B40	35	ZP534	140	235/50, 245/45, 255/45		
8,5 x 20	B24 / B42	35	ZP534	140	235/50, 245/45, 255/45		

NX450h+ NEU		ab Jänner 2022		AZ2 (M)	5/114,3	60,1	e6*2018/858*00081*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	B32	35	ZP534	136	235/60, 245/55, 255/55		
	AC-MB6	35	ZP568F+R	136	235/60, 245/55, 255/55		+ Red.Ringe 73,1-60,1
8 x 18	B36	35	ZP534	136	235/60, 245/55		
	B42 / B44	30	ZP534	136	235/60		
8,5 x 18	B32	35	ZP534	136	235/60		
8,5 x 19	B32 / B37	35	ZP534	136	235/55		
	B42	35	ZP534	136	235/55		
7,5 x 20	RC36	35	ZP568F	136	235/50, 245/45		
	B43	35	ZP568F	136	235/50, 245/45		
8 x 20	B38	35	ZP534	136	235/50, 245/45, 255/45		
	B40	35	ZP534	136	235/50, 245/45, 255/45		
8,5 x 20	B24 / B42	35	ZP534	136	235/50, 245/45, 255/45		

RC 200t & 300h (siehe Konfigurator)	ab 01.16	XC1 (EU, M)	5/114,3	60,1	e11*2007/46*2883*..., e6*2007/46*0336*..
---	-----------------	--------------------	----------------	-------------	--

RCF (siehe Konfigurator)	ab 2015	UXC1 (EU, M)	5/114,3	60,1	e11*2007/46*1532*..., e6*2007/46*0335*..
--	----------------	---------------------	----------------	-------------	--

RX350 / RX450H		ab 2015	AL1 (a)/ HAL1(a)	5/114,3	60,1	e6*2001/116*0117*...., e6*2001/116*0118*..	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC30	35	ZP574	183, 204	235/60, 255/55		
	B32	35	ZP574	183, 204	235/60, 255/55		
8 x 18	RC25 / RC29	35	ZP574	183, 204	235/60		
	RC32	40	ZP580D6F	183-204	235/55, 235/60, 245/55		
	B37	35	ZP574	183, 204	235/60		
8,5 x 18	B32	35	ZP574	183, 204	235/60		
8,5 x 19	B32 / B37	35	ZP574	183, 204	235/50, 235/55		
	B41	27	ZP580D6F	183-204	235/50, 235/55		
8 x 20	B38	35	ZP574	183, 204	235/45		
	B40	30	ZP580D6F	183, 204	235/45, 245/45, 255/45		
		35	ZP574	183, 204	235/45, 245/45, 255/45		
	B43	35	-	183, 204	235/45, 245/45, 255/45		Orig.-Verschr.
8,5 x 20	RC29	35	ZP574	183, 204	235/45, 245/45, 255/45, 265/45		
	B24	35	ZP574	183, 204	235/45, 245/45, 255/45, 265/45		
	B42	35	ZP574	183, 204	235/45, 245/45, 255/45		

RX (IV)		ab 2019	AL2 (EU,M) -TMG		5/114,3	60,1	e6*2007/46*0163*..., e13*2007/46*1613*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B41	27	ZP580D6F	175-221	235/55			
	Oxigin 28	30	ZP574	175-221	235/55, 245/55			
8 x 20	B40	30	ZP580D6F	175-221	235/55			
RX350H, RX450H+ NEU		3. Quartal 2023		AL3 (M)		5/114,3	60,1	e6*2018/858*00209*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	40	-	136-140	235/60, 245/55, 255/55			Orig.-Verschr.
8,5 x 20	B41	38	-	136-140	235/50, 235/55, 245/50, 265/45			Orig.-Verschr.
RX500h NEU				AL3 (M)		5/114,3	60,1	e6*2018/858*00209*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 20	B41	38	-	200	235/55			Orig.-Verschr., nur M+S
UX		ab 2019	ZA1 (EU, M), -TMG		5/114,3	60,1	e6*2007/46*0263* ..., e13*2007/46*2005*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	40	ZP580D6F	112, 127	215/60, 225/55, 235/55			
	RC34	40	ZP580D6F	112-127	215/60			
	RC27	35	-	112, 127	215/60, 225/55			Orig.-Verschr.
		45	ZP580D6F	112, 127	215/60, 225/55, 235/55			
7 x 17	RC34	45	ZP580D6F	112-127	215/55, 215/60, 225/55, 235/50, 235/55			
	RC27	35	ZP580D6F	112, 127	215/60			
		45	ZP574	112, 127	215/60, 225/55, 235/55			
	RC30	38	ZP574	112, 127	215/60, 225/55			
		45	ZP574	112, 127	215/60, 225/55, 235/55			
	RC32	39	ZP580D6F	112-127	215/60, 225/55			
	RC34	35	ZP580D6F	112-127	215/55, 215/60			
	B39	38	ZP574	112, 127	215/60, 225/55			
45		ZP574	112, 127	215/60, 225/55, 235/55				
7,5 x 17	RC24	45	ZP574	112, 127	215/60, 225/55, 235/55			
	RC28	45	ZP574	112, 127	215/60, 225/55, 235/55			
	RC29	38	ZP574	112, 127	215/60			
	RC32	40	ZP580D6F	112-127	215/55, 215/60, 225/55			
		45	ZP580D6F	112-127	215/60, 225/55, 235/55			auch für Hybrid
	RC34	40	ZP580D6F	112-127	215/55, 215/60, 225/55			auch für Hybrid
	B24	38	ZP574	112, 127	215/60			
	AC-518	40	ZP580D6F+ R	112, 127	215/60, 225/55			+ Red.Ringe 73,1-60,1
7 x 18	RC34	35	-	112-127	215/50, 215/55			Orig.-Verschr.
7,5 x 18	RC32	45	ZP580D6F	112-127	215/50, 215/55, 225/50, 235/50, 245/45			
	B32 / B39	45	ZP574	112, 127	215/50, 215/55, 225/50, 235/45, 235/50, 245/45			
	AC-MB6	45	Artikel Nr. 98502	112, 127	215/50, 215/55, 225/50, 235/45, 235/50, 245/45			Kit mit Artikelnummer 98502
	AC-521	45	ZP580D6F+ R	112, 127	215/50, 215/55, 225/50, 235/45, 235/50, 245/45			+ Red.Ringe 73,1-60,1
	CA 20	40	ZP574	112-127	215/50, 215/55, 225/50, 235/45, 245/45			
8 x 18	RC32	40	ZP580D6F	112-127	215/55			
		45	ZP580D6F	112, 127	215/55, 225/50, 235/50, 245/45, 255/45			
	B36 / B38	45	ZP574	112, 127	225/50, 235/45, 245/45			
	B37 / B42	45	ZP574	112, 127	225/50, 235/45, 245/45			
	B44	45	ZP574	112, 127	225/50, 235/45, 245/45			
	AC-518	40	ZP580D6F+ R	112, 127	225/50, 235/45			+ Red.Ringe 73,1-60,1
	AC-M10	45	ZP580D6F+ R	112, 127	225/50, 235/45, 245/45			+ Red.Ringe 73,1-60,1
7,5 x 19	CA 23	45	ZP574	112, 127	225/50, 235/45, 245/45			
	RC34	40	-	112-127	225/40, 225/45, 235/45			Orig.-Verschr.
	B32	40	ZP574	112, 127	225/45, 235/45			
8 x 19	AC-521	45	ZP580D6F+ R	112, 127	225/45, 235/45			+ Red.Ringe 73,1-60,1
	RC29	38	ZP574	112, 127	225/45			
		38	ZP574	112, 127	225/45, 235/40, 235/45			ab 235/40 ✖
	AC-518	40	ZP580D6F+ R	112, 127	225/45, 235/40, 235/45			+ Red.Ringe 73,1-60,1
	CA 19	45	ZP574	112, 127	225/45, 235/40, 235/45, 245/40			
8,5 x 19	Oxigin 29	40	ZP574	112, 127	225/45, 235/40, 235/45			
	B32 / B37	45	ZP574	112, 127	225/45, 235/40, 235/45			
	B36	44	ZP574	112, 127	225/45, 235/40, 235/45			
	B42	45	ZP574	112, 127	225/45, 235/40, 235/45			

	CA 20	45	ZP574	112, 127	225/45, 235/40, 235/45		
	Oxigin 28	45	ZP574	112, 127	225/45, 235/40, 235/45		
8 x 20	B38	45	ZP574	112, 127	225/40, 235/35, 235/40, 245/35		
8,5 x 20	RC29	45	ZP574	112, 127	225/40, 235/35, 235/40		
	B44	40	ZP574	112, 127	225/40		
	AC-518	40	ZP580D6F+R	112, 127	225/40		+ Red.Ringe 73,1-60,1
9 x 20	B37	43	ZP574	112, 127	225/40		
	CA 23	45	ZP574	112, 127	225/40, 235/35, 235/40		
8,5 x 21	B41	47	ZP574	112-127	245/30		

UX250H		ab 2019		ZA1 (EU, M), -/TMG		5/114,3	60,1	e6*2007/46*0263* ..., e13*2007/46*2005*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	Oxigin 25	45	ZP574	112	215/60, 225/55, 235/50, 235/55			
8 x 18	CA 24	45	ZP574	112	225/50, 235/45, 245/45			
8 x 19	CA 17	40	ZP574	112	225/45, 235/40, 235/45			
	CA 24	45	ZP574	112	225/45, 235/40, 235/45, 245/40			
8,5 x 19	Oxigin 25	43	ZP574	112	225/45, 235/40, 235/45			

UX Elektro NEU i.V.		ab Jänner 2022					
Dimension	Design	ET	KIT	KW	Reifendimension		Info

Lucid

Lucid

	Baujahr	Typ	LK/LZ	Nabe		
Air Elektro NEU	4. Quartal 2023	A1	5/120	64,1	e5*2018/858*00070*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 19	B40	40	ZP533D13F	165-271	245/45	
8,5 x 19	B32	35	-	165-271	245/45	Orig.-Verschr.
8 x 20	RC36	40	ZP533D13F	165-271	245/40	
	B40	31	ZP533D13F	165-271	245/40	

Lynk&Co.

Lynk&Co.	Baujahr	Typ	LK/LZ	Nabe	
Lynk & Co. 01 (Hybrid) NEU		GX6	5/108	63,4	e9*2018/858*11032*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	52	-	105	235/55			Orig.-Verschr., nur Bremse 345mm
		45	-	105	235/55			Orig.-Verschr., nur Bremse 345mm, es sind nur spezielle Gewebeschneeketten zulässig!
	B36 / B38	45	ZP531	105	235/55			nur Bremse 345mm, es sind nur spezielle Gewebeschneeketten zulässig!
	CA 26	45	ZP569F+R	105	235/55			+ Red.Ringe 65,1-63,4 , nur Bremse 345mm, es sind nur spezielle Gewebeschneeketten zulässig!
8 x 19	RC29	45	ZP531	105	235/50, 245/45, 255/45			nur Bremse 345mm
	B38	45	ZP531	105	235/50, 245/45, 255/45			nur Bremse 345mm
	B40	45	ZP569F	105	235/50, 245/45, 255/45			nur Bremse 345mm
	B43	47,5	-	105	235/50			Orig.-Verschr., i.V.
	Oxigin 29	45	ZP531	105	235/50, 245/45, 255/45			nur Bremse 345mm
8,5 x 19	B32	45	ZP531	105	245/45			nur Bremse 345mm
			ZP569F	105	245/45			nur Bremse 345mm
	B43	45	-	105	245/45			Orig.-Verschr., nur Bremse 345mm
	CA 20	45	ZP569F	105	245/45			nur Bremse 345mm
	CA 23	45	ZP531	105	245/45			nur Bremse 345mm
8 x 20	B43	52	-	105	235/45, 245/40			Orig.-Verschr., ECE i.V.
	B38	45	-	105	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
	B43	48,5+50	-	105	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
		50,5	-	105	235/45, 245/40			Orig.-Verschr.
8,5 x 20	B42 / B43	45	-	105	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
	B44	40	-	105	235/45			Orig.-Verschr., nur Bremse 345mm
	CA 20	45	ZP569F	105	235/45			nur Bremse 345mm
9 x 20	CA 23	45	ZP569F+R	105	235/45		+ Red.Ringe 65,1-63,4 , nur Bremse 345mm	
8,5 x 21	B43	49,5	-	105	245/35, 255/35			Orig.-Verschr., nur Bremse 345mm

Lynk & Co. 01 PHEV (Plug-in-Hybrid) NEU				GX6	5/108	63,4	e9*2018/858*11032*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	B43	52	-	132	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
	B38	45	-	132	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
	B43	48,5+50	-	132	235/45, 245/40			Orig.-Verschr., nur Bremse 345mm
		50,5	-	132	235/45, 245/40			Orig.-Verschr.

8,5 x 20	B42 / B43	45	-	132	235/45, 245/40		Orig.-Verschr., nur Bremse 345mm
	B44	40	-	132	235/45		Orig.-Verschr., nur Bremse 345mm
9 x 20	CA 20	45	ZP569F	132	235/45		nur Bremse 345mm
	CA 23	45	ZP569F+R	132	235/45		+ Red.Ringe 65,1-63,4, nur Bremse 345mm
8,5 x 21	B43	49,5	-	132	245/35, 255/35		Orig.-Verschr., nur Bremse 345mm

Lynk & Co. 02 (elektro) NEU							
E335				5/108	63,4	e9*2018/858*11646*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 21	B43	45	-	75 (200)	245/35, 245/40	Orig.-Verschr.	

MAN

MAN		Baujahr	Typ	LK/LZ	Nabe		
MAN TGE		ab 2017	SYN1E / SYNWE	5/120	65,1	e1*2007/46*1626*.., e1*2018/858*00136*..	
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC25T	60	-	103, 130	235/65C		Orig.-Verschr.
				90-130	235/65C		Orig.-Verschr., nur Heckantrieb
				75-130	205/75C, 235/65C		Orig.-Verschr., nur Frontantrieb, auch SYNVE
				103, 130	205/75C, 235/65C		Orig.-Verschr., Allrad
	Pro1	51	-	75-130	205/75C, 225/65C, 225/65CP, 235/65C, 235/65CP		Orig.-Verschr., auch Typ SYN2E u. SYM1E
7 x 17	B45	55	-	75-130	235/60C		Orig.-Verschr., Frontantrieb, auch Typ SYNWE
				90-130	235/60C		Orig.-Verschr., Heckantrieb
				103, 130	235/60C		Orig.-Verschr., Allradantrieb
	AC-V51	55	-	75,103,130	235/60C		Orig.-Verschr., Frontantrieb
				103, 130	235/60C		Orig.-Verschr., Allrad- u. Heckantrieb
7,5 x 17	RC25	55	-	75,103,130	235/60C		Orig.-Verschr., auch Allrad, geschl. Aufbau
8 x 20	B45	52	-	75-130	235/45C		Orig.-Verschr., Front- u. Heckantrieb
				103, 130	235/45C		Orig.-Verschr., Allradantrieb

MAN TGE		SYN2E / SYNVE		5/120	65,1	e1*2007/46*1627*.., e1*2018/858*00135*..	
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC25T	60	-	90-130	235/65C		Orig.-Verschr., nur Heckantrieb
				75-130	205/75C, 235/65C		Orig.-Verschr., nur Frontantrieb, auch SYNVE
				103, 130	235/65C		Orig.-Verschr., Allrad
7 x 17	B45	55	-	75-130	235/60C		Orig.-Verschr., Frontantrieb, auch Typ SYNVE
				90-130	235/60C		Orig.-Verschr., Heckantrieb
				103, 130	235/60C		Orig.-Verschr., Allradantrieb, auch Typ SYNVE
8 x 20	B45	52	-	75-130	235/45C		Orig.-Verschr., Front- u. Heckantrieb
				103, 130	235/45C		Orig.-Verschr., Allradantrieb

Maserati

Maserati		Baujahr	Typ	LK/LZ	Nabe		
Ghibli		ab 2013	M156	5/114,3	67,1	e3*2007/46*0224*..	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 18	B32	35	ZP583	184-243	235/50		✖
				302	235/50, 275/45		

Kombinationen

8,5 x 19	B32	35	ZP583	184-302	245/45		
9,5 x 19		30			275/40		

Ghibli		ab 2013	M156 / Modell 157		5/114,3	67,1	e3*2007/46*0224*..	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B32	35	ZP583	184-302	VA 245/45			
9,5 x 19		30			HA 275/40			

Grecale NEU		2. Quartal 2022	M182	5/110	65,1	e3*2018/858*00056*..	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 20	1972 - 8300	29	-		255/45		Orig.-Verschr.
9 x 21	FMI05 Makhai	29	-		255/40		Orig.-Verschr.

Levante		ab 2016	M156 / Modell 161		5/114,3	67,1	e3*2007/46*0224*..	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 18	B32	35	ZP583	184-257	255/55,255/60, 265/55, 275/50, 285/50			✖
8,5 x 19	Oxigin 14	42	ZP548	184-257	255/50, 255/55, 265/50, 275/45			nicht Bremse ab 345mm
9 x 20	Oxigin 19	38	ZP548	184-257	265/45, 275/40, 275/45			nicht Bremse 360 u. 380mm, ab 275/40 ✖

Kombinationen

8,5 x 19	B32	35	ZP583	184-257	VA 255/50, 255/55, 265/50, 275/45, 275/50		
9,5 x 19		30			HA 265/50, 275/45, 275/50, 285/45, 295/45		

MC20 RHT NEU i.V.		3. Quartal 2022					
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

Mazda

Mazda	Baujahr	Typ	LK/LZ	Nabe			
Mazda 2 III	ab 2014	DJ1	4/100	54,1	e1*2007/46*1135*...		
Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC24	40	ZP422	55-85	185/65, 195/60, 205/55		bei 205/55 ✖
	RC30	40	ZP422	55-85	185/65, 195/60, 205/55		bei 205/55 ✖
6,5 x 16	RC24 / RC30	38	ZP422	55-85	185/55, 185/60, 195/55		
7 x 17	B24 / B39	38	ZP422	55-85	195/45, 205/45		

	Mazda 2 Hybrid	NEU	ab 2022	ZV	5/100	54,1	e6*2018/858*00149*..
Sensor - Brocksens 6 - ab BJ 04/2022 - Brocksens Universal oder HUF ECR220 - Artikelnummer 97818							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC27	45	-	68	185/65, 195/60, 205/55		Orig.-Verschr.
6 x 16	RC30	50	ZP580D8F	68	185/55, 195/55		
	RC34	50	ZP580D6F	68	195/55		
6,5 x 16	CA 20	38	ZP510	68	185/55		
6,5 x 17	RC34	50	ZP580D6F	68	205/45		
7 x 17	RC30	43	ZP510	68	195/45, 205/45		
	CA 26	46	ZP510	68	195/45, 205/45		

	Mazda 3 III	Facelift 2017	BL / Typ BN	5/114,3	67,1	e11*2001/116*0262*10-... (FIN:-.MZBN...)
kein Sensor - indirektes RDKS						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	50	-	74-121	205/60, 215/55, 225/55	 Orig.-Verschr.
	RC30	50	-	74-121	205/60, 215/55, 225/55	 Orig.-Verschr.
	RC32	50	-	74-121	205/60, 215/55, 225/55, 235/50	 Orig.-Verschr.
	RC34	50	-	74-121	205/60, 215/55, 225/55, 235/50	 Orig.-Verschr.
	RC24	42	-	74-121	205/60, 215/55, 225/55	Orig.-Verschr., ab 215/55 ✖
	RC30	47+48	-	74-121	205/60, 215/55, 225/55	Orig.-Verschr.
	RC32	44+45	-	74-121	205/60, 215/55, 225/55	Orig.-Verschr.
	RC34	45	-	74-121	205/60, 215/55, 225/55	Orig.-Verschr.
7 x 17	RC27	45	ZP580	74-121	205/50, 205/55, 215/50, 225/45, 225/50	bei 215/50 u. 225/50 ✖
		47+50	-	74-121	205/50, 205/55, 215/50, 225/45, 225/50	Orig.-Verschr., bei 225/50 ✖
	RC30	45	ZP580	74-121	205/50, 205/55, 215/50, 225/45, 225/50	bei 215/50 u. ab 225/50 ✖
		-	-	74-121	205/50, 205/55, 225/45	Orig.-Verschr.
		50	-	74-121	205/50, 205/55, 215/50, 225/45, 225/50	Orig.-Verschr., bei 225/50 ✖
	B39	45	ZP580	74-121	205/50, 205/55, 225/45	
		50	-	74-121	205/50, 205/55, 215/50, 225/45	Orig.-Verschr.
		-	-	74-121	205/50, 205/55, 215/50, 225/45, 235/45	Orig.-Verschr.
7,5 x 17	RC24	50	-	74-121	205/50, 205/55, 215/50, 225/45, 235/45	
		45	ZP580	74-121	205/50, 205/55	
	RC28	50	ZP580	74-121	205/50, 205/55, 215/50, 225/45, 235/45	
		45	ZP580	74-121	205/50, 205/55	
	RC29	48	ZP580	74-121	205/50, 205/55, 225/45, 235/45	
	B36	46	ZP580	74-121	205/50, 205/55, 225/45, 235/45	
7 x 18	RC27	50	-	74-121	215/45	Orig.-Verschr.
	RC32	45+48,5	-	74-121	205/45, 215/45	Orig.-Verschr.
7,5 x 18	RC30	49,5	-	74-121	205/45, 215/45, 225/40, 225/45	Orig.-Verschr.
		50+50,5	-	74-121	205/45, 215/45, 225/40, 225/45	Orig.-Verschr.
	RC32	45	-	74-121	205/45, 215/45, 225/40	Orig.-Verschr.
		49,5	-	74-121	205/45, 215/45, 225/40, 225/45	Orig.-Verschr.
	B32	50,5	-	74-121	205/45, 215/45, 225/40, 225/45	Orig.-Verschr.
		50	-	74-121	205/45, 215/45, 225/40, 225/45	Orig.-Verschr.
8 x 18	RC34	50	-	74-121	205/45, 215/45, 225/40, 235/40	Orig.-Verschr.
	B24	48	ZP580	74-121	215/45, 225/40, 225/45	
	B36	45	ZP580	74-121	215/45, 225/40, 225/45, 235/40, 245/40	ab 225/40 ✖
	B38	49	ZP580	74-121	215/45, 225/40, 225/45	
7,5 x 19	B32	49,5	-	74-121	225/35, 225/40	Orig.-Verschr.
	B39	50	-	74-121	225/35, 235/35	Orig.-Verschr.
8 x 19	RC29	48	ZP580	74-121	225/35, 225/40, 235/35	bei 235/35 ✖
	B24	50	ZP580	74-121	225/35, 225/40	

	Mazda 3 IV	ab 03.2019	BP, BPE	5/114,3	67,1	e13*2007/46*1972*.., e13*2007/46*2249*..
Sensor - Brocksens 7 od. HUF RDE225 - Artikelnummer - 92085						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC30	45	-	85-137	205/60	 Orig.-Verschr., auch Typ BPE
	RC32	45	-	85-132	205/60, 215/55, 225/55	 Orig.-Verschr.
	RC34	45	-	85-137	205/60, 215/55, 225/55	 Orig.-Verschr., auch Typ BPE
	RC24	42	ZP580D6F	85-132	205/60, 215/55, 225/55	auch Typ BPE
		44	ZP580	85-132	205/60, 215/55, 225/55	auch Typ BPE
	RC27	38	ZP580	85-137	205/60	auch Typ BPE

6,5 x 17	RC27	45	ZP580	85-132	205/60, 215/55, 225/55		auch Typ BPE
	RC30	42	ZP580D6F	85-132	205/60, 215/55, 225/55		auch Typ BPE
	RC32	44	-	85-132	205/60, 215/55, 225/55		Orig.-Verschr.
	CA 20	45	ZP580	85-137	205/60, 215/55, 225/55		auch Typ BPE
7 x 17	RC27	40	ZP580D6F	85-132	205/50, 205/55, 215/50		
		38	ZP580	85-137	205/50, 205/55, 225/45		
		40	ZP580D6F	85-132	205/50, 205/55, 225/45		
	RC30	45	ZP580	85-137	205/50, 205/55, 215/50, 225/45		
		38	ZP580	85-132	205/50, 205/55, 225/45		
		45	ZP580D6F	85-132	205/50, 205/55, 215/50, 225/45		
			ZP580	85-132	205/50, 205/55, 215/50, 225/45		
	RC32	43,5	-	85-137	205/50, 205/55, 215/50, 225/45		Orig.-Verschr.
		45	-	85-137	205/50, 205/55, 215/50, 225/45, 225/50		Orig.-Verschr.
		47	-	85-132	205/50, 205/55, 215/50, 225/45, 225/50		Orig.-Verschr.
	B39	45	ZP580	85-137	205/50, 205/55, 215/50, 225/45		
	CA 26	45	ZP580	85-137	205/50, 205/55, 215/50, 225/45		
7,5 x 17	RC24 / RC28	45	ZP580	85-137	205/50, 205/55, 215/50, 225/45, 235/45		auch Typ BPE
	RC32	46	-	85-132	205/50, 205/55, 215/50, 225/45, 235/45		Orig.-Verschr.
7 x 18	RC32	45	-	85-137	205/45, 215/45		Orig.-Verschr., auch BPE
	RC34	45	-	85-137	205/45, 215/45		Orig.-Verschr., auch BPE
	RC27	38	ZP580D6F	85-137	205/45, 215/45, 225/45		auch Typ BPE
7,5 x 18	RC30	45	ZP580	85-137	205/45, 215/45, 225/40, 225/45		auch Typ BPE
	RC32	45	-	85-137	205/45, 215/45		Orig.-Verschr.
	B32	45	ZP580	85-132	205/45, 215/45, 225/40, 225/45		auch Typ BPE
	B39	45	ZP580	85-137	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	85-137	205/45, 215/45, 225/40, 225/45		Kit mit Artikelnummer 98499
	AC-518	45	ZP580D6F +R	85-137	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	85-137	205/45		
8 x 18	RC27	46	ZP580D6F	85-121	215/45		
	RC29	45	ZP580	85-132	215/45, 225/40, 225/45		
	B38	45	ZP580	85-132	215/45, 225/40, 225/45		
	B42	40	ZP580	85-137	215/45		
		45	ZP580	85-137	215/45, 225/40, 225/45		
	B44	40	ZP580	85-137	215/45		
		45	ZP580	85-137	215/45, 225/40, 225/45		
7,5 x 19	AC-M10	45	ZP580D6F +R	85-137	215/45, 225/40, 225/45		+ Red.Ringe 73,1-67,1
	RC32	45	-	85-132	225/35		Orig.-Verschr.
	B32	45	ZP580D6F	85-137	225/35		
8 x 19	AC-521	45	ZP580D6F +R	85-137	225/35		+ Red.Ringe 73,1-67,1
	B38	45	ZP580	85-137	225/35		
	CA 19	45	ZP580	85-137	225/35		
8,5 x 19	B32	45	ZP580	85-137	225/35		
	B42	45	ZP580	85-137	225/35		
	CA 20	45	ZP580	85-137	225/35		

Mazda 6 IIIab 12.2012GJ / GH5/114,367,1e1*2007/46*1001*... e1*2001/116*0448*14-...

Sensor - Brocksens 6

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC24	42	ZP580D6F	107-141	215/65	 Orig.-Verschr., incl. Facelift 2016, nur M+S
	RC30	42	-	107-141	215/60, 215/65 , 225/60, 235/60	 Orig.-Verschr., incl. FL2016 u. 2018, nur M+S
	RC24	42	-	107-141	215/60, 215/65, 225/60, 235/60	 215er Reifen nur M+S
7 x 17	RC27	50	ZP580D6F	107-141	215/55, 215/60, 225/55	 Orig.-Verschr., incl. Facelift 2016 u. 2018
	RC30	50	-	107-141	215/55M+S, 215/60M+S, 225/55	 Orig.-Verschr.
	RC32	50	-	88-141	215/55M+S, 215/60M+S, 225/55, 235/50, 235/55	 Orig.-Verschr.
	RC34	50	-	88-141	225/55	 Orig.-Verschr.
	B39	50	-	107-141	215/55M+S, 215/60M+S, 225/55	 Orig.-Verschr., incl. Facelift 2016 u. 2018
7,5 x 19	RC32	45	-	88-143	225/40, 225/45	 Orig.-Verschr.
	B32	45	-	107-143	225/40, 225/45	 Orig.-Verschr., inkl. FL2018

weitere Dimensionen/Designs siehe Konfigurator

CX-306.2015DJ15/114,367,1e1*2007/46*1335*...

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info
	RC27	50	ZP580D6F	77-115	215/60 , 225/55, 225/60	
	RC30	50	ZP580D6F	77-115	215/60 , 225/55, 225/60	
	RC32	50	-	77-115	215/60 , 225/55, 225/60	 Orig.-Verschr.
	RC34	50	-	77-115	215/60 , 225/55, 225/60	 Orig.-Verschr.

6,5 x 16	RC24	36+42	ZP580D6F	77-115	215/60, 225/55, 225/60		
		48	ZP580				
	RC27	50	ZP580	77-115	215/60, 225/55, 225/60		
	RC30	47	ZP580D6F	77-115	215/60, 225/55, 225/60		
		50	ZP580	77-115	215/60, 225/55, 225/60		
	RC32	47,5	-	77-115	215/60, 225/55, 225/60		Orig.-Verschr.
RC34	45	-	77-115	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.	
CA 20	45	ZP580	77-115	215/60, 225/55, 225/60			
7 x 17	RC27	45	ZP580	77-115	215/55, 225/50, 225/55, 235/50		bei 235/50 ✖
		47	-	77-115	215/55, 225/50, 225/55		Orig.-Verschr.
		50	ZP580D6F	77-115	215/55, 225/50, 225/55		
	RC30	47	ZP580D6F	77-115	215/55, 225/50, 225/55		
		50	-	77-115	215/55, 225/50, 225/55		Orig.-Verschr.
	RC32	43,5+45	-	77-115	215/50, 215/55, 225/50, 225/55		Orig.-Verschr.
		47+48,5	-	77-115	215/50, 215/55, 225/50		Orig.-Verschr.
		50	-	77-115	215/50, 215/55		Orig.-Verschr.
	B39	45	ZP580	77-115	215/55, 225/50, 225/55		
		50	ZP580D6F	77-115	215/55, 225/50, 225/55		
7,5 x 17	RC24	45	ZP580	77-115	215/55, 225/50, 225/55		
		50	ZP580	77-115	215/55		
	RC27	46	ZP580D6F	77-115	215/50, 215/55, 225/50		
	RC28	45	ZP580	77-115	215/55, 225/50, 225/55		
	RC29	48	ZP580	77-115	215/55		
	RC32	46	-	77-115	215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr.
	B36	46	ZP580	77-115	215/55, 225/50, 225/55		
	Oxigin 14	42	ZP580	77-115	215/50, 215/55		
	Oxigin 19	48	ZP580	77-115	215/50, 215/55, 225/50, 225/55		
	7 x 18	RC27	50	ZP580D6F	77-115	215/45, 215/50, 225/45, 225/50	
46			ZP580D6F	77-115	215/45, 215/50, 225/45, 225/50		
RC32		45+48,5	-	77-115	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18		RC30	45	ZP580	77-115	215/45, 215/50, 225/45, 235/45, 245/45	
	49,5+50		ZP580D6F	77-115	215/45, 215/50, 225/45, 235/45		
	50,5	ZP580D6F	77-115	215/45, 215/50, 225/45, 235/45			
	RC32	45	-	77-115	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32	45	ZP580	77-115	215/45, 215/50, 225/45, 235/45		
		49,5	ZP580D6F	77-115	215/45, 215/50, 225/45, 235/45		
		50,5	ZP580D6F	77-115	215/45, 215/50, 225/45, 235/45		
	B39	45	ZP580	77-115	215/45, 215/50, 225/45, 235/45, 245/45		
50		ZP580D6F	77-115	215/45, 215/50, 225/45, 235/45			
AC-521	45	ZP580D6F +R	77-115	215/45, 215/50, 225/45, 235/45, 245/45		+ Red.Ringe 73,1-67,1	
	Oxigin 18	45	ZP580	77-115	215/45, 215/50, 225/45, 235/45, 245/45		bei 245/45 ✖
7,5 x 19	RC32	45	-	77-115	225/40		Orig.-Verschr.
	B32	40	ZP580	77-115	225/40		
		45+49,5	ZP580D6F	77-115	225/40		
	B39	40+45	ZP580	77-115	225/40		
		50	ZP580D6F	77-115	225/40		
	AC-521	45	ZP580D6F +R	77-115	225/40		+ Red.Ringe 73,1-67,1
Oxigin 18	50	ZP580	77-115	225/40			
8 x 19	RC27	46	ZP580D6F	77-115	225/40, 235/40		
		47	-	77-115	225/40, 235/40		
	RC29	48	ZP580	77-115	225/40, 235/40		
	B38	45	ZP580	77-115	225/40, 235/40		
	B24	50	ZP580	77-115	225/40		
	AC-518	40	ZP580D6F +R	77-115	225/40		+ Red.Ringe 73,1-67,1
8,5 x 19	B32	45	ZP580	77-115	225/40, 235/40		bei 235/40 ✖
	B36	44	ZP580	77-115	225/40, 235/40		bei 235/40 ✖
	B37	45	ZP580	77-115	225/40, 235/40		
	B42	45	ZP580	77-115	225/40		
	B43	46,5	ZP580D6F	77-115	225/40		
	Oxigin 25	43	ZP580	77-115	225/40		
8 x 20	B38	45+50	ZP580	77-115	225/35, 235/35		ET50 nur 225/35

CX-30 ab 09.2019 DM 5/114,3 67,1 e13*2007/46*2041*..

Sensor - Brocksens 7 od. HUF RDE225 - Artikelnummer 92085

Dimension	Design	ET	KIT	KW	Reifendimension	Info
	RC30	45	ZP580D6F	85-143	215/65, 225/60	
	RC32	45	-	85-90	215/65, 225/60, 225/65, 235/60	
	RC34	45	-	85-143	215/65, 225/65, 235/60	
	RC24	42	ZP580D6F	85-143	215/65, 225/60, 235/60	

6,5 x 16	RC27	36	ZP580D6F	85-143	215/65, 225/60		
		38	ZP580	85-143	215/65, 225/60		
		45	ZP580	85-143	215/65, 225/60		
	RC30	42	ZP580D6F	85-143	215/65, 225/60, 235/60		
		44	ZP580D6F	85-143	215/65, 225/60		
	RC32	42,5+44	-	85-90	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
6,5 x 17	CA 20	45	ZP580	85-143	215/65, 225/60		
	RC27	40	ZP580D6F	85-143	215/60, 225/55, 235/55		
7 x 17	RC27	40	ZP580D6F	85-143	215/60, 225/55		
		45	ZP580	85-143	215/60, 225/55		
	RC30	38	ZP580	85-143	215/60		
		45	ZP580D6F	85-143	215/60, 225/55		
			ZP580	85-143	215/60, 225/55		
	RC32	43,5	-	85-143	215/60, 225/55		Orig.-Verschr.
		45+47	-	85-143	215/60, 225/55		Orig.-Verschr.
	B39	45	ZP580	85-143	215/60, 225/55		
7,5 x 17	CA 26	45	ZP580	85-143	215/60, 225/55		
	RC24 / RC28	45	ZP580	85-143	215/60		
	RC29	38	ZP580	85-143	215/60		
	AC-518	40	ZP580D6F +R	85-132	215/60		+ Red.Ringe 73,1-67,1
7 x 18	Oxigin 25	45	ZP580	85-137	215/60, 225/55, 225/60		
	RC32	45	-	85-143	215/55		Orig.-Verschr., auch Allrad
				85-143	215/55, 225/50, 235/50		Orig.-Verschr., 2WD
				85-137	215/55, 225/50, 235/50		Orig.-Verschr., 4WD
	RC34	45	-	85-143	215/55, 225/50, 235/50		Orig.-Verschr.
7,5 x 18	RC30	45	ZP580	85-143	215/50, 215/55, 235/45		
	RC32	45	-	85-143	215/55, 225/50, 245/45		Orig.-Verschr., 2WD
				85-137	215/55, 225/50		Orig.-Verschr., 4WD
	B32 / B39	45	ZP580	85-143	215/50, 215/55		
	AC-MB6 / AC-M10	45	Artikel Nr. 98499	85-143	215/50, 215/55, 235/45		Kit mit Artikelnummer 98499
	AC-521	45	ZP580D6F +R	85-143	215/50, 215/55, 235/45		+ Red.Ringe 73,1-67,1
	Oxigin 25	45	ZP580	85-137	215/55, 225/50, 235/45		
8 x 18	B36 / B37	45	ZP580	85-143	215/55, 235/45		
	B42	40+45	ZP580	85-143	215/55, 235/45		
	B44	40+45	ZP580	85-143	215/55, 235/45		
	AC-M10	45	ZP580D6F +R	85-143	215/55, 235/45		+ Red.Ringe 73,1-67,1
7 x 19	RC34	45	-	85-143	225/45		Orig.-Verschr.
7,5 x 19	B32	40	ZP580	85-143	225/45, 235/45		
		45	ZP580D6F	85-143	225/45, 235/45		
	RC32	45	-	85-143	225/45, 235/45		Orig.-Verschr., auch Allrad
	AC-521	45	ZP580D6F +R	85-143	215/50, 225/45, 235/45		+ Red.Ringe 73,1-67,1
8 x 19	RC29	38	ZP580	85-132	225/45		
	AC-518	40	ZP580D6F +R	85-143	225/45, 235/45		+ Red.Ringe 73,1-67,1
	CA 17	40	ZP580	85-137	225/45		
	CA 19	45	ZP580	85-143	225/45		
	CA 24	45	ZP580	85-137	225/45, 235/40, 235/45		
	Oxigin 29	40	ZP580	85-143	225/45, 235/45		
8,5 x 19	B44	40	ZP580	85-143	225/45		
	CA 23	40	ZP580	85-143	225/45		
8 x 20	B38	45	ZP580	85-143	225/40		
8,5 x 20	B24	42	ZP580	85-143	225/40		
	B44	40	ZP580	85-143	225/40		
	AC-518	40	ZP580D6F +R	85-143	225/40		+ Red.Ringe 73,1-67,1

CX-5 (siehe Konfigurator)	ab 04.12	KE/ GH	5/114,3	67,1	e13*2007/46*1247*..., e1*2001/116*0448*14+...
---------------------------	----------	--------	---------	------	---

CX-5	ab 06.2017	KF / KFE	5/114,3	67,1	e13*2007/46*1803*..., e13*2007/46*1832*..
------	------------	----------	---------	------	---

Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
RC27	50	-	110-143	225/65, 235/60, 235/65		Orig.-Verschr.	
		-	110-143	225/65, 235/60, 235/65			
	45	ZP580	110-143	225/65, 235/60, 235/65		Orig.-Verschr., beide ET's original	
		-	110-143	225/65, 235/60, 235/65			
RC30	50	-	110-143	225/65, 235/60, 235/65			
	45	-	110-143	225/65, 235/60, 235/65, 245/60, 255/55, 255/60		Orig.-Verschr., beide ET's original	
RC32	50	-	110-143	225/65, 235/60, 235/65, 245/60			
	45	-	110-143	225/65, 235/60, 235/65, 245/60			

7 x 17	RC34 B39	50	-	110-143	225/65		Orig.-Verschr.	
		50	-	110-143	225/65, 235/60, 235/65		Orig.-Verschr.	
	RC27	45	ZP580	110-143	225/65, 235/60, 235/65			
		47	-	110-143	225/65, 235/60, 235/65		Orig.-Verschr.	
	RC30	47	ZP580D6F	110-143	225/65, 235/60, 235/65			
51		-	110-143	225/65		Orig.-Verschr.		
7,5 x 17	RC32	47	-	110-143	225/65, 235/60, 235/65, 245/60, 255/55, 255/60		Orig.-Verschr.	
		48,5	-	110-143	225/65, 235/60, 235/65, 245/60, 255/60		Orig.-Verschr.	
	B39	38	ZP580	110-143	225/65, 235/60, 235/65			
		45	ZP580	110-143	225/65, 235/60, 235/65		beide ET's original	
	RC27	46	ZP580D6F	110-143	225/60, 225/65, 235/60			
	RC28	45	ZP580	110-143	225/65, 235/60, 235/65			
	RC29	38+48	ZP580	110-143	225/65, 235/60, 235/65			
	RC32	46	-	110-143	225/65, 235/60, 235/65, 245/60		Orig.-Verschr.	
	B24	48	ZP580	110-143	225/65, 235/60, 235/65			
	AC-518	40	ZP580D6F +R	110-143	225/65, 235/60, 235/65		+ Red.Ringe 73,1-67,1	
	Oxigin 25	45	ZP580	110-143	225/60, 225/65, 235/60, 235/65			
	7 x 18	RC27	50	-	110-143	225/55, 225/60, 235/55		
		RC32	45+48,5	-	110-143	225/55, 225/60, 235/55, 245/50, 245/55, 255/50, 255/55		Orig.-Verschr., nicht Bremse 320x28mm
7,5 x 18	RC30	45	ZP580	110-143	225/60, 235/55, 235/60			
		49,5	-	110-143	225/60, 235/55, 235/60		Orig.-Verschr.	
		50	-	110-143	225/60, 235/55, 235/60		Orig.-Verschr.	
	RC32	45	-	110-143	225/55, 225/60, 235/55, 245/50, 245/55		Orig.-Verschr.	
		45	ZP580	110-143	225/60, 235/55, 235/60			
	B32	49,5+50,5	-	110-143	225/60, 235/55, 235/60		Orig.-Verschr.	
		45	ZP580	110-143	225/60, 235/55, 235/60			
	B39	50	-	110-143	225/60, 235/55, 235/60		Orig.-Verschr.	
		45	Artikel Nr. 98499	110-143	225/60, 235/55, 235/60		Kit mit Artikelnummer 98499	
	AC-521	45	ZP580D6F +R	110-143	225/60, 235/55, 235/60		+ Red.Ringe 73,1-67,1	
8 x 18	Oxigin 18	45	ZP580	110-143	225/55, 225/60, 235/55, 235/60			
	RC27	46	ZP580D6F	110-143	225/55, 225/60			
	RC29	45	ZP580	110-143	225/60, 235/55, 235/60			
	RC34	50	-	110-143	225/55, 225/60, 235/55		Orig.-Verschr.	
	B24	48	ZP580	110-143	225/60, 235/55, 235/60			
	B38	45	ZP580	110-143	225/60, 235/55, 235/60			
		49	ZP580	110-143	225/60			
	B42	40+45	ZP580	110-143	225/60, 235/55, 235/60			
	B44	40+45	ZP580	110-143	225/60, 235/55, 235/60			
	AC-518	40	ZP580D6F +R	110-143	225/60, 235/55, 235/60		+ Red.Ringe 73,1-67,1	
	AC-M10	45	ZP580D6F +R	110-143	225/60, 235/55, 235/60		+ Red.Ringe 73,1-67,1	
	7 x 19	RC27	45	-	110-143	225/55, 235/50, 255/50		Orig.-Verschr.
		RC34	45	-	110-143	225/55		Orig.-Verschr.
7,5 x 19	RC32	45	-	110-143	225/55, 235/50, 245/45, 245/50		Orig.-Verschr.	
	B32	45+49,5	-	110-143	225/55, 235/50, 245/45, 255/50		Orig.-Verschr.	
	B39	40	ZP580	110-143	225/55, 235/50, 245/45			
		45	ZP580	110-143	225/55, 235/50, 245/45, 255/50			
		50	-	110-143	225/55, 235/50, 245/45, 255/50		Orig.-Verschr.	
	AC-521	45	ZP580D6F +R	110-143	225/55, 235/50, 245/45, 255/50		+ Red.Ringe 73,1-67,1	
	Oxigin 18	50	ZP580	110-143	225/55, 235/45, 245/45			
8 x 19	CA 19	45	ZP580	110-143	225/55, 235/50, 245/45, 255/45			
	CA 24	45	ZP580	110-143	225/55, 235/45, 235/50, 245/45, 255/45			
	Oxigin 29	50	ZP580	110-143	225/55, 235/50, 245/45, 255/45			
8,5 x 19	B44	40	ZP580	110-143	225/55, 245/45			
8 x 20	B38	35	ZP580	110-143	235/45, 245/40, 245/45			
		45+50	ZP580	110-143	235/45, 245/40, 245/45, 255/45			
8,5 x 20	B40	35	ZP580	110-143	235/45, 245/40, 245/45			
	RC29	40	ZP580	110-143	235/45, 245/40, 245/45			
	B24	42+50	ZP580	110-143	235/45, 245/40, 245/45, 255/40, 255/45			
	B32	45	ZP580	110-143	235/45, 245/40, 255/40, 255/45			
	B42	45	ZP580	110-143	235/45, 245/40, 245/45, 255/40, 255/45			
	B44	40	ZP580	110-143	235/45, 245/40, 245/45			
8,5 x 20	AC-518	40	ZP580D6F +R	110-143	235/45, 245/40, 245/45		+ Red.Ringe 73,1-67,1	
	B41	43,5	-	110-143	245/35, 245/40		Orig.-Verschr.	
weitere Dimensionen/Designs siehe Konfigurator								

CX-60		NEU		ab Juli 2022		KH01 / KH01E		5/114,3		67,1		e13*2018/858*00255*.., e13*2018/858*00449*..	
Sensor - Brocksens 7 od. HUF RDE225 - Artikelnummer 92085													
Dimension		Design		ET	KIT	KW	Reifendimension			Info			
7,5 x 18	RC32		45	-	141-187	235/60				Orig.-Verschr.			
	RC34		45	-	141-187	235/60				Orig.-Verschr.			
	B32		45	ZP580	141 (241)	235/60, 245/55							
	AC-MB6 / AC-M10		45	Artikel Nr. 98499	141-187	235/60, 245/55				Kit mit Artikelnummer 98499			
	Oxigin 25		45	ZP580	141-187	235/60							
8 x 18	B24		38	ZP580	141-187	235/60							
	B36		45	ZP580	141-187	235/60							
	B42		40	ZP580	141-187	235/60, 245/55							
			45	ZP580	141-187	235/60							
	B44		40	ZP580	141-187	235/60, 245/55							
			45	ZP580	141-187	235/60							
AC-M10		45	ZP580D6F +R	141-187	235/60				+ Red.Ringe 73,1-67,1				
7,5 x 19	RC32		45	-	141-187	235/55				Orig.-Verschr.			
8 x 19	CA 19		45	ZP580	141-187	235/55							
	Oxigin 29		40	ZP580	141-187	235/55, 245/50							
8,5 x 19	B32		45	ZP580	141-187	235/55							
	B37		45	ZP580	141 (241)	235/55							
	B36		38	ZP580	141-187	235/55							
	B44		40	ZP580	141-187	235/55							
	CA 20		45	ZP580	141-187	235/55							
	CA 23		40	ZP580	141-187	235/55							
	Oxigin 28		45	ZP580	141-187	235/55							
7,5 x 20	RC36		45	-	141-187	235/50, 245/45				Orig.-Verschr.			
	B43		45	-	141-187	235/50				Orig.-Verschr.			
				-	141-187	235/50, 245/45							
8,5 x 20	B42		45	ZP580	141-187	235/50, 245/45, 255/45							
9 x 20	B37		43	ZP580	141-187	245/45							
	CA 20 / CA 23		45	ZP580	141-187	245/45							
	Oxigin 28		40	ZP580	141-187	235/50, 245/45, 255/45							
8,5 x 21	B41		47	ZP580	141-187	235/45, 245/40							
	B43		43,5	-	141-187	235/45, 245/40, 255/40				Orig.-Verschr.			

CX-80		NEU		1. Quartal 2024		KL01		5/114,3		67,1		e13*2018/858*00760*..	
Dimension		Design		ET	KIT	KW	Reifendimension			Info			
7,5 x 18	RC32		45	-	141-187	235/60				Orig.-Verschr.			
	RC34		45	-	141-187	235/60				Orig.-Verschr.			
	AC-MB6		45	Artikel Nr. 98499	141, 187	235/60, 245/55				Kit mit Artikelnummer 98499			
	RC36		45	-	141, 187	235/50, 245/45				Orig.-Verschr.			

CX-80 NEU		1. Quartal 2024		KL01		5/114,3	67,1	e13*2018/858*00760*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 18	RC32	45	-	141-187	235/60				Orig.-Verschr.
	RC34	45	-	141-187	235/60				Orig.-Verschr.
	AC-MB6	45	Artikel Nr. 98499	141, 187	235/60, 245/55				Kit mit Artikelnummer 98499
7,5 x 20	RC36	45	-	141, 187	235/50, 245/45				Orig.-Verschr.
	B43	45	-	141, 187	235/50				Orig.-Verschr.
				141, 187	235/50, 245/45				
8,5 x 21	B41	47	- +R	141-187	235/45, 245/40				+ Red.Ringe 72,6-67,1

CX-9 (siehe Konfigurator)		ab 2009		TB1		5/114,3	67,1	e13*KS07/46*0005*..	

MX-30		ab 2020		DR		5/114,3		67,1		e13*2007/46*2300*...	
Sensor - Brocksens 7 od. HUF RDE225 - Artikelnummer 92085											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 18	RC32	45	-	60-81	215/55, 225/50				Orig.-Verschr.		
	RC34	45	-	60-81	215/55, 225/50				Orig.-Verschr.		
7,5 x 18	RC27	38	ZP580D6F	81 (107)	215/55						
	RC32	45	-	81	215/55				Orig.-Verschr.		
	Oxigin 25	45	ZP580	60-81	215/55						
8 x 18	B42	40	ZP580	60, 81	215/55						
	B44	40	ZP580	60, 81	215/55						
7 x 19	RC27	45	ZP580D6F	81 (107)	215/50, 225/45						
	RC34	45	-	81	215/50, 225/45				Orig.-Verschr.		
7,5 x 19	RC32	45	-	60-81	215/50, 225/45, 235/45				Orig.-Verschr.		
	B32	40	ZP580	81 (107)	215/50, 225/45, 235/45						
		51	ZP580D6F	81 (107)	225/45						
	B39	40	ZP580	81 (107)	215/50, 225/45, 235/45						
		45	ZP580	81 (107)	225/45						
	AC-521	45	ZP580D6F +R	81 (107)	225/45				+ Red.Ringe 73,1-67,1		
	RC29	38	ZP580	81 (107)	225/45						

8 x 19	B38	38	ZP580	81 (107)	225/45		
	AC-518	40	ZP580D6F+R	81 (107)	225/45, 235/45		+ Red.Ringe 73,1-67,1
	CA 24	45	ZP580	81	225/45		
	Oxigin 29	40	ZP580	60, 81	225/45, 235/45		
8,5 x 19	B44	40	ZP580	60, 81	225/45		
7,5 x 20	CA 23	40	ZP580	81 (107)	225/45		
8,5 x 20	B43	45	ZP580D6F	81 (107)	225/40		
	RC29	40	ZP580	81 (107)	225/40		
	B44	40	ZP580	60, 81	225/40		
	AC-518	40	ZP580D6F+R	81 (107)	225/40		+ Red.Ringe 73,1-67,1

MX-30 Plug-in-Hybrid NEU		2. Halbjahr 2022		DR	5/114,3	67,1	e13*2007/46*2300*...	
Sensor - Brocksens 7 od. HUF RDE225 - Artikelnummer 92085								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	B42	40	ZP580	60, 81	215/55			
7 x 19	RC27	45	ZP580D6F	60, 81	215/50, 225/45			
8 x 19	Oxigin 29	40	ZP580	60, 81	225/45, 235/45			
8,5 x 19	B44	40	ZP580	60, 81	225/45			
7,5 x 20	B43	45	-	60, 81	225/40			Orig-Verschr.

MX-5 IV		ab 10.2015		ND	4/100	54,1	e11*2007/46*2661*...	
Sensor - Brocksens 6								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	45	-	96, 118	195/50, 205/45		Orig.-Verschr.	
	RC34	45	-	96-118	195/50, 205/45, 205/50		Orig.-Verschr., nicht Brembo-Bremse mit 280x22mm	
	RC24	38	ZP422	96, 118	195/50, 205/45			
	RC30	38	ZP422	96, 118	195/50, 205/45			
7 x 16	RC28	38	ZP422	96, 118	195/50, 205/45			
		45	ZP422	96, 118	195/50, 205/45, 215/45			
	B24	38	ZP422	96, 118	195/50, 205/45			
6,5 x 17	RC14 EL	45	-	96, 97	195/45		Orig.-Verschr., RLP, SVR	
				118	195/45, 205/45		Orig.-Verschr., für 16 Zoll Serie, RLP, SVR	
7 x 17	RC34	45	-	96-135	195/40, 195/45, 205/40, 205/45, 215/40		Orig.-Verschr.	
	B24	45	ZP422	96, 118	195/45, 205/40, 205/45, 215/40HA			
	B39	38	ZP422	96, 118	195/45, 205/40			
		44	ZP422	96, 118	195/45, 205/40, 205/45, 215/40HA			
7,5 x 18	B39	38+45	ZP422	96, 97	205/35			

MX-5 RF		ab Frühjahr 2017		ND	4/100	54,1	e11*2007/46*2661*..	
Sensor - Brocksens 6								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC34	45	-	96-135	205/45		Orig-Verschr.	
	B39	38	ZP422	118	195/45, 205/40, 205/45			
		44	ZP422	118	195/45, 215/40			
				118, 135	205/40, 205/45			
7,5 x 18	B39	38+45	ZP422	118, 135	205/35			

Maxus

<

Mercedes

Mercedes		Baujahr	Typ	LK/LZ	Nabe	
A-Klasse		ab 2012	176 / 245G	5/112	66,6	e1*2007/46*0928*..., e1*2001/116*0470*04-..
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC32	49	-	66-135	205/55	 Orig.-Verschr.
	D17	49	-	66-135	205/55	 Orig.-Verschr., nur Bremse max. 295mm
6,5 x 17	D17	49	-	66-160	205/50M+S	 Orig.-Verschr., nicht Bremse 295mm
	RC27	49	-	66-160	205/50	 Orig.-Verschr., nur M+S, auch Allrad, nicht Bremse 320mm
	RC34	49	-	66-155	205/50	 Orig.-Verschr. , nicht Sportpaket
				120-160	205/50	Orig.-Verschr. , mit Sportpaket
7,5 x 17	RC27	52,5	-	66-160	225/45	 Orig.-Verschr.
7,5 x 18	B32	52	-	66-160	225/40	 Orig.-Verschr.
	B45	52	-	66-160	225/40	 Orig.-Verschr.
	Oxigin 18	52	-	66-155	225/40	 Orig.-Verschr.
8 x 18	RC27	48	-	125-265	235/40	 Orig.-Verschr.
	RC29	48	-	100-155	235/40	 Orig.-Verschr.
	RC34	48	ZP568F	120-160	235/40	
	B37	48	-	80-160	235/40	 Orig.-Verschr., 215/40 bis 135 KW
8 x 19	RC27	48	-	155-280	235/35	 Orig.-Verschr.
weitere Dimensionen/Designs siehe Konfigurator						

A-Klasse		2018	F2A (FIN: WDD177...)	5/112	66,6	e1*2007/46*1829*..		
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	D17	44	-	70-120	205/60, 215/55		Orig.-Verschr., Ausf. D42	
		44,5	-	70-120	205/60, 215/55		Orig.-Verschr., Bremse max. 305 mm, Ausf D4	
	RC32	44	-	70-120	205/60, 215/55, 225/55		Orig.-Verschr.	
	RC34	44	-	70-120	205/60, 215/55, 225/55		Orig.-Verschr.	
	CA 20	44	-	70-120	205/60		Orig.-Verschr., nicht Bremse 305mm	
	RC24	46	ZP568F	70-120	205/60, 215/55, 225/55		nicht Bremse 305mm	
	RC30	46	ZP568F	70-120	205/60, 215/55, 225/55		nicht Bremse 305mm	
6,5 x 17	RC32	44,5	-	80-120	205/60, 215/55, 225/55		Orig.-Verschr.	
	D17	44	-	70-165	205/50, 205/55		Orig.-Verschr., nicht Bremse 330 u. 350mm	
	RC34	44	-	70-165	205/55		Orig.-Verschr., nicht Bremse 350x30mm	
	D17	49	-	70-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330 u. 350mm	
	RC27	49	-	70-140	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330 u. 350mm	
7 x 17	D17	44	-	70-165	205/50, 205/55		Orig.-Verschr., nicht Bremse 350mm	
		48,5	-	70-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 350mm	
	RC27 / RC30	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm	
		44	-	70-165	205/50, 215/50, 225/45		Orig.-Verschr., nicht Bremse 350x30mm	
	RC32	44,5+48,5	-	70-165	205/50, 205/55, 215/50, 225/45		Orig.-Verschr., nicht Bremse 350mm	
	RC34	44	-	70-165	205/50, 215/50, 225/45		Orig.-Verschr., nicht Bremse 350x30mm	
	B39	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm	
	CA 26	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm	
	Pro1	49	F31	70-165	205/50, 205/55, 215/50, 225/45		nicht Bremse 350x30mm	
7,5 x 17	RC28	45	ZP568F	80-165	205/50, 205/55		nicht Bremse 350mm	
	RC29	45	ZP568F	70-165	205/50, 205/55		nicht Bremse 330mm	
	RC34	45	ZP568F	70-165	205/50, 215/50, 225/45, 235/45		nicht Bremse 350mm	
	B24	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 330 u. 350mm	
	CA 26	42	ZP568F	70-165	205/50, 205/55		nicht Bremse 350mm	
	AC-518	47	-	80-165	205/50, 205/55, 215/50		Orig.-Verschr., nicht Bremse 350mm	
7,5 x 18	RC32	49	-	70-165	205/45, 215/45, 225/40, 225/45		Orig.-Verschr., auch für Hybrid	
	B32	49	-	70-165	205/45, 215/45, 225/40, 225/45		Orig.-Verschr.	
	Oxigin 25	49	-	70-165	205/45, 215/45, 225/45		Orig.-Verschr.	
		44	-	80-165	205/45, 215/45		Orig.-Verschr.	
	RC30	45	ZP568F	80-165	205/45, 215/45, 225/40			
	RC32	42,5+44	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.	
	RC34	49	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.	
	B32	44	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.	
		45	ZP568F	70-165	205/45, 215/45, 225/40			
	B39	45	ZP568F	70-165	205/45, 215/45, 225/40, 225/45		nicht Plug in Hybrid	
	AC-MB6	45	AV1	70-165	205/45, 215/45, 225/40			
	RC25	45	ZP568F	70-165	215/45			
	RC27 / RC29	48	-	70-165	215/45, 225/40, 225/45, 235/40HA		Orig.-Verschr.	
	RC32	49	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.	
	8 x 18	RC34	43	ZP568F	70-165	205/45, 215/45		auch Hybrid
			48	ZP568F	70-165	205/45, 215/45, 225/40, 235/40		auch Hybrid
B24		48	ZP568F	70-165	215/45, 225/40, 225/45, 235/40			
B37		48	-	70-165	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.	
B42 / B44		45	ZP568F	70-165	215/45			
	AC-518	48	-	80-165	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.	

7,5 x 19	AC-M10	45	AV4	70-165	215/45		
	FMI08 Thoe	49	F31	70-165	205/45, 215/45, 225/40, 235/40		
	FMI11 Elatha	39	F95	70-165	205/45		
		45	F95	70-165	205/45, 215/45, 225/40		
	RC32	49	-	70-165	215/35, 225/35, 225/40		Orig.-Verschr.
8 x 19	RC34	49	-	70-165	215/35, 225/35, 225/40		Orig.-Verschr., auch Hybrid
		45,5	-	70-165	215/35, 225/35		Orig.-Verschr.
	RC32	40	-	70-165	215/35		Orig.-Verschr., auch für Hybrid
	RC34	48	ZP568F	70-165	215/35, 225/35, 225/40, 235/35		
		49	-	70-165	215/35, 225/35, 235/35		Orig.-Verschr.
9 x 19	AC-518	47	-	70-165	225/35		Orig.-Verschr.
	FMI07 Atena	47	F95	70-165	215/35, 225/35, 235/35		
	FMI12 Kari	49	-	70-165	225/35		Orig.-Verschr.
8 x 20	FMI08 Thoe	45	F31	70-165	225/30		
8,5 x 20	FMI12 Kari	50	F94	70-165	235/30		

A-Klasse A35 AMG		ab 2018	F2A	5/112	66,6	e1*2007/46**1829*... (FIN: WDD177)	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC32	33	-	225	215/40, 215/45 , 225/40		Orig.-Verschr., nur M+S, Ausführung "D4"
	RC34	40	-	225	215/40, 215/45, 225/40		Orig.-Verschr., nur M+S
	B39	35	ZP568F	225	215/45		nur M+S
8 x 18	D17	40	-	225	215/45M+S, 235/40		Orig.-Verschr., Ausführung "D4"
	RC34	40	ZP567F	225	215/40, 215/45, 225/40, 235/40 , 245/35		bis 225/40 nur M+S
		30	ZP567F	225	215/40		nur M+S
	B44	35	ZP568F	225	215/45		nur M+S
	AC-MB6	39	AV1	225	215/45M+S, 235/40		
8 x 19	RC32	40	-	225	235/35 , 245/30		Orig.-Verschr., Ausführung "D4"
	RC34	38	ZP568F	225	235/35		
	CA 19	38	F95	225	235/35		nicht Bremse 350mm
	CA 24	38	F95	225	235/35		
	FMI07 Atena	39	F95	225	235/35		
8,5 x 19	FMI07 Atena	40	F95	225	235/35		

A-Klasse A45 AMG		ab 2019		F2A		5/112		66,6		e1*2007/46*1829*... (FIN: WDD177)	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 18	B24	35	ZP568F	285, 310	225/45				nur M+S		
	RC34	40	ZP567F	285-310	225/45, 235/40				nur M+S		
		43	ZP567F	285-310	225/45, 235/40, 245/40				nur M+S		
	B44	35	ZP568F	285, 310	225/45				nur M+S		
	AC-MB6	39	AV1	285, 310	225/45, 235/40				nur M+S		
8 x 19	RC32	40	-	285-310	225/40, 235/35				Orig.-Verschr., nur M+S		
	RC34	38	ZP568F	285-310	235/35						
		43	ZP568F	285-310	225/40, 235/35, 245/35				nur M+S		
	B40	38	ZP568F	285, 310	225/40, 235/35				nur M+S		
	FMI07 Atena	39	F95	285-310	225/40, 235/35				nur M+S		
	Oxigin 29	39	ZP568F	285, 310	225/40, 235/35				nur M+S		
8,5 x 19	B32	45	ZP568F	285, 310	225/40M+S, 235/35M+S, 245/35						
	AC-M10	40	AV1	285, 310	225/40, 235/35				nur M+S		
	FMI07 Atena	40	F95	285-310	235/35M+S						
		45	F95	285-310	225/40M+S, 235/35M+S, 245/35						

A-Klasse A 250e NEU				F2A	5/112	66,6	e1*2007/46*1829*07-.. (FIN: WDD177)	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	Originaldim.	44			205/55			
7 x 17	D17	44	-	118	205/50, 205/55			Orig.-Verschr., nicht Bremse 350mm
		48,5	-	118	205/50, 205/55, 215/50, 225/50			Orig.-Verschr., nicht Bremse 350mm
	RC27	47	ZP568F	118, 120	205/50, 205/55, 215/50			nicht Bremse 350mm
	RC30	47	ZP568F	118	205/50, 205/55, 215/50			nicht Bremse 350mm
	B39	47	ZP568F	118	205/50, 205/55, 215/50			nicht Bremse 350mm
	CA 26	42	ZP568F	118, 120	205/50, 205/55			nicht Bremse 350mm
7 x 18	RC27	46	-	118, 120	205/45, 215/45, 225/45			Orig.-Verschr.
7,5 x 18	B32	49	-	118	205/45, 215/45, 225/40, 225/45			Orig.-Verschr.
	RC30	44	-	118	205/45, 215/45, 225/40			Orig.-Verschr.
		45	ZP568F	118, 120	205/45, 215/45, 225/40			
	B32	44	-	118	205/45, 215/45, 225/40			Orig.-Verschr.
		45	ZP568F	118, 120	205/45, 215/45, 225/40			
	B39	45	ZP568F	118	205/45, 215/45, 225/40			
	AC-MB6	45	AV1	118, 120	205/45, 215/45, 225/40			
	RC27	48	-	118	215/45, 225/40, 225/45, 235/40			Orig.-Verschr.
	RC29	48	-	118	215/45, 225/40, 225/45, 235/40			Orig.-Verschr.
	B24	48	ZP568F	118, 120	215/45, 225/40, 225/45, 235/40			

8 x 18	B36	45	ZP568F	118, 120	215/45		
	B37	48	-	118, 120	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
	B42 / B44	45	ZP568F	118, 120	215/45		
	AC-518	48	-	118	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
	AC-M10	45	AV4	118, 120	215/45		
7,5 x 19	Originaldim.	49			225/40		
8 x 19	RC27	48	-	118	225/40		Orig.-Verschr., ✖

AMG GT		ab 2018		R1EAMG	5/112	66,6	e1*2007/46*1878*..	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
10 x 21	FMI12 Kari	19	-	270-470	VA 255/35+HA 295/30			Orig.-Verschr., nur M+S
10,5 x 21	B41	31	ZP568F	270-470	VA 265/35+HA 305/30			
nur M+S								

Kombinationen

9,5 x 20	B32	VA 25	ZP568F	270-470	VA 255/40+HA 285/35, VA 265/35+HA 305/30, VA 265/40+HA 295/35		nur M+S
10,5x20		HA 20					
9,5 x 21	B41	VA 31	ZP568F	270-470	VA 255/35+HA 295/30, VA 265/35+HA 305/30, VA 275/35+ HA 315/30		nur M+S
10,5 x 21		HA 31					

B-Klasse		ab 11.11		246 / 245G		5/112		66,6		e1*2007/46*0751*.., e1*2001/116*0470*04-..	
Sensor - Brocksens 3											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 16	D17	49	-	66-135	205/55, 215/55				Orig.-Verschr., incl. Facelift 2014		
	RC32	49	-	66-135	195/55, 195/60, 205/55, 215/50, 215/55, 225/50				Orig.-Verschr.		
6,5 x 17	D17	49	-	66-155	205/50 M+S				Orig.-Verschr., incl. Facelift 2014, nicht Bremse 295mm		
				66-135	205/45, 205/50						
	RC27	49	-	66-155	205/50				M+S, Orig.-Verschr.,nicht Allrad, nicht Bremse 320mm		
7,5 x 17	RC27	52,5	-	66-155	225/45				Orig.-Verschr., incl. Facelift 2014		
				66-155	205/50, 215/45, 225/45						
7,5 x 18	B32	52	-	66-155	225/40				Orig.-Verschr., incl. Facelift 2014		
	B45	52	-	66-155	225/40				Orig.-Verschr., incl. FL2014, nicht Bremse 295mm		
	Oxigin 18	52	-	66-155	225/40				Orig.-Verschr.		

weitere Dimensionen/Designs siehe Konfigurator

B-Klasse		ab 02.2019		F2B	5/112	66,6	e1*2007/46*1909*..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC32	44	-	70-120	205/60, 215/55, 225/55		Orig.-Verschr.
	RC34	44	-	70-120	205/60, 215/55, 225/55		Orig.-Verschr.
	D17	44	-	70-120	205/60, 215/55		Orig.-Verschr., nicht Bremse 305mm
		44,5	-	70-120	205/60, 215/55		Orig.-Verschr., nicht Bremse 305mm, Ausführung D4
	CA 20	44	-	70-120	205/60		Orig.-Verschr., nicht Bremse 305mm
	RC24 / RC30	46	ZP568F	70-120	205/60, 215/55, 225/55		nicht Bremse 305mm
6,5 x 17	RC32	44,5	-	85-120	205/60, 215/55, 225/55		Orig.-Verschr.
	D17	44	-	70-165	205/50, 205/55		Orig.-Verschr., nicht Bremse 330 u. 350mm
	RC34	44	-	70-165	205/55		Orig.-Verschr.
	D17	49	-	70-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330 u. 350mm
	RC27	49	-	70-140	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330 u. 350mm
7 x 17	D17	44	-	70-165	205/50, 205/55		Orig.-Verschr., nicht Bremse 350mm
		48,5	-	70-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 350mm
	RC27 / RC30	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm
	RC32	44	-	70-165	205/50, 205/55, 215/50, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
					205/50, 205/55, 215/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
		48,5	-	70-165	205/50, 205/55, 215/50, 225/45, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
	RC34	44	-	70-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
					205/50, 205/55, 215/50, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
					205/50, 205/55, 215/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B39	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm
	CA 26	47	ZP568F	70-165	205/50, 205/55, 215/50		nicht Bremse 350mm
	Pro1	49	F31	70-165	205/50, 205/55, 215/50, 225/45, 225/50		mit Verbundlenker-Hinterachse
205/50, 205/55, 215/50, 225/50						mit Mehrlenker-Hinterachse	
7,5 x 17	RC24	42	ZP568F	85-140	205/50, 205/55		nicht Bremse 350mm
	RC34	45	ZP568F	70-165	205/50, 205/55, 215/50, 225/45, 235/45		
	B24	47	ZP568F	85-140	205/50, 205/55		nicht Bremse 330 u. 350mm
	B36	45	ZP568F	70-165	205/50, 205/55		nicht Bremse 330 u. 350mm
	AC-518	42+47	-	85-140	205/50, 205/55		Orig.-Verschr., nicht Bremse 350mm
	RC32	49	-	70-165	205/45, 215/45, 225/40, 225/45		Orig.-Verschr., auch für Hybrid
	B32	49	-	70-165	205/45, 215/45, 225/40, 225/45		Orig.-Verschr., nur zul. mit Einzelradaufhängung
	Oxigin 25	49	-	70-165	225/45		Orig.-Verschr.
	RC32	42,5+44	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.

7,5 x 18	RC34	49	-	70-165	205/45, 215/45, 225/40, 225/45		Orig.-Verschr.
	B32	44	-	70-165	205/45, 215/45, 225/40		Orig.-Verschr.
		45	ZP568F	70-165	205/45, 215/45, 225/40		
	B39	45	ZP568F	70-165	205/45, 215/45, 225/40, 225/45		nicht Plug in Hybrid
	AC-MB6	45	AV1	70-165	205/45, 215/45, 225/40		
8 x 18	RC27 / RC29	48	-	70-165	215/45, 225/40, 225/45		Orig.-Verschr.
	RC32	49	-	70-165	205/45, 215/45, 225/40, 235/40		Orig.-Verschr.
	RC34	43	ZP568F	70-165	205/45, 215/45		auch Hybrid
		48	ZP568F	70-165	205/45, 215/45, 225/40, 235/40		auch Hybrid
	B24	48	ZP568F	70-165	215/45, 225/40, 225/45		
	B37	48	-	70-165	215/45, 225/40, 225/45		Orig.-Verschr.
	B38	45	ZP568F	85-140	215/45, 225/40		
	B42 / B44	45	ZP568F	70-165	215/45		
	AC-518	48	-	85-140	215/45, 225/40, 225/45		Orig.-Verschr.
	AC-M10	45	AV4	70-165	215/45		
	FMI08 Thoe	49	F31	70-165	205/45, 215/45, 225/40, 235/40		
	FMI11 Elatha	39	F95	70-165	205/45		
		45	F95	70-165	205/45, 215/45, 225/40		
7,5 x 19	RC32	49	-	70-165	225/35, 225/40		Orig.-Verschr.
	RC34	49	-	70-165	225/35, 225/40		Orig.-Verschr., auch Hybrid
		45,5	-	70-165	225/35		Orig.-Verschr.
8 x 19	RC29	45	ZP568F	70-165	225/35		
	RC34	48	ZP568F	70-165	225/35, 235/35		235/35 nur mit Mehrlenker-Hinterachse
		49	-	70-165	225/35, 235/35		Orig.-Verschr.
	AC-518	47	-	85-140	225/35		Orig.-Verschr.
	FMI07 Atena	47	F95	70-165	225/35		

B-Klasse B 250e NEU		ab 2019		F2B	5/112	66,6	e1*2007/46*1909*05-...
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	D17	44	-	118	205/50, 205/55		Orig.-Verschr., nicht Bremse 350mm
		48,5	-	118	205/50, 205/55, 215/50		Orig.-Verschr., nicht Bremse 350mm
	RC27	47	ZP568F	118, 120	205/50, 205/55, 215/50		nicht Bremse 350mm
	RC30	47	ZP568F	118	205/50, 205/55, 215/50		nicht Bremse 350mm
	B39	47	ZP568F	118	205/50, 205/55, 215/50		nicht Bremse 350mm
7,5 x 17	CA 26	47	ZP568F	118, 120	205/50, 205/55, 215/50		nicht Bremse 350mm
7 x 18	CA 20	47	ZP568F	118, 120	205/50, 205/55		nicht Bremse 350mm
7,5 x 18	RC27	46	-	118, 120	205/45, 215/45, 225/45		Orig.-Verschr.
	B32	49	-	118	205/45, 215/45, 225/40, 225/45		Orig.-Verschr.
	RC30	44	-	118	205/45, 215/45		Orig.-Verschr.
		45	ZP568F	118, 120	205/45, 215/45		
	B32	44	-	118, 120	205/45, 215/45		Orig.-Verschr.
45		ZP568F	118, 120	205/45, 215/45			
8 x 18	AC-MB6	45	AV1	118, 120	205/45, 215/45		
	RC27	48	-	118	215/45, 225/40, 225/45		Orig.-Verschr.
	RC29	48	-	118	215/45, 225/40, 225/45		Orig.-Verschr.
	B24	48	ZP568F	118, 120	215/45, 225/40, 225/45		
	B36	45	ZP568F	118, 120	215/45		
	B37	48	-	118, 120	215/45, 225/40, 225/45		Orig.-Verschr.
	B42 / B44	45	ZP568F	118, 120	215/45		
	AC-518	48	-	118	215/45, 225/40, 225/45		Orig.-Verschr.
8 x 19	AC-M10	45	AV4	118, 120	215/45		
	RC27	48	-	118	225/40		Orig.-Verschr.

B-Klasse electric drive (28kWh-Batterie)							
ab 2014				245G	5/112	66,6	e1*2001/116*0470*..
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	D17	44	-	65 (132)	205/60		Orig.-Verschr., mit Kunststoffverbreiterung (Serie)
		44,5	-	65 (132)	205/60, 215/55, 225/55		Orig.-Verschr.
	RC32	44,5	-	65 (132)	205/60, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
	CA 20	44	-	65 (132)	205/60		Orig.-Verschr.
	RC24 / RC30	46	ZP568F	65 (132)	205/60, 215/55, 225/55		
	RC32	44+49	-	65 (132)	205/60, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., ET44 original-ET
	RC34	44	-	65 (132)	205/60, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
6,5 x 17	D17	38+44	-	65 (132)	205/50, 205/55, 215/50, 225/50		Orig.-Verschr.
	RC27	38	-	65 (132)	205/50, 205/55, 215/50, 225/50		Orig.-Verschr.
7 x 17	D17	48,5	-	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC32	48,5	-	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC34	48,5	-	65 (132)	225/50		Orig.-Verschr.
	RC27	47	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50		
	RC30	47	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50		
	B39	47	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50		
		47	ZP568F	65 (132)	205/50, 205/55		
	RC24	35	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45		
		42	ZP568F	65 (132)			

7,5 x 17	RC28	35	ZP568F	65 (132)	205/50, 205/55		
		45	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45		
	RC29	45	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45		
	RC34	36	ZP568F	65 (132)	205/50, 205/55, 225/45		
		40	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 235/45		
		45	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45		
	B36	45	ZP568F	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45		
	AC-518	42	-	65 (132)	205/50, 205/55, 215/50, 225/45, 225/50, 235/45		Orig.-Verschr.
	Oxigin 14	35	ZP568	65 (132)	205/50, 205/55		
7,5 x 18	Oxigin 19	35	ZP568F	65 (132)	205/50		
	RC30	44	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	RC32	44	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	B32	44	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	RC30	42	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	RC32	42,5	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
		49	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	B32	42	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	B39	45	ZP568F	65 (132)	215/45, 225/40, 225/45		
8 x 18	D17	40	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	RC25	45	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
	RC29	45	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
		48	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	RC32	49	-	65 (132)	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
	RC34	40	ZP568F	65 (132)	215/45, 225/40, 225/45		
		43+48	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
	B38	45	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
	B36	45	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
	B37	45	ZP568F	65 (132)	215/45, 225/40, 225/45, 235/40		
		48	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	AC-518	42	-	65 (132)	215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
		48	-	65 (132)	215/45, 225/40, 225/45		Orig.-Verschr.
	AF20	35	AV1	65 (132)	215/45		
	CA 17	35	ZP568F	65 (132)	215/45		
		45	ZP568F	65 (132)	215/45, 225/40, 225/45		
7,5 x 19	RC32	49	-	65 (132)	225/40		Orig.-Verschr.
	B32	44	-	65 (132)	225/40		Orig.-Verschr.
	B39	43	ZP568F	65 (132)	225/40		
8 x 19	RC29	39	-	65 (132)	225/40		Orig.-Verschr.
		45	ZP568F	65 (132)	225/40, 235/35		
	RC34	48	ZP568F	65 (132)	225/40, 235/35		
	B24	45	ZP568F	65 (132)	225/40, 235/35		nicht Allrad
	B38	39	-	65 (132)	225/40, 235/35		Orig.-Verschr., bei 235/35 ✖
		45	ZP568F	65 (132)	225/40, 235/35		nicht Allrad
	B40	43	ZP568F	65 (132)	225/40, 235/35		
	AC-518	38+47	-	65 (132)	225/40		Orig.-Verschr.

weitere Dimensionen/Designs siehe Konfigurator

Citan (siehe Konfigurator)	ab 2013	X	5/108	60,1	e2*2007/46*0129*.., e2*2007/46*0130*..
----------------------------	---------	---	-------	------	--

Citan NEU	im Laufe 1. Halbjahr	MFK	5/114,3	66,1	e2*2018/858*00015*..
-----------	----------------------	-----	---------	------	----------------------

Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC27	35	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60		Orig.-Verschr.
	RC24	40	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60		Orig.-Verschr.
6 x 16	RC34	38	-	55-96	205/60		Orig.-Verschr.
6,5 x 16	RC32	40	- (N7)	51-96	205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Ausführung N7
	RC24	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
	RC27	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
	RC30	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
6,5 x 17	RC27	32	-	55-96	205/50, 205/55		Orig.-Verschr.
7 x 17	RC32	43			205/55		TÜV i.V.
	RC34	43			205/55		TÜV i.V.
	RC27	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
	B39	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
	Pro1	45	-	51-96	205/55, 215/50, 225/45		Orig.-Verschr.
7,5 x 17	RC28	35	ZP581	55-96	205/50, 205/55, 225/45		
	RC24 / RC29	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		
	B24 / B36	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		
7 x 18	RC27	34+35+40	-	55-96	205/45, 215/45, 225/45		Orig.-Verschr.
	B32	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-	35	Artikel Nr.	55-96	205/45 215/45 225/40 225/45		Kit mit Artikelnummer 98478

7,5 x 18	M10	35	98478	55-96	205/45, 215/45, 225/40, 225/45	Kit mit Artikelnummer 98478
	AC-521	35	Artikel Nr. 98478	55-96	205/45, 215/45, 225/40, 225/45	Kit mit Artikelnummer 98478
	CA 20	40	ZP581	51-96	215/45, 225/40, 225/45	
	Oxigin 25	45	ZP581	51-96	215/45	
8 x 18	B24	38	ZP581	55-96	215/45, 225/40, 225/45	
	B36	35	ZP581	55-96	215/45	
	B42	40	ZP581	55-96	215/45	
	B44	40	ZP581	55-96	215/45	
7,5 x 19	AC-521	35	Artikel Nr. 98478	55-96	225/40	Kit mit Artikelnummer 98478
8 x 19	CA 17	40	ZP581	51-96	225/40	

Citan Tourer NEU		im Laufe 1. Halbjahr		MFK	5/114,3	66,1	e2*2018/858*00014*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC27	35	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60		Orig.-Verschr.
	RC24	40	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60		Orig.-Verschr.
6,5 x 16	RC32	40	- (N7)	51-96	205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Ausführung N7
	RC24	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
	RC27	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
	RC30	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		
6,5 x 17	RC27	32	-	55-96	205/50, 205/55		Orig.-Verschr.
	RC27	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
7 x 17	B39	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
	Pro1	45	-	51-96	205/55, 215/50, 225/45		Orig.-Verschr.
	RC24 / RC29	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		
7,5 x 17	RC28	35	ZP581	55-96	205/50, 205/55, 225/45		
	B24 / B36	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		
7 x 18	RC27	34+35+40	-	55-96	205/45, 215/45, 225/45		Orig.-Verschr.
7,5 x 18	B32	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	55-96	205/45, 215/45, 225/40, 225/45		Kit mit Artikelnummer 98478
	AC-521	35	Artikel Nr. 98478	55-96	205/45, 215/45, 225/40, 225/45		Kit mit Artikelnummer 98478
	Oxigin 25	45	ZP581	55-96	215/45		
8 x 18	B24	38	ZP581	55-96	215/45, 225/40, 225/45		
	B36	35	ZP581	55-96	215/45		
	B42	40	ZP581	55-96	215/45		
	B44	40	ZP581	55-96	215/45		
7,5 x 19	AC-521	35	Artikel Nr. 98478	55-96	225/40		Kit mit Artikelnummer 98478
8 x 19	CA 17	40	ZP581	55-96	225/40		

e-Citan NEU		2. Halbjahr 2022		MFK	5/114,3	66,1	e2*2018/858*000015*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC32	40	- (N7)	51-96	205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			Orig.-Verschr., Ausführung N7
6,5 x 17	RC27	32	-	51	205/50, 205/55			Orig.-Verschr., Elektro, kurze Karosserie
7 x 17	RC27	35+40	-	51	205/50, 205/55, 215/50, 225/45			Orig.-Verschr., Elektro, kurze Karosserie
		38	ZP581	51	205/50, 205/55, 215/50, 225/45			Elektro, kurze Karosserie
	B39	38	ZP581	51	205/50, 205/55, 215/50, 225/45			
	Pro1	45	-	51-96	205/55, 215/50, 225/45			Orig.-Verschr.
7,5 x 17	B24	38	ZP581	51	205/50, 205/55, 215/50, 225/45, 235/45			Elektro, kurze Karosserie
7 x 18	RC34	34	-	51	215/45, 225/45			Orig.-Verschr., Elektro, kurze Karosserie
7,5 x 18	RC30	35	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
	B32	35	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	51	215/45, 225/45			Kit mit Artikelnummer 98478
	Oxigin 25	45	ZP581	51-96	215/45			
8 x 18	B24	38	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
	B36 / B38	35	ZP581	51	215/45			Elektro, kurze Karosserie
	B42 / B44	40	ZP581	51	215/45			Elektro, kurze Karosserie

e-Citan Tourer NEU		2. Halbjahr 2022		MFK	5/114,3	66,1	e2*2018/858*000014*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 16	RC32	40	- (N7)	51-96	205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			 Orig.-Verschr., Ausführung N7
7 x 17	RC27	35+40	-	51	205/55, 215/50			Orig.-Verschr., Elektro
		38	ZP581	51	205/55, 215/50			Elektro
	B39	38	ZP581	51	205/55, 215/50			

	Pro1	45	-	51-96	205/55, 215/50, 225/45		Orig.-Verschr.
7,5 x 17	B24	38	ZP581	51	205/55, 215/50, 235/45		Elektro
7 x 18	RC27	34	-	51	225/45		Orig.-Verschr., Elektro
	B32	35	ZP581	51	225/45		Elektro
7,5 x 18	AC-MB6	35	Artikel Nr. 98478	51	225/45		Kit mit Artikelnummer 98478
	CA 20	40	ZP581	51-96	215/45, 225/40, 225/45		
8 x 18	B24	38	ZP581	51	225/45		Elektro
7,5 x 18	RC30	35	ZP581	51	225/45		Elektro

C-Klasse / Kombi		ab 2014	204/Model 205	5/112	66,6	Limo: e1*2001/116*0431*29-..., Kombi: e1*2001/116*0457*25-...	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC30	43	ZP568F	85-120	195/65, 205/60, 215/55, 215/60		nur Bremse max. 295mm
6,5 x 16	D17	38	-	85-155	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., auch Kombi, nicht Bremse 330mm und größer
				85-120	195/65		
	CA 20	45	ZP568F	85-120	195/65		incl. Facelift 2018, auch Kombi, ACHTUNG Bremsen siehe TÜV!
				85-155	205/60, 215/55, 215/60, 225/55		
6,5 x 17	D17	38+44	-	85-155	205/55, 215/50, 225/50		Orig.-Verschr., auch Kombi, ET38 nicht Bremse 342mm u. ET44 nur Bremse 305mm
	RC27	38	-	85-155	205/55, 215/50, 205/50		Orig.-Verschr., auch Kombi, nicht Bremse 330mm und größer VA u. nicht 342mm
7 x 17	D17	48,5	-	85-190	225/50		Orig.-Verschr., incl. Facelift 2018, auch Kombi
				85-155	205/55, 215/50		
	RC32	48,5	-	85-245	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/50		Orig.-Verschr., auch Kombi
	RC34	48,5	-	85-245	225/50		Orig.-Verschr., auch Kombi, nicht Bremse 318x30 u. 342x32mm
	RC27	47	ZP568F	85-155	205/55, 215/50		incl. Facelift 2018, nicht Bremse 342mm
				85-190	225/50		
	RC30	47	ZP568F	85-155	205/55, 215/50		incl. Facelift 2018, auch Kombi, nicht Bremse 318x28mm
				85-190	225/50		
	CA 26	47	ZP568F	85-155	205/55, 215/50		incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342mm
				85-190	225/50		
Pro1	49	F31	85-245	205/50, 205/55, 215/50, 215/55, 225/45, 225/50, 235/50		auch Kombi, nicht Bremse 295x24mm u. 305x28mm an VA u. 300x12mm HA	
7,5 x 18	RC30	44	-	85-180	225/45		Orig.-Verschr.
			-	85-155	215/45		
				85-190	225/45		Orig.-Verschr., incl. Facelift 2018
	RC32	44	-	85-245	215/45, 225/40, 225/45		Orig.-Verschr.
				85-190	225/45		
				85-155	215/45		
	B32	44	-	85-190	225/45		Orig.-Verschr., auch Kombi
				85-155	215/45		
				85-190	225/45		
	Oxigin 18	44	-	115-155	225/45		Orig.-Verschr.
	B39	35+45	ZP568F	85-155	215/45		auch Kombi, incl. Facelift 2018
				85-190	225/45		
AC-MB6	45	AV1	85-155	215/45		auch Kombi, incl. Facelift 2018	
			85-190	225/45			
8 x 18	D17	40	-	85-155	215/45		Orig.-Verschr., incl. Facelift 2018, auch Kombi u. Hybrid
				85-190	225/45		
	RC29	48	-	85-155	215/45		auch Kombi u. Hybrid
				85-190	225/45, 235/40		
	RC34	43	ZP568F	85-245	215/45, 225/40, 225/45		auch Kombi
				48	ZP568F	85-245	215/45, 225/40, 225/45, 235/40, 245/40
	B36	45	ZP568F	85-155	215/45		incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342 mm
				85-190	225/45, 235/40, 245/40		
	B37	48	-	85-155	215/45		Orig.-Verschr., incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342mm
				85-190	225/45, 235/40, 245/40		
	B38	45	ZP568F	85-155	215/45		incl. Facelift 2018, auch Kombi u. Hybrid
				85-190	225/45, 235/40, 245/40		
	B42	45	ZP568F	85-155	215/45		incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342mm
				85-190	225/45, 235/40, 245/40		
	B44	45	ZP568F	85-155	215/45		incl. Facelift 2018, auch Kombi
				85-190	225/45, 235/40, 245/40		
	AC-M10	40	AV1	85-155	215/45		incl. Facelift 2018, auch Kombi
85-190				225/45			
45		AV4	85-155	215/45		incl. Facelift 2018, auch Kombi	
			85-190	225/45, 235/40, 245/40			
AC-521	45	AV1	85-155	215/45		incl. Facelift 2018, auch Kombi	
			85-190	225/45, 235/40, 245/40			
FMI08 Thoe	49	F31	85-245	215/45, 225/40, 225/45, 235/40		auch Kombi	
FMI11 Elatha	39	F95	85-245	215/45			
	45	F95	85-245	215/45, 225/40, 225/45, 235/40			
7,5 x 19		44		85-245	VA 225/40+HA 225/35		Orig.-Verschr., auch Kombi u. Hybrid, beide ET's

8,5 x 19	RC32	52	-	85-245	VA 225/40+HA 245/35		ECE, Achtung! Bauart der Felgen ist unterschiedlich, die VA ist rund (nach außen gewölbt), die HA gerade, Kunden unbedingt darauf hinweisen!
7,5 x 19		44					
8,5 x 19		56,5					
7,5 x 19	RC32	49	-	85-245	225/35, 225/40		Orig.-Verschr.
	RC34	45,5	-	85-245	225/35, 225/40		Orig.-Verschr.
	B32	44	-	85-190	225/40		Orig.-Verschr.
	B39	43	ZP568F	85-180	225/40		
	Oxigin 18	50	ZP568F	85-245	225/40		
8 x 19	RC27	48	-	85-245	225/40		Orig.-Verschr., auch Kombi
	RC29	45	ZP568F	85-190	225/40, 235/35, 245/35		incl. Facelift 2018, auch Kombi
	RC34	43	ZP568F	85-245	225/35, 225/40		
		48	ZP568F	85-245	225/35, 225/40, 235/35		
		49	-	85-245	225/35, 225/40, 235/35		Orig.-Verschr., auch Kombi
	B24	45	ZP568F	85-180	225/40, 235/35, 245/35		auch Kombi, nicht Bremse 318 u. 342mm
	B38	39	-	85-180	225/40, 235/35, 245/35		Orig.-Verschr., auch Kombi, ab 235/35 ✖
		45	ZP568F	85-180	225/40, 235/35, 245/35		
	B40	43	ZP568F	85-190	225/40, 235/35		incl. Facelift 2018, auch Kombi
	B43	38	ZP568F	85-190	225/40		incl. Facelift 2018, auch Kombi
		43	ZP568F	85-190	225/40, 235/35		incl. Facelift 2018, auch Kombi
	AC-518	47	-	85-190	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2018, auch Kombi
8 x 20	FMI07 Atena	47	F95	85-245	225/35, 225/40, 235/35		
	Oxigin 29	43	ZP568F	85-190	225/40, 235/35		incl. Facelift 2018, auch Kombi
	B38	43,5+44	-	85-190	225/35, 245/30		Orig.-Verschr., incl. Facelift 2018, auch Kombi
		48	ZP568F	85-190	225/35		incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342mm
	B40	39	-	85-190	225/35		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	B43	39+48	ZP568F	85-190	225/35		incl. Facelift 2018, auch Kombi
	RC29	45	ZP568F	85-190	225/35, 235/30		incl. Facelift 2018, auch Kombi
	RC34	43	ZP568F	85-190	225/35, 235/30		
	B42	40	ZP568F	85-190	225/35		incl. Facelift 2018, auch Kombi
		45+48	ZP568F	85-190	225/35, 235/30		incl. Facelift 2018, auch Kombi, nicht Bremse 318 u. 342mm
8,5 x 20	B43	43	ZP568F	85-190	225/35, 235/30		incl. Facelift 2018, auch Kombi
	B44	40	ZP568F	85-190	225/35		incl. Facelift 2018, auch Kombi
	AC-518	45	AV1	85-190	225/35, 235/30		incl. Facelift 2018, auch Kombi
	AC-M10	40	AV1	85-190	225/35		incl. Facelift 2018, auch Kombi
	AF18	45	AV1	85-190	225/35, 235/30		incl. Facelift 2018, nicht Bremse 318 u. 342mm
	FMI12 Kari	50	F94	85-245	225/35		auch Kombi

weitere Dimensionen/Designs siehe Konfigurator

C-Klasse / Kombi 4-matic		ab 2014	204/Modell 205	5/112	66,6	Limo: e1*2001/116*0431*29-..., Kombi: e1*2001/116*0457*25-...	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	D17	48,5	-	125-245	225/50		Orig.-Verschr.
		44	-	125-245	225/50		Orig.-Verschr., incl. Facelift 2018
	RC27	47	ZP568F	125-245	225/50		incl. Facelift 2018
	RC30	47	ZP568F	125-245	225/50		
7,5 x 18	RC30	44	-	125-245	225/45		Orig.-Verschr.
			-	85-245	225/45		
	B32	44	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
	RC30	35+45	ZP568F	125-245	225/45		
	B32	42	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	B39	35+45	ZP568F	125-245	225/45		incl. Facelift 2018
	AC-MB6	45	AV1	125-245	225/45		incl. Facelift 2018
8 x 18	D17	40	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	RC29	48	-	125-245	225/45, 245/40		Orig.-Verschr.
	RC25	45	ZP568F	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018, auch Kombi
	B37	45	ZP568F	125-245	225/45, 235/40, 245/40HA		Kombi auch 215/45
	B38 / B44	45	ZP568F	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018, auch Kombi
	AC-M10	40	AV1	125-245	225/45		incl. Facelift 2018, auch Kombi
		45	AV4	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018, auch Kombi
	AC-518	42	-	125-245	225/45, 235/40		Orig.-Verschr., auch Kombi
		48	-	125-245	225/45, 245/40HA		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	AC-521	45	AV1	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018, auch Kombi
7,5 x 19	AF20	40	AV1	125-245	225/45		incl. Facelift 2018, auch Kombi
	B32	44	-	125-245	225/40		Orig.-Verschr., auch Kombi
	B39	43	ZP568F	125-245	225/40		auch Kombi
8 x 19	RC29	45	ZP568F	125-245	225/40, 235/35, 245/35		incl. Facelift 2018, auch Kombi
	B38	39	-	125-245	225/40, 235/35, 245/35		Orig.-Verschr., ab 235/35 ✖
		45	ZP568F	125-245	225/40, 235/35		
	B40	43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018, auch Kombi
	B43	38	ZP568F	125-245	225/40		incl. Facelift 2018, auch Kombi
		43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018, auch Kombi
	AC-518	38	-	125-245	225/40		Orig.-Verschr., incl. Facelift 2018, auch Kombi

		47	-	125-245	225/40, 245/35		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	Oxigin 29	43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018, auch Kombi
8,5 x 19	B32	45	ZP568F	125-245	225/40, 245/35HA, 255/35HA		auch Kombi, ab 245/35 ✖
	B37	45	ZP568F	125-245	225/40, 245/35HA, 255/35HA		
		43	ZP568F	125-245	225/40, 235/35, 245/35, 255/35		auch Kombi, ab 245/35 ✖
	B43	40	ZP568F	125-245	225/40		incl. Facelift 2018, auch Kombi
	B44	42	ZP568F	125-245	225/40		incl. Facelift 2018, auch Kombi
	AC-M10	45	AV4	125-245	225/40		incl. Facelift 2018, auch Kombi
	AF18 / AF20	40	AV1	125-245	225/40		incl. Facelift 2018, auch Kombi
	CA 23	45	ZP568F	125-245	225/40		incl. Facelift 2018, auch Kombi
8 x 20	Oxigin 28	40+45	ZP568F	125-245	225/40		incl. Facelift 2018, auch Kombi
	B38	43,5+44	-	125-245	225/35		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	B40	39	-	125-245	225/35		Orig.-Verschr., incl. Facelift 2018, auch Kombi
	B43	39+48	ZP568F	125-245	225/35		incl. Facelift 2018, auch Kombi
8,5 x 20	RC29	45	ZP568F	125-245	225/35, 235/30, 245/30, 255/30		ab 245/30 ✖
	RC34	43	ZP568F	85-190	225/35, 235/30		
	B42	40	ZP568F	125-245	225/35		incl. Facelift 2018, auch Kombi
	B43	43	ZP568F	125-245	225/35		incl. Facelift 2018, auch Kombi
	B44	40	ZP568F	125-245	225/35		incl. Facelift 2018, auch Kombi
	AC-518	45	AV1	125-245	225/35, 255/30HA		incl. Facelift 2018, HA ✖
	AC-M10	40	AV1	125-245	225/35		incl. Facelift 2018, auch Kombi

C-Klasse Plug-in-Hybrid NEU		204/Model 205 (WDD205...)			5/112	66,6	e1*2001/116*0431*35-...	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	D17	48,5	-	143, 155	225/50M+S		Orig.-Verschr.	
		44	-	143, 155	225/50M+S		Orig.-Verschr.	
	RC27 / RC30	47	ZP568F	143, 155	225/50M+S			
		RC34	44+48,5	-	143, 155	225/50M+S		Orig.-Verschr., ET48,5 Orig.-ET
7,5 x 18	RC30	44	-	143, 155	225/45M+S		Orig.-Verschr.	
	B32	44	-	143, 155	225/45M+S		Orig.-Verschr.	
	RC30	35	ZP568F	143, 155	225/45M+S			
		45	ZP568F	155	225/45M+S			
	B32	35+45	ZP568F	143, 155	225/45M+S			
		42	-	143, 155	225/45M+S		Orig.-Verschr.	
	AC-MB6	45	AV1	143, 155	225/45M+S			
	8 x 18	RC25	45	ZP568F	143, 155	225/45, 235/40M+S, 245/40		
RC29		45	ZP568F	143, 155	225/45, 235/40M+S, 245/40HA			
		48	-	143, 155	225/45, 235/40M+S, 245/40HA		Orig.-Verschr.	
B38 / B44		45	ZP568F	143, 155	225/45, 235/40, 245/40			
		40	AV1	143, 155	225/45			
AC-M10		45	AV4	143, 155	225/45, 235/40M+S, 245/40			
		AC-521	45	AV1	143, 155	225/45, 235/40, 245/40		
CA 23		45	ZP568F	143, 155	225/45, 235/40M+S, 245/40			
8,5 x 18	B32	48	ZP568F	143, 155	235/40			
7,5 x 19	B32	44	-	143, 155	225/40M+S		Orig.-Verschr.	
8 x 19	RC29	45	ZP568F	143, 155	VA 225/40+HA 245/35 od. VA+HA 245/35			
	B38	45	ZP568F	143, 155	VA 225/40+HA 245/35 od. VA+HA 245/35			
	B40	38+43	ZP568F	143, 155	225/40			
	B43	38+43	ZP568F	143, 155	225/40			
	Oxigin 29	43	ZP568F	143, 155	225/40			
8,5 x 19	B43	40	ZP568F	143, 155	225/40			
	B44	42	ZP568F	143, 155	225/40			
	AC-M10	45	AV4	143, 155	225/40			
	CA 23	45	ZP568F	143, 155	225/40			
	Oxigin 28	40+45	ZP568F	143, 155	225/40			
weitere Dimensionen/Designs siehe Konfigurator								

C-Klasse 4-Matic Plug-in-Hybrid NEU			Model 205 (WDD205...)		5/112	66,6	e1*2001/116*0431*53-...	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	D17	48,5	-	155	225/50M+S		Orig.-Verschr.	
		44	-	155	225/50M+S		Orig.-Verschr.	
	RC27 / RC30	47	ZP568F	155	225/50M+S			
	RC34	44+48,5	-	155	225/50M+S		Orig.-Verschr., ET48,5 Orig.-ET	
7,5 x 18	RC30	44	-	155	225/45M+S		Orig.-Verschr.	
	B32	44	-	155	225/45M+S		Orig.-Verschr.	
	RC30	45	ZP568F	155	225/45M+S			
		35+45	ZP568F	155	225/45M+S			
	B32	42	-	155	225/45M+S		Orig.-Verschr.	
		45	AV1	155	225/45M+S			
	RC25	45	ZP568F	155	225/45, 235/40M+S, 245/40HA			
RC29	45	ZP568F	155	225/45, 235/40M+S, 245/40HA				
	48	-	155	225/45, 245/40HA		Orig.-Verschr.		

8 x 18	B38 / B44	45	ZP568F	155	225/45, 235/40, 245/40		
	AC-M10	40	AV1	155	225/45		
		45	AV4	155	225/45, 235/40M+S, 245/40HA		
	AC-521	45	AV1	155	225/45, 235/40, 245/40HA		
	CA 23	45	ZP568F	155	225/45, 235/40M+S, 245/40		
7,5 x 19	B32	44	-	155	225/40M+S		Orig.-Verschr.
8 x 19	RC29	45	ZP568F	155	VA 225/40+HA 245/35		
	B38	45	ZP568F	155	VA 225/40+HA 245/35		
	B40	43	ZP568F	155	225/40		
	B43	38+43	ZP568F	155	225/40		
	Oxigin 29	43	ZP568F	155	225/40		
8,5 x 19	B43	40	ZP568F	155	225/40		
	B44	42	ZP568F	155	225/40		
	AC-M10	45	AV4	155	225/40		
	CA 23	45	ZP568F	155	225/40		
	Oxigin 28	40+45	ZP568F	155	225/40		

weitere Dimensionen/Designs siehe Konfigurator

C-Klasse T-Mod. Plug-in-Hybrid NEU	Model 205 (WDD205...)	5/112	66,6	e1*2001/116*0457*41...
Sensor - Brocksens 3				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	RC30	44	-	143, 155	225/45M+S		Orig.-Verschr.
	B32	44	-	143, 155	225/45M+S		Orig.-Verschr.
	RC30	45	ZP568F	143, 155	225/45M+S		
8 x 18	RC29	45	ZP568F	143	VA 225/45 , HA 245/40		nur M+S
				143, 155	225/45, 235/40		nur M+S
				155	VA 225/45, HA 245/40		
		48	-	143	VA 225/45 , HA 245/40		Orig.-Verschr., nur M+S
				143, 155	225/45, 235/40		Orig.-Verschr., nur M+S
				155	VA 225/45, HA 245/40		Orig.-Verschr.
	AC-521	45	AV1	143	VA 225/45 , HA 245/40		nur M+S
				143, 155	225/45, 235/40		nur M+S
				155	VA 225/45, HA 245/40		Orig.-Verschr.

Kombinationen

8 x 19	B40	43	ZP568F	143, 155	VA 225/40		
9 x 19		53			HA 255/35		

C-Klasse 43AMG	ab 2014	204/204K Modell 205	5/112	66,6	e1*2001/116*0431*36-.., e1*2001/116*0457*29-..
Sensor - Brocksens 3					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	B32	VA 33 HA 44	-	270	VA+HA 225/45		Orig.-Verschr., nur M+S
7,5 x 19	B32	VA 33	-	270	VA 225/40		Orig.-Verschr.
8,5 x 19		HA 52			HA 225/40M+S, 245/35, 255/35		

C-Klasse Coupé/Cabrio	2014	204/Modell 205	5/112	66,6	e1*2001/116*0431*37-..
Sensor - Brocksens 3					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	D17	48,5	-	115-180	225/50		Orig.-Verschr.
	RC32	48,5	-	115-245	225/45, 225/50, 235/50		Orig.-Verschr.
	RC27	47	ZP568F	110-190	225/50		incl. Facelift 2018, nicht Bremse 342mm
	RC30	47	ZP568F	110-190	225/50		nicht Bremse 318mm
	B39	47	ZP568F	110-190	225/50		incl. Facelift 2018, nicht Bremse 318 u. 342mm
7,5 x 17	RC24	42	ZP568F	110-190	225/50, 235/45		
	RC28	45	ZP568F	115-180	225/50, 235/45, 245/45		
	RC29	45	ZP568F	110-190	225/50, 235/45, 245/45		incl. FL2018, nicht Bremse 330 mm u. 342mm
	B36	45	ZP568F	110-190	225/50, 235/45, 245/45		incl. FL2018, nicht Bremse 330 mm u. 342mm
	AC-518	47	-	110-190	225/50, 235/45, 245/45		Orig.-Verschr., incl. Facelift 2018, nicht Bremse 318 u. 342mm
7,5 x 18	RC30	44	-	115-180	225/45		Orig.-Verschr.
				110-190	225/45		Orig.-Verschr., incl. Facelift 2018
	RC32	44	-	115-245	225/40, 225/45, 235/45		Orig.-Verschr.
	B32	44	-	110-190	225/45		Orig.-Verschr.
8 x 18	B39	35+45	ZP568F	110-190	225/45		incl. Facelift 2018
	D17	40	-	110-190	225/45		Orig.-Verschr., incl. Facelift 2018
	RC25	45	ZP568F	110-190	225/45, 235/40, 245/40		incl. Facelift 2018
	RC29	48	-	110-190	2255/45, 235/40		Orig.-Verschr.
	B24	48	ZP568F	115-155	225/45, 235/40, 245/40		nicht Bremse 318mm u. 342mm
	B37	48	-	110-190	225/45, 235/40, 245/40		Orig.-Verschr., incl. Facelift 2018, nicht Bremse 318 u. 342mm
	B38 / B44	45	ZP568F	110-190	225/45, 235/40, 245/40		incl. Facelift 2018

	AC-M10	40	AV1	110-190	225/45		incl. Facelift 2018
		45	AV4	110-190	225/45, 235/40, 245/40		incl. Facelift 2018
	AC-518	42+48	-	110-190	225/45, 235/40, 245/40HA		Orig.-Verschr., incl. Facelift 2018, ET48 nicht Bremse 318mm, ET42 bei 245/40 ✖
	AC-521	45	AV1	110-190	225/45, 235/40, 245/40		incl. Facelift 2018
7,5 x 19	AF20	40	AV1	110-190	225/45		incl. Facelift 2018
	B32	44	-	110-190	225/40		Orig.-Verschr.
	B39	43	ZP568F	115-180	225/40		
	Oxigin 18	50	ZP568F	115-180	225/40		
8 x 19	RC29	45	ZP568F	110-190	225/40, 235/35, 245/35		incl. Facelift 2018
	B24	45	ZP568F	110-190	225/40, 235/35, 245/35		incl. Facelift 2018, nicht Bremse 318 u. 342mm
	B38	45	ZP568F	110-190	225/40, 235/35, 245/35		incl. Facelift 2018
	B40	43	ZP568F	110-190	225/40, 235/35		incl. Facelift 2018
	B43	38	ZP568F	110-190	225/40		incl. Facelift 2018
		43	ZP568F	110-190	225/40, 235/35		incl. Facelift 2018
	AC-518	38	-	110-190	225/40		Orig.-Verschr., incl. Facelift 2018
		47	-	110-190	225/40, 235/35, 245/35		Orig.-Verschr., incl. Facelift 2018
	FMI07 Atena	39	F95				i.V.
	Oxigin 29	43	ZP568F	110-190	225/40, 235/35		incl. Facelift 2018
8,5 x 19	B32	45	ZP568F	115-180	225/40, 235/35, 245/35, 255/35		ab 245/35 ✖
	B36	45	ZP568F	110-190	225/40, 235/35, 245/35, 255/35		incl. Facelift 2018, nicht Bremse 318 u. 342mm, ab 245/35 ✖
	B37	48	-	115-180	225/40, 235/35, 245/35, 255/35		Orig.-Verschr., nicht Bremse 318 u. 342mm, bei 255/35 ✖
	B42	47	ZP568F	110-190	225/40, 235/35, 245/35, 255/35		incl. Facelift 2018, nicht Bremse 318 u. 342mm, ab 255/35 ✖
	B43	40	ZP568F	110-190	225/40		incl. Facelift 2018
	B44	42	ZP568F	110-190	225/40		incl. Facelift 2018
	AC-M10	45	AV4	110-190	225/40, 235/35		incl. Facelift 2018
	AF18 / AF20	40	AV1	110-190	225/40		incl. Facelift 2018
	CA 23	45	ZP568F	110-190	225/40, 235/35		incl. Facelift 2018, nicht Bremse 318mm
		40	ZP568F	110-190	225/40		incl. Facelift 2018
8 x 20	Oxigin 28	45	ZP568F	110-190	225/40, 235/35		incl. Facelift 2018
		43,5+44	-	110-190	225/35, 245/30		Orig.-Verschr., incl. Facelift 2018
	B38	48	ZP568F	110-190	225/35		incl. Facelift 2018, nur Bremse 320mm
		39	-	110-190	225/35		Orig.-Verschr., incl. Facelift 2018
	B40	39+48	ZP568F	110-190	225/35		incl. Facelift 2018
	B43	45	ZP568F	110-190	225/35, 235/30		incl. Facelift 2018
	B42	40	ZP568F	110-190	225/35		incl. Facelift 2018
		45+48	ZP568F	110-190	225/35, 235/30		incl. Facelift 2018, nicht Bremse 318 u. 342mm
	B43	43	ZP568F	110-190	225/35, 235/30		incl. Facelift 2018
	B44	40	ZP568F	110-190	225/35		incl. Facelift 2018
8,5 x 20	AC-518	45	AV1	110-190	225/35, 235/30		incl. Facelift 2018
	AF18	45	AV1	110-190	225/35, 235/30		incl. Facelift 2018, nicht Bremse 318 u. 342mm

C-Klasse Coupé/Cabrio 4matic		204/Modell 205		5/112	66,6	e1*2001/116*0431*37-..	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	D17	48,5	-	125-245	225/50		Orig.-Verschr.
		44	-	125-245	225/50		Orig.-Verschr., incl. Facelift 2018
	RC27	47	ZP568F	125-245	225/50		incl. Facelift 2018
7,5 x 17	RC24	42	ZP568F	125-245	225/50, 235/45, 245/45HA		bei 245/45 ✖
	RC28	45	ZP568F	125-245	225/50, 235/45, 245/45HA		
	AC-518	42	-	125-245	225/50, 235/45		Orig.-Verschr., incl. Facelift 2018
7,5 x 18	B32	44	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
	RC30	42	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
		44	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
	B32	42	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
	B39	35+45	ZP568F	125-245	225/45		incl. Facelift 2018
	D17	40	-	125-245	225/45		Orig.-Verschr., incl. Facelift 2018
8 x 18	RC25	45	ZP568F	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018
	RC29	48	-	125-245	225/45		Orig.-Verschr.
		45	ZP568F	125-245	225/45, 235/40, 245/40HA		
	B38 / B44	45	ZP568F	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018
	AC-M10	40	AV1	125-245	225/45		incl. Facelift 2018
		45	AV4	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018
	AC-518	42	-	125-245	225/45, 235/40		Orig.-Verschr., incl. Facelift 2018
		48	-	125-245	225/45, 245/40HA		Orig.-Verschr., incl. Facelift 2018
	AC-521	45	AV1	125-245	225/45, 235/40, 245/40HA		incl. Facelift 2018
	AF20	40	AV1	125-245	225/45		incl. Facelift 2018
7,5 x 19	B32	44	-	125-245	225/40		Orig.-Verschr.
	B39	43	ZP568F	125-245	225/40		
	RC29	45	ZP568F	125-245	225/40, 235/35, 245/35		incl. Facelift 2018
	B38	39	-	125-245	225/40, 235/35, 245/35		Orig.-Verschr., ab 235/35 ✖

8 x 19	B30	45	ZP568F	125-245	225/40, 235/35		
	B40	43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018
	B43	38	ZP568F	125-245	225/40		incl. Facelift 2018
		43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018
	AC-518	47	-	125-245	225/40, 245/35HA		Orig.-Verschr., incl. Facelift 2018
8,5 x 19	Oxigin 29	43	ZP568F	125-245	225/40, 235/35		incl. Facelift 2018
	B32	45	ZP568F	125-245	225/40, 245/35, 255/35		ab 245/35 ✖
	B37	43+45	ZP568F	125-245	225/40, 235/35, 245/35, 255/35		ab 245/35 ✖
	B43	40	ZP568F	125-245	225/40		incl. Facelift 2018
	B44	42	ZP568F	125-245	225/40		incl. Facelift 2018
	AC-M10	45	AV4	125-245	225/40		incl. Facelift 2018
	AF18 / AF20	40	AV1	125-245	225/40		incl. Facelift 2018
	CA 23	45	ZP568F	125-245	225/40		
8 x 20	Oxigin 28	40+45	ZP568F	125-245	225/40		incl. Facelift 2018
	B38	43,5+44	-	125-245	225/35		Orig.-Verschr., incl. Facelift 2018
	B40	39	-	125-245	225/35		Orig.-Verschr., incl. Facelift 2018
8,5 x 20	B43	39+48	ZP568F	125-245	225/35		incl. Facelift 2018
	B43	43	ZP568F	125-245	225/35		incl. Facelift 2018
	B44	40	ZP568F	125-245	225/35		incl. Facelift 2018
	AC-518	45	AV1	125-245	225/35, 255/30HA		incl. Facelift 2018, HA ✖

C-Klasse		Sommer 2021	R2CW / Modell 206		5/112	66,6	e1*2018/858*00016*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7 x 17	RC32	44,5	-	120-195	225/50			Orig.-Verschr., nicht 4-Kolben Festsattel mit 342x32mm
	D17	44	-	120-150	205/55, 215/50			Orig.-Verschr.
				120-195	225/50			
	RC27	34	-	120, 125	195/60			Orig.-Verschr., nur Bremse 342mm
				120-150	205/55			
		35	ZP568F	120, 125	195/60			nur Bremse 342mm
	RC30	35	ZP568F	125-150	205/55, 215/50			
				120, 125	195/60			
	RC32	44	-	120-195	205/55, 215/50, 225/50			Orig.-Verschr., nicht 4-Kolben Festsattel mit 342x32mm, auch für Hybrid
RC34	44	-	120-195	205/55, 215/50, 225/50			Orig.-Verschr., nicht 4-Kolben Festsattel mit 342x32mm, auch für Hybrid	
7,5 x 17	CA 26	42	ZP568F	120-150	205/55, 215/50			
				120-195	225/50			
	RC24	42	ZP568F	120-150	205/55, 215/50			
				120-195	225/50, 235/45, 245/45			
	RC34	36	ZP568F	120-195	205/55, 215/50			
40		ZP568F	120-195	205/55, 215/50			nur Fahrzeugausführ. ohne Hinterachslenkung	
7,5 x 18	8,5 x 18	VA 40 HA 52	-	120-195	VA 225/45			Orig.-Verschr.
					HA 245/40			
7,5 x 18	RC32	40	-	120-195	205/50, 215/45, 225/45			Orig.-Verschr., auch für Hybrid
	B32	40	-	125-195	225/45M+S			Orig.-Verschr., nur Bremse 342mm
				120-150	215/45			Orig.-Verschr.
	CA 20	40	ZP568F	120-195	225/45			auch für Mild-Hybrid
	RC30	42	-	120-150	215/45			Orig.-Verschr., nur Bremse 342mm
				120-195	225/45			
	RC32	42,5+ 44	-	125-195	205/50, 215/45, 225/45			Orig.-Verschr., auch für Hybrid, nur Fahrzeugausführungen ohne Hinterachslenkung
	RC34	40	-	120-195	205/50, 215/45, 225/45			Orig.-Verschr.
	B32	35+45	ZP568F	120-150	215/45			nur Bremse 342mm
				120-195	225/45			
	B39	35+45	ZP568F	120-150	215/45			nur Bremse 342mm
				120-195	225/45			
	AC-MB6	45	AV1	120-150	215/45			
				120-195	225/45			
	CA 20	40	ZP568F	120-195	205/50, 215/45, 225/45			
Oxigin 25	44	ZP568F	120-195	225/45, 235/45				
	D17	40	-	120-150	215/45			Orig.-Verschr.
				120-195	225/45			
	RC25	45	ZP568F	120-150	215/45			
				120-195	225/45, 235/40HA, 245/40HA			
	RC34	43	ZP568F	120-195	205/50, 215/45, 225/45			auch Hybrid
	B36 / B37	45	ZP568F	120-150	215/45			nur Bremse 342mm
				120-195	225/45, 235/40HA, 245/40HA			
	B42 / B44	45	ZP568F	120-150	215/45			
120-195				225/45, 235/40HA, 245/40HA				

8 x 18	AC-MB6 / AC-M10	45	AV4	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	AC-521	45	AV1	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	CA 17	45	ZP568F	120-195	225/45		
	CA 20 / CA 23	45	ZP568F	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	FMI08 Thoe	34	F31	120-195	215/45, 225/45		ohne Hinterachslenkung
					215/45		mit Hinterachslenkung
	FMI11 Elatha	39+45	F95	120-195	215/45, 225/45		
7,5 x 19	RC34	VA 40	-	120-195	VA 225/40		Orig.-Verschr.
9 x 19		HA 58,1			HA 255/35		
7,5 x 19	RC34	45,5	-	120-195	225/40		Orig.-Verschr.
8 x 19	RC29	45	ZP568F	120-195	225/40, 245/35HA		
	RC32	40	-	120-195	225/40, 235/35		Orig.-Verschr.
	RC34	43	ZP568F	120-195	225/40, 235/35		
	B40	43	ZP568F	120-150	235/35		
				120-195	225/40		
	B43	38	ZP568F	120-195	225/40		nur Bremse 342mm
		43	ZP568F	120-150	235/35		nur Bremse 342mm
				120-195	225/40		
8,5 x 19	Oxigin 29	43	ZP568F	120-150	235/35		
				120-195	225/40, 245/35HA		bei 245/35 ✖
	B41	39	ZP568F	120-195	225/40		
	B42	42	ZP568F	120-195	225/40		
	B43	40	ZP568F	120-195	225/40		nur Bremse 342mm
	B44	42	ZP568F	120-195	225/40		
	AC-M10	40	AV1	120-195	225/40		
	CA 26	40	ZP568F	120-195	225/40		
8 x 20	Oxigin 28	40	ZP568F	120-195	225/40		
	FMI08 Thoe	45	F31	120-195	225/35		
	RC29	40	ZP568F	120-150	225/35		nur Bremse 342mm
				120-190	225/35		
8,5 x 20	B24	42	ZP568F	120-150	225/35		nur Bremse 342mm
				120-190	225/35		
	AC-M10	40	AV1	120-190	225/35		

Kombinationen

7,5 x 18	RC32	40	F95	120-195	VA 225/45+HA 245/40		nur ABE, i.V.
8 x 18		49					
8 x 18	CA 17	43					
9 x 18		49					

C-Klasse T-Modell NEU Sommer 2021 R2CS / Modell 206 5/112 66,6 e1*2018/858*00017*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC32	44,5	-	120-195	225/50		Orig.-Verschr., nicht 4-Kolben Festsattel mit 342x32mm
	D17	44	-	120-150	205/55, 215/50		Orig.-Verschr.
				120-195	225/50		
	RC32	44	-	120-195	205/55, 215/50, 225/50		Orig.-Verschr., nicht 4-Kolben Festsattel mit 342x32mm, auch für Hybrid
	RC27	35	ZP568F	120-150	205/55, 215/50		nur Bremse 342mm
	RC30	35	ZP568F	120-150	205/55, 215/50		
	RC34	44	-	120-195	205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 342x32mm
7,5 x 17	CA 26	42	ZP568F	120-150	205/55, 215/50		
				120-195	225/50		
	RC24	42	ZP568F	120-150	205/55, 215/50		
				120-195	225/50, 235/45, 245/45		
	RC34	36	ZP568F	120-195	205/55, 215/50, 235/45		nur Fahrzeugausführ. ohne Hinterachslenkung
				120-195	205/50, 205/55, 215/45, 215/50, 225/45, 235/45		nur Fahrzeugausführungen mit Hinterachslenkung
		40	ZP568F	120-195	205/55, 215/50, 235/45		nur Fahrzeugausführ. ohne Hinterachslenkung
7,5 x 17				120-195	205/50, 205/55, 215/45, 215/50, 225/45, 225/50, 235/45, 245/45		nur Fahrzeugausführungen mit Hinterachslenkung
	B24	35	ZP568F	120-150	205/55		
7,5 x 18	RC34	VA 40	-	120-195	VA 225/45		Orig.-Verschr.
8,5 x 18		HA 52			HA 245/40		
	RC32	40	-	120-195	215/45, 225/45		Orig.-Verschr.,auch für Hybrid, Ausführung D4
	B32	40	-	147-195	225/45M+S		Orig.-Verschr., nur Bremse 342mm
				120-150	215/45		
				120-195	225/45		Orig.-Verschr.
	CA 20	40	ZP568F	120-195	225/45		auch für Mild-Hybrid
		40	ZP568F	120-195	215/45, 225/45		für Fahrzeugausführungen ohne Hinterachslenk.
				120-195	215/45, 225/40, 225/45		für Fahrzeugausführungen mit Hinterachslenk.

7,5 x 18	RC30	42	-	120-150	215/45		Orig.-Verschr., nur Bremse 342mm
		35+45	ZP568F	120-195	225/45		
				120-150	215/45		
	RC34	40	-	120-195	225/45		
				215/45, 225/45			
	B39	35+45	ZP568F	120-150	215/45		nur Bremse 342mm
				120-195	225/45		
8 x 18	AC-MB6	45	AV1	120-150	215/45		
				120-195	225/45		
	Oxigin 25	44	ZP568F	120-195	225/45, 235/45		
	D17	40	-	120-150	215/45		Orig.-Verschr.
				120-195	225/45		
	RC25	45	ZP568F	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	RC34	43	ZP568F	120-195	215/45, 225/45, 235/40		auch Hybrid
	B36 / B37	45	ZP568F	120-150	215/45		nur Bremse 342mm
				120-195	225/45, 235/40HA, 245/40HA		
	B40	43	ZP568F	147, 150	225/40, 235/35		nur Bremse 342mm
	B42 / B44	45	ZP568F	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
7,5 x 19	AC-MB6 / AC-M10	45	AV4	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	AC-521	45	AV1	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	CA 17	45	ZP568F	120-195	225/45		
	CA 20 / CA 23	45	ZP568F	120-150	215/45		
				120-195	225/45, 235/40HA, 245/40HA		
	FMI08 Thoe	34	F31	120-195	215/45, 225/45		ohne Hinterachslenkung mit Hinterachslenkung
					215/45		
7,5 x 19	RC34	VA 40 HA 58,1	-	120-195	VA 225/40		Orig.-Verschr.
					HA 255/35		
9 x 19	RC34	45,5	-	120-195	225/40		Orig.-Verschr.
8 x 19	RC29	45	ZP568F	120-150	225/40, 245/35HA		
	RC32	40	-	120-195	225/40, 235/35		Orig.-Verschr.
	RC34	43	ZP568F	120-195	225/40, 235/35		
	B38	45	ZP568F	120-150	225/40, 245/35HA		
	B40	43	ZP568F	120-150	225/40, 235/35, 245/35HA		nur Bremse 342mm, bei 245/35 ✖
		38	ZP568F	120-150	225/40		nur Bremse 342mm
	B43	43	ZP568F	120-150	225/40, 235/35		nur Bremse 342mm
		43	ZP568F	120-150	225/40, 235/35, 245/35HA		bei 245/35 ✖
8,5 x 19	Oxigin 29	43	ZP568F	120-150	225/40, 235/35, 245/35HA		
	B37	43	ZP568F	120-195	225/40		nur Bremse 342mm
	B41	39	ZP568F	120-195	225/40		
	B42 / B44	42	ZP568F	120-195	225/40		
	AC-M10	40	AV1	120-150	225/40		
	CA 26	40	ZP568F	120-150	225/40		
	Oxigin 28	40	ZP568F	120-195	225/40		

Kombinationen

7,5 x 18	RC32	40			VA 225/45+HA 245/40		nur ABE, i.V.
8 x 18		49					
8 x 18	CA 17	43	F95	120-195	VA 225/45+HA 245/40		
9 x 18		49					

C-Klasse C43 AMG NEU		R2CW /R2CS Modell 206		5/112	66,6	e1*2018/858*00016*..., e1*2018/858*00017*..	
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 19	RC32	43	-	300	245/35		Orig.-Verschr., Limousine u. Kombi
	RC34	45	-	300-310	235/40M+S, 245/35, 245/40		Orig.-Verschr., Limousine u. Kombi

C-Klasse Plug-in-Hybrid		NEU	2022	R2CW /R2CS Modell 206		5/112	66,6	e1*2018/858*00016*... e1*2018/858*00017*..	
Sensor - Brocksens 8									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
Kombinationen									
7,5 x 18	RC32	VA 40	- (D13)	145-185	VA 225/45			Orig.-Verschr., nur für Hybrid , nicht Bremse 330x22mm, Ausf. D13 , Typ R2CS nur bis 150kW	
9 x 18		HA 58			HA 255/40				

C-Klasse All Terrain		NEU	im Laufe 2023		R2CS	5/112	66,6	e1*2018/858*00017*..	
Sensor - Brocksens 8									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 17	RC27	44	-	147, 150	225/55				Orig.-Verschr.
	B24	35	ZP568F	147, 150	225/55				

7,5 x 18	RC30	42	-	147, 150	225/50, 235/45, 245/45		Orig.-Verschr.
		35	ZP568F	147, 150	225/50, 235/45, 245/45		
		45	ZP568F	147, 150	235/45		
	B32	33+40	-	147, 150	225/50, 235/45, 245/45		Orig.-Verschr.
		44	-	147, 150	235/45		Orig.-Verschr.
		45	ZP568F	147, 150	235/45		
	AC-MB6	45	AV1	147, 150	235/45		
8 x 18	Oxigin 25	44	ZP568F	147-150	245/45		
	RC27	41,1	-	147, 150	245/45		Orig.-Verschr.
	B24	35	ZP568F	147, 150	225/50, 235/45, 245/45		
	B36	35	ZP568F	147, 150	225/50, 235/45, 245/45		
		45	ZP568F	147, 150	235/45		
	B42	35	ZP568F	147, 150	225/50, 235/45, 245/45		
		45	ZP568F	147, 150	235/45		
	B44	35	ZP568F	147, 150	225/50, 235/45, 245/45		
		45	ZP568F	147, 150	235/45		
	AC-M10	40	AV1	147, 150	225/50, 235/45, 245/45		
		45	AV4	147, 150	235/45		
	AC-MB6	39	AV1	147, 150	225/50, 235/45, 245/45		
		45	ZP567F	147, 150	235/45		
	CA 20	45	ZP568F	147, 150	235/45		
	CA 23	39	-	147, 150	225/50, 235/45, 245/45		Orig.-Verschr.
		45	ZP568F	147, 150	235/45		
7,5 x 19	CA 26	32	ZP568F	147, 150	225/45		
8 x 19	B40	38	ZP568F	147, 150	225/45, 235/40, 245/40		
		43	ZP568F	147, 150	225/45, 235/40		
	CA 17	38+43	OX556F	147-150	225/45, 235/40		
	CA 24	38	-	147-150	225/45, 235/40		Orig.-Verschr.
		43	ZP568F	147-150	225/45, 235/40		
	Oxigin 29	32+43	ZP568F	147, 150	225/45, 235/40		
8,5 x 19	B32	34,5	ZP568F	147, 150	225/45, 235/40		
	B36 / B42	35	ZP568F	147, 150	225/45, 235/40		
	AC-M10	40	AV1	147, 150	225/45, 235/40		
	CA 26	40	ZP568F	147, 150	225/45, 235/40		
8 x 20	RC36	39	ZP568F	147, 150	245/35		
	B43	39	ZP568F	147, 150	245/35		

C43 AMG 4matic Coupé / Cabrio	204/ Modell 205	5/112	66,6	e1*2001/116*0431*39-... (FIN: WDD205...)
Sensor - Brocksens 3				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

Kombinationen

7,5 x 18	B32	VA 33 HA 44	-	270, 287	VA + HA 225/45		Orig.-Verschr., incl. Facelift 2018, nur M+S
7,5 x 19		VA 33 HA 52	-	270, 287	VA 225/40		Orig.-Verschr., incl. Facelift 2018
8,5 x 19	B40	VA 33 HA 52	-	270, 287	HA 245/35, 255/35		
8 x 19		VA 31	ZP568F	270, 287	VA + HA 225/40		incl. Facelift 2018
9 x 19		HA 49			HA 245/35, 255/35		

C450 / C43 AMG 4matic	204/204K Modell 205	5/112	66,6	e1*2001/116*0431*36-.., e1*2001/116*0457*29-.. (FIN: WDD205...)
Sensor - Brocksens 3				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

Kombinationen

7,5 x 18	B32	VA 33 HA 44	-	270, 287	VA + HA 225/45		Orig.-Verschr., incl. Facelift 2018, nur M+S
7,5 x 19		VA 33 HA 52	-	270, 287	VA 225/40		Orig.-Verschr., incl. Facelift 2018
8,5 x 19	B40	VA 33 HA 52	-	270, 287	HA 245/35, 255/35		
8 x 19		VA 31	ZP568F	270, 287	VA 225/40		incl. Facelift 2018
9 x 19		HA 49			HA 245/35, 255/35		

C 63 AMG	204, 204K, AMG / Model 205	5/112	66,6	e1*2001/116*0431*33-..., 0457*26-..., 0463*13-..., 0464*14-... (FIN: WDD205...)
Sensor - Brocksens 3				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

8,5 x 19	D17	VA 38 HA 54	-	350, 375	VA + HA 245/35 M+S		Orig.-Verschr.
	AC-M10	40	AV1	350, 375	245/35, 255/35		nur M+S
	AF18	40	AV1	350, 375	245/35, 255/35		nur M+S
9 x 20	B41	38	ZP568F	350-375	245/30		nur M+S

CLA			ab 2013	117 / 245G	5/112	66,6	e1*2007/46*1007*...., e1*2001/116*0470*04-..
Sensor - Brocksens 3							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

6,5 x 16	D17 RC32	49	-	80-130	205/55		Orig.-Verschr., Bremse max. 295mm
		49	-	80-135	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
6,5 x 17	D17	49	-	80-160	205/50M+S		Orig.-Verschr., nicht Bremse 295mm
	RC27	49	-	80-160	205/50M+S		Orig.-Verschr., auch Allrad, nicht Bremse 320mm
	RC34	49	-	80-155	205/50		Orig.-Verschr.
7,5 x 17	RC27	52,5	-	80-160	225/45		Orig.-Verschr.
7,5 x 18	B32	52	-	80-160	205/45, 215/40M+S, 225/40		Orig.-Verschr.
	B45	52	-	80-160	225/40		Orig.-Verschr., nur Bremse 295mm
8 x 18	RC27	48	-	155-265	235/40		Orig.-Verschr.
	RC29	48	-	80-160	225/40, 235/35, 235/40		Orig.-Verschr., ab 235/35 ✖
	RC34	48	ZP568F	155-160	235/40		nur Typ 245G
	B37	48	-	80-160	235/40		Orig.-Verschr., ab 235/35 ✖
8 x 19	RC27	48	-	155-280	235/35		Orig.-Verschr.

weitere Dimensionen/Designs siehe Konfigurator

CLA Shooting Brake		ab 2015	245G	5/112	66,6	e1*2001/116*0470*12-...	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	D17	49	-	80-135	205/55		Orig.-Verschr.
6,5 x 17	D17	49	-	80-160	205/50M+S		Orig.-Verschr., nicht Bremse 295mm
	RC27	49	-	80-160	205/50M+S		Orig.-Verschr., nicht Bremse 320mm
7,5 x 17	RC27	52,5	-	80-160	205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 18	B32	52	-	80-160	205/45, 215/40, 225/40		Orig.-Verschr.
	B45	52	-	80-160	225/40		Orig.-Verschr., nur Bremse 295mm
	RC27	48	-	155-265	235/40		Orig.-Verschr.
8 x 18	RC29	48	-	80-160	225/40, 235/35, 235/40		Orig.-Verschr.
	RC34	48	ZP568F	155-160	235/40		
	B37	48	-	80-160	235/40		Orig.-Verschr.
8 x 19	RC27	48	-	155-280	235/35		Orig.-Verschr.

weitere Dimensionen/Designs siehe Konfigurator

CLA 45 AMG 4matic	(siehe Konfigurator)	ab 2015	245G	5/112	66,6	e1*2007/46*1207*..., e1*2001/116*0470*04-...	
-------------------	----------------------	---------	------	-------	------	--	--

CLA 45 AMG 4matic Shooting Brake	(siehe Konfigurator)	245G	5/112	66,6	e1*2007/46*1207*..., e1*2001/116*0470*12-...		
----------------------------------	----------------------	------	-------	------	--	--	--

CLA		ab 2019	F2CLA	5/112	66,6	e1*2007/46*1912*... (FIN: WDD118...)	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	D17	44	-	85-120	205/60, 215/60, 225/55		Orig.-Verschr., auch Shooting Brake, Ausführung "D42"
		44,5	-	85-120	205/60, 215/60, 225/55		Orig.-Verschr., auch Shooting Brake, nicht Bremse 305mm, Ausführung "D4"
	RC32	44	-	85-120	205/60, 215/55		Orig.-Verschr.
	RC34	44	-	audi	205/60, 215/55		Orig.-Verschr.
	CA 20	44	-	85-120	205/60		Orig.-Verschr., auch Shooting Brake, nicht Bremse 305mm
	D17	49	-	85-120	205/60, 215/60, 225/55		Orig.-Verschr., nicht Bremse 305mm
	RC24	46	ZP568F	85-120	205/60, 215/60, 225/55		nicht Bremse 305mm, auch Shooting Brake
	RC30	46	ZP568F	85-120	205/60, 215/60, 225/55		nicht Bremse 305mm, auch Shooting Brake
	CA 20	45	ZP568F	85-120	205/60, 215/60, 225/55		nicht Bremse 305mm, auch Shooting Brake
6,5 x 17	D17	44	-	85-165	205/55, 215/50, 225/50		Orig.-Verschr., besser NICHT verkaufen, da Probleme mit Bremse und man das vorher nicht sagen kann!!! Falls doch, muss er ohne Montage vorher probieren - Innenkontur zu gering
	RC34	44	-	85-165	205/55		Orig.-Verschr.
	D17	49	-	85-165	205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330mm, incl. Shoot.
	RC27	46	-	85-165	205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 330mm, incl. Shoot.
7 x 17	D17	44+48,5	-	85-165	205/55, 215/50, 225/50		Orig.-Verschr., nicht Bremse 350mm, auch Shooting Brake, ET44 bei 225/50 ✖
	RC27	47	ZP568F	85-165	205/55, 215/50, 225/50		
	RC30	47	ZP568F	85-165	205/55, 215/50, 225/50		nicht Bremse 350mm, auch Shooting Brake
	RC32	44	-	85-165	205/50, 205/55		Orig.-Verschr., auch für Hybrid
		48,5	-	85-165	205/50, 205/55, 215/50, 225/50		Orig.-Verschr.
	RC34	44	-	85-165	205/50, 205/55		Orig.-Verschr.
	B24	47	ZP568F	85-165	205/55, 215/50, 235/45		auch Shooting Brake
	B39	47	ZP568F	85-165	205/55, 215/50, 225/50		nicht Bremse 350mm, auch Shooting Brake
	CA 26	47	ZP568F	85-165	205/55, 215/50, 225/50		nicht Bremse 350mm, auch Shooting Brake
Pro1	49	F31	85-165	205/50, 205/55, 215/50, 225/50			
7,5 x 17	RC24	42	ZP568F	85-165	205/55		nicht Bremse 350mm
	RC29	45	ZP568F	85-165	205/55		nicht Bremse 330 u. 350mm,auch Shooting Brake
	RC34	45	ZP568F	85-165	205/50, 205/55		
	AC-518	42	-	85-165	205/55		Orig.-Verschr., nicht Bremse 350mm
		47	-	85-165	205/55, 215/50, 235/45		Orig.-Verschr., nicht Bremse 350mm
	RC32	49	-	85-165	205/45, 215/45, 225/45		Orig.-Verschr., auch für Hybrid
	RC34	49	-	85-165	205/45, 215/45, 225/45		Orig.-Verschr.

7,5 x 18	B32	49	-	85-165	205/45, 215/45, 225/45		Orig.-Verschr., auch Shooting Brake
	Oxigin 25	49	-	85-165	215/45, 225/40, 225/45 , 235/45		Orig.-Verschr., Coupe u. Shooting Brake
	RC30	44	-	85-165	205/45, 215/45		Orig.-Verschr., auch Shooting Brake
		45	ZP568F	85-165	205/45, 215/45, 225/45		auch Shooting Brake
	RC32	42,5+44	-	85-165	205/45, 215/45		Orig.-Verschr.
	RC34	40	-	85-165	205/45		Orig.-Verschr.
	B32	42+44	-	85-165	205/45, 215/45		Orig.-Verschr., auch Shooting Brake
		45	ZP568F	85-165	205/45, 215/45, 225/45		auch Shooting Brake
	B39	45	ZP568F	85-165	205/45, 215/45, 225/45		nicht Plug in Hybrid, auch Shooting Brake
8 x 18	AC-MB6	45	AV1	85-165	205/45, 215/45, 225/45		
	CA 20	51	ZP568F	85-165	205/45, 215/45, 225/45		nicht Bremse 295x24 u. 330x30mm
	RC32	49	-	85-165	205/45, 215/45		Orig.-Verschr., ECE i.V.
	RC27	48	-	85-165	215/45, 225/40, 225/45		Orig.-Verschr.
	RC29	48	-	85-165	215/45, 225/45		Orig.-Verschr., auch Shooting Brake
	RC34	43	ZP568F	85-165	205/45, 215/45		auch Hybrid
		48	ZP568F	85-165	205/45, 215/45		auch Hybrid
	B24	48	ZP568F	85-165	215/45, 225/45		auch Shooting Brake
	B37	48	-	85-165	215/45, 225/45		Orig.-Verschr., auch Shooting Brake
	B38 / B42	45	ZP568F	85-165	215/45		
	B44	45	ZP568F	85-165	215/45		
	AC-518	42	-	85-165	215/45		Orig.-Verschr.
		48	-	85-165	215/45, 225/45		Orig.-Verschr.
	AC-M10	45	AV4	85-165	215/45		auch Shooting Brake
	CA 17	43	-	85-165	215/45		Orig.-Verschr.
7,5 x 19	FMI08 Thoe	49	F31	85-165	205/45, 215/45		auch Hybrid
	FMI11 Elatha	45	F95	85-165	205/45, 215/45		
7,5 x 19	RC32	49	-	85-165	225/35, 225/40		Orig.-Verschr.
	RC34	49	-	85-165	225/35, 225/40		Orig.-Verschr., auch Hybrid
		45,5	-	85-165	225/35		Orig.-Verschr.
8 x 19	RC27	48	-	85-165	225/40		Orig.-Verschr.
	RC34	48	ZP568F	85-165	225/35		
		49	-	85-165	225/35		Orig.-Verschr.
	FMI07 Atena	47	F95	85-165	225/35		
8 x 20	B38	48	ZP568F	85-165	225/30		auch Shooting Brake
	B43	48	ZP568F	85-165	225/30		auch Shooting Brake

CLA 35 AMG NEU		ab 2019		F2CLA	5/112	66,6	e1*2007/46*1912*... (FIN: WDD118...)	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	48	-	225	225/45M+S, 235/40			Orig.-Verschr., auch Shooting Brake
	RC32	49	-	225	225/40, 225/45, 235/40, 245/35, 245/40			Orig.-Verschr., 225er Reifen nur M+S
	FMI08 Thoe	49	F85	225	235/40			
	RC25	53	ZP568F	225	225/45M+S, 235/40, 245/40			auch Shooting Brake
	RC34	40	ZP568F	225	225/40, 225/45			nur M+S
		43	ZP568F	225	225/40, 225/45, 235/40			225er Reifen nur M+S
		48	ZP568F	225	225/40, 225/45, 235/40, 245/35, 245/40			225er Reifen nur M+S
	AC-MB6	45	ZP567F	225	225/45			nur M+S, auch Shooting Brake
	AC-518	42	-	225	225/45			Orig.-Verschr., nur M+S, auch Shooting Brake
8,5 x 18	AC-521	45	AV1	225	225/45			nur M+S, auch Shooting Brake
	B32	48	ZP568F	225	225/45M+S, 235/40			auch Shooting Brake
8 x 19	RC27	48	-	225	225/40			Orig.-Verschr., auch Shooting Brake, nur M+S
	RC34	43	ZP568F	225	235/35			auch Shooting Brake
		48	ZP568F	225	235/35, 245/30, 245/35			auch Shooting Brake
		49	-	225	235/35, 245/30, 245/35			Orig.-Verschr.
	B40 / B43	43	ZP568F	225	225/40			auch Shooting Brake, nur M+S
	FMI07 Atena	47	F95	225	235/35, 245/30, 245/35			
	Oxigin 29	43	ZP568F	225	225/40			auch Shooting Brake, nur M+S
8,5 x 19	B32	55,2	-	225	225/40M+S, 235/35, 245/35			Orig.-Verschr., auch Shooting Brake
9 x 19	B40	52	ZP568F	225	235/35			auch Shooting Brake
	FMI12 Kari	49	-	225	235/35			Orig.-Verschr.
8,5 x 20	FMI12 Kari	50	F94	225	245/30			

CLA 45 AMG/CLA AMG 45 S NEU			ab 2019	F2CLA	5/112	66,6	e1*2007/46*1912*... (FIN: WDD118...)
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC34	40+43	ZP568F	285-310	225/45, 235/40, 245/40		
		48	ZP568F	285-310	225/45, 235/40, 245/40		nicht 6-Kolben Festsattel mit 360x36mm
	FMI08 Thoe	34	F31	285-310	225/45M+S		nicht 6-Kolben Festsattel mit 360x36mm
	FMI11 Elatha	39	F95	285-310	225/45, 235/40, 245/40		nicht 6-Kolben Festsattel mit 360x36mm
8 x 19	RC32	40	-	285-310	225/40, 235/35		Orig.-Verschr., nur M+S
	RC34	49	-	285-310	225/40, 235/35, 245/35		Orig.-Verschr., nur M+S, nicht 6-Kolben Festsattel mit 360x36mm
	RC34	38	ZP568F	285-310	235/35		nur M+S
		43+48	ZP568F	285-310	225/40, 235/35, 245/35		ET48 nicht 6-Kolben Festsattel mit 360x36mm

	CA 24	43	ZP568F	285-310	245/35		
8,5 x 19	B41	39	ZP568F	285-310	235/35M+S		nicht 6-Kolben Festsattel mit 360x36mm
9 x 19	CA 24	49	ZP568F	285-310	245/35, 255/35		
	FMI12 Kari	49	-	285-310	225/40M+S, 235/35M+S, 245/35, 265/30		Orig.-Verschr.
8,5 x 20	RC34	38+43	ZP568F	285-310	225/35		
	FMI12 Kari	50	F94	285-310	245/30, 255/30		nicht 6-Kolben Festsattel mit 360x36mm

CLA 250e NEU	F2CLA	5/112	66,6	e1*2007/46*1912*... (FIN: WDD118...)
Sensor - Brocksens 1				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	D17	44	-	118	205/55, 215/50		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
		48,5	-	118	205/55, 215/50, 225/50		Orig.-Verschr., auch Shooting Brake, nicht Bremse 350mm
	RC27	47	ZP568F	118, 120	205/55, 215/50, 225/50		auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
	RC30	47	ZP568F	118	205/55, 215/50, 225/50		auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
	B39	47	ZP568F	118	205/55, 215/50, 225/50		auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
	CA 26	47	ZP568F	118, 120	205/55, 215/50, 225/50		auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
7,5 x 17	CA 20	47	ZP568F	118, 120	205/55, 215/50, 235/45		auch Shooting Brake u. Plug-in-Hybrid, nicht Bremse 350mm
7 x 18	RC27	46	-	118, 120	205/45, 215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
7,5 x 18	B32	49	-	118	205/45, 215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
	RC30	42	-	118, 120	205/45, 215/45		Orig.-Verschr., auch Shooting Brake, u. Plug-in-Hybrid
		44	-	118	205/45, 215/45		Orig.-Verschr., auch Shooting Brake, u. Plug-in-Hybrid
		45	ZP568F	118, 120	205/45, 215/45, 225/45		auch Shooting Brake, u. Plug-in-Hybrid
	B32	42	-	118	205/45, 215/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
		44	-	118, 120	205/45, 215/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
		45	ZP568F	118, 120	205/45, 215/45, 225/45		auch Shooting Brake u. Plug-in-Hybrid
	B39	45	ZP568F	118	205/45, 215/45, 225/45		auch Shooting Brake u. Plug-in-Hybrid
8 x 18	AC-MB6	45	AV1	118, 120	205/45, 215/45, 225/45		auch Shooting Brake u. Plug-in-Hybrid
	RC27	48	-	118	215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
	RC29	48	-	118	215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
	B24	48	ZP568F	118, 120	215/45, 225/45		auch Shooting Brake u. Plug-in-Hybrid
	B36	45	ZP568F	118, 120	215/45		auch Shooting Brake u. Plug-in-Hybrid
	B37	48	-	118, 120	215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
	B42 / B44	45	ZP568F	118, 120	215/45		auch Shooting Brake u. Plug-in-Hybrid
	AC-518	48	-	118	215/45, 225/45		Orig.-Verschr., auch Shooting Brake u. Plug-in-Hybrid
	AC-521	45	AV1	118	215/45		auch Plug-in-Hybrid
8,5 x 18	AC-M10	45	AV4	118, 120	215/45		auch Shooting Brake u. Plug-in-Hybrid
	B32	48	ZP568F	118	225/45, 235/40		auch Shooting Brake u. Plug-in-Hybrid, bei 235/40 

CLE NEU	im Laufe 2024			R2CLECA	5/112	66,6	e1*2018/858*00311*..
------------------------	---------------	--	--	---------	-------	------	----------------------

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	Serie	49,1			245/45		
	AC-MB6	39	AV1	120-190	245/45		nur Bremse 342mm
		45	ZP567F	120-190	245/45		nur Bremse 342mm
	CA 23	45	ZP568F	120-190	245/45		nur Bremse 342mm
8 x 20	RC36	39	ZP568F	120-190	245/35		

Kombinationen

8 x 18	Serie	VA 49,1			VA 245/45		
9 x 18		HA 60,5			HA 275/40		

CLE 300 e Coupe PHEV NEU		2024		R2CLECA	5/112	66,6	e1*2018/858*00311*..
---	--	------	--	---------	-------	------	----------------------

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 20	RC36	39	ZP568F	150	245/35		Plug-in Hybrid

CLS (siehe Konfigurator)		ab BJ2014		218	5/112	66,6	e1*2007/46*0485*...
---	--	-----------	--	-----	-------	------	---------------------

8 x 19	B40	VA 43	ZP568F	110-220	VA 225/40, 225/45, 235/40, 245/40		
9 x 19		HA 53			HA 245/40, 255/35, 255/40, 265/35, 275/35		
8 x 19		VA 43	ZP568F	110-220	VA 225/40, 225/45, 235/40, 245/40		
9 x 19		HA 49			HA 245/40, 255/35, 255/40, 265/35, 275/35		
8 x 19	RC27	43	-	110-270	245/40		Orig.-Verschr.
	RC32	43	-	110-270	215/45, 225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	B40	43	ZP568F	110-220	225/40, 225/45, 235/40, 245/35, 245/40		
	B43	43	ZP568F	110-220	225/40, 225/45, 235/40, 245/35, 245/40		nicht Bremse 360mm
	CA 17	43	OX556F	110-270	245/40		nicht Bremse 360mm
	CA 24	43	ZP568F	110-270	245/40		nicht Bremse 360mm
	Oxigin 29	43	ZP568F	110-220	225/40, 225/45, 235/40, 245/35, 245/40		
8 x 20	B40	VA 43	ZP568F	110-220	VA 235/35, 245/35		
9 x 20		HA 49+53			HA 235/35, 245/35, 265/30, 275/30		

weitere Dimensionen/Designs siehe Konfigurator

E-Klasse 4matic		ab 2015		212 (WDD213)	5/112	66,6	e1*2001/116*0501*24-...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	D17	40	-	120-143	225/50, 225/55 , 235/50, 245/50		Orig.-Verschr. für Alufelgen	
	RC27	40	-	120-145	225/55		Orig.-Verschr.	
8 x 18	D17	43	-	120-270	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr. für Alufelgen	
	RC27	43	-	110-270	235/45, 245/45		Orig.-Verschr.	
	RC32	43	-	110-270	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr.	
8 x 19	B40	VA 43	ZP568F	120-270	VA 245/40			
120-145				VA 225/40, 225/45, 235/40				
9 x 19		HA 53	120-270	HA 245/40, 255/35, 255/40, 265/35, 275/35				
8 x 19		VA 43	ZP568F	120-270	VA 225/40, 225/45, 235/40, 245/40			
9 x 19		HA 49		HA 275/35				
8 x 19	RC32	43	-	120-250	245/40		Orig.-Verschr., i.V.	
	B40	43	ZP568F	120-270	245/35, 245/40			
				120-145	225/40, 225/45, 235/40			
				120-220	245/40			
	Oxigin 29	43	ZP568F	120-145	225/40, 225/45, 235/40			
				120-270	245/35, 245/40			
8 x 20	B40	VA 43	ZP568F	120-270	VA 245/35			
		120-145		VA 235/35				
9 x 20		HA		120-270	HA 245/35, 275/30			
		49+53		120-145	HA 235/35, 265/30			

weitere Dimensionen/Designs siehe Konfigurator

E-Klasse Plug-in-Hybrid		NEU	ab 2020		212 (WDD213)	5/112	66,6	e1*2001/116*0501*28-... (FIN: WDD213...)	
Sensor - Brocksens 1									
Dimension		Design	ET	KIT	KW	Reifendimension		Info	
9 x 20	B43	44	ZP568F	143, 155	VA 245/35+HA 275/30			HA	✖
9,5 x 20	B42	42	ZP561F	143, 155	VA 245/35+HA 275/30				

Kombinationen

8 x 19	B40	43	ZP568F	143, 155	VA 245/40		
9 x 19		49+53			HA 275/35		
8 x 20	B40	43	ZP568F	143, 155	VA 245/35		
9 x 20		49+53			HA 275/30		

E-Klasse 4matic Plug-in-Hybrid			NEU	ab 2020	212 (WDD213)	5/112	66,6	e1*2001/116*0501*... (FIN: WDD213...)	
Sensor - Brocksens 1									
Dimension		ET	KIT	KW		Reifendimension		Info	
9 x 20	B43	44	ZP568F	143, 155	VA 245/35+HA 275/30			HA	✖
9,5 x 20	B42	42	ZP561F	143, 155	VA 245/35+HA 275/30				

Kombinationen

8 x 19	B40	43	ZP568F	143, 155	VA 245/40		
9 x 19		49+53			HA 275/35		
8 x 20	B40	43	ZP568F	143, 155	VA 245/35		
9 x 20		49+53			HA 275/30		

Lim. E43 AMG 4matic		212 (WDD213)		5/112		66,6		e1*2007/46*0501*27-..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 19	B40	20	ZP568F	295	VA 245/40				
9 x 19		HA 275/35							
8 x 20	B40	49	ZP568F	295	VA 245/35				
9 x 20		HA 275/30							

E63 / E63s AMG		ab 2020		212 (WDD213)	5/112	66,6	e1*2001/116*0501*25-... (FIN: WDD213...)
----------------	--	---------	--	--------------	-------	------	--

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
Kombinationen							
9,5 x 19	B32	VA 25	ZP561F	420, 450	VA + HA 265/40 M+S		
		HA 48					

E-Klasse T-Modell/T-Modell 4-maticab 09.16R1ES5/11266,6e1*2007/46*1560*... (WDD213)

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	D17	40	-	110-190	225/50, 225/55 , 235/50, 245/50		Orig.-Verschr. für Alufelgen
	RC27	40	-	110-210	225/50, 225/55 , 235/50, 245/50		Orig.-Verschr.
	RC32	40	-	110-245	225/50, 225/55 , 235/50		Orig.-Verschr., auch für Hybrid
	RC34	40	ZP568F	110-245	225/50, 225/55 , 235/50		
	RC24	35+42	ZP568F	110-190	225/50, 225/55, 235/50, 245/50		ET35 wenn 245/50 VA ✖
	RC28	35+45	ZP568F	110-190	225/50, 225/55, 235/50		
	RC29	35+45	ZP568F	110-210	225/50, 225/55, 235/50		ET45 nicht Bremse 330 u. 342mm
	B36	35	ZP568F	110-210	225/50, 225/55, 235/50, 245/50		ET35 wenn 245/50 VA ✖
		45	ZP568F	110-210	225/50, 225/55, 235/50, 245/50		nicht Bremse ab 330mm
7,5 x 18	AC-518	42	-	110-210	225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
	RC30	35+45	ZP568F	110-190	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm
	B32	35+45	ZP568F	110-210	225/45, 225/50, 235/45, 245/45		nicht Bremse 360mm
	B39	35+45	ZP568F	110-210	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm
	Oxigin 18	35	ZP568F	110-190	235/45, 245/45		nicht All Terrain ✖
8 x 18	RC32	VA 43	-	110-270	VA 245/45		Orig.-Verschr.
9 x 18		HA 49+52,5			HA 275/40		
8 x 18	D17	43	-	110-210	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr. für Alufelgen
	RC27	43	-	110-270	235/45, 245/45		Orig.-Verschr.
	RC32	43	-	110-270	235/45, 245/45		Orig.-Verschr.
	RC34	43	ZP568F	110-270	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		nicht 1-Kolben Faustsattel mit 360x26mm HA
	CA 17	43	OX556F	110-270	245/45		incl. Hybrid, nicht Bremse 360mm
	CA 24	43	OX556F	110-270	245/45		
	RC32	38	-	110-270	225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC29	35+45	ZP568F	110-210	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm
	B36	35+45	ZP568F	110-210	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm u. ET45 nicht 342mm
	B38	35+45	ZP568F	110-210	225/45, 225/50, 235/45, 245/40, 245/45		ET45 nicht Bremse 360mm
	AC-M10	40	AV1	110-210	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm
		45	AV4	110-195 110-270	225/45, 225/50, 235/45 245/40, 245/45		nicht Bremse 360mm
	AC-518	40	AV4	110-210	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm
		35+42	-	110-210	225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse 360mm
	AC-521	45	AV1	110-210	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm
	AC-522	35+40	AV1	110-210	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		ET40 nicht Bremse 360mm u. ET35 wenn 255/45 VA ✖
	AF18	35	AV1	110-210	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm
	FMI11 Elatha	45	F95	110-270	225/45, 225/50, 235/45, 245/45, 255/45		nicht 4-Kolben Festsattel mit 360x36mm u. 1-Kolben Faustsattel mit 360x26mm HA
8 x 19	B40	VA 43	ZP568F	110-210	VA 225/45, 235/40, 245/40		
9 x 19		HA 53			HA 245/40, 255/35, 255/40, 265/35, 275/35		
8 x 19		VA 43	ZP568F	110-210	VA 225/45, 235/40, 245/40		
9 x 19		HA 49			HA 245/40, 255/35, 255/40, 265/35, 275/35		
8 x 19	CA 19	VA 43	OX556F	110-270	VA 245/40+HA 275/35		nicht Bremse 360mm
9 x 19		HA 53					
8 x 19	RC27	43	-	110-270	245/40		Orig.-Verschr., nicht All Terrain
	RC32	43	-	110-270	245/40		Orig.-Verschr.
	B40	43	ZP568F	110-210	225/45, 235/40, 245/40		
		43	ZP568F	110-210	225/45, 235/40, 245/40		
	B43	43	ZP568F	110-195 110-270	225/45, 235/40		nicht Bremse 360mm
	CA 17	43	OX556F	110-270	245/40		nicht Bremse 360mm
	CA 19	43	OX556F	110-270	245/40		nicht Bremse 360mm
	CA 24	43	ZP568F	110-270	245/40		nicht Bremse 360mm
	Oxigin 29	43	ZP568F	110-270	245/40		
				110-195	225/45, 235/40		
				110-270	245/40		
	RC29	35+45	ZP568F	110-210	225/45, 235/40, 245/40		ET45 nicht Bremse 360mm
	RC32	32,5	-	110-270	225/45, 235/40		Orig.-Verschr.
	RC34	38+43	ZP568F	110-270	225/45, 235/40, 245/40		
	B24	35+45	ZP568F	110-190	225/45, 235/40, 245/40		ET45 nicht Bremse 342 u. 360mm
	B38	35+45	ZP568F	110-210	225/45, 235/40, 245/40		ET45 nicht Bremse 360mm
	B40	32,5	-	110-270	225/45, 235/40, 245/40		Orig.-Verschr.
		38	ZP568F	110-210	225/45, 235/40, 245/40		
	B43	32,5	-	110-210	225/45, 235/40		Orig.-Verschr.
				110-270	245/40		
		34+38+	ZP568F	110-210	225/45, 235/40		ET45 nicht Bremse 360mm

		45	ET 500	110-270	245/40		ET 500 nicht Bremse 360mm
	AC-518	38	-	110-210	225/45, 235/40, 245/40		Orig.-Verschr.
	AC-521	35	AV1	110-210	225/45, 235/40, 245/40		
	FMI07 Atena	39	F95	110-270	225/45, 235/40, 245/40		
8,5 x 19	D17	44	ZP561F	110-210	225/45, 235/40, 245/40, 255/35, 255/40HA		
	RC32	35,5	-	110-270	225/45, 235/40		Orig.-Verschr.
	B32	45	ZP568F	110-210	225/45, 235/40, 245/40, 255/35, 255/40		
	B36	35	ZP568F	110-190	225/45, 235/40, 245/40, 255/35, 255/40		nicht Bremse 342 u. 360mm, ab 255/35 ✖
	B37	43+45	ZP568F	110-190	225/45, 235/40, 245/40, 255/35, 255/40		nicht Bremse 360mm
	B41	36+39	ZP568F	110-270	225/45, 235/40		
	B42	35	ZP561F	110-210	225/45, 235/40, 245/40		nicht Bremse 360mm
				135-145	225/45, 235/40		4matic, nicht Bremse 360mm
				135-270	245/40		
	B43	40	ZP568F	110-195	225/45, 235/40		
				110-270	245/40, 255/35, 255/40		
	B44	42	ZP568F	110-195	225/45, 235/40		
				110-270	245/40, 255/35, 255/40		
	AF18	40	AV1	110-210	225/45, 235/40, 245/40, 255/35, 255/40		
	CA 20	45	ZP568F	110-210	225/45, 235/40, 245/40, 255/35, 255/40HA		nicht Bremse 342 u. 360mm VA u. nicht 320mm HA
	CA 23	40	-	110-195	225/45, 235/40		Orig.-Verschr.
				110-270	245/40, 255/35, 255/40		
		45	ZP568F	110-210	225/45, 235/40, 245/40, 255/35, 255/40HA		nicht Bremse 360mm
	FMI07 Atena	40	F95	110-270	225/45, 235/40, 245/40		
	Oxigin 18	45	ZP568F	110-210	225/45, 235/40, 245/40, 255/35, 255/40		nicht Bremse 342 u. 360mm
	Oxigin 28	40+45	ZP568F	110-195	225/45, 235/40		ET45 nicht Bremse 360mm
				110-270	245/40, 255/35, 255/40		
8 x 20	B40	VA 43	ZP568F	110-210	VA 235/35, 245/35		
9 x 20		HA 49+53			HA 245/35, 275/30		
8 x 20	B38	35	ZP568F	110-210	245/35		
	B43	39	ZP568F	110-270	245/35		
	FMI08 Thoe	45	F31	110-270	245/35		
8,5 x 20	RC29	40	ZP568F	110-190	245/35, 255/35		
		45	ZP568F	110-210	245/35		
	B32	40	ZP568F	110-210	245/35, 255/35		
	B42	40	ZP561F	110-210	245/35, 255/35		nicht Bremse 360mm
				135-270	245/35		4matic, nicht Bremse 360mm
		45	ZP561F	110-270	245/35		Achtung Bremsen! siehe TÜV!
	B43	40+43	ZP568F	110-270	245/35		
	B44	40	ZP561F	110-210	245/35, 255/35		nicht Bremse 360mm
				135-270	245/35		4matic, nicht Bremse 360mm
	AC-518	45	AV1	110-270	245/35		
	AC-M10	40	AV1	110-210	245/35, 255/35		
				135-270	245/35		4matic
9 x 20	AF18	45	AV1	110-210	245/35		nicht Bremse 342 u. 360mm
	AF18	40	AV1	110-210	235/35, 245/35		
	Oxigin 20	45	ZP568F	110-190	235/35, 245/35, 275/30		nicht Bremse 342 u. 360mm, bei 275/30 ✖

Kombinationen

8 x 18	CA 17	VA 43	OX556F	110-270	VA 245/45		nicht Bremse 360mm
9 x 18		HA 49			HA 275/40		
8 x 20	FMI08 Thoe	VA 45	F31	110-270	245/35		
9 x 20		HA 41					

E-Klasse T-Mod. Plug-in-Hybrid				2020	R1ES	5/112	66,6	e1*2007/46*1560*11-... (WDD213)	
Sensor - Brocksens 1									
Dimension		Design		ET	KIT	KW	Reifendimension		Info
Kombinationen									
8 x 19	B40		VA 43	ZP568F	143	VA 245/40			
HA 49			HA 275/35						

E-Klasse T-Mod. 4matic (PHEV)				2020	R1ES	5/112	66,6	e1*2007/46*1560*19-... (WDD213)	
Sensor - Brocksens 1									
Dimension		Design	ET	KIT	KW	Reifendimension		Info	
<u>Kombinationen</u>									
8 x 19	B40	VA 43	ZP568F	143	VA 245/40			Plug-in-Hybrid	
9 x 19		HA 49			HA 275/35				

E43 AMG 4matic T-Modell				2020	R1ES (WDD213..	5/112	66,6	e1*2007/46*1560*02-..... (WDD213)
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	B40	20	ZP568F	205	VA 245/40			

9 x 19	B40	49	ZP568F	295	HA 275/35		
8 x 20		20			VA 245/35		
9 x 20		49			HA 275/30		

E63 / E63S AMG T-Modell				R1ES	5/112	66,6	e1*2007/46*1560*04-.. (WDD213)
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 19	B40	VA 25 HA 52	-		VA+HA 265/40		Orig.-Verschr.

Kombinationen

9,5 x 19	B32	VA 25 HA 48	ZP561F	420, 450	VA + HA 265/40 M+S		nicht für Keramikbremse
----------	-----	----------------	--------	----------	--------------------	--	-------------------------

E-Klasse Coupé / Cabrio				ab Frühjahr 2017	R1EC	5/112	66,6	e1*2007/46*1666*..
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
7,5 x 17	D17	40	-	120-180	225/50, 225/55 , 235/50, 245/50		Orig.-Verschr. für Alufelgen	
	RC27	40	-	120-220	225/55		Orig.-Verschr.	
	RC32	40	-	120-220	225/55 , 235/50, 245/50		Orig.-Verschr., auch für Hybrid	
	RC34	40	ZP568F	120-220	225/55 , 235/50, 245/50			
	RC24	35+42	ZP568F	120-180	225/50, 225/55, 235/50, 245/50			
	RC28	35+45	ZP568F	120-180	225/50, 225/55, 235/50, 245/50			
	RC29	35+45	ZP568F	120-220	225/50, 225/55, 235/50, 245/50		ET45 nicht Bremse 330 u. 342mm	
7,5 x 18	AC-518	42	-	120-220	225/50, 225/55, 235/50, 245/50		Orig.-Verschr.	
	RC30	35+45	ZP568F	120-180	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm	
	RC32	44	-	120-220	225/50, 235/45, 245/45		Orig.-Verschr.	
	B32	35+45	ZP568F	120-180	225/45, 225/50, 235/45, 245/45		nicht Bremse 360mm	
	B39	35+45	ZP568F	120-220	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm	
8 x 18	RC32	43	-	120-270	VA 245/45+HA 275/40		Orig.-Verschr.	
9 x 18		49+52,5						
8 x 18	D17	43	-	120-220	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr. für Alufelgen	
	RC27	43	-	120-270	235/45, 245/45		Orig.-Verschr.	
	RC32	43	-	120-270	225/50, 235/45, 245/45 , 255/45		Orig.-Verschr.	
	RC34	43	ZP568F	120-220	225/50, 235/45, 245/45 , 255/45			
	CA 17	43	OX556F	120-270	245/45		Orig.-Verschr., nicht Bremse 360mm	
	CA 24	43	OX556F	120-270	245/45			
	RC29	35+45	ZP568F	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm	
	B36	45	ZP568F	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 342 u. 360mm	
	B38	35+45	ZP568F	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		ET45 nicht Bremse 360mm	
	B42	45	ZP568F	120-220	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 342 u. 360mm VA u. nicht 320mm HA	
	B44	45	ZP568F	120-220	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm	
	AC-M10	40	AV1	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm	
		45	AV4	120-220	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm	
	AC-518	35+42	F95	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm	
	AC-521	45	AV1	120-220	225/45, 225/50, 235/45, 245/40, 245/45		nicht Bremse 360mm	
	AF18	35+40	AV1	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm	
	AF20	28	AV1	120-220	225/45, 225/50, 235/45, 245/40, 245/45			
		35+40	AV1	120-220	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		nicht Bremse 360mm	
	FMI11 Elatha	45	F95	120-220	225/50, 235/45, 245/45, 255/45			
8 x 19	B40	43	ZP568F	120-220	VA 225/40, 225/45, 235/40, 245/35, 245/40			
9 x 19		49+53			HA 235/40, 245/35, 245/40, 255/35, 255/40, 265/35, 275/35			
8 x 19	CA 19	43	OX556F	120-270	VA 245/40+HA 275/35		nicht Bremse 360mm	
9 x 19		53						
8 x 19	RC27	43	-	120-270	245/40		Orig.-Verschr.	
	RC32	43	-	120-270	245/40		Orig.-Verschr.	
	RC34	43	ZP568F	120-220	225/45, 235/40, 245/35, 245/40			
	B40	43	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40			
	B43	43	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40		nicht Bremse 360mm	
	CA 17	43	OX556F	120-270	245/40		nicht Bremse 342 u. 360mm	
	CA 19	43	OX556F	120-270	245/40		nicht Bremse 360mm	
	CA 24	43	ZP568F	120-270	245/40		nicht Bremse 360 u. 370mm	
	Oxigin 29	43	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40			
	RC29	35+45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40		ET45 nicht Bremse 360mm	
	B24	35+45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40		ET45 nicht Bremse 342 u. 360mm	
	B38	35+45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40		ET45 nicht Bremse 360mm	
	AC-518	27+38	F95	120-220	225/40, 225/45, 235/40, 245/35, 245/40			
	AC-521	35	AV1	120-220	225/40, 225/45, 235/40, 245/35, 245/40			
	FMI07 Atena	39	F95	120-220	225/45, 235/40, 245/35, 245/40			
	D17	44	ZP568F	120-285	VA 235/35, HA 255/30			
	B32	45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40			

8,5 x 19	B36	35+45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		nicht Bremse 342 u. 360mm
	B37	45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		nicht Bremse 360mm
	B41	36+39	ZP568F	120-270	225/45, 235/40, 245/35, 245/40, 255/35, 255/40		
	B42	35+42	ZP561F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		ET35 nicht Bremse 360mm, ET42 nicht Bremse 342 u. 360mm
		40	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		
	B44	42	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		
	AC-M10	45	AV4	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		nicht Bremse 360mm
	AF18	40	AV1	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		
	AF20	30+40	AV1	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		ET30 ab 255/35 ✖
	CA 20	45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40HA		nicht Bremse 342 u. 360mm VA u. nicht 320mm HA
	CA 23	40	-	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		Orig.-Verschr.
		45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40HA		nicht Bremse 360mm
	FMI07 Atena	40	F95	120-270	225/45, 235/40, 245/35, 245/40, 255/35, 255/40		
	Oxigin 28	40+45	ZP568F	120-220	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		ET45 nicht Bremse 360mm
8 x 20	B38	35	ZP568F	120-220	235/35, 245/35		
	B43	27+30	ZP568F	120-220	235/35, 245/35		
		39	ZP568F	120-220	235/35, 245/35		
8,5 x 20	RC29	33	ZP568F	120-220	235/35, 245/35, 255/30, 255/35		
		40	ZP568F	120-180	235/35, 245/35, 255/30, 255/35		
		45	ZP568F	120-220	235/35, 245/35, 255/30		
	RC34	43	ZP568F	120-270	225/35, 235/35, 245/30, 245/35, 255/30, 255/35		
	B32	40	ZP568F	120-220	235/35, 245/35, 255/30, 255/35		
	B41	35	ZP568F	120-220	225/35, 235/35, 245/30, 245/35, 255/30, 255/35		
	B42	30	ZP561F	120-220	235/35, 245/35		
		35+40	ZP561F	120-220	235/35, 245/35, 255/30, 255/35		ET40 nicht Bremse 360mm
		45	ZP561F	120-220	235/35, 245/35, 255/30		nicht Bremse 342 u. 360mm
	B43	40+43	ZP568F	120-220	235/35, 245/35, 255/30		
	B44	30	ZP561F	120-220	235/35, 245/35		
		35+40	ZP561F	120-220	235/35, 245/35, 255/30, 255/35		ET40 nicht Bremse 360mm
	AC-518	45	AV1	120-220	235/35, 245/35, 255/30		
	AC-M10	40	AV1	120-220	235/35, 245/35, 255/30, 255/35		
	AF18	45	AV1	120-220	235/35, 245/35, 255/30		nicht Bremse 342 u. 360mm
	CA 17	43	OX556F	120-270	245/40		nicht Bremse 360mm
	FMI07 Atena	39	F95	120-270	225/35, 235/35, 245/30, 245/35, 255/30, 255/35		
9 x 20	B37	37	ZP568F	120-220	235/35, 245/35, 255/30, 255/35		
	B41	35	ZP568F	120-220	225/35, 235/35, 245/30, 245/35		
		38	ZP568F	120-220	225/35, 235/35, 245/30, 245/35, 255/30, 255/35		
	B43	33+35	ZP568F	120-220	235/35, 245/35		
	AF18	33	AV1	120-220	235/35, 245/35		
		40	AV1	120-220	235/35, 245/35, 255/30, 255/35, 265/30, 275/30		ET40 bei 275/30 ✖
	FMI07 Atena	33	F95	120-270	235/35, 245/30, 245/35		
8,5 x 21	B41	45	ZP568F	120-220	235/35, 245/35, 255/30, 265/30HA, 275/30HA		nicht Bremse 360mm
		30	ZP568F	120-270	245/30		
		34+37+40+43	ZP568F	120-270	245/30, 255/30		
	B43	30+43	ZP568F	120-220	245/30		
		34	ZP568F	120-220	245/30, 255/30		
9 x 21	B32	40	ZP568F	120-220	245/30		
	B43	36	ZP568F	120-220	245/30, 255/30		
	AF18	37	AV1	120-220	245/30, 255/30		

Kombinationen

8 x 18	CA 17	43	OX556F	120-270	VA 235/45, 245/45		nicht Bremse 360 u. 370mm
9 x 18		49			HA 275/40		
8 x 19	FMI08 Thoe	26	F31	120-220	VA+HA 235/40		
9 x 19		41					
8 x 20	B40	43	ZP568F	120-220	VA 235/35, 245/35		
9 x 20		49+53			HA 235/35, 245/35, 265/30, 275/30		

E-Klasse Coupé / Cabrio 4matic		ab 2017	R1EC	5/112	66,6	e1*2007/46*1666*..
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info

7,5 x 17	D17	40	-	135, 143	225/50, 225/55 , 235/50, 245/50		Orig.-Verschr. für Alufelgen	
	RC27	40	-	135, 143	225/55		Orig.-Verschr.	
	RC24	35+42	ZP568F	135, 143	225/50, 225/55, 235/50, 245/50			
	RC28	35+45	ZP568F	135, 143	225/50, 225/55, 235/50, 245/50			
	RC29	35+45	ZP568F	135, 143	225/50, 225/55, 235/50, 245/50		ET45 nicht Bremse 330 u. 342mm	
	AC-518	30	F95	135, 143	225/50, 225/55, 235/50			
42		-	135, 143	225/50, 225/55, 235/50, 245/50		Orig.-Verschr.		
7,5 x 18	RC30	35+45	ZP568F	135, 143	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm	
	B32	35+45	ZP568F	135, 143	225/45, 225/50, 235/45, 245/45		nicht Bremse 360mm	
	B39	35+45	ZP568F	135, 143	225/45, 225/50, 235/45, 245/45		ET45 nicht Bremse 360mm	
8 x 18	D17	43	-	135-270	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr. für Alufelgen	
	RC27	43	-	120-170	235/45, 245/45		Orig.-Verschr.	
	RC34	43	ZP568F	120-270	225/50, 235/45, 245/45 , 255/45		auch Hybrid, nicht Bremse 350 mm ab 220KW	
	RC29	35+45	ZP568F	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		nicht Bremse 360mm	
	B36	45	ZP568F	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		nicht Bremse 342 u. 360mm	
	B38	35+45	ZP568F	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		ET45 nicht Bremse 360mm	
	B42	45	ZP568F	135-195	225/45, 225/50, 235/45			
				135-270	245/40, 245/45		nicht Bremse 342 u. 360mm VA u. nicht 320mm HA	
	B44	45	ZP568F	135-195	225/45, 225/50, 235/45			
				135-270	245/40, 245/45		nicht Bremse 360mm	
	AC-M10	40	AV1	135-195	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		nicht Bremse 360mm	
		45	AV4	135-195	225/45, 225/50, 235/45		nicht Bremse 360mm	
	AC-518	35+42	-	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		Orig.-Verschr., nicht Bremse 360mm	
	AC-521	45	AV1	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45		nicht Bremse 360mm	
	AF18 / AF20	35+40	AV1	135, 143	225/45, 225/50, 235/45			
				135-270	245/40, 245/45, 255/45		nicht Bremse 360mm	
	8,5 x 18	B32	30	ZP568F	135, 143	225/45, 235/45		
	8 x 19	B40	43	ZP568F	135-270	VA 245/35, 245/40		
135, 143			VA 225/40, 225/45, 235/40					
49+53	135-270		HA 245/35, 245/40, 275/35					
9 x 19				135, 143	HA 235/40, 255/35, 255/40, 265/35			
8 x 19	RC32	43	-	135-245	245/40		Orig.-Verschr., i.V.	
	B40	43	ZP568F	135-270	245/35, 245/40			
				135, 143	225/40, 225/45, 235/40			
	B43	43	ZP568F	135-270	245/35, 245/40		nicht Bremse 360 mm	
				135, 143	225/40, 225/45, 235/40			
	Oxigin 29	43	ZP568F	135-270	245/40			
				135-195	225/40, 225/45, 235/40			
	RC29	35+45	ZP568F	135-270	245/35, 245/40			
				135, 143	225/40, 225/45, 235/40		ET45 nicht Bremse 360mm	
	B38	35+45	ZP568F	135, 143	225/40, 225/45, 235/40		ET45 nicht Bremse 360mm	
				135-270	245/35, 245/40			
	B40	32,5	-	135-195	225/40, 225/45, 235/40		Orig.-Verschr.	
				135-270	245/35, 245/40			
		31+38	ZP568F	135-195	225/40, 225/45, 235/40			
	B43	32,5	-	135, 143	225/40, 225/45, 235/40		Orig.-Verschr.	
				135-270	245/35, 245/40			
		34+38+45	ZP568F	135, 143	225/40, 225/45, 235/40		ET45 nicht Bremse 360mm	
AC-518	27+38	F95	135, 143	225/40, 225/45, 235/40				
			135-270	245/35, 245/40				
AC-521	35	AV1	135, 143	225/40, 225/45, 235/40				
			135-270	245/35, 245/40				
	RC25	38	-	135, 143	225/40, 225/45, 235/40		Orig.-Verschr. für Alufelgen	
				135-245	245/35, 245/40, 255/35, 255/40			
	B32	34,5+45	ZP568F	135, 143	225/40, 225/45, 235/40			
				135-270	245/35, 245/40, 255/35, 255/40			
	B36	35+45	ZP568F	135, 143	225/40, 225/45, 235/40		nicht Bremse 342 u. 360mm	
				135-270	245/35, 245/40, 255/35, 255/40			
	B37	35+43	ZP568F	135, 143	225/40, 225/45, 235/40			
				135-245	245/35, 245/40, 255/35, 255/40		ET43 nicht Bremse 360mm	
	B42	35+42	ZP561F	135, 143	225/40, 225/45, 235/40		ET35 nicht Bremse 360mm, ET42 nicht Bremse 342 u. 360mm	
				135-270	245/35, 245/40, 255/35, 255/40			
B43	40	ZP568F	135, 143	225/40, 225/45, 235/40				

8,5 x 19				135-270	245/35, 245/40, 255/35, 255/40		
	B44	42	ZP568F	135-195	225/40, 225/45, 235/40		
	AC-M10	45	AV4	135-270	245/35, 245/40, 255/35, 255/40		
				135-195	225/40, 225/45, 235/40		nicht Bremse 360mm
	AF18	40	AV1	135, 143	225/40, 225/45, 235/40		
				135-270	245/35, 245/40, 255/35, 255/40		
	AF20	30+40	AV1	135, 143	225/40, 225/45, 235/40		ET30 ab 255/35 ✖
				135-270	245/35, 245/40, 255/35, 255/40		
	CA 20	45	ZP568F	135, 143	225/40, 225/45, 235/40		nicht Bremse 360mm VA u. nicht Bremse 320mm HA
				135-270	245/35, 245/40, 255/35, 255/40HA		
CA 23	40	-	135-195	225/40, 225/45, 235/40		Orig.-Verschr.	
			135-270	245/35, 245/40, 255/35, 255/40			
	45	ZP568F	135-195	225/40, 225/45, 235/40		nicht Bremse 360mm	
			135-270	245/35, 245/40, 255/35, 255/40HA			
Oxigin 18	35+45	ZP568F	135, 143	225/40, 225/45, 235/40		nicht Bremse 342 u. 360mm	
			135-270	245/35, 245/40, 255/35, 255/40			
Oxigin 28	40+45	ZP568F	135-195	225/40, 225/45, 235/40		ET45 nicht Bremse 360mm	
			135-270	245/35, 245/40, 255/35, 255/40			
8 x 20	B38	35	ZP568F	135, 143	235/35		
				135-270	245/35		
	B43	27+30+39	ZP568F	135, 143	235/35		
				135-270	245/35		
8,5 x 20	RC29	40+45	ZP568F	135, 143	235/35		
				135-270	245/35, 255/30		
	B32	40	ZP568F	135, 143	235/35		
				135-270	245/35, 255/30		
	B42	35+40	ZP561F	135, 143	235/35		ET40 nicht 255/35 u. nicht Bremse 360mm
				135-270	245/35, 255/30, 255/35		
	45	ZP561F	135, 143	235/35		ET45 nicht Bremse 342 u. 360mm	
			135-270	245/35, 255/30			
	B43	40+43	ZP568F	135, 143	235/35		
				135-270	245/35, 255/30		
	B44	35+40	ZP568F	135-195	235/35		ET40 nicht Bremse 360mm
				135-270	245/35, 255/30		
AC-518	45	AV1	135, 143	235/35			
			135-270	245/35, 255/30			
AC-M10	40	AV1	135-195	235/35			
			135-270	245/35, 255/30			
AF18	45	AV1	135, 143	235/35		nicht Bremse 342 u. 360mm	
			135-270	245/35, 255/30			
9 x 20	B37	37	ZP568F	135, 143	235/35		
				135-270	245/35, 255/30, 255/35		
	B43	33+35	ZP568F	135, 143	235/35		
				135-270	245/35		
	AF18	40	AV1	135, 143	235/35, 265/30		bei 275/30 ✖
				135-270	245/35, 255/30, 275/30		
Oxigin 28	45	ZP568F	135, 143	235/35		nicht Bremse 360mm	
			135-270	245/35, 255/30, 265/30HA, 275/30HA			
9,5 x 20	B37C	38	ZP568F	135-245	245/35, 255/30, 255/35		nicht Bremse 360mm
	B42	42	ZP561F	135-270	245/35, 255/30, 275/30HA		bei 275/30 ✖
8,5 x 21	B43	30	ZP568F	135-270	245/30		
		34	ZP568F	135-270	245/30, 255/30		

Kombinationen

8 x 18	CA 17	43	OX556F	120-270	VA 235/45, 245/45		nicht Bremse 360 u. 370mm
9 x 18		49			HA 275/40		
8 x 20	B40	43	ZP568F	135, 143	VA 235/35		
9 x 20		49+53		135-270	VA 245/35		
				135, 143	HA 235/35, 265/30		
				135-270	HA 245/35, 275/30		

E-Klasse All Terrain 4matic			ab Frühj. 2017		R1ES	5/112	66,6	e1*2007/46*1560*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
	RC27	38	ZP563F	143-190	245/45			ACHTUNG!!! Kit ist nicht kostenlos, ist € 28,- netto	Preis
	RC32	38	ZP563F	143-250	245/40, 245/45			ACHTUNG!!! Kit ist nicht kostenlos, ist € 28,- netto	Preis
	RC34	38	ZP568F	143-250	245/40, 245/45				
	B40	38	ZP568F	143-250	245/45M+S				
	B43	38	ZP568F	143-250	245/45				
	CA 17	38	OX556F	143-250	245/45				
	CA 19	38	OX556F	143-250	245/45				

8 x 19	CA 24	38	OX556F	143-250	245/45		
	RC29	35	ZP568F	143-250	245/45		
	RC34	34	-	143-250	245/40		Orig.-Verschr.
	B24	35	ZP568F	143-250	245/45		
	B40	32,5	-	143-250	245/45		Orig.-Verschr.
	B43	32,5	-	143-250	245/45		Orig.-Verschr.
		34	ZP568F	143-250	245/45		
	AC-518	38	-	143-250	245/45		Orig.-Verschr.
	AC-521	35	AV1	143-250	245/45		
	FMI07 Atena	39	F95	143-250	245/40, 245/45		
8,5 x 19	Oxigin 29	32+39	ZP568F	143-250	245/45		
	RC25	38	-	143, 190	245/45, 255/40		Orig.-Verschr. für Alufelgen, nur M+S
	B41	39	ZP568F	143-250	245/40, 245/45		
	B43	40	ZP568F	143-250	245/45		
	AC-M10	40	AV1	143-250	245/45		
	AF18	40	AV1	143-250	245/45		
	CA 23	40	-	143-250	245/45		Orig.-Verschr.
	FMI07 Atena	40	F95	143-250	245/40, 245/45		
	Oxigin 20	40	ZP568F	143-190	245/45		nicht Bremse 342 u. 360mm
	Oxigin 28	40	ZP568F	143-250	245/45		
8,5 x 20	CA 19	40	OX556F	143-270	VA 245/40		incl. Hybrid, nicht Bremse 360mm
9,5 x 20		50			HA 275/35		
8 x 20	B38	35	ZP568F	143-250	245/40		
	B43	39	ZP568F	143-250	245/40		
8,5 x 20	RC34	43	ZP568F	110-270	245/35, 255/35		
	B32 / B43	40	ZP568F	143-250	245/40		
	B42	35+40	ZP568F	143-250	245/40		ET40 nicht Bremse 360mm
	B44	35+40	ZP568F	143-250	245/40		ET40 nicht Bremse 360mm
	AC-M10	40	AV1	143-250	245/40		
	CA 17 / CA 19	40	ZP568F	143-250	245/40		nicht Bremse 360mm
	FMI07 Atena	39	F95	143-250	245/35		
9 x 20	B37	37	ZP568F	143-250	245/40		

E-Klasse T-Modell NEU							
2024				R2ES (S214)	5/112	66,6	e1*2018/858*00214*..
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC32	32,5	-	120-280	225/55, 235/50		Orig.-Verschr.
	RC27	32,5	-	145, 150	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	RC34	30	ZP568F	120-280	225/55, 235/50		nicht Bremse 370x36mm VA u. 300x22mm HA
	AC-MB6	29	ZP567F	145, 150	225/55, 235/50, 255/45		nur Bremse 370mm
	FMI08 Thoe	34	F31	145-280	225/55, 235/50		nicht Bremse 370x36mm VA u. 300x22mm HA
8 x 19	RC32	32,5	-	145-280	225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
	RC34	30,5+32,5+34	-	120-280	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
		27+38	ZP568F	145-280	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	32,5+36	-	145, 150	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	CA 24	30	ZP569F	145-150	245/45		
	FMI08 Thoe	26	F31	145-280	225/50, 235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	FMI14 Jupiter	26	F31	145-280	225/50, 235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
8,5 x 19	B43	VA 30					i.V.
10 x 19		HA 48,1					
8,5 x 19	RC32	35,5	-	145-280	235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
	B41	35,5	-	145-280	245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
			ZP568F	120-280	235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	35,5	-	145, 150	245/45M+S		Orig.-Verschr., nur Bremse 370mm
	RC34	31,5	-	120-280	235/45, 245/45		Orig.-Verschr.
	B41	36	ZP568F	145-280	235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	CA 20	35	ZP568F	145, 150	235/45, 245/45, 255/40HA		nur Bremse 370mm
9 x 19	B40	30	-	145, 150	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145, 150	245/40, 255/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	B41	28	ZP568F	120-280	235/40		
9 x 20	B41	33	ZP568F	120-280	235/40, 245/40		nicht Bremse 370x36mm VA u. 300x22mm HA
		35	ZP568F	120-280	235/40		nicht Bremse 370x36mm VA u. 300x22mm HA
8,5 x 21	B41	34	ZP568F	145-280	245/35		nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	30	ZP568F	145-280	245/35		nur Bremse 370mm
9 x 21	FMI07 Atena	33	F95	145-280	245/35		zulässig für Bremse 370x36mm VA u. 300x22mm HA

Kombinationen

8 x 19	RC34	VA 32,5	-	120-280	VA 235/45, 245/45 od.		Orig.-Verschr., nicht Bremse 370x36mm VA u.
--------	------	---------	---	---------	-----------------------	--	---

9 x 19	B40	HA 30	-	145, 150	VA 245/45+HA 275/40		300x22mm HA
9 x 19		VA 30			VA 235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 255/40, 265/40, 275/40		
9 x 20	B43	VA 32 od. 34	-	145, 150	VA 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35, 285/35		
8,5 x 20	CA 17	VA 35	ZP561F	145-280	VA 245/40		
9,5 x 20		HA 50			HA 275/35		
8,5 x 21	B43	VA 34	ZP568F	145-280	VA 245/35		nur Bremse 370mm
9,5 x 21		HA 43			HA 275/30, 285/30		
8,5 x 21		VA 34	ZP568F	145, 150	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30, 285/30		
8,5 x 21	B41	VA 34	ZP568F	145-280	VA+HA 245/35 od.		nicht Bremse 370x36mm VA u. 300x22mm HA
10,5 x 21		HA 43			VA 245/35+HA 275/30, VA 245/35+HA 285/30		

E-Klasse T-Modell 4Matic NEU 2024 R2ES (S214) 5/112 66,6 e1*2018/858*00214*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	32,5	-	145-280	225/55		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	AC-MB6	29	ZP567F	145-280	225/55, 235/50, 245/50, 255/45		nur Bremse 370mm
8 x 19	B43	32,5+36	-	145-280	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 19	B43	35,5	-	145-280	245/45M+S		Orig.-Verschr., nur Bremse 370mm
	CA 20	35	ZP568F	145-280	235/45, 245/45, 255/40		nur Bremse 370mm
9 x 19	B40	30	-	145-280	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145-280	245/40, 255/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 20	RC36	32,1	-	145-280	245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm

Kombinationen

8,5 x 21	B43	VA 34	ZP568F	145-280	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30, 285/30		

E-Klasse T-Modell PHEV NEU 2024 R2ES (S214) 5/112 66,6 e1*2018/858*00214*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

Kombinationen

9 x 19	B40	VA 30	-	145, 150	VA 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40		
9 x 20	B43	VA 32 od. 34	-	145, 150	VA 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35, 285/35		
8,5 x 21	B43	VA 34	ZP568F	145, 150	VA 245/35		nur Bremse 370mm
9,5 x 21		HA 43			HA 285/30		
8,5 x 21		VA 34	ZP568F	145, 150	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 285/30		

E-Klasse T-Modell 4Matic PHEV NEU 2024 R2ES (S214) 5/112 66,6 e1*2018/858*00214*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 19	B43	35,5	-	145-280	245/45M+S		Orig.-Verschr., nur Bremse 370mm

Kombinationen

9 x 19	B40	VA 30	-	145	VA 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40		
9 x 20	B43	VA 32 od. 34	-	145	VA 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35, 285/35		
8,5 x 21	B43	VA 34	ZP568F	145	VA 245/35		nur Bremse 370mm
9,5 x 21		HA 43			HA 285/30		

E-Klasse All-Terrain NEU 2024 R2ES (S214) 5/112 66,6 e1*2018/858*00214*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

8 x 18	RC27	32,5	-	145-280	235/55, 245/50, 255/50		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	AC-MB6	29	ZP567F	145-280	235/55, 245/50, 255/50		nur Bremse 370mm
8 x 19	B43	32,5	-	145-280	235/50, 245/45, 255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	Oxigin 29	32	ZP568F	145-280	235/50, 245/45, 255/45		nur Bremse 370mm
8,5 x 19	B43	30	-	145-280	255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	CA 20	35	ZP568F	145-280	235/50, 245/45, 255/45		nur Bremse 370mm
8,5 x 19	B43	VA 30	-	145-280	VA 255/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 285/40		
8,5 x 19	B43	VA 30	-	145-280	VA 245/45, 255/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 275/40, 285/40		

9 x 19	B40	30	-	145-280	245/45, 255/45, 265/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145-280	245/40, 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9 x 20	RC36	32	-	145-280	VA+HA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
				145-280	245/40, 255/40, 265/35, 275/35HA		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	CA 23	30	ZP568F	145-280	245/40, 255/40		nur Bremse 370mm
9,5 x 20	RC36	32,1	-	145-280	245/40, 255/40, 265/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9 x 20	RC36	VA 32	-	145-280	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
9 x 20	B43	VA 32	-	145-280	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
8,5 x 21	B43	30	ZP568F	145-280	245/35, 255/35		nur Bremse 370mm

Kombinationen

9 x 19	B40	VA 30	-	145-280	VA 245/45, 255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40, 285/40		
9 x 20	B43	VA 32 od. 34	-	145-280	VA 245/40, 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35M+S, 285/35		
8,5 x 21	B43	VA 34	ZP568F	145-280	VA 245/35, 255/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30, 285/30		

E-Klasse All-Terrain PHEV		NEU	2024	R2ES (S214)	5/112	66,6	e1*2018/858*00214*..
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 19	B43	VA 30	-	145	VA 255/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 285/40		
9 x 20	RC36	VA 32	-	145	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
9 x 20	B43	VA 32	-	145	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
8,5 x 19	B43	VA 30	-	145	VA 245/45, 255/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 275/40, 285/40		

Kombinationen

8,5 x 19	B43	VA 31,5	-	145	VA 245/45M+S, 255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 19		HA 48,1			HA 275/40M+S, 285/40		
9 x 19	B40	VA 30	-	145	VA 245/45, 255/45		Orig.-Verschr. für Alufelgen, nur M+S, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40, 285/40		
9 x 20	B43	VA 32 od. 34	-	145	VA 245/40M+S, 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35M+S, 285/35		
8,5 x 21	B43	VA 34	ZP568F	145	VA 255/35		nur Bremse 370mm
10 x 21		HA 48			HA 285/30		

E-Klasse AMG E53 Hybrid		NEU	2024	R2ES (S214)	5/112	66,6	e1*2018/858*00214*..
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 21	B41	VA 22	ZP568F	330	VA 255/35+HA 285/30, VA 255/35+HA 295/30, VA 265/35+HA 295/30		
10,5 x 21		HA 43					

E-Klasse Limousine		NEU	2024	R2EW (W214)	5/112	66,6	e1*2018/858*00213*..
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	32,5	-	120-150	225/55, 235/50, 255/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	RC32	32,5	-	120-280	225/55, 235/50		Orig.-Verschr.
	RC34	30	ZP568F	120-280	225/55, 235/50		nicht Bremse 370x36mm VA u. 300x22mm HA
	B42	35	ZP568F	120-280	225/55, 235/50, 245/50, 255/45		nur Bremse 370mm
	B44	30+35	ZP568F	120-280	225/55, 235/50, 245/50, 255/45		nur Bremse 370mm, ET30 bei 245/50 ✖
	AC-MB6	29	ZP568F	120-150	225/55, 235/50, 255/45		nur Bremse 370mm
	FMI08 Thoe	34	F31	120-280	225/55, 235/50		nicht Bremse 370x36mm VA u. 300x22mm HA
8 x 19	RC32	32,5	-	120-280	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
	RC34	30,5+32,5+34	-	120-280	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
		27+38	ZP568F	120-280	225/50, 235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	32,5+36	-	120-150	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	CA 24	30	ZP569F	120-150	245/45		
	FMI08 Thoe	26	F31	120-280	225/50, 235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	FMI14 Jupiter	26	F31	120-280	225/50, 235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	Oxigin 29	32	ZP568F	120-280	235/45, 245/45		nur Bremse 370mm
	RC32	35,5	-	120-280	235/45, 245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA

8,5 x 19	B41	35,5	-	120-280	245/45		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA
			ZP568F	120-280	235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	35,5	-	120-150	245/45		Orig.-Verschr., nur Bremse 370mm
	RC34	31,5	-	120-280	235/45, 245/45		Orig.-Verschr.
	B36	30+35	ZP568F	120-280	235/45, 245/45, 255/40		nur Bremse 370mm
	B41	36	ZP568F	120-280	235/45, 245/45		nicht Bremse 370x36mm VA u. 300x22mm HA
	B44	30+35	ZP568F	120-280	235/45, 245/45, 255/40		nur Bremse 370mm
9 x 19	AC-M10	30	AV4	120-280	235/45, 245/45, 255/40		nur Bremse 370mm
	CA 20	35	ZP568F	120-150	235/45, 245/45, 255/40HA		nur Bremse 370mm
	B40	30	-	120-150	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	120-150	245/40, 255/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	B41	28	ZP568F	120-280	225/40, 235/40, 245/40		
9 x 20	B41	33	ZP568F	120-280	225/40, 235/40, 245/40		nicht Bremse 370x36mm VA u. 300x22mm HA
		35	ZP568F	120-280	225/40, 235/40		nicht Bremse 370x36mm VA u. 300x22mm HA
	CA 20	35	ZP568F	120-280	245/40, 255/35		nur Bremse 370mm
9,5 x 20	CA 17	35	ZP561F	120-280	245/40		
8,5 x 21	B41	30	ZP568F	120-280	245/35		
		34	ZP568F	120-280	245/35		nicht Bremse 370x36mm VA u. 300x22mm HA
	B43	30	ZP568F	120-280	245/35		nur Bremse 370mm, auch 4Matic
9 x 21	CA 20	30	ZP568F	120-280	245/35		nur Bremse 370mm
	FMI07 Atena	33	F95	120-280	245/35		zulässig für Bremse 370x36mm VA u. 300x22mm HA
9,5 x 21	B43	36	ZP568F	120-280	245/35, 275/30HA, 285/30HA		nur Bremse 370mm, ab 275/30 ✖

Kombinationen

8 x 19	RC34	VA 32,5	-	120-280	VA 235/45, 245/45 od.		Orig.-Verschr., nicht Bremse 370x36mm VA u. 300x22mm HA, bei HA 275/40 ✖
9 x 19		HA 30			VA 245/45+HA 275/40		
9 x 19	B40	VA 30	-	120-150	VA 235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 255/40, 265/40, 275/40		
8,5 x 20	CA 17	VA 35	ZP561F	120-280	VA 245/40		
9,5 x 20		HA 50			HA 275/35		
8,5 x 21	B41	VA 34	ZP568F	120-280	VA+HA 245/35 od.		nicht Bremse 370x36mm VA u. 300x22mm HA, bei 285/30 ✖
10,5 x 21		HA 43			VA 245/35+HA 275/30, VA 245/35+HA 285/30		
8,5 x 21	B43	VA 34	ZP568F	120-280	VA 245/35		nur Bremse 370mm, HA ✖
9,5 x 21		HA 43			HA 275/30, 285/30		
8,5 x 21		VA 34	ZP568F	120-150	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30		
9 x 21		VA 34	ZP568F	120-280	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30		

E-Klasse 4Matic NEU		2024	R2EW (W214)	5/112	66,6	e1*2018/858*00213*..	
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	32,5	-	145-280	225/55		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
					225/55, 235/50, 245/50, 255/45		
	AC-MB6	29	ZP567F	145-280	225/55, 235/50, 255/45		nur Bremse 370mm
8 x 19	B43	32,5+36	-	145-280	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 19	B43	35,5	-	145-280	245/45M+S		Orig.-Verschr., nur Bremse 370mm
	CA 20	35	ZP568F	145-280	235/45, 245/45, 255/40		nur Bremse 370mm
9 x 19	B40	30	-	145-280	235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145-280	245/40, 255/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 20	RC36	32,1	-	145-280	245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm

Kombinationen

9 x 19	B40	VA 30	-	145-280	VA 235/45, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 255/40, 265/40, 275/40		
8,5 x 21	B43	VA 34	ZP568F	145-280	VA 245/35		nur Bremse 370mm
10 x 21		HA 48			HA 275/30		

E-Klasse PHEV NEU		2024	R2EW (W214)		5/112	66,6	e1*2018/858*00213*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	B43	35,5	-	145, 150	245/45M+S			Orig.-Verschr., nur Bremse 370mm
	CA 20	35	ZP568F	145, 150	245/45M+S			nur Bremse 370mm
9 x 19	B40	30	-	145, 150	245/45M+S			Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145, 150	255/35			Orig.-Verschr. für Alufelgen, nur Bremse 370mm

Kombinationen

9 x 19	B40	VA 30	-	145, 150	VA 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40		
9 x 20	B43	VA 32 od. 34	-	145, 150	VA 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35		

8,5 x 21	B43	VA 34	ZP568F	145, 150	VA 245/35		nur Bremse 370mm, HA ✖
9,5 x 21		HA 43			HA 285/30		

E-Klasse 4Matic PHEV NEU		2024	R2EW (W214)	5/112	66,6	e1*2018/858*00213*..	
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 19	B43	35,5	-	145-185	245/45M+S		Orig.-Verschr., nur Bremse 370mm
	CA 20	35	ZP568F	145-185	245/45, 255/40		nur M+S, nur Bremse 370mm
9 x 19	B40	30	-	145-185	245/45M+S		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
8,5 x 20	RC36	33	-	145-185	255/35		Orig.-Verschr. für Alufelgen, nur Bremse 370mm

Kombinationen

9 x 19	B40	VA 30	-	145-185	VA 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
9,5 x 19		HA 52			HA 275/40		
9 x 20	B43	VA 32 od. 34	-	145-185	VA 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 275/35		
8,5 x 21	B43	VA 34	ZP568F	145-185	VA 245/35		nur Bremse 370mm, HA ✖
9,5 x 21		HA 43			HA 285/30		

E-Klasse AMG E53 Hybrid		NEU	2024		R2EW (W214)	5/112	66,6	e1*2018/858*00213*..	
Sensor - Brocksens 8									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
Kombinationen									
9,5 x 21	B41	VA 22	ZP568F	330	VA 255/35+HA 285/30, VA 255/35+HA 295/30, VA 265/35+HA 295/30				
10,5 x 21		HA 43							

EQA		2. Quartal 2021		F2B	5/112	66,6	e1*2007/46*1909*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 18	RC34	44,5	-	80-139	215/60		Orig.-Verschr., Ausführung D13	
7,5 x 18	RC32	53,5	-	80-139	225/55M+S, 235/55		Orig.-Verschr.	
	RC30	45	ZP568F	80-139	215/60, 225/55		nur M+S	
				95	215/60, 225/55			
	RC32	42,5+44	ZP564F	80-139	215/60M+S			
		49	ZP564F	80-139	215/60M+S, 225/55M+S, 235/55			
	B32	45	ZP561F	80-139	215/60, 225/55		nur M+S	
	B39	45	ZP561F	80 (140)	215/60, 225/55		nur M+S	
	AC-MB6	45	AV1	80-139	215/60, 225/55		nur M+S	
	AC-V51	50	ZP564F	80-139	225/55M+S, 235/55		nicht Bremse 350mm	
CA 20	51	ZP568F	80-139	225/55, 235/55		nicht Bremse 330x30mm		
	Oxigin 25	51+52	-	80-139	235/55		Orig.-Verschr.	
8 x 18	RC25	53	ZP561F	80-139	215/60M+S, 225/55M+S, 235/55			
	RC34	48	ZP568F	80-139	225/55M+S			
	B24	48	ZP561F	80-139	215/60M+S, 225/55M+S			
				95	215/60, 225/55			
	B36 / B42 / B44	45	ZP561F	80-139	215/60M+S			
				95	215/60			
	AC-518	48	AV1	80 (140)	215/60, 225/55		nur M+S	
	AC-521	45	AV1	80-139	215/60		nur M+S	
	AC-M10	45	AV4	80-139	215/60		nur M+S	
	AC-V51	52	AV1	80-139	225/55, 235/55		nicht Bremse 350mm	
CA 23	45	ZP568F	80-139	215/60		nur M+S		
	FMI08 Thoe	49	F31	80-139	225/55		nur M+S	
7,5 x 19	RC32	53,5	ZP564F	80-139	235/45, 235/50, 245/45			
	RC34	53,5	-	80-139	235/45, 235/50, 245/45		Orig.-Verschr., max. Achslast bis 1390 kg	
	B32	53,5	-	80-139	235/50, 245/45		Orig.-Verschr.	
	RC32	49+53	-	80-139	225/50, 235/45, 235/50, 245/45		Orig.-Verschr.	
	RC34	45,5	-	80-139	235/45, 245/45		Orig.-Verschr.	
8 x 19	RC34	45	ZP568F	80-139	235/45			
		48	ZP568F	80-139	235/45, 245/45			
	AC-518	47	AV1	80 (140)	225/50M+S, 245/45			
	FMI08 Thoe	47	F31	80-139	235/45			
8,5 x 19	RC32	47,5	-	80-139	235/45		Orig.-Verschr.	
	RC34	47,5	-	80-139	235/45		Orig.-Verschr., nicht Bremse 330x30mm	
8 x 20	B38	48	ZP561F	80-139	215/45M+S, 235/45, 245/40			
	B40	43	ZP561F	80-139	215/45M+S, 235/45			
	B43	39	ZP568F	80-139	215/45M+S			
				95	215/45			
		48	ZP568F	80-139	215/45M+S, 235/45, 245/40			
	FMI08 Thoe	45	F31	80-139	235/40			
8,5 x 20	B43	50,5	-	80-139	235/45, 245/40		Orig.-Verschr.	
	B42	48	ZP561F	80-139	235/45			
	FMI12 Kari	50	F94	80-139	235/40, 235/45			

9 x 20	B40	49	ZP561F	80-139	235/45		
	B43	50	-	80-139	235/45		Orig.-Verschr. für Alufelgen

EQB							
2. Quartal 2021				F2B	5/112	66,6	e1*2007/46*1909*12-..
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 18	RC34	44,5	-	80-139	215/60		Orig.-Verschr., Ausführung D13
7,5 x 18	RC32	53,5	-	80-139	225/55M+S, 235/55		Orig.-Verschr.
	RC30	45	ZP561F	95-139	215/60M+S, 225/55M+S		
	B32	45	ZP561F	95-139	215/60M+S, 225/55M+S		
	AC-MB6	45	AV1	95-139	215/60M+S, 225/55M+S		
	AC-V51	50	ZP564F	95-139	225/55M+S, 235/55		nicht Bremse 350mm
	CA 20	51	ZP568F	80-139	225/55, 235/55		nicht Bremse 330x30mm
8 x 18	RC25	53	ZP561F	111, 139	215/60M+S, 225/55M+S, 235/55		
	B24	48	ZP561F	95-139	215/60M+S, 225/55M+S		
	B36 / B42 / B44	45	ZP561F	95-139	215/60		nur M+S
	AC-521	45	AV1	111, 139	215/60		nur M+S
	AC-M10	45	AV4	95-139	215/60		nur M+S
	AC-V51	52	AV1	95-139	225/55M+S, 235/55		nicht Bremse 350mm
7,5 x 19	CA 20 / CA 23	45	ZP568F	95-139	215/60		nur M+S
	RC32	53,5	ZP564F	80-139	225/50, 235/45, 235/50, 245/45		
	RC34	53,5	-	80-139	235/45, 235/50, 245/45		Orig.-Verschr., max Achslast bis 1390 kg
	B32	53,5	-	111, 139	235/50, 245/45		Orig.-Verschr.
	RC32	49+53	-	80-139	225/50, 235/45, 235/50, 245/45		Orig.-Verschr.
8 x 19	RC34	45	ZP568F	80-139	235/45		
	FMI08 Thoe	47	F31	80-139	235/45		
8,5 x 19	RC32	47,5	-	80-139	235/45		Orig.-Verschr.
	RC34	47,5	-	80-139	235/45		Orig.-Verschr., nicht Bremse 330x30mm
8 x 20	B38	48	ZP561F	111	215/45M+S		
				111, 139	235/45, 245/40		
	B40	43	ZP561F	111	215/45M+S		
				111, 139	235/45		
	B43	39	ZP568F	111	215/45M+S		
		48	ZP568F	111	215/45M+S		
8,5 x 20	B43	50,5	-	111, 139	235/45, 245/40		Orig.-Verschr.
	B42	48	ZP561F	111, 139	235/45		
	FMI12 Kari	50	F94	80-139	235/40, 235/45		
9 x 20	B40	49	ZP561F	111, 139	235/45		
	B43	50	-	95-139	235/45		Orig.-Verschr. für Alufelgen

EQC							
ab 07.2019				204X	5/112	66,6	e1*2001/116*0480*..
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 19	RC32	32	-	145	VA 235/55		Orig.-Verschr., Ausführung "D14"
8 x 19		34			HA 255/50		
8 x 19	RC32	34	-	145	VA+HA 235/55		Orig.-Verschr., Ausführung "D14"
					VA 235/55+HA 255/50		
	RC34	34	-	145	VA+HA 235/55		Orig.-Verschr.
					VA+HA 235/55 od.		Orig.-Verschr.
	RC32	32,5	-	145	VA 235/55+HA 255/50		Orig.-Verschr.
					VA+HA 235/55 od.		Orig.-Verschr.
8,5 x 19	RC34	30,5+	-	145	VA 235/55+HA 255/50		Orig.-Verschr.
		32,5			VA 235/55+HA 255/50		Orig.-Verschr.
	RC32	27	ZP568F	145	VA 235/55+HA 255/50		VA ✖
		35,5	-	145	VA+HA 235/55 od.		Orig.-Verschr.
		35,5+36			VA 235/55+HA 255/50		ET28 VA ✖
8,5 x 20	B41	28	ZP568F	145	VA 235/55+HA 255/50		VA ✖
		35,5+36	ZP568F	145	VA 235/55+HA 255/50		VA ✖
	FMI07 Atena	28	F95	145	VA 235/55+HA 255/50		VA ✖
		28	F95	145	VA 235/55+HA 255/50		VA ✖
	RC29	33	ZP568F	145 (300)	235/50, 245/45, 255/45 od.		
		33	ZP568F	145	VA 235/50+HA 255/45		
	RC34	33	ZP568F	145	VA 235/50+HA 255/45		
		20	ZP568F	145	VA 235/50+HA 255/45		VA ✖
8,5 x 20	B41	28	ZP568F	145	235/45 od.		
		28	ZP568F	145	VA 235/50+HA 255/45		VA ✖
	CA 19	35	ZP568F	145	235/45, 235/50 od.		
		35	ZP568F	145	VA 235/50+HA 255/45		
9 x 20	AC-518	32+35	ZP568F	145	235/50, 245/45, 255/45		
9 x 21	CA 17	33	F95	145	245/45		
9 x 21	CA 17	35	ZP568F	145	245/40, 255/40		
9,5 x 21	B41	36	ZP568F	145	VA 245/40+HA 275/35		

EQC 400 4matic				204X	5/112	66,6	e1*2001/116*0480*31-..
----------------	--	--	--	------	-------	------	------------------------

Sensor - Brocksens 3

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	B43	34	ZP568F	145 (300)	235/55, 245/50, 255/50HA		
	B40	32,5	-	145 (300)	235/55, 255/50HA		Orig.-Verschr.
	B43	32,5	-	145 (300)	235/55, 255/50HA		Orig.-Verschr.
	AC-521	35	AV1	145 (300)	235/55, 245/50, 255/50HA		
	Oxigin 29	32	ZP568F	145 (300)	235/55, 255/50HA		
8,5 x 19	B32	34,5	ZP561F	145 (300)	235/55, 255/50HA		
	B37	32+35	ZP561F	145 (300)	235/55, 255/50HA		
	CA 20	35	ZP568F	145 (300)	235/55, 255/50HA		
7,5 x 20	B43	32	-	145 (300)	VA 235/50+HA 255/45		Orig.-Verschr., Ausführung "D12"
8,5 x 20		30					
8 x 20	B43	27	ZP568F	145 (300)	245/45		
		30	ZP568F	145 (300)	235/50, 245/45, 255/45		
8,5 x 20	RC36	33	-	145 (300)	235/50, 245/45, 255/45		Orig.-Verschr. für Alufelgen
	B24	33	ZP561F	145 (300)	235/50, 245/45, 255/45		
	B43	34,5	-	145 (300)	235/50, 245/45, 255/45		Orig.-Verschr.
		35	ZP568F	145 (300)	235/50, 245/45, 255/45		
9 x 20	RC36	32	-	145 (300)	245/45, 275/40HA		Orig.-Verschr. für Alufelgen
	B37	29	ZP561F	145 (300)	235/50, 245/45, 255/45, 275/40HA		✖
	B40	34	ZP561F	145 (300)	235/50, 245/45, 255/45, 275/40HA		
	B43	33	ZP568F	145 (300)	245/45, 275/40HA		
		35	ZP568F	145 (300)	235/50, 245/45, 255/45, 275/40HA		
	CA 20	35	ZP568F	145 (300)	235/50, 245/45, 255/45, 275/40HA		
	CA 23	30	ZP568F	145 (300)	245/45		
	Oxigin 28	35	ZP568F	145 (300)	235/50, 245/45, 255/45, 275/40HA		
8,5 x 21	B43	30+34	ZP568F	145 (300)	235/45, 245/40, 255/40		

Kombinationen

8,5 x 21	B43	VA 30	ZP568F	145 (300)	VA 235/45, 245/40		
9 x 21		HA 36			HA 255/40, 275/35		

EQE - Limousine NEU

Sommer 2022

E2EQEW

5/112

66,6

e1*2018/858*00036*...

Sensor - Brocksens 8

Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 19	RC34	45	-	109-135	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	45	-	109, 135	235/50, 245/45, 255/45		Orig.-Verschr. max. Leistung 180, 215, 300 kW
	FMI12 Kari	45	-	109-135	235/50		Orig.-Verschr.
	RC32	43	-	109-135	235/50, 245/45, 255/45		
	RC34	38	ZP568F	109-135	245/45		
		43	ZP568F	109-135	235/50, 245/45, 255/45		
	B43	36	-	109, 135	235/50, 245/45		Orig.-Verschr. für Alufelgen
		38	ZP568F	109, 135	245/45		max. Leistung 180, 215, 300 kW
	43	ZP568F	109, 135	235/50, 245/45, 255/45		max. Leistung 180, 215, 300 kW	
8,5 x 19	RC32	47,5	-	109-135	235/50, 245/45, 255/40, 255/45, 265/45		Orig.-Verschr.
	RC34	47,5	-	109-135	255/45		Orig.-Verschr.
			-	109-135	235/50, 245/45, 255/40, 255/45, 265/45		Orig.-Verschr., ohne/mit Hinterachslenkung 5°
	B43	47,5	-	109-135	235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Hinterachslenkung 10°
			109-135	235/50, 245/45, 255/45, 265/45		Orig.-Verschr. max. Leistung 180, 215, 300 kW	
	D17	44	ZP568F	109, 135	235/50, 245/45, 255/45		max. Leistung 180, 215, 300 kW
	AC-M10	45	AV4	109, 135	235/50, 245/45, 255/45, 265/45		max. Leistung 180, 215, 300 kW
	CA 20 / CA 23	45	ZP568F	109, 135	235/50, 245/45, 255/45, 265/45		
Oxigin 28	45	ZP568F	109, 135	235/50, 245/45, 255/45, 265/45			
8 x 20	RC36	39	ZP568F	109, 135	245/45, 255/45		
8,5 x 20	B43	50,5	-	109, 135	235/45, 255/40		Orig.-Verschr. max. Leistung 180, 215, 300 kW
		35	ZP568F	109, 135	235/45		max. Leistung 180, 215, 300 kW
		43	ZP568F	109, 135	235/45, 255/40		max. Leistung 180, 215, 300 kW
	AC-M10	40	AV1	109, 135	235/45		max. Leistung 180, 215, 300 kW
	FMI12 Kari	50	F94	109-135	255/40		
9 x 20	B43	VA 50 HA 66	-	109, 135	VA 255/40		Orig.-Verschr. für Alufelgen
10 x 20				HA 285/35			
9 x 20	B43	50	-	109, 135	255/40		Orig.-Verschr. max. Leistung 180, 215, 300 kW
				109, 135	235/45, 255/40, 265/40HA		Orig.-Verschr., max. 4,5° Hinterachslenkung
				109, 135	235/45, 255/40		Orig.-Verschr., max. 10° Hinterachslenkung
	B37	48	ZP568F	109, 135	235/45, 255/40, 265/40		max. 4,5° Hinterachslenkung
				109, 135	235/45, 255/40		max. 10° Hinterachslenkung
	B40	49	ZP568F	109, 135	235/45, 255/40, 265/40		max. Leistung 180, 215, 300 kW
	B43	44	ZP568F	109, 135	235/45, 255/40, 265/40HA		max. Leistung 180, 215, 300 kW, bei 265/40 ✖
	AC-522	40	AV1	109-135	235/45, 245/40		
	CA 20	45	ZP568F	109, 135	235/45, 255/40, 265/40HA		max. Leistung 180, 215, 300 kW, bei 265/40 ✖
	FMI11 Elatha	46	F95	109-135	235/45		
	Oxigin 28	45	ZP568F	109, 135	235/45, 255/40		max. Leistung 180, 215, 300 kW
9,5 x 20	CA 17	50	ZP561F	109-135	245/40		
8,5 x 21	B43	43	ZP568F	109, 135	255/35		max. Leistung 180, 215, 300 kW

9 x 21	CA 20	45	ZP568F	109, 135	255/35		max. Leistung 180, 215, 300 kW
		50	OX556F	109, 135	255/35		max. Leistung 180, 215, 300 kW
	FMI07 Atena	50	F95	109-135	265/35		

EQE350+ NEU			E2EQEW		5/112	66,6	e1*2018/858*00036*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	45	-		235/50			Orig.-Verschr., i.V.
8,5 x 19	RC32	47,5	-		255/45			Orig.-Verschr., i.V.
8,5 x 20	CA 19	45	ZP561F	109	245/40			

EQE AMG NEU i.V.		Sommer 2023			E2EQEW	5/112	66,6	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW		Reifendimension		Info
EQE - SUV NEU		4. Halbjahr 2022			E2EQEX	5/112	66,6	e1*2018/858*00187*..
Sensor - Brocksens 8								

EQE - SUV		NEU	4. Halbjahr 2022		E2EQEX	5/112	66,6	e1*2018/858*00187*..	
Sensor - Brocksens 8									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
8 x 19	B43	36	-	109, 135	235/55		Orig.-Verschr. für Alufelgen		
					235/55, 245/50, 255/50, 265/50		Orig.-Verschr. für Alufelgen, mit 21"/22" Serie		
					235/55, 245/50, 255/50		Orig.-Verschr. für Alufelgen		
		32,5	-	109, 135	235/55, 245/50, 255/50		Orig.-Verschr. für Alufelgen, mit 21"/22" Serie		
					235/55, 245/50		Orig.-Verschr. für Alufelgen		
	CA 24	30	ZP569F	109-135	235/55				
8,5 x 19	CA 20	35	ZP568F	109, 135	235/55, 245/50, 255/50, 275/45		mit 21"/22" Serienbereifung		
					235/55, 245/50				
	CA 26	40	ZP568F	109, 135	235/55, 245/50, 255/50, 265/50, 275/45		mit 21"/22" Serienbereifung		
					235/55, 245/50, 255/50, 275/45				
9 x 19	B40	30	-	109, 135	235/55		Orig.-Verschr. für Alufelgen, mit 21"/22" Serie		
8 x 20	RC36	39	ZP568F	109, 135	235/50, 245/45, 255/45		auch mit 21"/22" Serienbereifung		
8,5 x 20	B43	38,5	-	109, 135	255/45		Orig.-Verschr., Ausführung "D12"		
			-	109, 135	255/45, 265/45		Orig.-Verschr. für Alufelgen		
	RC36	33	-	109, 135	235/50, 245/45, 255/45, 265/45		Orig.-Verschr. für Alufelgen		
9 x 20	RC36	32	-	109, 135	245/45, 255/45, 265/45		Orig.-Verschr. für Alufelgen, mit 21"/22" Serie		
				109, 135	245/45, 255/45		Orig.-Verschr. für Alufelgen		
8,5 x 21	B43	30+37	ZP568F	109, 135	235/45, 255/40		mit 21"/22" Serienbereifung		
				109, 135	235/45, 255/40				
9,5 x 21	B43	41,5	-	109, 135	255/40, 265/40		Orig.-Verschr. für Alufelgen, mit 21"/22" Serienbereifung		
				109, 135	255/40, 265/40		Orig.-Verschr. für Alufelgen		

EQE AMG - SUV		43/53 4Matic NEU	4. Halbjahr 2022		E2EQEX	5/112	66,6	e1*2018/858*00187*..	
Sensor - Brocksens 8									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
9,5 x 21	B43	41,5	-	135, 185	265/40M+S, 275/40			Orig.-Verschr. für Alufelgen	

EQS - Limousine NEU		2. Halbjahr 2022		E2EQSW		5/112		66,6		e1*2018/858*00035*..	
Sensor - Brocksens 8											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
8 x 19	RC34	30,5	-	109-135	235/55				Orig.-Verschr., beide ET's sind ECE		
				109-135	235/55, 245/50						
		34	-	109-135	235/55				Orig.-Verschr., beide ET's sind ECE		
				109-135	235/55, 245/50						
	B43	34	ZP568F	109, 135	235/55, 245/50, 255/50						
	RC32	32,5	-	109-135	235/55, 245/50, 255/50			Orig.-Verschr.			
	RC34	32,5	-	109-135	235/55, 245/50, 255/50			Orig.-Verschr.			
	B43	27+28	ZP568F	109, 135	235/55						
		32,5	-	109, 135	235/55, 245/50			Orig.-Verschr.			
		36	-	109, 135	235/55, 245/50, 255/50			Orig.-Verschr. für Alufelgen			
	AC-521	35	AV1	109, 135	235/55, 245/50, 255/50						
	CA 24	30	ZP569F	109-135	235/55, 245/50			nicht Brembo Bremse			
Oxigin 29	32	ZP568F	109, 135	235/55, 245/50							
8,5 x 19	RC32	35,5	-	109-135	235/55, 245/50, 255/50, 275/45			Orig.-Verschr.			
	RC34	31,5	-	109-135	235/55, 245/50			Orig.-Verschr.			
	B37	35	ZP568F	109, 135	235/55, 245/50						
	B41	35,5	ZP559F	109-135	235/55, 245/50, 255/50, 275/45						
		39	ZP568F	109-135	235/55, 245/50, 255/50, 265/50, 275/45			mit Hinterachslenkung 4,5°			
				109-135	245/50, 255/50, 265/50, 275/45			mit Hinterachslenkung 10°			
9 x 19	B41	38	ZP568F	109-135	255/50, 275/45						
	CA 24	35	ZP569F	109-135	265/45			nicht Brembo Bremse			
8 x 20	B43	27+30	ZP568F	109, 135	245/45, 255/45						
		39	ZP568F	109, 135	245/45, 255/45						
	RC36	33		109, 135	255/45				Orig.-Verschr. für Alufelgen		

8,5 x 20	RC36	30	-	109, 135	245/45, 255/45, 265/45		Orig.-Verschr. für Alufelgen
	B43	33	-		255/45		Orig.-Verschr., i.V.
	B24	33	ZP568F	109, 135	245/45, 255/45, 265/45		
		42	ZP568F	109, 135	255/45, 265/45		
	B41	28	ZP559F	109-135	235/50, 245/45, 255/45		
		35	ZP568F	109-135	235/50, 245/45, 255/45, 265/45		
	B43	34,5	-	109, 135	245/45, 255/45, 265/45		Orig.-Verschr.
		30+35+40	ZP568F	109, 135	245/45, 255/45, 265/45		ET30 bei 265/45 ✖
	AC-M10	30	ZP568F	109, 135	245/45, 255/45		
		40	AV1	109, 135	245/45, 255/45, 265/45		
9 x 20	CA 17	35	ZP561F	109-135	235/50, 245/45, 255/45		
	CA 19	32	ZP568F	109-135	235/50, 245/45, 255/45		nicht für Carbon-/Keramikbremscheiben
	RC36	32	-	109, 135	245/45, 255/45		Orig.-Verschr. für Alufelgen
	B37	37	ZP568F	109, 135	245/45, 255/45, 265/45		
	B40	34	ZP568F	109, 135	245/45, 255/45, 265/45		
	B41	33+35	ZP559F	109-135	235/50, 245/45, 255/45, 265/45		
		38	ZP559F	109-135	235/50, 245/45, 255/45, 265/45, 275/40		
	B43	33+35	ZP568F	109, 135	245/45, 255/45, 265/45		
		38	ZP568F	109, 135	245/45, 255/45, 265/45, 275/40		
		42	ZP568F	109, 135	255/45, 265/45, 275/40		
9,5 x 20	AC-522	33	AV1	109-135	245/45, 255/45		nicht für Carbon-/Keramikbremscheiben
		40	AV1	109-135	255/45, 265/40		nicht für Carbon-/Keramikbremscheiben
	CA 20	35	ZP568F	109, 135	245/45, 255/45, 265/45		
	FMI11 Elatha	34	F95	109-135	235/50, 245/45, 255/45, 265/45		
	Oxigin 28	35	ZP568F	109, 135	245/45, 255/45, 265/45		
8,5 x 21	B41	30+34+37	ZP568F	109-135	235/45, 255/40		
9 x 21	B43	36	ZP568F	109, 135	255/40, 265/40		
	CA 20	37	ZP568F	109, 135	255/40, 265/40		
	FMI07 Atena	33	F95	109-135	255/40, 265/40		
		40	F95	109-135	VA+HA 255/40, 265/40, 275/35 od. VA 245/40+HA 275/35		
9,5 x 21	B41	41,5	-	109-135	265/40		Orig.-Verschr.
	B43	41,5	-	109, 135	255/40, 265/40		Orig.-Verschr. für Alufelgen
	FMI10 e-Joule	41,5	-	109, 135	255/40, 265/40, 275/35		Orig.-Verschr.
	B41	36	ZP559F	109-135	255/40, 265/40		
		43	ZP568F	109-135	255/40, 265/40, 275/35		
10 x 21	B43	36	ZP568F	109, 135	255/40		
10 x 21	FMI07 Atena	40	F95	10-135			
9,5 x 22	B41	37	ZP568F	109-135	265/35		

Kombinationen

8,5 x 21	B41	VA 34	ZP568F	109-135	VA+HA 255/40 od.		
10,5 x 21		HA 43			VA 245/40+HA 275/35, VA 255/40+HA 285/35		
9,5 x 21	B41	VA 31	ZP568F	109-135	VA+HA 265/40 od.		HA bei 275/35 u. 285/35 ✖
10,5 x 21		HA 43			VA 245/40+HA 275/35, VA 255/40+HA 285/35		

EQS - SUV NEU		4. Halbjahr 2022		E2EQS	5/112	66,6	e1*2018/858*00188*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
9 x 20	B41	20	ZP559F	135	275/45			
9 x 21	FMI07 Atena	26	F95	135	265/45, 275/40, 275/45, 285/45			
10 x 21	FMI07 Atena	31	F95	135	265/45, 275/40, 275/45, 285/40, 285/45, 295/40			
10 x 22	FMI07 Atena	31	F95	135	265/40, 275/40, 285/35, 285/40, 295/35			
10 x 23	STC-23	32	Kit0613	135	275/35, 285/35		Achtung - Kit ist nicht kostenlos - Preis ist € 52,00 netto	

Kombinationen

9,5 x 21	B41	VA 31	ZP568F	135	VA+HA 275/40, 275/45, 285/40, 285/45		
10,5 x 21		HA 31					

EQS 53 AMG NEU		2022		E2EQSW	5/112	66,6	e1*2018/858*00035*4-9	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
9,5 x 21	B41	41,5	-	185	265/40		Orig.-Verschr.	
	B43	41,5	-		265/40		Orig.-Verschr., i.V.	
	FMI10 e-Joule	41,5	-	185	265/40, 275/35, 275/40		Orig.-Verschr., nur M+S	
	B41	36+43	ZP559F	185	265/40, 275/35, 275/40		nur M+S	
10 x 21	B41	47	-		275/40		Orig.-Verschr., i.V.	
	FMI07 Atena	40	F95	185	265/40M+S, 275/35, 275/40			

10,5 x 22	B41	43	ZP568F	185	275/35, 285/35		
-----------	-----	----	--------	-----	----------------	--	--

EQT NEU		im Laufe 2023		MFK	5/114,3	66,1	e2*2018/858*00014*..., e2*2018/858*00015*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC32	40	- (N7)	51-96	205/60			Orig.-Verschr., Ausführung N7
6,5 x 17	RC27	32	-	51	205/50, 205/55			Orig.-Verschr., Elektro, kurze Karosserie
7 x 17	RC27	35+40	-	51	205/50, 205/55, 215/50, 225/45			Orig.-Verschr., Elektro, kurze Karosserie
		38	ZP581	51	205/50, 205/55, 215/50, 225/45			Elektro, kurze Karosserie
					205/55, 215/50			Elektro
	B39	38	ZP581	51	205/50, 205/55, 215/50, 225/45			Elektro, kurze Karosserie
					205/55, 215/50			Elektro
	Pro1	45	-	51-96	205/55, 215/50, 225/45			Orig.-Verschr.
7,5 x 17	B24	38	ZP581	51	205/50, 205/55, 215/50, 225/45, 235/45			Elektro, kurze Karosserie
					205/55, 215/50, 235/45			Elektro
7 x 18	RC27	34	-	51	215/45, 225/45			Elektro, kurze Karosserie
					225/45			Elektro
7,5 x 18	RC30	35	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
	B32	35	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	51	215/45, 225/45			Elektro, kurze Karosserie, Kit mit Art.Nr.98478
					225/45			Elektro
8 x 18	CA 20	40	ZP581	51-96	215/45, 225/40, 225/45			
	B24	38	ZP581	51	215/45, 225/45			Elektro, kurze Karosserie
					225/45			Elektro
	B36	35	ZP581	51	215/45			Elektro, kurze Karosserie
B42 / B44	40	ZP581	51	215/45			Elektro, kurze Karosserie	

EQV 300		ab 2020		639/2	5/112	66,6	e1*2007/46*0457*25-... (FIN: W447...)	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	Originaldim.	51		70	245/55			900 kg Mindesttraglast pro Felge
	RC25T	51	-	70 (150)	245/55			Orig.-Verschr.
	RC30T	51	-	70 (150)	245/55			Orig.-Verschr., nur Frontantrieb
	B45	51	-	70 (150)	245/55			Orig.-Verschr., nur Frontantrieb
	AC-V51	51	14x1,5, Kug.R14, 30mm	70 (150)	245/55			
	Pro1	49	ZP569F	70	245/55			
7,5 x 17	RC25	51	-	70 (150)	245/55			Orig.-Verschr.
7,5 x 18	B45	52	-	70 (150)	245/50			Orig.-Verschr.
	AC-V51	50	ZP564F	70 (150)	245/50			
	CA 20	51	ZP568F	70	245/50			
8 x 18	RC25	45	ZP561F	70 (150)	245/50, 255/45			bei 245/50 ✖

G-Klasse		ab 03.2019	463A	5/130	84,1	e1*2007/46*1830*...	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC25T	43	-	210-310	265/60, 275/60		Orig.-Verschr., mit AMG-Line Verbreiterungen
	B45	43	-	210-310	265/60, 275/60		Orig.-Verschr. für Alufelgen, mit AMG-Line Verbreiterungen
8 x 18	8400 Bluster	35	-	210-310	265/55, 265/60, 275/60, 285/55		Orig.-Verschr., ohne AMG-Line ab 275/60 ✖
8,5 x 19	B41	52	-	210-310	265/50, 265/55, 275/50, 275/55		Orig.-Verschr.
8,5 x 20	B41	32	-	310	275/50		Orig.-Verschr.
				210-310	265/45, 265/50, 275/45, 275/50, 285/50		Orig.-Verschr., ohne AMG-Line nur 265/45 auflagenfrei!
9 x 20	8400 Bluster	32	-	210-310	265/45, 265/50, 275/45, 275/50, 285/45, 285/50		Orig.-Verschr., ohne AMG-Line nur 265/45 auflagenfrei!
9,5 x 20	B40	35	-	210-310	265/50, 275/50, 285/45, 295/45		Orig.-Verschr. für Alufelgen, mit AMG-Line Verbr.
9 x 21	CA 17	35	ZP561F	210-310	265/45, 275/45		Allrad
10 x 21	B43	33	-	210-310	265/45, 275/45, 285/45, 295/40		Orig.-Verschr. für Alufelgen, mit AMG-Line Verbreiterungen
10,5 x 21	CA 20	38	ZP569F	210-310	275/45, 285/45, 295/40		mit AMG-Line Verbreiterungen
10 x 22	CA 20	35	ZP569F	210-310	265/40, 275/40, 285/40, 295/35, 295/40, 305/35		mit AMG-Line Verbreiterungen
	FMI09 CRATOS	36	-	210-310	265/40, 275/40, 285/35, 285/40, 295/35, 305/35		Orig.-Verschr.
10,5 x 22	B41	35	-	210-310	265/40, 275/40, 285/35, 285/40, 295/35, 295/40, 305/35		Orig.-Verschr., mit AMG-Line Verbreiterungen
11 x 22	CA 20	30	ZP569F	210-310	275/40, 285/40		mit AMG-Line Verbreiterungen
10 x 23	STC-23	35	-	210-310	285/35, 295/35		nur mit AMG-Line Verbreiterung auflagenfrei!

AMG G 63		ab 2018		463A	5/130	84,1	e1*2007/46*1830*00-12	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
9,5 x 20	B40	35	-	430	275/50, 285/45, 295/45			Orig.-Verschr. für Alufelgen, mit AMG-Line Verbreiterungen

10 x 21	RC36	35,1	-	430	275/50, 285/45, 295/45		Orig.-Verschr. für Alufelgen
	B41	33	-	430	275/45, 285/45		Orig.-Verschr.
	B43	33	-	430	275/45, 285/45, 295/40		Orig.-Verschr. für Alufelgen
10 x 22	FMI09 CRATOS	36	-	430	275/40, 285/40, 295/35, 295/40, 305/35		Orig.-Verschr.
	CA 20	35	ZP569F	430	275/40, 285/40, 295/35, 295/40, 305/35		
10,5 x 22	B41	35	-	430	275/40, 285/35, 285/40, 295/35, 295/40, 305/35		Orig.-Verschr.
11 x 22	CA 20	30	ZP569F	430	275/40, 285/40		
10 x 23	STC-23	35	-	430	285/35, 295/35		

AMG G 63		ab 2018	463A (Baureihe 465)		5/130	84,1	e1*2007/46*1830*13*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
9,5 x 20	RC36	35,1	-	430	275/50, 285/45, 295/45			Orig.-Verschr. für Alufelgen
10 x 21	B43		33	-	430	275/45M+S, 285/45		Orig.-Verschr. für Alufelgen
						275/45, 285/45, 295/40		

GL-Klasse (siehe Konfigurator)	ab 2013	166	5/112	66,6	e1*2007/46*0598*... (FIN: WDC1668...)		
--------------------------------	---------	-----	-------	------	---------------------------------------	--	--

GL 63 AMG (siehe Konfigurator)	ab 2013	166	5/112	66,6	e1*2007/46*0826*...		
--------------------------------	---------	-----	-------	------	---------------------	--	--

GLA	2014	245G	5/112	66,6	e1*2001/116*0470*06-..., e1*2007/46*1207*...
Sensor - Brocksens 3					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	D17	38	-	80-155	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.
	RC27	38	-	100-155	215/60		Orig.-Verschr., auch Allrad
			-	80-155	215/60, 225/55, 225/60, 235/55		
7 x 17	D17	44+48,5	-	80-155	215/60, 225/55, 225/60, 235/55		auch Allrad
	RC27	47	ZP568F	80-155	215/60, 225/55, 225/60, 235/55		auch Allrad
		37	-	80-155	215/60, 225/55, 225/60, 235/55		Orig.-Verschr., auch Allrad
	RC30	47	ZP568F	80-155	215/60, 225/55, 225/60, 235/55		auch Allrad
	RC32	44	-	80-155	215/60, 225/55, 225/60, 235/55, 245/50		Orig.-Verschr.
	B39	35+47	ZP568F	80-155	215/60, 225/55, 225/60		ET47 nicht Bremse 295mm
7 x 18	RC27	46	-	80-155	235/50		Orig.-Verschr., auch Allrad
7,5 x 18	RC30	42+44	-	80-155	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr.
		45	ZP568F	80-155	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		
	RC32	42,5+44	-	80-155	215/50, 215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
		44	-	80-155	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr.
	B32	45	ZP568F	80-155	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		
	B39	45	ZP568F	80-155	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		
8 x 18	D17	40	-	80-155	215/55, 225/50, 235/45, 245/45		Orig.-Verschr., auch Allrad
	RC29	45	ZP568F	80-155	215/55, 225/50, 235/45, 245/45		
		48	-	80-155	215/55, 235/45		Orig.-Verschr., auch Allrad
	RC34	40	ZP568F	80-155	215/55		
		43	ZP568F	80-155	215/55, 225/50, 245/45		
	B36	45	ZP568F	80-155	215/55, 225/50, 235/45, 235/50, 245/45, 255/45		auch Allrad
	B37	45	ZP568F	80-155	215/55, 225/50, 235/45, 245/45		auch Allrad
		48	-	80-155	215/55, 235/45		Orig.-Verschr.
	B38	45	ZP568F	80-155	215/55, 225/50, 235/45, 245/45		auch Allrad
	AC-518	42	-	80-155	215/55, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		48	-	80-155	215/55, 235/45		Orig.-Verschr.
	AF20	35	AV1	80-155	215/55, 235/45		
		40	AV1	80-155	215/55, 225/50, 235/45, 245/45		
7,5 x 19	B32	44	-	80-155	225/45, 235/45, 245/45		Orig.-Verschr., auch Allrad
	B39	33	ZP568F	80-155	225/45, 235/45		
		43	ZP568F	80-155	225/45, 235/45, 245/45		
8 x 19	B43	43	ZP568F	80-155	235/45		
	Oxigin 29	43	ZP568F	80-155	235/45		
	RC29	39	-	80-155	225/45, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr., auch Allrad
		45	ZP568F	80-155	225/45, 235/40, 235/45, 245/40, 245/45		
	RC32	40	-	80-155	225/45, 235/40		Orig.-Verschr.
	RC34	38	ZP568F	80-155	225/45, 235/40		
		43	ZP568F	80-155	225/45, 235/40, 235/45, 245/40		
	B24	45	ZP568F	80-155	225/45, 235/40, 235/45, 245/40, 245/45		auch Allrad, nicht Bremse 295mm
	B38	39	-	80-155	225/45, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr., auch Allrad
		45	ZP568F	80-155	225/45, 235/40, 235/45, 245/40, 245/45		auch Allrad, nicht Bremse 295mm
	B40	38+43	ZP568F	80-155	225/45, 235/40, 235/45, 245/40, 245/45		
	B43	34	ZP568F	80-155	225/45, 235/40, 235/45		
	AC-518	38+47	-	80-155	225/45, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr., auch Allrad
	CA 17	45	ZP568F	80-280	235/45		
	FMI07 Atena	39	F95	80-155	225/45, 235/40		
8 x 20	B38	43,5	-	80-155	235/35, 235/40, 245/35, 245/40		Orig.-Verschr.
		44	-	80-155	235/35, 235/40, 245/35		Orig.-Verschr.
	B40	39	-	80-155	235/35, 235/40, 245/35, 245/40		Orig.-Verschr.
	B43	39	ZP568F	80-155	235/35, 235/40, 245/35		

		48	ZP568F	80-155	235/35, 235/40		
weitere Dimensionen/Designs siehe Konfigurator							

GLA 45 AMG 4matic (siehe Konfigurator)		ab 2014		245G	5/112	66,6	e1*2001/116*0470*..., e1*2007/46*1207*...	
GLA		ab 2020		F2B	5/112	66,6	e1*2007/46*1909*...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	D17	44	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 330 u. 350mm
	RC34	44	-	85-165	215/65			Orig.-Verschr.
	D17	49	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 330 u. 350mm
	RC27	49	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nur Bremse 305mm u. nicht 350mm
	D17	44	-	85-165	215/65, 225/60			Orig.-Verschr., nicht Bremse 350mm
	RC32	44	-	85-165	215/65, 225/60, 225/65			Orig.-Verschr., auch für Hybrid
7 x 17	RC34	44	-	85-165	215/65, 225/60, 225/65			Orig.-Verschr.
	D17	48,5	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 350mm
	RC27	47	ZP568F	85-165	215/65, 225/60, 235/60			nicht Bremse 350mm
	RC30	47	ZP568F	85-165	215/65, 225/60, 235/60			nicht Bremse 350mm
	RC34	48,5	-	85-165	215/65, 225/60, 225/65, 235/60, 245/55, 245/60			Orig.-Verschr., auch für Hybrid
	B45	51	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 318, 330 u. 350mm
	AC-V51	51	-	85-165	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 318, 330 u. 350mm
	CA 26	47	ZP568F	85-165	215/65, 225/60, 235/60			nicht Bremse 350mm
	Pro1	49	F31	85-165	215/65, 225/60, 225/65, 235/60			
	7,5 x 17	RC25	51	-	85-165	215/65, 225/60, 235/60		
RC27		52,5	-	85-165	225/60			Orig.-Verschr., nicht Bremse 350mm
RC34		45	ZP568F	85-165	215/65, 225/60, 225/65			
B24		47	ZP568F	85-165	215/65, 225/60			nicht Bremse 330 u. 350mm
6,5 x 18	RC34	44	-	85-165	215/60			Orig.-Verschr., Ausführung D4
7 x 18	RC27	46	-	85-165	215/60, 225/55			Orig.-Verschr.
7,5 x 18	RC32	53	-	85-165	215/60, 225/55, 225/60, 235/55			Orig.-Verschr., Ausführung D4
	RC34	53	-	85-165	235/55			Orig.-Verschr.
	RC32	42,5+44	-	85-165	215/60			Orig.-Verschr.
		49	-	85-165	215/60, 225/55, 225/60, 235/55			Orig.-Verschr., auch für Hybrid
	RC34	49	-	85-165	215/60, 225/55, 225/60, 235/55			Orig.-Verschr.
	B32	49+52	-	85-165	215/60, 225/55, 235/55			Orig.-Verschr.
	AC-MB6	45	AV1	85-165	215/60, 225/55			
	AC-V51	50	-	85-165	225/55, 235/55			Orig.-Verschr., nicht Bremse 318 u. 350mm
	CA 20	51	ZP568F	85-165	215/60, 225/55, 225/60, 235/55			nicht Bremse 330x30mm
	RC25	53	ZP568F	85-165	215/60, 225/55, 235/55			
8 x 18	RC27	48	-	85-165	215/60, 225/55			Orig.-Verschr.
	RC29	48	-	85-165	215/60, 225/55			Orig.-Verschr.
	RC34	48	ZP568F	85-165	225/55, 225/60			auch Hybrid
	B37	48	-	85-165	215/60, 225/55			Orig.-Verschr.
	B42 / B44	45	ZP568F	85-165	215/60			
	AC-518	48	-	85-165	215/60, 225/55			Orig.-Verschr.
	AC-521	45	AV1	85-165	215/60			
	AC-M10	45	AV4	85-165	215/60			
	AC-V51	52	AV1	85-165	225/55, 235/55			nicht Bremse 350mm
	FMI08 Thoe	49	F31	85-165	225/55, 225/60			
7,5 x 19	RC32	53	-	85-165	215/50, 225/50, 235/50, 245/45			Orig.-Verschr.
	RC34	53	-	85-165	215/50, 225/50, 235/50, 245/45			Orig.-Verschr.
	RC32 / RC34	49	-	85-165	215/50, 225/50, 235/50, 245/45			Orig.-Verschr.
8 x 19	RC27	48	-	85-165	225/50, 245/45			Orig.-Verschr.
		52	-	85-165	225/50, 235/50, 245/45, 255/45			Orig.-Verschr.
	RC29	52	-	85-165	225/50, 235/50, 245/45, 255/45			Orig.-Verschr., nicht Bremse 318mm
	RC32	52	-	85-165	225/50, 235/50, 245/45, 255/45			Orig.-Verschr., auch für Hybrid
	RC34	48	ZP568F	85-165	225/50, 245/45			
		49	-	85-165	225/50, 245/45			Orig.-Verschr.
		52	-	85-165	225/50, 235/50, 245/45, 255/45			Orig.-Verschr.
	B43	52	-	85-165	225/50, 235/50, 245/45, 255/45			Orig.-Verschr.
9 x 19	AC-518	47	-	85-165	225/50, 245/45			Orig.-Verschr.
	CA 17	53	OX556F	85-165	235/45			auch für Hybrid
	CA 19	53	OX556F	85-165	235/45			nicht Bremse 318x30mm
8 x 20	B43	48	ZP568F	85-165	215/45, 235/45, 245/40			
	B38	48	ZP568F	85-165	215/45, 235/45, 245/40			
	FMI08 Thoe	45	F31	85-165	215/45, 235/45			
8,5 x 20	B43	51,5	-	85-165	235/45, 245/40			Orig.-Verschr.
	CA 17	48	ZP568F	85-165	235/45			
	FMI12 Kari	50	F94	85-165	235/45, 245/40			
8,5 x 21	B43	51	-	85-165	245/35			Orig.-Verschr.

GLA NEU i.V.	im Laufe 2023
--------------	---------------

GLA 35 AMG		ab 2020		F2B	5/112	66,6	e1*2007/46*1909*...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	49	-	225-310	235/45, 235/50 , 245/45, 255/45			Orig.-Verschr.
	RC27	48	-	225	235/50, 245/45, 255/45			Orig.-Verschr.
	RC29	45	ZP568F	225	235/50, 245/45, 255/45			
	RC32	40	-	225-310	235/45, 235/50, 245/45, 255/45			Orig.-Verschr.
	RC34	43+48	ZP568F	225-310	235/45, 235/50, 245/45, 255/45			ET48 nicht 6-Kolben Festsattel mit 360x36mm
	B40 / B43	43	ZP568F	225	235/50, 245/45			
	Oxigin 29	43	ZP568F	225	235/50, 245/45			
8,5 x 19	D17	44	ZP568F	225	235/50, 245/45			
	B32	45	ZP568F	225	235/50, 245/45, 255/45			
		52	-	225	235/50, 245/45, 255/45			Orig.-Verschr.
	B41	35,5+36	ZP568F	225-310	235/45			
		39	ZP568F	225-310	235/45, 245/45			nicht 6-Kolben Festsattel mit 360x36mm
	B44	42	ZP568F	225	235/50, 245/45			
	AC-M10	45	AV4	225	235/50, 245/45, 255/45			
9 x 19	FMI12 Kari	49	-	225-310	235/45, 245/45, 255/45, 265/40, 265/45			Orig.-Verschr.
8 x 20	B38	48	ZP568F	225	235/45, 245/40			
	B40	43	ZP568F	225	235/45, 245/40			
	B43	39	ZP568F	225	235/45			
	FMI08 Thoe	45	F31	225-310	235/40, 235/45, 245/40			nicht 6-Kolben Festsattel mit 360x36mm
8,5 x 20	B43	51,5	-	225	235/45, 245/40, 255/40			Orig.-Verschr.
	RC29	45	ZP568F	225	235/45, 245/40			
	RC34	43	ZP568F	225-310	235/40, 235/45, 245/40, 255/40			
	B43 / B44	40	ZP568F	225	235/45			
	AC-518	45	AV1	225	235/45, 245/40			
	AC-M10	40	AV1	225	235/45			
	FMI12 Kari	50	F94	225-310	235/40, 235/45, 245/40, 255/40			nicht 6-Kolben Festsattel mit 360x36mm
9 x 20	B40	49	ZP568F	225	235/45, 245/40, 255/40			
	B43	42	ZP568F	225	235/45			
		44	ZP568F	225	235/45, 245/40			
	CA 23	45	ZP568F	225	235/45, 245/40			
FMI11 Elatha	46	F95	225-310	235/40, 235/45, 245/40, 255/40				
8,5 x 21	B43	51	-	225	245/35, 255/35			Orig.-Verschr.

Kombinationen

8 x 19	FMI08 Thoe	VA 47	F31	225-310	VA+HA 235/45, 245/45		nicht 6-Kolben Festsattel mit 360x36mm
9 x 19		HA 41					
8 x 20	FMI08 Thoe	VA 45	F31	225-310	VA+HA 235/40, 235/45, 245/40		nicht 6-Kolben Festsattel mit 360x36mm
9 x 20		HA 41					

GLA 45 AMG		ab 2020		F2B	5/112	66,6	e1*2007/46*1909*...	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	49	-	225-310	235/45, 235/50 , 245/45, 255/45			Orig.-Verschr.
	RC32	40	-	225-310	235/45, 235/50, 245/45, 255/45			Orig.-Verschr.
	RC34	43	ZP568F	225-310	235/45, 235/50, 245/45, 255/45			
8,5 x 19	B41	35,5+36	ZP568F	225-310	235/45			
9 x 19	FMI12 Kari	49	-	225-310	235/45, 245/45, 255/45, 265/40, 265/45			Orig.-Verschr.
8 x 20	FMI08 Thoe	45	F31	225-310	235/40, 235/45, 245/40			nicht 6-Kolben Festsattel mit 360x36mm
8,5 x 20	RC34	43	ZP568F	225-310	235/40, 235/45, 245/40, 255/40			
9 x 20	FMI11 Elatha	46	F95	225-310	235/40, 235/45, 245/40, 255/40			

Kombinationen

8 x 19	FMI08 Thoe	VA 47	F31	225-310	VA+HA 235/45, 245/45		nicht 6-Kolben Festsattel mit 360x36mm
9 x 19		HA 41					
8 x 20	FMI08 Thoe	VA 45	F31	225-310	VA+HA 235/40, 235/45, 245/40		nicht 6-Kolben Festsattel mit 360x36mm
9 x 20		HA 41					

GLA 45, - 45s AMG NEU		im Laufe 2023		F2B	5/112	66,6	e1*2007/46*1909*07-..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 20	B43	39	ZP568F	285, 310	235/45			
8,5 x 20	AC-M10	40	AV1	285, 310	235/45			

GLA 250e NEU				F2B	5/112	66,6	e1*2007/46*1909*08-..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	D17	44	-	118	215/65, 225/60, 235/60			Orig.-Verschr., Plug-in-Hybrid, nicht Bremse 350mm
	RC27	47	ZP568F	118, 120	215/65, 225/60, 235/60			Plug-in-Hybrid, nicht Bremse 350mm
	RC30	35	ZP568F	118	215/65, 225/60			Plug-in-Hybrid, nicht Bremse 350mm
	CA 26	42+47	ZP568F	118, 120	215/65, 225/60, 235/60			Plug-in-Hybrid, nicht Bremse 350mm

7,5 x 17	B24	35	ZP568F	118, 120	215/65		nicht Bremse 350mm
	CA 20	47	ZP568F	118, 120	215/65, 225/60, 235/60		Plug-in-Hybrid, nicht Bremse 350mm
7 x 18	RC27	46	-	118, 120	215/60, 225/55, 235/55		Orig.-Verschr., Plug-in-Hybrid
7,5 x 18	RC30	42	-	118, 120	215/60, 225/55		Orig.-Verschr., Plug-in-Hybrid
		35	ZP568F	118, 120	215/60		Plug-in-Hybrid
	B32	40	-	118, 120	215/60, 225/55		Orig.-Verschr., Plug-in-Hybrid
		44	-	118, 120	215/60, 225/55, 235/55		Orig.-Verschr., Plug-in-Hybrid
	AC-MB6	45	AV1	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	AC-V51	50	-	118, 120	225/55, 235/55		Orig.-Verschr., nicht Bremse 350mm
8 x 18	D17	40	-	118	215/60, 225/55		Orig.-Verschr., Plug-in-Hybrid
	RC27	48	-	118	215/60, 225/55, 235/55		Orig.-Verschr., Plug-in-Hybrid
	RC25	45	ZP568F	118	215/60, 225/55, 235/55		Plug-in-Hybrid
	B24	48	ZP568F	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	B36	35	ZP568F	118, 120	215/60		Plug-in-Hybrid
		45	ZP568F	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	B37	48	-	118, 120	215/60, 225/55, 235/55		Orig.-Verschr., Plug-in-Hybrid
	B42	45	ZP568F	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	B44	35	ZP568F	118, 120	215/60		Plug-in-Hybrid
		45	ZP568F	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	AC-M10	40	AV1	118, 120	215/60, 225/55		Plug-in-Hybrid
		45	AV4	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
	AC-521	45	AV1	118	215/60, 225/55, 235/55		Plug-in-Hybrid
	CA 20 / CA 23	45	ZP568F	118, 120	215/60, 225/55, 235/55		Plug-in-Hybrid
8 x 19	RC29	45	ZP568F	118	225/50		Plug-in-Hybrid
	B40	43	ZP568F	118, 120	225/50		Plug-in-Hybrid
	B43	43	ZP568F	118	225/50		Plug-in-Hybrid
	Oxigin 29	43	ZP568F	118, 120	225/50		Plug-in-Hybrid
8,5 x 19	B37	48	-	118	235/50		Orig.-Verschr., Plug-in-Hybrid
	CA 26	47,5	ZP568F	118, 120	235/50		Plug-in-Hybrid
8 x 20	B43	48	ZP568F	118, 120	215/45, 235/45, 245/40		Plug-in-Hybrid
	B40	43	ZP568F	118	215/45, 235/45		Plug-in-Hybrid
8,5 x 20	B42	45+48	ZP568F	118	235/45		Plug-in-Hybrid
	B43	52,5	-	118	235/45		Orig.-Verschr., Plug-in-Hybrid
		43	ZP568F	118	235/45		Plug-in-Hybrid
9 x 20	B43	44	ZP568F	118	235/45		Plug-in-Hybrid
	CA 20 / CA 23	45	ZP568F	118, 120	235/45		Plug-in-Hybrid
	Oxigin 28	45	ZP568F	118	235/45		Plug-in-Hybrid
GLB	ab 2019			F2B	5/112	66,6	e1*2007/46*1909*..

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	D17	44	-	85-165	215/65, 225/60, 235/60		Orig.-Verschr., nicht Bremse 330 u. 350mm, Felge muss unbedingt vorher probiert werden, es kann sein, dass die Bremszange an den Speichen streift!
	RC34	44	-	85-165	215/65		Orig.-Verschr.
7 x 17	D17	49	-	85-165	215/65, 225/60, 235/60		Orig.-Verschr., nicht Bremse 330 u. 350mm
	D17	44	-	85-165	215/65, 225/60		Orig.-Verschr., nicht Bremse 350mm
	RC32	44	-	85-165	215/65, 225/60, 225/65		Orig.-Verschr.
	RC34	44	-	85-165	215/65, 225/60, 225/65		Orig.-Verschr.
	D17	48,5	-	85-165	215/65, 225/60, 235/60		Orig.-Verschr., nicht Bremse 350mm
	RC27	47	ZP568F	85-165	215/65, 225/60, 235/60		nicht Bremse 350mm
	RC30	47	ZP568F	85-165	215/65, 225/60, 235/60		nicht Bremse 350mm
	RC32	48,5	-	85-165	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	B39	47	ZP568F	85-165	215/65, 225/60, 235/60		nicht Bremse 318 u. 350mm
	CA 26	47	ZP568F	85-165	215/65, 225/60, 235/60		nicht Bremse 350mm
7,5 x 17	Pro1	49	F31	85-165	215/65, 225/60, 225/65, 235/60		
	RC25	51	-	85-165	215/65, 225/60, 235/60		Orig.-Verschr., nicht Bremse 330 u. 350mm
	RC34	45	ZP568F	85-165	215/65, 225/60, 225/65		
6,5 x 18	B24	47	ZP568F	85-165	215/65, 225/60		nicht Bremse 330 u. 350mm
	RC34	44	-	85-165	215/60		Orig.-Verschr., Ausführung D4
7,5 x 18	RC32	53	-	85-165	215/60, 225/55, 225/60, 235/55		Orig.-Verschr., Ausführung D4
	RC34	53	-	85-165	235/55		Orig.-Verschr.
	RC32	42,5+44	-	85-165	215/60		Orig.-Verschr.
		49	-	85-165	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.
	RC34	49	-	85-165	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.
	B32	49+52	-	85-165	215/60, 225/55, 235/55		Orig.-Verschr.
	AC-MB6	45	AV1	85-165	215/60, 225/55		
	AC-V51	50	-	85-165	225/55, 235/55		Orig.-Verschr., nicht Bremse 318 u. 350mm
	CA 20	51	ZP568F	85-165	215/60, 225/55, 225/60, 235/55		nicht Bremse 330x30mm
	RC25	53	ZP568F	85-165	215/60, 225/55, 235/55		
	RC29	48	-	85-165	215/60, 225/55		Orig.-Verschr.
	RC34	48	ZP568F	85-165	225/55, 225/60		
	B36	45	ZP568F	85-165	215/60		

8 x 18	B37	48	-	85-165	215/60, 225/55		Orig.-Verschr.
	B42 / B44	45	ZP568F	85-165	215/60		
	AC-518	48	-	85-165	215/60, 225/55		Orig.-Verschr.
	AC-521	45	AV1	85-165	215/60		
	AC-M10	45	AV4	85-165	215/60		
	AC-V51	52	AV1	85-165	225/55, 235/55		nicht Bremse 350mm
	CA 23	45	ZP568F	85-165	215/60		
7,5 x 19	FMI08 Thoe	49	F31	85-165	225/55, 225/60		
	RC32	53	-	85-165	215/50, 225/50, 235/50 , 245/45		Orig.-Verschr.
	RC34	53	-	85-165	215/50, 225/50, 235/50 , 245/45		Orig.-Verschr., bis Achslast 1390 kg
8 x 19	RC32 / RC34	49	-	85-165	215/50, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC29	52	-	85-165	225/50, 235/50, 245/45, 255/45		nicht Bremse 318mm
	RC32	52	-	85-165	225/50, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC34	48	ZP568F	85-165	225/50, 245/45		
		49	-	85-165	225/50, 245/45		Orig.-Verschr.
		52	-	85-165	225/50, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	52	-	85-165	225/50, 235/50, 245/45, 255/45		Orig.-Verschr.
	AC-518	47	-	85-165	225/50, 245/45		Orig.-Verschr.
	FMI07 Atena	47	F95	85-165	225/50, 245/45		
8 x 20	B43	48	ZP568F	85-165	215/45, 235/45 , 245/40		
	B38	48	ZP568F	85-165	215/45, 235/45, 245/40		
	FMI08 Thoe	45	F31	85-165	215/45, 235/45		
8,5 x 20	B43	51,5	-	85-165	235/45, 245/40		Orig.-Verschr.
	CA 17	48	ZP568F	85-165	235/45		
	FMI12 Kari	50	F94	85-165			
8,5 x 21	B43	51	-	85-165	245/35		Orig.-Verschr.

GLB 35 AMG				ab 2020	F2B	5/112	66,6	e1*2007/46*1909*...	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
8 x 19	RC34	49	-	225	235/45, 235/50 , 245/45, 255/45		Orig.-Verschr.		
	RC29	45	ZP568F	225	235/50, 245/45, 255/45				
	RC32	40	-	225	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.		
	RC34	43+48	ZP568F	225	235/45, 235/50, 245/45, 255/45				
	B40 / B43	43	ZP568F	225	235/50, 245/45				
	CA 24	43	ZP568F	225	245/45				
8,5 x 19	Oxigin 29	43	ZP568F	225	235/50, 245/45				
	D17	44	ZP568F	225	235/50, 245/45				
	B32	45	ZP568F	225	235/50, 245/45, 255/45				
		52	-	225	235/50, 245/45, 255/45		Orig.-Verschr.		
	B41	35,5+36	ZP568F	225	235/45				
		39	ZP568F	225	235/45, 245/45				
9 x 19	B44	42	ZP568F	225	235/50, 245/45				
	AC-M10	45	AV4	225	235/50, 245/45, 255/45				
	CA 17	49	ZP568F	225	245/45				
	FMI12 Kari	49	-	225	235/45, 245/45, 255/45, 265/40, 265/45		Orig.-Verschr.		
	8 x 20	B38	48	ZP568F	225	235/45, 245/40			
		B40	43	ZP568F	225	235/45, 245/40			
B43		39	ZP568F	225	235/45				
FMI08 Thoe		45	F31	225	235/40, 235/45, 245/40				
8,5 x 20	B43	51,5	-	225	235/45, 245/40, 255/40		Orig.-Verschr.		
	RC29	45	ZP568F	225	235/45, 245/40				
	RC34	43	ZP568F	225	235/40, 235/45, 245/40, 255/40				
	B43 / B44	40	ZP568F	225	235/45				
	AC-518	45	AV1	225	235/45, 245/40				
	AC-M10	40	AV1	225	235/45				
9 x 20	B40	49	ZP568F	225	235/45, 245/40, 255/40				
	B43	42	ZP568F	225	235/45				
		44	ZP568F	225	235/45, 245/40				
	CA 23	45	ZP568F	225	235/45, 245/40				
	FMI11 Elatha	46	F95	225	235/40, 235/45, 245/40, 255/40				
8,5 x 21	B43	51	-	225	245/35, 255/35		Orig.-Verschr.		

Kombinationen

8 x 19	FMI08 Thoe	VA 47	F31	225	VA+HA 235/45, 245/45		
9 x 19		HA 41					
8 x 20	FMI08 Thoe	VA 45	F31	225	VA+HA 235/40, 235/45, 245/40		
9 x 20		HA 41					

GLC							
ab 2015				204X (WDC253)	5/112	66,6	e1*2001/116*0480*16... (FIN: WDC253 9 ...
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
	D17	36	-	100-190	235/60, 235/65		Orig.-Verschr. für Alufelgen, nicht Bremse 360mm
	RC27	36	-	100-190	235/65		Orig.-Verschr.

7,5 x 17	RC32	36	-	100-190	235/65, 245/60, 255/60		Orig.-Verschr., auch Hybrid
	RC34	36	ZP568F	100-190	235/65, 245/60, 255/60		
	RC27	40	-	100-190	235/60, 235/65		Orig.-Verschr., nicht Bremse 360mm
	RC32	40	-	100-190	235/65, 245/60, 255/60		Orig.-Verschr., auch Hybrid
	RC34	40	ZP568F	100-190	235/65, 245/60, 255/60		
	B36	35	ZP568F	120-190	235/60, 235/65, 255/60		nicht Bremse 360mm
7,5 x 18	AC-518	30	-	100-190	235/60, 235/65		Orig.-Verschr., nicht Bremse 360mm
	RC30	35	ZP561F	100-190	235/55, 235/60, 255/50, 255/55		
	B32	35	ZP561F	100-190	235/55, 235/60, 255/50, 255/55		
8 x 18	B39	35	ZP568F	100-190	235/55, 235/60, 255/50, 255/55		
	D17	38	-	100-190	235/55, 235/60		Orig.-Verschr. für Alufelgen
	RC27	38	-	100-243	235/60		Orig.-Verschr.
				100-190	235/55, 235/60		
	RC32	38	-	100-243	235/60, 245/55, 255/55		Orig.-Verschr.
	RC25	38	-	100-190	235/55, 235/60		Orig.-Verschr. für Alufelgen
	RC27	32,5	-	100-243	235/55, 235/60		Orig.-Verschr.
	RC29	35	ZP561F	100-190	235/55, 235/60		nicht Bremse 360mm
	RC34	30+40	ZP568F	100-243	235/60, 245/55		auch für Hybrid
	B36	35	ZP568F	120-190	235/55, 235/60		
	B37	35	ZP568F	120-180	235/55, 235/60		
	B38	35	ZP568F	100-190	235/55, 235/60		
	B42	30	ZP568F	100-243	235/55, 235/60		
		35	ZP561F	100-243	235/55, 235/60		
	B44	35	ZP561F	100-243	235/55, 235/60		
	AC-M10	30	AV4	100-243	235/55, 235/60		
		40	AV1	100-243	235/55, 235/60		nicht Bremse 360mm
	AF18	35	AV1	100-190	235/55, 235/60		
	FMI11 Elatha	26	F95	100-243	235/60		
		39	F95	100-243	235/60, 245/55		
8,5 x 18	B32	30	ZP568F	100-243	235/55, 235/60		
7,5 x 19	B39	33	ZP568F	100-190	235/50, 235/55, 245/50, 255/50		
	Oxigin 18	35	ZP568F	100-190	235/55, 245/50		nicht Bremse 360mm
8 x 19	RC27	38	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	RC32	38	-	100-243	235/55		Orig.-Verschr., auch Hybrid
	RC34	38	ZP568F	100-243	235/50, 235/55, 245/50		
	B40	38	ZP561F	100-243	235/50, 235/55, 245/50, 255/45		
	B43	38	ZP568F	100-243	235/50, 235/55, 245/50, 255/45		auch für Hybrid
	CA 17	38	OX556F	100-190	235/55		Orig.-Verschr.
	CA 19	38	OX556F	100-243	235/55		
	CA 24	38	OX556F	100-243	235/55		
	RC32	32,5+34	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	RC34	27	ZP568F	100-243	235/50, 235/55		
	B38	35	ZP568F	100-190	235/50, 235/55, 245/50, 255/45		
	B40	32,5	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	B43	32,5	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
		34	ZP568F	100-243	235/50, 235/55, 245/50, 255/45, 255/50		
	AC-518	38	-	100-190	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	AC-521	35	AV1	100-243	235/50, 235/55, 245/50, 255/45		
	FMI07 Atena	39	F95	100-243	235/50, 235/55, 245/50		
8,5 x 19	D17	38	-	100-190	235/50, 235/55, 255/45		Orig.-Verschr. für Alufelgen
	RC25	38	-	100-190	235/50, 235/55, 255/45		Orig.-Verschr. für Alufelgen
	RC32	35,5	-	100-243	235/50, 235/55, 245/50, 275/45		Orig.-Verschr.
	B32	34,5	ZP561F	100-190	235/50, 235/55, 245/50, 255/45		
	B37	35	ZP561F	100-190	235/50, 235/55, 245/50, 255/45		
	B41	35,5+36	ZP568F	100-243	235/50, 235/55, 245/50, 275/45		
		39	ZP568F	100-243	235/50, 235/55, 245/50		
	B42	30	ZP561F	100-243	235/50, 235/55, 255/45		
		35	ZP561F	100-243	235/50, 235/55, 245/50, 255/45		nicht Bremse 360mm
	B43	40	ZP568F	100-243	235/50, 235/55, 245/50		
	B44	30	ZP561F	100-243	235/50, 235/55, 255/45		
		35	ZP561F	100-243	235/50, 235/55, 245/50, 255/45		
	AF18	30+40	AV1	100-190	235/50, 235/55, 255/45		ET40 nicht Bremse 360mm
	AF20	30	AV1	100-243	235/50, 235/55, 255/45		
	CA 23	40	OX556F	100-243	235/50, 235/55, 255/45		nicht Bremse 360mm
	FMI07 Atena	28	F95	100-243	235/50, 235/55		
	Oxigin 25	35	ZP568F	100-243	235/55		nicht Bremse 360mm
	Oxigin 28	30+40	ZP569F	100-243	235/50, 235/55, 255/45		ET40 nicht Bremse 360mm
8 x 20	B38	35	ZP568F	100-190	235/45, 245/45, 255/45		
	B43	27+30	ZP568F	100-243	235/45, 245/45, 255/45		
		39	ZP568F	100-243	235/45, 245/45, 255/45		
	B43	40	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		auch Hybrid
	RC29	40	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	CA 19	40	F95	100-243	235/45, 255/45		nicht Bremse 330 u. 360mm
	FMI12 Kari	40	-	100-243	255/45		Orig.Verschr.

8,5 x 20	RC34	38	ZP568F	100-243	245/45, 255/45		auch für Hybrid
	B32	40	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	B41	35	ZP568F	100-243	235/45, 245/45, 255/45, 265/45		
	B42	40	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		nicht Bremse 360mm
			ZP561F	120-243	235/45, 245/45, 255/40, 255/45		nicht Bremse 360mm, mit AMG-Line Verbreiterungen
	B43	34,5	-	100-243	235/45, 245/45, 255/40, 255/45		Orig.Verschr.
		35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
	B44	30+35	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		
		40	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		ET40 nicht Bremse 360mm
	AC-518	32	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AC-521	32	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AC-M10	30	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
		40	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AF18	32	AV1	100-190	235/45, 245/45, 255/40, 255/45		
	CA 17	35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		nicht Bremse 360mm
		40	ZP568F	100-243	235/45, 255/45		
	CA 19	32	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
	FMI07 Atena	39	F95	100-243	235/45, 245/45, 255/45		
	B37	37	ZP568F	120-180	235/45, 245/45, 255/40, 255/45		
	B40	34	ZP568F	100-190	235/45, 245/45, 255/40, 255/45		
9 x 20	B41	35	ZP568F	100-243	235/45, 245/45, 255/45, 265/40		
		33+38	ZP568F	100-243	235/45, 245/45, 255/45		
	B43	33+35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45, 265/40		
		38	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
	AC-518	33	F95	100-243	235/45, 245/45		
	AC-522	40	AV1	100-243	235/45		
	AF18	40	AV1	100-190	235/45, 245/45		
	FMI07 Atena	33	F95	100-243	235/45, 245/45, 255/45		
	Oxigin 18	35	ZP568F	120-190	235/45, 245/45, 255/40, 255/45, 265/40		nicht Bremse 360mm
	Oxigin 20	35	ZP568F	100-190	235/45, 245/45, 255/40, 255/45		nicht Bremse 360mm
9,5 x 20	Oxigin 25	35	ZP568F	100-190	235/45, 245/45, 255/40, 255/45		
	Oxigin 28	35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45, 265/40		
	B37C	32	ZP561F	100-190	255/40, 255/45		
8,5 x 21	B42	35	ZP561F	100-243	255/40, 255/45		
	B41	30+34+37+40	ZP568F	100-243	245/40, 255/40		ET40 nur 245/40
8,5 x 21	B43	30+34+37	ZP568F	100-243	245/40, 255/35, 255/40		
	B32	30	ZP561F	100-190	245/40, 255/35, 255/40, 265/35		bei 265/35 ✖
9 x 21	B32	40	ZP561F	100-190	245/40		
		36	ZP568F	100-243	245/40, 255/35, 255/40		
	B43	36	ZP568F	100-243	245/40, 255/35, 255/40		
	AF18	30+37	AV1	100-190	245/40, 255/35, 255/40		
	CA 17	30+35	ZP561F	100-243	245/40		
	Oxigin 18	35	ZP568F	100-243	245/40		
9,5 x 21	B41	31+36	ZP568F	100-243	245/40		
9 x 22	AF18	35	AV1	100-190	255/30, 255/35		

GLC Coupé							
ab 10.2016				204X	5/112	66.6	e1*2001/116*0480*.. (FIN: WDC2533...)
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	D17	38	-	100-190	235/55, 235/60 , 255/55HA		Orig.-Verschr. für Alufelgen
	RC27	38	-	100-243	235/55, 235/60		Orig.-Verschr.
	RC32	38	-	100-243	235/60 , 245/55, 255/55		Orig.-Verschr.
	RC25	38	-	100-190	235/55, 235/60, 255/55HA		Orig.-Verschr. für Alufelgen
	RC27	32,5	-	100-243	235/55, 235/60, 255/50HA, 255/55HA, 285/50HA		Orig.-Verschr., mit Verbreiterungen
	RC29	35	ZP561F	100-190	235/55, 235/60, 255/55HA		nicht Bremse 360mm
	RC34	30+40	ZP568F	100-243	235/55, 235/60, 245/55		auch für Hybrid
	B36	35	ZP568F	120-190	235/55, 235/60		
	B38	35	ZP568F	100-190	235/55, 235/60		
	B42	30	ZP568F	100-243	235/55, 235/60		
		35	ZP561F	100-243	235/55, 235/60, 255/55HA		
	B44	35	ZP561F	100-243	235/55, 235/60, 255/55HA		
	AC-M10	30	AV4	100-243	235/55, 235/60		
	AC-518	35	-	100-190	235/55, 235/60, 285/50HA		Orig.-Verschr.
	AF18	35	AV1	100-190	235/55, 235/60, 255/55		
	FMI11 Elatha	39	F95	100-243	235/55, 235/60, 245/55		mit Radhausverbreiterungen
8,5 x 18	B32	30	ZP561F	100-243	235/55, 235/60		
8 x 19	B40	VA 38	ZP561F	100-243	VA 235/50, 235/55 , 245/50, 255/45		
9 x 19		HA 20			HA 235/55, 255/45, 255/50 , 275/45, 285/45		
	RC27	38	-	100-190	235/55		Orig.-Verschr.
	RC32	38	-	100-243	235/55		Orig.-Verschr., auch Hybrid Fahrzeuge
	RC34	38	ZP568F	100-243	235/50, 235/55 , 245/50		
	B40	38	ZP561F	100-243	235/50, 235/55 , 245/50, 255/45		

8 x 19	B43	38	ZP568F	100-243	235/50, 235/55 , 245/50, 255/45, 255/50HA		auch für Hybrid
	CA 17	38	OX556F	100-190	235/55		
	CA 19	38	OX556F	100-243	235/55		
	CA 24	38	OX556F	100-243	235/55		
	RC29	35	ZP561F	100-190	235/50, 235/55, 245/50, 255/45, 255/50		
	RC32	32,5+34	-	100-243	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	B24	35	ZP561F	100-190	235/50, 235/55, 245/50, 255/45, 255/50		
	B38	35	ZP561F	100-190	235/50, 235/55, 245/50, 255/45, 255/50		
	B40	32,5	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
	B43	32,5	-	100-243	235/50, 235/55, 245/50, 255/45		Orig.-Verschr.
		34	ZP568F	100-243	235/50, 235/55, 245/50, 255/45, 255/50		
	AC-518	38	-	100-190	235/50, 235/55, 245/50, 255/45, 255/50HA		Orig.-Verschr.
	AC-521	35	AV1	100-243	235/50, 235/55, 245/50, 255/45, 255/50		
	FMI07 Atena	39	F95	100-243	235/50, 235/55, 245/50		
8,5 x 19	D17	38	-	100-190	235/50, 235/55, 255/45, 255/50HA		Orig.-Verschr. für Alufelgen
	RC25	38	-	100-190	235/50, 235/55, 255/45, 255/50HA		Orig.-Verschr. für Alufelgen
	RC32	35,5	-	100-243	235/50, 235/55, 245/50, 275/45		Orig.-Verschr.
	B32	34,5	ZP561F	100-190	235/50, 235/55, 245/50, 255/45, 255/50, 275/45		
	B37	32+35	ZP561F	100-190	235/50, 235/55, 245/50, 255/45, 275/45		ET32 bei 275/45 ✖
	B41	35,5+36	ZP568F	100-243	235/50, 235/55, 245/50, 275/45		
		39	ZP568F	100-243	235/50, 235/55, 245/50		
	B42	30	ZP561F	100-243	235/50, 235/55, 255/45		
		35	ZP561F	100-243	235/50, 235/55, 245/50, 255/45, 255/50HA, 275/45HA		nicht Bremse 360mm
	B43	40	ZP568F	100-243	235/50, 235/55, 255/45, 255/50HA		
	B44	30	ZP561F	100-243	235/50, 235/55, 255/45		
		35	ZP561F	100-243	235/50, 235/55, 245/50, 255/45, 255/50HA		
	AF18	30+40	AV1	100-190	235/50, 235/55, 255/45		ET40 nicht Bremse 360mm
	AF20	30	AV1	100-243	235/50, 235/55, 255/45		
	CA 23	40	OX556F	100-243	235/50, 235/55, 255/45, 255/50HA		nicht Bremse 360mm
	FMI07 Atena	28	F95	100-243	235/50, 235/55		
	Oxigin 20	35	ZP568F	100-243	235/50, 235/55, 255/45		
	Oxigin 25	35	ZP568F	100-243	235/50, 235/55, 255/45		nicht Bremse 360mm
	Oxigin 28	30	ZP568F	100-243	235/50, 235/55, 255/45		
		40	ZP568F	100-243	235/50, 235/55, 255/45, 255/50HA		ET40 nicht Bremse 360mm
8 x 20	B43	27+30	ZP568F	100-243	235/45, 245/45, 255/45		
		39	ZP568F	100-243	235/45, 245/45, 255/45		
8,5 x 20	B43	40	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		auch Hybrid
	RC29	40	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	CA 19	40	F95	100-243	255/45		nicht Bremse 330 u. 360mm
	FMI12 Kari	40	-	100-243	255/45		Orig.-Verschr.
	RC29	29+33	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	RC34	38	ZP568F	100-243	235/45, 245/45, 255/45		auch für Hybrid
	B24	33	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	B32	40	ZP561F	100-190	235/45, 245/45, 255/40, 255/45		
	B41	35	ZP568F	100-243	235/45, 245/45, 255/45, 265/45		
	B42	40	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		ET40 nicht Bremse 360mm
	B43	34,5	-	100-243	235/45, 245/45, 255/40, 255/45		Orig.-Verschr.
		35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
	B44	30+35	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		
		40	ZP561F	100-243	235/45, 245/45, 255/40, 255/45		
	AC-518	32	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AC-521	32	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AC-M10	30	ZP568F	100-243	235/45, 245/45, 255/40, 255/45		
		40	AV1	100-243	235/45, 245/45, 255/40, 255/45		
	AF18	32	AV1	100-190	235/45, 245/45, 255/40, 255/45		
	CA 17	35	ZP568F	100-243	255/40, 255/45		nicht Bremse 360mm
		40	ZP568F	100-243	255/45		nicht Bremse 360mm
	CA 19	32	ZP568F	100-243	255/40, 255/45		
	FMI07 Atena	39	F95	100-243	235/45, 245/45, 255/45		
9 x 20	B40	34	ZP568F	100-190	255/40, 255/45		
	B41	35	ZP568F	100-243	235/45, 245/45, 255/45, 265/40		
		38	ZP568F	100-243	235/45, 245/45, 255/45		
	B43	33+35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45, 265/40, 275/40HA		
		38	ZP568F	100-243	235/45, 245/45, 255/40, 255/45, 265/40HA, 275/40HA		
	AC-518	33	F95	100-243	235/45, 245/45		
	AF18	40	AV1	100-190	235/45, 245/45, 265/40		
	FMI07 Atena	33	F95	100-243	235/45, 245/45, 255/45, 265/40, 265/45		
	Oxigin 18	35	ZP568F	100-190	255/40, 255/45		nicht Bremse 360mm
	Oxigin 25	35	ZP568F	100-190	255/40, 255/45		
	Oxigin 28	35	ZP568F	100-243	235/45, 245/45, 255/40, 255/45, 265/40, 275/40HA		
9,5 x 20	B37C	32	ZP561F	100-190	255/40, 255/45		
	B42	35	ZP561F	100-243	255/40, 255/45		

8,5 x 21	B41	30+34+ 37+40	ZP568F	100-243	245/40, 255/40		ET40 nur 245/40
	B43	30+34+ 37	ZP568F	100-243	245/40, 255/35, 255/40		
9 x 21	B32	30+39	ZP561F	100-190	245/40, 255/35, 255/40		
		30+40	ZP561F	100-190	245/40		
	B43	36	ZP568F	100-243	245/40, 255/35, 255/40, 275/35HA		
	AF18	30+44	AV1	100-190	245/40, 255/35, 255/40		
		30+45	AV1	100-190	245/40, 255/35, 255/40, 275/35		
	CA 17	30+35	ZP561F	100-243	245/40		
9,5 x 21	B41	31+36+ 48	ZP568F	100-243	245/40		
	B43	36	ZP568F	100-243	245/40, 255/35, 255/40, 275/35HA		
9 x 22	AF18	30+49	AV1	100-190	255/30, 255/35, 265/30		

GLC 43 AMG		ab 2016		204X	5/112	66.6	e1*2001/116*0480*18-.. (FIN: WDC253...)	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	B40	VA 38	ZP561F	270, 287	VA 235/50, 235/55 , 255/45			
9 x 19		HA 20			HA 235/55M+S, 255/45, 255/50 , 275/45, 285/45			
8 x 19	RC27	38	-	270	235/55			Orig.-Verschr., nur M+S
	RC32	38	-	270-287	235/55			Orig.-Verschr.
	RC34	38	ZP568F	270-287	235/50, 235/55 , 245/50, 255/45			nur M+S
	B40	38	ZP561F	270, 287	235/50, 235/55 245/50, 255/45			nur M+S
	B43	38	ZP568F	270-287	235/50, 235/55 245/50, 255/45, 255/50HA			nur M+S
	CA 17	38	OX556F	270	235/55			nur M+S
	CA 19	38	OX556F	270-287	235/55			nur M+S
	CA 24	38	OX556F	270-287	235/55			nur M+S
	RC29	35	ZP561F	270	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	RC32	32,5+34	-	270-287	235/50, 235/55, 245/50, 255/45, 255/50			Orig.-Verschr., nur M+S
	B24	35	ZP561F	270	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	B38	35	ZP561F	270	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	B40	32,5	-	270, 287	235/50, 235/55, 245/50, 255/45			Orig.-Verschr., nur M+S
	B43	32,5	-	270, 287	235/50, 235/55, 245/50, 255/45			Orig.-Verschr., nur M+S
		34	ZP568F	270, 287	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	AC-518	38	F95	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			Orig.-Verschr., nur M+S
AC-521	35	AV1	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			nur M+S	
FMI07 Atena	39	F95	270-287	235/50, 235/55, 245/50, 255/45			nur M+S	
8,5 x 19	D17	38	-	270	235/50, 235/55, 255/45			Orig.-Verschr. für Alufelgen, nur M+S
	RC25	38	-	270	235/50, 235/55, 255/45			Orig.-Verschr. für Alufelgen, nur M+S
	RC32	35,5	-	270-287	235/50, 235/55, 245/50, 255/45, 275/45			Orig.-Verschr., nur M+S
	B32	34,5	ZP561F	270	235/50, 235/55, 245/50, 255/45			nur M+S
	B37	32+35	ZP561F	270	235/50, 235/55, 245/50, 255/45			nur M+S
	B41	35,5+36	ZP568F	270-287	235/50, 235/55, 245/50, 255/45, 275/45			nur M+S
		39	ZP568F	270-287	235/50, 235/55, 245/50, 255/45			nur M+S
	B42	30	ZP561F	270, 287	235/50, 235/55, 255/45			nur M+S
	B43	40	ZP568F	270, 287	235/50, 235/55, 255/45			bis 235/55 nur M+S
	B44	30	ZP561F	270, 287	235/50, 235/55, 255/45			nur M+S
		35	ZP561F	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			nur M+S
	AF18	30	AV1	270	235/50, 235/55, 255/45			nur M+S
	AF20	30	AV1	270, 287	235/50, 235/55, 255/45			nur M+S
	FMI07 Atena	28	F95	270-287	235/50, 235/55, 255/45			nur M+S
	Oxigin 28	30	ZP569F	270, 287	235/50, 235/55, 255/45			nur M+S
	8 x 20	B38	35	ZP568F	270	235/45, 245/45, 255/45		
B43		27+30	ZP568F	270, 287	235/45, 245/45, 255/45			nur M+S
		39	ZP568F	270, 287	235/45, 245/45, 255/45			nur M+S
8,5 x 20	B43	40	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	RC29	40	ZP561F	270	235/45, 245/45, 255/40, 255/45			nur M+S
	FMI12 Kari	40	-	270-287	255/45			Orig.-Verschr.
	RC34	38	ZP568F	270-287	235/45, 245/45, 255/40, 255/45			nur M+S
	B32	40	ZP561F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	B41	35	ZP568F	270-287	235/45, 245/45, 255/40, 255/45, 265/45			nur M+S
	B42	30	ZP561F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	B43	34,5	-	270, 287	235/45, 245/45, 255/40, 255/45			Orig.-Verschr., nur M+S
		35	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	B44	30+35	ZP561F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	AC-518	32	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	AC-521	32	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	AC-M10	30	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
		40	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
	AF18	32	AV1	270	235/45, 245/45, 255/40, 255/45			nur M+S
	FMI07 Atena	39	F95	270-287	235/45, 245/45, 255/40, 255/45			nur M+S
	B41	33	ZP568F	270-287	235/45, 245/45, 255/40, 255/45, 265/40, 265/45			bis 245/45 nur M+S
		35	ZP568F	270-287	235/45, 245/45, 255/40, 255/45, 265/40			bis 245/45 nur M+S

9 x 20		38	ZP568F	270-287	235/45, 245/45, 255/40, 255/45		bis 245/45 nur M+S
	B43	33	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45, 265/40, 275/40HA		
		35+38	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45, 265/40		245/45 nur M+S
	AF18	33	AV1	270	235/45, 245/45, 255/40, 255/45, 265/40		
	FMI07 Atena	33	F95	270-287	235/45, 245/45, 255/40, 255/45, 265/40, 265/45		bis 245/45 nur M+S
9,5 x 20	Oxigin 28	35	ZP569F	270, 287	235/45, 245/45M+S, 255/40, 255/45, 265/40		
	B37C	32	ZP561F	270	255/40, 255/45		
8,5 x 21	B42	35	ZP561F	270, 287	255/40, 255/45		
9,5 x 21	B41	VA 40	ZP568F	270-287	VA 245/40M+S, 255/35, 255/40		Orig.-Verschr.
9,5 x 21		HA 22			HA 245/40M+S, 255/35, 255/40, 275/35, 285/35		
8,5 x 21	B41	30+34+37+40	ZP568F	270-287	245/40, 255/35, 255/40		nur M+S, ET40 nicht 255/40
	B43	30+34+37	ZP568F	270, 287	245/40, 255/35, 255/40		nur M+S
9 x 21	B32	30	ZP561F	270	245/40, 255/35, 255/40, 265/35		bei 265/35 ✖
	B43	36	ZP568F	270, 287	245/40M+S, 255/35, 255/40		
	AF18	30+37	AV1	270	245/40M+S, 255/35, 255/40		
9,5 x 21	B41	31	ZP568F	270-287	245/40M+S		
		36	ZP568F	270-287	245/40M+S, 255/35		
9 x 22	AF18	35	AV1	270	255/30, 255/35, 265/30		

GLC 43 AMG Coupé		ab 2016		204X	5/112	66.6	e1*2001/116*0480*18-... (FIN: WDC253...)	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	B40	VA 38	ZP561F	270, 287	VA 235/50, 235/55 , 245/50, 255/45			
9 x 19		HA 20			HA 235/55M+S, 255/45, 255/50 , 275/45, 285/45			
8 x 19	RC27	38	-	270	235/55			Orig.-Verschr., nur M+S
	RC32	38	-	270-287	235/55			Orig.-Verschr.
	RC34	38	ZP568F	270-287	235/50, 235/55 , 245/50, 255/45			nur M+S
	B40	38	ZP561F	270, 287	235/50, 235/55 245/50, 255/45			
	B43	38	ZP568F	270, 287	235/50, 235/55 245/50, 255/45, 255/50HA			nur M+S
	CA 17	38	OX556F	270	235/55			nur M+S
	CA 19	38	OX556F	270-287	235/55			nur M+S
	CA 24	38	OX556F	270-287	235/55			nur M+S
	RC32	32,5+34	-	270-287	235/50, 235/55, 245/50, 255/45, 255/50			Orig.-Verschr., nur M+S
	B24	35	ZP561F	270	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	B38	35	ZP561F	270	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	B40	32,5	-	270, 287	235/50, 235/55, 245/50, 255/45			Orig.-Verschr., nur M+S
	B43	32,5	-	270, 287	235/50, 235/55, 245/50, 255/45			Orig.-Verschr., nur M+S
		34	ZP568F	270, 287	235/50, 235/55, 245/50, 255/45, 255/50			nur M+S
	AC-518	38	F95	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			Orig.-Verschr., nur M+S
	AC-521	35	AV1	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			nur M+S
FMI07 Atena	39	F95	270-287	235/50, 235/55, 245/50, 255/45			nur M+S	
8,5 x 19	D17	38	-	270	235/50, 235/55, 255/45, 255/50HA			Orig.-Verschr. für Alufelgen, nur M+S
	RC25	38	-	270	235/50, 235/55, 255/45, 255/50HA			Orig.-Verschr. für Alufelgen, nur M+S
	RC32	35,5	-	270-287	235/50, 235/55, 245/50, 255/45, 275/45			Orig.-Verschr., nur M+S
	B32	34,5	ZP561F	270	235/50 235/55, 245/50, 255/45			nur M+S
	B37	35	ZP561F	270	235/50 235/55, 245/50, 255/45			nur M+S
	B41	35,5+36	ZP568F	270-287	235/50, 235/55, 245/50, 255/45, 275/45			nur M+S
		39	ZP568F	270-287	235/50, 235/55, 245/50, 255/45			nur M+S
	B42	30	ZP561F	270, 287	235/50, 235/55, 255/45			nur M+S
	B43	40	ZP568F	270, 287	235/50, 235/55, 255/45, 255/50HA			nur M+S
	B44	30	ZP561F	270, 287	235/50, 235/55, 255/45			nur M+S
		35	ZP561F	270, 287	235/50, 235/55, 245/50, 255/45, 255/50HA			nur M+S
	AF18	30	AV1	270	235/50 235/55, 255/45			nur M+S
	AF20	30	AV1	270, 287	235/50 235/55, 255/45			nur M+S
	FMI07 Atena	28	F95	270-287	235/50, 235/55, 255/45			nur M+S
	Oxigin 28	30	ZP568F	270, 287	235/50, 235/55, 255/45			nur M+S
	8,5 x 20	B43	40	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45		
RC29		40	ZP561F	270	235/45, 245/45, 255/40, 255/45			nur M+S
RC34		38	ZP568F	270-287	235/45, 245/45, 255/40, 255/45			nur M+S
B32		40	ZP561F	270	235/45, 245/45, 255/40, 255/45			nur M+S
B41		35	ZP568F	270-287	235/45, 245/45, 255/40, 255/45, 265/45			nur M+S
B42		30	ZP561F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
B43		34,5	-	270, 287	235/45, 245/45, 255/40, 255/45			Orig.-Verschr., nur M+S
		35	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
B44		30+35	ZP561F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
AC-518		32	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
AC-521		32	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
AC-M10		30	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
		40	AV1	270, 287	235/45, 245/45, 255/40, 255/45			nur M+S
AF18		32	AV1	270	235/45, 245/45, 255/40, 255/45			nur M+S
FMI07 Atena		39	F95	270-287	235/45, 245/45, 255/40, 255/45			nur M+S
		B41	35	ZP568F	270-287	235/45, 245/45, 255/40, 255/45, 265/40		

9 x 20		38	ZP568F	270-287	235/45, 245/45, 255/40, 255/45		bis 245/45 nur M+S
	B43	33+35	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45, 265/40, 275/40HA		
		38	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45, 265/40HA, 275/40HA		
	AF18	33	AV1	270	235/45, 245/45, 255/40, 255/45, 265/40		
	FMI07 Atena	33	F95	270-287	235/45, 245/45, 255/40, 255/45, 265/40, 265/45		bis 245/45 nur M+S
9,5 x 20	Oxigin 28	35	ZP568F	270, 287	235/45, 245/45, 255/40, 255/45, 265/40, 275/40HA		
	B37C	32	ZP561F	270	255/40, 255/45		
8,5 x 21	B42	35	ZP561F	270, 287	255/40, 255/45		
	B41	VA 40 HA 22	ZP568F	270-287	VA 245/40M+S, 255/35, 255/40 HA 245/40M+S, 255/35, 255/40, 275/35, 285/35		Orig.-Verschr.
8,5 x 21	B41	30+34+ 37	ZP568F	270-287	245/40, 255/35, 255/40		nur M+S, ET40 nicht 255/40
	B43	30+34+ 37	ZP568F	270, 287	245/40, 255/35, 255/40		nur M+S
9 x 21	B32	30	ZP561F	270	245/40, 255/35, 255/40, 265/35		bei 265/35 ✖
	B43	36	ZP568F	270, 287	245/40, 255/35, 255/40, 275/35HA		
	AF18	37	AV1	270	245/40, 255/35, 255/40, 275/35		
9,5 x 21	B41	31	ZP568F	270-287	245/40M+S		
		36	ZP568F	270-287	245/40M+S, 255/35		
9 x 22	AF18	35	AV1	270	255/30, 255/35, 265/30		

GLC 63 AMG		ab 2016		5/112	66,6	e1*2007/46*0598*16-..., (FIN: WDC1660...)	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 19	RC34	27	ZP568F	350-375	235/55		nur M+S
8,5 x 19	B41	20+21+ 28	ZP568F	350-375	235/55		nur M+S
	FMI07 Atena	28	F95	350-375	235/55		nur M+S, nicht Bremse 402x39mm
	FMI11 Elatha	21	F95	350-375	235/55		nur M+S
9 x 19	B41	21	ZP568F	350-375	265/45		
8,5 x 20	RC34	30	ZP568F	350-375	235/45		nur M+S
	B41	20	ZP568F	350-375	235/45		nur M+S
9 x 20	B41	20	ZP568F	350-375	235/45M+S, 255/45, 265/40, 265/45		
	FMI07 Atena	20	F95	350-375	235/45M+S, 255/45, 265/40, 265/45		
	FMI11 Elatha	20	F95	350-375	235/45M+S, 255/45, 265/40, 265/45		
9 x 21	FMI07 Atena	26	F95	350-375	245/40, 255/40, 265/35, 265/40, 275/35		

Kombinationen

8 x 19	FMI08 Thoe	26	F31	350-375	VA 235/55+HA 255/50 od. VA 245/55+HA 265/50		
9 x 19		20					
9,5 x 20	B32	25	ZP568F		VA265/45+HA295/40		Ausführung "D3", TÜV i.V.
10,5 x 20		20					

GLC NEU		Sommer 2022		R2CGLC		5/112		66,6		e1*2018/858*00186*..				
Sensor - Brocksens 8														
Dimension		Design		ET	KIT	KW	Reifendimension			Info				
8 x 18		RC32		VA 32,5 HA 30	-		VA 235/60+HA 255/55				Orig.-Verschr., i.V.			
9 x 18														
8 x 18		RC27		32,5	-	120-270	235/60				Orig.-Verschr., incl. Coupe			
							120-270	235/60, 245/55, 255/55HA, 285/50HA				Orig.-Verschr. für Alufelgen, incl. Coupe, mit AMG-Line Verbreiterungen		
								235/60, 245/55, 255/55HA				Orig.-Verschr. für Alufelgen, incl. Coupe		
		RC32		32,5	-	120-270	235/60, 245/55				Orig.-Verschr., incl. Coupe			
							33	-	145-198	VA+HA 235/60, 245/55 od.				Orig.-Verschr.
										VA 235/60+HA 255/55				
		B42		30	ZP568F	120-270	235/60, 245/55, 255/55HA, 285/50HA				mit AMG-Line Verbreiterungen, incl. Coupe, nur Bremse 370mm			
							235/60, 245/55				incl. Coupe, nur Bremse 370mm			
				35	ZP568F	120-270	235/60, 245/55, 255/55HA, 285/50HA				mit AMG-Line Verbreiterungen, incl. Coupe, nur Bremse 370mm			
							235/60, 245/55, 255/55HA				incl. Coupe, nur Bremse 370mm			
		B44		30	ZP568F	120-270	235/60, 245/55, 255/55HA, 285/50HA				mit AMG-Line Verbreiterungen, incl. Coupe			
							235/60, 245/55				incl. Coupe			
				35	ZP568F	120-270	235/60, 245/55, 255/55HA, 285/50HA				mit AMG-Line Verbreiterungen, incl. Coupe			
							235/60, 245/55, 255/55HA				incl. Coupe			
		AC-M10		30	AV4	145-198	VA+HA 235/60, 245/55 od.				mit AMG-Line Verbreiterungen, nur Bremse 370mm			
							VA 255/55+HA 285/50							
						145-198	235/60, 245/55				nur Bremse 370mm			
							235/60, 245/55				nur Mild Hybrid			
		FMI08 Thoe		34	F31	120-198	235/60, 245/55							
FMI11 Elatha		26	F95	145-198	VA+HA 235/60				nicht Bremse 370x36mm VA u. 360x26mm HA					
					VA 235/60+HA 255/55									

8 x 19	RC34	VA 32,5	-	120-270	VA 235/55+HA 255/50		Orig.-Verschr., Mild Hybrid
9 x 19		HA 30					
8 x 19	B40	VA 32,5	-	120-270	VA 235/55+HA 255/50		Orig.-Verschr., mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupe
9 x 19		HA 30					
8 x 19	B40	VA 32,5	-	120-270	VA 235/55, 245/50		Orig.-Verschr., mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupe
9 x 19		HA 30			HA 255/50, 275/45, 285/45		
8 x 19	RC32	32,5	-	120-270	235/55, 245/50		Orig.-Verschr., nur Mild Hybrid
	RC34	32,5	-	120-270	235/55		Orig.-Verschr., nur Mild Hybrid
				120-270	235/55, 245/50		Orig.-Verschr., Mild Hybrid
	B40	32,5	-	120-270	235/55, 245/50, 255/50HA		Orig.-Verschr., auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B43	32,5	-	120-270	235/55		Orig.-Verschr. für Alufelgen, incl. Coupe
				120-270	235/55, 245/50, 255/50HA		
	Oxigin 29	32	ZP568F	120-170	235/55, 245/50, 255/50		incl. Coupe, nur Bremse 370mm
	RC29	35	ZP568F	145-198	235/55, 245/50, 255/50HA		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	RC34	30,5	-	120-270	235/55, 245/50		Orig.-Verschr., Mild Hybrid, ohne Verbreiterung
		34	-	120-270	235/55, 245/50, 255/50		Orig.-Verschr., Mild Hybrid, mit Verbreiterung
	CA 24	30	ZP569F	120-270	235/55, 245/50, 255/50		Orig.-Verschr., Mild Hybrid
	FMI08 Thoe	26	F31	120-198	VA+HA 235/55 od.		nur Mild Hybrid
					VA 235/55+HA 255/50		
8,5 x 19	RC32	35,5	-	120-170	VA+HA 235/55 od.		Orig.-Verschr., nur Mild Hybrid
					VA 235/55+HA 255/50		
	B32	34,5	ZP568F	145-198	VA 235/55+HA 255/50		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B36	30	ZP568F	120-270	235/55, 245/50, 255/50HA, 265/45, 275/45HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupe
					235/55, 245/50, 265/45		nur Bremse 370mm, incl. Coupe
		35	ZP568F	120-270	VA 235/55+HA 255/50		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupe
	B37	35	ZP568F	145-198	VA 235/55+HA 255/50		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B41	35,5+36	ZP559F	120-270	VA+HA 235/55 od.		nur Mild Hybrid, nur Bremse 370mm
					VA 235/55+HA 255/50		
	B42	30	ZP568F	145-198	245/50, 265/45, 275/45HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B44	30	ZP568F	120-270	235/55, 245/50, 255/50HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupe
		35	ZP568F	120-270	VA 235/55+HA 255/50		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	AC-M10	30	AV4	120-270	235/55, 245/50, 255/50HA, 265/45, 275/45HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm
	CA 20	35	ZP568F	120-270	VA 235/55+HA 255/50		mit AMG-Line Verbreiterungen
	CA 23	30	ZP568F	145-198	235/55, 245/50, 255/50HA, 265/45, 275/45HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm
	Oxigin 28	30	ZP568F	145-198	235/55, 245/50, 255/50HA, 265/45, 275/45HA		mit AMG-Line Verbreiterungen, nur Bremse 370mm
8 x 20	B38	35	ZP568F	145-198	235/50, 245/45, 255/45		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B43	30	ZP568F	145-198	235/50, 245/45, 255/45		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
8,5 x 20	B43	34,5	-	120-270	235/50, 245/45, 255/45 , 265/45		Orig.-Verschr. für Alufelgen, auch mit AMG-Line Verbreiterungen, incl. Coupe, nur Bremse 370mm
	RC36	34,5	-	120-270	255/45		Orig.-Verschr. für Alufelgen, auch mit AMG-Line Verbreiterungen, incl. Coupe
		33	-	120-270	235/50, 245/45, 255/45, 265/45HA		Orig.-Verschr. für Alufelgen, auch mit AMG-Line Verbreiterungen, incl. Coupe
	B41	28	ZP559F	120-270	235/50, 245/45, 255/45		mit Verbreiterungen, ohne Verbreiterungen ist nur 245/45 auflagenfrei!
	B43	30	ZP568F	145-198	235/50, 245/45, 255/45, 265/45		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm
	B44	30+35	ZP568F	120-270	235/50, 245/45, 255/45, 265/45		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupé
	AC-M10	30	ZP568F	120-270	235/50, 245/45, 255/45, 265/45		auch mit AMG-Line Verbreiterungen, nur Bremse 370mm, incl. Coupé
9 x 20	RC36	32	-	120-270	245/45, 255/45, 275/40HA		Orig.-Verschr. für Alufelgen
	B37	29	ZP568F	145-198	245/45		nur Bremse 370mm
	B41	33	ZP559F	120-270	235/50, 245/45, 255/45		nur Mild Hybrid
		35	ZP559F	120-270	245/45		
	AC-522	25	AV1	145-198	235/45, 245/45		mit Radhausverbreiterungen

		33	AV1	145-198	245/45, 255/45, 265/40, 265/45		mit Radhausverbreiterungen
8,5 x 21	B41	30	ZP559F	120-270	235/45, 245/40, 255/40		
		34	ZP559F	120-270	235/45, 245/40, 255/40		
	B43	30+34	ZP568F	120-270	235/45, 245/40, 255/40		nur Bremse 370mm
9 x 21	CA 20	25	ZP568F	120-270	245/40, 255/40		nur Bremse 370mm
		30	ZP568F	120-270	235/45, 245/40, 255/40		nur Bremse 370mm
	FMI07 Atena	33	F95	120-270	245/40, 255/40		nur Mild Hybrid

Kombinationen

8,5 x 20	B42	VA 30	ZP568F	120-270	VA 235/50, 245/45		
9,5 x 20		HA 25			HA 255/45, 265/45, 275/40		
8,5 x 20	CA 17	VA 35	ZP568F	120-270	VA 235/50, 255/45		nur an Fahrzeugen mit Luftfederung zulässig
9,5 x 20		HA 36			HA 255/45, 265/40, 275/40, 285/40		
8,5 x 21	B43	VA 34	ZP568F	120-270	VA 235/45, 245/40, 255/40		incl. Coupé, nur Bremse 370mm, ohne AMG-Line
9,5 x 21		HA 36			HA 255/40, 265/40, 275/35, 285/35		Verbreiterungen ab 275/35 ✖

GLC PHEV Plug-in Hybrid NEU			R2CGLC		5/112	66,6	e1*2018/858*00186*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	VA 32,5	-	145-185	VA 235/55+HA 255/50		Orig.-Verschr., incl. Coupe	
9 x 19		HA 30						
8 x 19	B40	VA 32,5	-	145-185	VA 235/55+HA 255/50		Orig.-Verschr., nur Bremse 370mm, incl. Coupe	
9 x 19		HA 30						
8 x 19	B40	VA 32,5	-	145-185	VA 235/55, 245/50		Orig.-Verschr., nur Bremse 370mm, incl. Coupe	
9 x 19		HA 30			HA 255/50, 275/45, 285/45			
9 x 20	RC36	32	-	145-185	VA 245/45+HA 275/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm	
	B37	29	ZP568F	145-185	VA 245/45+HA 275/40		nur Bremse 370mm	
	B41	33+35	ZP559F	145-185	VA 235/45+HA 265/40, VA 245/45+HA 275/40			
	B43	33	ZP568F	145-185	VA 245/45+HA 275/40		nur Bremse 370mm	
	CA 23	30	ZP568F	145-185	VA 245/45+HA 275/40		nur Bremse 370mm	
9 x 21	CA 20	25	ZP568F	145-185	VA 235/45+HA 255/40 od. HA 265/40		nur Bremse 370mm	
		30	ZP568F	145-185	VA 235/45+HA 255/40 od. HA 265/40, VA 245/40+HA 275/35		nur Bremse 370mm	

Kombinationen

8,5 x 21	B43	VA 34	ZP568F	145-185	VA 235/45, 245/40, 255/40		incl. Coupé, nur Bremse 370mm
9,5 x 21		HA 36			HA 255/40, 265/40, 275/35, 285/35		

GLC 43 4matic		NEU		ab 2023		R2CGLC	5/112	66,6	e1*2018/858*00186*..	
Sensor - Brocksens 8										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
9 x 20	RC36	32	-	310	255/45, 265/45				Orig.-Verschr. für Alufelgen, nur M+S, incl. Coupe	
9,5 x 20	RC36	32,1	-	310	255/45M+S, 265/45, 285/40				Orig.-Verschr. für Alufelgen, incl. Coupe	

GLC AMG 63S E Performance		NEU		Sommer 2022		R2CGLC	5/112	66,6	e1*2018/858*00186*..	
Sensor - Brocksens 8										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		

<u>Kombinationen</u>										
9,5 x 21	B41	VA 31	ZP568F	350	VA 265/40				nicht Keramikbremse mit 420x40mm	
10,5 x 21		HA 31			HA 295/35					

GLE (siehe Konfigurator)		ab 2015		166	5/112	66,6	e1*2007/46*0598*16-..., (FIN: WDC1660...)	
--------------------------	--	---------	--	-----	-------	------	---	--

GLE Coupé		ab 2015		166	5/112	66,6	e1*2007/46*0598*16-..., (FIN: WDC292...)	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 19	D17	VA 57 HA 38	-	190-245	VA+HA 265/55, 275/55			Orig.-Verschr. für Alufelgen, nur M+S
	RC25	VA 57 HA 38	-	190-245	VA+HA 265/55, 275/55			Orig.-Verschr. für Alufelgen, nur M+S
8,5 x 20	RC29	VA 53 HA 29	ZP561F	190-245	VA+HA 275/50			

weitere Dimensionen/Designs siehe Konfigurator

GLE AMG 63/s Coupé (siehe Konfigurator)				ab 2015	166, 166AMG	5/112	66,6	e1*2007/46*0598*16-..., e1*2007/46*0826*07-... (FIN: WDC292...)
GLE 450 / 43-AMG Coupé (siehe Konfigurator)					166	5/112	66,6	e1*2007/46*0598*16-..., (FIN: WDC292...)
GLE 500 Coupé					166	5/112	66,6	e1*2007/46*0598*16-..., (FIN: WDC292...)
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension			Info

Kombinationen

8,5 x 19	D17	VA 57 HA 38	-	335	VA + HA 265/55 M+S, 275/55		Orig.-Verschr. für Alufelgen, nur M+S
10 x 22	B32	VA 55	ZP561F	335	VA 275/40, 285/40		
11 x 22		HA 40			HA 275/40, 285/40, 325/35		

GLE	ab 10.2019	H1GLE	5/112	66,6	e1*2007/46*1885*..
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
-----------	--------	----	-----	----	-----------------	------

Serienschrauben 15x1,25, Kugelbund, Länge 44,2mm

8 x 19	CA 24	43	OX565F	180-270	255/50, 255/55		nicht Brembo Bremse u. nicht Bremse 400mm
8,5 x 19	RC25	VA+HA 55	-	180-210	235/55, 245/50, 245/55		Orig.-Verschr., Ausführung "D13", ohne AMG-Line, HA ✖
				180-270	255/50, 265/50, 275/45		
		VA 55	-	180-210	VA+HA 235/55, 245/50, 245/55		Orig.-Verschr., Ausführung "D13", ohne AMG-Line, HA ✖
		HA 42		180-270	VA+HA 255/50, 265/50, 275/45		
	B41	VA+HA 57	-	180-270	VA+HA 235/55, 245/55, 255/50		Orig.-Verschr.
8,5 x 20	B41	VA+HA 61,5	-	180-270	VA+HA 265/45		Orig.-Verschr.
		VA 55,5 HA 42	-	143-360	VA+HA 275/50		Orig.-Verschr., nicht 6-Kolben Festsattel mit Bremse 400x38mm, nur zulässig wenn Serie 275/.. eingetragen sind
	B43	VA 55,5 HA 42	-	143-360	VA+HA 275/50		Orig.-Verschr., nicht Hybrid, nicht Festsattelbremse, nur zulässig wenn Serie 275/50 R20 eingetragen sind
		VA 55,5 HA 42	-	143-360	VA+HA 275/50, 285/50		Orig.-Verschr., nicht Hybrid, nicht Festsattelbremse, nur zulässig wenn Serie 275/50 R20 eingetragen sind
	B32	VA 55,5 HA 42	-	180-270	275/50, 285/50		Orig.-Verschr., Ausführung "D13", auflagenfrei nur mit AMG-Line, nur zulässig wenn Serie 275/50 R20 eingetragen sind
	CA 19	45	OX565F	180-270	265/45		incl. Hybrid
9 x 20	B40	VA 57 HA 44	-	143-360	275/50, 285/45		Orig.-Verschr., Ausführung "D13", auflagenfrei nur mit AMG-Line, nicht Festsattelbremse, nur zulässig wenn Serie 275/50 R20 eingetragen sind
	B41	VA 57 HA 44	-	143-360	VA+HA 275/50		Orig.-Verschr., nicht 6-Kolben Festsattel mit Bremse 400x38mm, nur zulässig wenn Serie 275/.. eingetragen sind
	B43	VA 57 HA 44	-	143-380	VA+HA 275/50		Orig.-Verschr., nicht Festsattelbremse, nur zulässig, wenn Serie 275/50 R20 eingetragen ist
		VA 57 HA 44	-	143-360	VA+HA 275/50, 285/45		Orig.-Verschr., ohne Coupe, nicht Festsattelbremse
	B41	VA 51 HA 47	-	320-330	VA 275/45+HA 315/40		Orig.-Verschr., auch für Hybrid, nur zulässig wenn Serie 275/...eingetragen ist
		VA 54 HA 49	-	143-380	VA 275/45+HA 315/40		Orig.-Verschr., auch für Hybrid, nur zulässig wenn Serie 275/...eingetragen ist
10 x 21	B43	VA 54 HA 49	-	143-360	VA 275/45+HA 315/40		Orig.-Verschr., nicht Festsattelbremse, nur wenn Serie 275/50 R20 eingetragen ist
11 x 21							
10 x 21	B43	VA 54 HA 49	-	143-360	VA 275/45, 285/40, 285/45, 295/40		Orig.-Verschr., nicht Festsattelbremse, nur wenn Serie 275/50 R20 eingetragen ist
11 x 21					HA 285/40, 295/40, 315/40, 325/40		

Kombinationen

10 x 21	B41	VA 51	-	143-380	VA 275/45+HA 315/40 od. VA 285/45+HA 325/40		Orig.-Verschr., mit Radhausverbr., mit Serienreifen ab 275/..
11 x 21		HA 47					
9,5 x 22	AF18	VA 37	15x1,25x30	143-360	VA+HA 285/40		VA ✖
10,5 x 22		HA 43					
10 x 22	CA 17	VA 50	OX565F	143-360	VA 285/40+HA 325/35		incl. Hybrid, ✖
11 x 22		HA 40					
10 x 23	AF18	VA 56	-	143-360	VA 285/35+HA 325/30		Orig.-Verschr., auch für Hybrid, HA ✖
11,5 x 23		HA 47					

GLE Coupe	ab 2019	H1GLE	5/112	66,6	e1*2007/46*1885*..
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
-----------	--------	----	-----	----	-----------------	------

Serienschrauben 15x1,25, Kugelbund, Länge 44,2mm

Kombinationen

8,5 x 20	B41	VA 55,5 HA 42	-	143-360	VA+HA 275/50		Orig.-Verschr., nicht 6-Kolben Festsattel mit Bremse 400x38mm
		VA 55,5	-	143-243	VA+HA 275/50		Orig.-Verschr., nicht Hybrid, nicht Festsattelbremse

9 x 20	B43	HA 42	-	143-243	VA+HA 275/50, 285/50		Orig.-Verschr., nicht Hybrid, nicht Festsattelbremse
		VA 55,5					
		HA 42					
9 x 20	B40	VA 57	-	143-243	275/50, 285/45		Orig.-Verschr., Ausführung "D13", auflagenfrei nur mit AMG-Line, nicht Festsattelbremse
		HA 44					
	B41	VA 57	-	143-360	VA+HA 275/50		Orig.-Verschr., nicht 6-Kolben Festsattel mit Bremse 400x38mm
		HA 44					
9 x 20	B43	VA 57	-	143-270	VA+HA 275/50		Orig.-Verschr., nicht Festsattelbremse
		HA 44					
		VA 57					
		HA 44					
10 x 21	B41	VA 51	-	320-330	VA 275/45+HA 315/40		Orig.-Verschr., auch für Hybrid
11 x 21		HA 47					
10 x 21		VA 54			VA 275/45+HA 315/40		Orig.-Verschr., auch für Hybrid
11 x 21		HA 49					
10 x 21	B43	VA 54	-	143-243	VA 275/45+HA 315/40		Orig.-Verschr., nicht Festsattelbremse
11 x 21		HA 49					
10 x 21	B43	VA 54	-	143-380	VA 275/45, 285/40, 285/45, 295/40 HA 285/40, 295/40, 315/40, 325/40		Orig.-Verschr., nicht Festsattelbremse
11 x 21		HA 49					
10 x 23	AF18	VA 56	-	143-360	VA 285/35+HA 325/30		Orig.-Verschr., HA ✖
11,5 x 23		HA 47					

GLE AMG 53		NEU	2024		H1GLE	5/112	66,6	e1*2007/46*1885*..	
Sensor - Brocksens 1									
Dimension		Design		ET	KIT	KW	Reifendimension		Info
9 x 20		B43		VA 57 HA 44	-	320	VA+HA 275/50		 Orig.-Verschr., incl. Coupe, nicht Festsattelbremse

GLE AMG 63, 63S/ Coupe 63, 63S				2020	H1GLE	5/112	66,6	e1*2007/46*1885*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
Serienschrauben 15x1,25, Kugelbund, Länge 44,2mm									

Kombinationen

10 x 21	B41	VA 51	-	420-450	VA 275/45+HA 315/40 od. VA 285/45+HA 325/40		Orig.-Verschr., auch Hybrid
11 x 21		HA 47					

GLS (siehe Konfigurator)	ab 03.16	166	5/112	66,6	e1*2007/46*0598*... (FIN: WDC1668...)		
---	----------	-----	-------	------	---------------------------------------	--	--

GLS 63 AMG (siehe Konfigurator)	ab 2015	166 / 166AMG	5/112	66,6	e1*2007/46*0598*, e1*2007/46*0826*.. (FIN: WDC1668...)		
--	---------	--------------	-------	------	--	--	--

GLS		ab 2019		H1GLE		5/112		66,6		e1*2007/46*1885*..	
Sensor - Brocksens 1											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8,5 x 19	B41	57	-	210-360	275/55				✖		
8,5 x 20	B41	VA 62,6 HA 35,5	-	210-360	VA+HA 275/50				Orig.-Verschr.		
9 x 20	B41	VA 57 HA 44	-	210-360	275/50, 285/45				Orig.-Verschr., ohne Radhausverbr. ✖		
10 x 21	B41	VA 44	-	210-360	VA 275/45+HA 315/40				Orig.-Verschr., auch Hybrid		
11 x 21		HA 42									

Kombinationen

10 x 21	B41	VA 51	-	210-360	VA+HA 295/40		Orig.-Verschr., mit Radhausverbreiterungen, Serie bis 21 Zoll
11 x 21		HA 47					
10 x 23	AF18	VA 56	-	210-360	VA 285/40+HA 325/35		Orig.-Verschr.
11,5 x 23		HA 47					

GLS NEU i.V.	im Laufe 2023						
-----------------------------	---------------	--	--	--	--	--	--

S-Klasse (siehe Konfigurator)	ab 2013	222, 221	5/112	66,6	e1*2007/46*0960*..., e1*2001/116*0335*19-... (FIN: WDD222)		
--	---------	----------	-------	------	--	--	--

S-Klasse (S63, S65 AMG) (siehe Konfigurator)	2014	221 (Model WDD222)	5/112	66,6	e1*2001/116*0335*20-..., e1*2001/116*0396*09-..., ACHTUNG: Achslast beachten		
---	------	--------------------	-------	------	---	--	--

S-Klasse NEU		im Laufe 2022		R2S	5/112	66,6	e1*2007/46*2115*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 18	RC27	32,5	-	210-280	235/55, 245/50		Orig.-Verschr., nur Bremse 370mm	
				210-330	255/50			
	RC32	33	-	210-370	235/55, 245/50, 255/50		Orig.-Verschr., mit Hinterachslenkung bis 4,5°	
				210-370	235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit Hinterachslenkung bis 10°	
	RC34	30	ZP568F	210-370	235/55, 245/50, 255/50		mit Hinterachslenkung bis 4,5°	
				210-370	235/50, 235/55, 245/50, 255/50		mit Hinterachslenkung bis 10°	

	AC-MB6	29	ZP567F	210-280	235/55, 245/50		nur Bremse 370mm, bei 255/50 ✖
				210-330	255/50		
	AC-M10	30	AV4	210-280	235/55, 245/50		nur Bremse 370mm, bei 255/50 ✖
				210-330	255/50		
8 x 19	RC32	32,5	-	210-370	235/50, 245/45, 255/45		Orig.-Verschr., mit Hinterachslenkung bis 4,5°
				210-370	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., mit Hinterachslenkung bis 10°
	RC34	27	ZP567F	210-370	235/50, 245/45, 255/45		mit Hinterachslenkung bis 4,5°
				210-370	235/45, 235/50, 245/45, 255/45		mit Hinterachslenkung bis 10°
		30,5+ 32,5+34	-	210-370	235/50, 245/45, 255/45		Orig.-Verschr., mit Hinterachslenkung bis 4,5°, nicht Bremse 390x36mm u. 390x38mm
				210-370	235/45, 235/50, 245/45, 255/45		mit Hinterachslenkung bis 10°, nicht Bremse 390x36mm u. 390x38mm
		38	ZP568F	210-370	235/50, 245/45, 255/45		mit Hinterachslenkung bis 4,5°, nicht Bremse 390x36mm
				210-370	235/45, 235/50, 245/45, 255/45		mit Hinterachslenkung bis 10°, nicht Bremse 390x36mm
	B40	31+38	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45		
		32,5	-	210-280	235/50, 245/45		Orig.-Verschr., nur Bremse 370mm
				210-330	255/45		
	B43	32,5	-	210-280	235/50, 245/45		Orig.-Verschr., nur Bremse 370mm
				210-330	255/45		
		36	-	210-280	235/50, 245/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
				210-330	255/45		
	CA 24	30	ZP569F	210	235/45, 235/50		nicht Bremse 390mm
				210-370	245/45, 255/45		
		38	-	210	235/50		Orig.-Verschr., nicht Bremse 390mm
				210-370	255/45		
	FMI08 Thoe	26	F31	210-370	235/50, 245/45, 255/45		mit Hinterachslenkung bis 4,5°
				210-370	235/45, 235/50, 245/45, 255/45		mit Hinterachslenkung bis 10°
	FMI14 Jupiter	26	F31	210-370	235/50, 245/45, 255/45		mit Hinterachslenkung bis 4,5°
				210-370	235/45, 235/50, 245/45, 255/45		mit Hinterachslenkung bis 10°
Oxigin 29	32	ZP568F	210-280	235/50, 245/45			
			210-330	255/45		nur Bremse 370mm	
8,5 x 19	B43	VA 31,5	-	210-330	VA 255/45		Orig.-Verschr., nur Bremse 370mm
HA 48,1		HA 285/40					
8,5 x 19	B43	VA 31,5 HA 48,1	-	210-280	VA 245/45		Orig.-Verschr., nur Bremse 370mm
210-330				VA 255/45, 265/45			
210-280				HA 275/40			
210-330				HA 285/40, 295/40			
8,5 x 19	RC34	31,5	-	210-450	255/45		Orig.-Verschr.
	RC32	35,5	-	210-450	235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Hinterachslenkung bis 4,5°
				210-450	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Hinterachslenkung bis 10°
	RC34	31,5	-	210-450	235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Hinterachslenkung bis 4,5°
				210-450	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Hinterachslenkung bis 10°
	B32	34,5	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	B36	30+35	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	B37	35	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	B41	35,5+ 36+39	ZP568F	210-450	235/50, 245/45, 255/45, 265/45		mit Hinterachslenkung bis 4,5°, ET39 nicht Bremse 390x38mm
				210-450	235/45, 235/50, 245/45, 255/45, 265/45		mit Hinterachslenkung bis 10°, ET39 nicht Bremse 390x38mm
	AC-M10	30	AV4	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	CA 20	35	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	CA 23	30	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	FMI11 Elatha	21	F95	210-450	245/45		mit Hinterachslenkung bis 4,5°
				210-450	235/45, 245/45		mit Hinterachslenkung bis 10°
	Oxigin 28	30	ZP568F	210-280	235/50, 245/45		nur Bremse 370mm
				210-330	255/45, 265/45		
	9 x 19	B41	38	ZP568F	210-450	245/45, 255/45, 265/45, 275/40	
210-450					235/45, 245/45, 255/45, 265/40, 265/45, 275/40	mit Hinterachslenkung bis 10°	
CA 24		35	ZP569F	210	235/45		nicht Bremse 390mm
				210-370	245/45, 255/45		
	RC36	33	-	210-280	235/45, 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
				210-330	255/40		
	B41	28+35	ZP568F	210-450	235/45, 245/40, 255/40		
				210-280	235/45, 245/40		
		34,5	-	210-330	255/40		Orig.-Verschr., nur Bremse 370mm

8,5 x 20	B43	30	ZP568F	210-280	235/45, 245/40		nur Bremse 370mm
				210-330	255/40		
		38,5	-	210-330	255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
	AC-M10	30	ZP568F	210-280	235/45, 245/40		nur Bremse 370mm
				210-330	255/40		
	CA 19	32	ZP568F	210	245/40		nur Bremse 390mm
9 x 20	B43	VA 34	-	210-330	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
9 x 20	B43	VA 34	-	210-330	VA 235/45, 245/40, 255/40, 265/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 255/40, 265/40, 275/35, 285/35, 295/35		
9 x 20	RC36	32	-	210-280	235/45, 245/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
				210-330	255/40, 265/35, 265/40		
	B37	29	ZP568F	210-280	235/45, 245/40		nur Bremse 370mm
				210-330	255/40		
		37	ZP568F	210-280	235/45, 245/40, 265/40HA, 275/35HA		max. 4,5° Hinterachslenkung, nur Bremse 370mm
				210-330	255/40		
		37	ZP568F	210-280	235/45, 245/40		max. 10° Hinterachslenkung, nur Bremse 370mm
				210-330	255/40		
	B41	33	ZP568F	210-450	235/45, 245/40, 255/40, 265/40		mit Hinterachslenkung bis 4,5°
				210-450	235/45, 245/40, 255/40, 265/35, 265/40		mit Hinterachslenkung bis 10°
		35	ZP568F	210-450	235/45, 245/40, 255/40, 265/40, 275/35		mit Hinterachslenkung bis 4,5°
				210-450	235/45, 245/40, 255/40, 265/35, 265/40, 275/35		mit Hinterachslenkung bis 10°
		38	ZP568F	210-450	235/45, 245/40, 255/40, 265/40, 275/35		mit Hinterachslenkung bis 4,5°
				210-450	235/45, 245/40, 265/35, 265/40, 275/35		mit Hinterachslenkung bis 10°
	B43	33	ZP568F	210-280	235/45, 245/40		nur Bremse 370mm
				210-330	255/40, 265/35, 265/40		
	AC-522	25	AV1	210	245/40		nur Bremse 390mm
		33	AV1	210	245/40		nur Bremse 390mm
				210-370	255/40		
	CA 20	35	ZP568F	210-280	235/45, 245/40, 275/35HA		ohne Hinterachslenkung u. max. 4,5°
				210-330	255/40, 265/35, 265/40		Hinterachslenkung, nur Bremse 370mm
			ZP568F	210-280	235/45, 245/40		max. 10° Hinterachslenkung, nur Bremse 370mm
				210-330	255/40, 265/35, 265/40		
	CA 23	38	ZP568F	210-280	235/45, 245/40HA, 275/35HA		ohne Hinterachslenkung u. max. 4,5°
				210-330	255/40, 265/35, 265/40		Hinterachslenkung, nur Bremse 370mm
			ZP568F	210-280	235/45, 245/40		max. 10° Hinterachslenkung, nur Bremse 370mm
				210-330	255/40		
	FMI11 Elatha	34	F95	210-450	235/45, 245/40, 255/40, 265/40, 275/35		mit Hinterachslenkung bis 4,5°
				210-450	235/45, 245/40, 255/40, 265/35, 265/40, 275/35		mit Hinterachslenkung bis 10°
	Oxigin 28	35	ZP568F	210-280	235/45, 245/40, 275/35HA		ohne Hinterachslenkung u. max. 4,5°
				210-330	255/40, 265/35, 265/40		Hinterachslenkung, nur Bremse 370mm
			ZP568F	210-280	235/45, 245/40		max. 10° Hinterachslenkung, nur Bremse 370mm
				210-330	255/40, 265/35, 265/40		
8,5 x 21	B41	30+34+37	ZP568F	210-450	255/35		
	B43	30	ZP568F	210-330	255/35		nur Bremse 370mm
		34+37	ZP568F	210-330	255/35		nur Bremse 370mm
9 x 21	CA 20	37	ZP568F	210-280	VA 245/35+HA 275/30		ohne Hinterachslenkung u. max. 4,5°
				210-330	VA+HA 255/35		Hinterachslenkung, nur Bremse 370mm
				210-330	255/35		max. 10° Hinterachslenkung, nur Bremse 370mm
	FMI07 Atena	33	F95	210-450	255/35, 265/35		
9 x 21		40	F95	210-150	255/35		
9 x 21	B43	VA 34	ZP568F	210-330	VA 255/35+HA 285/30		nur Bremse 370mm
10 x 21		HA 48					
9 x 21	B43	VA 34	ZP568F	210-280	VA 245/35		nur Bremse 370mm
				210-330	VA 255/35, 265/35		
				210-280	HA 275/30		
10 x 21				210-330	HA 285/30, 295/30		
9,5 x 21	B41	31	ZP568F	210-450	255/35		
		36	ZP568F	210-450	255/35, 265/35		
	B43	31	ZP568F	210-330	255/35		nur Bremse 370mm

Kombinationen

8,5 x 21	B43	VA 34	ZP568F	210-280	VA 245/35		nur Bremse 370mm
9,5 x 21		HA 43		210-330	VA 255/35		
				210-280	HA 275/30		
				210-330	HA 285/30		
8,5 x 21	B41	VA 34	ZP568F	210-450	VA+HA 255/35 od.		
10,5 x 21		HA 43			VA 255/35+HA 285/30		
9,5 x 21	B41	VA 31	ZP568F	210-450	VA 255/35		
10,5 x 21		HA 43			HA 285/30		

S-Klasse PHEV NEU	im Laufe 2022	R2S	5/112	66,6	e1*2007/46*2115*..
----------------------------------	---------------	-----	-------	------	--------------------

Sensor - Brocksens 8

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	B43	32,5	-	220, 270	255/45		Orig.-Verschr., Plug-in-Hybrid, nur Bremse 370mm
		36	-	220, 270	255/45		Orig.-Verschr. für Alufelgen, Plug-in-Hybrid, nur Bremse 370mm
8,5 x 19	B43	VA 31,5	-	220, 270	VA 255/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 285/40		
8,5 x 19	B43	VA 31,5	-	220, 270	VA 255/45, 265/45		Orig.-Verschr., nur Bremse 370mm
10 x 19		HA 48,1			HA 285/40, 295/40		
8,5 x 19	B37	35	ZP568F	220, 270	255/45, 265/45		Plug-in-Hybrid, nur Bremse 370mm
	CA 20	35	ZP568F	220, 270	255/45, 265/45		Plug-in-Hybrid, nur Bremse 370mm
	Oxigin 28	30	ZP568F	220, 270	255/45, 265/45		Plug-in-Hybrid, nur Bremse 370mm
9 x 19	CA 24	35	ZP569F	220-270	255/45		nicht Bremse 390mm
9 x 20	B43	VA 34	-	220, 270	VA 255/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35		
9 x 20	B43	VA 34	-	220, 270	VA 255/40, 265/40		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 20		HA 48,1			HA 285/35, 295/35		
9 x 20	RC36	32	-	220, 270	265/40		Orig.-Verschr. für Alufelgen, Plug-in-Hybrid, nur Bremse 370mm
	B43	33	ZP568F	220, 270	265/40		Plug-in-Hybrid, nur Bremse 370mm
	CA 20	35	ZP568F	220, 270	265/40		Plug-in-Hybrid, nur Bremse 370mm
	Oxigin 28	35	ZP568F	220, 270	265/40		Plug-in-Hybrid, nur Bremse 370mm

Kombinationen

8,5 x 19	B43	VA 30	-	220, 270	VA 255/45, 265/45		Orig.-Verschr. für Alufelgen, nur Bremse 370mm
10 x 19		HA 48,1			HA 285/40, 295/40		
9 x 21	B43	VA 34	ZP568F	220, 270	VA 255/35, 265/35		Plug-in-Hybrid, nur Bremse 370mm
10 x 21		HA 48			HA 295/30		

S-Klasse S63 AMG E Performance NEU ab 2024 R2S 5/112 66,6 e1*2007/46*2115*..

Sensor - Brocksens 8

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 21	B41	VA 31	ZP568F	450	VA 255/40+HA 285/35, VA 265/35+HA 305/30		HA ✖
10,5 x 21		HA 43					

S-Coupé/Cabrio S63/S65 (siehe Konfigurator) 221 (Model WDD217) 5/112 66,6 e1*2001/116*0335*23-... ACHTUNG: Achslast beachten

--	--	--	--	--	--	--	--

S-Coupé/Cabrio S63/S65 AMG (siehe Konf.) 221 (Model WDD217) 5/112 66,6 e1*2001/116*0335*23-..., e1*2001/116*0396*12-..., ACHTUNG: Achslast beachten

SL 500 (siehe Konfigurator) ab 03.12 231 5/112 66,6 e1*2007/46*0803*...

SLC (siehe Konfigurator) ab 04.16 172 5/112 66,6 e1*2007/46*0548*..

SLC 43 AMG (siehe Konfigurator) ab 2016 172 5/112 66,6 e1*2007/46*0548*..

Sprinter (siehe Konfigurator) ab 04.06 W906 6/130 84,1 e1*2004/116*0353*..., e1*2001/116*0354*..., L765, L766

Sprinter 2018 FL3A4,-5, KL3A4,-5 6/130 84,1 e1*2007/46*1761*..., e1*2007/46*1763*..., e1*2007/46*1760*..., e1*2007/46*1762*...

Sensor - Brocksens 1

Sensor - Brocksens 1							ET 2007/46 1760 ... ET 2007/46 1762 ...	
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!								
6,5 x 16	RC35	62	ZP631F		225/65		ECE i.V., auch ET62 ist ECE	
				84-130	225/65C, 225/75C, 235/65C		Frontantrieb, geschl. Aufbau, Typ KL3A4	
				105, 110	225/65C, 225/75C, 235/65C		Frontantrieb, geschl. Aufbau, Typ KL3A5	
	Pro2	54	70-130	225/65C, 225/65CP, 225/75C, 225/75CP, 235/65C, 235/65CP		Frontantrieb, geschlossener Kasten, ✖		
	AC-V61			54	70-105	225/65C, 225/75C, 235/65C		Orig.-Verschr. passt nur von der Stahlfelge! ✖
7 x 16	RC31	53	- od. ZP631F	70-130	225/65C, 225/75C, 235/65C, 245/70C		Orig.-Verschr. passt nur von der Stahlfelge! Frontantrieb ✖	
6,5 x 17	RC35	54	ZP631F	84-130	225/70C		Frontantrieb, geschl. Aufbau, Typ KL3A4, ✖	
				105, 110	225/70C		Frontantrieb, geschl. Aufbau, Typ KL3A5, ✖	
		62	ZP631F	84-130	225/70C, 235/60C		Frontantrieb, geschl. Aufbau, Typ KL3A4	
				105, 110	225/70C, 235/60C		Frontantrieb, geschl. Aufbau, Typ KL3A5	
	RC31	57	- od. ZP631F	70-130	225/70C, 235/60C		Orig.-Verschr. passt nur von der Stahlfelge! ✖	

7 x 17	B45	60	ZP630	84-130	225/70C, 235/60C		Frontantrieb, geschl. Aufbau, bei 235/60 ✖, Typ KL3A4
				105, 110	225/70C, 235/60C		Frontantrieb, geschl. Aufbau, bei 235/60 ✖, Typ KL3A5
	Pro2	50		70-130	225/70C, 235/60C		Frontantrieb, geschlossener Kasten, ✖
7,5 x 18	B45	47	ZP630	84-130	255/55C		Frontantrieb, geschl. Aufbau, Typ KL3A4, ✖
				105, 110	255/55C		Frontantrieb, geschl. Aufbau, Typ KL3A5, ✖
8 x 20	B45	60	ZP631F	84-130	235/45C		Frontantrieb, Typ KL3A4
				105, 110	235/45C		Frontantrieb, Typ KL3A5

Sprinter	ab Modelljahr 2018	W907	6/130	84,1	e1*2001/116*0354*21-, e1*2007/46*0301*16-..., e1*2007/46*0296*09-..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC35	54	ZP631F	84-140	205/75C, 225/75C, 235/65C		Typ 906AC35, 906BB35
				84-140	225/75C, 235/65C		Typ 906BB50
				84-140	205/75C, 215/70C, 225/65, 225/65C, 225/75, 225/75C, 235/60, 235/65, 235/65C, 235/70		Heckantrieb, geschl. Aufbau, Typ 906AC35, 906BB35
				84-140	225/75C, 235/65C		Heckantrieb, geschl. Aufbau, Typ 906BB50
		62	ZP631F	84-140	205/75C, 235/65C		Typ 906AC35, 906BB35, auch ET62 ist ECE
				84-140	235/65C		Typ 906BB50
				84-140	205/75C, 215/70C, 225/65, 225/65C, 235/60, 235/65, 235/65C		Heckantrieb, geschl. Aufbau, Typ 906AC35, 906BB35
				84-140	235/65C		Heckantrieb, geschl. Aufbau, Typ 906BB50
	Pro2	54		84-140	205/75C, 205R16C, 215/70C, 215/75C, 215/75CP, 215R16C, 225/65C, 225/65CP, 225/75C, 225/75CP, 235/65C, 235/65CP, 235/70		Heckantrieb, geschl. Kasten
				84-140	205/75C, 215/70C, 215/75C, 215/75CP, 215R16C, 225/65C, 225/65CP, 225/75C, 235/65C		Heckantrieb, offener Kasten
				105-140	225/75C, 225/75CP		Allrad
6,5 x 17	RC35	54	ZP631F	84-140	235/60C		
				84-140	205/70C, 225/65, 225/70C, 235/60, 235/60C, 235/65		Heckantrieb, geschl. Aufbau, Typ 906AC35, 906BB35
				84-140	235/60C		Heckantrieb, geschl. Aufbau, Typ 906BB50
		62	ZP631F	84-140	205/70C, 235/60, 235/60C		Heckantrieb, geschl. Aufbau, Typ 906AC35, 906BB35
				84-140	235/60C		Heckantrieb, geschl. Aufbau, Typ 906BB50
7 x 17	B45	60	ZP630	84-140	235/60, 235/60C		Heckantrieb, geschl. Aufbau, Typ 906AC35, 906BB35
				84-140	235/60C		Heckantrieb, geschl. Aufbau, Typ 906BB50
	Pro2	50		84-140	225/65C, 225/70C, 235/60, 235/60C, 235/65, 245/55, 245/60, 255/55, 255/60		Heckantrieb, geschl. Kasten
				105-140	245/70, 255/65		
8,5 x 17	8400 Bluster	40		84-140	235/60, 235/65, 245/55, 245/60, 255/55, 255/55C, 255/60		Heckantrieb, geschl. Aufbau, ✖
				105-140	255/65, 265/65, 285/60		Allrad, geschl. Aufbau, ✖
7,5 x 18	B45	47	ZP630	84-140	225/60, 235/55, 235/60, 245/50, 245/60, 255/50, 255/55, 255/55C		Heckantrieb, geschl. Aufbau, Typ 906AC35, ab 255/50 ✖
				84-140	225/60, 235/55, 235/60, 245/50, 255/50, 255/55, 255/55C		Heckantrieb, geschl. Aufbau, Typ 906BB35, ab 255/50 ✖
				84-140	255/55C		Heckantrieb, geschl. Aufbau, Typ 906BB50, ab 255/50 ✖
8 x 18	RC31	53	-	84-140	225/60, 235/55, 235/60		Orig.-Verschr., Heckantrieb
				105-140	255/55C, 265/60		Allrad, ✖
	8400 Bluster	50		105-140	255/55C, 265/60		Allrad, ✖
				84-140	225/60, 235/55, 235/60, 245/50		Frontantrieb
8 x 20	B45	60	ZP631F	84-140	235/45C		

Sprinter Allrad NEU	W907	6/130	84,1	e1*2001/116*0424*15-..., e1*2007/46*0305*11-..
Sensor - Brocksens Universal				

Dimension	Design	ET	KIT	KW	Reifendimension	Info
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!						
6,5 x 16	RC35	54	ZP631F	105-140	225/75C	 Typ 906AC35/ 906BB35

T-Klasse NEU	im Laufe 2023	MFK	5/114,3	66,1	e2*2018/858*00014*..., e2*2018/858*00015*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	32	-	55-96	205/50, 205/55		Orig.-Verschr., auch Citan Tourer
		40	-	55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr.
		38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
		38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
7 x 17	B39	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		
7,5 x 17	B24	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		

7 x 18	RC27	34	-	55-96	205/45, 215/45, 225/45		Orig.-Verschr.
7,5 x 18	RC30	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	B32	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	55-96	205/45, 215/45, 225/40, 225/45		Kit mit Artikelnummer 98478
8 x 18	B24	38	ZP581	55-96	215/45, 225/40, 225/45		
	B36	35	ZP581	55-96	215/45		
	B42 / B44	40	ZP581	55-96	215/45		

V-Klasse/Vito

09/2014

639/2, 639/4

FIN WDF447

5/112

66,6

e1*2007/46*0457*09-..., e1*2007/46*0458*08-...
(FIN: WDF447...), e1*2007/46*0459*06-...

Sensor - Brocksens 3 - ab Baujahr 03/2024 Brocksens 1

!!!ACHTUNG!!! unbedingt Achslasten überprüfen!

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC25T	52	-	65-140	205/65C, 225/60C	 Orig.-Verschr., nicht Allrad
				65-100	195/65C	
				65-120	205/65, 215/60, 215/65	
				65-140	225/55, 225/60, 235/60	
	Pro1	52	-	65-100	205/65+C, 215/60+C, 215/65+C, 225/60+C	Orig.-Verschr., Frontantrieb, Ausführung "D43"
				100-140	205/65+C, 215/60+C, 215/65+C, 225/60+C	Orig.-Verschr., Heckantrieb, Ausführung "D43"
7 x 17	RC25T	51	-	65-176	195/65C, 195/75C, 205/65, 205/65C, 205/75C, 215/60, 215/60C, 215/65, 215/65C, 225/60, 225/60C, 225/65, 225/65C, 235/55, 235/60	Front- und Allradantrieb, nicht Faustsattelbremse mit 330x32mm, Serienbereifung bis 18 Zoll
				75-176	225/60, 225/60C, 225/65, 225/65C, 235/55, 235/60	Front- und Allradantrieb, nicht Faustsattelbremse mit 330x32mm, Serienbereifung in 19 Zoll
	RC30T	51	-	65-100	215/55, 215/60, 215/60C, 225/55, 225/55C, 225/60, 235/50, 235/55	 Orig.-Verschr., Frontantrieb
				100-140	215/55, 215/60+C, 225/55+C, 225/60	
				100-176	235/50, 235/55	 Orig.-Verschr., Heckantrieb
				100-176	225/55+C, 225/60, 235/50, 235/55	Orig.-Verschr., Allradantrieb
	RC30T	51	-	65-100	225/55+C	 Orig.-Verschr., Frontantrieb
				65, 84	215/55, 215/60+C, 225/60, 235/50, 235/55	
				100-140	225/55+C	
				100-176	235/55	Orig.-Verschr., Heckantrieb, incl. Marco Polo, Mixto...
	RC30T	51	-	100-176	215/55, 215/60+C, 225/55+C, 225/60, 235/50, 235/55	
				100-176	225/55+C, 235/55	 Orig.-Verschr., Allradant, incl. Marco Polo, Mixto
	B45	51	-	65-100	225/55, 225/55C	Orig.-Verschr., Frontantrieb
				100-140	225/55, 225/55C	 Orig.-Verschr., Heckantrieb
				100-176	235/55	Orig.-Verschr., Allradantrieb
				100-176	225/55, 225/55C, 235/55	
	AC-V51	51	-	65-100	215/55, 215/60, 215/60C, 225/55, 225/55C, 225/60, 235/50, 235/55	Orig.-Verschr., Frontantrieb
				100-140	215/55, 215/60, 215/60C, 225/55, 225/55C, 225/60	
				100-176	235/50, 235/55	
				100-176	225/55, 225/55C, 225/60, 235/50, 235/55	
	AC-V51	51	14x1,5, Kugel R14, 30mm	100-140	215/60, 215/60C, 225/55, 225/55C, 225/60	
				100-176	235/50, 235/55	Heckantrieb
				65-100	215/60, 215/60C, 225/55, 225/55C, 225/60, 235/50, 235/55	
				100-176	225/55, 225/55C, 225/60, 235/50, 235/55	
	RC27	47	ZP561F	100-140	215/55, 215/60, 215/60C, 225/55, 225/55C, 225/60	nur Heckantrieb
	RC27	47	ZP561F	100-176	235/50, 235/55	
	Pro1	49	ZP569F	65-176	215/55, 215/60, 215/60C, 225/50, 225/55, 225/55C, 235/50, 235/55	Front- u. Allradantrieb, Serienbereifung bis 18 Zoll
				75-176	225/50, 225/55, 225/55C, 235/50, 235/55	Front- u. Allradantrieb, Serienbereifung in 19 Zoll
7,5 x 17	RC25	47,5	ZP565F	65, 84	215/55, 215/60, 225/55+C, 225/60, 235/50, 235/55	Ausführung Felge "D8" , Frontantrieb
				100-140	215/55, 215/60, 225/55+C, 225/60	Ausführung Felge "D8" , Heckantrieb
				100-176	235/50, 235/55	
				100-176	225/55+C, 225/60, 235/50, 235/55	Ausführung Felge "D8" , Allradantrieb
	RC25	51	-	65-140	215/55, 215/60, 225/55+C, 225/60	
				100-176	225/55+C, 225/60	
				65, 84	215/55, 215/60, 225/55+C, 225/60	Frontantrieb
				100-140	215/55, 215/60, 225/55+C, 225/60	Heckantrieb
	RC29	45	ZP561F	100-176	225/55+C, 225/60	Allradantrieb
				65, 84	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55	nur Frontantrieb, ab 235/50 ✖
				100-140	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55	Heck- u. Allradantrieb, ab 235/50 ✖
				100-140	215/55, 225/55C	Orig.-Verschr., Frontantrieb
	AC-518	47	-	100-140	215/55, 225/55C	Orig.-Verschr., Allrad- u. Heckantrieb
				100-176	245/45	 Orig.-Verschr., ECE nur Heckantrieb- u. Allrad
	AC-518	47	-	65-100	215/55, 225/50, 225/55, 235/45, 245/45	Orig.-Verschr., Frontantrieb

7,5 x 18	B45	52	-	100-140	215/55, 225/50, 225/55		Orig.-Verschr., Heckantrieb
				100-176	235/45, 245/45		
				100-176	225/50, 225/55, 235/45, 245/45		Orig.-Verschr., Allradantrieb
	RC25T	52	-	100-140	215/55, 225/50, 225/55		Orig.-Verschr., nur Heckantrieb
				100-176	235/45, 245/45		
				100-176	225/50, 225/55, 235/45, 245/45		Orig.-Verschr., Allradantrieb
	RC30	45	ZP568F	65-100	215/55, 225/50, 225/55, 235/45, 245/45		Frontantrieb
				100-140	215/55, 225/50, 225/55		Heckantrieb
				100-176	235/45, 245/45		
				100-176	225/50, 225/55, 235/45, 245/45		Allradantrieb
	RC32	49	-	65-190	235/45		Orig.-Verschr., Achtung Auflage E106 beachten!
	B32	45	ZP561F	65-140	215/50, 215/55, 225/50, 225/55, 235/45, 235/50, 245/45		auch Allrad
B39	45	ZP561F	100-140	215/55, 225/50, 225/55, 235/45, 245/45		nur Heckantrieb	
AC-V51	50	ZP564F	65-100	225/55, 235/45, 235/50, 245/45		Frontantrieb	
			100-140	225/55			
			100-176	235/45, 235/50, 245/45		Heckantrieb	
			100-176	225/55, 235/45, 235/50, 245/45		Allradantrieb	
8 x 18	RC25	45	ZP561F	100-140	225/50, 225/55, 235/45		
	RC29	45	ZP561F	65-140	225/50, 225/55, 235/45		
	B24	48	ZP561F	65-100	225/50, 225/55, 235/45, 245/45		Frontantrieb
				100-140	225/50, 225/55		Heckantrieb
				100-176	235/45, 245/45		
				100-176	225/50, 225/55, 235/45, 245/45		Allradantrieb
	B36	45	ZP561F	65, 84	235/45		nur Frontantrieb
				100-176	235/45		Heck- u. Allradantrieb
	B37	45	ZP561F	65, 84	225/50, 225/55, 235/45, 235/50, 245/45, 255/45		nur Frontantrieb, ✖ außer 235/45
				100-140	225/50, 225/55, 235/45, 235/50, 245/45, 255/45		Allrad- u. Heckantrieb, ✖ außer 235/45
	AC-518	48	-	65, 84	225/50, 225/55, 235/45, 245/45		Orig.-Verschr., Frontantrieb
				100-176	225/50, 225/55, 235/45, 245/45		Orig.-Verschr., Allrad- u. Heckantrieb
AC-V51	52	AV1	65-100	225/50, 225/55, 235/45, 245/45		Frontantrieb	
			100-140	225/50, 225/55			
			100-176	235/45, 245/45		Heckantrieb	
			100-176	225/50, 225/55, 235/45, 245/45		Allradantrieb	
8 x 19	RC27	52	-	100-176	245/45		Orig.-Verschr., nur Heckantrieb
				65-176	235/45, 245/45		Orig.-Verschr., Front- Heck u. Allradantrieb
	RC29	52	-	100-140	245/45		Orig.-Verschr., nur Heck- und Allradantrieb
				100-176	235/45, 245/40, 245/45		Orig.-Verschr., Heckantrieb- u. Allrad
				65-100	235/45, 245/40, 245/45		Orig.-Verschr., Frontantrieb
	RC32	52	-	75-176	245/45		Orig.-Verschr.
	RC34	52	-	75-176	245/45		Orig.-Verschr.
	B43	52	-	100-176	235/45, 245/40, 245/45		Orig.-Verschr., ECE nur Heckantrieb- u. Allrad
				65-100	235/45, 245/40, 245/45		Orig.-Verschr., Frontantrieb
				100-176	235/45, 245/40, 245/45		Orig.-Verschr., Heckantrieb- u. Allrad
				65, 84	235/45, 245/40, 245/45		nur Frontantrieb, ab 245/40 ✖
	RC29	45	ZP561F	100-176	235/45, 245/40, 245/45		Heck- u. Allradantrieb, ab 245/40 ✖
65, 84				235/45, 245/40, 245/45		Frontantrieb	
AC-518	47	-	100-176	235/45, 245/40, 245/45		Heck- und Allradantrieb	
			65-176	235/45		Front- Heck- u. Allradantrieb	
8,5 x 19	Oxigin 19	45	ZP561F	65-140	235/45, 245/45, 255/40		Front- und Heckantrieb, ✖
	B37	48	-	65, 84	235/45, 245/40, 245/45		Orig.-Verschr., nur Frontantrieb, ab 245/40 ✖
				100-176	235/45, 245/40, 245/45		Orig.-Verschr., Heck- u. Allradantrieb
9 x 19	CA 17 / CA 24	49	ZP568F	65-176	235/45		Front- Heck- u. Allradantrieb
8 x 20	B43	48	ZP568F	65-176	245/40		
8,5 x 20	B24	48	ZP561F	65, 84	245/40		✖
	B42	48	ZP561F	65-176	245/40		Front- Heck- u. Allradantrieb, ✖
	Oxigin 14	50	ZP561F+R	65-140	245/40		+ BA12= R72,6-66,6, ✖

eVito /eVito Tourer NEUab 2022639/2, 639/4 FIN WDF4475/11266,6e1*2007/46*0457*20-...e1*2007/46*0458*15-...
(FIN: WDF447...)

Sensor - Brocksens 3 - ab Baujahr 03/2024 Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC25T	51	-	70 (150)	245/55	Orig.-Verschr., mit 245er Serienbereifung
				70 (85)	225/55, 225/55C, 225/60, 225/60C, 235/55, 245/55	Orig.-Verschr., mit 225er Serienbereifung
	RC30T	51	-	70 (85)	225/55C	Orig.-Verschr., mit 225er Serienbereifung
				70 (150)	245/55	Orig.-Verschr., mit 245er Serienbereifung
	B45	51	-	70 (85)	225/55C	Orig.-Verschr., mit 225er Serienbereifung
				70 (150)	245/55	Orig.-Verschr., mit 245er Serienbereifung
				70 (85)	225/55, 225/55C, 225/60, 225/60C, 235/55, 245/55	Orig.-Verschr., mit 225er Serienbereifung
				70 (150)	245/55	Orig.-Verschr., mit 245er Serienbereifung
	AC-V51	51	14x1,5,Kug. R14,30mm	70 (85)	225/55, 225/55C, 225/60, 225/60C, 235/55, 245/55	mit 225er Serienbereifung
				70 (150)	245/55	mit 245er Serienbereifung
7,5 x 17	Pro1	49	ZP569F	70	225/50, 225/55, 225/55C, 235/50	Serie 225/55R17C
	RC25	51	-	70 (85)	225/55, 225/55C, 225/60, 225/60C, 235/55, 245/55	Orig.-Verschr., mit 225er Serienbereifung

				70 (150)	245/55		Orig.-Verschr., mit 245er Serienbereifung
7,5 x 18	B45	52	-	70 (150)	245/50		Orig.-Verschr., mit 245er Serienbereifung
				70 (85)	225/50C, 225/55, 235/50, 245/50		Orig.-Verschr., mit 225er Serienbereifung
	AC-V51	50	ZP564F	70 (150)	245/50		mit 245er Serienbereifung
				70 (85)	225/55, 235/50, 245/50		mit 225er Serienbereifung
	CA 20	51	ZP568F	70	245/50		
8 x 18	RC25	45	ZP561F	70 (150)	255/45		mit 245er Serienbereifung
8 x 19	RC29	52	-	70 (85)	245/40, 245/45		Orig.-Verschr., mit 225er Serienbereifung
	RC34	52	-	70	245/40		Orig.-Verschr., mit 225er Serienbereifung
	B43	52	-	70 (85)	245/40, 245/45		Orig.-Verschr., mit 225er Serienbereifung
8,5 x 19	B37	48	-	70 (85)	245/40, 245/45		Orig.-Verschr., mit 225er Serienbereifung

X-Klasse				4701	6/114,3	66,1	e9*2007/46*6531*..
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	Originaldim.	50			255/65		Originaldaten
	RC14-6S	40	ZP610F	120-140	255/65, 265/60		
7,5 x 18	Originaldim.	50			255/60		Originaldaten
8 x 18	RC31	45	ZP610F	120-140	255/60, 265/55		
	8400 Bluster	42	-	120-190	255/60, 265/55		Orig.-Verschr.

MG (Saic)

MG (Saic)		Baujahr	Typ	LK/LZ	Nabe		
MG EHS (RX6) Plug-in-Hybrid NEU		ab 2021	AS23P-L, AS23P-R	5/112	57,1	e5*2018/858*00003*..., e5*2018/858*01000*..., e11*2018/858*00252*..	
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	41	- (V10)	119	215/60, 225/55, 235/55		Orig.-Verschr., Ausführung V10
	RC34	41	- (V10)	119	215/60, 225/55, 235/55		Orig.-Verschr., Ausführung V10
7 x 17	RC27	41	- (V10)	119	215/60, 225/55, 235/55, 245/50HA, 255/50HA		Orig.-Verschr., Ausführung V10
		35	ZP562D	119	215/60, 225/55, 235/55, 245/50		
	RC30	35	ZP562D	119	215/60, 225/55, 235/55, 245/50		
	RC34	41	- (V10)	119	215/60, 225/55, 235/55, 245/50		Orig.-Verschr., Ausführung V10
7,5 x 17	CA 26	42	ZP560D	119	215/60, 225/55, 235/55, 245/50HA, 255/50HA		
	RC29	35	ZP560D	119	215/60, 225/55, 235/55		
	RC34	40	ZP560D	119	215/60, 225/55, 235/55, 245/50		
7,5 x 18	B24 / B36	35	ZP562D	119	215/60, 225/55, 235/55		
	RC32	41	- (V10)	119	215/55, 225/50, 235/50, 245/45		Orig.-Verschr., Ausführung V10
	RC34	41	- (V10)	119	215/55, 225/50, 235/50, 245/45		Orig.-Verschr., Ausführung V10
	RC30	35	ZP562D	119	215/55, 225/50, 235/50, 245/45		
	B32	35	ZP562D	119	215/55, 225/50, 235/50, 245/45		
	B39	35	ZP562D	119	215/55, 225/50, 235/50, 245/45		
	Oxigin 25	44	ZP560D	119	215/50, 215/55, 225/50		
8 x 18	RC34	43	ZP560D	119	215/55, 225/50, 235/50, 245/45, 255/45		
	B24	35	ZP562D	119	225/50, 245/45		
	B36 / B37	35	ZP562D	119	225/50, 245/45		B36 nur e5*2018/858*00003*..
	B42 / B44	35	ZP562D	119	225/50, 245/45		
	AC-M10	40	AV1	119	225/50, 235/50, 245/45, 255/45		
	AC-MB6	39	AV1	119	225/50, 235/50, 245/45, 255/45		
	AC-522	35	AV1	119	225/50, 245/45		
		40	AV1	119	225/50, 235/50, 245/45, 255/45		
	FMI08 Thoe	34	F31+R	119	215/55, 225/50, 245/45		+ Red.Ringe BA25=66,6-57,1
	FMI11 Elatha	39	F95	119	215/55, 225/50, 235/50, 245/45, 255/45		
	FMI12 Kari	34	Kit 0353	119	215/55, 225/50, 245/45		
7,5 x 19	CA 26	40	ZP560D	119	215/50, 225/45, 235/45		
8 x 19	RC29	35	ZP562D	119	225/45, 235/45, 245/40		
	RC34	38+43	ZP560D	119	225/45, 235/45, 245/40		
	B38	35	ZP562D	119	225/45, 235/45, 245/40		
	B40	38	ZP562D	119	225/45, 235/45, 245/40		
	CA 17	37+45	ZP560D	119	225/45, 235/45		
	AC-521	35	AV1	119	225/45, 235/45, 245/40		
	FMI08 Thoe	26	F31+R	119	225/45		+ Red.Ringe BA25=66,6-57,1
	FMI14 Jupiter	26	Kit0338	119	225/45		
	Oxigin 29	32	ZP560D	119	225/45, 235/45		
39		ZP560D	119	225/45, 235/45, 245/40			
8,5 x 19	B32	34,5	ZP562D	119	225/45, 235/45		nur e5*2018/858*00003*..
	B37	35	ZP562D	119	225/45, 235/45		
	B42	35	ZP562D	119	225/45, 235/45		
		42	ZP562D	119	225/45, 235/45, 245/40HA, 255/40HA		
	B43	38	ZP569F	119	225/45, 235/45, 245/40HA, 255/40HA		
	B44	35	ZP562D	119	225/45, 235/45		
		42	ZP562D	119	225/45, 235/45, 245/40HA, 255/40HA		
	AC-M10	40	AV1	119	225/45, 235/45, 245/40, 255/40HA		
	CA 23	30	ZP560D	119	225/45		
	FMI11 Elatha	32	F95	119	225/45, 235/45		
	Oxigin 26	40	ZP560D	119	225/45, 235/45		
	Oxigin 28	40	ZP560D	119	225/45, 235/45, 245/40, 255/40HA		
8300 - 1972	32	F85+R	119	225/45, 235/45		+ Red.Ringe BA25=66,6-57,1	
9 x 19	FMI08 Thoe	41	F31+R	119	235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
8 x 20	B43	39	ZP560D	119	225/40, 235/40, 245/35		
8,5 x 20	RC29	40	ZP562D	119	225/40, 235/40, 245/35		
	B24	42	ZP562D	119	225/40, 235/40		
	B42	35	ZP562D	119	225/40, 235/40		
		40	ZP562D	119	225/40, 235/40, 245/35		
	B43	40	ZP560D	119	225/40, 235/40, 245/35		
	B44	35	ZP562D	119	225/40, 235/40		
		40	ZP562D	119	225/40, 235/40, 245/35		
	AC-521	32	AV1	119	225/40, 235/40		
	AC-M10	40	AV1	119	225/40, 235/40, 245/35		
9 x 20	CA 17	40	ZP560D	119	225/40		
	B37	37	ZP562D	119	225/40, 235/40		
	AC-521	42	AV1	119	225/40, 235/40		
	AC-522	40	AV1	119	225/40		
	CA 20	35	ZP560D	119	225/40, 235/40		

	CA 23	38	ZP560D	119	225/40, 235/40, 245/35		
	FMI11 Elatha	34	F95	119	235/40		
	Oxigin 28	35	ZP560D	118	225/40, 235/40		
MG HS NEU 4. Quartal 2023 AS23 / AS23P-R 5/112 57,1 e4*2018/858*00111*..., e5*2018/858*01000*..							
Sensor - Brocksens 8							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	41	- (V10)	119	215/60 , 225/55, 235/55		Orig.-Verschr., Ausführung "V10"
	RC34	41	- (V10)	119	215/60 , 225/55, 235/55		Orig.-Verschr., Ausführung "V10"
7 x 17	RC27	41	- (V10)	119	215/60, 225/55, 235/55, 245/50HA, 255/50HA		Orig.-Verschr., Ausführung "V10"
	RC34	41	- (V10)	119	215/60, 225/55, 235/55, 245/50		Orig.-Verschr., Ausführung "V10" , auch Plug-in-Hybrid
	RC27	35	ZP562D	119	215/60, 225/55, 235/55, 245/50		
	CA 26	42	ZP560D	119	215/60, 225/55, 235/55, 245/50HA, 255/50HA		
7,5 x 17	B24	35	ZP562D	119	215/60, 225/55, 235/55		
7,5 x 18	RC32	41	- (V10)	119	215/55, 225/50, 235/50 , 245/45		Orig.-Verschr., Ausführung "V10" , auch Plug-in-Hybrid
	RC34	41	- (V10)	119	215/55, 225/50, 235/50 , 245/45		Orig.-Verschr., Ausführung "V10" , auch Plug-in-Hybrid
	RC30	35	ZP562D	119	215/55, 225/50, 235/50, 245/45		
	RC34	43	ZP560D	119	215/55, 225/50, 235/50, 245/45, 255/45		
8 x 18	B24 / B36 / B42	35	ZP562D	119	225/50, 245/45		
	B44	35	ZP562D	119	225/50, 245/45		
	AC-M10	40	AV1	119	225/50, 235/50, 245/45, 255/45		
	AC-MB6	39	AV1	119	225/50, 235/50, 245/45, 255/45		
7,5 x 19	CA 26	40	ZP560D	119	215/50, 225/45, 235/45		
8 x 19	B40	38	ZP562D	119	225/45, 235/45, 245/40		
	CA 17	37+45	ZP560D	119	225/45, 235/45		
	FMI14 Jupiter	26	Kit0338	119	225/45		
	Oxigin 29	32	ZP560D	119	225/45, 235/45		
8,5 x 19		39	ZP560D	119	225/45, 235/45, 245/40		
	B32	34,5	ZP562D	119	225/45, 235/45		
	B36	30	ZP562D	119	225/45		
		35	ZP562D	119	225/45, 235/45		
	B42	30	ZP562D	119	225/45		
	B44	35	ZP562D	119	225/45, 235/45		
		42	ZP562D	119	225/45, 235/45		
	AC-M10	40	AV1	119	225/45, 235/45, 245/40HA, 255/40HA		
8 x 20	CA 20	35	ZP562D	119	225/45, 235/45		
	B43	39	ZP560D	119	225/40, 235/40, 245/35		
	B42	40	ZP562D	119	225/40, 235/40, 245/35		
8,5 x 20	B44	35	ZP562D	119	225/40, 235/40		
		40	ZP562D	119	225/40, 235/40, 245/35		
	AC-M10	40	AV1	119	225/40, 235/40, 245/35		
9 x 20	AC-522	40	AV1	119	225/40		
	CA 20	35	ZP560D	119	225/40, 235/40		
	CA 23	38	ZP560D	119	225/40, 235/40, 245/35		

MG ZS EV		elektro NEU	ab 2021	ZS1, SZS1, MZS1	5/112	57,1	e4*2007/46*1417*.., e4*2007/46*1435*.., e5*2007/46*1329*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC27	41	- (V10)	68-75	205/60, 215/55, 215/60, 225/55			Orig.-Verschr., Ausführung "V10"
	RC30	41	- (V10)	68-75	205/60, 215/55, 215/60, 225/55			Orig.-Verschr., Ausführung "V10"
7 x 16	RC28	35	ZP562D	68-75	205/60, 215/55, 215/60, 225/55			
6,5 x 17	RC27	41	- (V10)	68-75	205/55, 215/50, 215/55, 225/50			Orig.-Verschr., Ausführung "V10"
	RC34	41	- (V10)	68-75	205/55, 215/50, 215/55, 225/50, 235/50			Orig.-Verschr., Ausführung "V10"
7 x 17	RC27	41	- (V10)	68	215/50			Orig.-Verschr., Ausführung "V10"
				68-75	205/55, 215/50, 215/55, 225/50			
	RC34	41	- (V10)	68-75	205/55, 215/50, 215/55, 225/50			Orig.-Verschr., Ausführung "V10"
	RC30	35	ZP562D	68-75	205/55, 215/50, 215/55, 225/50			
7,5 x 17	CA 26	42	ZP560D	68-75	205/55, 215/50, 215/55, 225/50			
	RC29	35	ZP560D	68-75	205/55, 215/50, 215/55			
	RC34	40	ZP560D	68-75	205/55, 215/50, 215/55, 225/50, 245/45			
	B24 / B36	35	ZP562D	68-75	205/55, 215/50, 215/55			
7,5 x 18	RC30	35	ZP562D	68-75	215/45, 225/45			
	RC32	41	- (V10)	68-75	215/45, 225/45			Orig.-Verschr., Ausführung "V10"
	RC34	41	- (V10)	68-75	215/45, 225/45			Orig.-Verschr., Ausführung "V10"
	B32	35	ZP562D	68-75	215/45, 225/45			
	B39	35	ZP562D	68-75	215/45, 225/45			
	RC34	43	ZP560D	68-75	215/45, 225/45, 235/40, 245/40			
	B24	35	ZP562D	68-75	215/45, 225/45			

7,5 x 17	B36	45	ZP560D	54, 68	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45		
	CA 20	47	ZP560D	54, 68	205/50, 205/55, 215/50, 225/45, 225/50, 235/45, 245/45		
7,5 x 18	RC30	35	ZP560D	54, 68	205/45, 215/45		
		45	ZP560D	54, 68	205/45, 215/45, 225/40, 225/45		
	RC32	41	- (V10)	54-68	215/45, 225/40		Orig.-Verschr., Ausführung "V10"
	B32 / B39	45	ZP560D	54, 68	205/45, 215/45, 225/40, 225/45		
	AC-MB6	45	AV1	54, 68	205/45, 215/45, 225/40, 225/45		
	AC-M10	45	AV1	54, 68	205/45, 215/45, 225/40, 225/45		
		44	ZP560D	54-68	205/45, 215/45, 225/40, 225/45		
8 x 18	RC27	51	- (V10)	68	235/45		Orig.-Verschr., Ausführung "V10"
				54, 68	215/45, 225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Ausführung "V10"
				68	235/45, 245/40		Orig.-Verschr., Ausführung "V10", 18 Zoll Serie
	RC34	43	ZP560D	54-68	215/45, 225/40, 235/40, 245/40		
	B24	48	ZP560D	54, 68	215/45, 225/40, 225/45, 235/40, 245/40		
				68	235/45, 245/40		18 Zoll Serie
	B36	45	ZP560D	54, 68	215/45, 225/40, 225/45, 235/40		
	B42 / B44	45	ZP560D	54, 68	215/45, 225/40, 225/45, 235/40		
				68	235/45, 245/40		18 Zoll Serie
	AC-MB6 / AC-M10	45	ZP560D	54, 68	215/45, 225/40, 225/45, 235/40		
				68	235/45, 245/40		18 Zoll Serie
	AC-522	40	AV1	54, 68	215/45, 225/40, 225/45		
		45	AV1	54, 68	215/45, 225/40, 225/45, 235/40		
	CA 20	45	ZP560D	54, 68	215/45, 225/40, 225/45, 235/40		
				68	235/45, 245/40		18 Zoll Serie
	FMI08 Thoe	34	F31+R	54-68	215/45		+Red.Ringe BA25=66,6-57,1
		49	F31+R	54-68	215/45, 225/40, 235/40, 245/40		+Red.Ringe BA25=66,6-57,1
	FMI11 Elatha	39	F95	54-68	215/45, 225/40		
		45	F95	54-68	215/45, 225/40, 235/40, 245/40		
	FMI12 Kari	45	Kit 0353	54-68	215/45, 225/40, 235/40, 245/40		
8 x 19	RC34	43	ZP560D	54-68	235/35, 245/35		
	B38	45	ZP560D	54, 68	235/35		
	B40	43	ZP560D	54, 68	235/35		
				68	235/40		18 Zoll Serie
	FMI08 Thoe	47	F31+R	54-68	235/35, 245/35		+Red.Ringe BA25=66,6-57,1
8,5 x 19	Oxigin 29	43	ZP560D	54, 68	235/35		
				68	235/40		18 Zoll Serie
	B32	45	ZP560D	54, 68	235/35		
				68	235/40		18 Zoll Serie
	B42	47	ZP560D	54, 68	235/35		
				68	235/40		18 Zoll Serie
	AC-M10	45	AV4+R	54, 68	235/35		+Red.Ringe BA25=66,6-57,1
				68	235/40		18 Zoll Serie
	CA 20	45	ZP560D	54, 68	235/35		
				68	235/40		18 Zoll Serie
8 x 20	CA 23	45	ZP560D	54, 68	235/35		
	FMI11 Elatha	45	F95	54-68	235/35		
	8300 - 1972	45	F85+R	54-68	235/35		+ Red.Ringe 66,6-57,1
	Oxigin 28	45	ZP560D	54, 68	235/35		
	B38	48	ZP560D	54, 68	245/30		
	B43	48	ZP560D	54, 68	245/30		
				68	235/35, 245/30		18 Zoll Serie

MG 4 Electric Trophy E.R. NEU		4. Quartal 2023	SEH3	5/112	57,1	e4*2018/858*00093*..	
Sensor - nur Klonen möglich							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC27	51	- (V10)	90	235/45, 245/40		Orig.-Verschr., Ausführung "V10"
	B24	48	ZP562D	90	235/45, 245/40		
	B36 / B42	45	ZP562D	90	235/45, 245/40		
	B44	45	ZP562D	90	235/45, 245/40		
	AC-MB6	45	ZP560D	90	235/45, 245/40		
8 x 19	AC-M10	45	ZP560D	90	235/45, 245/40		
	B40	43	ZP562D	90	235/40		
	CA 17	45	ZP560D	90	235/40, 245/35		
8,5 x 19	Oxigin 29	43	ZP560D	90	235/40		
	AC-M10	45	AV4+R	90	235/40		+Red.Ringe BA25=66,6-57,1
8 x 20	CA 20	45	ZP560D	90	235/40		
	B43	48	ZP562D	90	235/35		

MG 4 Electric XPower NEU		4. Quartal 2023		SEH3		5/112		57,1		e4*2018/858*00093*..	
Sensor - nur Klonen möglich											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8 x 18	RC27	51	- (V10)	152	235/45, 245/40				Orig.-Verschr., Ausführung "V10"		
	B24	48	ZP562D	152	235/45, 245/40						
	B36 / B42	45	ZP562D	152	235/45, 245/40						
	B44	45	ZP562D	152	235/45, 245/40						
	AC-MB6	45	ZP560D	152	235/45, 245/40						
	AC-M10	45	ZP560D	152	235/45, 245/40						
8 x 19	B40	43	ZP562D	152	235/40						
	CA 17	45	ZP560D	152	235/40, 245/35						
	Oxigin 29	43	ZP560D	152	235/40						
8,5 x 19	AC-M10	45	AV4+R	152	235/40				+Red.Ringe BA25=66,6-57,1		
	CA 20	45	ZP560D	152	235/40						
8 x 20	B43	48	ZP562D	152	235/35						

MG 5 Electric NEU		2. Quartal 2022		EP22-L		5/112		57,1		e4*2018/858*00053*...		
Sensor - Brocksens 8												
Dimension	Design	ET	KIT	KW	Reifendimension				Info			
6,5 x 16	RC27	41	- (V10)	73, 75	205/55, 205/60 , 215/55, 225/50, 225/55					Orig.-Verschr.,	Ausführung "V10"	
	RC30	41	- (V10)	73, 75	205/55, 205/60 , 215/55, 225/50, 225/55					Orig.-Verschr.,	Ausführung "V10"	
6,5 x 17	RC27	41	- (V10)	73, 75	205/50, 205/55, 215/50, 225/50					Orig.-Verschr.,	Ausführung "V10"	
	RC34	41	- (V10)	73	205/50, 205/55, 215/50, 225/50					Orig.-Verschr.,	Ausführung "V10"	
7 x 17	RC27	45	- (V10)	73, 75	205/50, 205/55, 215/50 , 225/45					Orig.-Verschr.,	Ausführung "V10"	
	RC34	45	- (V10)	73	205/50, 205/55, 215/50 , 225/50					Orig.-Verschr.,	Ausführung "V10"	
	CA 26	45	-	73, 75	205/50, 205/55, 215/50 , 225/45					Orig.-Verschr.		
	RC27	41	- (V10)	73, 75	205/50, 205/55, 215/50, 225/45					Orig.-Verschr.,	Ausführung "V10"	
		35	ZP562D	73, 75	205/50, 205/55, 225/45							
	RC30	35	ZP562D	73, 75	205/50, 205/55, 225/45							
	RC34	41	- (V10)	73	205/50, 205/55, 215/50					Orig.-Verschr.,	Ausführung "V10"	
	CA 26	42	ZP560D	73, 75	205/50, 205/55, 215/50, 225/45, 225/50							
7,5 x 17	RC28	45	ZP562D	73, 75	205/50, 205/55, 215/50, 225/45, 235/45							
	B36	45	ZP562D	73, 75	205/50, 205/55, 215/50, 225/45, 235/45							
7,5 x 18	RC30	35	ZP562D	73, 75	205/45, 215/45							
		45	ZP562D	73, 75	205/45, 215/45, 225/40							
	RC32	41	- (V10)	73	215/45, 225/40					Orig.-Verschr.,	Ausführung "V10"	
	RC34	41	- (V10)	73	215/45, 225/40					Orig.-Verschr.,	Ausführung "V10"	
	B32	35	ZP562D	73, 75	205/45, 215/45							
		45	ZP562D	73, 75	205/45, 215/45, 225/40							
	B39	45	ZP562D	73, 75	205/45, 215/45, 225/40							
	AC-MB6	45	AV1	73, 75	205/45, 215/45, 225/40							
	AC-M10	45	AV1	73, 75	205/45, 215/45, 225/40							
	Oxigin 25	44	ZP560D	73-75	215/45, 225/40							
8 x 18	RC34	43	ZP560D	73	215/45, 225/40							
	B36 / B42	45	ZP562D	73, 75	215/45, 225/40							
	B44	45	ZP562D	73, 75	215/45, 225/40							
	AC-MB6	45	ZP560D	73, 75	215/45, 225/40							
	AC-M10	40	AV1	73, 75	215/45, 225/40							
		45	ZP560D	73, 75	215/45, 225/40							
	AC-521	45	AV1	73, 75	215/45, 225/40							
	AC-522	40+45	AV1	73, 75	215/45, 225/40							
	CA 20	45	ZP560D	73, 75	215/45, 225/40							
	FMI11 Elatha	39	F95	73	215/45							
		45	F95	73	215/45, 225/40, 235/40							
	FMI12 Kari	45	Kit 0353	73	215/45, 225/40, 235/40							
	7,5 x 19	CA 26	40	ZP560D	73, 75	225/35						
	8 x 19	RC29	45	ZP562D	73, 75	225/35						
RC34		43	ZP560D	73	235/35					✖		
B38		45	ZP562D	73, 75	225/35							
B40		43	ZP562D	73, 75	225/35							
AC-521		45	AV1	73, 75	225/35							
FMI08 Thoe		47	F31+R	73	235/35					+Red.Ringe BA25=66,6-57,1		

Mini One		Baujahr	Typ	LK/LZ	Nabe	e1*2007/46*0371*10...., e12007/46*1679*..., e1*2007/46*1678*..., e1*2007/46*1680*...
Mini One		ab 2014	UKL-L F55 / F56 / F57	5/112	66,7	
Sensor - Brocksens 1						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	47	-	55-100	175/65, 185/60, 185/65, 195/60, 205/55	Orig.-Verschr., auch Typ FML2, FML4 u. FMCA, ab 195/60 

6,5 x 16	RC27	54	-	55-155	185/55M+S, 195/50M+S, 195/55		Orig.-Verschr., auch Typ FML2, FML4 u. FMCA
				55-100	185/55, 195/50		
	RC30	54	-	55-155	185/55M+S, 195/50M+S, 195/55		Orig.-Verschr., auch Typ FML2, FML4 u. FMCA
				55-100	185/55, 195/50		
	RC32	54	-	55-155	185/50, 185/55, 195/55		Orig.-Verschr., auch Typ FMCA, FML2
					185/50, 185/55, 195/50, 195/55		Orig.-Verschr., auch Typ FML4
7 x 16	CA 20	54	-	55-155	185/55M+S, 195/50M+S, 195/55		Orig.-Verschr., auch Typ FML2, FML4 u. FMCA
				55-100	185/55, 195/50		
	RC28	52	-	55-100	195/50		Orig.-Verschr., auch Typ FML2, FML4 u. FMCA ✖
				55-155	195/50M+S, 195/55		
	RC30	52	-	55-100	195/50		Orig.-Verschr. ✖
				55-155	195/50M+S, 195/55		
6,5 x 17	RC27	39	-	55-100	195/45		Orig.-Verschr., ✖
				55-155	185/50, 205/45		
7 x 17	RC27	54	-	55-155	205/45		Orig.-Verschr., auch Typ FML2, FML4 u. FMCA
				55-100	195/45, 205/40		
	BR-I	54	-	55-155	205/45		Orig.-Verschr., auch Typ FMCA, FML2 u. FML4, nicht Brembo Bremse
	CA 26	54	ZP593F	55-155	205/45		auch Typ FMCA, FML2 u. FML4
				55-100	195/45, 205/40		
				55-155	205/45		
	RC30	47	-	55-100	195/45, 205/40		Orig.-Verschr., ✖
				55-141	205/45, 215/40, 215/45		
	RC32	47	-	55-155	195/45, 205/40, 205/45, 215/40		Orig.-Verschr., auch Typ FMCA, FML2 u. FML4, ✖
B39	47	-	55-100	195/45, 205/40		Orig.-Verschr., ✖	
			55-155	205/45, 215/40, 215/45			
7 x 18	RC27	54	-	55-155	205/40		Orig.-Verschr., auch Typ FMCA, FML2 u. FML4
	RC32	54	-	55-155	205/40		Orig.-Verschr., auch Typ FMCA, FML2 u. FML4
	RC34	54	-	55-155	205/40		Orig.-Verschr., auch Typ FMCA, FML2 u. FML4
7,5 x 18	RC30	51	-	75-110	205/45, 215/40, 215/45		Orig.-Verschr.
				75-141	225/40		Orig.-Verschr., ✖
	RC32	51	-	55-155	205/35, 205/40		Orig.-Verschr., auch TYP FMCA u. FML2
8,5 x 18	Oxigin 20	50	ZP599F+R	55-155	195/45, 205/40, 205/45		+ Red. Ringe BA12=72,6-66,6 - auch Typ FML4 u. FMCA
8 x 19	RC27	57	-	75-141	225/35		Orig.-Verschr.

Mini John Cooper Works		ab 2021	UKL-L F56 / F57		5/112	66,7	
Sensor - Brocksens 1							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC32	51	-	170	205/40		Orig.-Verschr., 

Mini Cooper C, Mini Cooper S		NEU	2024	FM6	5/112	66,7	e1*2018/858*00373*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC27	47	-		195/55		Orig.-Verschr., i.V., Lieferzeit August
		47	-		205/45, 215/45		Orig.-Verschr., i.V.
	RC30	47	-	100-150	195/45, 195/50, 205/45 , 215/40, 215/45		Orig.-Verschr.
		47	-	110-150	195/45, 195/50, 205/45 , 215/40, 215/45		Orig.-Verschr.
		41	-	100-150	195/45, 195/50, 205/45, 215/40, 215/45		Orig.-Verschr.
7,5 x 17	RC34	45	-	100-150	195/45, 205/45, 215/40, 215/45		Orig.-Verschr.
7,5 x 18	CA 20	40	-	100-150	205/40		Orig.-Verschr.

Mini Cooper		electric NEU i.V.	ab 2024	JM1	5/112	66,7	e1*2018/858*00347*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC27	40	-		195/60		Orig.-Verschr., i.V., Lieferzeit August
7 x 17	RC30	47	-		205/50		Orig.-Verschr., i.V.

Mini Cooper SE		ab 2021	FML2E		5/112	66,7	e1*2007/46*2063*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	54	-	75 (135)	185/55M+S, 195/50, 195/55		Orig.-Verschr.
	RC27	54	-	75 (135)	185/55M+S, 195/50, 195/55		Orig.-Verschr.
	RC32	54	-	75	195/55		Orig.-Verschr.
	CA 20	54	-	75 (135)	185/55M+S, 195/50, 195/55		Orig.-Verschr.
7 x 17	RC27	54	-	75 (135)	195/45, 205/40, 205/45		Orig.-Verschr.
	BR-I	54	-	75	205/45		Orig.-Verschr.
	CA 26	54	ZP593F	75 (135)	195/45, 205/40, 205/45		Orig.-Verschr.
	RC32	47	-	75	195/45, 205/45, 215/40		Orig.-Verschr., ✖
7,5 x 17	B39	47	-	75 (135)	195/45, 205/40, 205/45, 215/40, 215/45		Orig.-Verschr., ✖
	Oxigin 25	54	ZP599F	75	195/45		nicht Bremse 335mm in Verb. mit Brembo

Mini Clubman		ab 2019	UKL-L / FMK (F54)		5/112	66,7	e1*2007/46*0371*19-..., e1*2007/46*1683*...
--------------	--	---------	-------------------	--	-------	------	---

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC28	52	-	75-110	195/60M+S, 205/55 , 215/55, 225/50		Orig.-Verschr., auch Typ FMK, ab 215/55 ✖
				75-155	205/55 , 215/55		Orig.-Verschr., nur M+S, auch Typ FMK, bei 215/55 ✖
	RC30	52	-	75-110	195/60M+S, 205/55 , 215/55, 225/50		Orig.-Verschr., bei 215/55 ✖
				75-155	205/55 , 215/55		Orig.-Verschr., nur M+S, bei 215/55 ✖
7 x 17	RC30	47	-	75-155	195/55		Orig.-Verschr., auch Typ FMK
				75-110	205/50, 225/45		Orig.-Verschr., nur 195/55 auflagenfrei!
				75-141	195/55, 205/50, 215/50, 225/45		Orig.-Verschr., auch Typ FMK, alle M+S außer 215/50
	RC32	47	-	75-155	195/50, 195/55		Orig.-Verschr., auch Typ FMK
	RC34	47	-	75-155	195/50, 195/55		Orig.-Verschr., nur M+S, auch Typ FMK
	B39	47	-	75-155	195/55		Orig.-Verschr., auch Typ FMK, nur M+S
	CA 26	47	ZP599F	75-155	195/55M+S		
	RC27	49	-	75-110	205/50, 225/45		Orig.-Verschr. ✖
				75-141	195/55, 205/50, 215/50, 225/45		Orig.-Verschr., alle M+S außer 215/50 ✖
	RC27	54	-	75-110	205/50, 215/50, 225/45		Orig.-Verschr., auch Typ FMK
				75-141	195/55, 205/50, 215/50, 225/45		Orig.-Verschr., auch Typ FMK, nur M+S
7,5 x 17	CA 26	54	ZP593F	75-110	205/50, 215/50, 225/45		auch Typ FMK
				75-155	195/55, 205/50, 215/50, 225/45		auch Typ FMK, nur M+S
	RC27	54	-	75-110	205/50, 215/50, 225/45 , 235/45		Orig.-Verschr.
				75-155	205/50, 215/45, 225/45		Orig.-Verschr.
	BR-I	54	-	75-155	225/45		Orig.-Verschr., nur zulässig an Fahrzeugausführungen ohne Kunststoff- Verschlusskappen auf Fahrzeugnaben
	RC27	52	-	75-110	205/50, 215/50		Orig.-Verschr., auch Typ FMK, auch 245/45, nicht Bremse 335mm VA, bei 215/50 u. ab 235/45 ✖
				75-155	225/45		
				75-170	235/45		
				170	205/50M+S, 215/50M+S		
	RC28	54	-	75-110	205/50, 215/50		Orig.-Verschr., bei 215/50 ✖
				75-155	195/55, 205/50, 215/50, 225/45, 235/45		Orig.-Verschr., bei 215/50 u. 235/45 ✖
	Oxigin 14	50	ZP599F+R	75-155	225/45		+ Red.Ringe BA12=72,6-66,6 - nicht Brembo- Bremse, auch Typ FMK ✖
				75-170	205/50, 215/50		
	Oxigin 25	54	ZP599F	75-155	205/50, 215/50, 225/45, 235/45		nicht Bremse 280 u. 293mm u. nicht 335mm in Verb. mit Brembo
6,5 x 18	RC34	42	-	75-141	205/45		Orig.-Verschr.
7 x 18	RC32	54	-	75-155	205/45, 215/40, 215/45		Orig.-Verschr., auch Typ FMK
7,5 x 18	RC30	51	-	75-110	205/45, 215/40, 215/45		Orig.-Verschr., auch Typ FMK
				75-155	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr., auch Typ FMK, ab 225/40 ✖
	RC32 / RC34	50	-	75-155	205/45		Orig.-Verschr.
		51	-	75-155	205/45, 215/40, 215/45		Orig.-Verschr., auch Typ FMK
	B32 / B39	51	-	75-110	205/45, 215/40, 215/45		Orig.-Verschr., auch Typ FMK
				75-155	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr., auch Typ FMK, bei 225/40 ✖
	CA 20	51	-	75-155	205/45, 215/40, 215/45		Orig.-Verschr.
	Oxigin 25	51	-	75-155	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr., nicht Brembo Bremse mit 335mm
8 x 18	RC27	57	-	75-155	215/45M+S, 225/40		Orig.-Verschr., auch Typ FMK
				155-170	215/45M+S		Orig.-Verschr., auch Typ FMK
	RC29	57	-	75-155	215/40M+S, 215/45M+S, 225/40		Orig.-Verschr., auch Typ FMK
				75-110	215/40, 215/45		
	RC32	54	-	75-141	205/45, 215/40, 215/45, 225/40		Orig.-Verschr., auch ET54 ist ECE
		57	-	75-155	205/45, 215/40, 215/45, 225/40		Orig.-Verschr.
	RC34	54	-	75-141	225/40		Orig.-Verschr., auch ET54 ist ECE
				75-155	205/45, 215/40, 215/45		Orig.-Verschr.
	B37	54	-	75-110	215/40, 215/45, 235/40		Orig.-Verschr., bei 235/40 ✖
				75-155	215/40M+S, 215/45M+S, 225/40, 245/35		Orig.-Verschr., ab 225/40 ✖
7,5 x 19	B32	52	-	75-110	215/40, 215/45		Orig.-Verschr.
				75-155	225/40, 235/40, 245/35		
8 x 19	B39	51	-	75-155	225/35		Orig.-Verschr., auch Typ FMK, ✖
	Oxigin 18	50	ZP599F	75-170	225/35		nicht Bremse 307 u. 335mm, ✖
	RC27	57	-	75-141	225/35		Orig.-Verschr.
				75-155	225/35		Orig.-Verschr., auch Typ FMK
	RC29	57	-	75-155	225/35 , 235/35		Orig.-Verschr., auch Typ FMK
	RC32	57	-	75-155	215/35, 225/35		Orig.-Verschr.

Mini Clubman John Cooper Works UKL-L / FMK (F54) 5/112 66,7 e1*2007/46*1683*..

Sensor - Brocksens 1

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC34	47	-	170	195/55		Orig.-Verschr.
7,5 x 17	Oxigin 25	54	ZP599F	75-225	205/50, 215/50, 225/45, 235/45		nicht Bremse 280 u. 293mm u. nicht 335mm in Verb. mit Brembo

6,5 x 18	RC34	42	-	225	205/45		Orig.-Verschr., nicht Bremse 335x30mm
7,5 x 18	RC32 / RC34	50+51	-	170-225	205/45M+S		Orig.-Verschr., nicht Bremse 335x30mm
8 x 18	RC32	54	-	225	225/40		Orig.-Verschr., nicht Bremse 360x30mm
		57	-	225	225/40		Orig.-Verschr., auch ET54 ist ECE
	RC34	54	-	225	225/40		Orig.-Verschr., auch ET54 ist ECE
				170-225	205/45M+S		
7,5 x 19	Oxigin 18	50	ZP599F	75-170	225/35		nicht Bremse 307 u. 335mm, ✖
8 x 19	RC32	57	-	170	225/35		Orig.-Verschr.

Mini Countryman	(siehe Konfigurator)	ab 09.10	UKL/X	5/120	72,6	e1*2007/46*0496*...
-----------------	----------------------	----------	-------	-------	------	---------------------

Mini Countryman JCW	(siehe Konfigurator)	ab 2012	UKL/X	5/120	72,6	e1*2007/46*0496*...
---------------------	----------------------	---------	-------	-------	------	---------------------

Mini Countryman	ab 02.2017	FMX (F60)	5/112	66,7	e1*2007/46*1682*..
Sensor - Brocksens 1					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	Pro1	48	F93	75-110	205/60, 205/65, 215/60, 215/65, 225/55, 225/60, 235/55, 235/60		nur M+S, auch Hybrid
7 x 16	RC30	41	-	75-110	205/65		Orig.-Verschr.
6,5 x 17	RC27	39	-	100-155	205/60 M+S		Orig.-Verschr., auch Hybrid (100 kW)
	RC34	39	-	75-155	205/60		Orig.-Verschr.
	RC27	45	-	75-155	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., auch Hybrid (92,100 kW)
	RC27	41	-	75-155	205/60		Orig.-Verschr., auch Hybrid (92,100 kW)
7 x 17	RC27	49	-	75-155	205/60, 215/55, 215/60, 225/55		Orig.-Verschr., auch Hybrid (100 kW)
		47	-	75-155	205/60, 215/55, 215/60		Orig.-Verschr., auch Hybrid (100 kW), nur M+S
	RC32	47	-	77-155	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., ✖
	RC34	41	-	75-155	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
		47	-	75-155	205/55, 205/60, 215/55, 215/60		Orig.-Verschr., auch Hybrid (100kW)
	B39	47	-	75-155	205/60, 215/55, 215/60		
	Pro1	49	ZP599F	75-155	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		
7,5 x 17	RC27	52	-	75-155	225/55		Orig.-Verschr.
	RC32	52	-	75-155	205/55, 205/60, 215/55, 215/60, 225/55		Orig.-Verschr.
	RC34	52	-	75-155	205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., auch Hybrid
	BR-I	52	-	75-155	225/55		Orig.-Verschr.
	AC-518	47	ZP593F	75-155	205/60, 215/55, 215/60		auch Hybrid (100 kW)
6,5 x 18	RC34	42	-	75-141	205/55		Orig.-Verschr.
7,5 x 18	RC30	51	-	75-155	225/50		Orig.-Verschr., auch Hybrid (92,100 kW)
			-	100-110	215/50		
			-	100-155	215/50 M+S, 225/50, 235/45, 245/45		Orig.-Verschr., auch Hybrid (100 kW)
	RC32	51	-	75-155	225/45, 225/50		Orig.-Verschr.
	RC34	51	-	75-155	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	B32	51	-	75-155	215/50 M+S, 225/50, 235/45, 245/45		
			-	75-110	215/50		Orig.-Verschr., auch Hybrid (92,100 kW)
			-	92, 100	215/50 M+S, 225/50, 235/45, 245/45		
	B39	51	-	75-155	215/50 M+S, 225/50, 235/45, 245/45		Orig.-Verschr.
			-	75-110	215/50		
			-	92, 100	215/50 M+S, 225/50, 235/45, 245/45		Orig.-Verschr., Hybrid
	BR-I	51	-	75-155	225/50		Orig.-Verschr.
	CA 20	51	-	75-155	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	Oxigin 25	51	-	75-155	225/50		Orig.-Verschr.
	RC32	50	-	75-155	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Hybrid
	RC34	50	-	75-155	205/55, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Hybrid
8 x 18	RC34	43	-	75-155	225/45		Orig.-Verschr., auch Hybrid
		48	-	75-155	225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., auch Hybrid
	AC-518	50	-	75-155	235/45		Orig.-Verschr. , auch Hybrid (92, 100 kW)
	FMI08 Thoe	49	-	75-155	225/45, 225/50, 235/45, 245/40		Orig.-Verschr., auch Hybrid
	FMI11 Elatha	45	F93	75-155	225/45, 235/45		
7,5 x 19	RC34	45,5	-	75-155	225/40, 225/45		Orig.-Verschr.
	B39	51	-	100-155	225/40, 225/45		Orig.-Verschr. , auch Hybrid (100 kW)
8 x 19	RC32	47	-	75-155	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr. , auch Hybrid (100 kW)
	B40	47	-	75-155	225/40, 225/45		Orig.-Verschr. , auch Hybrid (92,100 kW)
	BR-I	47	-	75-155	225/40, 225/45		Orig.-Verschr., nur für Fahrzeuge ohne Kunststoff Verschlusskappen auf den Fahrzeugnaben
	CA 19	47	ZP599F	75-170	225/45		nicht Bremse 307mm
	FMI07 Atena	47	F93	75-155	225/40, 225/45, 235/40, 245/35, 245/40		
	FMI08 Thoe	47	-	75-155	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	FMI14 Jupiter	47	-	75-155	225/45		Orig.-Verschr.
	RC27	47	-	75-170	225/40, 225/45, 235/40		Orig.-Verschr., nur 225/45 auflagenfrei ✖

	RC32	46	-	75-155	225/40, 225/45, 235/40		Orig.-Verschr., auch Hybrid
	RC34	43	-	75-155	225/40, 225/45		Orig.-Verschr., auch Hybrid
		46	-	75-155	225/40, 225/45, 235/40		Orig.-Verschr., auch Hybrid
		48	-	75-155	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	B38	52	-	75-155	225/40, 225/45, 235/40		Orig.-Verschr. , auch Hybrid (92,100 kW)
	B43	46	-	75-155	225/40, 225/45		Orig.-Verschr. , auch Hybrid (92,100 kW)
8 x 20	B38	52	-	75-155	225/35, 235/35		Orig.-Verschr. , auch Hybrid (92,100 kW)
	B43	46+48	-	75-155	225/35		Orig.-Verschr. , auch Hybrid (92,100 kW)
	FMI08 Thoe	45	-	75-155	225/35, 235/35		Orig.-Verschr.
8,5 x 20	AC-MB6	50	-	75-155	225/35		Orig.-Verschr. , auch Hybrid (92,100 kW)

Mini Countryman Cooper Works				ab 2017	FMX (F60)	5/112	66,7	e1*2007/46*1682*..	
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 17	RC34	45	-	170	205/55, 205/60, 215/55, 215/60, 225/50, 225/55				Orig.-Verschr., nur M+S
6,5 x 18	RC34	42	-	225	205/55				Orig.-Verschr., nicht Bremse 335x30mm
7,5 x 18	RC32	51	-	170	225/50				Orig.-Verschr.
				170-225	205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr., bis 215/50 nur M+S
	RC34	51	-	170-225	205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr., bis 215/50 nur M+S, nicht Bremse 335x30mm
	RC32	50	-	170-225	205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr., bis 215/50 nur M+S, nicht Bremse 335x30mm
	RC34	50	-	170-225	205/55, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr.
8 x 18	RC34	43	-	170-225	225/45				Orig.-Verschr.
		48	-	170-225	225/45, 225/50, 235/45, 245/45				Orig.-Verschr.
	FMI08 Thoe	49	-	170-225	225/45, 225/50, 235/45				Orig.-Verschr., nicht Bremse 335x30mm
	FMI11 Elatha	45	F93	170-225	225/45, 235/45				
7,5 x 19	RC34	45,5	-	170-225	225/40, 225/45				Orig.-Verschr.
8 x 19	RC32	47	-	170-225	225/40, 225/45, 235/40, 245/40				Orig.-Verschr.
	FMI07 Atena	47	F93	170-225	225/40, 225/45, 235/40, 245/40				
	RC32	46	-	170-225	225/40, 225/45, 235/40				Orig.-Verschr.
	RC34	43	-	170-225	225/40, 225/45				Orig.-Verschr.
		46	-	170-225	225/40, 225/45, 235/40				Orig.-Verschr.
		48	-	170-225	225/40, 225/45, 235/40, 245/40				Orig.-Verschr.
	B43	46	-	170-225	225/40, 225/45, 235/40				Orig.-Verschr.
	FMI08 Thoe	47	-	170-225	225/40, 225/45, 235/40, 245/40				Orig.-Verschr., nicht Brembo-Bremse mit 335x30mm
8 x 20	FMI08 Thoe	45	-	170-225	225/35, 235/35				Orig.-Verschr., nicht Brembo-Bremse mit 335x30mm

Mini Countryman SE Hybrid		ab 2020		FMX (F60)		5/112		66,7		e1*2007/46*1682*..	
Sensor - Brocksens 1											
Dimension		Design	ET	KIT	KW	Reifendimension			Info		
7,5 x 17		RC27	52	-	92, 100	225/55				Orig.-Verschr.	
7,5 x 18		B32	51	-	92, 100	225/50				Orig.-Verschr.	

Mini Countryman NEU		ab Februar 2024		UMX	5/112	66,7	e1*2018/858*00370*..	
Sensor - Brocksens 1								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	45	-	100-150	205/65, 215/60, 225/60, 235/55			Orig.-Verschr., nur Bremse 330mm
7,5 x 18	Oxigin 25	51	-	100-150	225/50, 225/55			Orig.-Verschr., mit Radhausverbreiterung, nicht für M-Sportbremse
				100-221	215/55M+S			
		44	ZP599F	100-150	215/55, 225/50, 225/55, 235/50, 245/50			mit Radhausverbreiterung, nicht für 19"-Sportbremse
				100-221	205/60M+S, 215/55M+S			
8 x 20	RC36	46	-	100-150	215/45, 225/40, 235/40, 245/40			Orig.-Verschr., nur Bremse 330mm
8,5 x 20	RC36	40	-	100-150	225/40, 235/40, 245/40			Orig.-Verschr., nur Bremse 330mm
	CA 17	48	ZP599F	100-150	225/40, 235/40			mit Radhausverbreiterung, nicht für M-Sportbremse
				100-221	245/40			

Mini Countryman SE NEU		ab Februar 2024		UMX	5/112	66,7	e1*2018/858*00370*..	
Sensor - Brocksens 1								
Dimension		Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	Oxigin 25	51	-	68-104	215/55M+S, 225/50, 225/55			Orig.-Verschr., mit Radhausverbreiterung, nicht für M-Sportbremse
		44	ZP599F	68-104	205/60M+S, 215/55, 225/50, 225/55, 235/50, 245/50			mit Radhausverbreiterung, nicht für 19"-Sportbremse
8,5 x 20	CA 17	48	ZP599F	68	235/40			mit Radhausverbreiterung, nicht für M-Sportbremse
				68-104	245/40			

Mini Paceman (siehe Konfigurator)		ab 04.13	UKL-C/X	5/120	72,6	e1*2007/46*0563*01	
--	--	----------	---------	-------	------	--------------------	--

Mitsubishi	Baujahr	Typ	LK/LZ	Nabe	
ASX (siehe Konfigurator)	ab MJ2015	GA0	5/114,3	67,1	e1*2007/46*0368*10-...

ASX	ab MJ2020	GA0	5/114,3	67,1	e1*2007/46*0368*21-..
-----	-----------	-----	---------	------	-----------------------

Sensor - Brocksens 4 / Klonen / Anlernprobleme						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	46	-	110	215/70	 Orig.-Verschr.
	RC24	38	ZP580	110	215/65, 215/70, 225/65, 235/60, 235/65	ohne Radhausverbr. ab 225/65 ✖
		42	ZP580D6F	110	215/65, 215/70, 225/65, 235/60, 235/65	ohne Radhausverbr. ab 235/60 ✖
		44	ZP580	110	215/65, 215/70, 225/65, 235/60, 235/65	
	RC27	36	ZP580D6F	110	215/65, 215/70	
		45	ZP580	110	215/65, 215/70, 225/65, 235/60, 235/65	
	RC30	36	ZP580D6F	110	215/65, 215/70	
		44+45	ZP580D6F	110	215/65, 215/70, 225/65, 235/60, 235/65	
6,5 x 17	RC27	40	ZP580D6F	110	215/60, 215/65, 225/60	
	RC27	45	ZP580	110	215/60, 215/65, 225/60	
7 x 17	RC30	45	ZP580D6F	110	215/60, 215/65, 225/60	
			ZP580	110	215/60, 215/65, 225/60	
	B39	45	ZP580	110	215/60, 215/65, 225/60	
7,5 x 17	B36	46	ZP580	110	215/60, 215/65, 225/60	
	AC-518	40	ZP580D6 F+R	110	215/60, 215/65, 225/60, 235/55, 235/60	+ Red. Ringe 73,1-67,1, ohne Radhausverbr. ✖
7,5 x 18	RC30	45	ZP580	110	215/55, 225/55	
	B32	45	ZP580	110	215/55, 225/55	
	AC-521	45	ZP580D6 F+R	110	215/55, 225/55	+ Red.Ringe 73,1-67,1
8 x 18	AC-518	40	ZP580D6 F+R	110	225/55, 235/50	+ Red.Ringe 73,1-67,1, ohne Radhausverbr. ✖
7,5 x 19	B32	45	ZP580D6F	110	225/45, 235/45, 245/45	
	AC-521	45	ZP580D6 F+R	110	225/45, 235/45, 245/45	+ Red.Ringe 73,1-67,1
	RC29	38	ZP580	110	225/45, 235/45, 245/45	ohne Radhausverbr. ✖
8 x 19	AC-518	40	ZP580D6 F+R	110	225/45	+ Red.Ringe 73,1-67,1
	B38	45	ZP580	110	215/45, 225/40, 235/40	
8,5 x 20	RC29	45	ZP580	110	225/40, 235/40	
	B24	42	ZP580	110	225/40, 235/40	mit Radhausverbreiterungen
	AC-518	40	ZP580D6 F+R	110	225/40, 235/40	+ Red.Ringe 73,1-67,1, ohne Radhhausverbr. ✖

ASX (II) NEU		ab 2023			RJB	5/114,3	66,1	e2*2007/46*0684*21-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 17	RC27	32	-	67-116	215/60, 225/55, 235/55				Orig.-Verschr.
7 x 17	RC27	35	-	67-116	215/60				Orig.-Verschr., Ausführung N13
	RC34	35	-	67-116	215/60, 235/55				Orig.-Verschr., Ausführung N42
7,5 x 17	RC28	35	ZP581	67-116	215/60				
7 x 18	RC27	35	-	67-116	215/50				Orig.-Verschr.
		34	-	67-116	215/50, 215/55, 225/50				Orig.-Verschr.
	RC32	35	-	67-116	215/50, 215/55, 225/50, 235/50				Orig.-Verschr.
7,5 x 18	RC34	35	-	67-116	215/50, 215/55, 225/50, 245/45				Orig.-Verschr.
	B32	35	ZP581	67-116	215/50, 215/55				
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	67-116	215/50, 215/55				Kit mit Artikelnummer 98478
8 x 19	B40	35	ZP581	67-116	225/45				
8 x 20	RC36	35	-	67-116	225/40				Orig.-Verschr.
	B38	35	ZP581	67-116	225/40				
	B40	35	ZP581	67-116	225/40				

ASX (II) PHEV NEU		ab 2023			RJB	5/114,3	66,1	e2*2007/46*0684*21-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC27	35	-	68	215/60				Orig.-Verschr., Ausführung N13
	RC34	35	-	68	215/60, 225/55, 235/55, 245/50				Orig.-Verschr., Ausführung N42
7 x 18	RC27	35	-	68	215/55				Orig.-Verschr.
		34	-	68	215/50, 215/55				Orig.-Verschr.
	RC32	35	-	68-80	215/55, 225/50, 235/50				Orig.-Verschr.
7,5 x 18	RC34	35	-	68-69	215/55, 225/50, 235/50, 245/45				Orig.-Verschr.
8 x 18	B42	30	ZP581	68	215/55				
	B44	30	ZP581	68	215/55				
	B44	30	ZP581	68	225/45				
8,5 x 19	CA 20	30	ZP581	68	225/45				

	Oxigin 28	30	ZP581	68	225/45		
8,5 x 20	B44	30	ZP581	68	225/40		

Colt NEU		3.Quartal 2023			RJA	4/100	60,1	e2*2007/46*0676*22-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 16	RC30	37	-	49-69	185/55, 185/60, 195/50, 195/55				Orig.-Verschr.
	RC34	37	-	49-69	195/55				Orig.-Verschr.
				49-69	185/55, 195/50, 195/55, 205/50, 215/50				
7 x 17	RC34	37	-	49-69	205/45				Orig.-Verschr.
				49-69	195/45, 205/45, 215/40, 215/45				
	B24	38	ZP440	49-69	195/45, 205/45				

Eclipse Cross		ab 2017	GK0	5/114,3	67,1	e1*2007/46*1769*..	
Sensor - Brocksens 4 / Klonen / Anlernprobleme							

ACHTUNG! wenn in Serie 18"eingetragen sind, können keine kleineren Dimensionen montiert werden, Bremse passt nicht!

6,5 x 16	RC32	38	ZP580D6F	109-120	215/70 , 225/65, 235/60, 235/65				
	RC24	38	ZP580	109-120	215/65, 215/70, 225/65, 235/60, 235/65				nicht Bremse 320mm
	RC27	38	ZP580	109-120	215/65, 215/70, 225/65, 235/60, 235/65				
	RC30	38	ZP580	109-120	215/65, 215/70, 225/65, 235/60, 235/65				nicht Bremse 320mm
7 x 17	RC27	38	ZP580	120	215/60, 215/65, 225/60, 235/55, 235/60, 245/55				
		40	ZP580D6F	120	215/60, 215/65, 225/60, 235/55, 235/60, 245/55				
	RC30	38	ZP580	109-120	215/60, 215/65, 225/60, 235/55, 235/60, 245/55				
	B39	38	ZP580	109-120	215/60, 215/65, 225/60, 235/55, 235/60, 245/55				
7,5 x 17	RC24	38	ZP580	109, 120	215/60, 215/65, 225/60, 235/55, 235/60				
	RC28	35	ZP580	120	215/60, 215/65, 225/60, 235/55, 235/60				
	RC29	38	ZP580	109-120	215/60, 215/65, 225/60, 235/55, 235/60				
	B24	38	ZP580	109-120	215/60, 215/65, 225/60, 235/55, 235/60				
	AC-518	40	Artikel Nr. 98499	109-120	215/60, 215/65, 225/60, 235/55, 235/60				Kit mit Artikelnummer 98499
	Oxigin 25	45	ZP580	109-120	215/60, 215/65				
7 x 18	RC27	38	ZP580D6F	120	215/55, 215/60, 225/55 , 235/50,				
	RC32	38	ZP580D6F	109-120	215/55, 215/60, 225/55 , 235/50, 235/55, 245/50				
	RC34	38	-	109-120	225/55				Orig.-Verschr.
7,5 x 18	RC30	35	ZP580	120	215/55, 225/50, 225/55, 235/50, 235/55				
	B32	35	ZP580	109-120	215/55, 225/50, 225/55, 235/50, 235/55				
	AC-MB6 / AC-M10	35	Artikel Nr. 98499	109-120	215/55, 225/50, 225/55, 235/50, 235/55				Kit mit Artikelnummer 98499
	RC29	35	ZP580	120	225/50, 225/55				
8 x 18	B24	38	ZP580	109-120	225/50, 225/55, 235/50, 235/55				
	B42 / B44	40	ZP580	109-120	225/50, 225/55, 235/50				
	AC-518	40	Artikel Nr. 98499	109, 120	225/50, 225/55, 235/50				Kit mit Artikelnummer 98499
7,5 x 19	B32	40	ZP580	109-120	225/45, 235/45, 245/45				
	Oxigin 18	40	ZP580	120	235/45, 245/45				bei 245/45 ✖
8 x 19	RC29	38	ZP580	120	225/45, 235/45				
	B24	38	ZP580	120	225/45, 235/45				
	B38	38	ZP580	109-120	225/45, 235/45				
	B40	35	ZP580	109-120	225/45, 235/45				
	AC-518	40	Artikel Nr. 98499	109-120	225/45, 235/45, 245/45				Kit mit Artikelnummer 98499
	CA 17	40	ZP580	72-120	235/45				
	Oxigin 29	40	ZP580	109-120	225/45, 235/45, 245/45				
8,5 x 19	B36	38	ZP580	109-120	225/45, 235/45				
	B42	35	ZP580	109-120	225/45, 235/45				
	B44	40	ZP580	109-120	225/45, 235/45, 245/45				
	CA 23	40	ZP580	109-120	225/45, 235/45, 245/45				
8 x 20	B38	35	ZP580	109, 120	215/45				
	B40	35	ZP580D6F	109-120	215/45				
8,5 x 20	RC29	40	ZP580	120	235/40, 245/40				bei 245/40 ✖
	B32	40	ZP580	109, 120	235/40				
	B44	40	ZP580	109-120	235/40				

Eclipse Cross PHEV Hybrid					ab 2020	GK0	5/114,3	67,1	e1*2007/46*1769*..	
Sensor - Brocksens 4 / Klonen / Anlernprobleme										
Dimension	Design	ET	KIT	KW	Reifendimension				Info	
7 x 17	RC27	38	ZP580	72	215/60, 215/65, 225/60, 235/55, 235/60, 245/55					
7,5 x 17	RC24	38	ZP580	72	215/60, 215/65, 225/60, 235/55, 235/60					
	B24 / B36	38	ZP580	72	215/60, 215/65, 225/60, 235/55, 235/60					

8 x 18	B32 / B39	35	ZP580	108, 110	215/55, 225/55, 235/50		incl. Facelift 2016, auch Typ GF0
	RC29	35	ZP580	108, 110	225/55, 235/50, 245/50, 255/45		incl. Facelift 2016, ab 235/50 ✖
	B36	35	ZP580	108, 110	225/55, 235/50, 245/50, 255/45		
	B37	35	ZP580	108, 110	225/55, 235/50, 245/50, 255/45		incl. FL2016, ohne Radhausverb. ab 235/50 ✖
7,5 x 19	AC-518	40	ZP580D6 F+R	108, 110	225/55, 235/50, 255/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2016, (auch FIN: JMBX.GF..)
	B32	40	ZP580	108, 110	225/45, 235/45, 245/45		incl. FL2016
	B39	40	ZP580	108, 110	225/45, 235/45, 245/45		incl. FL2016, auch Typ GF0
	Oxigin 18	40	ZP580	103-130	235/45, 245/45		
8 x 19	RC29	38	ZP580	108, 110	225/45, 235/45, 245/45, 255/45		
	B24	38	ZP580	108, 110	225/45, 235/45, 245/45, 255/45		incl. FL2016
	B38	38	ZP580	108, 110	225/45, 235/45, 245/45, 255/45		incl. FL2016, (auch FIN. JMBX.GF..) ohne Radhausverbr. bei 255/45 ✖
	B40	35	ZP580	108-110	225/45, 235/45, 245/45, 255/45		incl. FL2016, (auch FIN. JMBX.GF..) ohne Radhausverbr. bei 255/45 ✖
	AC-518	40	ZP580D6 F+R	108-110	225/45, 235/45, 245/45, 255/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2016, (auch FIN: JMBX.GF..)
8 x 20	B38	35	ZP580	108, 110	235/40, 245/40		incl. Facelift 2016, (auch FIN: JMBX.GF..)
	B40	35	ZP580	108, 110	235/40, 245/40		incl. Facelift 2016, (auch FIN: JMBX.GF..)

weitere Dimensionen/Designs siehe Konfigurator

Outlander III Hybrid							
ab 2013				CWO	5/114,3	67,1	e1*2001/116*0406*17*...
Sensor - Brocksens 4 / Klonen / Anlernprobleme							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC27	38	-	89	215/70		Orig.-Verschr.
	RC24	36	ZP580D6F	89	215/70, 225/65, 235/60, 235/65		incl. Facelift 2016
		38	ZP580	89	215/70, 225/65, 235/60, 235/65		
	RC30	36	ZP580D6F	89	215/70, 225/65, 235/60, 235/65		
		38	ZP580	89	215/70, 225/65, 235/60, 235/65		
7 x 16	RC24	38	ZP580	89	215/70, 225/65, 235/60, 235/65, 245/60		incl. Facelift 2016
	RC28	35	ZP580	89	215/70, 225/65, 235/60, 235/65		
	RC30	40	ZP580D6F	89	215/70, 225/65, 235/60, 235/65, 245/60		incl. Facelift 2016
6,5 x 17	RC27	40	ZP580D6F	89	215/60, 215/65, 225/60, 235/55, 235/60		
7 x 17	RC27	36+38	ZP580	89	215/60, 215/65, 225/60, 235/55, 235/60		ET36 KEIN RED. Ring
		40	ZP580D6F	89, 99	215/60, 215/65, 225/60, 235/55, 235/60, 245/55		incl. Facelift 2016
	RC30	38	ZP580	89-99	215/60, 215/65, 225/60, 235/55, 235/60, 245/55		incl. Facelift 2016
	B39	38	ZP580	89	215/60, 215/65, 225/60, 235/55, 235/60, 245/55		incl. Facelift 2016
7,5 x 17	RC24	38	ZP580	89	215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2016
	RC28	35	ZP580	89	215/60, 215/65, 225/60		
	RC29	38	ZP580	89	215/60, 215/65, 225/60, 235/55, 235/60		incl. FL2016
	B24	38	ZP580	89, 99	215/60, 215/65, 225/60, 235/55, 235/60		incl. FL2016
	B36	38	ZP580	89	215/60, 215/65, 225/60, 235/55, 235/60, 245/55		incl. FL2016, ohne Radhausverbr. bei 245/55 ✖
	AC-518	40	ZP580D6 F+R	89-99	215/60, 215/65, 225/60, 235/55, 235/60, 245/55		+ Red.Ringe 73,1-67,1, incl. Facelift 2016
7 x 18	RC27	38	ZP580D6F	89	225/55, 235/50, 235/55		
	RC34	38	-	89-110	225/55		Orig.-Verschr.
7,5 x 18	RC30	35	ZP580	89	215/55, 225/55		
	B32 / B39	35	ZP580	89	215/55, 225/55		incl. Facelift 2016
8 x 18	RC29	35	ZP580	89	225/55, 235/50, 245/50		ab 235/50 ✖
	B24	38	ZP580	89	225/55, 235/50, 245/50		incl. Facelift 2016, ab 235/50 ✖
	B36	35	ZP580	89	225/55, 235/50, 245/50		ab 235/50 ✖
	B37	35	ZP580	89	225/55, 235/50, 245/50		incl. Facelift 2016, ab 235/50 ✖
	AC-518	40	ZP580D6 F+R	89, 99	225/55, 235/50		+ Red.Ringe 73,1-67,1, incl. Facelift 2016
7,5 x 19	B32 / B39	40	ZP580	89	225/45, 235/45, 245/45		incl. Facelift 2016
8 x 19	RC29	38	ZP580	89	225/45, 235/45, 245/45		
	B24	38	ZP580	89	225/45, 235/45, 245/45		incl. Facelift 2016
	B40	35	ZP580	89-99	225/45, 235/45, 245/45		incl. Facelift 2016
	AC-518	40	ZP580D6 F+R	89-99	225/45, 235/45, 245/45		+ Red.Ringe 73,1-67,1, incl. Facelift 2016
8 x 20	B38	35	ZP580	89, 99	235/40, 245/40		incl. Facelift 2016
	B40	35	ZP580	89	235/40, 245/40		incl. Facelift 2016

weitere Dimensionen/Designs siehe Konfigurator

Outlander NEU							
2025				GN0W	5/114,3	66,1	e1*2018/858*00511*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC34	35	-	100	235/60, 245/55		Orig.-Verschr.
8 x 20	RC36	35	-	100	255/45		Orig.-Verschr., Plug-in Hybrid
					235/45, 235/50, 245/45, 255/45		

Pajero							
ab 2006				V80	6/139,7	67,1	e1*2001/116*0385*...

Dimension	Design	ET	KIT	KW	Reifendimension	Info
Nur verwenden wenn mit Alufelgen (Serienverschraubung) ausgeliefert						
7 x 16	RC31	38+46	-	118-125	265/70	Orig.-Verschr. für Alufelgen
8 x 18	RC31	38	-	118-184	265/60, 285/55, 285/60	Orig.-Verschr., fix geb., 

Space Star		ab 04.16	A00	4/100	56,1	e1*2007/46*0951*..
Sensor - Brocksens 4 / Klonen / Anlernprobleme						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
5 x 14	RC30	39	ZP428	52, 59	165/65, 175/60	
6 x 15	RC24	40	-+R	52, 59	165/55, 165/60	Orig.-Verschr. + Ringe BA05=63,4 - 56,1
	RC30	40	-+R	52, 59	165/55, 165/60	Orig.-Verschr. + Ringe BA05=63,4 - 56,1

Space Star Cross		ab 04.16	A00	4/100	56,1	e1*2007/46*0951*..
Sensor - Brocksens 4 / Klonen / Anlernprobleme						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	40	ZP428	52, 59	165/55, 165/60	
	RC30	40	ZP428	52, 59	165/55, 165/60	

Nissan

	Baujahr	Typ	LK/LZ	Nabe	
Ariya	2022	FE0E	5/114,3	66,1	e13*2018/858*00237*...
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 19	RC34	40	-	45-90	235/55, 245/50, 255/50	 Orig.-Verschr.
		35	-	45-90	235/55, 245/50	Orig.-Verschr.
		45	-	45-90	245/50, 255/50	Orig.-Verschr.
	CA 26	45	ZP578	45, 90	235/55, 245/50, 255/50	
	FMI10 e-Joule	40	-	45-90	235/55	 Orig.-Verschr.
8 x 19	RC29	38	ZP578	45, 90	235/55	
	B40	35	ZP578	45, 90	235/55	
	CA 17	40	ZP578	45-90	235/55	
	CA 19	45	ZP578	45, 90	235/55, 245/50, 255/50	
	CA 24	45	ZP578	45-90	235/55	
	FMI08 Thoe	40	-	45-90	235/55, 245/50	Orig.-Verschr.
	Oxigin 29	40	ZP578	45, 90	235/55, 245/50	
8,5 x 19	B32	45	ZP578	45, 90	235/55, 245/50, 255/50, 265/45, 275/45	
	B36	38	ZP578	45, 90	235/55	
	B44	40	ZP578	45, 90	235/55	
	CA 23	40	ZP578	45, 90	235/55	
	Oxigin 28	45	ZP578	45, 90	235/55, 245/50, 255/50, 265/45, 275/45	
8 x 20	B43	45	-	45, 90	255/45	 Orig.-Verschr.
	RC36	40	-	45, 90	235/45, 235/50, 245/45, 255/45	Orig.-Verschr., Ausführung N43
	B38	35	ZP578	45, 90	235/45, 245/45, 255/45	
		45	ZP578	45, 90	235/45, 235/50, 245/45, 255/45	
	B40	35	ZP578	45, 90	235/45, 245/45, 255/45	
	B43	40	-	45, 90	235/45, 235/50, 245/45, 255/45	Orig.-Verschr., Ausführung N42 u. N43
	AC-521	45	ZP578D2F+R	45, 90	235/45, 235/50, 245/45, 255/45	
8,5 x 20	RC36	37	-	45, 90	235/45, 235/50, 245/45, 255/45	Orig.-Verschr.
	B42	35	ZP578	45, 90	235/45, 245/45	
		45	ZP578	45, 90	235/45, 235/50, 245/45, 255/45	
	B44	40	ZP578	45, 90	235/45, 235/50, 245/45, 255/45	
9 x 20	CA 20 / CA 23	45	ZP578	45, 90	235/45, 245/45, 255/45, 265/40	
	Oxigin 28	40	ZP578	45, 90	235/45, 245/45, 255/45	

Juke (siehe Konfigurator)	ab 12.10	F15	5/114,3	66,1	e11*2007/46*0132*..., e3*2007/46*0162*..., e5*2007/46*1031*..
---------------------------	----------	-----	---------	------	---

Juke	ab 2019	F16	5/114,3	66,1	e9*2007/46*6697*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	32	-	86	215/65, 225/60, 225/65, 235/60	 Orig.-Verschr., Ausführung N13
	RC34	32	-	84-86	215/65, 225/60, 235/60	 Orig.-Verschr., Frontantrieb
6,5 x 17	RC27	32	-	84, 86	215/60, 225/55, 235/55	Orig.-Verschr.
7 x 17	RC27	35	-	69-86	215/60, 225/55	 Orig.-Verschr.
	RC32	35	-	84-86	215/55, 215/60, 225/55, 235/50	 Orig.-Verschr.
	RC34	35	-	84-86	215/55, 215/60, 225/55, 235/50	 Orig.-Verschr.
7,5 x 17	RC28	35	ZP581	69-86	215/60	
7 x 18	RC27	34	-	69-86	215/50, 215/55, 225/50	Orig.-Verschr.
	RC32	35	-	84-86	215/50, 215/55, 225/50	Orig.-Verschr., Frontantrieb
7,5 x 18	RC30	35	ZP581	84, 86	215/50, 215/55, 235/45	
	B32	35	ZP581	69-86	215/50, 215/55, 235/45	
	B39	35	ZP581	84, 86	215/50, 215/55, 235/45	
	AC-MB6	35	Artikel Nr. 98478	69-86	215/50, 215/55, 235/45	Kit mit Artikelnummer 98478
	AC-521	35	Artikel Nr. 98478	69-86	215/50, 215/55, 235/45	Kit mit Artikelnummer 98478
8 x 18	RC29	35	ZP581	84, 86	215/55, 235/45	
	B36	35	ZP581	69-86	215/55, 235/45	
	B37	35	ZP581	84, 86	215/55, 235/45	
	B42 / B44	30	ZP581	69-86	215/55, 235/45	
7,5 x 19	RC34	35	-	84-86	225/45	 Orig.-Verschr.
	AC-521	35	Artikel Nr. 98478	69-86	225/45, 235/45	 Kit mit Artikelnummer 98478
8 x 19	B40	35	ZP581	69-86	225/45	
8,5 x 19	B44	30	ZP581	69-86	225/45	
	Oxigin 28	30	ZP581	69-86	225/45	
8 x 20	B38	35	ZP581	69-86	225/40	
	B40	35	ZP581	69-86	225/40	
8,5 x 20	B44	30	ZP581	69-86	225/40	

Leaf (siehe Konfigurator)	ab 2013	ZE0	5/114,3	66,1	
----------------------------------	----------------	------------	----------------	-------------	--

Leaf	ab 2018	ZE1	5/114,3	66,1	e9*2007/46*6537*..
-------------	----------------	------------	----------------	-------------	--------------------

Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	40	-	90 (110)	205/55 , 205/60, 215/55, 225/50	 Orig.-Verschr.
	RC32	40	-	90 (110)	205/55 , 205/60, 215/50, 215/55, 225/50, 225/55, 235/50	 Orig.-Verschr.
	RC34	40	-	90 (110)	205/55 , 205/60, 215/50, 215/55, 225/50, 225/55, 235/50	 Orig.-Verschr.
	RC24	38	ZP578	90 (110)	205/55, 205/60, 215/55	
		44	ZP578	90 (110)	205/55, 205/60, 215/55, 225/50	
	RC27	44	-	90 (110)	205/55, 205/60, 215/55, 225/50	Orig.-Verschr.
		45	ZP578	90 (110)	205/55, 205/60, 215/55, 225/50	
	RC30	38+45	ZP578	90 (110)	205/55, 205/60, 215/55, 225/50	ET38 bei 225/50 ✖
	RC32	41	-	90 (110)	205/55, 205/60, 215/50, 215/55, 225/50, 225/55, 235/50	Orig.-Verschr.
	CA 20	45	ZP578	90	205/55, 205/60, 215/55, 225/50	
7 x 17	RC27	40	-	90 (110)	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
		35	ZP578	90 (110)	205/50, 215/45, 225/45	
		38+45	ZP578	90 (110)	205/50, 215/45, 215/50, 225/45	
	RC30	45	-	90 (110)	205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
			ZP578	90 (110)	205/50, 215/45, 215/50, 225/45	
	RC32	35	ZP578D2F	90 (110)	205/45, 205/50, 215/45, 225/45	
		40	-	90 (110)	205/45, 205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
		43	-	90 (110)	205/45, 205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
	RC34	43	-	90 (110)	205/45, 205/50, 215/45, 215/50, 225/45	Orig.-Verschr.
	B39	38+45	ZP578	90 (110)	205/50, 215/45, 215/50, 225/45	
7,5 x 17	RC24	38	ZP578	90 (110)	205/50, 215/45, 225/45	
		45	ZP578	90 (110)	205/50, 215/45, 215/50, 225/45	
	RC28	45	ZP578	90 (110)	205/50, 215/45, 215/50, 225/45	
	RC29	38	ZP578	90 (110)	205/50, 215/45, 225/45	
	B24	38	ZP578	90 (110)	205/50, 215/45, 225/45	max.Leistung: 110, 160kW
	B36	38	ZP578	90 (110)	205/50, 215/45, 225/45	
	AC-518	40	ZP578D2F+R	90 (110)	205/50, 215/45, 225/45	+ Red.Ringe 73,1-66,1
	Oxigin 25	45	ZP578	90	205/50, 205/55, 215/45, 225/45	
7 x 18	RC27	40	-	90 (110)	215/40, 215/45	Orig.-Verschr.
	RC32	35+40+45	-	90 (110)	205/40, 205/45, 215/40, 215/45	Orig.-Verschr.
7,5 x 18	RC30	45	ZP578	90 (110)	205/45, 215/40, 215/45, 225/40	max.Leistung: 110, 160kW
	RC34	40	-	90	205/40, 205/45, 215/40, 215/45, 225/35, 225/40	Orig.-Verschr.
	B32	35	ZP578	90 (110)	205/45, 215/40, 215/45	
		45	ZP578	90 (110)	205/45, 215/40, 215/45, 225/40	
	B39	35	ZP578	90 (110)	205/45, 215/40, 215/45	
		45	ZP578	90 (110)	205/45, 215/40, 215/45, 225/40	
	AC-521	35	ZP78D2F+R	90 (110)	205/45, 215/40, 215/45	+ Red.Ringe 73,1-66,1
	RC29	45	ZP578	90 (110)	215/40, 215/45, 225/40	max.Leistung: 110, 160kW
	B24	38	ZP578	90	215/40, 215/45	max.Leistung: 110, 160kW
	B37 / B38	45	ZP578	90 (110)	215/40, 215/45, 225/40	
8 x 18	B42	40+45	ZP578	90	215/40, 215/45, 225/40	max.Leistung: 110, 160kW
	AC-518	40	ZP578D2F+R	90 (110)	215/40, 215/45, 225/40	+ Red.Ringe 73,1-66,1
7,5 x 19	B32	40	ZP578	90 (110)	225/35	max.Leistung: 110, 160kW
	AC-521	45	ZP578D2F+R	90	225/35	+ Red.Ringe 73,1-66,1
8 x 19	AC-518	40	ZP578D2F+R	90 (110)	225/35	+ Red.Ringe 73,1-66,1

Micra (siehe Konfigurator)	ab 07.11	K13	4/100	60,1	e13*2007/46*1111*..
-----------------------------------	-----------------	------------	--------------	-------------	---------------------

Micra	ab 03.2017	K14	4/100	60,1	e9*2007/46*6454*..
--------------	-------------------	------------	--------------	-------------	--------------------

Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC30	50	-	52,66,74	185/65	 Orig.-Verschr.
				52-86	185/60, 185/65, 195/60, 205/55, 205/60	
	RC24	40	ZP440	52-86	185/60, 185/65	
	RC30	40	ZP440	52-86	185/60, 185/65	

6,5 x 15	RC28	45	ZP440	52, 66	185/60, 185/65, 195/60		
6 x 16	RC30	50	-	52-86	185/55, 195/50, 195/55 , 205/50		Orig.-Verschr.
6,5 x 16	RC24	48	ZP440	52, 66	185/55, 195/50, 195/55		
	RC30	48	ZP440F	52-86	185/55, 195/50, 195/55		
7 x 17	B24	45	ZP440	52-86	195/45M+S, 205/45		
	B39	44	ZP440	52, 66	195/45		

Navara (siehe Konfigurator)	ab 05.05	D40	6/114,3	66,1	L617
------------------------------------	-----------------	------------	----------------	-------------	------

Navara	ab 2015	962D (D401)	6/114,3	66,1	e9*2007/46*0018*...
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
7 x 16	RC31	30	-	106-140	235/70, 245/70, 245/75, 255/65, 255/70, 265/70		Orig.-Verschr. bei Alufelgen,nicht Bremse 320mm
	Matrix T	30	ZP610F	106-140	235/70, 245/70, 245/75, 255/65, 255/70, 265/70		nicht Bremse 320mm
7 x 17	RC31	30	-	106-170	255/60, 255/65		Orig.-Verschr.
7,5 x 17	RC14 6S	30	ZP610F	106-140	235/70, 245/65, 245/70, 255/65, 265/60, 265/65		
8 x 18	RC31	30	-	106-170	255/55, 255/60, 265/55, 265/60		Orig.-Verschr.

Navara NP300	2016	D231	6/114,3	66,1	e9*2007/46*6364*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
7 x 16	RC31	45	ZP610F	120-140	255/65, 255/70		nur in silber
7 x 17	RC31	30	-	120	225/65, 225/70, 235/65, 235/70, 245/65		Orig.-Verschr., ab 245/65 ✖
				120-140	255/60, 255/65		
7,5 x 17	RC14-6S	40	ZP610F	120	225/65, 245/60, 275/55		bei 275/55 ✖
				120-140	255/65, 265/60, 275/60		ab 265/60 ✖
8,5 x 17	8400 Bluster	32	-	120	245/60, 275/55		Orig.-Verschr., mit Serienreifen 205/..., ✖
				120-140	255/65, 265/60, 275/60		Orig.-Verschr., mit Serienreifen 255/..., ✖
8 x 18	RC31	45	ZP610F	120-140	255/60		
	8400 Bluster	42	-	120	225/60, 235/55, 245/55, 255/55, 255/55C		Orig.-Verschr., nur Allrad, mit Serienreifen 205/...
				120-140	255/60, 265/55		Orig.-Verschr., nur Allrad, mit Serienreifen 255/..., bei 265/55 ✖
9 x 20	Oxigin 24	25	ZP610F	120-140	255/45, 265/40, 265/45, 265/50, 275/40, 275/45, 285/45		✖

Note	ab 2013	E12	4/100	60,1
Sensor - Brocksens 4				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	40	ZP442	59, 66, 72	185/65, 195/60, 205/55		
	RC30	37	ZP442	59, 66, 72	175/65, 185/65		ab 205/55 ✖
		40	ZP442	59, 66, 72	175/65, 185/65		
6,5 x 15	RC28	35+45	ZP442	59, 66, 72	185/65, 195/60, 205/55		ET35 ab 205/55 ✖
6,5 x 16	RC30	38	ZP442	59, 66, 72	185/55, 195/50, 195/55, 205/50		bei 205/50 ✖
7 x 16	RC28	45	ZP442	59, 66, 72	195/50, 195/55, 215/45		
7 x 17	B24	38	ZP442	59, 66, 72	195/45, 205/45		
	B39	38	ZP442	59, 66, 72	195/45, 205/45		
		44	ZP442	59, 66, 72	195/45, 205/45, 215/40, 215/45		

NV 200	ab 2013	M20M I-N	4/114,3	66,1
Sensor - Brocksens 4				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	B24	40	ZP478	63-81	195/50, 215/45		

e-NV200	ab 2014	ME0M / ME0N	5/114,3	66,1	e11*2007/46*1340*..., e11*2007/46*1339*..., e5*2007/46*1028*..., e5*2007/46*1035*..
Sensor - Brocksens 4					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC30	45	ZP578	80	185/65		
6,5 x 16	RC32	40+41	-	80	195/55, 205/50		Orig.-Verschr.
	RC34	40	-	80	195/55, 205/50		Orig.-Verschr.
7 x 17	RC32	40	-	80	215/45		Orig.-Verschr.
		43	-	80	215/45		Orig.-Verschr.
	RC34	43	ZP578D2F	80	215/45		
	Pro1	45	ZP578D2F	80	215/45		

NV 300 (siehe Konfigurator)	ab 2014	4, J4	5/114,3	66,1	e2*2007/46*0037*11-..
------------------------------------	----------------	--------------	----------------	-------------	-----------------------

NV 400 (siehe Konfigurator)	ab 2011	M1/M9/V9	5/130	89,1	e2*2007/46*0137*..., e2*2007/46*0142*..., e2*2007/46*0151*..
------------------------------------	----------------	-----------------	--------------	-------------	--

Pulsar (siehe Konfigurator)		ab 11.2014		C13	5/114,3	66,1	e9*2007/46*3086*...	
Qashqai (siehe Konfigurator)		ab 2014		J11	5/114,3	66,1	e11*2007/46*0963*..., e5*2007/46*1029*...	
Sensor - Brocksens 4								
Qashqai NEU		im Laufe 2. Quartal 2021		J12	5/114,3	66,1	e9*2018/858*11042*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC27	40	-		215/65		Orig.-Verschr., i.V.	
	RC32	40	-	103-116	215/65		Orig.-Verschr.	
	RC34	40	-	103-116	215/65		Orig.-Verschr.	
	RC27	35	-	103, 116	215/65, 225/60, 235/60		Orig.-Verschr.	
		38	ZP581	103, 116	215/65, 225/60, 235/60		incl. Facelift 2024, ohne e-Power	
	RC32	35	-	103-116	215/65, 225/60, 235/60		Orig.-Verschr.	
		43	-	103-116	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.	
	RC34	43	-	103-116	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.	
	B39	38	ZP581	103, 116	215/65, 225/60, 235/60			
	AC-V51	45	ZP590F	103, 116	215/65, 225/60, 235/60			
Pro1	45	F28	103-116	215/65, 225/60, 225/65, 235/60, 245/55, 245/60				
7,5 x 17	RC28	35	ZP581	103, 116	215/65, 225/60, 235/60		ohne e-Power	
	RC29	38	ZP581	103, 116	215/65, 225/60, 235/60			
	B24	38	ZP581	103, 116	215/65, 225/60, 235/60		ohne e-Power	
7 x 18	RC27	34	-	103, 116	215/60, 225/55		Orig.-Verschr., incl. Facelift 2024	
		35	-	103, 116	215/60, 225/55, 235/55		Orig.-Verschr., incl. Facelift 2024	
		40	-	103, 116	215/60, 225/55, 235/55, 245/50		Orig.-Verschr.	
	RC32	35	-	103-116	215/60, 225/55, 235/55		Orig.-Verschr.	
		40	-	103-116	215/60, 225/55, 225/60, 235/55, 245/50, 255/50		Orig.-Verschr.	
7,5 x 18	RC32	45	-	103-116	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.	
	RC30	35	ZP581	103, 116	215/60, 225/55			
		45	ZP581	103, 116	215/60, 225/55, 235/55			
	RC34	40	-	103-116	215/60, 225/55, 225/60, 235/55, 245/50		Orig.-Verschr.	
	B32	35	ZP581	103, 116	215/60, 225/55			
		45	ZP581	103, 116	215/60, 225/55, 235/55			
	B39	45	ZP581	103, 116	215/60, 225/55, 235/55			
	AC-MB6 / AC-M10	45	Artikel Nr. 98478	103, 116	215/60, 225/55, 235/55		Kit mit Artikelnummer 98478, incl. Facelift 2024, ohne e-Power	
				116	235/55		Kit mit Artikelnummer 98478, incl. Facelift 2024, e-Power	
	AC-521	35	ZP590F+R	103, 116	215/60, 225/55		+ Red.Ringe 73,1-66,1	
		45	ZP590F+R	103, 116	215/60, 225/55, 235/55		+ Red.Ringe 73,1-66,1	
	CA 20 Oxigin 25	40	ZP581	103-116	215/60, 225/55, 225/60, 235/55, 245/50			
45		ZP581	103-116	215/55, 215/60, 225/55, 235/50, 235/55				
8 x 18	B24	38	ZP581	103, 116	225/55, 235/55		ohne e-Power	
				116	235/55		e-Power	
	B37	35	ZP581	103, 116	225/55			
	B36	35	ZP581	103, 116	225/55		ohne e-Power	
	B38	35	ZP581	103, 116	225/55			
	B42	40	ZP581	103, 116	225/55, 235/55		ohne e-Power	
				116	235/55		e-Power	
	B44	40	ZP581	103, 116	225/55, 235/55		incl. Facelift 2024, ohne e-Power	
				116	235/55		incl. Facelift 2024, e-Power	
CA 24	45	ZP581	103-116	225/55, 235/50, 235/55				
7 x 19	RC27	40	-	103, 116	225/50, 235/50			
7,5 x 19	RC32	45	-	103, 116	235/50		Orig.-Verschr., i.V.	
	RC34	45	-	103-116	225/50, 235/50, 245/45		Orig.-Verschr., Ausführung N43	
	RC34	35	-	103-116	225/50, 245/45		Orig.-Verschr.	
		40	-	103-116	225/50, 235/50, 245/45		Orig.-Verschr.	
	B32	40	ZP581	103, 116	225/50, 235/50, 245/45			
	AC-521	35	ZP590F+R	103, 116	225/50		+ Red.Ringe 73,1-66,1	
		45	ZP590F+R	103, 116	225/50, 235/50, 245/45		+ Red.Ringe 73,1-66,1	
	CA 26	45	ZP581	103, 116	225/50, 235/50, 245/45		incl. Facelift 2024, ohne e-Power	
116				235/50, 245/45		incl. Facelift 2024, e-Power		
8 x 19	CA 17 CA 24 FMI08 Thoe Oxigin 29	40	ZP581	103-116	235/45			
		45	ZP581	103-116	235/45, 235/50, 245/45, 255/45			
		40	-	103-116	225/50, 245/45, 255/45		Orig.-Verschr.	
		40	ZP581	103, 116	225/50, 235/50, 245/45		ohne e-Power	
	8,5 x 19	B44	40	ZP581	116	235/50, 245/45		e-Power
103, 116					235/50, 245/45		ohne e-Power	
116					235/50, 245/45		e-Power	
CA 22	40	ZP581	103, 116	235/50, 245/45		ohne e-Power		

	RC 20	40	-	116	235/50, 245/45		e-Power
8 x 20	RC36	40	-	103, 116	235/45		Orig.-Verschr., incl. FL2024, Ausführung N43
	B43	40	-	103, 116	235/45		Orig.-Verschr., incl. FL2024, Ausführung N43
	FMI08 Thoe	40	-	103-116	235/45		Orig.-Verschr.
	RC36	35	-	103, 116	235/45		Orig.-Verschr., incl. FL2024, ohne e-Power
				116	235/45		Orig.-Verschr., incl. FL2024, e-Power
	B38	45	ZP581	103, 116	235/45, 245/40		ohne e-Power
	B40	35	ZP581	103, 116	235/45, 245/40		e-Power
	B43	45	-	103, 116	235/45		
8,5 x 20	RC36	37	-	103, 116	235/45		Orig.-Verschr., incl. FL2024, ohne e-Power
				116	235/45		Orig.-Verschr., incl. FL2024, e-Power
	B42	45	ZP581	103, 116	235/45		
	B44	40	ZP581	103, 116	235/45		
9 x 20	B37	43	ZP581	103, 116	235/45		
	CA 20 / CA 23	45	ZP581	103, 116	235/45		
	Oxigin 28	40	ZP581	103, 116	235/45		

Townstar NEU				NFK	5/114,3	66,1	e2*2018/858*00024*... , e2*2018/858*00025*..		
Sensor - Brocksens 4									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
6 x 15	RC27	35	-	96	195/65, 195/70, 205/65, 215/60, 225/60			Orig.-Verschr., auch Kombi, nicht für Scheibenbremsen an der HA	
	RC30	35	-	96	195/65			Orig.-Verschr., auch Kombi, nicht für Scheibenbremsen an der HA	
	RC24	40	-	96	195/65, 195/70, 205/65, 215/60, 225/60			Orig.-Verschr., auch Kombi, nicht für Scheibenbremsen an der HA	
6 x 16	RC34	38	-	96	205/60			Orig.-Verschr.	
6,5 x 16	RC24	38	ZP581	96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55			nicht für Scheibenbremsen an der HA, auch Kombi	
	RC27	38	ZP581	96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55			nicht für Scheibenbremsen an der HA, auch Kombi	
	RC30	38	ZP581	96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55			nicht für Scheibenbremsen an der HA, auch Kombi	
	RC32	40	-	51-96	195/60, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			Orig.-Verschr.	
		41	-	51-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			Orig.-Verschr.	
	RC34	40	-	96	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			Orig.-Verschr.	
6,5 x 17	RC27	32	-	96	205/50, 205/55			Orig.-Verschr., auch Kombi	
7 x 17	RC32	43	-	96	195/55, 205/50, 205/55, 215/45, 215/50, 225/45, 225/50			Orig.-Verschr.	
	RC34	43	-	96	195/55, 205/50, 205/55, 215/45, 215/50, 225/45, 225/50			Orig.-Verschr.	
	RC27	38	ZP581	96	205/50, 205/55, 215/50, 225/45			auch Kombi	
	B39	38	ZP581	96	205/50, 205/55, 215/50, 225/45			auch Kombi	
	Pro1	45	F28	51-96	205/50, 205/55, 215/45, 215/50, 225/45				
7,5 x 17	RC24 / RC29		38	ZP581	96	205/50, 205/55, 215/50, 225/45, 235/45			nicht für Scheibenbremsen an der HA, auch Kombi
	RC28		35	ZP581	96	205/50, 205/55, 225/45			nicht für Scheibenbremsen an der HA, auch Kombi
	B24		38	ZP581	96	205/50, 205/55, 215/50, 225/45, 235/45			auch Kombi
	B36		38	ZP581	96	205/50, 205/55, 215/50, 225/45, 235/45			nicht für Scheibenbremsen an der HA
7 x 18	RC27	34+35+40	-	96	205/45, 215/45, 225/45			Orig.-Verschr., nicht für Scheibenbremsen an der HA, auch Kombi	
7,5 x 18	RC32	45	-	96	215/45, 225/40			Orig.-Verschr.	
	RC34	40	-	96	215/45, 225/40, 225/45			Orig.-Verschr.	
	B32	35	ZP581	96	205/45, 215/45, 225/40, 225/45			auch Kombi	
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	96	205/45, 215/45, 225/40, 225/45			Kit mit Artikelnummer 98478, auch Kombi	
	AC-521	35	Artikel Nr. 98478	96	205/45, 215/45, 225/40, 225/45			Kit mit Artikelnummer 98478, nicht für Scheibenbremsen an der HA, auch Kombi	
	CA 20	40	ZP581	51-96	215/45, 225/40, 225/45				
	Oxigin 25	45	ZP581	51-96	215/45				
8 x 18	B24	38	ZP581	96	215/45, 225/40, 225/45			auch Kombi	
	B36	35	ZP581	96	215/45			auch Kombi	
	B42 / B44	40	ZP581	96	215/45			auch Kombi	
	RC34	35+40	-	96	225/40			Orig.-Verschr.	

7,5 x 19	AC-521	35	Artikel Nr. 98478	96	225/40		Kit mit Artikelnummer 98478 , nicht für Scheibenbremsen an der HA, auch Kombi
8 x 19	CA 17	40	ZP581	96	225/40		

Townstar EV NEU	im Laufe 2023	NFK	5/114,3	66,1	e2*2018/858*00024*.., e2*2018/858*00025*..		
---------------------------------------	----------------------	------------	----------------	-------------	--	--	--

Sensor - Brocksens 4

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC32	40	-	51-96	195/60, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
		41	-	51-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
6,5 x 17	RC27	32	-	51	205/50, 205/55		Orig.-Verschr., Elektro, kurze Karosserie
7 x 17	RC27	35	-	51	205/55, 215/50		Orig.-Verschr., Elektro
		40	-	51	205/55, 215/50		Orig.-Verschr., Elektro
		38	ZP581	51	205/50, 205/55, 215/50, 225/45		Elektro, kurze Karosserie
					205/55, 215/50		Elektro, Kombi
	B39	38	ZP581	51	205/50, 205/55, 215/50, 225/45		Elektro, kurze Karosserie
					205/55, 215/50		Elektro, Kombi
	Pro1	45	F28	51-96	205/50, 205/55, 215/45, 215/50, 225/45		
7,5 x 17	B24	38	ZP581	51	205/50, 205/55, 215/50, 225/45, 235/45		Elektro, kurze Karosserie
					205/55, 215/50, 235/45		Elektro, Kombi
7 x 18	RC27	34	-	51	215/45, 225/45		Orig.-Verschr., Elektro, kurze Karosserie
					225/45		Orig.-Verschr., Elektro, Kombi
7,5 x 18	RC30	35	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
					225/45		Elektro, Kombi
	B32	35	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
					225/45		Elektro, Kombi
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	51	215/45, 225/45		Kit mit Artikelnummer 98478
	CA 20	40	ZP581	51-96	215/45, 225/40, 225/45		
8 x 18	Oxigin 25	45	ZP581	51-96	215/45		
	B24	38	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
					225/45		Elektro, Kombi
	B36 / B38	35	ZP581	51	215/45		Elektro, kurze Karosserie
8 x 19	B42 / B44	40	ZP581	51	215/45		Elektro, kurze Karosserie
	CA 17	40	ZP581	51-96	225/40		

X-Trail	2014	T32	5/114,3	66,1	e13*2007/46*1456*...		
----------------	-------------	------------	----------------	-------------	----------------------	--	--

Sensor - Brocksens 4

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC30	45	-	96-130	225/65 , 235/60, 235/65		Orig.-Verschr.
	RC27	35	-	96-130	225/65, 235/60, 235/65		Orig.-Verschr.
		40	-	96-130	225/65, 235/60, 235/65, 255/55, 255/60		Orig.-Verschr.
	RC32	40	-	96-130	225/65, 235/60, 235/65, 245/60		Orig.-Verschr.
		43	-	96-130	225/65, 235/60, 235/65		Orig.-Verschr.
		35	ZP578D2F	96-130	225/65, 235/60, 235/65		
	RC34	43	-	96-130	225/65, 235/60, 235/65		Orig.-Verschr.
	B39	38	ZP578	96-130	225/65, 235/60, 235/65, 255/55, 255/60		
		45	ZP578	96-130	225/65, 235/60, 235/65		
	AC-V51	45	ZP578D2F	96-130	225/65, 235/60, 235/65		
7 x 18	Pro1	45	ZP578D2F	96-130	225/65		
	RC32	45	-	96-130	225/55, 225/60		Orig.-Verschr.
	RC27	34	-	96-130	225/60, 235/55, 235/60		Orig.-Verschr.
		40	-	96-120	225/60, 235/55		Orig.-Verschr.
	RC32	35	-	96-130	225/55, 225/60, 235/55		Orig.-Verschr.
		40	-	96-130	225/55, 225/60, 235/55, 245/50, 245/55		Orig.-Verschr.
	B42	40	ZP578	96-130	225/60, 235/55, 235/60		
8 x 18	B44	40+45	ZP578	96-130	225/60, 235/55, 235/60		
	AC-M10	45	ZP578D2F +R	96-130	225/60, 235/55, 235/60		+ Red.Ringe 73,1-66,1
7 x 19	RC27	40	-	96-130	225/55 , 235/50, 245/50, 255/50		Orig.-Verschr.
	RC34	40	-	96-130	225/55		Orig.-Verschr.
7,5 x 19	RC34	35+45	-	96-130	225/55, 245/45		Orig.-Verschr.
	B32	40	ZP578	96-130	225/55, 235/50, 245/50		
	B39	40+45	ZP578	96-130	225/55, 235/50, 245/50		ET45 nicht 245/50
	AC-521	35+45	ZP578D2F +R	96-130	225/55, 235/50		+ Red.Ringe 73,1-66,1
	Oxigin 18	40	ZP578	96	225/55		
8 x 19	CA 19	45	ZP578	96-130	225/55, 235/50, 255/45		
	FMI08 Thoe	40	-	96-130	225/55, 245/45		Orig.-Verschr.
	Oxigin 29	40	ZP578	96-130	225/55, 235/50, 245/50, 255/45		

8,5 x 19	B44	40	ZP578	96-130	225/55, 235/50, 255/45		
8 x 20	B38	35	ZP578	96, 120	235/45, 245/40, 245/45		
	B40	35	ZP578	96-130	235/45, 245/40, 245/45		

weitere Dimensionen/Designs siehe Konfigurator

X-Trail		ab 2022		T33	5/114,3	66,1	e13*2018/858*00293*...
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC34	40	-	116-120	235/60, 245/55		Orig.-Verschr., auch Hybrid
	B32	35	ZP578	116, 120	235/60, 245/55		2WD
				116	235/60, 245/55, 255/55		Allrad
	AC-MB6 / AC-M10	35	Artikel Nr. 98495	116, 120	235/60, 245/55		Kit mit Artikelnummer 98495, 2WD
		45	Artikel Nr. 98495	116	235/60, 245/55, 255/55		Kit mit Artikelnummer 98495, 4WD
	CA 20	40	ZP578	116-120	235/60, 245/55		
	AC-V51	38	ZP578D2F	116, 120	235/60, 245/55, 255/55		
8 x 18	B24	38	ZP578	116, 120	235/60, 245/55		auch Allrad
	B36	35	ZP578	116, 120	235/60, 245/55		auch Allrad
	B42	40	ZP578	116, 120	235/60, 245/55		auch Allrad
		45	ZP578	116, 120	235/60		auch Allrad
	B44	40	ZP578	116, 120	235/60, 245/55		auch Allrad
		45	ZP578	116, 120	235/60		auch Allrad
	AC-M10	45	ZP578D2F +R	116, 120	235/60		+ Red.Ringe 73,1-66,1, auch Allrad
	CA 20	45	ZP578	116, 120	235/60		2WD
7,5 x 19	RC34	40	-	116-120	235/50, 235/55, 245/50		Orig.-Verschr., auch Hybrid
		35	-	116-120	235/50, 235/55		Orig.-Verschr., auch Hybrid
		45	-	116-120	235/50, 235/55, 245/50, 255/50		Orig.-Verschr., auch Hybrid
	CA 26	45	ZP578	116, 120	235/55		
	FMI10 e-Joule	40	-	116-120	235/55		Orig.-Verschr.
8 x 19	RC29	38	ZP578	116, 120	235/55, 245/50		2WD
	B40	35	ZP578	116	235/55, 245/50		4WD
				116, 120	235/55, 245/50		2WD
	CA 17	40	ZP578	116-120	235/55		auch Allrad
	CA 19	45	ZP578	116, 120	235/55		
	FMI08 Thoe	40	-	116-120	235/50, 235/55		Orig.-Verschr., auch Hybrid
	Oxigin 29	40	ZP578	116, 120	235/55, 245/50		
8,5 x 19	B36	38	ZP578	116, 120	235/55, 245/50, 265/45		2WD
	B32 / B37	35	ZP578	116	235/55, 245/50, 265/45		4WD
		40	ZP578	116, 120	235/55		
	B44	40	ZP578	116	235/55		2WD
				116	235/55		4WD
CA 23	40	ZP578	116, 120	235/55		2WD	
8 x 20	B43	45	-	116, 120	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., 2WD
				116	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., 4WD
	RC36	40	-	116, 120	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., 2WD, Ausführung N43
				116	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., 4WD, Ausführung N43
	B38	35	ZP578	116, 120	235/45, 235/50, 245/45, 255/45		2WD
				116	235/45, 235/50, 245/45, 255/45		4WD
		45	ZP578	116, 120	235/45, 235/50, 245/45, 255/45		2WD
				116	235/45, 235/50, 245/45, 255/45		4WD
	B40	35	ZP578	116, 120	235/45, 235/50, 245/45, 255/45		2WD
				116	235/45, 235/50, 245/45, 255/45		4WD
	B43	40	-	116, 120	235/45, 235/50, 245/45, 255/45		2WD, Ausführung N42 u. N43
				116	235/45, 235/50, 245/45, 255/45		4WD
8,5 x 20	RC36	37	-	116, 120	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., 2WD
	B42	35	ZP578	116	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., 4WD
				116	235/45, 235/50, 245/45, 255/45, 265/45		2WD
		45	ZP578	116, 120	235/45, 245/45		2WD
				116	235/45, 245/45		4WD
	B44	30	ZP578	116, 120	235/45, 245/45		2WD
				116	235/45, 245/45		4WD
		40	ZP578	116, 120	235/45, 235/50, 245/45, 255/45		2WD
116	235/45, 235/50, 245/45, 255/45				4WD		
9 x 20	Oxigin 28	40	ZP578	116, 120	235/45, 245/45, 255/45		2WD
				116	235/45, 245/45, 255/45		4WD

Opel

		Baujahr		Typ	LK/LZ	Nabe	
Adam (siehe Konfigurator)		ab 2013		S-D	4/100	56,6	
Adam Rocks (siehe Konfigurator)		ab 2014		S-D	4/100	56,6	

Adam S (siehe Konfigurator)		ab 2015		S-D	5/110	65,1	
-----------------------------	--	---------	--	-----	-------	------	--

Adam Rocks S (siehe Konfigurator)		ab 2015		S-D	5/110	65,1	
-----------------------------------	--	---------	--	-----	-------	------	--

Ampera (siehe Konfigurator)		ab 2011		D1JOI	5/115	70,1	
-----------------------------	--	---------	--	-------	-------	------	--

Ampera-e		ab 2017		1G0F	5/105	56,6	
----------	--	---------	--	------	-------	------	--

Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	41	-	55 (150)	205/55, 205/60		Orig.-Verschr.
	RC32	41	-	55 (150)	205/55, 205/60		Orig.-Verschr.
	RC24	39	-	55 (150)	205/55, 205/60		Orig.-Verschr.
	RC27	38+39	-	55 (150)	205/55, 205/60		Orig.-Verschr.
	RC30	38	-	55 (150)	205/55, 205/60		Orig.-Verschr.
7 x 17	RC27	42	-	55 (150)	205/50, 215/50, 225/45		Orig.-Verschr., bei 215/50 ✖
	RC32	38	-	55 (150)	205/45, 215/45		Orig.-Verschr.
7 x 18	RC32	38	-	55 (150)	215/40, 215/45		Orig.-Verschr.
7,5 x 18	RC32	44	-	55 (150)	215/40, 215/45, 225/40		Orig.-Verschr.

Astra J (normalerw. Benzin) (siehe Konfigurator)		ab 12.09		P-J	5/105	56,6	
--	--	----------	--	-----	-------	------	--

Astra J (normalerw. Diesel) (siehe Konfigurator)		ab 12.09		P-J	5/115	70,3	
--	--	----------	--	-----	-------	------	--

Astra K		08.2015		B-K	5/105	56,6	
---------	--	---------	--	-----	-------	------	--

Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC30	37	-	66-110	195/65, 205/60, 215/60		Orig.-Verschr., incl. Facelift 2019
	RC24	39	-	66-110	195/65, 205/60, 215/60		Orig.-Verschr., incl. Facelift 2019
	RC30	41	-	66-147	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
6,5 x 16	RC30	41	-	66-110	195/55, 195/60		Orig.-Verschr.
				66-110	195/55, 195/60		Orig.-Verschr.
	RC32	41	-	66-147	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC24	39	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
	RC27	38+39	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
	RC30	38	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
7 x 16	RC30	41	-	70-147	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
				66-147	205/55		Orig.-Verschr., incl. Facelift 2019
				66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
7 x 17	RC30	41	-	66-147	205/55, 215/50, 215/55, 225/50HA		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50HA		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50HA		Orig.-Verschr., incl. Facelift 2019
7 x 18	RC27	42	-	66-147	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2019
	RC32	38	-	70-147	205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	RC27	44	-	66-147	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2019
	RC27	38	-	70-147	205/40, 205/45, 215/40		Orig.-Verschr., bei 215/40 ✖
7,5 x 18	RC32	44	-	66-147	205/40, 205/45, 215/40		Orig.-Verschr.
				66-147	205/40, 205/45, 215/40		Orig.-Verschr.
8 x 18	RC32	44	-	81-147	225/40		Orig.-Verschr.
				70-147	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
				70-147	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
7,5 x 19	B39	38	-	70-147	205/40, 215/40, 225/40		Orig.-Verschr.
				70-147	205/40, 215/40, 225/40		Orig.-Verschr.
				70-147	205/40, 215/40, 225/40		Orig.-Verschr.
8 x 19	B37	33	-	66-147	205/40, 215/40, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr., ab 215/40 ✖
				66-147	205/40, 215/40, 225/40		Orig.-Verschr.
7,5 x 19	RC32	38	-	66-147	215/35, 225/35		Orig.-Verschr.
				66-147	215/35, 225/35		Orig.-Verschr.
8 x 19	B24	42	-	66-147	215/35, 225/35		Orig.-Verschr.
				66-147	215/35, 225/35		Orig.-Verschr., incl. Facelift 2019

Astra K Sports Tourer		ab 04.16		B-K	5/105	56,6	
-----------------------	--	----------	--	-----	-------	------	--

Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC30	37	-	66-110	195/65, 205/60, 215/60		Orig.-Verschr., incl. Facelift 2019
	RC24	39	-	66-110	195/65, 205/60, 215/60		Orig.-Verschr., incl. Facelift 2019
	RC30	41	-	66-147	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
				66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019

6,5 x 16	RC32	41	-	92-100	205/55		Orig.-Verschr.
			-	66-147	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC24	39	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55, 225/50		
	RC30	38	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019, bei 225/50 ✖
				66-147	205/55, 215/50, 215/55, 225/50		
7 x 16	RC27	38+39	-	66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019
				66-147	205/55, 215/50, 215/55		
	RC30	41	-	66-147	205/55		Orig.-Verschr., incl. Facelift 2019
				66-110	195/55, 195/60		Orig.-Verschr., incl. Facelift 2019, bei 225/50 ✖
				66-147	205/55, 215/50, 215/55, 225/50HA		
7 x 17	RC27	42	-	66-147	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2019
	RC32	38	-	70-147	205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	RC27	44	-	66-147	205/50, 215/45, 225/45		Orig.-Verschr., incl. FL2019
7 x 18	RC32	38	-	66-147	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC32	44	-	81-147	225/40		Orig.-Verschr.
				70-147	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
	B39	38	-	70-147	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
8 x 18	B24	38	-	70-147	205/40, 215/40, 225/40		Orig.-Verschr.
	B38	38	-	66-147	205/40, 215/40		Orig.-Verschr.
7,5 x 19	RC32	38	-	66-147	215/35, 225/35		Orig.-Verschr.
	B39	38	-	70-147	215/35, 225/35		Orig.-Verschr.
8 x 19	B24	42	-	66-147	215/35, 225/35		Orig.-Verschr., incl. Facelift 2019

Astra L NEU							
1. Quartal 2022				F	5/108	65,1	e2*2007/46*0628*16-..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC30	44	ZP538F	81-100	205/55, 215/55, 225/50		
7 x 17	RC27	42	- od ZP537F	81-100	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	81-96	205/50, 215/45, 225/45		
	RC32	42	ZP538F	81-100	205/45, 205/50, 215/45, 225/45		
	RC34	42+44	- od ZP537F	81-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26 Pro1	42 45	ZP538F -	81-100 81-100	205/50, 215/45, 225/45 205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	RC34	44	- od ZP537F	81-96	205/45, 205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC27	37	ZP538F	81-100	205/50, 215/45		
				81-132	225/45		
	RC29	45	ZP538	81-96	205/50, 215/45		
				81-132	225/45		
	RC32	40	ZP538F	81-96	205/45, 215/45		
	RC34	40	ZP538F	81-100	205/45, 215/45		
7 x 18	B36	45	ZP538	81-96	205/50, 215/45		nicht Bremse 304 u. 330mm
				81-132	225/45		
7,5 x 18	RC27	44	- od ZP537F	81-100	205/45, 215/40		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC32	49	ZP538F	81-96	215/40, 225/40		nicht Bremse 304x28mm
	RC34	49	-	81-110	215/40, 225/40		Orig.-Verschr.
	B32	45	ZP538	81-100	205/45, 215/40		
				81-132	225/40		
	AC-MB6 / AC-M10	42	ZP538F+R	81-100	205/45, 215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
	AC-521	42	ZP538F+R	81-96	205/45, 215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
8 x 18	CA 20	45	ZP538F	81-110	205/45, 215/40, 225/40		
	RC32	44	ZP538F	81-96	205/45, 215/40		
	RC34	44	ZP538F	81-100	205/45, 215/40		
	B37	45	ZP538	81-100	215/40		
				81-132	225/40		
	B42	42	ZP538	81-96	215/40		
				81-132	225/40		
	B44	42	ZP538	81-100	215/40		
				81-132	225/40		
	AC-M10	42	ZP538F+R	81-96	215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
8 x 19	AC-521	43	ZP538F+R	81-96	215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
	CA 20	45	ZP538	81-100	215/40		nicht Bremse 304 u. 330mm
				81-132	225/40		

8,5 x 18	B32	45	ZP538	81-96	215/40		
				81-132	225/40		
7,5 x 19	B32	42	ZP538F	81-96	215/35		nicht Bremse 304mm
				81-132	225/35		
	AC-521	42	ZP538F+R	81-96	215/35		+ Red.Ringe 73,1-65,1
				81-132	225/35		
	CA 26	45	ZP538	81-100	215/35		
				81-132	225/35		
8 x 19	RC29	45	ZP538	81-96	215/35		
				81-132	225/35		
	Oxigin 29	45	ZP538	81-100	215/35		
				81-132	225/35		
8,5 x 19	B32	45	ZP538	81-96	215/35		
				81-132	225/35		

Astra L Sports Tourer

NEU

im Laufe 2022

F

5/108

65,1

e2*2007/46*0628*16-..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC28	44	ZP538F	81-96	205/55, 215/55, 225/50		nicht Bremse 304mm
	RC30	44	ZP538F	81-100	205/55		
7 x 17	RC27	42	- od ZP537F	81-100	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	81-96	205/50, 215/45, 225/45		
	RC34	42+44	- od ZP537F	81-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26 Pro1	42	ZP538F -	81-100	205/50, 215/45, 225/45		
		45		81-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	RC27	37	ZP538F	81-100	205/50, 215/45		
				81-132	225/45		
	RC34	40	ZP538F	81-100	205/45, 215/45		
				81-96	205/50, 215/45		nicht Bremse 304 u. 330mm
	B36	45	ZP538	81-132	225/45		
7 x 18	RC27	44	- od ZP537F	81-100	205/45, 215/40		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC34	49	-	81-110	215/40, 225/40		Orig.-Verschr.
	B32	45	ZP538	81-100	205/45, 215/40		
				81-132	225/40		
	AC-MB6 / AC-M10	42	ZP538F+R	81-100	205/45, 215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
	AC-521	42	ZP538F+R	81-96	205/45, 215/40		+ Red.Ringe 73,1-65,1
				81-132	225/40		
	CA 20	45	ZP538F	81-110	205/45, 215/40, 225/40		
8 x 18	RC34	44	ZP538F	81-100	205/45, 215/40		
				81-100	215/40		
	B37	45	ZP538	81-132	225/40		
				81-96	215/40		
	B42	42	ZP538	81-132	225/40		
				81-100	215/40		
	B44	42	ZP538	81-132	225/40		
				81-96	215/40		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	81-132	225/40		
				81-96	215/40		+ Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	81-132	225/40		
				81-100	215/40		nicht Bremse 304 u. 330mm
7,5 x 19	CA 20	45	ZP538	81-132	225/40		
				81-96	215/35, 225/35		+ Red.Ringe 73,1-65,1
8 x 19	RC29	45	ZP538	81-100	215/35, 225/35		
				81-132	225/35		
8,5 x 19	B32	45	ZP538	81-96	215/35, 225/35		

Astra L Electric

NEU

2024

F

5/108

65,1

e2*2007/46*0628*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 18	RC27	44	- od ZP537F	62 (115)	215/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! incl. Sportstourer
7,5 x 18	B32	45	ZP538	62 (115)	215/45		incl. Sports Tourer
	AC-MB6	42	ZP538F+R	62 (115)	215/45, 225/40		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	62 (115)	215/45, 225/40		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	62	215/45, 225/40		
8 x 18	B42	42	ZP538	62 (115)	215/45		
	B44	42	ZP538	62 (115)	215/45		

	AC-M10	42	ZP538F+R	62 (115)	215/45		+ Red.Ringe 73,1-65,1
8 x 19	RC34	42	ZP538F	62	215/40		

Combo E							
kein Sensor - indirektes RDKS				5/108	65,1	e2*2007/46*0623*..	
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	47	ZP538F	55-96	205/55, 205/60 , 215/55		nicht bei 15" Serie, nicht Bremse 283mm
	RC32	47	ZP538F	55-96	205/60 , 215/50, 215/55, 215/60, 225/50, 225/55		
	RC34	47	- od. ZP537F	55-96	205/60 , 215/50, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 20	45	ZP538	55-96	205/55, 205/60, 215/55, 225/50, 225/55		
7 x 17	RC30	50	ZP538F	55-96	205/50, 205/55 , 225/45		nicht bei 16" Serie
	RC34	50	- od. ZP537F	55-96	205/55 , 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	50	ZP538F	55-96	205/55		
	RC27	42	- od ZP537F	55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
				55-81	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! bei 15" Serie
	RC32	42	ZP538F	55-96	205/55, 215/45		
	CA 26	42	ZP538F	55-81	205/50, 215/45, 225/45		15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		nicht bei 15" Serie
7,5 x 17	RC24	50	ZP538F	55-96	205/50, 205/55, 225/45		
		44	ZP538F	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC29	47	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
		45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC34	44	ZP537F	55-96	205/55, 215/45, 225/45		Achtung! Kit ist nicht kostenlos - € 28,00 netto!
	B24	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	B36	45	ZP538	55-96	205/50, 205/55, 225/45		
	AC-518	45	ZP538F+R	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
7 x 18	RC27	44+48	- od ZP537F	55-96	205/45, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45		nicht bei 15" Serie
	RC32	49	ZP538F	55-96	215/40, 215/45, 225/40		
	RC34	49	ZP537F	55-96	215/40, 215/45, 225/40		Achtung! Kit ist nicht kostenlos - € 28,00 netto!
	B32 / B39	45	ZP538	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	AC-521	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
7,5 x 19	B32	42	ZP538F	55-81	205/45, 215/40, 225/40		bei 15" Serie
					225/35		nicht bei 16" Serie
	AC-521	42	ZP538F+R	55-81	225/35		15 Zoll Serie, + Red.Ringe 73,1-65,1

weitere Dimensionen/Designs siehe Konfigurator

Combo E Life							
kein Sensor - indirektes RDKS				ab 2018	E	5/108	65,1
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	47	ZP538F	56-96	205/55, 205/60 , 215/55		nicht bei 15" Serie, nicht Bremse 283mm
	RC32	47	ZP538F	56-96	205/60 , 215/50, 215/55, 215/60, 225/50, 225/55		
	RC34	47	- od. ZP537F	56-96	205/60 , 215/50, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
	CA 20	45	ZP538	55-96	205/55, 205/60, 215/55, 225/50, 225/55		
	Pro1	42	-	56-96	205/60, 215/50, 215/55, 215/60		Orig.-Verschr., Serienreifen bis 205/..
7 x 17	RC30	50	ZP538F	55-96	205/50, 205/55 , 225/45		nicht bei 16" Serie
	RC34	50	- od. ZP537F	56-96	205/55 , 215/45, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
	CA 26	50	ZP538F	55-96	205/55		
	RC27	42	- od. ZP537F	55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
	RC30	42	ZP538F	55-96	205/50, 205/55, 215/50, 225/45		nicht bei 15" Serie
	RC32	42	ZP538F	56-96	205/55, 215/45		
	CA 26	42	ZP538F	55-96	205/50, 205/55, 215/50, 225/45		
		50	ZP538F	55-96	205/50, 205/55, 225/45		
	Pro1	45	-	56-96	205/55, 215/45, 215/50, 225/45		Orig.-Verschr., Serienreifen bis 205/..
7,5 x 17	RC24	44	ZP538F	56-96	205/50, 205/55, 225/45		nicht bei 15" Serie
		47	ZP538	56-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC29	45	ZP538	56-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC34	44	- od. ZP537F	56-96	205/55, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
	B24	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	B36	45	ZP538	55-96	205/50, 205/55, 225/45		
	AC-518	45	ZP538F+R	56-96	205/50, 205/55, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1

7 x 18	RC27	44+48	- od ZP537F	55-96	205/45, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45		nicht bei 15" Serie
	RC32	49	ZP538F	56-96	215/40, 215/45, 225/40		
	RC34	49	-	56-96	215/40, 215/45, 225/40		Orig.-Verschr.
	B32	45	ZP538	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	B39	45	ZP538	56-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	AC-MB6	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-65,1
8 x 18	AC-521	42	ZP538F+R	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
	RC29	45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie
	RC32	44	ZP538F	56-96	215/40, 215/45		
	RC34	44	ZP538F	56-96	215/40, 215/45		
	B36	45	ZP538	56-96	215/45, 225/40, 225/45		nicht bei 15" Serie, nicht Bremse 283 u. 304mm
	B37 / B38	45	ZP538	56-96	215/45, 225/40, 225/45		nicht bei 15" Serie da andere Bremse kommt
	B42 / B44	42	ZP538	55-96	215/45		
	AC-M10	42	ZP538F+R	55-96	215/45		+ Red.Ringe 73,1-65,1, nicht Bremse 283mm
	AC-518	45	ZP538F+R	56-96	215/45, 225/40, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	55-96	215/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1

Corsa E (siehe Konfigurator)	ab 2015	S-D, S-D/Van	4/100	56,6	e1*2001/116*0379*30-..., e1*2007/46*0505*08-...
------------------------------	---------	--------------	-------	------	---

Corsa E (siehe Konfigurator)	ab 2015	S-D	5/110	65,1	e1*2001/116*0379*32-...
------------------------------	---------	-----	-------	------	-------------------------

Corsa F	ab 09.2019	U	4/108	65,1	e2*2007/46*0639*05-...
---------	------------	---	-------	------	------------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC30	32	ZP402F	55-96	185/60, 185/65 , 195/60		
6,5 x 16	RC30	38	ZP402F	55-96	195/55		incl. Facelift 2023
				55-96	185/55		
				55-100	195/55		
	RC34	38	- od. ZP401F	55-96	185/55, 195/55 , 205/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
	RC30	32	ZP402F	55-96	185/55		
	RC34	32	- od. ZP401F	55-96	185/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
7 x 17	RC34	38	- od. ZP401F	55-100	195/45, 205/45 , 215/40		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
	B39	38	ZP402F	55-96	195/45, 205/45		
	RC34	32	- od. ZP401F	55-96	195/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
7,5 x 18	B39	32					i.V.

Corsa-e (F) NEU	ab 02.2020	U	4/108	65,1	e2*2007/46*0639*06-...
-----------------	------------	---	-------	------	------------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	32	ZP402F	57, 62	195/55, 205/50		incl. Facelift 2023
	RC34	32	- od. ZP401F	57-62	195/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
7 x 16	RC28	32	ZP402F	57 (100)	195/55		
7 x 17	RC34	32	- od. ZP401F	57-62	205/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
				57-62	195/45, 205/45		
	B24	25	ZP402F	57 (100)	195/45		
7,5 x 18	B39	25			205/45		i.V.
	B39	32	ZP402F	57 (100)	205/40		

Corsa NEU i.V.	1. Quartal 2024
----------------	-----------------

Crossland X	ab 06.2017	P7 Monocab C	4/108	65,1	e4*2007/46*1194*..
-------------	------------	--------------	-------	------	--------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	20	ZP402F	55-96	195/60, 205/55, 205/60, 215/55		incl. Facelift 2021
	RC24	20	ZP402F	55-96	195/60, 205/55, 205/60, 215/55		incl. Facelift 2021
	RC34	20	- od. ZP401F	60-96	195/60, 205/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
7 x 16	RC28	18	ZP402F	60-96	195/60, 205/55, 205/60, 215/55		
7 x 17	RC34	20	- od. ZP401F	60-96	195/50, 195/55, 205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
		25	- od. ZP401F	60-96	195/50, 195/55, 215/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit 32,00 netto
	B39	18	ZP402F	60-96	195/55, 205/50, 215/50, 225/45		
7,5 x 18	B39	20	ZP402F	55-96	205/45, 215/45, 225/40		incl. Facelift 2021

7,5 x 19	B39	18	ZP402F	60-96	215/35, 225/35		
----------	-----	----	--------	-------	----------------	--	--

Frontera NEU i.V.		2025		C	4/108	65,1	e2*2018/858*00035*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	28	-		215/65		Orig.-Verschr., i.V., Lieferzeit August

Frontera electric NEU i.V.		2025		C	4/108	65,1	e2*2018/858*00035*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	28	-		215/65		Orig.-Verschr., i.V., Lieferzeit August

Grandland X	ab 2017	Z	5/108	65,1	e2*2007/46*0597*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC30	44	ZP538F	75-133	205/70, 215/70, 225/65		incl. Facelift 2021
7 x 17	RC27	42	- od. ZP537F	75-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60, 245/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto, incl. Facelift 2021
	RC30	42	ZP538F	75-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60, 245/55		incl. Facelift 2021
	RC32	42	ZP538F	75-133	205/65, 215/65, 225/60, 225/65, 235/60		
	RC34	42	- od. ZP537F	75-133	215/65, 225/60, 225/65, 235/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
	CA 26	42	ZP538F	75-133	215/65		incl. Facelift 2021
	RC30	50	ZP538F	75-133	205/65, 215/60, 215/65, 225/60		
	RC34	44	- od. ZP537F	75-133	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto
7,5 x 17	CA 26 Pro1	50	ZP538F	75-133	205/65, 215/60, 215/65, 225/60		incl. Facelift 2021, nicht Bremse 330mm
	RC27	45	-	75-133	205/65, 215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
	RC29	37	ZP538F	75-133	205/65		incl. Facelift 2021
	RC29	45	ZP538	75-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2021, ohne Verbr. ab 235/55 ✖
	RC32	40	ZP538F	75-133	215/65, 225/60, 225/65		
	RC34	40	ZP538F	75-133	215/65, 225/60, 225/65		
	RC34	44	-	75-133	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
7 x 18	B24	45	ZP538	75-133	205/65, 215/60, 215/65, 225/60		incl. Facelift 2021, nicht Bremse 304 u. 330mm
	B36	45	ZP538	75-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2021, nicht Bremse 304 u. 330mm, ohne Verbr. ab 235/55 ✖
	RC27	44+48	- od. ZP537F	75-133	215/55, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! incl. Facelift 2021
	RC30	49	ZP538F	75-133	215/55, 225/55		incl. FL2021, nicht Bremse 304 u. 330mm
	RC32	49	ZP538F	75-133	215/60, 225/55		
	RC34	49	-	75-133	215/55, 215/60, 225/55		Orig.-Verschr.
	B32	45	ZP538	75-133	215/55, 225/55, 235/50, 235/55		incl. Facelift 2021
7,5 x 18	B39	45	ZP538	75-133	215/55, 225/55, 235/50, 235/55		incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
	AC-521	42	ZP538F+R	75-133	215/55, 225/55, 235/50, 235/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
	CA 20	45	ZP538F	75-133	215/55, 215/60, 225/55, 235/50, 235/55		
	RC29	45	ZP538	75-133	225/55		
	RC32	44	ZP538F	75-133	225/55		
	RC34	44	ZP538F	75-133	215/55, 225/55		
	B37 / B38	45	ZP538	75-133	225/55		B37 incl. Facelift 2021
8 x 18	AC-518	45	ZP538F+R	75-133	225/55		+ Red.Ringe 73,1-65,1
	RC27	38	ZP538F	75-133	205/55, 225/50, 235/50		incl. Facelift 2021
	RC34	38	ZP537F	96-133	205/55		ACHTUNG!!! Kit ist nicht kostenlos - Preis ist € 28,00 netto!!!
	RC27	41	- od. ZP537F	75-133	205/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. Facelift 2021
	RC32	42	ZP538F	75-133	235/50, 245/45		
	B32	46	ZP538F	96	225/50		auch ET46 mit Reifen 225/50 ist ECE
	AC-521	42	ZP538F	75-133	235/45, 235/50, 245/45		incl. Facelift 2021
7,5 x 19	CA 26	42	ZP538F+R	75-133	235/45, 235/50, 245/45		incl. Facelift 2021, + Red.Ringe 73,1-65,1
	RC29	45	ZP538	75-133	225/50, 235/45, 245/45		incl. Facelift 2021
	RC32	45	ZP538	75-133	235/45, 245/45		incl. Facelift 2021
	RC34	42	ZP538F	75-133	245/45		
	B38	42	ZP538F	75-133	235/45, 245/45		
	B38	45	ZP538	75-133	235/45, 245/45		incl. Facelift 2021, nicht Bremse 304 u. 330mm
	AC-518	45	ZP538F+R	75-133	235/45, 245/45		+ Red.Ringe 73,1-65,1
8 x 19	Oxigin 29	45	ZP538	75-133	225/50, 235/45, 245/45		incl. Facelift 2021
	B32	45	ZP538	75-133	235/45, 245/45		incl. Facelift 2021
	CA 23	45	ZP538	75-133	235/45		nicht Bremse 304 u. 330mm
	RC36	50	ZP537F	75-133	215/45, 235/40		ACHTUNG!!! Kit ist nicht kostenlos - Preis ist € 28,00 netto!!! incl. Facelift 2021

	B43	44	-	75-133	215/45, 235/40, 245/40		Orig.-Verschr. für Alufelgen, incl. Facelift 2021
8,5 x 20	B32	45	ZP538	75-133	235/40, 245/40		
	AC-518	45	ZP538F+R	75-133	235/40, 245/40		+ Red.Ringe 73,1-65,1 , ohne Verbreiter. bei 245/40 

Grandland X Hybrid							
ab 2019				Z	5/108	65,1	e2*2007/46*0597*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	110-147	205/65, 215/60, 215/65 , 225/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto , incl. Facelift 2021
	RC30	42	ZP538F	133, 147	205/65, 215/60, 215/65 , 225/60		incl. Facelift 2021
	RC34	42	- od. ZP537F	133-147	215/65		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto
	CA 26	42	ZP538F	110-147	205/65, 215/60, 215/65 , 225/60		incl. Facelift 2021
7,5 x 17	RC27	37	ZP538F	110-147	205/65		incl. Facelift 2021
	RC34	40	ZP538F	133-147	215/65, 225/60		
	RC29	45	ZP538	133, 147	205/65, 215/60, 215/65, 225/60		incl. Facelift 2021
7 x 18	RC27	44+48	- od. ZP537F	110-147	215/55, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto
7,5 x 18	RC32	49	ZP538F	133-147	225/55		
	RC34	49	ZP537F	110-147	225/55		ACHTUNG!!! Kit ist nicht kostenlos - Preis ist € 28,00 netto!!!
	B32	45	ZP538	110-147	215/55, 225/55		incl. Facelift 2021
	B39	45	ZP538	133, 147	215/55, 225/55		incl. Facelift 2021
	AC-MB6	42	ZP538F+R	110-147	215/55, 225/55		incl. Facelift 2021, + Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	133, 147	215/55, 225/55		incl. Facelift 2021, + Red.Ringe 73,1-65,1
8 x 18	CA 20	45	ZP538F	110-147	225/55, 235/55		
	RC29	45	ZP538	133, 147	225/55		
	RC32	44	ZP538F	133-147	225/55		
	RC34	44	ZP538F	110-147	225/55		
	B37	45	ZP538	110-147	225/55		incl. Facelift 2021
7 x 19	RC27	38	ZP538F	110-147	205/55		incl. Facelift 2021
	RC34	38	ZP537F	147	205/55 , 215/50, 225/50		ACHTUNG!!! Kit ist nicht kostenlos - Preis ist € 28,00 netto!!!
	RC27	41	- od. ZP537F	110-147	205/55, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. Facelift 2021
7,5 x 19	RC32	46	ZP538F	110-147	225/50		
		42	ZP538F	133-147	205/55, 215/50, 225/50, 235/45, 245/45		
	B32	42	ZP538F	133, 147	235/45		incl. Facelift 2021
	AC-521	42	ZP538F+R	133, 147	235/45		incl. Facelift 2021, + Red.Ringe 73,1-65,1
8 x 19	CA 26	45	ZP538	110-147	225/50, 235/45, 245/45		incl. Facelift 2021
	RC29	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021
	RC32	42	ZP538F	133-147	225/50, 235/45, 245/45		
	RC34	42	ZP538F	110-147	225/50, 235/45, 245/45		
	Oxigin 29	45	ZP538	110-147	225/50, 235/45, 245/45		incl. Facelift 2021
8,5 x 19	B32	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021, bei 245/45 
8 x 20	RC36	50	ZP537F	110-147	215/45, 235/40		ACHTUNG!!! Kit ist nicht kostenlos - Preis ist € 28,00 netto!!! incl. Facelift 2021
	B43	44	-	133, 147	215/45, 235/40		Orig.-Verschr., incl. Facelift 2021
8,5 x 20	B32	45	ZP538	133, 147	235/40		

Grandland Hybrid NEU							
ab 2024				K	5/108	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 18	FMI06 Koros	48	-		225/60		Orig.-Verschr., i.V.
8 x 20	RC36	50	- od. ZP537F	100	235/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto

Grandland electric NEU							
ab 2024				K	5/114,3	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	104, 105	235/50 , 245/45, 255/45		Orig.-Verschr.

Grandland Plug-in Hybrid NEU							
ab 2024				K	5/114,3	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	110	235/50 , 245/45, 255/45		Orig.-Verschr.

Insignia		ab 2017		Z-B		5/115		70,2		e8*2007/46*0264*..	
Sensor - Brocksens Universal od. Schrader 3025 - Artikelnummer 82294											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
Automatik nur ab 17 Zoll											
6,5 x 16	RC30	41	-	81-121	215/60, 215/65, 225/55, 225/60				Orig.-Verschr., nur Bremse 300mm		
	RC32	41	-	100-121	215/60				Orig.-Verschr.		
				81-121	215/60, 215/65, 225/55, 225/60, 235/55						
	RC24	41	-	81-121	215/60, 215/65, 225/55, 225/60				Orig.-Verschr., nur Bremse 300mm		
7 x 16	RC27	41	-	81-121	215/60, 215/65, 225/55, 225/60				Orig.-Verschr., nur Bremse 300mm		
	RC28	40	-	81-121	215/60, 215/65, 225/55, 225/60				Orig.-Verschr., nur Bremse 300mm		
7 x 17	RC27	44	-	81-121	215/55, 225/55				Orig.-Verschr., ohne GSI		
				81-121	215/55						
				81-147	225/50, 225/55, 235/50						
7,5 x 17	RC32	45	-	81-154	215/55, 225/55				Orig.-Verschr.		
	RC24	41	-	81-121	215/55				Orig.-Verschr.		
				81-154	225/50, 225/55						
	RC28	40	-	81-121	215/55				Orig.-Verschr.		
7,5 x 18	RC32	45	-	81-154	215/50, 215/55, 225/50, 225/55, 235/45, 235/50, 245/45				Orig.-Verschr.		
					215/45, 215/50, 225/45, 225/50, 235/45, 245/45				Orig.-Verschr.		
	B32	41	-	81-191	235/45, 245/45				Orig.-Verschr., nicht Brembo Bremse in Verb. mit 345mm		
				81-121	215/50						
				81-154	225/45, 225/50						
8 x 18	RC32	40	-	81-191	215/45, 225/45, 235/40, 235/45				Orig.-Verschr.		
8,5 x 18	Originaldim.	49			245/45						
8 x 19	B24	46	-	81-154	225/40, 225/45				Orig.-Verschr., nicht Bremse 321mm		
				81-191	235/40, 245/40						
8,5 x 20	RC29	49	-	81-191	245/35				Orig.-Verschr., ohne GSI, nicht Brembo Bremse in Verb. mit 345mm		
				81-125	225/35						
				81-191	235/35, 245/30, 245/35						
	B32	41	-	81-191	235/35, 245/30, 245/35				Orig.-Verschr., ab 245/30 ✖		

Insignia-B Country Tourer				ab 2017	Z-B	5/115	70,2	e8*2007/46*0264*..	
Sensor - Brocksens Universal od. Schrader 3025 - Artikelnummer 82294									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 18	RC32	40	-	100-191	235/45, 235/50, 245/45				Orig.-Verschr.
8,5 x 18	B32	38	-	100-191	235/45, 235/50, 245/45, 255/45				
8,5 x 19	B32	35	-	100-191	235/40, 235/45, 245/40				Orig.-Verschr.
8,5 x 20	B32	41	-	100-191	235/35, 235/40, 245/35				Orig.-Verschr.

Insignia-B GSI - 5/115		ab MJ2020		Z-B	5/115	70,2	e8*2007/46*0264*10-..	
Sensor - Brocksens Universal od. Schrader 3025 - Artikelnummer 82294								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8,5 x 20	B32	41	-	154, 169	235/35M+S			Orig.-Verschr.

Insignia-B GSI - 5/120	2020	Z-B	5/120	67,1	e8*2007/46*0264*05-...
Sensor - Brocksens Universal					

Achtung! Hat einen Lochkreis von 5/120!

Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC32	41	ZP597F	154-191	235/45			

Karl (siehe Konfigurator)		ab 2015		D-A	4/100	56,6	e4*2007/46*0957*...	
---------------------------	--	---------	--	-----	-------	------	---------------------	--

Karl Rocks (siehe Konfigurator)		ab 01.2017		D-A	4/100	56,6	e4*2007/46*0957*..	
---------------------------------	--	------------	--	-----	-------	------	--------------------	--

Mokka (siehe Konfigurator)		ab 10.12		J-A	5/105	56,6	e4*2007/46*0537*...	
----------------------------	--	----------	--	-----	-------	------	---------------------	--

Mokka-X		ab 2016		J-A	5/105	56,6	e4*2007/46*0537*15-..	
---------	--	---------	--	-----	-------	------	-----------------------	--

Sensor - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC27	38	-	81-112	205/65, 205/70, 215/65, 225/60, 225/65			Orig.-Verschr.
	RC30	38	-	81-112	205/65, 205/70, 215/65, 225/60, 225/65			Orig.-Verschr.
	RC32	38	-	81-112	195/70, 205/70, 215/65			Orig.-Verschr.
7 x 17	RC32	38	-	81-112	205/65, 215/55, 215/60, 225/55			Orig.-Verschr.
7 x 18	RC32	38	-	81-112	205/55, 215/50, 215/55, 225/50			Orig.-Verschr.
7,5 x 19	RC32	38	-	81-112	225/40, 225/45			Orig.-Verschr.
	B39	38	-	81-112	225/45, 235/45			Orig.-Verschr.

Mokka B NEU		ab März 2021		U	4/108	65,1	e2*2007/46*0639*12-..	
-------------	--	--------------	--	---	-------	------	-----------------------	--

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	32	ZP402F	74-100	215/65, 225/60, 235/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
	RC34	32	- od. ZP401F	74-100	215/65		
7 x 16	RC28	32	ZP402F	74,81,96	215/65, 225/60		
6,5 x 17	RC34	32	- od. ZP401F	74-100	215/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7,5 x 18	B39	32	ZP402F	74-100	215/50, 215/55, 235/45		

Mokka-e B NEU		ab März 2021		U	4/108	65,1	e2*2007/46*0639*12-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	32	ZP402F	57, 62	215/65			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
	RC34	32	- od. ZP401F	57-62	215/65			
7 x 16	RC28	32	ZP402F	57 (100)	215/65			
6,5 x 17	RC34	32	- od. ZP401F	57-62	215/60			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7,5 x 18	B39	32	ZP402F	57, 62	215/50, 215/55, 235/45			

Vivaro (siehe Konfigurator)	X83/F7	5/118	71,1
--	--------	-------	------

Vivaro B X83, F7 5/114,3 66,1 e1*2007/46*0575*..						
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC25T	47	-	66-107	205/65C	Orig.-Verschr., geschl. Aufbau
				66-107	215/60C, 215/65, 215/65C	
	Pro1	45	-	66-107	205/65C, 215/60C, 215/65, 215/65C, 225/60, 225/60C	Orig.-Verschr., geschl. Aufbau
6,5 x 17	RC27	47	-	66-107	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau
7 x 17	B45	45	-	66-107	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau
	AC-V51	45	-	66-107	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau
	Pro1	45	-	66-107	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau

Vivaro NEU ab 2019 V 5/108 65,1 e2*2007/46*0532*..., e2*2007/46*0533*..						
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 16	RC30	46	- od. ZP541F	70-130	215/65, 215/65C	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
7 x 17	RC25T	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
				70-130	215/60C, 225/55C	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
	RC30T	46	- od. ZP541F	70-130	215/60+C, 225/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
				70-130	215/60C	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50	 Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!, nicht Bremse 294x22mm
	B45	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
				70-130	215/60C, 225/55C	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
	RC32	42	ZP538F	75-130	215/55, 215/60, 225/55+C, 235/50	
	RC34	42	- od ZP537F	57-130	215/55, 225/55, 225/55C, 235/50	Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
		44	- od ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50	Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	AC-V51	45	-	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55	Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
			-	70-130	215/60C, 225/55C	Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse

	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 17	RC32	40	ZP538F	57-130	215/55, 225/55+C		nur zulässig an Fahrzeugausführungen "geschlossener Kasten", auch Vivaro-e
	RC34	40	ZP538F	57-130	215/55, 225/55, 225/55C		
		44	- od. ZP537F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50		Orig.-Verschr. Von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto!! nur zulässig an Fahrzeugausführungen "geschlossener Kasten"
7,5 x 18	RC25T	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis!
	B45	45	- od. ZP541F	70-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast
				70-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast
	AC-V51	47	-	70-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC32	44	ZP538F	70-130	235/45, 245/45		

Vivaro-e (C) NEU		im Laufe 2022		V	5/108	65,1	e2*2007/46*0533*11-..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 16	RC25T							Felge ist lt. Thorsten geplant, wann diese tatsächlich kommen wird, kann er noch nicht sagen!
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis!
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis!
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!, nicht Bremse 294x22mm
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	RC34	42	- od ZP537F	57 (100)	215/55, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
		44	- od ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr.
7,5 x 17	RC34	40	ZP538F	57-130	215/55, 225/55, 225/55C			
		44	- od. ZP537F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50			Orig.-Verschr. Von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! nur zulässig an Fahrzeugausführungen "geschlossener Kasten"
7,5 x 18	B45	45	- od. ZP537F	57 (100)	225/50C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 28,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45			

Zafira Tourer (siehe Konfigurator)	ab 2011	P-J/SW	5/115	70,1	e4*2007/46*0204*...., e4*2007/46*0308*...		
--	---------	--------	-------	------	---	--	--

Zafira Life		ab 2019	V	5/108	65,1	e2*2007/46*0532*..., e2*2007/46*0533*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC30	46	- od. ZP541F	70-130	215/65, 215/65C		 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast!
	RC25T	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55		 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast!
				70-130	215/60C, 225/55C		 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast!
	RC30T	46	- od. ZP541F	70-130	215/60+C, 225/55		 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , ohne erhöhte Nutzlast!
				70-130	215/60C		 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis , mit erhöhter Nutzlast!
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		 Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! , nicht Bremse 294x22mm

7 x 17	B45	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast!
				70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast!
	RC32	42	ZP538F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50		
	RC34	42	- od. ZP537F	57-130	215/55, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
		44	- od. ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	AC-V51	45	-	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
			-	70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse
7,5 x 17	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
	RC32	40	ZP538F	57-130	215/55, 225/55+C		nur zulässig an Fahrzeugausführungen "geschlossener Kasten", auch Zafira e-Life
	RC34	40	ZP538F	57-130	215/55, 225/55, 225/55C		
		44	- od. ZP537F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50		Orig.-Verschr. Von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto!! nur zulässig an Fahrzeugausführungen "geschlossener Kasten"
7,5 x 18	RC25T	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit € 32,00 netto Aufpreis
	B45	45	- od. ZP541F	70-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast
				70-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast
	AC-V51	47	-	70-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC32	44	ZP538F	70-130	235/45, 245/45		
	RC34	44	ZP538F	57-130	235/45, 245/45		

Zafira e-Life NEU2022V5/10865,1e2*2007/46*0532*13-..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit € 32,00 netto Aufpreis
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit € 32,00 netto Aufpreis
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50	 Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!, nicht Bremse 294x22mm
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55	 Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	RC32	42	ZP538F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50	
	RC34	42	- od ZP537F	57-130	215/55, 225/55, 225/55C, 235/50	Orig.-Verschr. von Alufelge, wenn Stahl dann ZP537F für € 28,00 netto!!
		44	- od ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50	Orig.-Verschr. von Alufelge, wenn Stahl dann ZP537F für € 28,00 netto!!
7,5 x 17	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50	Orig.-Verschr.
	RC34	40	ZP538F	57-130	215/55, 225/55, 225/55C	
		44	- od. ZP537F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50	Orig.-Verschr. Von Alufelge, bei Stahlfelge ZP537F mit 28,00 netto!! nur zulässig an Fahrzeugausführungen "geschlossener Kasten"
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C	Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45	
8 x 18	RC34	44	ZP538F	57-130	235/45, 245/45	

Peugeot		Baujahr	Typ	LK/LZ	Nabe					
Peugeot 108		ab 2014	P****	4/100	54,1	e11*2001/116*0237*11-...				
kein Sensor - indirektes RDKS										
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
5 x 14	RC30	35	ZP440F	51, 60	165/65, 175/60, 175/65, 185/55, 185/60		ab 185/55 ✖			
5,5 x 15	RC19	36	ZP440F	51, 53, 60	165/60		incl. Facelift 2018			
Peugeot 1008		2018								
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
auf Anfrage										
Peugeot 208 (siehe Konfigurator)		ab 05.12	C	4/108	65,1	e2*2007/46*0070*..., e2*2007/46*0071*...				
Peugeot 208 GTI (siehe Konfigurator)		ab 2013	C	4/108	65,1	e2*2007/46*0070*..				
Peugeot 208 II		2018	U	4/108	65,1	e2*2007/46*0639*03-..				
kein Sensor - indirektes RDKS										
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
6 x 15	RC30	32	ZP402F	55-96	185/60, 185/65, 195/60		ohne GT-Line			
				55-96	185/55, 195/55					
6,5 x 16	RC30	38	ZP402F	55-96	185/55		incl. Facelift 2023, ohne GT-Line			
				55-100	195/55					
				RC34	32	- od. ZP401F	55-96	185/55, 195/55, 205/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!! Beide ET's sind ECE!
						38	- od. ZP401F	55-96		
	RC30	32	ZP402F	55-96	185/55, 195/55		ohne GT-Line			
		RC34	32	- od. ZP401F	55-96	185/55, 195/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!		
6,5 x 17	RC34	32	-	55-96	185/50, 195/45, 205/45		Orig.-Verschr.			
7 x 17	RC34	32	- od. ZP401F	55-100	195/45, 205/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!! Beide ET's sind ECE!			
		38	- od. ZP401F	55-100	195/45, 205/45, 215/40					
	B39	38	ZP402F	55-96	195/45, 205/45		ohne GT-Line			
Peugeot 208 II GT-Line		2018	U	4/108	65,1	e2*2007/46*0639*03-..				
kein Sensor - indirektes RDKS										
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
6,5 x 16	RC30	32	ZP402F	74-100	195/55, 205/50		incl. Facelift 2023, nur M+S			
	RC34	32	ZP402F	74-96	195/55		i.V.			
	RC24	23	ZP402F	74-96	195/55		nur M+S			
	RC30	38	ZP402F	74-100	195/55		incl. Facelift 2023, nur M+S			
7 x 16	RC28	32	ZP402F	74-96	195/55, 205/50, 225/45		nur M+S			
7 x 17	RC34	32+38	-	74-96	205/45		Orig.-Verschr., beide ET's sind ECE			
	B39	38	ZP402F	74-96	195/45M+S, 205/45					
7,5 x 18	B39	32	ZP402F	74-100	205/40, 215/35		incl. Facelift 2023			
Peugeot e-208 elektro		ab 02.2020	U	4/108	65,1	e2*2007/46*0639*..				
kein Sensor - indirektes RDKS										
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
6,5 x 16	RC30	32	ZP402F	57, 62	195/55		incl. Facelift 2023			
	RC34	32	- od. ZP401F	26-62	195/55, 205/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!, beide ET's sind ECE			
		38	- od. ZP401F	26-57	195/55, 205/50					
7 x 16	RC28	32	ZP402F	57	195/55					
6,5 x 17	RC34	32	-	26-57	195/45, 205/45		Orig.-Verschr.			
7 x 17	RC34	32	- od. ZP401F	26-62	195/45, 205/45, 215/40		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!! beide ET's sind ECE			
		38	- od. ZP401F	26-57	195/45, 205/45, 215/40					
		B24	25	ZP402F	57, 62	195/45, 205/45				
7,5 x 18	B39	25	ZP402F	57, 62	195/45, 205/45					
	B39	32	ZP402F	57, 62	205/40		incl. Facelift 2023			
Peugeot 208 / e-208 NEU i.V.		im Laufe 2023								
Dimension	Design	ET	KIT	KW	Reifendimension	Info				
Peugeot 2008 (siehe Konfigurator)		ab 2013	C	4/108	65,1					

Peugeot 2008		ab FL2016		C	4/108	65,1	e2*2007/46*0070*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 15	RC28	20	ZP402F	55-88	195/65, 205/60, 215/60			mit Radhausverbreiterungen
6,5 x 16	RC30	20	ZP402F	55-96	195/60, 205/55			mit Radhausverbreiterungen
	RC34	20	- od. ZP401F	50-96	195/60, 205/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
	RC24	20	ZP402F	55-96	195/60, 205/55			mit Radhausverbreiterungen
7 x 16	RC28	18	ZP402F	55-96	195/60, 205/55			
6,5 x 17	RC34	20	- od. ZP401F	55-96	205/45, 205/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 17	RC34	20	- od. ZP401F	50-96	205/45, 215/45			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7,5 x 18	B39	20	ZP402F	55-96	205/40, 205/45			mit Radhausverbreiterungen
7,5 x 19	B39	18	ZP402F	55-96	215/35			

Peugeot 2008		ab 01.2020		U	4/108	65,1	e2*2007/46*0639*05-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	32	ZP402F	74-114	215/60, 215/65, 225/60			incl. Facelift 2023
	RC34	32	- od. ZP401F	74-114	215/60, 215/65, 225/60, 225/65			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
6,5 x 17	RC34	32	- od. ZP401F	74-114	215/60, 225/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 17	RC34	32	- od. ZP401F	74-114	215/60			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 18	Originaldim.	35			215/55			
7,5 x 18	B39	32	ZP402F	74-114	215/50, 215/55, 235/45			incl. Facelift 2023

Peugeot e-2008		ab 2020		U	4/108	65,1	e2*2007/46*0639*05-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	32	ZP402F	57, 62	215/60, 215/65			incl. Facelift 2023
	RC34	32	- od. ZP401F	57-62	215/60, 215/65, 225/60			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 16	RC28	32	ZP402F	57 (100)	215/60, 215/65			
6,5 x 17	RC34	32	- od. ZP401F	57-62	215/60, 225/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7 x 17	RC34	32	- od. ZP401F	57-62	215/60, 225/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP401F mit € 32,00 netto!!
7,5 x 18	B39	32	ZP402F	57, 62	215/50, 215/55, 235/45			incl. Facelift 2023

Peugeot 308 (siehe Konfigurator)		ab 2013		L	5/108	65,1	e2*2007/46*0405*...	
Peugeot 308 GTI (siehe Konfigurator)		ab 2015		L	5/108	65,1	e2*2007/46*0405* ...	

Peugeot 308 (III) NEU			im Laufe 2022		F	5/108	65,1	e2*2007/46*0628*13-..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 16	RC30	44	ZP538F	81-96	205/55, 215/55, 225/50				
7 x 17	RC34	44	- od. ZP537F	81-132	205/50, 215/45, 225/45				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC27	42	- od. ZP537F	81-96 81-132	205/50, 215/45 225/45				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC32	42	ZP538F	81-132	205/50, 215/45, 225/45				
	RC34	42	- od. ZP537F	81-132	205/50, 215/45, 225/45				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42	ZP538F	81-96 81-132	205/50, 215/45 225/45				
	Pro1	45	-	81-132	205/50, 215/45, 225/45				Orig.-Verschr.
7,5 x 17	RC34	44	-	81-132	205/50, 215/45, 225/45				Orig.-Verschr.
	RC29	45	ZP538	81-96 81-132	205/50, 215/45 225/45				
	RC32	40	ZP538F	81-132	215/45				
	B36	45	ZP538	81-96	205/50, 215/45				nicht Bremse 304 u. 330mm
				81-132	225/45				
	7 x 18	RC27	44	- od. ZP537F	81-96	205/45			
	RC32	49	ZP538F	81-132	225/40				nicht Bremse 304x28mm
	RC34	49	-	81-96	205/45, 225/40				Orig.-Verschr.
	B32	45	ZP538	81-96	205/45				
				81-132	225/40				

7,5 x 18	AC-MB6 / AC-M10	42	ZP538F+R	81-96 81-132	205/45 225/40		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	81-96 81-132	205/45 225/40		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	81-132	205/45, 225/40		
8 x 18	RC34	44	ZP538F	81-132	205/45		
	B37	45	ZP538	81-132	225/40		
	B42 / B44	42	ZP538	81-132	225/40		
	AC-M10	42	ZP538F+R	81-132	225/40		+ Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	81-132	225/40		+ Red.Ringe 73,1-65,1
8,5 x 18	CA 20	45	ZP538	81-132	225/40		nicht Bremse 304 u. 330mm
	B32	45	ZP538	81-132	225/40		

Peugeot e-308 NEU Mitte 2023 F 5/108 65,1 e2*2007/46*0628*25-..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 18	RC27	44	- od. ZP537F	62 (115)	215/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	62 (115)	215/45		
	AC-MB6	42	ZP538F+R	62 (115)	215/45, 225/40		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	62 (115)	215/45, 225/40		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	62	215/45, 225/40		
8 x 18	B42	42	ZP538	62 (115)	215/45		
	B44	42	ZP538	62 (115)	215/45		
7,5 x 19	RC32	42	ZP538F	62	215/40		

Peugeot 3008 ab 2016 M 5/108 65,1 e2*2007/46*0534*...							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	73-133	205/65, 215/60, 215/65, 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. FL2021
	RC30	42	ZP538F	73-133	205/65, 215/60, 215/65, 225/60		incl. FL2021
	RC32	42	ZP538F	73-133	205/65, 215/60, 215/65, 225/60		
	RC34	42	- od. ZP537F	73-133	205/65, 215/60, 215/65, 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42	ZP538F	73-133	205/65, 215/60, 215/65, 225/60		incl. FL2021
	RC30	50	ZP538F	73-133	205/65, 215/60, 215/65, 225/60		
	RC34	44+46	- od. ZP537F	73-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	AC-V51	45	-	73-133	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr. von Alufelgen, incl. Facelift 2021, nicht Bremse 304 u. 330 VA u. nicht 268mm HA
	CA 26 Pro1	50 45	ZP538F -	73-133 73-133	205/65, 215/60, 215/65, 225/60 205/65, 215/60, 215/65, 225/60, 235/55, 235/60		incl. Facelift 2021, nicht Bremse 330mm Orig.-Verschr.
7 x 18	RC27	44+48	- od. ZP537F	73-133	215/55, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	RC30	49	ZP538F	73-133	215/55, 225/55		incl. FL2021, nicht Bremse 304 u. 330mm
	RC32	49	ZP538F	73-133	215/55, 215/60, 225/55		
	RC34	49	-	73-133	215/55, 215/60, 225/55		Orig.-Verschr.
	B32	45	ZP538	73-133	215/55, 225/55, 235/50, 235/55		incl. Facelift 2021
	B39	45	ZP538	73-133	215/55, 225/55, 235/50, 235/55		incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
	AC-521	42	ZP538F+R	73-133	215/55, 225/55, 235/50, 235/55		+ Red.Ringe 73,1-65,1, incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
7 x 19	CA 20	45	ZP538F	73-133	215/55, 215/60, 225/55		
	RC27	38	ZP538F	73-133	205/55, 235/50		incl. Facelift 2021
	RC34	38	-	73-133	205/55		Orig.-Verschr.
7,5 x 19	RC27	41	- od. ZP537F	73-133	205/55, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC32	42	ZP538F	73-133	205/55, 225/45, 235/45, 235/50		
	B32	42	ZP538F	73-133	235/45, 235/50, 245/45		incl. Facelift 2021
8 x 19	AC-521	42	ZP538F+R	73-133	235/45, 235/50, 245/45		incl. Facelift 2021
	RC29	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021
	RC34	42	ZP538F	73-133	225/45, 235/45		
	B38	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021, nicht Bremse 304 u. 330mm
	AC-518	45	ZP538F+R	73-133	235/45, 245/45		+ Red. Ringe 73,1-65,1
8 x 20	Oxigin 29	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021
	B43	44	-	73-133	215/45, 235/40		Orig.-Verschr. für Alufelgen, incl. Facelift 2021

weitere Dimensionen/Designs siehe Konfigurator

Peugeot 3008 Hybrid ab 2019 M 5/108 65,1 e2*2007/46*0534*...							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	133, 147	205/65, 215/60, 215/65, 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. FL2021

	RC30	42	ZP538F	133, 147	205/65, 215/60, 215/65 , 225/60		incl. Facelift 2021
	CA 26	42	ZP538F	133, 147	205/65, 215/60, 215/65 , 225/60		incl. Facelift 2021
7,5 x 17	RC29	45	ZP538	133, 147	205/65, 215/60, 215/65, 225/60		incl. Facelift 2021
7 x 18	RC27	44+48	- od. ZP537F	133, 147	215/55, 225/55, 235/50, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	Originaldim.	49			225/55		
	B32	45	ZP538	133, 147	215/55, 225/55		
	B39	45	ZP538	133, 147	215/55, 225/55		incl. Facelift 2021
	AC-MB6	42	ZP538F+R	133, 147	215/55, 225/55		incl. Facelift 2021, + Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	133, 147	215/55, 225/55, 235/50, 235/55		+ Red.Ringe 73,1-65,1 , incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
8 x 18	RC29	45	ZP538	133, 147	225/55		
	B37	45	ZP538	133, 147	225/55		incl. Facelift 2021
7 x 19	RC27	38	ZP538F	133, 147	205/55		incl. Facelift 2021
		41	- od. ZP537F	133, 147	205/55, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! bei 235/50 ✖
7,5 x 19	B32	42	ZP538F	133, 147	235/45		incl. Facelift 2021
	AC-521	42	ZP538F+R	133, 147	235/45		incl. Facelift 2021, + Red.Ringe 73,1-65,1
	CA 26	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021
8 x 19	RC29	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021
	Oxigin 29	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021
8,5 x 19	B32	45	ZP538	133, 147	235/45, 245/45		incl. Facelift 2021, bei 245/45 ✖
8 x 20	RC36	50	- od. ZP537F	133, 147	215/45, 235/40		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. FL2021
	B43	44	-	133, 147	215/45, 235/40		Orig.-Verschr. für Alufelgen, incl. Facelift 2021
8,5 x 20	B32	45	ZP538	133, 147	235/40		

Peugeot 3008 HEV		Mild-Hybrid NEU	Frühj. 2024	K	5/108	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 18	RC27	48	- od. ZP537F	100	225/60		Orig.-Verschr. von Alufelge, i.V., wenn Stahlfelge dann Kit ZP537F für € 28,00!!
				100	225/60, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. FL2021
	FMI06 Koros	48	-		225/60		Orig.-Verschr., i.V.
	RC27	44	- od. ZP537F	100	225/60, 235/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	100	225/60, 235/55		
	AC-MB6	42	ZP538F+R	100	225/60		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	100	225/60		+ Red.Ringe 73,1-65,1
8 x 18	B37	45	ZP538	100	225/60		
7 x 19	RC27	41	-		225/55		Orig.-Verschr., i.V.
7,5 x 19	RC32	42			225/55		i.V.
	CA 26	45	ZP538	100	225/55, 235/50		
8 x 20	RC36	50	- od. ZP537F	100	235/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!

Peugeot 3008 PHEV		Plug-in-Hybrid NEU	Frühj. 2024	K	5/114,3	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	B43	43	-	110	235/55, 255/50HA		Orig.-Verschr. HA ✖
	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	110	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	43	-	110	235/50		Orig.-Verschr.
				110	235/50, 245/45, 255/45		

Peugeot e-3008		NEU	Frühjahr 2024	K	5/114,3	65,1	e2*2018/858*00064*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	B43	43	-	104 (157)	235/55, 255/50HA		Orig.-Verschr., HA ✖
	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	104, 105	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	43	-	104, 105	235/50		Orig.-Verschr.
				104, 105	235/50, 245/45, 255/45		

Peugeot 408		NEU	Ende 2023	F	5/108	65,1	e2*2007/46*0628*20..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	42	- od. ZP537F	96, 100	205/65, 215/65 , 225/60		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42	ZP538F	96, 100	205/65, 215/65 , 225/60		
7,5 x 17	RC27	37	ZP538F	96, 100	205/65		

7 x 18	RC27	44	- od. ZP537F	96, 100	205/60, 215/55, 215/60, 225/55, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	96, 100	205/60, 215/55, 215/60, 225/55		
	AC-MB6	42	ZP538F+R	96, 100	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	96, 100	205/60, 215/55, 215/60, 225/55		+ Red.Ringe 73,1-65,1
8 x 18	B37	45	ZP538	96, 100	225/55		mit Kotflügelverbreiterungen
7 x 19	RC27	41	- od. ZP537F	96, 100	205/55, 215/50, 225/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		38	ZP538F	96, 100	205/55, 215/50		
7,5 x 19	CA 26	45	ZP538	96, 100	215/50, 225/50, 235/45, 245/45		
8 x 19	Oxigin 29	45	ZP538	96, 100	235/45		
8 x 20	RC36	50	- od. ZP537F	96, 100	215/45, 235/40, 245/40		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!

Peugeot e-408		Plug-in Hybrid NEU		November 2024		F	5/108	65,1	e2*2007/46*0628*..
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC27	42	- od. ZP537F	110, 132	205/65, 215/65 , 225/60				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42	ZP538F	110, 132	205/65, 215/65 , 225/60				
7,5 x 17	RC27	37	ZP538F	110, 132	205/65				
7 x 18	RC27	44	- od. ZP537F	110, 132	205/60, 215/55, 215/60, 225/55, 235/50				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	B32	45	ZP538	110, 132	205/60, 215/55, 215/60, 225/55				
	AC-MB6	42	ZP538F+R	110, 132	205/60, 215/55, 215/60, 225/55				+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	110, 132	205/60, 215/55, 215/60, 225/55				+ Red.Ringe 73,1-65,1
8 x 18	B37	45	ZP538	110, 132	225/55				mit Kotflügelverbreiterungen
7 x 19	RC27	41	- od. ZP537F	110, 132	205/55, 215/50, 225/50				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		38	ZP538F	110, 132	205/55, 215/50				
7,5 x 19	CA 26	45	ZP538	110, 132	215/50, 225/50, 235/45, 245/45				
8 x 19	Oxigin 29	45	ZP538	110, 132	235/45				
8 x 20	RC36	50	- od. ZP537F	110, 132	215/45, 235/40, 245/40				Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!

Peugeot 508 (siehe Konfigurator)	ab 05.11	8	5/108	65,1	e2*2007/46*0080*..., e2*2007/46*0081*...
----------------------------------	----------	---	-------	------	--

Peugeot 508		2018		F	5/108	65,1	e2*2007/46*0628*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	Originaldim.	40		96, 133	215/60		
	RC30	44	ZP538F	96, 133	215/60, 225/55		nur Bremse 304mm
7 x 17	RC27	42	- od. ZP537F	96-165	215/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	42	ZP538F	96-165	215/55, 225/50, 235/50		
	RC34	42	- od. ZP537F	96-165	215/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42	ZP538F	96-165	215/55, 225/50, 235/50		
	RC32	42	ZP538F	96-165	215/55, 225/50, 235/50		
	RC34	44	- od. ZP537F	96-165	215/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
		46	- od. ZP537F	96-165	215/55, 225/50, 235/50		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! nicht Bremse 330x30mm VA u. 268x12mm HA
	AC-V51	45	-	96-165	225/50		Orig.-Verschr. von Alufelgen, nicht Bremse 330mm
	Pro1	45	-	96-165	215/55, 225/50, 235/50		Orig.-Verschr.
	7,5 x 17	RC32	40	ZP538F	96-165	215/55, 225/50, 245/45	
RC34		40	ZP538F	96-165	215/55, 225/50		
RC24		44	ZP538F	120-165	215/55, 225/50, 235/50, 245/45		Felge gibt es nur in silber, nur Bremse 330mm
RC29		45	ZP538	96-165	215/55, 235/50HA		
RC34		44	-	96-165	215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
7,5 x 18	B39	45	ZP538	96-165	215/50, 225/45, 235/45		
	AC-MB6	42	ZP538F+R	96-165	215/50, 225/45, 235/45		+ Red.Ringe 73,1-65,1
	AC-M10	42	ZP538F+R	96-165	215/50, 225/45, 235/45		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	96-165	215/50, 225/45, 235/45		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	96-165	215/50, 225/45, 235/45, 245/45		
8 x 18	RC32	44	ZP538F	96-165	235/45		
	RC34	44	ZP538F	96-165	225/45, 235/45, 245/40, 245/45		
	RC29	45	ZP538	96-165	225/45, 235/45, 245/40HA		
	B37	45	ZP538	96-165	225/45, 235/45, 245/40HA		
	B42 / B44	42	ZP538	96-165	225/45, 235/45, 245/40HA		

	AC-M10	42	ZP538F+R	96-165	225/45, 235/45, 245/40HA		+ Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	96-165	225/45, 235/45, 245/40HA		+ Red.Ringe 73,1-65,1
7,5 x 19	RC32	40+42	ZP538F	96-165	225/40		
8 x 19	Originaldim.	44		96-165	235/40		
	RC29	45	ZP538	96-165	225/40, 235/35, 235/40, 245/35		
	RC34	42	ZP538F	96-165	225/40, 235/40, 245/35		
	B38	45	ZP538	96-165	225/40, 235/35, 235/40, 245/35		nicht Bremse 330mm
	Oxigin 29	45	ZP538	96-165	225/40, 235/35, 235/40, 245/35HA		
8,5 x 19	Oxigin 28	38	ZP538	96-165	225/40		
8 x 20	B43	44	-	96-165	225/35, 235/35		Orig.-Verschr. für Alufelgen

Peugeot 508 Plug-in-Hybrid							
ab 2019				F	5/108	65,1	e2*2007/46*0628*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT		KW	Reifendimension	Info
7 x 17	RC27	42	- od.	ZP537F	133	215/55 , 225/50, 235/50	 Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	42		ZP538F	133	215/55 , 225/50, 235/50	
	CA 26	42		ZP538F	133	215/55 , 225/50, 235/50	
7,5 x 17	RC27	37		ZP538F	133	215/55, 225/50, 245/45	
	RC29	45		ZP538	133	215/55, 235/50HA	
7,5 x 18	B32	45		ZP538	133	215/50, 225/45, 235/45	
	AC-MB6	42		ZP538F+R	133	215/50, 225/45, 235/45	+ Red.Ringe 73,1-65,1
	AC-M10	42		ZP538F+R	133	215/50, 225/45, 235/45	+ Red.Ringe 73,1-65,1
	AC-521	42		ZP538F+R	133	215/50, 225/45, 235/45	+ Red.Ringe 73,1-65,1
8 x 18	RC29	45		ZP538	133	225/45, 235/45, 245/40HA	
	B37	45		ZP538	133	225/45, 235/45, 245/40HA	
	B42 / B44	42		ZP538	133	225/45, 235/45, 245/40HA	
	AC-M10	42		ZP538F+R	133	225/45, 235/45, 245/40HA	+ Red.Ringe 73,1-65,1
	AC-521	43		ZP538F+R	133	225/45, 235/45, 245/40HA	+ Red.Ringe 73,1-65,1
	Originaldim.	44			133	235/45	
8 x 19	RC29	45		ZP538	133	225/40, 235/40	
	Oxigin 29	45		ZP538	133	225/40, 235/40, 245/35HA	
8,5 x 19	Oxigin 28	38		ZP538	133	225/40	

Peugeot 5008							
ab 04.2017				M	5/108	65,1	e2*2007/46*0534*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT		KW	Reifendimension	Info
7 x 17	RC27	42	- od.	ZP537F	73-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60, 245/55	 Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. Facelift 2021
	RC30	42		ZP538F	73-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60, 245/55	 incl. FL2021
	RC32	42		ZP538F	73-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60	
	RC34	42	- od.	ZP537F	73-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60	 Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	CA 26	42		ZP538F	73-133	205/65, 215/60, 215/65 , 225/60, 235/55, 235/60, 245/55	 incl. Facelift 2021
	RC30	50		ZP538F	73-133	205/65, 215/60, 215/65, 225/60	
	RC34	44+46	- od.	ZP537F	73-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60	Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7 x 18	CA 26 Pro1	50		ZP538F	73-133	205/65, 215/60, 215/65, 225/60	incl. Facelift 2021, nicht Bremse 330mm
		45		-	73-133	205/65, 215/60, 215/65, 225/60, 235/55, 235/60	Orig.-Verschr.
	RC27	44+48	- od.	ZP537F	73-133	215/55, 225/55, 235/50, 235/55, 245/50	Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
	RC30	49		ZP538F	73-133	215/55, 225/55	 incl. Facelift 2021, nicht Bremse 304 u. 330mm
	RC32	49		ZP538F	73-133	215/55, 215/60, 225/55	
	RC34	49		-	73-133	215/55, 215/60, 225/55	 Orig.-Verschr.
	B32	45		ZP538	73-133	215/55, 225/55, 235/50, 235/55	incl. Facelift 2021
	B39	45		ZP538	73-133	215/55, 225/55, 235/50, 235/55	
7,5 x 18	AC-MB6	42		ZP538F+R	73-133	215/55, 225/55, 235/50, 235/55	+ Red.Ringe 73,1-65,1, incl. Facelift 2021
	AC-521	42		ZP538F+R	73-133	215/55, 225/55, 235/50, 235/55	+ Red.Ringe 73,1-65,1, incl. Facelift 2021
	CA 20	45		ZP538F	73-133	215/55, 215/60, 225/55, 235/50, 235/55	
	B42	42		ZP538	73-133	225/55 225/55, 235/50, 235/55	incl. Facelift 2021 Reifen zulässig bei Serie 235/50 R19
7 x 19	RC27	38		ZP538F	73-133	205/55 , 235/50	 incl. Facelift 2021
	RC34	38		-	73-133	205/55	 Orig.-Verschr.
	RC27	41	- od.	ZP537F	73-133	205/55, 235/50	Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!! incl. Facelift 2021
7,5 x 19	RC32	42		ZP538F	73-133	205/50, 205/55, 225/45, 235/45, 235/50 , 245/45	 incl. Facelift 2021, nicht Bremse 304mm in Verbindung mit Bremssattelträger mit Bügel
	B32	42		ZP538F	73-133	235/45, 235/50 , 245/45	
	AC-521	42		ZP538F+R	73-133	235/45, 235/50, 245/45	 + Red.Ringe 73,1-65,1
	CA 26	45		ZP538	73-133	235/45, 235/50, 245/45	

8 x 19	RC29	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021
	RC34	42	ZP538F	73-133	225/45, 235/45, 245/45		
	B38	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021, nicht Bremse 304 u. 330mm
	AC-518	45	ZP538F+R	73-133	235/45, 245/45		+ Red.Ringe 73,1-65,1
	Oxigin 29	45	ZP538	73-133	235/45, 245/45		incl. Facelift 2021
8 x 20	B43	44	-	73-133	215/45, 235/40, 245/40		Orig.-Verschr. für Alufelgen

weitere Dimensionen/Designs siehe Konfigurator

Peugeot 5008 Hybrid NEU			2024	K	5/108	65,1	e2*2018/858*00065*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 18	FMI06 Koros	48	-		225/60			Orig.-Verschr.
8 x 20	RC36	50	- od. ZP537F	100	235/45			Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!

Peugeot 5008 Plug-in Hybrid NEU		Herbst 2024		K	5/114,3	65,1	e2*2018/858*00064*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	110	235/50, 245/45, 255/45		Orig.-Verschr.

Peugeot e-5008 NEU		Herbst 2024		K	5/114,3	65,1	e2*2018/858*00064*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	FMI06 Koros	43	-		235/55		Orig.-Verschr.
8 x 20	RC36	43	-	104, 105	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	43	-	104, 105	235/50		Orig.-Verschr.

Expert III, Traveller			ab 2019		V	5/108	65,1	e2*2007/46*0532*..., e2*2007/46*0533*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 16	RC30	46	- od. ZP541F	70-130	215/65, 215/65C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, ohne erhöhte Nutzlast!	
7 x 17	RC25T	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55+C, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, ohne erhöhte Nutzlast!	
			- od. ZP541F	70-130	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, mit erhöhter Nutzlast!	
			- od. ZP541F	70-130	215/60+C, 225/55, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto	
	RC30T	46	- od. ZP541F	70-130	215/60+C, 225/55, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto	
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!	
	B45	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, ohne erhöhte Nutzlast!	
			- od. ZP541F	70-130	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, mit erhöhter Nutzlast!	
	RC32	42	ZP538F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50				
	RC34	42	- od. ZP537F	57-130	215/55, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!	
		44	- od. ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!	
		AC-V51	45	-	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55			Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	-			70-130	215/60C, 225/55C			Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse	
Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50			Orig.-Verschr.		
7,5 x 17	RC34	44	- od. ZP537F	70-130	215/55, 215/60, 225/55, 225/55C, 235/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!	
7,5 x 18	RC25T	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45			Orig.-Verschr. von Stahlfelge, sonst ZP541F mit Aufpreis € 32,00 netto, ohne erhöhte Nutzlast!!	
	B45	45	- od. ZP541F	70-130	215/55, 225/50, 225/50C, 235/45, 245/45			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast	
				70-130	225/50C			Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast	
	AC-V51	47	-	70-130	245/45			Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse	
	CA 20	45	ZP538F	57-130	235/45, 245/45				

8 x 18	RC32	44	ZP538F	70-130	235/45, 245/45		
	RC34	44	ZP538F	57-130	235/45, 245/45		

e-Expert (III) NEU							
kein Sensor - indirektes RDKS				V	5/108	65,1	e2*2007/46*0533*11-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto
	RC34	46	- od. ZP537F	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, geschl. Aufbau
	RC32	42	ZP538F	57-130	215/55, 215/60, 225/55, 225/55C, 235/50		
	RC34	42	- od. ZP537F	57-130	215/55, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
		44	- od. ZP537F	57-130	215/55, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC34	44	ZP538F	57-130	235/45, 245/45		

e-Expert / e-Traveller NEU							
kein Sensor - indirektes RDKS				V	5/108	65,1	e2*2007/46*0532*13-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, geschl. Aufbau
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau

Partner IV							
Sensor - Brocksens 6				ab 2018	E	5/108	65,1
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC30	47	ZP538F	55-96	205/55, 205/60, 215/55		 nicht bei 15" Serie, nicht Bremse 283mm
	RC32	47	ZP538F	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55		Serienreifen bis 205/..
					215/65, 215/65C, 225/65C		Serienreifen ab 215/..
	RC34	47	- od. ZP537F	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 20	45	ZP538	55-96	205/55, 205/60, 215/55, 225/50, 225/55		
7 x 17	Pro1	42	-	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55		Orig.-Verschr., Serienreifen bis 205/..
	RC30	50	ZP538F	55-96	205/50, 205/55, 225/45		nicht bei 16" Serie
	RC34	50	- od. ZP537F	55-96	205/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	50	ZP538F	55-96	205/55		
	RC27	42	- od. ZP537F	55-81	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! bei 15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	55-81	205/50, 215/45, 225/45		bei 15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		nicht bei 15" Serie
	RC32	42	ZP538F	55-96	195/50, 195/55, 205/45, 205/50, 205/55, 215/45		
	RC34	42	- od. ZP537F	55-96	195/50, 195/55, 205/45, 205/50, 205/55, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	42	ZP538F	55-81	205/50, 215/45, 225/45		15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		
		50	ZP538F	55-96	205/50, 205/55, 225/45		
7,5 x 17	Pro1	45	-	55-96	205/45, 205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr., Serienreifen bis 205/..
	RC29	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie
	RC34	44	- od. ZP537F	55-96	205/45, 205/50, 205/55, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	B36	45	ZP538	55-96	205/50, 205/55, 225/45		

	AC-518	45	ZP538F+R	55-96	205/50, 205/55, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
7 x 18	RC27	44+48	- od. ZP537F	55-96	205/45, 215/45, 225/45		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45		nicht bei 15" Serie
	RC32	49	ZP538F	55-96	215/40, 215/45, 225/40		
	RC34	49	-	55-96	215/40, 215/45, 225/40		Orig.-Verschr.
	B32 / B39	45	ZP538	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	AC-MB6 / AC-M10	42	ZP538F+R	55-81	205/45, 215/40, 225/40		bei 15" Serie
				55-96	205/45, 215/45, 225/40, 225/45		
8 x 18	AC-521	42	ZP538F+R	55-81	205/45, 215/40, 225/40		bei 15" Serie
				55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15" Serie
	RC29	45	ZP538	55-96	215/45, 225/40, 225/45		
	RC32 / RC34	44	ZP538F	55-96	215/40, 215/45		
	B24	45	ZP538	55-96	215/45, 225/40, 225/45		
	B38	45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie, nicht Bremse 283 u. 304mm
	B42	42	ZP538	55-81	215/40		bei 15" Serie
				55-96	215/45		
	AC-M10	42	ZP538F+R	55-81	215/40		+ Red.Ringe 73,1-65,1, bei 15" Serie
7,5 x 19				55-96	215/45		+ Red.Ringe 73,1-65,1 , nicht Bremse 283mm
	AC-518	45	ZP538F+R	55-96	215/45, 225/40, 225/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
	AC-521	43	ZP538F+R	55-96	215/45		nicht bei 15" Serie, + Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	55-81	225/35		15 Zoll Serie, + Red.Ringe 73,1-65,1

RCZ (siehe Konfigurator)	ab 05.10	4J	5/108	65,1	e2*2007/46*0036*...
---------------------------------	-----------------	-----------	--------------	-------------	---------------------

RCZ R (siehe Konfigurator)	ab 2013	4J	5/108	65,1	e2*2007/46*0036*...
-----------------------------------	----------------	-----------	--------------	-------------	---------------------

Rifter	ab 2018	E	5/108	65,1	e2*2007/46*0624*..., e2*2007/46*0625*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
-----------	--------	----	-----	----	-----------------	------

ACHTUNG! unbedingt Achslasten beachten!

6,5 x 16	RC30	47	ZP538F	56-96	215/65		nicht Bremse 283mm
	RC32	47	ZP538F	55-96	215/65, 225/65C		
	RC34	47	- od. ZP537F	55-96	215/65, 215/65C, 225/65C		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC24	47	ZP538F	56-96	215/65		
	CA 20	45	ZP538	56-96	215/65, 225/60		
	Pro1	42	-	55-96	215/65, 215/65C, 225/60, 225/60C, 235/60		Orig.-Verschr.
7 x 17	RC34	44	- od. ZP537F	55-96	215/55, 215/60 , 215/60C, 225/55, 225/55C		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC27	42	- od. ZP537F	56-96	215/55, 215/60, 225/55		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	56-96	215/55, 215/60, 225/55		
	RC32	42	ZP538F	55-96	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		
	RC34	42	- od. ZP537F	55-96	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	AC-V51	45	-	56-96	215/60		Orig.-Verschr. von Alufelge, nicht Bremse 283 u. 304mm
	CA 26	42	ZP538F	56-96	215/55, 215/60, 225/55		
	Pro1	45	-	55-96	215/55, 215/60, 215/60C, 225/55, 225/55C		Orig.-Verschr.
7,5 x 17	RC24	44	ZP538F	56-96	215/55, 215/60		
	RC29	45	ZP538	56-96	215/55, 215/60		
	RC34	40	ZP538F	55-96	215/55, 215/60, 225/55, 235/50		
		44	- od. ZP537F	55-96	215/55, 215/60		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	B24	45	ZP538	56-96	215/55, 215/60		
	B36	45	ZP538	56-96	215/55, 215/60		
7 x 18	RC27	44	- od. ZP537F	56-96	215/50, 215/55		Orig.-Verschr. von Alufelge, wenn Stahlfelge dann Kit ZP537F für € 28,00!!
7,5 x 18	RC32	49	ZP538F	55-96	215/50, 235/45		
	RC34	49	-	55-96	215/50, 235/45		Orig.-Verschr.
	B32	45	ZP538	56-96	215/50, 215/55, 235/45		
	B39	45	ZP538	56-96	215/50, 215/55, 235/45		
	AC-MB6	42	ZP538F+R	56-96	215/50, 215/55, 235/45		+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	56-96	215/50, 215/55, 235/45		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538F	55-96	215/50, 225/50, 235/45		
8 x 18	B42 / B44	42	ZP538	56-96	235/45		
	AC-M10	42	ZP538F+R	56-96	235/45		+ Red.Ringe 73,1-65,1 , nicht Bremse 283mm
7 x 19	RC34	38	-	55-96	225/45		Orig.-Verschr.
7,5 x 19	RC32	42	ZP538F	55-96	225/45		
	B32	42	ZP538F	56-96	225/40, 225/45, 235/45		
	AC-521	42	ZP538F+R	56-96	225/40, 225/45, 235/45		+ Red.Ringe 73,1-65,1
	CA 26	45	ZP538	56-96	225/40, 225/45		

8 x 19	RC29	45	ZP538	56-96	225/40, 225/45		mit Radhausverbreiterung
	RC34	42	ZP538F	55-96	225/45, 235/40		
	B24	45	ZP538	56-96	225/40, 225/45		nicht Bremse 283 u. 304mm
	B38	45	ZP538	56-96	225/40, 225/45		
	AC-518	45	ZP538F+R	56-96	225/40, 225/45		+ Red.Ringe 73,1-65,1
8 x 20	Oxigin 29	45	ZP538	56-96	225/40, 225/45		
	B43	44	-	56-96	225/40		Orig.-Verschr. für Alufelgen

e-Rifter NEU		ab 2022		E	5/108	65,1	e2*2007/46*0624*..., e2*2007/46*0625*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	Pro1	42	-	57	205/60, 215/55, 215/60			Orig.-Verschr., Serienreifen bis 205/..
7 x 17	RC34	50	- od. ZP537F	57	205/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC32	42	ZP538F	57	205/50, 205/55			
	RC34	42	- od. ZP537F	57	205/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
		44	- od. ZP537F	57	205/50, 205/55, 215/50			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	Pro1	45	-	57	205/50, 205/55, 215/50			Orig.-Verschr.
7,5 x 18	CA 20	45	ZP538F	57	215/45, 225/40, 225/45			
8 x 18	RC34	44	ZP538F	57-62	215/45			

Boxer (5/118)		bis 2002		Y, 250,250L	5/118	71,1	
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC25T	60	-	74-110	205/65C, 215/60C		Orig.-Verschr., ohne Radhausverbr. ✖
				74-132	215/65, 215/65C, 215/75C, 225/60, 225/60C, 225/65, 225/65C, 225/75C		Orig.-Verschr., ohne Radhausverbr. ✖
7 x 17	B45	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C		Orig.-Verschr., ohne Radhausverbr. ✖
	AC-V51	62	-	74-132	215/60C, 215/65, 225/55, 225/55C, 225/65, 235/55, 235/60C		Orig.-Verschr., ohne Radhausverbr. ✖
7,5 x 18	AC-V51	65	-	74-132	225/60, 235/50, 235/55, 235/60		Orig.-Verschr., ohne Radhausverbr. ✖

Boxer (5/130)		bis Modelljahr 2013		Y, 250,250L	5/130	78,1	e2*2007/46*0219*... e3*2001/116*0233*... e3*2007/46*0045*..	
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC25T	60	-	74-132	215/75C, 225/75C, 235/65C		Orig.-Verschr., ohne Radhausverbr. ✖	
	Pro1	58	-	88-130	215/75C, 225/75C, 235/65C		Orig.-Verschr., ab 235/65C ✖	
7 x 17	B45	62	-	74-132	235/60C		Orig.-Verschr., nicht Bremse 300mm HA, ohne Radhausverbr. ✖	

Boxer (5/130)		ab Modelljahr 2014			Y	5/130	78,1	e2*2007/46*0219*... e3*2001/116*0233* ... e3*2007/46*0045*..
Sensor - Brocksens 3								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 16	Pro1	58	-	96-130	215/75C, 225/75C, 235/65C			Orig.-Verschr., ab 225/75C ✖

Porsche

Porsche	Baujahr	Typ	LK/LZ	Nabe		
Boxster	ab 05.2016	982	5/130	71,6	e13*2007/46*1607*..	
Sensor - Brocksens 2						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
Kombinationen:						
8,5 x 19	B32	VA 54	-	220	VA 235/40	Orig.-Verschr.
				220, 257	VA 235/40 M+S	
9,5 x 19		HA 46		220	HA 265/40	Orig.-Verschr.
				220, 257	HA 265/40 M+S	
8,5 x 20	B32	VA 51	-	220	VA 235/35, 245/30, 255/30	Orig.-Verschr., nur Bremse 330mm u. nicht Keramikbremse, 245/30 u. 255/30 ✖
				220, 257	VA 235/35 M+S	
9,5 x 20		HA 45		220	HA 265/35, 275/30, 275/35, 285/30	Orig.-Verschr., nur Bremse 330mm u. nicht Keramikbremse
				220, 257	HA 265/35 M+S, 275/35 M+S	

718 Boxster T		ab 02.2019				
Dimension	Design	ET	KIT	KW	Reifendimension	Info
auf Anfrage						

Cayman/CaymanS	(siehe Konfigurator)	2005-2013	987	5/130	71,6
----------------	----------------------	-----------	-----	-------	------

Cayman	(siehe Konfigurator)	ab 2013	981	5/130	71,6
--------	----------------------	---------	-----	-------	------

Cayman					982	5/130	71,6	e13*2007/46*1607*..	
Sensor - Brocksens 2									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
Kombinationen:									
8,5 x 19	B32	VA 54	-	220	VA 235/40			Orig.-Verschr.	
				220, 257	VA 235/40 M+S				
9,5 x 19		HA 46		220	HA 265/40			Orig.-Verschr.	
				220, 257	HA 265/40 M+S				
8,5 x 20	B32	VA 51	-	220	VA 235/35, 245/30, 255/30			Orig.-Verschr., nur Bremse 330mm u. nicht Keramikbremse, 245/30 u. 255/30 ✖	
				220, 257	VA 235/35 M+S				
9,5 x 20		HA 45		220	HA 265/35, 275/30, 275/35, 285/30			Orig.-Verschr., nur Bremse 330mm u. nicht Keramikbremse	
				220, 257	HA 265/35 M+S, 275/35 M+S				

Cayenne	(siehe Konfigurator)	92A	5/130	71,6	e13*2007/46*1085*..., e13*2007/46*1106*...
---------	----------------------	-----	-------	------	--

Cayenne			2018	9YA	5/130	71,5	e13*2007/46*0900*...
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
10 x 22	FMI09 CRATOS	48	-	250-324	VA 255/35+HA 285/30, VA 265/35+HA 295/30		Orig.-Verschr., mit 15mm Radhausverbreiterungen, nicht Bremse 440mm VA u. 410mm HA

Kombinationen:

8,5 x 19	B32	47	-	250-324	VA255/55+HA275/0, VA265/50+HA295/45		Orig.-Verschr., nicht Keramikbremse
9,5 x 19		54					
9 x 20	AC-M08	50	-	250-404	VA 275/45+HA 305/40		Achtung!!! Achlasten an der HA sind dringend zu überprüfen!!!! , nicht Porsche Keramikbremse
10,5x20		55					
9 x 20	B40	50	-	250-324	VA 275/45+HA 305/40		Orig.-Verschr., nicht Keramikbremse, auch E-Hybrid
10,5x20		64					
9 x 20	B41	50	-	250-404	VA 275/45+HA 305/40		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
10,5x20		64					
9 x 20	AC-M08	50					i.V., auch E-Hybrid
10,5x20		64					
9 x 20	B40	50	-	250-324	VA 275/45		Orig.-Verschr., nicht Keramikbremse, ohne Radhausverbr. HA ✖
10,5x20		55			HA 305/40		
9 x 20	B41	50	-	250-404	VA 275/45		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
10,5x20		55			HA 305/40		
9 x 20	FMI15 Zelos	50	-	250-404	VA 275/45		Orig.-Verschr.
10,5 x 20		64			HA 305/40		
9,5 x 21	B41	46	-	250-404	VA 255/40+HA 285/35, VA 255/45+HA 275/40, VA 265/40+HA 295/35, VA 275/40+HA 305/35, VA 285/40+HA 315/35		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid (mit 15mm Radhausverbreiterungen)
11 x 21		58					
9,5 x 21	B41	46	-	250-404	VA 255/40+HA 285/35, VA 255/45+HA 275/40, VA 265/40+HA 295/35, VA 275/40+HA 305/35		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid (mit 5mm Radhausverbreiterungen) , HA ab 295/35 ✖
11 x 21		58					
9,5 x 21	B43	46	-	224-404	VA 275/40M+S, 285/40		Orig.-Verschr., nicht Keramikbremse u. nicht Bremse 410mm
11 x 21		58			HA 305/35M+S, 315/35		
10 x 22	AC-M08	50	-	250-404	VA 285/35+HA 315/30		Orig.-Verschr., nicht für PSCB-Bremsen!
11,5x22		61					

10 x 22	FMI09 CRATOS	48	-	250-404	VA 275/35+HA 305/30, VA 285/35+HA 315/30		Orig.-Verschr., nicht Bremse 440mm VA u. 410mm HA, mit 15mm Radhausverbr.
11,5x22		60+61					

Cayenne Coupé	ab 10.2019	9YA	5/130	71,5	e13*2007/46*0900*...
Sensor - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
-----------	--------	----	-----	----	-----------------	------

Kombinationen:

9 x 20	AC-M08	50	-	250-404	VA 275/45+HA 305/40		Achtung!!! Achlasten an der HA sind dringend zu überprüfen!!!!, nicht Porsche Keramikbremse
10,5x20		55					
9 x 20	B40	50	-	250-324	VA 275/45+HA 305/40		Orig.-Verschr., nicht Keramikbremse, auch Hybrid
10,5x20		55					
9 x 20	B41	50	-	250-404	VA 275/45+HA 305/40		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA
10,5x20		55					
9 x 20	FMI15 Zelos	50	-	250-404	VA 275/45		Orig.-Verschr.
10,5 x 20		64			HA 305/40		
9 x 20	B41	50	-	250-404	VA 275/45		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA
10,5x20		64			HA 305/40		
9,5 x 21	B41	46	-	250-404	VA 275/40+HA 305/35 od. VA 285/40+HA 315/35		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
11 x 21		49					
9,5 x 21		46	-	250-324	VA 275/40+HA 305/35		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
11 x 21		58					
9,5 x 21	B43	46	-	224-404	VA 275/40M+S, 285/40		Orig.-Verschr., nicht Keramikbremse u. nicht Bremse 410mm
11 x 21		49			HA 305/35M+S, 315/35		
9,5 x 21	FMI09 CRATOS	46	-	250-404	VA 275/40+HA 305/35 od. VA 285/40+HA 315/35		Orig.-Verschr.
11 x 21		49					
9,5 x 21	B41	46	-	250-404	VA 275/40+HA 305/35, VA 285/35+HA 325/30, VA 285/40+HA 315/35		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
11 x 21		58					
10 x 21	AC-M08	50					i.V.
11,5x21		52					
10 x 22	FMI09 CRATOS	48	-	250-404	VA 285/35+HA 315/30		Orig.-Verschr.
11,5x22		52					
10 x 22		48	-	250-404	VA 275/35+HA 305/30, VA 285/35+HA 315/30		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, auch E-Hybrid
11,5x22		60					
10 x 22	AC-M08	50	-	250-404	VA 285/35+HA 315/30		Orig.-Verschr., nicht für PSCB-Bremsen!
11,5x22		52					

Cayenne ^{NEU}	Modelljahr 2023	9YA	5/130	71,5	ab Nachtrag *13
Sensor - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
9 x 20	B41	VA 50	-	224-349	VA 255/55+HA 295/45, VA 255/50+HA 305/40, VA 255/55+HA 305/45	 Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, mit 5mm Radhausverbreiterungen im Bereich Radmitte
10,5 x 20		HA 64				
9 x 20	FMI15 Zelos	VA 50	-	250-404	VA 255/55	 Orig.-Verschr.
10,5 x 20		HA 64			HA 295/45	
9,5 x 21	B41	VA 46	-	224-349	VA 285/45	 Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA
11 x 21		HA 58			HA 315/40	
10 x 23	STC-23	VA 45	-	224-441	VA 285/35+HA 325/30	Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, bei HA ✖
11,5 x 23		HA 51				

Cayenne e-Hybrid ^{NEU}	4. Quartal 2023	9YA	5/130	71,5	e13*2007/46*0900*..
Sensor - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
9 x 20	B41	VA 50	-	224-349	VA 255/55+HA 295/45, VA 255/50+HA 305/40, VA 255/55+HA 305/45		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, mit 5mm Radhausverbreiterungen im Bereich Radmitte
10,5 x 20		HA 64					
9 x 20	FMI15 Zelos	VA 50	-	250-404	VA 255/55		Orig.-Verschr.
10,5 x 20		HA 64			HA 295/45		
9,5 x 21	B41	VA 46	-	224-349	VA 285/45		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA
11 x 21		HA 58			HA 315/40		
10 x 23	STC-23	VA 45	-	224-441	VA 285/35+HA 325/30		Orig.-Verschr., nicht Porsche Keramikbremse mit 440mm VA u. 410mm HA, bei HA ✖
11,5 x 23		HA 51					

Macan (siehe Konfigurator)	ab 2014	95B, 95BN	5/112	66,6	e13*2007/46*1164*02-09, e13*2007/46*1165*02-09
----------------------------	---------	-----------	-------	------	--

Macan	ab MJ2019	95B	5/112	66,6	e13*2007/46*1165*10-..
Sensor - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC32	VA 21	-	155-260	VA 235/60+HA 255/55, VA 235/60+HA 275/50, VA 245/60 + HA 265/55, VA 255/55+HA 275/50		Orig.-Verschr.; nicht für Keramikbremse mit 396x38mm, nicht 6-Kolben-Festsattel
9 x 18		HA 21					
9 x 19	B41	21	ZP559F	180-324	255/50		
8,5 x 19	RC34	VA 21	-	155-324	VA 235/55+HA 255/50		Orig.-Verschr., nicht Bremse 396x38mm
9 x 19		HA 21					

8,5 x 19	B41	VA 21	ZP559F	180-324	VA 235/55+HA 255/50		
9 x 19		HA 21					
9 x 20	B43	VA 26	ZP568F	180-280	VA 265/45+HA 295/40		nicht Bremse 390mm u. nicht Keramikbremse
10 x 20		HA 19					
9 x 20	AC-MB6	VA 25	-	180-280	VA 235/45+HA 265/40, VA 245/45+HA 275/40		Orig.-Verschr., nicht Bremse 390mm u. nicht Keramikbremse
10 x 20		HA 18					
9 x 20	B43	VA+HA 20	ZP568F	180-280	VA 235/45+HA 265/40, VA 245/45+HA 275/40		nicht Bremse 390mm u. nicht Keramikbremse
	AC-522	20	-	155-324	VA245/45+HA275/40		Orig.-Verschr., nicht Keramikbremse
	FMI11 Elatha	20	F95	155-324	VA235/45+HA265/40, VA245/45+HA275/40		nicht Porsche Keramikbremse mit 396x38mm, 6-Kolben Festsattel
	Oxigin 28	20	ZP568F	180-280	VA235/45+HA265/40, VA245/45+HA275/40		nicht Bremse 390mm u. nicht Keramikbremse
9,5 x 20	B37C	VA+ HA 22	-	180, 260	VA 255/45+HA 285/40		Orig.-Verschr., nicht Bremse 390mm u. nicht Keramikbremse
	CA 19	25	ZP568F	155-324	VA 255/45+HA 285/40		Orig.-Verschr., nicht Keramikbremse
9,5 x 21	B41	VA 27	ZP568F	180-324	VA 265/40+HA 295/35		nicht Porsche Keramikbremse mit 396x38mm
10 x 21		HA 19					
9,5 x 21	B43	VA 27	ZP568F	180-280	VA 265/40+HA 295/35		nicht Bremse 390mm u. nicht Keramikbremse
10 x 21		HA 19					
9,5 x 21	B43	VA 27	ZP568F	180-280	VA 245/40, 255/40, 265/40		nicht Bremse 390mm u. nicht Keramikbremse, HA ab 285/35 ✖
10 x 21		HA 19			HA 275/35, 285/35, 295/35		
9,5 x 21	AF18	20	-	180-280	VA 245/40+HA 275/35 od. VA 255/40+HA 285/35		Orig.-Verschr., nicht Keramikbremse u. nicht Bremse 390mm

Kombinationen:

8 x 19	B40	21	-	180, 260	VA 235/55+HA 255/50, VA 235/55+HA 285/45, VA 245/50+HA 275/45, VA 255/50+HA 285/45		Orig.-Verschr., nicht für Keramikbremse u. nicht Bremse 390mm
9 x 19		21					
8,5 x 19	B32	25	-	180, 260	VA 235/55, 245/50, 255/50		Orig.-Verschr., nicht für Keramikbremse u. nicht Bremse 390mm
9,5 x 19		22			HA 255/50, 275/45, 285/45, 295/45		
8,5 x 20	B32	26	-	180, 260	VA 235/45+HA 265/40, VA 245/45+HA 275/40, VA 255/45+HA 285/40		Orig.-Verschr., nicht für Keramikbremse u. nicht Bremse 390mm
9,5 x 20		22					
9 x 20	AC-M08	26	-	155-324	VA 255/45+HA 285/40 od. VA 265/45+HA 295/40		Orig.-Verschr., nicht Keramikbremse, HA ohne Radhausverbr. ✖
10 x 20		19					
9,5 x 20	B40	22	-	180-280	VA 255/45, 265/45		Orig.-Verschr., nicht für Keramikbremse u. nicht Bremse 390mm, HA ✖
10,5x20		18			HA 285/40, 295/40		
9,5 x 21	AC-M08	27	-	155-324	VA 255/40+HA 285/35		Orig.-Verschr., nicht Keramikbremse, HA ✖
10 x 21		19					
9 x 22	AF18	VA 25	-	180, 260	VA 265/35		Orig.-Verschr., nicht Bremse 390mm u. nicht Keramikbremse, HA ✖
10 x 22		HA 20			HA 295/30		
9,5 x 22	B41	21	ZP568F	155-324	VA 255/35		nicht Keramikbremse mit 396x38mm, 6-Kolben Festsattel
10,5 x 22		19			HA 285/30, 295/30		

Macan electric NEU		2024		XA	5/130	66,5	e13*2018/858*00462*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 20	RC36	VA 32	-	120, 145	VA 235/55		Orig.-Verschr., nur Bremse max. 350mm	
10 x 20		HA 49			HA 285/45			
7,5 x 20	B43	VA 32	-	120, 145	VA 235/55		Orig.-Verschr., nur Bremse max. 350mm	
10 x 20		HA 49			HA 285/45			

Panamera (siehe Konfigurator)	970	5/130	71,6
-------------------------------	-----	-------	------

Panamera		ab 2016	971	5/130	71,6	e13*2007/46*0971*..	
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
Kombinationen:							
9 x 19	B40	64	-	310, 324	VA 265/45		Orig.-Verschr., nicht für Keramikbremse u. nur Bremse 360mm
10,5x19		62			HA 295/40		
9,5 x 20	B40	71	-	310-338	VA 265/40, 275/40		Orig.-Verschr., nicht für Keramikbremse
10,5x20		71			HA 295/35, 305/35, 315/35		
9,5 x 21	AC-M08	71	-	243-463	VA 275/35+HA 315/30		Orig.-Verschr.
11,5x21		69					
10 x 22	FMI09 CRATOS	65	-	243-353	VA 265/30+HA 315/25		Orig.-Verschr., VA ✖
11,5x22		60					

Panamera 4 E-Hybrid		ab 2017	971	5/130	71,6	e13*2007/46*0971*..	
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9 x 19	B40	64	-	243	VA 265/45		Orig.-Verschr., nicht für Keramikbremse
10,5x19		62			HA 295/40		
9,5 x 20	B40	71	-	243	VA 265/40, 275/40		Orig.-Verschr., nicht für Keramikbremse
10,5x20		71			HA 295/35, 305/35, 315/35		

9,5 x 21	AC-M08	71	-	243-463	VA 275/35+HA 315/30		Orig.-Verschr.
11,5x21		69					

Panamera 4, 4S Sport Turismo				ab 2017	971	5/130	71,6	e13*2007/46*0971*..	
Sensor - Brocksens 2									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
9 x 19	B40	64	-	243, 324	VA 265/45+HA 295/40		Orig.-Verschr., nicht für Keramikbremse u. nur Bremse 360mm		
10,5x19		62							
9,5 x 20	B40	71	-	243-338	VA 265/40, 275/40		Orig.-Verschr., nicht für Keramikbremse		
10,5x20		71			HA 295/35, 305/35, 315/35				
9,5 x 20	AC-M08	71	-	243-404	VA 275/40+HA 315/35		Orig.-Verschr.		
11,5x20		68							
9,5 x 21	AC-M08	71	-	243-463	VA 275/35+HA 315/30		Orig.-Verschr.		
11,5x21		69							

Panamera	NEU i.V.	ab 2024	YA	5/130	71,6	e13*2018/858*00425*..
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321						
Für dieses Fahrzeug gibt es lt. Thorsten im Moment KEINE Räder - noch KEIN Anbau vorhanden - Stand: 14.10.2024						

Taycan NEU		Y1A		5/130		71,6		e13*2007/46*0919*...	
Sensor - Brocksens 2									
Dimension		Design	ET	KIT	KW	Reifendimension		Info	
<u>Kombinationen:</u>									
9 x 20		B40	50	-	113-140	VA 235/45+HA 275/40 od. VA 245/40+HA 285/35 od. VA 255/40+HA 295/35		Orig.-Verschr.; nicht Bremse 360x36 6-Kolben oder Ceramic Bremse	
10,5x20			55						
9 x 20		B41	50	-	113-140	VA 235/45+HA 275/40 od. VA 245/40+HA 285/35 od. VA 245/45+HA 285/40 od. VA 255/40+HA 295/35		Orig.-Verschr.; nicht Bremse 360x36 6-Kolben oder Ceramic Bremse	
10,5x20			55						
10 x 22		FMI09 CRATOS	48	-	113-142	VA 255/35+HA 305/30		Orig.-Verschr.; nicht Bremse 360x36mm VA u. 358x28mm HA	
11,5 x 22			52						

Taycan Cross Turismo NEU						e13*2007/46*0919*...	
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
Kombinationen:							
10 x 22	FMI09 CRATOS	48	-	140-142	VA 255/35+HA 305/30		Orig.-Verschr.; nicht Bremse 360x36mm VA u. 358x28mm HA
11,5 x 22		52					

Taycan GTS Sport Turismo NEU i.V.		1. Quartal 2022	Y1A	5/130	71,6		
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

911 (siehe Konfigurator)	997	5/130	71,6				
--------------------------	-----	-------	------	--	--	--	--

911 (siehe Konfigurator)	991	5/130	71,6				
--------------------------	-----	-------	------	--	--	--	--

911 Turbo		ab 02.16		991 Turbo		5/130		71,6		e13*2007/46*1188*00-03	
Sensor - Brocksens 2											
Dimension		Design		ET	KIT	KW	Reifendimension			Info	
8,5 x 20		B32		VA 51	-	383, 412	VA 245/35			Orig.-Verschr., auch mit Keramikbremse	
11 x 20				HA 57			HA 295/30M+S, 305/30				

911		ab 2019		992	5/130	71,6	e13*2007/46*0992*..	
Sensor - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
8,5 x 19	B32	VA 52	-	331	VA 235/40 M+S		Orig.-Verschr., nicht Keramikbremse	
11 x 20		HA 66			HA 295/35 M+S			

911 Safari		im Laufe 2022					
Dimension	Design	ET	KIT	KW	Reifendimension		Info
auf Anfrage							

911 GT3 RS		3. Quartal 2022					
Dimension	Design	ET	KIT	KW	Reifendimension		Info
auf Anfrage							

Renault

		Baujahr	Typ	LK/LZ	Nabe		
Renault 5 E-Tech		NEU	Oktober 2024	P01	5/114,3	66,1	e2*2018/858*00093*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 18	RC34	38	-	70-78	195/55		 Orig.-Verschr.
	RE7	38	-	78 (110)	195/55		 Orig.-Verschr.
7 x 18	RC32	35	-	70-78	195/50		Orig.-Verschr.

Alaskan		ab 06.2017	D231C	6/114,3	66,1	e9*2007/46*6515*..	
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC14-6S	40	ZP610F	120	225/65, 245/60		Fahrzeuge mit Serienreifen 205/...
				120-140	255/65		Fahrzeuge mit Serienreifen 255/....
8 x 18	RC31	45	ZP610F	120-140	255/60		
	8400 Bluster	42	-	120-140	255/60		Orig.-Verschr., nur Allrad, mit Serie 255/...
				120	225/60, 235/55, 245/55, 255/55, 255/55C		Orig.-Verschr., nur Allrad, mit Serie 205/...
9 x 20	Oxigin 24	25	ZP610F	120-140	255/45, 265/40, 265/45, 265/50, 275/40, 275/45, 285/45		✖

Arkana		NEU	im Laufe 2. Quartal 2021		RJL	5/114,3	66,1	e6*2018/858*00003*..	
direkt Brocksens 3 - teilweise indirekt									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC32	35	-	69-116	215/60, 225/55, 235/55				Orig.-Verschr., auch Hybrid, Ausführung N42
	RC34	35	-	69-116	215/60, 225/55, 235/55				Orig.-Verschr., auch Hybrid, Ausführung N42
	RC27	35	-	69-116	215/60, 225/55				Orig.-Verschr., Ausführung N13
7,5 x 17	RC28	35	ZP578	69-116	215/60				
7 x 18	RC27	35	-	69-116	215/50, 215/55, 225/50				Orig.-Verschr., Ausführung N16
	RC32	35	-	69-116	215/55, 225/50				Orig.-Verschr., auch Hybrid
	RC34	35	-	69-116	215/55, 225/50				Orig.-Verschr., auch Hybrid
	RC27	34	-	69-116	215/50, 215/55, 225/50				Orig.-Verschr.
7,5 x 18	RC30	35	ZP578	69-116	215/50, 215/55				
	B32	35	ZP578	69-116	215/50, 215/55				
	B39	35	ZP578	69-116	215/50, 215/55				
	AC-MB6 / AC-M10	35	Artikel Nr. 98495	69-116	215/50, 215/55				Kit mit Artikelnummer 98495
	AC-521	35	Artikel Nr. 98495	69-116	215/50, 215/55				Kit mit Artikelnummer 98495
	B38	35	ZP578	69, 103	215/55				
7,5 x 19	RC34	35	-	69-116	225/45, 235/45				Orig.-Verschr.
	AC-521	35	Artikel Nr. 98495	69-116	215/50, 225/45, 235/45				Kit mit Artikelnummer 98495
8 x 19	B40	35	ZP578	69-116	225/45, 235/45				
8,5 x 19	B32 / B42	35	ZP578	69-116	225/45				
8 x 20	RC36	35	-	69-116	225/40				Orig.-Verschr.
	B40	35	ZP578	69, 103	225/40				
8,5 x 20	RC29	35	ZP578	69-116	225/40				
	B42	35	ZP578	69-116	225/40				

Austral		NEU	ab Oktober 2022		RHN	5x114,3	66,1	e9*2018/858*0002*...		
Sensor - Brocksens 4										
Dimension		Design	ET	KIT	KW	Reifendimension		Info		
7 x 17		RC27	35	- (N13)	96-116	215/65			Orig.-Verschr., Ausführung N13	
		RC32	35	- (N42)	96-116	215/65, 225/60, 225/65, 235/60, 245/55			Orig.-Verschr., Ausführung N42	
		RC34	35	- (N42)	96-116	215/65, 225/60, 225/65, 235/60, 245/55			Orig.-Verschr., Ausführung N42	
		RC27	38	ZP581	96-116	215/65, 225/60, 235/60, 245/55				
		RC34	43	- (N42)	96-116	235/60, 245/55, 255/55			Orig.-Verschr., Ausführung N42	
		B39	38	ZP581	96-116	215/65, 225/60, 235/60, 245/55				
		AC-V51	45	-	96-116	215/65, 225/60, 235/60, 245/55			Orig.-Verschr.	
		Pro1	45	-	96-116	235/60, 245/55, 255/55			Orig.-Verschr.	
7,5 x 17		RC24	38	ZP581	96-116	215/65, 225/60, 235/60			Orig.-Verschr., nicht Bremse 350x30mm	
		RC28	35	ZP581	96-116	215/65, 225/60				
		B24	38	ZP581	96-116	215/65, 225/60, 235/60				
		RC27	34	-	96-116	205/60, 215/60, 225/55, 235/55			Orig.-Verschr.	
7 x 18		RC32	35	- (N42)	96-116	215/60, 225/55, 235/55, 245/50			Orig.-Verschr., Ausführung N42	
		RC34	35	-	96-116	215/60, 225/55, 235/55, 245/50			Orig.-Verschr., ohne 4-Control Hinterachslenkung, Ausführung N42	
	96				215/60, 225/55, 235/55			Orig.-Verschr., mit 4-Control Hinterachslenkung, Ausführung N42		
		RC34	45	- (N42)	96-116	235/55			Orig.-Verschr., Ausführung N42	
96-116	225/55, 235/55, 245/50					Orig.-Verschr., ohne 4-Control Hinterachslenkung, Verbundlenkerachse				
96	225/55, 235/55, 245/50					Orig.-Verschr., mit 4-Control Hinterachslenkung, Mehrlenkerachse				

7,5 x 18		45	ZP568F	96	235/55		Ausführung N42, 4-Control
			- (N43)	96-116	235/55		Orig.-Verschr., Felge ist nur in KS u. SG erhältlich! Ausführung N43 - diese passt mit Gewinde 12x1,5 u. 14x1,5
	AC-MB6 / AC-M10	45	Artikel Nr. 98482	96-116	215/60, 225/55, 235/55, 245/50		Kit mit Artikelnummer 98482
	AC-V51	38	-	96-116	235/55		Orig.-Verschr.
	Oxigin 25	45	ZP581	96-116	235/50, 235/55		Felge passt mit Gewinde 12x1,5 u. 14x1,5, mit Radhausverbreiterung
	B32	35	ZP581	96-116	205/60, 215/60, 225/55		
8 x 18	B24	38	ZP581	96-116	225/55		
	B36	35	ZP581	96-116	225/55		
	B42	40+45	ZP581	96-116	225/55, 235/55		
	B44	40+45	ZP581	96-116	225/55, 235/55		
	AC-M10	45	ZP578D2F +R	96-116	225/55, 235/55		+ Red.Ringe 73,1-66,1
	CA 20	45	ZP581	96-116	225/55, 235/55		
7 x 19	CA 24	45	ZP581	96-116	225/55		
	RC34	32	- (N43)	96-116	205/55		Orig.-Verschr., Felge ist nur in SGVP erhältlich! Ausführung N43 - diese passt mit Gewinde 12x1,5 u. 14x1,5
7,5 x 19	RC27	40	- (N7)	69-116	215/50, 225/50, 235/50		Orig.-Verschr., Ausführung N7
	RC34	35+40	-	96-116	205/55, 215/50, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr., ohne 4-Control Hinterachslenkung, Verbundlenkerachse
		46	-	96-116	215/50, 225/50, 235/45, 245/45		Orig.-Verschr.
	CA 26	45	ZP581	96-116	215/50, 225/50, 235/50, 245/45		
8 x 19	RC29	38	ZP581	96-116	225/50, 245/45		
	CA 17	40	ZP581	96-116	235/45		
	CA 19	45	ZP581	96-116	225/50, 235/50, 245/45, 255/45		
	CA 24	45	ZP581	96-116	225/50, 245/45		Felge passt mit Gewinde 12x1,5 u. 14x1,5
	FMI08 Thoe Oxigin 29	40	-	96-116	225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
8,5 x 19	B32	45	ZP581	96-116	225/50, 235/50, 245/45, 255/45		
			ZP581	96-116	245/45		
	B36	38	ZP561F+R	96	245/45		+ Red.Ringe 72,6-66,1, 4Control - mit Allradlenkung
	B44	40	ZP581	96-116	245/45		
	CA 23	40	ZP581	96-116	245/45		
8 x 20	RC36	40	-	96-116	215/45, 235/45, 245/40		Orig.-Verschr., Ausführung N43
	B43	40	-	96-116	215/45, 235/45, 245/40		Orig.-Verschr., Ausführung N43
	FMI08 Thoe	40	-	96-116	235/45		Orig.-Verschr.
	RC36	35	-	96-116	215/45, 235/45, 245/40		Orig.-Verschr.
				96	215/45, 235/45, 245/40		Orig.-Verschr., mit Allradlenkung
	B38	35+45	ZP581	96-116	215/45, 235/45, 245/40		
8,5 x 20	B40	35	ZP581	96-116	215/45, 235/45, 245/40		
			ZP561F+R	96	215/45, 235/45, 245/40		+ Red.Ringe 72,6-66,1, 4Control - mit Allradlenkung
	RC36	37	-	96-116	235/45		Orig.-Verschr.
				96	235/45		Orig.-Verschr., mit Allradlenkung
9 x 20	B44	40	ZP581	96-116	235/45, 245/40		
	CA 20 / CA 23	45	ZP581	96-116	235/45, 245/40		
	Oxigin 28	40	ZP581	96-116	235/45, 245/40		

Captur (siehe Konfigurator)	ab 07.2013	R	4/100	60,1	e2*2001/116*0327*52-...
-----------------------------	------------	---	-------	------	-------------------------

Captur	ab 2019	RJB	5/114,3	66,1	e2*2007/46*0684*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	32	-	70-113	215/65, 225/60, 225/65, 235/60	 Orig.-Verschr.
	RC34	32	-	67-116	215/65, 225/60, 225/65, 235/60	 Orig.-Verschr.
6,5 x 17	RC27	32	-	67-116	215/60, 225/55, 235/55	Orig.-Verschr.
7 x 17	RC27	35	-	67-116	215/60, 225/55	 Orig.-Verschr., Ausführung N13
	RC32	35	-	67-116	215/60, 225/55, 235/55	 Orig.-Verschr., auch für Hybrid
	RC34	35	-	67-116	215/60, 225/55, 235/55	 Orig.-Verschr., auch für Hybrid
7,5 x 17	RC28	35	ZP581	67-116	215/60	
7 x 18	RC27	35	-	67-116	215/50, 215/55, 225/50	 Orig.-Verschr., Ausführung N16
	RC32	35	-	67-113	215/55, 225/50, 235/50	 Orig.-Verschr.
	RC34	35	-	67-116	215/55, 225/50, 235/50	 Orig.-Verschr.
	RC27	34	-	67-116	215/50, 215/55, 225/50	Orig.-Verschr.
	RC30	35	ZP581	67-113	215/50, 215/55	
	B32	35	ZP581	70-113	215/50, 215/55	
	B39	35	ZP581	67-113	215/50, 215/55	

7,5 x 18	AC-MB6 / AC-M10	35	Artikel Nr. 98478	67-116	215/50, 215/55		Kit mit Artikelnummer 98478
	AC-521	35	Artikel Nr. 98478	67-113	215/50, 215/55		Kit mit Artikelnummer 98478
7,5 x 19	RC34	35	-	67-116	215/50, 225/45 , 235/45		Orig.-Verschr.
	AC-521	35	Artikel Nr. 98478	67-113	225/45, 235/45		Kit mit Artikelnummer 98478
8 x 19	B40	35	ZP581	67-116	225/45		
8,5 x 19	Oxigin 25	35	ZP581	70-113	225/45		
8 x 20	RC36	35	-	67-116	225/40		Orig.-Verschr.
	B38	35	ZP581	67-116	225/40		
	B40	35	ZP581	67-116	225/40		

Captur E-Tech (II) NEU ab 2020 RJB 5/114,3 66,1 e2*2007/46*0684*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	RC27	35	- (N13)	68	215/60		Orig.-Verschr., Plug-in-Hybrid, Ausführung N13
	RC32	35	- (N42)	68-69	215/60, 225/55, 235/55, 245/50		Orig.-Verschr., Plug-in-Hybrid, Ausführung N42
	RC34	35	- (N42)	68-69	215/60, 225/55, 235/55, 245/50		Orig.-Verschr., Plug-in-Hybrid, Ausführung N42
7 x 18	RC27	35	- (N16)	68	215/50, 215/55		Orig.-Verschr., Plug-in-Hybrid, Ausführung N16
	RC34	35	-	68-69	215/55, 225/50, 235/50		Orig.-Verschr.
	RC32	35	- (N42)	68-69	215/55, 225/50, 235/50		Orig.-Verschr., Plug-in-Hybrid, Ausführung N42
	RC27	34	-	68	215/50, 215/55		Orig.-Verschr., Plug-in-Hybrid
8 x 18	B42	30	ZP581	68	215/55		
	B44	30	ZP581	68	215/55		
7,5 x 19	RC34	35	-	69 68-69	225/45, 235/45	 	Orig.-Verschr., Plug-in-Hybrid
	AC-521	35	ZP590F+R	68	225/45		+ Red.Ringe 73,1-66,1 , Plug-in-Hybrid
8,5 x 19	B44	30	ZP581	68	225/45		
	CA 20	30	ZP581	68	225/45		
	Oxigin 28	30	ZP581	68	225/45		
8,5 x 20	B44	30	ZP581	68	225/40		

Clio IV (siehe Konfigurator) ab 11.12 R 4/100 60,1 e2*2001/116*0327*46-..., e2*2007/46*0008*16-...							
---	--	--	--	--	--	--	--

Clio IV R.S. (siehe Konfigurator) ab 2013 R 5/114,3 66,1 e2*2001/116*0327*51-...							
---	--	--	--	--	--	--	--

Clio V ab 2019 RJA 4/100 60,1 e2*2007/46*0676*...							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	31	-	48-96	185/60, 185/65		Orig.-Verschr.
		37	ZP440F	48-96	185/60, 185/65, 195/60		mit Trommelbremse an HA, nicht Bremse 280mm
6,5 x 16	RC30	37	-	48-103	185/55, 185/60, 195/50, 195/55		Orig.-Verschr., incl. Facelift 2023, auch Hybrid
	RC34	37	-	48-103	185/55, 195/55 , 205/50, 215/50		Orig.-Verschr., auch Hybrid
	RC24 / RC30	38	ZP440	48-96	185/55, 185/60, 195/50, 195/55		
7 x 17	RC34	37	-	48-103	205/45		Orig.-Verschr.
	B39	37					i.V.
	B24	38	ZP440	48-103	195/45, 205/45		incl. Facelift 2023
	B39	38	ZP440	48-103	195/45, 205/45		incl. Facelift 2023

Espace V 2015 RFC 5/114,3 66,1 e2*2007/46*0470*...							
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	

7 x 17	RC27	35	-	96-165	235/65		Orig.-Verschr.
		40	-	96-165	235/65, 255/60		Orig.-Verschr.
		38	ZP577	96-165	235/65, 255/60		
		45	ZP577	96-165	235/65		
	RC30	45	ZP577	96-165	235/65		
	RC32	40+43	-	96-165	235/65, 245/60, 245/65, 255/60		Orig.-Verschr.
	RC34	35	-	96-165	235/65		Orig.-Verschr.
		43	- (N42)	96-165	235/65, 245/60, 245/65, 255/60		Orig.-Verschr., Ausführung N42
	B39	38+45	ZP577	96-165	235/65, 255/60		ET45 nicht 255/60
7,5 x 17	AC-V51	45	ZP567F	96-165	235/65		
	Pro1	45	-	96-165	235/65, 245/60, 245/65, 255/60		Orig.-Verschr.
	RC24	38	ZP577	96-165	235/65, 255/60		ab 255/60 ✖
		45	ZP577	96-165	235/65		
	RC28	35+45	ZP577	96-165	235/65		
	RC29	38	ZP577	96-165	235/65, 255/60		ab 255/60 ✖
	B24	38	ZP577	96-165	235/65		
	B36	38	ZP577	96-165	235/65, 255/60		ab 255/60 ✖
	AC-518	40	ZP561F+R	96-165	235/65		+ Red.Ringe 73,1-66,1
	Oxigin 19	38	ZP577	96-147	235/65		
7 x 18	RC27	34	-	96-165	235/60		Orig.-Verschr.
	RC32	40+45	-	96-165	235/60, 245/55, 255/55		Orig.-Verschr.

	RC34	35	-	96-165	235/60		Orig.-Verschr.
7,5 x 18	RC30	45	ZP577	96-165	235/60		
	RC32	46	-	96-165	235/60, 245/55, 255/55		Orig.-Verschr.
	B32	35+45	ZP577	96-165	235/60		
	B39	35+45	ZP577	96-165	235/60		
	AC-MB6 / M10	35+45	Artikel Nr. 98486	96-165	235/60		Kit mit Artikelnummer 98486
	AC-521	35+45	AV4+R	96-165	235/60		+ Red.Ringe 73,1-66,1
	AC-V51	38	ZP567F	96-165	235/60		
8 x 18	RC29	35	ZP577	96-165	235/60		
		45	ZP577	96-165	235/60		
	RC32	48	-	96-165	235/60, 245/55		Orig.-Verschr.
	B24	38	ZP577	96-165	235/60		
	B36	35+45	ZP577	96-147	235/60		
	B37	45	ZP577	96-147	235/60, 245/55		
	B38	45	ZP577	96-165	235/60		
	B42	40+45	ZP577	96-165	235/60		
	B44	40+45	ZP577	96-165	235/60		
	AC-518	40	AV4+R	96-165	235/60		+ Red.Ringe 73,1-66,1
7 x 19	AC-M10	45	AV4+R	96-165	235/60		+ Red.Ringe 73,1-66,1
7,5 x 19	RC34	40	-	96-165	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	RC34	35	-	96-165	235/50, 235/55		Orig.-Verschr.
		40	-	96-165	235/50, 235/55, 245/50		Orig.-Verschr.
		46	-	96-165	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
	B32	40	ZP577	96-165	235/50, 235/55, 245/50, 255/50		ab 255/50 ✖
	B39	40	ZP577	96-165	235/50, 235/55, 245/50, 255/50		ab 255/50 ✖
		45	ZP577	96-165	235/50, 235/55, 245/50		
	AC-521	35	AV4+R	96-165	235/50, 235/55		+ Red.Ringe 73,1-66,1
		45	AV4+R	96-165	235/50, 235/55, 245/50		+ Red.Ringe 73,1-66,1
	CA 26	45	ZP577	96-165	235/50, 235/55, 245/50		
8 x 19	Oxigin 18	40	ZP577	96-147	235/55		
	RC27	42	-	96-165	235/55		Orig.-Verschr.
	RC29	38+48	ZP577	96-165	235/50, 235/55		
	B24	38	ZP577	96-165	235/50, 235/55		
	B38	45	ZP577	96-165	235/50, 235/55, 245/50		
	B40	35	ZP577	96-165	235/50, 235/55		
	AC-518	40	AV4+R	96-165	235/50, 235/55, 245/50		+ Red.Ringe 73,1-66,1
	CA 17	40	ZP577	96-165	235/55		
	CA 19	45	ZP577	96-165	235/50, 235/55, 245/50		
	FMI08 Thoe	40	-	96-165	235/50, 235/55		Orig.-Verschr.
8,5 x 19	Oxigin 29	40	ZP577	96-165	235/50, 235/55, 245/50		
	B44	40	ZP577	96-165	235/50, 235/55		
	CA 26	46	ZP577	96-165	235/50, 235/55		
8 x 20	RC36	40	-	96-165	235/45, 245/45, 255/45		Orig.-Verschr., Ausführung N43
		35	-	96-165	235/45, 245/45, 255/45		Orig.-Verschr., Ausführung N12
	B38	35+45	ZP577	96-165	235/45, 245/45, 255/45		
	B40	35	ZP577	96-165	235/45, 245/45, 255/45		
	B43	40	-	96-165	235/45, 245/45, 255/45		Orig.-Verschr., Ausführung N42 u. N43
		45	-	96-165	235/45, 245/45, 255/45		Orig.-Verschr.
8,5 x 20	RC29	40+45	ZP577	96-165	235/45, 245/45, 255/45		
	RC36	37	-	96-165	235/45, 245/45, 255/45		Orig.-Verschr.
	B24	35	ZP577	96-165	235/45, 245/45		
		42	ZP577	96-165	235/45, 245/45, 255/45, 265/45		
	B32	40	ZP577	96-165	235/45, 245/45, 255/45		
	B42	35	ZP577	96-165	235/45, 245/45		
		45	ZP577	96-165	235/45, 245/45, 255/45		
	B44	30	ZP577	96-165	235/45		
		40	ZP577	96-165	235/45, 245/45, 255/45		
	AC-518	40	AV4+R	96-165	235/45, 245/45, 255/45		+ Red.Ringe 73,1-66,1
9 x 20	CA 23	45	ZP577	96-165	235/45, 245/45		
8,5 x 21	B41	47	ZP577	96-165	245/40		

Espace VI 4Control NEU		4. Quartal 2023			RHN	5/114,3	66,1	e9*2018/858*30002*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 19	RC34	35	-	96	215/50, 235/45				Orig.-Verschr.
8 x 20	RC36	40	-	96	235/45				Orig.-Verschr., Ausführung N43
	B43	40	-	96	235/45				Orig.-Verschr., mit Allradlenkung, Ausführung N43
	FMI08 Thoe	40	-	96	235/45				Orig.-Verschr.
	RC36	35	-	96	235/45				Orig.-Verschr., mit Allradlenkung, Ausf. N12
8,5 x 20	RC36	37	-	96	235/45				Orig.-Verschr., mit Allradlenkung
	B44	40	ZP577	96	235/45				mit Allradlenkung

Kadjar		ab 2015		RFE	5/114,3	66,1	e2*2007/46*0475*...	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC27	40	-	81-120	215/65, 225/60, 225/65, 235/60			Orig.-Verschr., nur 2WD
	RC32	40	-	81-120	215/65, 225/60, 235/60			
	RC34	40	-	81-120	215/65, 225/60, 235/60			Orig.-Verschr., Ausführung "N42"
	RC24	38	ZP581	81-120	215/65, 225/60, 225/65, 235/60			2WD
	RC27	32	-	81-120	215/65, 225/60, 225/65			Orig.-Verschr., nur 2WD
		38	ZP581	81-120	215/65, 225/60, 225/65, 235/60			2WD
	RC30	38	ZP581	81-120	215/65, 225/60, 225/65, 235/60			2WD
	RC34	32	-	81-120	215/65, 225/60			Orig.-Verschr.
7 x 16	RC28	35	ZP581	81, 96	215/65, 225/60, 225/65, 235/60			2WD, bei 235/60 ✖
6,5 x 17	RC27	32	-	81-120	215/60, 225/55			Orig.-Verschr., nur 2WD
7 x 17	RC27	40	-	81-120	215/60, 225/55			Orig.-Verschr.
	RC32	40	-	81-120	215/55, 215/60, 225/55, 235/50, 235/55			Orig.-Verschr.
	RC34	40	-	81-120	215/60			Orig.-Verschr.
	RC27	35	-	81-120	215/60, 225/55			Orig.-Verschr.
		38	ZP581	81-120	215/60, 225/55			
	RC32	35	-	81-120	215/55, 215/60, 225/55			Orig.-Verschr.
	RC34	35	-	81-120	215/55, 215/60, 225/55			Orig.-Verschr.
7,5 x 17	B39	38	ZP581	81-120	215/60, 225/55			
	AC-521	35	ZP590F+R	81-120	215/60, 225/55			+ Red.Ringe 73,1-66,1
	RC24	38	ZP581	81-120	215/60, 225/55			
	RC28	35	ZP581	81-120	215/60, 225/55			
	RC29	38	ZP581	81-120	215/60, 225/55			
	B36	38	ZP581	81-120	215/60, 225/55			
	AC-518	40	ZP590F+R	81-120	215/60			+ Red.Ringe 73,1-66,1
	Oxigin 19	38	ZP581	81-96	215/55, 215/60, 225/55			
7 x 18	RC27	40	-	81-120	215/50, 215/55, 225/50			Orig.-Verschr.
	RC32	40	-	81-120	215/50, 215/55, 225/50, 235/50			Orig.-Verschr.
	RC27	34	-	81-120	215/50, 215/55, 225/50			Orig.-Verschr.
	RC32	35	-	81-120	215/50, 215/55, 225/50			Orig.-Verschr.
	RC34	35	-	81-120	215/50, 215/55, 225/50			Orig.-Verschr., Ausführung "N42"
7,5 x 18	RC30	35	ZP581	81, 96	215/50, 215/55, 225/50, 235/45, 245/45			
	B32	35	ZP581	81-120	215/50, 215/55, 225/50, 235/45, 245/45			
	B39	35	ZP581	81-120	215/50, 215/55, 225/50, 235/45, 245/45			
	AC-521	35	ZP590F+R	81-120	215/50, 215/55, 225/50, 235/45, 245/45			+ Red.Ringe 73,1-66,1
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	81-120	215/50, 215/55, 225/50, 235/45, 245/45			Kit mit Artikelnummer 98478
	AC-V51	38	-	81-120	245/45			Orig.-Verschr.
	Oxigin 18	35	ZP581	81-120	215/50, 225/50, 235/45, 245/45			
8 x 18	B42	40	ZP581	81-120	215/55, 235/45			
	B44	40	ZP581	81-120	215/55, 235/45			
7 x 19	RC27	40	-	81-120	225/45			Orig.-Verschr., Ausführung N7 - alle Farben
		-	-	81-120	225/45			Orig.-Verschr., Ausführung N13 in den Farben TM u. SGVP, RLP, SVR
	RC34	40	-	81-120	225/45			Orig.-Verschr.
7,5 x 19	RC34	35	-	81-120	225/45, 235/45			Orig.-Verschr.
	B32	40	ZP581	81-120	225/45, 235/45			
	B39	40	ZP581	81-120	225/45, 235/45			
	AC-521	35	ZP590F+R	81-120	225/45, 235/45			+ Red.Ringe 73,1-66,1
	Oxigin 18	40	ZP581	81-96	225/45			
8 x 19	RC29	38	ZP581	81-120	225/45, 235/40, 235/45			
	B24	38	ZP581	81-120	225/45, 235/40, 235/45			
	B38	38	ZP581	81, 96	225/45, 235/40, 235/45			
	B40	35	ZP581	81-120	225/45, 235/40, 235/45			
	CA 17	40	ZP581	81-120	225/45			
	FMI08 Thoe	40	-	81-120	225/45, 235/40, 235/45, 245/40			Orig.-Verschr.
	Oxigin 29	40	ZP581	81-120	225/45, 235/45			
8,5 x 19	B44	40	ZP581	81-120	225/45			2WD
				96, 110	225/45			4WD
8 x 20	B38	35	ZP581	81-120	235/35			
	B40	35	ZP581	81-120	235/35			
weitere Dimensionen/Designs siehe Konfigurator								

weitere Dimensionen/Designs siehe Konfigurator

Kangoo NEU		Frühjahr 2021		RFK	5/114,3	66,1	e2*2018/858*00001*..., e2*2018/858*00002*...	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC27	35	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60			Orig.-Verschr., auch Rapid, nicht für Scheibenbremsen an der HA
	RC30	35	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60			Orig.-Verschr., auch Rapid, nicht für Scheibenbremsen an der HA, Felge ist nur in silber erhältlich!

	RC24	40	-	55-96	195/65, 195/70, 205/65, 215/60, 225/60		Orig.-Verschr., auch Rapid, nicht für Scheibenbremsen an der HA
6 x 16	RC34	38	-	51-96	205/55, 205/60 , 215/55, 215/60, 225/50, 225/55		Orig.-Verschr.
6,5 x 16	RC24	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		auch Rapid, nicht für Scheibenbremsen an der HA
	RC27	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		auch Rapid, nicht für Scheibenbremsen an der HA
	RC30	38	ZP581	55-96	195/60, 205/55, 205/60, 215/55, 225/50, 225/55		auch Rapid, nicht für Scheibenbremsen an der HA
	RC32	40+41	-	51-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
	RC34	32	-	55-96	205/55, 205/60, 215/55, 215/60		Orig.-Verschr.
		40	-	55-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
		41	-	55-96	205/55, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
		44	-	55-96	205/55, 215/55, 215/60, 225/50, 225/55, 235/50		Orig.-Verschr.
	Pro1	45	-	51-96	205/55, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr.
6,5 x 17	RC27	32	-	55-96	205/50, 205/55		Orig.-Verschr., auch Rapid
7 x 17	RC32	43	- (N42)	51-96	205/55 , 215/45, 215/50, 225/45, 225/50		Orig.-Verschr., Ausführung "N42"
	RC34	43	- (N42)	55-96	205/55 , 215/50, 225/45, 225/50		Orig.-Verschr., Ausführung "N42"
	RC27	35	-	55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr.
		38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		auch Rapid
	RC32	35	-	51-96	205/55, 215/50, 225/45		Orig.-Verschr.
		40	-	55-96	205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC34	35	-	51-96	205/55, 215/45, 215/50, 225/45		Orig.-Verschr.
		40	-	55-96	205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
	B39	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45		auch Kangoo Rapid
	Pro1	45	-	51-96	205/55, 215/50, 225/45		Orig.-Verschr.
7,5 x 17	RC24 / RC29	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		nicht für Scheibenbremsen an der HA, auch Kangoo Rapid
	RC28	35	ZP581	55-96	205/50, 205/55, 225/45		nicht für Scheibenbremsen an der HA, auch Kangoo Rapid
	B24	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		auch Rapid
	B36	38	ZP581	55-96	205/50, 205/55, 215/50, 225/45, 235/45		nicht für Scheibenbremsen an der HA, auch Kangoo Rapid
7 x 18	RC27	34+35+40	-	55-96	205/45, 215/45, 225/45		Orig.-Verschr., nicht für Scheibenbremsen an der HA, auch Kangoo Rapid
		35	-	51-96	215/45, 225/45		Orig.-Verschr.
	RC32	40	-	55-96	215/45, 225/45		Orig.-Verschr.
		35	-	51-96	215/45, 225/45		Orig.-Verschr., Ausführung "N42"
7,5 x 18	RC30	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	RC32	45	-	55-96	215/45, 225/40		Orig.-Verschr.
	B32	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		auch Kangoo Rapid
	B39	35	ZP581	55-96	205/45, 215/45, 225/40, 225/45		
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	55-96	205/45, 215/45, 225/40, 225/45		Kit mit Artikelnummer 98478 , auch Kangoo Rapid
	AC-521	35	ZP590F+R	55-96	205/45, 215/45, 225/40, 225/45		+ Red.Ringe 73,1-66,1 , nicht für Scheibenbremsen an der HA, auch Kangoo Rapid
8 x 18	B24	38	ZP581	55-96	215/45, 225/40, 225/45		auch Kangoo Rapid
	B36 / B37 / B38	35	ZP581	55-96	215/45		
	B42 / B44	40	ZP581	55-96	215/45		auch Rapid
7,5 x 19	RC34	35	-	51-96	225/40		Orig.-Verschr.
		40	-	55-96	225/40		Orig.-Verschr.
	AC-521	35	ZP590F+R	55-96	225/35, 225/40		+ Red.Ringe 73,1-66,1 , nicht für Scheibenbremsen an der HA, auch Kangoo Rapid nur mit 225/40
8 x 19	CA 17	40	ZP581	55-96	225/40		

Kangoo E-Tech NEU		im Laufe 2023		RFK	5/114,3	66,1	e2*2018/858*00001*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 16	RC32	40+41	-	51-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55			Orig.-Verschr.
7 x 17	RC32	35	-	51-96	205/55, 215/50, 225/45			Orig.-Verschr.
	RC34	35	- (N42)	51-96	205/55, 215/50, 225/45			Orig.-Verschr., Ausführung N42
		43	- (N42)	51-96	205/55, 215/50, 225/45, 225/50			Orig.-Verschr., Ausführung N42
	RC27	38	ZP581	51	205/55, 215/50			
	B39	38	ZP581	51	205/55, 215/50			
					205/50, 205/55, 215/50, 225/45			kurze Karosserie
7,5 x 17	Pro1	45	-	51-96	205/55, 215/50, 225/45			Orig.-Verschr.
7 x 18	B24	38	ZP581	51	205/55, 215/50, 235/45			
	RC27	34	-	51	225/45			Orig.-Verschr.
	RC32	35	-	51-96	215/45, 225/45			Orig.-Verschr.

	RC34	35	-	51-96	215/45, 225/45		Orig.-Verschr.
7,5 x 18	B32	35	ZP581	51	225/45		
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	51	225/45		Kit mit Artikelnummer 98478
8 x 18	B24	38	ZP581	51	225/45		
	B42	40	ZP581	51	225/45		
8 x 19	CA 17	40	ZP581	51-96	225/40		

Kangoo Rapid E-Tech NE		im Laufe 2023		RFK	5/114,3	66,1	e2*2018/658*00002*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC32	40	-	51-96	205/55, 205/60, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
6,5 x 17	RC27	32	-	51	205/50, 205/55		Orig.-Verschr., Elektro, kurze Karosserie
7 x 17	RC27	40	-	51	205/50, 205/55, 215/50, 225/45		Orig.-Verschr., Elektro, kurze Karosserie
		38	ZP581	51	205/50, 205/55, 215/50, 225/45		Elektro, kurze Karosserie
	RC34	35	-	51	205/55, 215/50, 225/45		Orig.-Verschr., Elektro
7,5 x 17	B24	38	ZP581	51	205/50, 205/55, 215/50, 225/45, 235/45		Elektro, kurze Karosserie
7 x 18	RC27	34	-	51	215/45, 225/45		Orig.-Verschr., Elektro, kurze Karosserie
7,5 x 18	RC30	35	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
	B32	35	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	51	215/45, 225/45		Kit mit Artikelnummer 98478
8 x 18	B24	38	ZP581	51	215/45, 225/45		Elektro, kurze Karosserie
	B36	35	ZP581	51	215/45		Elektro, kurze Karosserie
	B42 / B44	40	ZP581	51	215/45		Elektro, kurze Karosserie

Kangoo Express		ab 2021			RJK	5/114,3	66,1	e2*2007/46*0717*..
Dimension	Design	ET	KIT	KW	Reifendimension			Info
Kein TÜV hat bis dato dieses Fahrzeug angebaut (reines Nutzfahrzeug) - Info von Thorsten (Stand:10.02.2025)								

Koleos			ab 05.2017		RZG	5/114,3	66,1	e11*2007/46*3255*...., e6*2007/46*0269*....	
Sensor - Brocksens 4									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC27	35	-	96-140	225/65, 235/60, 235/65				Orig.-Verschr., Ausführung N13
	RC32	35	ZP578D2F	96-130	225/65, 235/60, 235/65, 245/60, 255/55, 255/60				Ausführung N22
			-	96-140	225/65, 235/60, 235/65, 245/60, 255/55, 255/60				Orig.-Verschr., Ausführung N42
	RC34	35	-	96-140	225/65, 235/60, 235/65, 245/60, 255/55, 255/60				Orig.-Verschr., Ausführung N42
	RC27	38	ZP578	96-140	225/65, 235/60, 235/65, 255/55, 255/60				
		40	-	96-140	225/65, 235/60, 235/65				Orig.-Verschr.
	RC32	40	-	96-140	225/65, 235/60, 235/65, 245/60, 255/55, 255/60				Orig.-Verschr.
7,5 x 17	B39	38	ZP578	96-140	225/65, 235/60, 235/65, 255/55, 255/60				
	RC24	38	ZP578	96-140	225/65, 235/60, 235/65				
	RC28	35	ZP578	96-140	225/65, 235/60, 235/65				
	RC29	38	ZP578	96-140	225/65, 235/60, 235/65				
	B24	38	ZP578	96-140	225/65, 235/60, 235/65				
	B36	38	ZP578	96-140	225/65, 235/60, 235/65				
	AC-518	40	Artikel Nr. 98495	96-140	225/65, 235/60, 235/65				Kit mit Artikelnummer 98495
7 x 18	RC27	35	-	96-140	225/60				Orig.-Verschr.
	RC32	35	-	96-140	225/55, 225/60, 235/55, 245/50, 245/55, 255/50, 255/55				Orig.-Verschr.
	RC34	35	-	96-140	225/55, 225/60, 235/55, 245/50, 245/55, 255/50, 255/55				Orig.-Verschr., Ausführung N42
	RC32	40	-	96-140	225/55, 225/60, 235/55, 245/50, 245/55, 255/50, 255/55				Orig.-Verschr.
		34	-	96-140	225/60, 235/55				Orig.-Verschr.
	RC27	40	-	96-130	225/60, 235/55, 235/60, 245/55				Orig.-Verschr.
7,5 x 18	RC30	35	ZP578	96, 130	225/60, 235/55				
	B32	35	ZP578	96-140	225/60, 235/55				
	B39	35	ZP578	96-140	225/60, 235/55				
	AC-MB6 / AC-M10	35	Artikel Nr. 98495	96-140	225/60, 235/55				Kit mit Artikelnummer 98495
	AC-521	35	Artikel Nr. 98495	96-140	225/60, 235/55				Kit mit Artikelnummer 98495
	AC-V51	38	ZP578D2F	96-140	235/55				
	8 x 18	B24	38	ZP578	96-140	225/60, 235/55			
B42 / B44		40	ZP578	96-140	225/60, 235/55				
7 x 19	RC34	40	-	96-140	225/55, 235/50, 245/50				Orig.-Verschr.
	RC27	40	-	96-140	225/55, 235/50, 245/50				Orig.-Verschr., Ausführung N13 - in den Farben TM u. SGVP, RLP, SVR
	RC34	35	-	96-140	225/55, 235/50, 245/50				Orig.-Verschr.
		40	-	96-140	225/55, 235/50, 245/45, 245/50				Orig.-Verschr.
	B32	40	ZP578	96-140	225/55, 235/50, 245/50				

7,5 x 19	B39	40	ZP578	96, 130	225/55, 235/50, 245/50		
	AC-521	35	Artikel Nr. 98495	96-140	225/55, 235/50		Kit mit Artikelnummer 98495
	Oxigin 18	40	ZP578	96-130	225/55, 235/50, 235/55, 245/50		
8 x 19	RC29	38	ZP578	96-140	225/55, 235/50, 255/45		
	B24	38	ZP578	96-140	225/55, 235/50, 255/45		
	B38	38	ZP578	96-140	225/55, 235/50, 255/45		
	B40	35	ZP578	96-140	225/55, 235/50, 255/45		
	AC-518	40	Artikel Nr. 98495	96-140	225/55, 235/50, 255/45		Kit mit Artikelnummer 98495
	CA 17	40	ZP578	96-140	225/55, 235/50, 235/55, 255/45		
	FMI08 Thoe	40	-	96-140	225/55, 235/50, 245/50, 255/45		Orig.-Verschr.
8 x 20	Oxigin 29	40	ZP578	96-140	225/55, 235/50, 255/45		
	B38	35	ZP578	96-140	235/45, 245/45, 255/45		
	B40	35	ZP578	96-140	235/45, 245/45, 255/45		
	B43	40	-	96-140	235/45, 245/45, 255/45		Orig.-Verschr., Ausführung N42 u. N43

weitere Dimensionen/Designs siehe Konfigurator

Master	NEU i.V.	2024	R6A/R6B + RDA/RDB/RDC/RDD	5/130	e2*KS18/858*00015*.., e2*2018/858*00074*..
Noch kein Fahrzeuganbau vorhanden - Info Thorsten (Stand:12.02.2025)					

Megane E-Tech (V)	NEU	2022	RCB	5/114,3	66,1	e2*2018/858*00018*..
Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 18	RC34	38	-	55	195/60	 Orig.-Verschr.
	RE 7	38	-	55	195/60	 Orig.-Verschr., max. Leistung: 96, 160kW
7 x 18	RC27	34	-	55	195/60, 205/55, 215/55	 Orig.-Verschr., max. Leistung: 96, 160kW
		35	-	55	205/55	Orig.-Verschr., max. Leistung: 96, 160kW
	RC32	35	-	55	195/60, 205/55, 215/55	Orig.-Verschr.
	RC34	35	-	55	205/55, 215/55	Orig.-Verschr., Ausführung "N42"
	B32	35	ZP581	55	205/55	
7,5 x 18	AC-MB6	35	Artikel Nr. 98478	55	205/55	Kit mit Artikelnummer 98478
	AC-521	35	Artikel Nr. 98478	55	205/55	Kit mit Artikelnummer 98478
7 x 19	RC34	40	-	55	225/45	Orig.-Verschr.
7,5 x 19	RC34	35	-	55	205/55, 225/45	Orig.-Verschr.
8 x 20	RC36	35	-	55	215/45	Orig.-Verschr.
	B38 / B40	35	ZP581	55	215/45	max. Leistung: 96, 160kW

Megane (IV)		ab 02.16	RFB	5/114,3	66,1	e2*2007/46*0546*..
Sensor - Brocksens 4						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC27	35	-	66-103	195/65, 205/60	 Orig.-Verschr., nur Bremse bis max. 280mm
	RC30	35	-	66-103	195/65, 205/60	 Orig.-Verschr., nur Bremse bis max. 280mm, Felge ist nur in silber erhältlich!
	RC24	40	-	66-103	195/65, 205/60, 215/60	Orig.-Verschr., nur Bremse bis max. 280mm
		45	ZP581	66-103	195/65, 205/60, 215/60	nur Bremse bis max. 280mm
6 x 16	RC34	38	-	66-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50	Orig.-Verschr.
6,5 x 16	RC32	41	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50	 Orig.-Verschr.
	RC34	41	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50	 Orig.-Verschr.
	RC24	44	ZP581	66-103	195/55, 195/60	
				66-120	205/55, 215/55, 225/50	
	RC27	40	-	66-97	195/55, 195/60	Orig.-Verschr.
				66-120	205/55, 215/55	
		44	-	66-103	195/55, 195/60	Orig.-Verschr.
				66-120	205/55, 215/55, 225/50	
	RC30	38	ZP581	66-103	195/55, 195/60	
				66-120	205/55	
		45	ZP581	66-103	195/55, 195/60	
				66-120	205/55, 215/55, 225/50	
	RC32	40	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50	Orig.-Verschr.
	RC34	40	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50	Orig.-Verschr.
		44	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50	Orig.-Verschr.
	CA 20	45	ZP581	66-103	195/55, 195/60	
				66-120	205/55, 215/55, 225/50	
	Pro1	45	-	66-130	195/55, 195/60, 205/55, 215/50, 215/55, 225/50, 235/50	Orig.-Verschr.
	RC32	43	-(N42)	66-130	205/45, 205/50, 215/45, 225/45	 Orig.-Verschr., Ausführung "N42"
	RC34	43	-(N42)	66-130	205/45, 205/50, 215/45, 225/45	 Orig.-Verschr., Ausführung "N42"
		40	-	66-120	205/45, 215/45	Orig.-Verschr.

7 x 17	RC27	45	ZP581	66-121	225/45		Orig.-Verschr.
				66-120	205/50, 215/45		
				66-121	225/45		
	RC30	45	ZP581	66-120	205/50, 215/45		
				66-121	225/45		
	RC32	35	-	66-130	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
		40	-	66-130	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	35	-	66-130	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	B39	38+45	ZP581	66-120	205/50, 215/45		
				66-121	225/45		
7 x 18	AC-V51	45	-	66-121	225/45		Orig.-Verschr.
	Pro1	45	-	66-130	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC27	34	-	66-120	205/40, 205/45		Orig.-Verschr.
		40	-	66-97	215/40		Orig.-Verschr.
	RC32	35+40+45	-	66-130	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC34	35	-	66-130	205/40, 205/45, 215/40		Orig.-Verschr., Ausführung "N42"
	RC32	46	-	66-130	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	RC30	45	ZP581	66-120	205/40, 205/45, 215/40		
				66-121	225/40		
	B32	45	ZP581	66-120	205/40, 205/45, 215/40		
				66-121	225/40		
		46	-	66-97	205/40, 205/45, 215/40, 225/40		Orig.-Verschr., ET46 Ausführung "N10", SVR
	AC-MB6	45	Artikel Nr. 98478	66-120	205/40, 205/45, 215/40		Kit mit Artikelnummer 98478
				66-121	225/40		
	AC-521	35	ZP590F+R	66-120	205/40, 205/45		+ Red.Ringe 73,1-66,1
		45	ZP590F+R	66-120	205/40, 205/45, 215/40		+ Red.Ringe 73,1-66,1
	Oxigin 18	45	ZP581	66-121	225/40		
		45	ZP581	66-97	215/40		
	Oxigin 25	45	ZP581	66-151	215/40		
8 x 18	B42 / B44	45	ZP581	66-120	205/40, 215/40		
				66-121	225/40		
	AC-M10	45	ZP590F+R	66-120	205/40, 215/40		+ Red.Ringe 73,1-66,1
7 x 19	RC34	40	-	66-121	225/40		
		40	-	66-130	215/35		Orig.-Verschr.
7,5 x 19	RC34	35	-	66-130	215/35		Orig.-Verschr.
		40+46	-	66-130	215/35, 225/35		Orig.-Verschr.
	B32	40	ZP581	66-120	215/35		
				66-121	225/35		bei 225/35 ✖
	B39	40+45	ZP581	66-97	215/35, 225/35		ET40 bei 225/35 ✖
	AC-521	45	ZP590F+R	66-120	215/35		+ Red.Ringe 73,1-66,1
				66-121	225/35		

weitere Dimensionen/Designs siehe Konfigurator

Megane GT (IV)		ab 2016		RFB	5/114,3	66,1	e2*2007/46*0546*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC32	43	- (N42)	151	225/45		Orig.-Verschr., Ausführung "N42"	
	RC34	43	- (N42)	151	225/45		Orig.-Verschr., Ausführung "N42"	
	RC27	40	-	120, 151	225/45		Orig.-Verschr.	
		38+45	ZP581	120, 151	225/45			
	RC30	45	ZP581	120, 151	225/45			
	RC32	35+40	-	151	225/45		Orig.-Verschr.	
	RC34	35	-	151	225/45		Orig.-Verschr.	
	B39	38+45	ZP581	120, 151	225/45			
	AC-V51	45	-	120, 151	225/45		Orig.-Verschr.	
7,5 x 17	Pro1	45	-	151	225/45		Orig.-Verschr.	
	RC24 / RC28	45	ZP581	120, 151	225/45, 235/45			
	B36	46	ZP581	120, 151	225/45, 235/45			
	RC32	46	-	151	225/35, 225/40		Orig.-Verschr.	
7,5 x 18	RC30	45	ZP581	120, 151	225/40			
	B32	45	ZP581	120, 151	225/40			
		46	-	151	225/40		Orig.-Verschr., ET46 Ausführung "N10", SVR	
	B39	45	ZP581	120, 151	225/40			
	AC-MB6 / AC-M10	45	Artikel Nr. 98478	120, 151	225/40		Kit mit Artikelnummer 98478	
	AC-521	45	ZP590F+R	120, 151	225/40		+ Red.Ringe 73,1-66,1	
	Oxigin 18	45	ZP581	151	225/40			
8 x 18	B42 / B44	45	ZP581	120, 151	225/40			
	AC-M10	45	ZP590F+R	120, 151	225/40		+ Red.Ringe 73,1-66,1	
7,5 x 19	RC34	40+46	-	151	225/35		Orig.-Verschr.	
	B39	45	ZP581	120, 151	225/35			
	AC-521	45	ZP590F+R	120, 151	225/35		+ Red.Ringe 73,1-66,1	
	CA 26	45	ZP581	120, 151	225/35			

8 x 19	B38	45	ZP581	120, 151	225/35		
weitere Dimensionen/Designs siehe Konfigurator							

Megane R.S. (IV)				ab 2017	RFB	5/114,3	66,1	e2*2007/46*0546*..
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
8 x 18	RC32	48	-	205	235/40, 245/35, 245/40			Orig.-Verschr.
	RC29	45	ZP581	205, 221	235/40			
	B37	45	ZP581	205, 221	235/40			
	B38 / B42	45	ZP581	205, 221	235/40			
	B44	45	ZP581	205, 221	235/40			
	AC-M10	45	ZP590F+R	205, 221	235/40			+ Red.Ringe 73,1-66,1
8 x 19	B40	49	ZP590F	205	235/35, 245/30, 245/35			
	CA 19	45	ZP581	205, 221	235/35			
	FMI08 Thoe	40	-	205	235/35			Orig.-Verschr.
	Oxigin 29	50	ZP581	205, 221	235/35, 245/30, 245/35			
8,5 x 19	CA 26	46	ZP581	205, 221	235/35			
8 x 20	RC36	50	-	205, 221	245/30			Orig.-Verschr.
	B38	45	ZP581	205	245/30			
		50	ZP581	205, 221	245/30			
8,5 x 20	B24	50	ZP581	205	235/30			
				205, 221	245/30			

Megane E-Tech (IV)		ab 2020		RFB	5/114,3	66,1	e2*2007/46*0546*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC24	38	ZP581	67, 69	205/55		Plug-in-Hybrid
	RC27	38	ZP581	67, 69	205/55		Plug-in-Hybrid
	RC30	38	ZP581	67, 69	205/55		Plug-in-Hybrid
		45	ZP581	67, 69	205/55, 215/55, 225/50		Plug-in-Hybrid
	CA 20	45	ZP581	67, 69	205/55, 215/55, 225/50		Plug-in-Hybrid
7 x 17	RC27	38	ZP581	67, 69	205/50, 225/45		Plug-in-Hybrid
		45	ZP581	67	205/50, 225/45		Plug-in-Hybrid
	RC30	45	-	67	205/50, 225/45		Orig.-Verschr., Plug-in-Hybrid
		38	ZP581	67, 69	205/50, 225/45		Plug-in-Hybrid
	B39	45	ZP581	67	205/50, 225/45		Plug-in-Hybrid
		38	ZP581	67	205/50, 225/45		Plug-in-Hybrid
7,5 x 18	AC-V51	45	-	67, 69	225/45		Orig.-Verschr., Plug-in-Hybrid
	RC30	45	ZP581	67, 69	225/40		Plug-in-Hybrid
	B32	45	ZP581	67	225/40		Plug-in-Hybrid
	B39	45	ZP581	67, 69	225/40		Plug-in-Hybrid
	AC-MB6 / AC-M10	45	Artikel Nr. 98478	67, 69	225/40		Kit mit Artikelnummer 98478
8 x 18	AC-521	45	ZP590F+R	67, 69	225/40		+ Red.Ringe 73,1-66,1
	RC29	45	ZP581	67	225/40		Plug-in-Hybrid
	B36 / B37	45	ZP581	67, 69	225/40		Plug-in-Hybrid
	B42 / B44	45	ZP581	67, 69	225/40		Plug-in-Hybrid
	AC-M10	45	ZP590F+R	67, 69	225/40		+ Red.Ringe 73,1-66,1
	CA 20	45	ZP581	67, 69	225/40		

Rafale		NEU	ab 2024		RHN	5/114,3	66,1	e9*2018/858*30002*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8,5 x 20	RC36	37	-	96, 110	245/45				Orig.-Verschr., incl. Allradlenkung
	B41	37	-	96-110	245/45				nur in SG u. FG erhältlich!

Scenic E-Tech NEU				2024	RCB	5/114,3	66,1	e2*2018/858*00018*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 19	RC34	46	-	55	205/55, 215/50, 225/50, 235/45, 245/45				Orig.-Verschr.
	CA 26	45	ZP581	55	215/50, 225/50, 245/45				
8 x 20	RC36	50	-	55	215/45, 235/45, 245/40				Orig.-Verschr.
	B43	40	-	55	215/45				Orig.-Verschr.

Scenic, Grand Scenic		ab 2016		RFA	5/114,3	66,1	e2*2007/46*0574*...	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 18	RC34	35	-	70-120	215/60M+S			Orig.-Verschr., Ausführung "N42"
7 x 19	RC34	40	-	70-120	205/55M+S			Orig.-Verschr.
7,5 x 19	RC34	35+40	-	70-120	205/55M+S			Orig.-Verschr.

Symbioz E-Tech NEU				2024	RJB	5/114,3	66,1	e2*2007/46*0684*27-..
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info

7 x 17	RC32	35	-	69	215/60		Orig.-Verschr., Ausführung N42
					215/55, 215/60, 225/55, 235/50, 235/55		
	RC34	35	-	69	215/60		Orig.-Verschr., Ausführung N42
7 x 18	FMI06 Koros	35	-	69	215/60		Orig.-Verschr.
	RC27	35	-	69	215/50, 215/55 , 225/50		Orig.-Verschr., Ausführung N16
	RC34	35	-	69	215/50, 215/55 , 225/50, 235/50		Orig.-Verschr., Ausführung N42
	RC27	34	-	69	215/50, 215/55, 225/50		Orig.-Verschr.
7,5 x 18	RC32	35	-	69-103	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Ausführung N42
	B32	35	ZP581	69	215/50, 215/55		
	AC-MB6 / AC-M10	35	Artikel Nr. 98478	69	215/50, 215/55		Kit mit Artikelnummer 98478
7,5 x 19	RC34	35	-	69	225/45		Orig.-Verschr., Ausführung N42
				69	215/45, 215/50, 225/45, 235/45		
8 x 20	RC36	35	-	69-103	225/40		Orig.-Verschr., Ausführung N12

Talisman		ab 03.16		RFD	5/114,3	66,1	e11*2007/46*2969*00-07; e2*2007/46*0653*..	
Sensor - Brocksens 4								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC32	41	-	81-100	215/60			Orig.-Verschr.
					215/60, 215/65, 225/55, 225/60, 235/55			
	RC34	40	-	81-147	215/60, 215/65, 225/55, 225/60, 235/55			Orig.-Verschr., beide ET's ECE
		41	-	81-117	215/60, 215/65, 225/55, 225/60, 235/55			
	RC24	38	ZP581	81-110	215/60, 215/65, 225/60			
		44	ZP581	81-110	215/60, 215/65, 225/60			
	RC27	40+44	-	81-110	215/60, 215/65, 225/60			Orig.-Verschr., ET40 orig.-ET
		38	ZP581	81, 96	215/60, 215/65, 225/60			
		45+50	ZP581	81-110	215/60, 215/65, 225/60			
	RC30	38+45	ZP581	81-110	215/60, 215/65, 225/60			
	RC32	40	-	81-147	215/60, 215/65, 225/55, 225/60, 235/55			Orig.-Verschr.
	RC34	32+44	-	81-147	215/60, 215/65, 225/55, 225/60, 235/55			Orig.-Verschr.
CA 20	45	ZP581	81-110	215/60, 215/65, 225/60				
7 x 17	Pro1	45	-	81-147	215/60, 215/65, 225/55, 225/60, 235/55			Orig.-Verschr.
	RC32	43	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., Ausführung N22	
			-	81-165	225/55		Orig.-Verschr., Ausführung N42	
	RC34	43	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., Ausführung N42	
	RC27	40	-	81-110	215/55			Orig.-Verschr., auch Talisman 4Control aber nur 225/55 auflagenfrei!
				81-165	225/55, 235/50			
				81-110	215/55			
	RC30	45	ZP581	81-165	225/55, 235/50, 245/50			auch Talisman 4Control, dieser bei 245/50 ✖
				81-110	215/55			
	RC32	35	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50			Orig.-Verschr., Ausführung N22 u. N42
		40	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50, 245/50			Orig.-Verschr.
RC34	35	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50			Orig.-Verschr., Ausführung N42	
7,5 x 18	B39	45	ZP581	81,96	215/55			
				81-147	225/55, 235/50, 245/50			auch Talisman 4Control- dieser bei 245/50 ✖
	AC-V51	45	-	81-165	225/55, 235/50, 245/50			Orig.-Verschr.
				81-165	225/55, 235/50			Orig.-Verschr., Talisman 4Control
	Pro1	45	-	81-165	215/50, 215/55, 225/50, 225/55, 235/50, 245/50			Orig.-Verschr.
	7 x 18	RC27	40	-	81-96	215/45, 215/50, 215/55		
81-147					225/45, 225/50			
RC32		35	-	81-165	215/45, 215/50, 225/45			Orig.-Verschr.
		40+45	-	81-165	215/45, 215/50, 225/45, 225/50			Orig.-Verschr.
RC34	35	-	81-165	215/45, 215/50, 225/45			Orig.-Verschr., Ausführung "N42"	
8 x 18	RC32	46	-	81-165	215/45, 215/50, 225/45, 225/50, 235/45, 245/45			Orig.-Verschr.
	RC30	45	ZP581	81-147	225/45, 225/50, 235/45, 245/45			auch Talisman 4Control
	B32	35+45	ZP581	81-147	225/45, 225/50, 235/45, 245/45			Talisman 4Control mit 245/45, ET35 bei 225/50 u. 245/45 ✖
		46	-	81-147	225/45, 225/50, 235/45, 245/45			Orig.-Verschr., Ausführung "N10", SVR, Talisman 4Control mit 245/45
	B39	45	ZP581	81-165	225/45, 225/50, 235/45, 245/45			
				81-165	245/45			Talisman 4Control
	AC-MB6	45	Artikel Nr. 98478	81-165	225/45, 225/50, 235/45, 245/45			Kit mit Artikelnummer 98478, Talisman 4Control mit 245/45
	AC-521	35	ZP590F+R	81-165	225/45, 235/45			+ Red.Ringe 73,1-66,1
		45	ZP590F+R	81-165	225/45, 225/50, 235/45, 245/45			+ Red.Ringe 73,1-66,1, 4Control nur 245/45
	AC-V51	38	-	81-165	245/45			Orig.-Verschr., Talisman 4Control ✖
	Oxigin 18	45	ZP581	81-147	225/45, 225/50, 235/45, 235/50, 245/45			
	8 x 18	B42	40	ZP581	81-165	225/45, 225/50, 235/45, 245/45		
45			ZP581	81-165	225/45, 225/50, 235/45, 245/45, 255/45			
				81-165	245/45			Talisman 4Control
B44		40	ZP581	81-165	225/45, 225/50, 235/45, 245/45			
				81-165	245/45			Talisman 4Control ✖

7,5 x 19	AC-M10	45	ZP590F+R	81-165	245/45		Talisman 4Control
				81-165	225/45, 225/50, 235/45, 245/45, 255/45		+ Red.Ringe 73,1-66,1
				81-165	245/45		+ Red.Ringe 73,1-66,1, Talisman 4Control
	RC34	35	-	81-165	225/40		Orig.-Verschr.
		40+46	-	81-165	225/40, 225/45		Orig.-Verschr.
8 x 19	Oxigin 18	40	ZP581	81-147	225/40, 225/45, 235/45		
	B40	49	ZP590F	81-147	245/40		auch Talisman 4Control
				81-165	225/40, 225/45, 235/40, 245/40		Talisman Control nur 245/40
	CA 19	45	ZP581	81-165	225/40, 225/45, 235/40, 245/40		Talisman Control nur 245/40
	CA 24	45	ZP581	81-165	225/40, 225/45, 235/40, 235/45, 245/40		
8 x 20	FMI08 Thoe	40	-	81-165	225/40, 235/35, 235/40, 245/35, 245/40		Orig.-Verschr.
	Oxigin 29	50	ZP581	81-165	225/40, 225/45, 235/40, 245/40		Talisman Control nur 245/40
	B38	45+50	ZP581	81-165	225/35, 235/35, 245/35		
				81-165	245/35		Talisman 4Control
	B43	40	-	81-165	225/35, 235/35, 245/35		Orig.-Verschr., Ausführung N42 u. N43
		45	-	81-165	225/35, 235/35, 245/35		Orig.-Verschr.
				81-165	245/35		Orig.-Verschr., Talisman 4Control

weitere Dimensionen/Designs siehe Konfigurator

Traffic (siehe Konfigurator)	ab 10.01	JL/FL/J	5/118	71,1
------------------------------	----------	---------	-------	------

Trafic III		ab 2014	JL/L	5/114,3	66,1	e2*2007/46*0014*21-..
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC25T	47	-	66-107	205/65C	Orig.-Verschr., geschl. Aufbau
				66-125	215/60, 215/65, 215/65C	
	Pro1	45	-	66-125	205/65C, 215/60, 215/65, 215/65C, 225/60, 225/60C	Orig.-Verschr., geschl. Aufbau
6,5 x 17	RC27	47	-	66-125	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau
7 x 17	B45	45	-	66-125	215/60, 215/60C	Orig.-Verschr., incl. Facelift 2020, geschl. Aufbau
	AC-V51	45	-	66-125	215/60, 215/60C	Orig.-Verschr., geschl. Aufbau
	Pro1	45	-	66-125	215/60, 215/60C	Orig.-Verschr.
8 x 18	B36	35	ZP577	66-103	245/45	✖
	B37	35	ZP577	66-103	245/45	✖

Twingo III		ab 10/2014	AH	4/100	60,1	e2*2007/46*0457*..
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	37	ZP440F	48-68	VA 165/65, 175/60, 185/55	bei 175/60 u. 185/55 ✖
					HA 185/60, 195/55, 205/50	
6,5 x 16	RC34	37	-	31-68	VA 185/50+HA 205/45	Orig.-Verschr., VA ✖

Twingo GT III		ab 2016	AH	4/100	60,1	e2*2007/46*0457*08-..
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	31	-	80	VA165/65, HA185/60, HA195/55	Orig.-Verschr.
		37	ZP440F	80	VA165/65, VA175/60, VA185/55, VA185/60	wenn 185/60 VA dann ✖
					HA185/60, HA195/55, HA205/50, HA205/55	
6,5 x 16	RC34	37	-	80	VA 185/50+HA 205/45	Orig.-Verschr., VA ✖

Twingo Electric NEU		ab Jänner 2021	AH	4/100	60,1	e2*2007/46*0457*
Sensor - Brocksens 3						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	37	ZP440F	31 (60)	VA 165/65+HA 185/60 od. VA 165/65+HA 195/55	
	RC30	37	ZP440F	31 (60)	VA 165/65+HA 185/60 od. VA 165/65+HA 195/55	

Zoe		ab 2013		AG	4/100	60,1	e2*2007/46*0251*...	
Sensor - Continental VDO - Artikelnummer 74673								
Dimension		Design	ET	KIT	KW	Reifendimension		Info
22 kWh-Batterie								
6 x 15	RC24	40	ZP440	43 (57-68)	185/65, 195/60, 205/55			
		37	ZP440F	43 (57-68)	185/65, 195/60, 205/55			
	RC30	37	ZP440F	43 (65)	185/65, 195/60, 205/55			
		40	ZP440	43 (65)	185/65, 195/60, 205/55			
6,5 x 15	RC28	35	ZP440	43 (65)	185/65, 195/60, 205/55			ab 205/55 ✖
		45	ZP440	43 (57-68)	185/65, 195/60			
6,5 x 16	RC24	38	ZP440	43, 53	195/50, 195/55			
				43 (65)	185/55			
	RC30	38	ZP440	43 (65)	185/55, 195/50, 195/55			
7 x 16	RC28	38	ZP440	43, 53	195/50, 195/55, 215/45			
	B24	38	ZP440	43, 53	195/50, 195/55, 215/45			
7 x 17	B24	45	ZP440	43, 53	205/45			
	B30	38+44	ZP440	43 (57-68)	205/45, 215/45			ET38 nur 205/45 auflegen! ✖

	500	50144	41440	43 (65)	215/40		Bitte nur ZSP40 anbringen!
7,5 x 17	RC28	45	ZP440	43 (65)	205/45		

Zoe Facelift NEU ab 11.2019 AG 5/114,3 66,1 e2*2007/46*0251*15-..., e2*2007/46*0681*03							
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC24	40	-	51	185/65, 195/60, 205/55, 205/60		Orig.-Verschr., max. Leistung 80, 100kW
	RC30	35	-	51	185/65, 195/60		Orig.-Verschr., max. Leistung 80, 100kW, Felge ist nur in silber erhältlich!
	RC27	35	-	51	185/65, 195/60		Orig.-Verschr., max. Leistung 80, 100kW
6 x 16	RC34	38	-	51	195/55		Orig.-Verschr.
6,5 x 16	RC27	44	-	51	195/55, 205/50, 215/50		Orig.-Verschr.
	RC34	44	-	51	195/55		Orig.-Verschr.
	RC24	38	ZP581	51	195/55		max. Leistung 80, 100kW
	RC27	38	ZP581	51	195/55		
	RC30	38	ZP581	51	195/55		
		45	ZP581	51	195/55, 205/50		max. Leistung 80, 100kW
	RC32	41	-	51	195/55, 205/50, 205/55, 215/50		Orig.-Verschr., ab 205/50 ✖
	RC34	40+41	-	51	195/55, 205/50, 205/55, 215/50		Orig.-Verschr., ab 205/50 ✖
		44	-	51	195/55, 205/50, 205/55, 215/50		Orig.-Verschr., ab 215/50 ✖
	CA 20	45	ZP581	51	195/55, 205/50		
	Pro1	45	-	51	195/55, 205/50, 205/55, 215/50, 225/50		Orig.-Verschr., ab 215/50 ✖
7 x 17	RC27	40	-	51	VA 215/45+HA 205/45		Orig.-Verschr.
		45	ZP581	51	VA 215/45+HA 205/45		
	RC30	45	-	51	VA 215/45+HA 205/45		Orig.-Verschr.
			ZP581	51	VA 215/45+HA 205/45		
	RC32	40	-	51	215/45		Orig.-Verschr., ✖
	RC34	43	-	51	VA+HA 215/45 od. VA 215/45+HA 205/45		Orig.-Verschr.
	B39	45	ZP581	51	VA+HA 215/45 od. VA 215/45+HA 205/45		
7,5 x 17	Pro1	45	-	51	VA+HA 215/45 od. VA 215/45+HA 205/45		Orig.-Verschr.
	RC29	38	ZP581	51	VA 215/45+HA 205/45		VA ✖
	B36	38	ZP581	51	VA 215/45+HA 205/45		VA ✖

Originaldaten in 17 Zoll

7 x 17		VA 44					
		HA 48					

Seat

	Baujahr	Typ	LK/LZ	Nabe	
Alhambra (siehe Konfigurator)	ab 09.10	7N	5/112	57,1	e1*2007/46*0402*..., e1*2007/46*0435*...

Arona	ab 11.2017	KJ	5/100	57,1	e9*2007/46*3134*02*...
-------	------------	----	-------	------	------------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC27	45	-	66-110	205/55, 205/60 , 215/55, 215/60		Orig.-Verschr.
				70-110	195/60 , 195/65		
	RC30	45	-	66-110	205/55, 205/60 , 215/55, 215/60		Orig.-Verschr.
				70-110	195/60 , 195/65		
				70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60		
	RC34	45	-	66-110	195/55, 195/60 , 195/65, 205/55 , 205/60 , 215/50, 215/55, 215/60		Orig.-Verschr.
	RC27	38	-	70-110	195/60, 195/65		
	RC30	35+38	-	70-110	195/60, 195/65		Orig.-Verschr.
RC34	35	-	66-110	195/55, 195/60, 195/65		Orig.-Verschr.	
	40	-	66-110	195/55, 195/60, 195/65, 205/55, 205/60		Orig.-Verschr.	
6,5 x 16	RC27	40	-	70-110	195/60, 195/65		Orig.-Verschr.
		47	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60		Orig.-Verschr.
	RC30	38	-	70-110	195/60, 195/65		Orig.-Verschr.
		47	-	66-110	205/55, 205/60, 215/55, 215/60		Orig.-Verschr.
			70-110	195/60, 195/65			
	RC32	47	-	66-110	195/60, 195/65, 205/55, 205/60, 215/50, 215/55, 215/60		Orig.-Verschr.
	RC34	40	-	66-110	195/55, 195/60, 195/65		Orig.-Verschr.
		47	-	66-110	195/55, 195/60, 195/65, 205/55, 205/60, 215/50, 215/55, 215/60		Orig.-Verschr.
	CA 20	38	ZP516	70-110	195/60, 195/65		
	6,5 x 17	RC27	48	-	70-110	195/55, 205/50, 205/55 , 215/50	
RC34		48	-	66-110	205/55		
7 x 17	RC30	46	-	66-110	205/50, 205/55, 225/45		Orig.-Verschr.
				70-110	195/55		
	B39	46	-	70-110	195/55, 205/50, 205/55, 225/45		Orig.-Verschr.
	RC27 / RC30	43	ZP516	70-110	195/55		
	CA 26	46	ZP516	66-110	195/55, 205/50, 205/55, 225/45		
7 x 18	RC27	47	-	70-110	215/45		Orig.-Verschr.
				66-110	205/45, 215/40, 215/45, 225/45		
	RC32	47	-	66-110	195/50, 205/45, 205/50, 215/40, 215/45 , 225/45		Orig.-Verschr.
	RC34	47	-	66-110	215/45		Orig.-Verschr.

weitere Dimensionen/Designs siehe Konfigurator

Ateca	ab 2015	5FP	5/112	57,1	e9*2007/46*6394*..
-------	---------	-----	-------	------	--------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC27	43	-	81-110	215/60 , 215/65, 225/55, 225/60		Orig.-Verschr., incl. ab Modell 2021, Frontantrieb
				110, 140	215/60 , 215/65, 225/60		Orig.-Verschr., incl. ab Modell 2021, 4drive
	RC30	43	-	85, 110	215/60 , 215/65, 225/55, 225/60		Orig.-Verschr., incl. ab Modell 2021, Frontantrieb
	RC34	43	-	110, 140	215/60 , 225/60		Orig.-Verschr., incl. ab Modell 2021, 4drive
6,5 x 16	RC24	42+43	-	81-140	215/60 , 215/65, 225/60		Orig.-Verschr.
				85, 110	215/60, 215/65, 225/55, 225/60, 235/60		Orig.-Verschr., Frontantrieb
	RC27	42+44+	-	110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., Ateca 4drive
				110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., Ateca 4drive
		43	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60		Orig.-Verschr., Front., ohne Verbr. bei 235/60 ✖
				110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., Ateca 4drive
	RC30	39+41+ 42+44+ 46	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60		Orig.-Verschr., Frontantrieb
				110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., Ateca 4drive
	RC32	41	-	81-140	215/60, 215/65, 225/55, 225/60		Orig.-Verschr., auch Allrad
				81-140	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr.
	RC34	43	-	81-140	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr.
				81-110	215/60, 215/65, 225/55, 225/60, 235/60		incl. ab Modell 2021, Frontantrieb
6,5 x 17	RC27	39	-	85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Radhausverbr. ab 225/50 ✖
		43	-	85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr.
7 x 17	RC27	45	-	85, 110	215/55 , 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
				110, 140	215/55 , 215/60, 225/50, 225/55 , 235/50, 235/55		Orig.-Verschr., 4drive
	RC30	45	-	81-110	215/55 , 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
				110, 140	215/55 , 215/60, 225/50, 225/55 , 235/50, 235/55		Orig.-Verschr., Ateca 4drive
	RC32	45	-	85-140	215/50, 215/55 , 215/60, 225/50, 225/55 , 235/50		Orig.-Verschr., ohne Radhausverbr. bei 235/50 ✖
	RC34	45	-	81-140	215/55 , 225/55		Orig.-Verschr.
	RC27	45	-	81-110	215/50		Orig.-Verschr., Frontantrieb, mit Verbreiterungen
				110, 140	215/50 , 225/50		Orig.-Verschr., Allrad, mit Verbreiterungen
				85-221	215/45, 215/50, 215/55, 225/45, 225/50, 235/50		Orig.-Verschr., nicht Bremse 370mm

7 x 18	RC32	45	-	81-140	215/45, 215/50 , 225/45, 225/50		Orig.-Verschr.
	RC34	45	-	81-140	215/50 , 225/50		Orig.-Verschr.
	RC27	43	-	85-221	215/45, 215/50, 215/55, 225/45, 225/50, 235/50		Orig.-Verschr.
	RC32	40	-	85-140	215/45, 215/50, 225/45		Orig.-Verschr.
		43	-	85-140	215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
7,5 x 18	RC32	45	-	85-140	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC30	45	ZP560D	85-140	215/50, 225/45, 225/50, 235/45, 245/45		
	B32	45	ZP560D	85-140	215/50, 225/45, 225/50, 235/45, 245/45		
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		4drive
	B39	35	ZP560D	85-140	215/50, 225/45, 235/45		ohne Radhausverbr. ✖
		45	ZP560D	85-140	215/50, 225/45, 225/50, 235/45, 245/45		ohne Radhausverbr. bei 225/50 u. 245/45 ✖
8 x 18	Oxigin 18	37+45	-	85-140	215/45, 215/50, 215/55, 225/45, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr., ET37 bei 225/50 u. ab 235/50 ✖
	RC27	40	-	85-140	215/45, 225/45, 235/45		Orig.-Verschr., auch Allrad
		44	-	85-221	215/45, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., auch Allrad
		46	-	85-140	215/45, 225/45, 225/50, 235/45, 235/50, 245/40, 245/45, 255/45		Orig.-Verschr., auch Allrad
	RC29	44	-	85, 110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., Frontantrieb
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Ateca 4drive
	RC32	40	-	85-140	215/45, 225/45		Orig.-Verschr., mit Verbreiterung
		44	-	85-140	215/45, 225/45, 235/40, 235/45		Orig.-Verschr., mit Verbreiterung
	RC34	40	-	81-140	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., ohne Verbr. ab 225/50 ✖
		45	-	81-140	225/45, 235/45		Orig.-Verschr.
	B38	44	-	85-140	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr. auch Ateca 4drive
	AC-521	45	- +R	81-110	215/50, 225/45, 235/45		Orig.-Verschr. + Ringe BA25=66,6-57,1 , incl. ab Modell 2021, Frontantrieb, ohne Radhausverbr.
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Ringe BA25=66,6-57,1 , incl. ab Modell 2021, Ateca 4drive, mit Radhausverbr.
	AF20	35	AV1	85-140	225/45		
	CA 17	45	ZP560D	85-221	215/45, 225/45, 225/50, 235/45, 235/50, 245/40, 245/45, 255/45		nicht Bremse 370x32mm
7,5 x 19	B39	33+43	ZP560D	85-140	225/40, 225/45		auch Allrad, ET33 ohne Radhausverbr. ✖
	Oxigin 18	37	-	85-140	225/40, 225/45		Orig.-Verschr.
8 x 19	RC27	45	-	85, 110	235/40		Orig.-Verschr., Frontantrieb, incl. Modell ab 2021
				110, 140	225/45 , 245/40		Orig.-Verschr., 4drive, incl. Modell ab 2021
	RC32	45	-	85-140	225/45 , 235/40 , 245/40		Orig.-Verschr., auch Allrad
				85-140	225/45 , 235/40 , 245/40		
	RC34	45	-	81-140	225/40, 225/45, 235/40		Orig.-Verschr.
				81-140	225/40, 225/45, 235/40		
	B40	45	-	85, 110	225/40, 225/45, 235/40 , 245/35, 245/40		Orig.-Verschr., incl. ab Modell 2021, Frontantrieb, ohne Radhausverbr. ab 235/40 ✖
				110, 140	225/40, 225/45 , 235/40, 245/40		Orig.-Verschr., incl. ab Modell 2021, Allrad, mit Radhausverbreiterungen
	B43	45	-	85, 110	235/40		Orig.-Verschr., incl. Modell ab 2021
				110, 140	225/45 , 245/40		Orig.-Verschr., 4drive, incl. Modell ab 2021
	RC27	44	-	85-221	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	RC29	40	-	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb, ohne Radhausverbr. ✖
				110, 140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., 4drive, bei 245/40 ✖
	RC32	40	-	81-140	225/40, 225/45		Orig.-Verschr.
		44	-	81-140	225/40, 225/45, 235/40		Orig.-Verschr.
	B38	44	-	85-140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., auch 4drive
	B40	40	-	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., incl. ab Modell 2021, Frontantrieb, ohne Radhausverbr. ✖
				110, 140	225/40, 225/45, 235/40		Orig.-Verschr., incl. ab Modell 2021, Allrad, mit Radhausverbreiterungen
	B43	47	-	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., incl. ab Modell 2021, Frontantrieb, mit Radhausverbreiterungen
				110, 140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., incl. ab Modell 2021, Allrad, mit Radhausverbreiterungen
	RC34	43	ZP560D	85-140	225/40, 225/45, 235/40		ohne Radhausverbr. bei 235/40 ✖
	AC-518	47	AV4	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Frontantrieb, mit Radhausverbreiterungen
				110, 140	225/40, 225/45, 235/40, 245/40		Allrad, mit Radhausverbreiterungen
	AC-521	45	-	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb, mit Radhausverbr.
				110, 140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Allrad, mit Radhausverbr.
	CA 17	37	ZP560D	85-221	225/40, 225/45		
		45	ZP560D	85-221	225/40, 225/45, 235/40, 245/35, 245/40		
	CA 19	47	ZP560D	81-140	225/40, 225/45, 235/40, 245/35, 245/40		
8,5 x 19	B32	42	-	85, 110	225/40, 225/45, 235/40		Orig.-Verschr.
				110, 140	225/40, 225/45, 235/40		Orig.-Verschr., 4drive
	B36 / B37	45	ZP560D	85-140	225/40, 225/45, 235/40		auch Allrad
	AF20	40	- +R	85, 110	225/40, 225/45, 235/40		Orig.-Verschr. + Red.Ringe 66,6-57,1 , Frontantrieb, mit Radhausverbr.
				110, 140	225/40, 225/45		Orig.-Verschr. + Red.Ringe 66,6-57,1 , Allrad, mit Radhausverbr.

9 x 19	Oxigin 20 / 23	45	ZP560D	85-221	225/40, 225/45, 235/40, 245/35, 245/40		auch Allrad, nicht Bremse 370x32mm
	Oxigin 25	45	ZP560D	85-221	225/40, 225/45, 235/40, 245/35, 245/40		nicht Bremse 370mm
	CA 17	45	ZP560D	85-221	225/40, 235/40		nicht Bremse 370mm
	CA 19	43+44	ZP560D	81-140	225/40, 235/40		
8 x 20	B38	40+41	-	85, 110	225/35, 235/35, 245/30, 245/35		Orig.-Verschr., ohne Verbr. ⚡, Frontantrieb
				110, 140	225/35, 235/35, 245/35		Orig.-Verschr., Ateca 4drive, bei 245/35 ⚡
	B40	40	-	85, 110	225/35, 235/35, 245/30, 245/35		Orig.-Verschr., ohne Verbr. ⚡, Frontantrieb
				110, 140	225/35, 235/35, 245/35		Orig.-Verschr., Ateca 4drive, bei 245/35 ⚡
	B43	45	-	81-110	225/35, 235/35, 245/30, 245/35		Orig.-Verschr., ohne Verbr. ab 235/35 ⚡, Frontantrieb
				110, 140	225/35, 235/35, 245/35		Orig.-Verschr., 4drive, mit Radhausverbr.
FMI08 Thoe	45	F31+R	81-140	225/35		+ Red. Ringe BA25=66,6-57,1	
8,5 x 20	RC29	40	ZP560D	85, 110	225/35, 235/35		Frontantrieb
				110, 140	225/35		4drive
	RC34	43	ZP560D	81-140	225/35		
	B24	42	ZP560D	85-140	225/35, 235/35		auch 4drive, nur mit Radhausverbr. auflagenfrei!
	B32	45	ZP560D	85-140	235/35		4drive
	B42	45	ZP560D	81-140	225/35, 235/35		Frontantrieb ohne Radhausverbr. bei 235/35 ⚡
	AC-518	45	- +R	81-140	225/35, 235/35		Orig.-Verschr. + Ringe BA25=66,6-57,1, ohne Radhausverbr. bei 235/35 ⚡
	AC-521	45	-	85-140	225/35, 235/35		Orig.-Verschr., ohne Radhausverbr. bei 235/35 ⚡
	AF18	45	- +R	85-140	225/35, 235/35		+ Ringe BA25,ohne Radhausverbr. bei 235/35 ⚡
	CA 17	40+48	ZP560D	85-221	225/35, 235/35		nicht Bremse 370x32mm
	CA 19	45	ZP560D	81-140	235/35, 245/30, 245/35		
	Oxigin 14	45	ZP560	85-140	225/35, 235/35, 245/30, 245/35		
9 x 20	Oxigin 19	45	ZP560D	85-140	225/35, 235/35		auch 4drive
	Oxigin 25	45	ZP560D	85-221	225/35, 235/35		nicht Bremse 370mm
	Oxigin 26	45	ZP560D	81-140	235/35		

Ateca Cupra							
ab 2018				5FP	5/112	57,1	e9*2007/46*6394*11....
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 18	RC27	45	-	221	225/50		Orig.-Verschr.
	RC32	45	-	110-221	225/45, 215/50, 225/50		Orig.-Verschr., nicht Bremse 370mm
	RC34	45	-	221	225/50		Orig.-Verschr., nicht Bremse 370x32mm
	RC32	40	-	110-221	225/50		Orig.-Verschr., nicht Bremse 370x32mm
	RC34	43	-	221	225/45, 225/50		Orig.-Verschr., nicht Bremse 370mm
		43	-	110-221	225/50		Orig.-Verschr., nicht Bremse 370x32mm
7,5 x 18	RC32	45	-	110-221	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370mm
	RC34	46	-	110-221	225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370mm
	B32 / B39	45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
	AC-MB6	45	- +R	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
8 x 18	RC32	40	-	110-221	225/45		Orig.-Verschr.
		44	-	221	225/45, 235/40, 235/45		Orig.-Verschr.
	RC34	40	-	221	225/50, 235/45, 245/45		Orig.-Verschr.
		45	-	110-221	225/50, 235/45, 245/45, 255/45		Orig.-Verschr.
	B37	44	-	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370mm
	B38	44	-	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370mm
	RC29	44	-	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., nicht Bremse 370mm
		45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
	RC34	40	ZP560D	221	225/50, 235/45, 245/45		
		43	ZP560D	110-221	225/50, 235/45, 245/45, 255/45		
	B36	45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
	B42 / B44	45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
	AC-M10	40	- +R	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
		45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
	AC-518	40	AV4+R	221	225/45, 235/45		nicht Bremse 370mm, + Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	221	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	221	225/45, 235/45		nicht Bremse 370mm
	AF20	35	AV1	221	225/45		nicht Bremse 370mm
	CA 20	45	ZP560D	221	225/45, 225/50, 235/45, 245/45		nicht Bremse 370mm
7 x 19	RC27	43	-	221	225/45		Orig.-Verschr., nicht Bremse 370mm
7,5 x 19	B32	43	-	221	225/40, 225/45		Orig.-Verschr., nicht Bremse 370mm
	RC34	45,5	ZP560D	110-221	225/45		
	RC27	45	-	221	225/45, 245/40		Orig.-Verschr., nicht Bremse 370mm
	RC32	45	-	221	225/45, 245/40		Orig.-Verschr.
	RC34	45	-	110-221	225/45, 235/40, 245/40		Orig.-Verschr.
				110-221	225/45, 235/40, 245/40		
	B40	45	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 370mm
	B43	45	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 370 mm
	RC29	40	-	221	225/40, 225/45, 235/40		Orig.-Verschr.

8 x 19	RC32	40	-	110-221	225/45, 235/40, 245/40		Orig.-Verschr.
		44	-	110-221	225/45, 235/40, 245/40		Orig.-Verschr.
	RC34	40	-	110-221	225/45, 235/40, 245/40		Orig.-Verschr.
	B38	44	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr.
	B40	40	-	221	225/40, 225/45, 235/40		Orig.-Verschr.
	B43	40	-	221	225/40, 225/45, 235/40		Orig.-Verschr.
	RC29	45	ZP560D	221	225/40, 225/45, 235/40, 245/40		nicht Bremse 370mm
	RC34	38	ZP560D	221	225/45, 235/40		
		43	ZP560D	110-221	225/45, 235/40, 245/40		
	B24	45	ZP560D	221	225/40, 225/45, 235/40, 245/40		nicht Bremse 370mm
	B38	45	ZP560D	221	225/40, 225/45, 235/40, 245/40		nicht Bremse 370mm
	AC-521	35	- +R	221	225/40, 225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., nicht Bremse 370 mm
	CA 17	45	ZP560D	221	225/40, 225/45, 235/40, 245/35, 245/40		nicht Brembo-Bremse
	CA 19	47	ZP560D	221	225/40, 225/45, 235/40, 245/35, 245/40		nicht Brembo-Bremse
	FMI07 Atena	47	- +R	221	225/45, 235/40, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 19	Oxigin 29	43	ZP560D	221	225/40, 225/45, 235/40, 245/40		
	B32	42	-	221	225/40, 225/45, 235/40		Orig.-Verschr.
		36	ZP560D	221	225/45		
	B41	39	ZP560D	221	225/45, 235/40		
		42	ZP560D	221	225/40, 225/45, 235/40		nicht Bremse 370mm
	B42	42	ZP560D	221	225/40, 225/45, 235/40		nicht Bremse 370mm
	B43	38	ZP568F	221	225/40, 225/45		
	B44	42	ZP560D	221	225/40, 225/45, 235/40		nicht Bremse 370mm
	AC-M10	45	AV4+R	221	225/40, 225/45, 235/40, 245/40		+ Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	221	225/40, 225/45		
	AF20	40	- +R	221	225/40, 225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 23	40	- +R	221	225/40, 225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	ZP560D	221	225/40, 225/45, 235/40, 245/40		nicht Bremse 370mm
	FMI07 Atena	45	- +R	221	225/45, 235/40, 245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 18	45	ZP560D	221	225/40, 225/45, 235/40		nicht Bremse 340 u. 370mm
	Oxigin 28	40	ZP560D	221	225/40, 225/45		nicht Bremse 370mm
		45	ZP560D	221	225/40, 225/45, 235/40, 245/40		nicht Bremse 370mm
9 x 19	CA 19	43+44	ZP560D	221	225/40, 235/40		
	FMI08 Thoe	41	F31+R	221	235/40		+ Red.Ringe BA25=66,6-57,1
8 x 20	B38	40+41	-	221	225/35, 235/35		Orig.-Verschr., ET41 nicht Bremse 370mm
	B40	40+41	-	221	225/35, 235/35		Orig.-Verschr., ET41 nicht Bremse 370mm
	B43	41+45	-	221	225/35, 235/35, 245/35		Orig.-Verschr., ET45 nicht Bremse 370mm
	FMI08 Thoe	45	F31+R	221	225/35, 225/40, 235/35, 245/35		+ Red.Ringe BA25, nicht Bremse 370x32mm
8,5 x 20	B43	38+40	-	221	225/35		Orig.-Verschr.
	RC29	45	ZP560D	221	225/35, 235/35		
		38	ZP568F	221	225/35, 225/40, 235/35		
	RC34	43	ZP560D	221	225/35, 225/40, 235/35, 245/35		
		42	ZP560D	221	225/35, 235/35		
	B24	45	ZP560D	221	235/35		
	B41	35	ZP560D	110-221	225/35, 225/40		
		40	ZP560D	221	225/35		nicht Bremse 370mm
	B42	45	ZP560D	221	225/35, 235/35		nicht Bremse 370mm
		40	ZP560D	221	225/35		
	B43	40	ZP560D	221	225/35		
	B44	40	ZP560D	221	225/35		nicht Bremse 370mm
	AC-518	45	- +R	221	225/35, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	45	-	221	225/35, 235/35		Orig.-Verschr.
	AC-M10	40	- +R	221	225/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	45	- +R	221	225/35, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nicht Bremse 370mm
	CA 17	48	ZP560D	221	225/35, 235/35		nicht Bremse 370x32mm
	CA 19	45	ZP560D	221	235/35, 245/30, 245/35		nicht Brembo-Bremse
	FMI07 Atena	39	- +R	221	225/35, 225/40, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	B41	38	ZP560D	221	225/35, 225/40		
	FMI11 Elatha	46	- +R	221	235/35, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 26	45	ZP560D	221	235/35		
	Oxigin 28	45	ZP560D	221	225/35		nicht Bremse 370mm
8,5 x 21	B41	43	ZP560D	221	245/30		nicht Bremse 370x32mm

Ateca Cupra VZ-Edition							
				5FP	5/112	57,1	e9*2007/46*6394*23-...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	B40	45	-	221	225/45M+S, 245/40		Orig.-Verschr., mit Zusatzverbreiterungen
	RC29	40	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., mit Zusatzverbreiterungen, bis 235/40 nur M+S
	B40	40	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., mit Zusatzverbreiterungen, bis 235/40 nur M+S
	B43	40	-	221	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., mit Zusatzverbreiterungen, bis 235/40 nur M+S
	B40	38	ZP560D	221	225/40, 225/45, 235/40, 245/40		mit Zusatzverbreiterungen, bis 235/40 nur M+S

	AC-521	35	- +R	221	225/40, 225/45, 235/40, 245/40	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , mit Zusatzverbreiterungen, bis 235/40 nur M+S
	Oxigin 29	32	ZP560D	221	225/40, 225/45, 235/40	nur M+S, mit Zusatzverbreiterungen
		39+43	ZP560D	221	225/40, 225/45, 235/40, 245/40	mit Zusatzverbreiterungen, bis 235/40 nur M+S
8,5 x 19	B32	42	-	221	225/40, 225/45, 235/40, 245/40	Orig.-Verschr., bis 235/40 nur M+S, mit Zusatzverbreiterungen
	B32	34,5	ZP560D	221	225/40, 225/45, 235/40	nur M+S, mit Zusatzverbreiterungen
		45	ZP560D	221	225/40, 225/45, 235/40, 245/40	bis 235/40 nur M+S, mit Zusatzverbreiterungen
	B42	42	ZP560D	221	225/40, 225/45, 235/40, 245/40	bis 235/40 nur M+S, mit Zusatzverbreiterungen
	B43	38	ZP568F	221	225/40, 225/45, 235/40, 245/40	bis 235/40 nur M+S, mit Zusatzverbreiterungen
	B44	35	ZP560D	221	225/40, 225/45, 235/40	nur M+S, mit Zusatzverbreiterungen
	AC-M10	45	AV4+R	221	225/40, 225/45, 235/40, 245/40	+ Red.Ringe BA25=66,6-57,1 , mit Zusatzverbreiterungen, bis 235/40 nur M+S
8 x 20	CA 23	40	- +R	221	225/40, 225/45, 235/40, 245/40	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , mit Zusatzverbreiterungen, bis 235/40 nur M+S
	RC36	38	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S, mit Verbreiter.
	B43	41	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S, mit Verbreiter.
8,5 x 20	B43	38+40	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S
	B24	42	ZP560D	221	225/35, 235/35	
	B42	35	ZP560D	221	225/35, 235/35	nur M+S, mit Zusatzverbreiterungen
	B43	40	ZP560D	221	225/35, 235/35, 245/35	bis 235/35 nur M+S
	B44	35	ZP560D	221	225/35, 235/35	nur M+S, mit Zusatzverbreiterungen
	AC-521	45	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S
	B43	42	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S
9 x 20	AC-521	42	-	221	225/35, 235/35, 245/35	Orig.-Verschr., bis 235/35 nur M+S
8,5 x 21	B43	40	-	221	245/30	Orig.-Verschr., mit Zusatzverbreiterungen

Ateca Cupra 1,5TSI					5FP	5/112	57,1	e9*2007/46*6394*40-...	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 17	RC27	45	-	110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., nur M+S, Frontantrieb		
	CA 26	45	-	110	215/55M+S		Orig.-Verschr., nur M+S, Frontantrieb		
	RC27	35	-	110	215/55, 215/60, 225/50, 225/55		Orig.-Verschr., nur M+S, Frontantrieb		
		40+42	-	110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., nur M+S, Frontantrieb		
	B39	40	-	110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., nur M+S, Frontantrieb		
7,5 x 17	CA 26	42	ZP560D	110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		nur M+S, Frontantrieb		
	RC27	40	-	110	215/55, 215/60, 225/50, 225/55, 245/45		Orig.-Verschr., nur M+S, Frontantrieb		
	CA 20	45	- +R	110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, Frontantrieb		
7 x 18	RC27	45	-	110	215/50M+S, 225/45, 225/50		Orig.-Verschr., nur M+S, Frontantrieb		
		43	-	110	215/50, 225/45, 225/50		Orig.-Verschr., nur M+S, Frontantrieb		
7,5 x 18	RC30	35	ZP560D	110	215/50, 225/45, 235/45		nur M+S, Frontantrieb		
		45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/45		nur M+S, Frontantrieb		
	B32 / B39	45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/45		nur M+S, Frontantrieb		
		AC-MB6 / AC-M10	45	- +R	110	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, Frontantrieb	
8 x 18	RC27	40+44	-	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., nur M+S, Frontantrieb		
	B36 / B42	45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
	B44	45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
		45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
	AC-MB6	45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
		AC-M10	40	- +R	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S, Frontantrieb	
	45		ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
7,5 x 19	CA 20	45	ZP560D	110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		nur M+S, Frontantrieb		
	CA 26	40	ZP560D	110	225/40, 225/45		nur M+S, Frontantrieb		
	8 x 19	RC27	45	-	110	235/40		Orig.-Verschr., Frontantrieb	
B40		45	-	110	225/40M+S, 225/45M+S, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb		
		45	-	110	235/40		Orig.-Verschr., Frontantrieb		
B43		-	-	110	225/40M+S, 225/45M+S, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb		
		40	-	110	225/40M+S, 225/45M+S, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb		
B40		38	ZP560D	110	225/40M+S, 225/45M+S, 235/40		Frontantrieb		
		43	ZP560D	110	225/40M+S, 225/45M+S, 235/40, 245/35, 245/40		Frontantrieb		
Oxigin 29	39	ZP560D	110	225/40M+S, 225/45M+S, 235/40		Frontantrieb			
	43	ZP560D	110	225/40M+S, 225/45M+S, 235/40, 245/35, 245/40		Frontantrieb			
	8,5 x 19	B32	42	-	110	225/40M+S, 225/45M+S, 235/40		Orig.-Verschr., Frontantrieb	
B32 / B36		45	ZP560D	110	225/40M+S, 225/45M+S, 235/40		Frontantrieb		
		42	ZP560D	110	225/40M+S, 225/45M+S, 235/40		Frontantrieb		
AC-M10		45	AV4+R	110	225/40M+S, 225/45M+S, 235/40		+ Red.Ringe BA25=66,6-57,1, Frontantrieb		
8 x 20	RC36	41+45	-	110	225/35M+S, 235/35, 245/30, 245/35		Orig.-Verschr., Frontantrieb		
	B43	41+45	-	110	225/35M+S, 235/35, 245/30, 245/35		Orig.-Verschr., Frontantrieb		
8,5 x 20	B42 / B44	40	ZP560D	110	225/35M+S, 235/35		Frontantrieb		
	AC-M10	40	- +R	110	225/35M+S, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1		
Ateca Cupra 2,0TSI					5FP	5/112	57,1	e9*2007/46*6394*40-...	

Ateca Cupra 2,0TSI							5FP	5/112	57,1	e9*2007/46*6394*40-..
--------------------	--	--	--	--	--	--	-----	-------	------	-----------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 18	RC27	45	-	140	225/45, 225/50		Orig.-Verschr., nur M+S
		43	-	140	225/45, 225/50		Orig.-Verschr., nur M+S
7,5 x 18	RC30	35	ZP560D	140	225/45, 235/45		nur M+S
		45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
	B32 / B39	45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
		45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
8 x 18	AC-MB6 / AC-M10	45	- +R	140	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	RC27	40+44	-	140	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., nur M+S
	B36 / B42	45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
	B44	45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
	AC-MB6	45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
	AC-M10	40	- +R	140	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, nur M+S
		45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
	CA 20	45	ZP560D	140	225/45, 225/50, 235/45, 245/45		nur M+S
7,5 x 19	CA 26	40	ZP560D	140	225/40, 225/45		nur M+S
	RC27	45	-	140	225/45M+S, 245/40		Orig.-Verschr.
	B40	45	-	140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., bis 235/40 nur M+S
8 x 19	B43	45	-	140	225/45M+S, 245/40		Orig.-Verschr.
		45	-	140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., bis 235/40 nur M+S
	B40	40	-	140	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., bis 235/40 nur M+S
		38	ZP560D	140	225/40, 225/45, 235/40		nur M+S
	Oxigin 29	43	ZP560D	140	225/40, 225/45, 235/40, 245/35, 245/40		bis 235/40 nur M+S
		39	ZP560D	140	225/40, 225/45, 235/40		nur M+S
		43	ZP560D	140	225/40, 225/45, 235/40, 245/40		bis 235/40 nur M+S
8,5 x 19	B32	42	-	140	225/40, 225/45, 235/40		Orig.-Verschr., nur M+S
	B32 / B36	45	ZP560D	140	225/40, 225/45, 235/40, 245/40		bis 235/40 nur M+S
	B42 / B44	42	ZP560D	140	225/40, 225/45, 235/40		nur M+S
	AC-M10	45	AV4+R	140	225/40, 225/45, 235/40, 245/40		+ Red.Ringe BA25=66,6-57,1,bis 235/40 nur M+S
8 x 20	RC36	41+45	-	140	225/35M+S, 235/35M+S, 245/35		Orig.-Verschr.
	B43	41+45	-	140	225/35M+S, 235/35M+S, 245/35		Orig.-Verschr.
8,5 x 20	B42 / B44	40	ZP560D	140	225/35M+S		
	AC-M10	40	- +R	140	225/35M+S		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1

Ibiza

ab 06.2017

KJ

5/100

57,1

e9*2007/46*3134*..

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
5 x 14	RC30	38	-	48-70	185/70 , 185/75, 195/70		Orig.-Verschr.
5,5 x 15	RC19	40	-	48-110	185/65 , 195/60, 195/65		Orig.-Verschr.
6 x 15	RC24	38	-	48-110	185/65		Orig.-Verschr.
	RC27	38	-	48-110	185/65		Orig.-Verschr.
6 x 16	RC30	38	-	48-110	185/65		Orig.-Verschr.
	RC27	45	-	48-110	185/55, 185/60 , 195/55		Orig.-Verschr.
	RC30	45	-	48-110	185/55, 185/60 , 195/55		Orig.-Verschr.
	RC34	45	-	48-110	185/55, 185/60 , 195/55 , 205/50, 205/55, 215/50		Orig.-Verschr.
	RC27	38	-	48-110	185/55, 185/60		Orig.-Verschr.
	RC30	38	-	48-110	185/55, 185/60		Orig.-Verschr.
	RC34	35	-	48-110	185/55, 185/60		Orig.-Verschr.
		40	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.
	RC27	47	-	48-85	195/55		Orig.-Verschr.
	RC30	47	-	48-110	185/55, 185/60 , 195/55		Orig.-Verschr.
6,5 x 16	RC32	47	-	48-110	185/55, 185/60, 195/55 , 205/50, 205/55, 215/50		Orig.-Verschr.
	RC34	47	-	48-110	185/55, 185/60 , 195/55 , 205/50, 205/55, 215/50		Orig.-Verschr.
	RC27	40	-	48-110	185/55, 185/60		Orig.-Verschr.
		47	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.
6,5 x 17	RC34	40	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.
	RC27	48	-	48-110	185/50, 205/45		Orig.-Verschr.
7 x 17	RC27	51	-	48-110	205/45, 215/45		Orig.-Verschr.
	RC30	51	-	48-110	205/45, 215/45		Orig.-Verschr.
	RC32	51	-	48-110	195/45, 195/50, 205/45, 215/40, 215/45 , 225/45		Orig.-Verschr.
	RC34	51	-	48-110	215/45		Orig.-Verschr.
	CA 26	51	-	48-110	205/45, 215/45		Orig.-Verschr.
	RC30	46	-	48-110	205/45		Orig.-Verschr.
	B39	46	-	48-110	205/45		Orig.-Verschr.
7,5 x 17	RC27	46+51	-	48-110	195/45, 205/45		Orig.-Verschr.
7 x 18	Oxigin 25	51	ZP516	48-110	195/45, 205/45		
	RC32	51	-	48-110	205/40, 215/35, 215/40		Orig.-Verschr.
	RC34	51	-	48-110	215/40		Orig.-Verschr.
	RC32	47	-	48-110	205/40, 215/35, 215/40		Orig.-Verschr.
7,5 x 18	RC32	46+51	-	48-110	205/35, 205/40, 215/35, 215/40		Orig.-Verschr.

Leon (siehe Konfigurator)

ab 11.12

5F

5/112

57,1

e9*2007/46*0094*..

Leon X-Perience (siehe Konfigurator)	ab 2014	5F	5/112	57,1	e9*2007/46*0094*...
---	----------------	-----------	--------------	-------------	---------------------

Leon Cupra (siehe Konfigurator)	ab 2014	5F	5/112	57,1	e9*2007/46*0094*...
--	----------------	-----------	--------------	-------------	---------------------

Leon	ab 04.2020	KL	5/112	57,1	e9*2007/46*3167*27
-------------	-------------------	-----------	--------------	-------------	--------------------

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC27	43	-	66-85	195/65 , 205/60		Orig.-Verschr., nicht Bremse 312 mm
	RC30	43	-	66-85	195/65 , 205/60		Orig.-Verschr., nicht Bremse 312 mm, incl. Sportstourer
	RC24	43	-	66-85	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
		47	-	66-85	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
	RC27	47	-	66-85	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
	RC30	47	-	66-85	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
6 x 16	RC27	43+48	-	66-85	205/55, 215/55		Orig.-Verschr., incl. Sportstourer
	RC30	43+48	-	66-85	205/55, 215/55		Orig.-Verschr., ET48 incl. Sportstourer
	RC34	43+48	-	66-85	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55		Orig.-Verschr., auch Sportstourer
6,5 x 16	RC27	46	-	66-110	205/55 , 215/55, 225/50		Orig.-Verschr., incl. Sportstourer
	RC30	46	-	66-110	205/55 , 215/55, 225/50		Orig.-Verschr.
	RC32	46	-	66-110	195/55, 195/60, 205/55 , 205/60, 215/50, 215/55, 225/50, 225/55		Orig.-Verschr., auch Sportstourer
	RC34	46	-	66-110	195/55, 195/60, 205/55 , 205/60, 215/50, 215/55, 225/50, 225/55		Orig.-Verschr., auch Sportstourer, mit Verbundlenker-Hinterachse
	RC24	42+43	-	66-110	205/55, 215/55		Orig.-Verschr.
	RC27	44	-	66-110	205/55, 215/55, 225/50		Orig.-Verschr.
	RC30	41	-	66-110	205/55, 215/55		Orig.-Verschr., incl. Sportstourer
		42+44+48	-	66-110	205/55, 215/55, 225/50		Orig.-Verschr., ET42 bei 225/50 ✖
	RC32	48	-	66-110	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55, 235/50		Orig.-Verschr., auch Sportstourer
	RC34	43	-	66-110	195/55, 195/60, 205/55, 205/60, 215/50, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
	CA 20	45	ZP560D	66-110	205/55, 215/55, 225/50		
	Pro1	48	ZP562D	66-110	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55, 235/50		auch Sportstourer, mit Verbundlenker-Hinterachse
				110	225/50, 235/50		auch Sportstourer, mit Mehrlenker-Hinterachse
7 x 16	RC30	43	-	66-110	205/55 , 215/55		Orig.-Verschr., incl. Sportstourer
		48	-	66-110	205/55, 215/55, 225/50		Orig.-Verschr.
6,5 x 17	RC27	39+43+46+48,5	-	66-110	205/50		Orig.-Verschr.
7 x 17	RC27	40+42+43+46+47	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Sportstourer
	RC30	38	-	66-110	215/45		Orig.-Verschr.
		40+45	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	45+47	-	66-110	195/50, 195/55, 205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
		46	-	66-110	195/50, 195/55, 205/45, 205/50, 215/45, 215/50, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
	CA 26	45	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Sportstourer
		42+47	ZP560D	66-110	205/50, 215/45, 225/45		incl. Sportstourer
7,5 x 17	RC32	46	-	66-140	205/45, 205/50 , 215/45, 215/50, 225/45 , 235/45		Orig.-Verschr., auch Sportstourer
				110	225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	46	-	66-110	205/45, 205/50 , 215/45, 215/50, 225/45 , 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/50 , 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC24	42	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC32	43	-	66-110	205/45, 205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	47	-	66-110	205/45, 205/50, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC28	45	ZP560D	66-140	205/50, 215/45, 225/45, 235/45		
				110	205/50, 215/45		
	RC30	47	ZP560D	66-110	205/50, 215/45, 225/45		
	RC34	40	ZP560D	66-110	205/45, 215/45		mit Verbundlenker-Hinterachse
				110	225/45		mit Mehrlenker-Hinterachse
		45	ZP560D	66-110	205/45, 205/50, 215/45, 225/45		mit Verbundlenker-Hinterachse
				110	225/45		mit Mehrlenker-Hinterachse
	B24	47	ZP560D	66-110	205/50, 215/45, 225/45, 235/45		incl. Sportstourer
	Oxigin 25	45	ZP560D	66-140	205/45, 205/50, 215/45, 215/50		
				66-140	225/45, 235/45		
	RC32	40	-	66-110	195/50, 205/40, 205/45, 215/40, 215/45		Orig.-Verschr., auch Sportstourer

7 x 18		45	-	66-110	205/40, 205/45, 215/40		Orig.-Verschr.
	RC34	43	-	66-110	205/40, 205/45, 215/40, 245/45		Orig.-Verschr., auch Sportstourer
7,5 x 18	RC34	46	-	81-110	225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		46	-	66-110	205/40, 205/45, 215/40, 215/45, 225/35, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B32	46	-	66-110	225/40		Orig.-Verschr., auch Sportstourer
	RC32	45+48+50	-	66-110	205/40, 205/45, 215/40, 215/45, 225/35, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	50	-	66-110	205/40, 205/45, 215/40, 215/45, 225/35, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC30	45	ZP560D	66-110	205/45, 215/40, 225/35, 225/40		
	B32	45	ZP560D	110, 140	205/45, 215/40, 225/35, 225/40		nur M+S
				66-110	205/45, 215/40, 225/35, 225/40		
8 x 18	B39	45	ZP560D	66-110	205/45, 215/40, 225/35, 225/40		mit Verbundlenker-Hinterachse, incl. Sportstourer
				110	205/45, 215/40		
				110, 140	205/45M+S, 215/40M+S, 225/40		mit Mehrlenker-Hinterachse
	RC29	45	ZP560D	66-110	215/40, 225/35, 225/40		incl. Sportstourer
	RC34	40	ZP560D	66-110	205/40, 205/45		
		43	ZP560D	66-110	205/40, 205/45, 215/40, 215/45		
		48	ZP560D	66-110	205/40, 205/45, 215/40, 215/45, 225/35, 225/40		incl. Sportstourer u. Hybrid
	B24	48	ZP560D	66-110	215/40, 225/35, 225/40		incl. Sportstourer
				110	215/40		
				110, 140	215/40M+S, 225/40		
	B36 / B42	45	ZP560D	66-110	215/40, 225/35, 225/40		incl. Sportstourer
				110	215/40		
				110, 140	215/40M+S, 225/40		
	B38	45	ZP560D	66-110	215/40, 225/35, 225/40		
				66-110	215/40, 225/35, 225/40		incl. Sportstourer
	B44	45	ZP560D	110	215/40		
				110, 140	215/40M+S, 225/40		
	AC-521	45	- +R	66-110	215/40, 225/35, 225/40		Orig.-Verschr. + BA25, incl. Sportstourer
				110	215/40		
				110, 140	215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-M10	45	ZP560D	66-110	215/40, 225/35, 225/40		incl. Sportstourer
				110	215/40		
	AF20	48	-	110, 140	215/40M+S, 225/40		
				66-110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Sportstourer
				66-110	215/40, 225/35, 225/40		incl. Sportstourer, mit Verbundlenker-HA
	CA 20	45	ZP560D	110	215/40		
				110, 140	215/40M+S, 225/40		mit Mehrlenker-Hinterachse
				66-110	205/40, 205/45, 215/40, 215/45, 225/35, 225/40, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1, mit Verbundlenker-Hinterachse
	FMI08 Thoe	49	F31+R	110-140	225/35, 225/40, 235/35		+ Red.Ringe BA25, mit Mehrlenker-Hinterachse
				66-110	205/40, 205/45		mit Verbundlenker-Hinterachse
	FMI11 Elatha	39	F95	66-110	205/40, 205/45		
8,5 x 18	B32	48	ZP560D	66-110	215/40, 225/35, 225/40		
7,5 x 19	RC32	50	-	66-110	215/35, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	48+50	-	66-110	215/35, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B32	43	-	66-110	215/35, 225/35		Orig.-Verschr., incl. Sportstourer
	RC34	45,5	ZP560D	66-110	215/35, 225/35		mit Verbundlenker-Hinterachse
				110-140	225/35		mit Mehrlenker-Hinterachse
8 x 19	Oxigin 18	50	ZP560D	66-110	225/35		auch Hybrid
	RC34	49	-	110	235/35		Orig.-Verschr., mit Mehrlenkerachse
	RC32	50	-	66-110	215/35, 225/30, 225/35		Orig.-Verschr., incl. Sportstourer, mit Verbundlenker-Hinterachse
				110-140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
	RC34	45	-	66-110	215/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse ✖
		50	-	66-110	215/35, 225/30, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B40	45	-	66-110	215/35, 225/35		Orig.-Verschr.
	B43	45+47	-	66-110	215/35, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	AC-521	45	-	66-110	215/35, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	CA 17	45	ZP560D	66-110	225/35		auch Sportstourer u. Hybrid
	CA 19	47	ZP560D	66-140	225/35, 235/35		
8,5 x 19	B42	47	ZP560D	66-110	215/35, 225/35		incl. Sportstourer
8 x 20	B43	45	-	66-140	225/30		Orig.-Verschr., incl. Sportstourer

Leon NEU		ab Facelift 2024		KL	5/112	57,1	e9*2007/46*3167*28-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	46	-	85, 110	205/55			Orig.-Verschr., incl. Sportstourer
6,5 x 17	RC27	46	-	85, 110	205/50			Orig.-Verschr., incl. Sportstourer
7 x 17	CA 26	45	-	85, 110	205/50, 215/45, 225/45			Orig.-Verschr., incl. Sportstourer
		42+47	ZP560D	85, 110	205/50, 215/45, 225/45			incl. Sportstourer
7,5 x 18	B39	45	ZP560D	85, 110	205/45, 215/40, 225/40			incl. Sportstourer
8 x 18	RC27	46	-	85, 110	215/40, 225/40			Orig.-Verschr., incl. Sportstourer

Leon Cupra, Cupra Sportstourer				ab 04.2020	KL	5/112	57,1	e9*2007/46*3167*27		
kein Sensor - indirektes RDKS										
Dimension	Design	ET	KIT	KW	Reifendimension			Info		
6,5 x 16	Pro1	48	ZP562D	110	205/55, 215/50, 215/55, 225/50, 235/50				auch Sportstourer	
7 x 16	RC30	43	-	66-110	205/55, 215/55				Orig.-Verschr., incl. Sportstourer	
	RC27	38	-	66-110	205/50				Orig.-Verschr., incl. Sportstourer	
6,5 x 17	RC34	38+46	-	110	205/45, 205/50, 215/50				Orig.-Verschr., nicht Brembo Bremse mit 370x32mm, auch für Hybrid	
7 x 17	RC32	38	-	110-228	225/45				Orig.-Verschr., nur M+S, nicht Brembo Bremse mit 370x32mm, auch für Hybrid	
		40+45+49	-	110	225/45				Orig.-Verschr., nur M+S, nicht Brembo Bremse mit 370x32mm	
		47	-	110-228	225/45				Orig.-Verschr., nur M+S, nicht Brembo Bremse mit 370x32mm, auch für Hybrid	
	B39	40	-	110	205/50, 215/45, 225/45				Orig.-Verschr.	
	CA 26	47	ZP560D	110	205/50, 215/45, 225/45				auch Sportstourer	
7,5 x 17	RC32	46	-	110-228	205/50, 225/45				Orig.-Verschr., nicht Bremse 370x32mm	
	RC34	46	-	110-140	205/50, 225/45				Orig.-Verschr., nicht Bremse 370x32mm	
				110-228	205/45, 205/50, 215/45, 215/50, 225/45, 235/45					
	RC32	43	-	110	225/45, 235/45				Orig.-Verschr., nicht Bremse 370x32mm	
7 x 18	RC32	40	-	110-228	205/40, 205/45, 215/40, 215/45				Orig.-Verschr., nicht Bremse 375x36mm	
	RC34	35	-	110-228	205/40, 205/45, 215/40				Orig.-Verschr.	
		43	-	110-228	205/40, 205/45, 215/40, 215/45				Orig.-Verschr., nicht Bremse 370x32mm u. 375x36mm	
7,5 x 18	RC34	46	-	110-245	225/40				Orig.-Verschr., nicht Bremse 370x32 u. nicht 375x36mm	
			-	110-245	205/40, 205/45, 215/40, 215/45, 225/35, 225/40					
	RC32	45	-	110-245	205/40, 205/45, 215/40, 215/45, 225/35, 225/40				Orig.-Verschr., nicht Bremse 370x32 u. nicht 375x36mm	
		50	-	110-228	225/35, 225/40				Orig.-Verschr., nicht Bremse 370x32mm	
		51	-	110-245	205/40, 215/40, 215/45, 225/35, 225/40				Orig.-Verschr., nicht Bremse 370x32 u. nicht 375x36mm	
	RC34	50	-	110-228	225/35, 225/40				Orig.-Verschr., nicht Bremse 370x32mm	
8 x 18	RC34	45	-	110-245	205/40, 205/45, 215/40, 215/45, 225/35, 225/40, 235/35, 235/40				Orig.-Verschr., nicht Bremse 375x36mm	
		43	ZP560D	110-245	205/40, 205/45, 215/40, 215/45, 225/35, 225/40				nicht Bremse 375x36mm	
	FMI08 Thoe	49	F31+R	110-228	225/35, 225/40, 235/35, 235/40				+ Red.Ringe BA25, nicht Bremse 370x32mm	
7,5 x 19	RC32	50+51	-	110-245	215/35, 225/35				Orig.-Verschr., nicht Bremse 370x32mm u. nicht 375x36mm	
	RC34	48	-	110-245	215/35, 225/35				Orig.-Verschr., nicht Bremse 370x32mm	
		50	-	110-245	215/35, 225/35				Orig.-Verschr., nicht Bremse 370x32mm u. nicht 375x36mm	
		45,5	ZP560D	110-245	215/35, 225/35				nicht Bremse 375x36mm	
8 x 19	RC34	49	-	110-245	225/35, 235/35				Orig.-Verschr., nicht Bremse 375x36mm	
	FMI07 Atena	49	-	110	215/35, 225/30, 225/35, 235/35					
					B43	49	-	180-228	235/35	
	RC32	50	-	110-228	225/35 M+S, 235/35				Orig.-Verschr., nicht Bremse 370x32mm	
	RC34	50	-	110-228	215/35, 225/30, 225/35, 235/35				Orig.-Verschr., auch Hybrid	
		RC34	45	-	110-245	215/35, 225/30, 225/35				Orig.-Verschr., auch Hybrid, nicht Bremse 375x36mm
			50	-	110-245	215/35, 225/30, 225/35, 235/35				Orig.-Verschr., auch Hybrid, nicht Bremse 375x36mm
	RC34	43	ZP560D	110-245	215/35, 225/30, 225/35				auch Hybrid, nicht Bremse 375x36mm	
		48	ZP560D	110-245	215/35, 225/30, 225/35, 235/35				auch Hybrid, nicht Bremse 375x36mm	
CA 19	47	ZP560D	110-228	225/35, 235/35				nicht Brembo-Bremse		

Kombinationen

8 x 19	FMI08 Thoe	VA 47	F31+R	110-228	VA+HA 225/35		+ Red.Ringe BA25=66,6-57,1, nicht 4-Kolben Festsattel mit 370x32mm
9 x 19		HA 41					

Leon / Sportstourer Plug-in-Hybrid				ab 2020	KL	5/112	57,1	e9*2007/46*3167*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
	RC28	45	ZP560D	110	205/50, 215/45, 225/45, 235/45				bis 215/45 nur M+S
	B24	47	ZP560D	110	225/45, 235/45				

7,5 x 17	B36	45	ZP560D	110	225/45, 235/45		nicht Bremse 340mm
	CA 20	45	- +R	110	205/50, 215/45, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
7,5 x 18	B32	46	-	110	225/40		Orig.-Verschr.
	RC30	45	ZP560D	110	205/45M+S, 215/40M+S, 225/40		
	B39	45	ZP560D	110	225/40		
8 x 18	RC29	45	ZP560D	110	225/40		
	B24	48	ZP560D	110	215/40M+S, 225/40		
	B36	45	ZP560D	110	225/40		
	B42	45	ZP560D	110	215/40M+S, 225/40		
	AF20	48	-	110	225/40		Orig.-Verschr.
7,5 x 19	B32	43	-	110	215/35, 225/35		Orig.-Verschr.
8 x 19	B43	49	-	110	225/35 M+S, 235/35		Orig.-Verschr., nicht Bremse 370mm
		45+47	-	110	225/35		Orig.-Verschr., nicht Bremse 370mm
	AC-521	45	-	110	225/35		Orig.-Verschr.
8,5 x 19	B42	42+47	ZP560D	110	225/35		

Leon PHEV NEU		ab Facelift 2024		KL	5/112	57,1	e9*2007/46*3167*28-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension			Info
7,5 x 18	B39	45	ZP560D	110	225/40			incl. Sportstourer
8 x 18	RC27	46	-	110	225/40			Orig.-Verschr., incl. Sportstourer

Mii		ab 03.12		AA, AAN		4/100		57,1	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
5 x 14	RC30	35	-	44,50,55	165/70, 175/65				Orig.-Verschr.
					165/70, 175/65, 185/60, 185/65				Orig.-Verschr.
6 x 15	RC30	39	ZP436	44, 50, 55	165/70, 175/65, 185/60, 185/65				
	RC24	40	ZP436	44-55	165/60, 165/65, 175/55, 175/60, 185/55				✖
6,5 x 15	RC30	40	ZP436	44-55	165/60, 165/65, 175/55, 175/60, 185/55				
	RC28	35	ZP436	44-55	185/55, 195/50, 195/55, 205/50				✖
6 x 16	RC30	43	-	44, 50, 55	175/50, 185/50, 195/45				Orig.-Verschr.
	RC34	43	-	44-55	165/50, 175/50, 175/55, 185/50, 195/45				Orig.-Verschr.
6,5 x 16	RC24	38	ZP436	44, 50, 55	195/45				
	RC30	38	ZP436	44, 55	195/45				
6,5 x 17	RC34	43	-	44-55	195/40				Orig.-Verschr.
7 x 17	B24	38	ZP436	44-55	195/40, 215/35				✖
	B39	38	ZP436	44-55	195/40, 215/35				✖

Mii electric		ab 2019		AA	4/100	57,1	e13*2007/46*1168*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5 x 14	RC30	35	-	61	165/70, 175/65, 185/60, 185/65			Orig.-Verschr.
	RC30	39	ZP436	61	165/70, 175/65, 185/60, 185/65			
6 x 15	RC24 / RC30	40	ZP436	61	165/60, 165/65, 175/55, 175/60, 185/55			
6 x 16	RC34	43	-	61	165/50, 175/50, 175/55, 185/50 , 195/45			Orig.-Verschr.
	RC30	43	-	61	175/50, 185/50, 195/45			Orig.-Verschr.
6,5 x 16	RC24 / RC30	38	ZP436	61	195/45			

Tarraco		ab 02.2019		KN	5/112	57,1	e9*2007/46*6666*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC37	38	-	110-180	215/65			Orig.-Verschr. auch Hybrid u. FR-Line
	RC34	38	-	110-180	215/65			Orig.-Verschr., auch für Hybrid
	RC27	39+43	-	110-147	215/65, 225/60, 225/65, 235/60			Orig.-Verschr., ohne Radhausverbreiterung
	RC34	43	-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr., ohne Radhausverbreiterung
					225/60, 225/65, 235/60			Orig.-Verschr., mit Radhausverbreiterung
7 x 17	RC27	40	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55			Orig.-Verschr., auch FR-Line
	RC30	40	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55			Orig.-Verschr. auch Hybrid u. FR-Line
	RC32	40	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60			Orig.-Verschr.
	RC34	40	-	110-180	215/65			Orig.-Verschr.
	RC27	42+43	-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr., auch FR-Line
		45	-	110-147	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
	RC30	38	-	110, 140	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
		45	-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
	RC32	38	-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
		39	-	110-147	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
		45	-	110-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55			Orig.-Verschr., auch für Hybrid
	CA 26	42	ZP560D	110-180	215/65, 225/60, 225/65, 235/60			
45		-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.	
	RC24	42	-	110-180	215/65, 225/60, 225/65, 235/60			Orig.-Verschr., auch FR-Line

7,5 x 17	RC27	40+41	-	110-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., auch FR-Line
	RC32	43	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., auch für Hybrid
	RC24	42	ZP560D	110, 140	215/65, 225/60, 225/65, 235/60		
	RC28	45	ZP560D	110-180	215/65, 225/60, 225/65		
	RC29	35+45	ZP560D	110-180	215/65, 225/60, 225/65		auch FR-Line, nicht Bremse 340mm
	RC34	36	ZP560D	110-147	215/65, 225/60, 225/65		
		40	ZP560D	110-180	215/65, 225/60, 225/65, 235/60		
		45	ZP560D	110-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		
	B24	35	ZP560D	110-180	215/65, 225/60, 225/65		
7 x 18	B36	45	ZP560D	110-180	215/65, 225/60, 225/65		auch FR-Line, nicht Bremse 340mm
	AC-518	42	AV4+R	110, 140	215/65, 225/60, 225/65, 235/60		+ Red.Ringe BA25=66,6-57,1
	RC27	43	-	110-180	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
	RC32	43	-	110-140	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
	RC34	43	-	110-180	235/55		Orig.-Verschr.
				110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		
	RC32	35	-	110-147	215/55, 215/60, 225/55, 225/60		Orig.-Verschr., auch für Hybrid
		40	-	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr., auch für Hybrid, ohne Radhausverbreiterung
		45	-	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr., auch für Hybrid
7,5 x 18	RC32	45	-	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	RC34	35	-	110-180	215/55, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC30	35	ZP560D	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50		ohne Radhausverbr. ab 235/50 ✖
		45	ZP560D	110-180	215/55, 215/60, 225/55, 225/60		auch FR-Line
	B32	35	ZP560D	110, 140	215/55, 215/60, 225/55, 225/60		
		45	ZP560D	110-147	215/55, 215/60, 225/55, 225/60		ohne FR-Line
	B39	35	ZP560D	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50		ohne Radhausverbr. ab 235/50 ✖
		45	ZP560D	110, 140	215/55, 215/60, 225/55, 225/60		
	AC-MB6	45	- +R	110-180	215/55, 215/60, 225/55, 225/60		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, auch FR-Line
8 x 18	RC27	40	-	110-140	225/55, 235/50, 235/55		Orig.-Verschr.
	RC29	40	-	110-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr., auch FR-Line
	RC32	40	-	110-180	215/55, 225/55, 225/60		Orig.-Verschr.
		44	-	110-140	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC34	40	-	110-180	215/55, 225/55, 225/60		Orig.-Verschr., auch Hybrid
		45	-	110-180	225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr., auch Hybrid
	RC34	40	ZP560D	110-180	215/55, 225/55, 225/60		auch Hybrid
		43	ZP560D	110-180	215/55, 225/55, 225/60, 235/50, 235/55		auch Hybrid
	AC-M10	40	- +R	110-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, auch FR-Line
	AC-518	40	AV4+R	110, 140	225/55, 225/60, 235/50, 235/55		+ Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	110, 140	225/55, 225/60, 235/50, 235/55		
	FMI11 Elatha	39	F95	110-180	215/55, 225/55, 225/60		ohne Radhausverbreiterungen
					215/55, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		mit Radhausverbreiterungen
		45	F95	110-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		
7 x 19	RC27	43	-	110-180	235/50		Orig.-Verschr., auch FR-Line
	RC34	43	-	110-180	235/50		Orig.-Verschr.
7,5 x 19	B32	43	-	110, 140	235/45, 235/50, 245/45		Orig.-Verschr.
8 x 19	RC29	40	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch FR-Line
	RC32	40	-	110-180	235/45, 245/45		Orig.-Verschr., ohne Radhausverbreiterung
					225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid, mit Verbreiter.
		45	-	110-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid
	RC34	40	-	110-180	235/45, 245/45		Orig.-Verschr., auch für Hybrid, ohne Verbreiter.
					225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid, mit Verbreiter.
		44	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid, ohne Verbreiter.
					225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid, mit Verbreiter.
		45	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid
	B40	40	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., ohne FR-Line
	B43	40	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch FR-Line
	RC34	38	ZP560D	110-180	235/45, 245/45		
		43	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbreiterung
	B40	38	ZP560D	110-180	225/50, 235/45, 235/50, 245/45, 255/45		mit Radhausverbreiterung
					235/45, 245/45		ohne FR-Line
	CA 17	37	ZP560D	110-140	245/45		
	FMI07 Atena	39	- +R	110-140	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	RC32	38	-	110-180	255/45		Orig.-Verschr.
	RC34	38	-	110-180	255/45		Orig.-Verschr.

8,5 x 19	B43	38	ZP568F	110-180	235/45, 235/50, 245/45, 255/45		nur FR, auch Hybrid, mit Radhausverbreiterung
	CA 26	38	ZP568F	110-180	255/45		mit Radhausverbreiterung
	B37	35	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		auch FR-Line
	B41	36+39	ZP560D	110-180	235/45		
	B42	35	ZP560D	110-180	235/45		
	B44	35	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		nur FR
	AC-M10	40	- +R	110-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	110, 140	235/45, 245/45		
	CA 20 / CA 23	40	- +R	110-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI07 Atena	45	- +R	110-140	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 20	Oxigin 28	40	ZP560D	110-180	235/45, 245/45		
	RC36	41	-	110-180	235/40, 235/45 , 245/40		Orig.-Verschr., auch FR-Line
	B38	41	-	110-180	235/40, 235/45 , 245/40		Orig.-Verschr., auch FR-Line
	B40	41	-	110-180	235/40, 235/45 , 245/40		Orig.-Verschr., auch FR-Line
	B43	41	-	110-180	235/40, 235/45 , 245/40		Orig.-Verschr., auch FR-Line
8,5 x 20	FMI08 Thoe	45	F31+R	110-180	215/45, 235/40, 235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
	RC29	38	-	110-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., ohne Verbr. ab 245/40 ✕
	RC36	38	-	110-180	255/40		Orig.-Verschr., FR-Line
	B43	38	-	110-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., auch Hybrid, nur FR-Line
		40	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., auch FR-Line
	B32	41	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., ohne FR-Line
		40	ZP560D	110-180	235/40, 235/45, 245/40		auch FR-Line
	RC29	45	ZP560D	110-180	235/40, 235/45		auch FR-Line
		38	ZP568F	110-147	235/40, 235/45		
	RC34	43	ZP560D	110-147	235/40, 235/45, 245/40, 255/40		
		42	ZP560D	110-180	235/40, 235/45		auch FR-Line
	B24	40	ZP560D	110-180	235/40, 235/45, 245/40		ohne FR-Line
		45	ZP560D	110, 140	235/40, 235/45		
	B42	35+45	ZP560D	110-180	235/40, 235/45		auch FR-Line
		40	ZP560D	110-180	235/40, 235/45, 245/40		auch FR-Line
	B43	40	ZP560D	110-180	235/40, 235/45, 245/40		auch FR-Line
		43	ZP560D	110-180	235/40, 235/45		auch FR-Line
	B44	35	ZP560D	110-180	235/40, 235/45		auch FR-Line
		40	ZP560D	110-180	235/40, 235/45, 245/40		auch FR-Line
	AC-518	45	- +R	110-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	45	-	110-180	235/40, 235/45		Orig.-Verschr., auch FR-Line
	AC-M10	40	- +R	110-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	45	- +R	110-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 17	35	ZP560D	110-140	235/45		
		40	ZP560D	110-180	235/45, 245/40		nicht Bremse 340mm
	FMI07 Atena	39	- +R	110-140	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	B43	42	-	110-180	235/40, 235/45		Orig.-Verschr., auch FR-Line
	B37	37	ZP560D	110-180	235/40, 235/45		auch FR-Line
	AC-521	42	-	110-180	235/40, 235/45		auch FR-Line
	AC-522	40	- +R	110-180	235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 23	38	ZP560D	110-180	235/40, 235/45		
8,5 x 21	B43	40	-	110-180	245/35		Orig.-Verschr., auch FR-Line
	B41	40	ZP560D	110-180	245/35		
		43	ZP560D	110-147	245/35, 255/35		

Toledo (siehe Konfigurator)

ab 03.13

NH

5/100

57,1

e11*2007/46*0251*00-19, e11*2007/46*252*....,
e8*2007/46*0321*....

Skoda

Citigo E iV		ab 2019		AA	4/100	57,1	e13*2007/46*1169*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5 x 14	RC30	35	-	61	165/70, 175/65, 185/60, 185/65			Orig.-Verschr.
	RC30	39	ZP436	61	165/70, 175/65, 185/60, 185/65			
6 x 15	RC24 / RC30	40	ZP436	61	165/60, 165/65, 175/55, 175/60, 185/55			
6 x 16	RC30	43	-	61	175/50, 185/50 , 195/45			Orig.-Verschr.
	RC34	43	-	61	165/50, 175/50, 175/55, 185/50 , 195/45			Orig.-Verschr.
6,5 x 16	RC24 / RC30	38	ZP436	61	195/45			

Elroq NEU		2025		NY		5/112		57,1		e8*2007/46*0416*17-..	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8 x 19	RC34	45	-	70-89	VA+HA 235/55 od.				Orig.-Verschr.		
				VA 235/55+HA 255/50							
				70-89	VA+HA 235/50, 235/55, 245/50, 255/50 od.						
		VA 235/55+HA 255/50									
		40	-	70-89	VA+HA 235/50, 235/55, 245/50, 255/50od.						
					VA 235/55+HA 255/50						
43	ZP560D	70-89	VA+HA 235/50, 235/55, 245/50, 255/50, 265/50 od.								
			VA 235/55+HA 255/50								
8 x 20	RC36	45	-	70	VA+HA 235/50				Orig.-Verschr., Elroq 50 / 60		
				235/50, 245/45, 255/45							
		38+41	-	70	235/50, 245/45, 255/45						
9 x 20	RC36	42	-	70	245/45, 255/45, 265/45				Orig.-Verschr., Elroq 50 / 60		
8,5 x 21	B41	40	-	70-89	VA+HA 235/45, 245/40, 255/40 od.				Orig.-Verschr.		
					VA 235/45+HA 255/40						

Kombinationen

8 x 20	B43	VA 45	-	70	VA 235/50		Orig.-Verschr.
9 x 20		HA 42			HA 255/45, 265/45		
8,5 x 21	B43	VA 40	-	70	VA 235/45		Orig.-Verschr.
9 x 21		HA 42			HA 255/40, 265/40		

Elroq 85 NEU		2025		NY	5/112	57,1	e8*2007/46*0416*17-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	RC36	38+41	-	89 (210)	VA 235/50+HA 255/45			Orig.-Verschr.
		45	-	89 (210)	VA 235/50+HA 255/45			Orig.-Verschr.
9 x 20	RC36	42	-	89 (210)	255/45, 265/45			Orig.-Verschr.

Kombinationen

8 x 20	B43	VA 45	-	89 (210)	VA 235/50		Orig.-Verschr.
9 x 20		HA 42			HA 255/45, 265/45		
8,5 x 21	B43	VA 40	-	89 (210)	VA 235/45		Orig.-Verschr.
9 x 21		HA 42			HA 255/40, 265/40		

Elroq RS, 85X NEU		2025		NY	5/112	57,1	e8*2007/46*0416*19-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	RC36	VA 45	-	77	VA 235/50		Orig.-Verschr., Elroq 85X	
9 x 20		HA 42			HA 255/45			
9 x 20	RC36	VA+HA 42	-	77	255/45, 265/45			Orig.-Verschr.

Enyaq		ab April/Mai 2021		NY	5/112	57,1	e8*2007/46*0416*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC34	45	-	70	235/60, 245/55, 245/60, 255/55			Orig.-Verschr.
	RC27	40+44	-	70	235/60, 245/55, 255/55			Orig.-Verschr., mit Trommelbremse an HA
	RC32	44	-	70	235/60, 245/55, 245/60, 255/55			Orig.-Verschr.
		46	-	70	235/60, 245/55, 245/60			Orig.-Verschr.
	RC34	44	-	70	235/60, 245/55, 245/60, 255/55			Orig.-Verschr.
	B37	44	-	70	235/60, 245/55, 255/55			Orig.-Verschr., nur Enyaq 60 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
	B36	45	ZP560D	70	235/60, 245/55, 255/55			Enyaq 50 / 60 , mit Trommelbremse an der HA, nicht Bremse 358mm VA
	B42 / B44	45	ZP560D	70	235/60, 245/55, 255/55			Enyaq 50 / 60 , mit Trommelbremse an der HA
	AC-MB6 / AC-	45	ZP560D	70	235/60, 245/55, 255/55			Enyaq 50 / 60 , mit Trommelbremse an der HA

	M10	45	- +R	70	235/60, 245/55, 255/55		Orig.-Verschr. + Red.Ringe 66,6-57,1 , Enyaq 50 / 60, mit Trommelbremse an der HA	
	AC-521						Enyaq 50	
	CA 17						Enyaq 50	
	CA 20						Enyaq 50 / 60, incl. Coupe, mit Trommelbremse an der HA	
8 x 19	RC27	45	-	70	VA+HA 235/55		Orig.-Verschr., Enyaq 50 / 60 , incl. Coupe, mit Trommelbremse an der HA	
			-	70-89	VA 235/55+HA 255/50		Orig.-Verschr., Enyaq 80 / 85X , incl. Coupe, mit Trommelbremse an der HA	
	RC32	45	-	70-89	VA+HA 235/55		Orig.-Verschr., auch Coupe	
					VA 235/55+HA 255/50			
				70-89	VA+HA 235/55, 245/50, 255/50 od.			
					VA 235/55+HA 255/50			
	RC34	45	-	70-89	VA+HA 235/55, 245/50, 255/50		Orig.-Verschr.	
					VA 235/55+HA 255/50			
	B40	45	-	70	235/55, 245/50, 255/50		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA	
				70, 77	VA 235/55+HA 255/50		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA, nur mit Bremse 358mm VA	
	B43	45	-	70	235/55, 245/50, 255/50		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse HA	
				70-89	VA 235/55 + HA 255/50		Orig.-Verschr., Enyaq 80/85X , incl. Coupe	
		40	-	70	235/55, 245/50, 255/50		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA	
				70, 77	VA 235/55+HA 255/50		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA	
	RC29	45	ZP560D	70	235/55, 245/50, 255/50		Enyaq 50 / 60 , mit Trommelbremse an der HA	
			ZP560D	70, 77	VA 235/55+HA 255/50		Enyaq 80 / 80X , mit Trommelbremse an der HA	
	RC32	44	-	70-89	VA+HA 235/55, 245/50, 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr.	
	AC-521	45	-	70	235/55, 245/50, 255/50		Orig.-Verschr., Enyaq 60 , mit Trommelbremse an der HA, nur Bremse 358mm VA	
			-	70	VA 235/55+HA 255/50		Enyaq 80 , mit Trommelbremse an der HA, nur Bremse 358mm VA	
	CA 17	45	ZP560D	70-89	VA 235/55+HA 255/50			
	FMI08 Thoe	47	F31+R	70-89	VA+HA 235/55, 245/50 od. VA 235/55+HA 255/50		+ Red.Ringe BA25=66,6-57,1	
	Oxigin 29	43	ZP560D	70	235/55, 245/50, 255/50		Enyaq 50 / 60 , mit Trommelbremse an der HA	
			ZP560D	70-89	VA 235/55+HA 255/50		Enyaq 80 / 85X , mit Trommelbremse an der HA	
	8,5 x 19	B32	45	ZP560D	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 50 / 60 - mit Trommelbremse an der HA
			45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 80 / 80X - mit Trommelbremse an der HA
B37		43	ZP560D	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 60 + Enyaq 80 - mit Trommelbremse an der HA, nur mit Bremse 358mm VA	
				70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 50 / 60 - mit Trommelbremse an der HA	
		45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 80 / 80X - mit Trommelbremse an der HA	
B41		36+39	ZP560D	70-77	235/55			
AC-M10		45	AV4+R	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		+ Red.Ringe BA25=66,6-57,1, Enyaq 50 / 60 , mit Trommelbremse an der HA	
				70-89	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		+ Red.Ringe BA25=66,6-57,1, Enyaq 80 / 85X , mit Trommelbremse an der HA	
CA 20 / CA 23		45	ZP560D	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 50 / 60 - mit Trommelbremse an der HA	
				70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 80 / 80X - mit Trommelbremse an der HA	
Oxigin 28	40+45	ZP560D	70	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 50 / 60 , mit Trommelbremse an der HA, ET40 bei 255/50 ✖		
			70, 77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45		Enyaq 80 / 80X , mit Trommelbremse an der HA, ET40 bei 255/50 ✖		
8 x 20	B40	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Enyaq 80 / 80X , mit Trommelbremse an der HA, nur mit Bremse 358mm VA	
9 x 20		42						

8 x 20	B40	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
		42					
8 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA, Enyaq 80/80X
9 x 20		42					
8 x 20	AC-521	45	-	70	VA 235/50, 245/45		Orig.-Verschr., Enyaq 50 / 60 , für Trommelbremse an der HA, bei 275/40 ✖
9 x 20		42			HA 255/45, 275/40		
8 x 20		45	-	70, 77	VA 235/50, 245/45		Orig.-Verschr., Enyaq 80 / 80X , für Trommelbremse an der HA, bei 275/40 ✖
9 x 20		42			HA 255/45, 275/40		
8 x 20	RC36	45	-	70	235/50		Orig.-Verschr., Enyaq 50 / 60
	B43	45	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60
		45	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr., Enyaq 80, 85X
	RC36	38+41+45	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , incl. Coupe, incl. FL2025
				70-89	VA 235/50+ HA 255/45		Orig.-Verschr., Enyaq 80 / 85X , incl. Coupe, incl. FL2025
	B38	40+41	-	70	245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA
	B40	41	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 60 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
		41+45	-	70, 77	VA 235/50+ HA 255/45		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
	B43	41	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , incl. Coupe
			-	70, 77	VA 235/50+ HA 255/45		Orig.-Verschr., Enyaq 80, 85X , incl. Coupe
		39	ZP560D	70	235/50, 245/45, 255/45		Enyaq 50 / 60 , incl. Coupe
				70-89	VA 235/50+ HA 255/45		Enyaq 80 / 85X , incl. Coupe
	FMI08 Thoe	45	F31+R	70-77	VA+HA 235/50, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1
					VA 235/50+HA 255/45		
8,5 x 20	B43	38+40	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA
	RC29	40+45	ZP560D	70	235/50, 245/45, 255/45		Enyaq 60 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
				70	VA 235/50+HA 255/45		Enyaq 80 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
	B24	42	ZP560D	70	235/50, 245/45, 255/45		Enyaq 60 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
				70	VA 235/50+HA 255/45		Enyaq 80 , mit Trommelbremse an der HA, nur mit Bremse 358mm VA
	B42	40+45	ZP560D	70	235/50, 245/45, 255/45		Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Enyaq 80 / 80X , mit Trommelbremse an der HA
	B43	40+43	ZP560D	70	235/50, 245/45, 255/45		Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Enyaq 80 / 80X , mit Trommelbremse an der HA
	B44	40	ZP560D	70	235/50, 245/45, 255/45		nur Enyaq 50 / 60 , mit Trommelbremse an der HA
	AC-521	45	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA
	AC-M10	40	- +R	70	235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, Enyaq 80 / 80X , mit Trommelbremse an der HA
	CA 17	40	ZP560D	70	235/50, 245/45		Enyaq 50 / 60
				70-77	VA 235/50+HA 255/45		Enyaq 80 / 80X
9 x 20	B40	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA
	B43	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr., Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Orig.-Verschr., Enyaq 80 / 80X , mit Trommelbremse an der HA
	B37	37	ZP560D	70, 77	VA 245/45+HA 275/40		Enyaq 80 / 80X , mit Trommelbremse an der HA, bei 275/40 ✖
	AC-521	42	-	70	235/50, 245/45, 255/45		Enyaq 50 / 60 , mit Trommelbremse an der HA
				70, 77	VA 235/50+HA 255/45		Enyaq 80 / 80X , mit Trommelbremse an der HA
	CA 20 / CA 23	45	ZP560D	70	235/50, 245/45, 255/45, 275/40HA		Enyaq 50 / 60 , mit Trommelbremse an der HA
				70-89	VA 235/50+HA 255/45 u. VA 245/45+HA 275/40		Enyaq 80 / 85X , mit Trommelbremse an der HA
	FMI11 Elatha	46	- +R	70-77	VA+HA 235/50, 245/45, 255/45, 265/45 od.		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
					VA 235/50+HA 255/45 u. VA 245/45+HA 275/40		
				70	235/50 245/45 255/45 275/40HA		Enyaq 50 / 60 mit Trommelbremse an der HA

	Oxigin 28	45	ZP560D	70	235/50+HA 255/45 u. VA 245/45+HA 275/40		Enyaq 80 / 80X, mit Trommelbremse an der HA
				70, 77			
9,5 x 20	B42	42	ZP560D	70	255/45		Enyaq 60, mit Trommelbremse an der HA, nur mit Bremse 358mm VA
			ZP560D	70	255/45		Enyaq 80, mit Trommelbremse an der HA, nur mit Bremse 358mm VA
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45+ HA 255/40		Orig.-Verschr., Enyaq 80 / 80X, mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 21		HA 42					
8,5 x 21	B41	40	-	70	VA+HA 235/45		Orig.-Verschr.
		40	-	70-89	VA+HA 235/45, 245/40, 255/40 od. VA 235/45+HA 255/40		Orig.-Verschr.
	B43	40	-	70	235/45, 245/40, 255/40		Orig.-Verschr., Enyaq 50 / 60, mit Trommelbremse an der HA
		40	-	70-89	VA 235/45+HA 255/40		Orig.-Verschr., Enyaq 80 / 85X, mit Trommelbremse an der HA
	B41	37+40	ZP560D	70-77	VA+HA 235/45, 245/40, 255/40 od. VA 235/45+HA 255/40		Heck- u. Allradantrieb
	B43	38	ZP568F	70	235/45, 245/40, 255/40		Enyaq 50 / 60, incl. Coupé, mit Trommelbremse an der HA
		38	ZP568F	70-89	VA 235/45+HA 255/40		Enyaq 80 / 85X, incl. Coupé, mit Trommelbremse an der HA
	9 x 21	B32	40	ZP560D	70	245/40, 255/40, 275/35HA	
VA 245/40+HA 275/35							Enyaq 80, mit Trommelbremse an der HA, nur mit Bremse 358mm VA, HA ✖
CA 20		45	ZP560D	70 70-89	235/45, 245/40, 255/40, 275/35HA VA 235/45+HA 255/40, VA 255/40+HA 275/35		Enyaq 50 / 60, für Trommelbremse an der HA Enyaq 80, 85X, für Trommelbremse an der HA
FMI07 Atena		40	- +R	70-89	245/40, 255/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
9,5 x 21	FMI10 e-Joule	41,5	F95	70-77	VA+HA 245/40, 255/40		

Kombinationen

8,5 x 20	B42	VA 40	ZP560D	70	VA 235/50		Enyaq 50 / 60, incl. Coupe
9,5 x 20		HA 42			HA 255/45		
8,5 x 20		VA 40	ZP560D	70-89	VA 235/50		Enyaq 80, 85X, incl. Coupe
9,5 x 20		HA 42			HA 255/45		

Enyaq RS Coupé NEU		2. Quartal 2022			NY	5/112	57,1	e8*2007/46*0416*...	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 19	RC27	45	-	77	VA 235/55+HA 255/50				Orig.-Verschr., incl. Coupe, mit Trommelbremse an der HA
	RC34	45	-	77	VA 235/55+HA 255/50				Orig.-Verschr.
	B43	45	-	77	VA 235/55+HA 255/50				Orig.-Verschr., nur Bremse 358mm VA, mit Trommelbremse an HA
	RC32	45	-	70-89	VA+HA 235/55, 245/50, 255/50 od.				
					VA 235/55+HA 255/50				
	B40	45	-	77	VA 235/55+HA 255/50				Orig.-Verschr., nur Bremse 358mm VA, für Trommelbremse HA
	RC34	40	-	77	VA 235/55+HA 255/50				Orig.-Verschr., nur M+S
	B43	40	-	77	VA 235/55+HA 255/50				Orig.-Verschr., nur Bremse 358mm VA, für Trommelbremse HA
	FMI08 Thoe	47	F31+R	70-89	VA+HA 235/55, 245/50 od.			+ Red.Ringe BA25=66,6-57,1	
VA 235/55+HA 255/50									
Oxigin 29	43	ZP560D	77	VA 235/55+HA 255/50				mit Trommelbremse an der HA	
8,5 x 19	B32	45	ZP560D	77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45				nur M+S, mit Trommelbremse an der HA
	B37	45	ZP560D	77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45				nur M+S, mit Trommelbremse an der HA
	AC-M10	45	AV4+R	77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45				+ Red.Ringe BA25=66,6-57,1 , nur M+S, mit Trommelbremse an der HA
	CA 20 / CA 23	45	ZP560D	77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45				nur M+S, mit Trommelbremse an der HA
	Oxigin 28	40+45	ZP560D	77	VA 235/55+HA 255/50 od. VA 245/50+HA 275/45				nur M+S, mit Trommelbremse an der HA, ET40 bei 255/50 ✖
8 x 20	B43	45	-	77	VA 235/50+HA 255/45				Orig.-Verschr., für Trommelbremse HA
9 x 20		42							
8 x 20	AC-521	45	-	77	VA 235/50+HA 255/45				Orig.-Verschr., für Trommelbremse HA
9 x 20		42							
	RC36	38+41+	-	77	VA 235/50+HA 255/45				Orig.-Verschr. nur M+S

8 x 20	RC30	45			VA 235/50+HA 255/45		Orig.-Verschr., nur M+S
	B43	41+45	-	77	VA 235/50+HA 255/45		Orig.-Verschr., nur M+S
		39	ZP560D	77	VA 235/50+HA 255/45		nur M+S, incl. Coupe
8,5 x 20	B43	38+40	-	77	VA 235/50+HA 255/45		Orig.-Verschr., nur M+S, mit Trommelbremse an der HA
		40+43	ZP560D	77	VA 235/50+HA 255/45		nur M+S, mit Trommelbremse an der HA
	CA 17	40	ZP560D	77	VA 235/50+HA 255/45		
	AC-M10	40	- +R	77	VA 235/50+HA 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , nur M+S, mit Trommelbremse an der HA
9 x 20	B40	42	-	77	VA 235/50+HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA
	B43	42	-	77	VA 235/50+HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA
	B37	37	ZP560D	77	VA 245/45+HA 275/40		mit Trommelbremse an der HA
	AC-521	42	-	77	VA 235/50+HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA
	CA 20 / CA 23	45	ZP560D	77	VA 235/50+HA 255/45 u. VA 245/45+HA 275/40		mit Trommelbremse an der HA
	FMI11 Elatha	46	- +R	70-77	VA 235/50+HA 255/45 u. VA 245/45+HA 275/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 21	B41	40	-	77	VA+HA 235/45, 245/40, 255/40 od.		Orig.-Verschr.
					VA 235/45+HA 255/40		
	B43	40	-	77	VA 235/45+HA 255/40		Orig.-Verschr., nur M+S, mit Trommelbremse an der HA
		38	ZP568F	77	VA 235/45+HA 255/40		nur M+S, mit Trommelbremse an der HA
9 x 21	CA 20	45	ZP560D	70-89	VA 235/45+HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA
	FMI07 Atena	40	- +R	70-89	245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1

Fabia / Fabia Kombi		ab MJ2015		5J / Modell 6V	5/100	57,1	e11*2001/116*0291*43-., e11*2007/46*0013*20-..	
Sensor - direktes RDKS möglich - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5 x 14	RC30	35	-	44,55,66	175/65, 175/70 , 185/65		Orig.-Verschr.	
				44-70	165/70M+S, 175/65, 175/70, 185/65			
		38	-	44-70	165/70M+S, 175/65, 175/70, 185/65		Orig.-Verschr.	
5,5 x 15	RC19	40	-	44-70	175/60, 175/65, 185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
6 x 15	RC27	38	-	44-92	185/55, 185/60 , 195/55		Orig.-Verschr.	
				44-70	175/60, 175/65			
	RC30	38	-	44-92	185/55, 185/60 , 195/55		Orig.-Verschr.	
				44-70	175/60, 175/65			
	RC24	38	-	44-70	175/60, 175/65		Orig.-Verschr.	
				44-92	185/55, 185/60, 195/55			
6 x 16	RC27	35+37	-	44-70	175/60, 175/65		Orig.-Verschr.	
				44-92	185/55, 185/60			
	RC27	35+38	-	44-92	185/50, 185/55, 195/45		Orig.-Verschr., ET38 nicht Bremse 288mm	
				44-92	185/50, 185/55, 195/45		Orig.-Verschr.	
	RC30	38	-	44-92	185/50, 185/55, 195/45		Orig.-Verschr., nicht Bremse 288mm	
6,5 x 16	RC34	35+40	-	44-92	175/50, 175/55, 185/50, 185/55, 195/45, 195/50		Orig.-Verschr.	
	RC27	40+47	-	44-92	185/50, 185/55, 195/45, 195/50, 205/45		Orig.-Verschr., ET47 nicht Bremse 288mm	
	RC30	38+47	-	44-92	185/50, 185/55, 195/45, 195/50, 205/45		Orig.-Verschr., ET38 bei 195/50 ✖	
	RC32	40	-	44-92	185/50, 185/55, 195/45, 195/50, 205/45		Orig.-Verschr.	
7 x 16	RC30	46	-	44-92	195/45, 195/50, 205/45, 215/45		Orig.-Verschr.	
				44-92	195/50, 205/45, 215/45		Orig.-Verschr.	
6,5 x 17	RC27	39+40	-	44-92	195/40, 195/45		Orig.-Verschr., nicht Bremse 288mm	
7 x 17	RC30	46	-	44-92	195/40, 195/45, 205/40, 215/35, 215/40		Orig.-Verschr.	
	B39	46	-	44-92	195/40, 195/45, 205/40, 215/35, 215/40		Orig.-Verschr.	
	RC27	43	ZP516	44-92	195/40, 195/45, 205/40, 215/35, 215/40		nicht Bremse 288mm	
7,5 x 18	B39	42	ZP516	44-92	205/35			

Fabia		ab 2021		PJ	5/100	57,1	e8*2018/858*00014*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5 x 14	RC30	38	-		185/70		Orig.-Verschr., i.V.	
5,5 x 15	RC19	40	-	48-110	185/65, 195/60, 195/65		Orig.-Verschr.	
6 x 15	RC27	38	-	48-110	185/65		Orig.-Verschr.	
6 x 16	RC27	45	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC30	45	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC34	45	-	48-110	195/55		Orig.-Verschr.	
	RC27	35+38	-	48-110	185/55, 185/60		Orig.-Verschr.	
	RC30	35	-	48-110	185/55, 185/60		Orig.-Verschr.	
	RC34	35+40	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.	
6,5 x 16	RC27	40	-	48-110	185/55, 185/60		Orig.-Verschr.	
	RC30	38	-	48-110	185/55, 185/60		Orig.-Verschr.	
		47	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
		CA 20	38	ZP516	48-110	185/55, 185/60		

7 x 16	RC30	46	-	48-110	195/55		Orig.-Verschr.
6,5 x 17	RC34	39	-	48-110	195/45		Orig.-Verschr.
		40	-	48-110	195/45, 205/45		Orig.-Verschr.
7 x 17	RC27	51	-	48-110	205/45, 215/45		Orig.-Verschr.
	RC30	51	-	48-110	205/45, 215/45		Orig.-Verschr.
	RC32	51	-	48-81	195/45, 195/50, 205/45, 215/40, 215/45 , 225/45		Orig.-Verschr.
	RC34	51	-	48-110	195/45, 195/50, 205/45, 215/40, 215/45 , 225/45		Orig.-Verschr.
	CA 26	51	-	48-110	205/45, 215/45		Orig.-Verschr.
7 x 18	RC34	51	-	70-110	215/40		Orig.-Verschr.

Fabia Monte Carlo

NEU i.V.

1. Quartal 2022

Dimension	Design	ET	KIT	KW	Reifendimension	Info

Kamiq

ab 10.2019

NW

5/100

57,1

e8*2007/46*0349*...

Sensor - direktes RDKS möglich - Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 16	RC27	35	-	66-110	195/60 , 195/65, 205/55, 205/60 , 215/55, 215/60	Orig.-Verschr., 195er Reifen nur M+S, beide ET's
		38	-	66-110	195/60, 195/65, 205/55, 205/60 , 215/55, 215/60	ECE
	RC30	35	-	66-110	195/60 , 195/65, 205/55, 205/60 , 215/55, 215/60	Orig.-Verschr., 195er Reifen nur M+S, beide ET's
		38	-	66-110	195/60, 195/65, 205/55, 205/60 , 215/55, 215/60	ECE
	RC34	35	-	66-110	195/60M+S , 205/55, 205/60 , 215/50, 215/55, 215/60, 225/50, 225/55	Orig.-Verschr.
		40	-	66-110	195/60M+S, 205/55, 205/60, 215/50, 215/55, 215/60, 225/50, 225/55	Orig.-Verschr.
6,5 x 16	RC27	40	-	66-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55	Orig.-Verschr., 195er Reifen nur M+S
	RC30	38	-	66-110	195/60M+S, 195/65M+S, 205/55, 205/60, 215/55, 215/60	Orig.-Verschr.
	RC32	40	-	66-110	195/60M+S, 205/55, 205/60, 215/50, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55	Orig.-Verschr.
	CA 20	38	ZP516	66-110	195/60M+S, 195/65M+S, 205/55, 205/60, 215/55, 215/60	
6,5 x 17	RC27	40	-	70-110	195/55M+S, 205/50, 205/55 , 215/50, 225/50	Orig.-Verschr.
	RC34	40	-	66-110	205/55	Orig.-Verschr.
	RC27	39	-	70-110	195/55M+S, 205/50, 205/55, 215/50, 225/50	Orig.-Verschr.
	RC34	39	-	66-110	205/50, 205/55, 215/50, 225/50	Orig.-Verschr.
7,5 x 17	RC28	38	ZP516	66-110	205/50, 205/55, 225/45	
	RC29	38	ZP516	66-110	205/50, 205/55, 225/45	
	B24 / B36	38	ZP516	66-110	205/50, 205/55, 225/45	
7 x 18	RC32	39	-	66-110	205/45, 215/45 , 225/45	Orig.-Verschr., ECE nur von 70-110 KW!!!
	RC34	39	-	66-110	215/45	Orig.-Verschr.
8 x 19	B40	39	ZP516	66-110	215/35	

Karoq

ab 10.2017

NU

5/112

57,1

e8*2007/46*0272*...

Sensor - direktes RDKS möglich - Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 16	RC27	43	-	81-110	215/60 , 215/65, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60M+S , 215/65M+S, 225/60	Orig.-Verschr., Allrad
	RC30	43	-	81-110	215/60 , 215/65, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60M+S , 215/65M+S, 225/60	Orig.-Verschr., Allrad
	RC34	43	-	81-110	215/60 , 225/60	Orig.-Verschr.
				81-110	215/60, 225/55, 225/60	Orig.-Verschr., Frontantrieb
6,5 x 16	RC24	42+43	-	85, 110	215/60, 215/65, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60M+S, 215/65M+S, 225/60	Orig.-Verschr., Allrad
		46	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60M+S, 215/65M+S, 225/60, 235/60	Orig.-Verschr., Allrad
	RC27	42+43+	-	85, 110	215/60, 215/65, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60, 215/65, 225/60	Orig.-Verschr., Allrad, 215er Reifen M+S
		46	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60, 215/65, 225/60, 235/60	Orig.-Verschr., Allrad, 215er Reifen M+S
	RC30	41+42+	-	81-110	215/60, 215/65, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60, 215/65, 225/60	Orig.-Verschr., Allrad, 215er Reifen M+S
		46	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60	Orig.-Verschr., Frontantrieb
				110, 140	215/60, 215/65, 225/60, 235/60	Orig.-Verschr., Allrad, 215er Reifen M+S
	RC32	41	-	85-110	215/60, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110-140	215/60, 215/65, 225/60, 235/55, 235/60	Orig.-Verschr., Allrad, 215er Reifen M+S
		43	-	85-110	215/60, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110-140	215/60, 215/65, 225/55, 225/60, 235/55, 235/60	Orig.-Verschr., Allrad
	RC34	43	-	81-110	215/60, 225/55, 225/60	Orig.-Verschr., Frontantrieb
				110-140	215/60, 215/65, 225/55, 225/60, 235/55, 235/60	Orig.-Verschr., Allrad
	CA 20	45	ZP560D	81-110	215/60, 215/65, 225/55, 225/60, 235/60	Frontantrieb
				110, 140	215/60, 215/65, 225/60, 235/60	Allrad

6,5 x 17	RC27	39	-	85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Radhausverbr. ab 225/50 ✖
		43	-	85-140	215/55, 215/60, 225/50, 225/55		Orig.-Verschr., 215er Reifen bei Allrad nur M+S
7 x 17	RC27	45	-	85, 110	215/55 , 215/60, 225/50, 225/55		Orig.-Verschr.
				110, 140	215/55M+S , 215/60M+S, 225/50, 225/55		
	RC30	45	-	81-140	215/55M+S, 225/55		Orig.-Verschr.
					215/55, 215/60, 225/50, 225/55		auch Allrad
	RC32	45	-	85-110	215/55 , 225/50, 225/55		Orig.-Verschr., Frontantrieb
				110-140	215/50, 215/55 , 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Allrad
	RC34	45	-	81-140	215/55, 225/55		Orig.-Verschr.
	RC27	40	-	85, 110	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb, ab 225/50 ✖
				110, 140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., Allrad, 215er Reifen M+S, ab 225/50 ✖
		42+43	-	81-140	215/55, 215/60		Orig.-Verschr.
	RC32	38	-	110-140	215/50, 215/55, 215/60		Orig.-Verschr., nur Allrad
		40	-	85-110	215/55		Orig.-Verschr., Frontantrieb
				110-140	225/50, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., Allrad
	B39	40	-	85, 110	215/55		Orig.-Verschr., Frontantrieb
				110, 140	215/55, 215/60		Orig.-Verschr., Allrad, nur M+S
	RC27	45	ZP568F (V10)	81-140	215/55, 215/60, 225/50, 225/55		Ausführung "V10"
7,5 x 17	RC27	49	-	85-140	205/55, 205/60, 215/50, 215/55, 215/60, 225/50		Orig.-Verschr.
	RC32	43	-	81-110	215/55		Orig.-Verschr., Frontantrieb
				110-140	215/50, 215/55, 215/60		Orig.-Verschr., Allrad
	RC34	45	ZP560D	81-140	215/55		auch Allrad
	RC28	45	ZP560D	85-140	215/55, 215/60		auch Allrad
7 x 18	Oxigin 25	45	ZP560D	81-140	205/55, 205/60, 215/50, 215/55, 215/60		
	RC27	45	-	81-140	205/55, 215/50 , 225/45, 225/50		Orig.-Verschr.
	RC32	45	-	81-110	215/50 , 225/45, 225/50		Orig.-Verschr., ECE nur von 85-110 KW!!!!
				110-140	215/45, 215/50, 225/45, 225/50		Orig.-Verschr., Allrad
	RC34	45	-	81-140	215/50, 225/50		Orig.-Verschr.
	RC27	43	-	85-140	205/55, 215/50, 225/45		Orig.-Verschr.
	RC32	40	-	81-110	215/50, 225/45		Orig.-Verschr., Frontantrieb
				110-140	215/45, 215/50, 225/45		Orig.-Verschr., Allrad
		43	-	85-110	215/50, 225/45, 225/50		Orig.-Verschr., Frontantrieb
				110-140	215/45, 215/50, 225/45, 225/50		Orig.-Verschr., Allrad
7,5 x 18	RC32	45	-	85-110	215/50, 225/45, 235/45		Orig.-Verschr., Frontantrieb
				110-140	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Allrad
	RC30	45	ZP560D	85-140	215/50, 225/45, 235/45		auch Allrad
	B32 / B39	45	ZP560D	85-140	215/50, 225/45, 235/45		auch Allrad
8 x 18	Oxigin 18	45	-	85-140	205/55, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC27	46	-	85-140	215/45, 225/45		Orig.-Verschr.
	RC29	44	-	85-140	225/45		Orig.-Verschr., auch Allrad
	RC32	44	-	85-110	225/45		Orig.-Verschr., Frontantrieb
				110-140	215/45, 225/45, 235/40, 235/45		Orig.-Verschr., Allrad
		40	-	110-140	215/45, 225/45		Orig.-Verschr., nur Allrad
	RC34	45	-	81-110	225/45, 235/45		Orig.-Verschr., Frontantrieb
				110-140	215/45, 225/45, 235/40, 235/45		Orig.-Verschr., Allrad
	B38	44	-	85-140	225/45		Orig.-Verschr., auch Allrad
	RC34	40	ZP560D	110-140	215/45, 225/45		nur Allrad
		43	ZP560D	81-110	225/45		Frontantrieb
				110-140	215/45, 225/45, 235/40, 235/45		Allrad
	B37 / B42	45	ZP560D	81-140	215/50, 225/45, 235/45		auch Allrad
	AF20	35	AV1	85-140	225/45		
	CA 17	45	ZP560D	85-140	215/45, 225/45		
	CA 20	45	ZP560D	81-140	215/50, 225/45, 235/45		
7,5 x 19	B32	43	-	85-140	225/40, 225/45		Orig.-Verschr., auch Allrad
	B39	43	ZP560D	85-140	225/40, 225/45		auch Allrad
	Oxigin 18	50	ZP560D	85-140	225/40, 225/45		
8 x 19	RC27	45	-	81-110	225/40		Orig.-Verschr., Frontantrieb
				110, 140	225/45		Orig.-Verschr., Allrad
	RC32	45	-	81-110	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Frontantrieb
				110-140	225/45, 245/40		Orig.-Verschr., Allrad
	RC34	45	-	81-110	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., Frontantrieb
				110-140	225/40, 225/45, 235/35, 235/40, 245/40		Orig.-Verschr., Allrad
	B40	45	-	81-110	225/40 , 225/45		Orig.-Verschr., Frontantrieb
				110, 140	225/40, 225/45		Orig.-Verschr., Allrad
	B43	45	-	81-110	225/40 , 225/45		Orig.-Verschr.
				110, 140	225/40, 225/45		Orig.-Verschr., 4x4
	RC29	45	ZP560D	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Frontantrieb, ab 235/40 ✖
				110, 140	225/40, 225/45, 235/40, 245/40		Allrad, ab 235/40 ✖
	RC34	43	ZP560D	81-110	225/40, 225/45		Frontantrieb
				110-140	225/40, 225/45, 235/35, 235/40		Allrad

	B24 / B38	45	ZP560D	85-140	225/40, 225/45		auch Allrad
	B40	43	ZP560D	85-140	225/40		
		45	-	85-140	225/40, 225/45		Orig.-Verschr. auch Allrad
	CA 17	45	ZP560D	85-140	225/40, 225/45		
	CA 19	47	ZP560D	81-140	225/40, 225/45		
	Oxigin 29	43	ZP560D	81-110	225/40, 225/45		Frontantrieb
				110, 140	225/40, 225/45		Allrad
8,5 x 19	B32	45	ZP560D	85-140	225/40, 225/45		auch Allrad
	B36	45	ZP560D	85, 110	225/40		
				110, 140	225/40, 225/45		
	B37	45	ZP560D	85-140	225/40, 225/45		auch Allrad
	CA 23	45	ZP560D	81-110	225/40, 225/45		Frontantrieb
				110, 140	225/40, 225/45		Allrad
	FMI07 Atena	45	- +R	85-110	225/40, 225/45		Orig.-Verschr. +Ringe BA25 , Frontantrieb
				110-140	225/40, 225/45, 235/35, 235/40		Orig.-Verschr. +Ringe BA25 , Allrad
Oxigin 18	45	ZP560D	85-140	225/40, 225/45			
8 x 20	CA 23	45	ZP560D	81-110	225/40, 225/45		Frontantrieb
				110, 140	225/40, 225/45		Allrad
				81-110	225/35, 235/35		+Ringe BA25=66,6-57,1 , Frontantrieb
				110-140	225/35, 225/40, 235/35		+Ringe BA25=66,6-57,1 , Allrad
8,5 x 20	RC29	45	ZP560D	81-140	225/35		auch Allrad
	RC34	43	ZP560D	110-140	225/35, 225/40		nur Allrad
	B42	45	ZP560D	81-140	225/35		
	AC-518	45	- +R	81-140	225/35		Orig.-Verschr. +Ringe BA25=66,6-57,1
	AC-521	45	-	81-140	225/35		Orig.-Verschr.
	AF18	45	- +R	81-140	225/35		Orig.-Verschr. +Ringe BA25=66,6-57,1
	CA 17	48	ZP560D	85-140	225/35		

Karoq Scout							
ab 2019				NU	5/112	57,1	e8*2007/46*0272*..
Sensor - direktes RDKS möglich - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 16	RC27	43	-	85, 110	215/60		Orig.-Verschr., Frontantrieb, mit Verbreiterung.
				110, 140	215/60, 225/60		Orig.-Verschr., Allrad, mit Verbreiterungen
	RC30	43	-	85, 110	215/60, 215/65, 225/55, 225/60		Orig.-Verschr., Frontantrieb
				110, 140	215/60, 225/60		Orig.-Verschr., Allrad, mit Verbreiterungen
	RC34	43	-	85-140	215/60, 225/60		Orig.-Verschr.
				85-140	215/60, 225/55, 225/60		Orig.-Verschr.
6,5 x 16	RC24	43	-	110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., 215er Reifen nur M+S, mit Radhausverbreiterung
		46	-	110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., 215er Reifen nur M+S, mit Radhausverbreiterung
	RC27	44	-	110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., 215er Reifen nur M+S
	RC30	42	-	85, 110	215/60, 215/65, 225/55, 225/60, 235/60		Orig.-Verschr., Frontantrieb, mit Verbreiterung.
				110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., Allrad, mit Verbreiterungen
		44+46	-	110, 140	215/60, 215/65, 225/60, 235/60		Orig.-Verschr., 215er Reifen nur M+S
	RC32	41	-	110	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr., 215er Reifen nur M+S
		43	-	85-110	215/60, 225/55, 225/60		Orig.-Verschr., Frontantrieb
				110-140	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr., Allrad
	RC34	43	-	85-110	215/60, 225/55, 225/60		Orig.-Verschr., Frontantrieb
				110-140	215/60, 215/65, 225/60, 235/55, 235/60		Orig.-Verschr., Allrad
	CA 20	45	ZP560D	85, 110	215/60, 215/65, 225/55, 225/60, 235/60		Frontantrieb
				110, 140	215/60, 215/65, 225/60, 235/60		Allrad
6,5 x 17	RC27	39+43	-	110, 140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., 215er Reifen nur M+S
7 x 17	RC27	45	-	110, 140	215/55M+S, 225/55		Orig.-Verschr., Allrad, mit Verbreiterungen
				85, 110	215/55		Orig.-Verschr., Frontantrieb, mit Verbreiter.
	RC34	45	-	110-140	215/55, 225/55		Orig.-Verschr.
				85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., 215er Reifen nur M+S
	RC27	43	-	85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., mit Verbreiterungen
				85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., mit Radhausverbr., 215er Reifen nur M+S
	RC30	45	-	110, 140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Orig.-Verschr., nur Allrad
				110-140	215/55, 215/60, 225/55		Orig.-Verschr., 215er Reifen nur M+S
				85-110	215/55		Orig.-Verschr., Frontantrieb
				110	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Allrad, 215er Reifen nur M+S
	RC27	45	ZP568F (V10)	85-140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		Ausführung "V10"
7,5 x 17	RC27	40	-	110, 140	215/55M+S, 215/60M+S, 225/50, 225/55		
	RC32	43	-	85-110	215/55		Orig.-Verschr., Frontantrieb
				110-140	215/55, 215/60, 225/55		Orig.-Verschr., Allrad, 215er Reifen nur M+S
	RC34	45	ZP560D	110-140	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		
	B36	45	ZP560D	110, 140	215/55, 215/60, 225/50, 225/55, 235/50, 235/55		215er Reifen M+S, mit Verbreiterung
				85-110	215/50		Orig.-Verschr., Frontantrieb, mit Verbreiterung.
				110, 140	225/50		Orig.-Verschr., Allrad, mit Verbreiterungen

7 x 18	RC32	45	-	85-110	215/50		Orig.-Verschr., Frontantrieb
				110-140	225/50		Orig.-Verschr., Allrad
	RC34	45	-	85-140	215/50, 225/50		Orig.-Verschr.
	RC32	40+43	-	85-110	215/50		Orig.-Verschr., Frontantrieb
				110-140	225/50		Orig.-Verschr., Allrad
7,5 x 18	RC32	45	-	85-110	215/50, 235/45		Orig.-Verschr., Frontantrieb
				110-140	215/50, 225/50, 235/45, 245/45		Orig.-Verschr., Allrad
	RC30	45	ZP560D	85-140	215/50, 225/45, 225/50, 235/45, 245/45		mit Radhausverbreiterungen
8 x 18	B32	45	ZP560D	110, 140	215/50M+S, 225/45, 225/50, 235/45, 245/45		mit Radhausverbreiterungen
	RC29	44	-	85, 110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., Frontantrieb
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Allrad
	RC32	44	-	110-140	225/50, 235/45, 245/45		Orig.-Verschr., nur Allrad
	RC34	40	-	110-140	235/45		Orig.-Verschr., nur Allrad
		45	-	85-110	235/45		Orig.-Verschr., Frontantrieb
				110-140	225/50, 235/45, 245/45		Orig.-Verschr., Allrad
	B37	44	-	85, 110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr., Frontantrieb, mit Verbreiterung.
				110-140	215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Allrad, mit Verbreiterungen
	B36 / B37	45	ZP560D	85-140	215/50, 225/45, 225/50, 235/45, 245/45		mit Radhausverbreiterungen
	B42	45	ZP560D	85, 110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Frontantrieb, mit Radhausverbreiterungen
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		Allrad, mit Radhausverbreiterungen
	AF20	35	AV1	85-140	225/45		mit Radhausverbreiterungen
7,5 x 19	CA 20	45	ZP560D	85, 110	215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Frontantrieb, mit Radhausverbreiterungen
				110, 140	215/50, 225/45, 225/50, 235/45, 245/45		Allrad, mit Radhausverbreiterungen
	B32	43	-	110, 140	225/40, 225/45		Orig.-Verschr.
	RC27	45	-	85, 110	225/40, 235/40		Orig.-Verschr., Frontantrieb
				110, 140	225/45, 245/40		Orig.-Verschr., Allrad
	RC32	45	-	85-110	225/40, 235/40		Orig.-Verschr., Frontantrieb
				110-140	225/45, 245/40		Orig.-Verschr., Allrad
	RC34	45	-	85-110	225/40, 225/45, 235/40		Orig.-Verschr., Frontantrieb
				110-140	225/45, 235/40, 245/40		Orig.-Verschr., Allrad
	B40	45	-	85, 110	225/40, 235/40		Orig.-Verschr., Frontantrieb
8 x 19				110, 140	225/45, 245/40		Orig.-Verschr., Allrad
	B43	45	-	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., Frontantrieb
				110, 140	225/45, 245/40		Orig.-Verschr., Allrad
	RC29	40	-	110, 140	225/40, 225/45, 235/40		Orig.-Verschr.
	B40	40	-	110, 140	225/40, 225/45, 235/40		Orig.-Verschr., mit Radhausverbreiterungen
	RC29	45	ZP560D	110, 140	225/40, 225/45, 235/40, 245/40		ohne Verbreiter. ab 235/40 ✖
	AC-518	38	AV4+R	110, 140	225/40, 225/45		+ Red.Ringe BA25=66,6-57,1
	Oxigin 29	43	ZP560D	85, 110	225/40, 225/45, 235/40, 245/35, 245/40		Frontantrieb, mit Radhausverbreiterungen
				110, 140	225/40, 225/45, 235/40, 245/40		Allrad, mit Radhausverbreiterungen
	B32 / B36	45	ZP560D	110, 140	225/40, 225/45, 235/40		mit Radhausverbreiterungen
	B37	43+45	ZP560D	110, 140	225/40, 225/45, 235/40		mit Radhausverbreiterungen
	B41	39	ZP560D	110-140	225/45		Allrad
	B42	42	ZP560D	110, 140	225/40, 225/45, 235/40		mit Radhausverbreiterungen
8,5 x 19	AF20	40	- +R	110, 140	225/40, 225/45		Orig.-Verschr. +Ringe BA25, mit Radhausverb.
	CA 23	45	ZP560D	85, 110	225/40, 225/45, 235/40		Frontantrieb
				110, 140	225/40, 225/45, 235/40		Allrad
	FMI07 Atena	45	- +R	85-110	235/40		Orig.-Verschr. +Ringe BA25, Frontantrieb ✖
				110-140	225/45, 235/40		Orig.-Verschr. +Ringe BA25, Allrad
	Oxigin 18	45	ZP560D	110, 140	225/40, 225/45, 235/40		mit Radhausverbreiterungen
	Oxigin 28	45	ZP560D	85-140	225/40, 225/45, 235/40		
	B38	41	-	110, 140	225/35, 235/35		Orig.-Verschr., mit Verbreiterung
	B40	40+41	-	110, 140	225/35, 235/35		Orig.-Verschr., mit Verbreiterung
	B43	45	-	85, 110	225/35, 235/35, 245/30, 245/35		Orig.-Verschr., Frontantrieb, mit Verbreiterung
8 x 20				110, 140	225/35, 225/40, 235/35		Orig.-Verschr., Allrad, mit Verbreiterungen
	FMI08 Thoe	45	F31+R	85-110	225/35, 235/35		+ Red.Ringe BA25=66,6-57,1, Frontantrieb
				110-140	225/35, 225/40, 235/35		+ Red.Ringe BA25=66,6-57,1, Allrad
	RC29	45	ZP560D	110, 140	225/35, 235/35		
	RC34	43	ZP560D	110-140	225/35, 225/40, 235/35		nur Allrad
	B24	42	ZP560D	85-140	225/35, 235/35		mit Radhausverbreiterungen
	B42	45	ZP560D	85-140	225/35, 235/35		mit Radhausverbreiterungen
8,5 x 20	AC-518	45	- +R	110, 140	225/35, 235/35		Orig.-Verschr. +Ringe BA25=66,6-57,1
	AC-521	45	-	85-140	225/35, 235/35		Orig.-Verschr.
	FMI07 Atena	39	-	110-140	225/35		Orig.-Verschr., Frontantrieb ✖

Kodiaq		ab 03.2017		NS	5/112	57,1	e8*2007/46*0249*..	
Sensor - direktes RDKS möglich - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	38	-	85-147	215/65		Orig.-Verschr.	
				85-180	215/65M+S			
	RC34	38	-	82-147	215/65		Orig.-Verschr.	
	RC27	39+43	-	85-176	215/65, 225/60, 225/65, 235/60			Orig.-Verschr.
	RC27	40	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.	

7 x 17	RC30	40	-	85-147	215/65		Orig.-Verschr.
				85-180	215/65M+S		
				85-180	215/65, 225/60, 225/65, 235/60, 245/55		
	RC32	40	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	40	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	B39	40	-	92-140	215/65		Orig.-Verschr.
				85-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
	RC27	35	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
		38	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
		42+43+45	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC30	38	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
		45	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC32	38	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
		45	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC27	45	ZP568F (V10)	85-180	215/65, 225/60, 225/65, 235/60		Ausführung "V10"
7,5 x 17	RC24	35	-	92-140	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
		42	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC27	40+41	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC32	43	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	41	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC24	42	ZP560D	85-176	215/65, 225/60, 225/65, 235/60		
	RC28	45	ZP560D	85-180	215/65, 225/60, 225/65		
	RC34	45	ZP560D	82-147	215/65, 225/60, 225/65, 235/60		
	RC29	35	ZP560D	85-180	215/65, 225/60, 225/65, 235/60, 245/55		incl. Scout
		45	ZP560D	85-180	215/65, 225/60, 225/65		incl. Scout, ET45 nicht Bremse 340mm
	B36	35	ZP560D	85-180	215/65, 225/60, 225/65, 235/60, 245/55		
		45	ZP560D	85-180	215/65, 225/60, 225/65		ET45 nicht Bremse 340mm
7 x 18	AC-518	42	AV4+R	85-176	215/65, 225/60, 225/65, 235/60		+ Red.Ringe BA25=66,6-57,1
	Oxigin 14	35	ZP560	92-140	215/65, 225/60, 245/55		
	RC27	43	-	85-147	235/55		Orig.-Verschr.
				85-180	235/55M+S		
				85-180	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC32	43	-	82-140	235/55		Orig.-Verschr.
	RC34	43	-	82-147	235/55		Orig.-Verschr.
				82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC27	45	-	85-180	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC32	40	-	82-147	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
		45	-	82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC32	40	-	110-147	235/55		Orig.-Verschr.
	RC34	40	-	110-147	235/55		Orig.-Verschr.
	RC32	45	-	82-140	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
7,5 x 18	RC34	35	-	82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC30	35	ZP560D	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		
		45	ZP560D	85-180	215/55, 225/55, 225/60		
	B32	35	ZP560D	85-176	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		
		45	ZP560D	85-176	215/55, 225/55, 225/60		
	B39	35	ZP560D	92-140	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		
		45	ZP560D	85-176	215/55, 225/55, 225/60		incl. Scout
	AC-MB6	45	- +R	85-180	215/55, 225/55, 225/60		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 18	37	-	92-140	215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC27	40	-	85-176	225/55, 225/60, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC29	40	-	85-176	225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC32	40	-	82-140	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
8 x 18	RC34	44	-	82-147	215/55, 225/55, 235/50, 235/55		Orig.-Verschr.
		40+45	-	82-147	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., ET45 nicht 245/50
	RC34	30	ZP560D	82-147	215/55, 225/55		
		34	ZP568F	82-147	215/55, 225/55, 235/50, 235/55		
		40+43	ZP560D	82-147	215/55, 225/55, 235/50, 235/55, 245/50		ET43 nicht 245/50
	B24 / B36	35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		incl. Scout
	B37	35	ZP560D	85-176	225/55, 225/60, 235/50, 235/55		
	B38	35	ZP560D	85-140	225/55, 225/60, 235/50, 235/55		
				85-176	225/55, 225/60, 235/50, 235/55		nur M+S
	B42	35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		
	B44	30	ZP560D	85-180	225/55, 225/60		
		35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		
	AC-M10	30	AV4+R	85-180	225/55, 225/60		+ Red.Ringe BA25=66,6-57,1
		40	- +R	85-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	85-176	225/55, 225/60, 235/50, 235/55		+ Red.Ringe BA25=66,6-57,1
	AF18	35+40	AV1	85-176	225/55, 225/60, 235/50, 235/55		

7 x 19	FMI08 Thoe	34	F31	82-147	215/55, 225/55, 235/50, 235/55		
	RC27	43	-	85-176	235/50		Orig.-Verschr., incl. Scout
	RC34	43	-	82-147	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	110-147	235/50		Orig.-Verschr.
	B32	43	-	85-176	235/45, 235/50, 245/45		Orig.-Verschr.
	B39	33+43	ZP560D	85-140	235/45, 235/50, 245/45		
8 x 19	Oxigin 18	37	-	92-140	235/45, 235/50, 245/45		Orig.-Verschr.
	RC29	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC32	40+44	-	82-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		45	-	82-147	235/45, 245/45		Orig.-Verschr.
	RC34	40	-	82-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		45	-	82-147	235/45, 245/45		Orig.-Verschr.
	B40	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	40	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC29	35	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
	RC34	38+43	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
	B24	35	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		incl. Scout
	B38 / B40	38	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
	AC-518	38	AV4+R	85-176	235/45, 235/50, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1
	CA 17	37+43	ZP560D	85-176	235/45, 245/45		
	FMI07 Atena	39	- +R	82-140	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	85-180	235/45, 245/45		
		39	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		
8,5 x 19	B32	34,5	ZP560D	85-180	235/45, 245/45		
	B37	35	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		incl. Scout
	B41	36	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
		39	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
	B42	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		
	B43	38	ZP568F	85-180	235/45, 235/50, 245/45, 255/45		
	B44	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		
	AC-M10	40	- +R	85-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25
	AF18	40	AV1	85-176	235/45, 245/45		incl. Scout
	CA 23	30	ZP560D	85-180	235/45		
		40	- +R	85-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25
	FMI07 Atena	40	- +R	82-140	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25
		45	- +R	82-140	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25
	FMI11 Elatha	32	- +R	82-147	235/45		Orig.-Verschr. + Red.Ringe BA25
	Oxigin 18	35	ZP560D	85-140	235/45, 235/50, 245/45, 255/45		
	Oxigin 20	35+40	ZP560D	92-140	235/45, 245/45		
		45	ZP560D	85-176	235/45, 245/45		
	Oxigin 25	35+45	ZP560D	85-176	235/45, 245/45		incl. Scout
	Oxigin 28	40	ZP560D	85-180	235/45, 245/45		
8 x 20	RC36	41	-	85-180	235/45		Orig.-Verschr.
	B38	41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr.
	B40	41	-	85-176	235/40, 235/45, 245/40		Orig.-Verschr.
	B43	41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr.
	FMI08 Thoe	45	F31+R	82-147	215/45, 235/40, 235/45, 245/40		Red.Ringe BA25=66,6-57,1
8,5 x 20	RC34	38	ZP568F	110-140	255/40		
	B43	38	-	85-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr.
	RC29	38	-	85-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr.
	RC34	38	ZP568F	82-140	235/40, 235/45, 245/40		
	B32	41	-	85-176	235/40, 235/45, 245/40		Orig.-Verschr.
	B41	35	ZP560D	82-147	235/40, 235/45, 245/40		
		45	ZP560D	85-180	235/40, 235/45		
	B42	35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		
		40	ZP560D	85-180	235/40, 235/45, 245/40		
		35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		
	B44	40	ZP560D	85-180	235/40, 235/45, 245/40		
		45	- +R	85-176	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	32	- +R	85-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	45	-	85-180	235/40, 235/45		Orig.-Verschr.
		30	ZP560D	85-180	235/40, 235/45		
	AC-M10	40	- +R	85-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		32	- +R	85-176	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF18	45	- +R	85-176	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 17	35+40	ZP560D	85-180	235/45, 245/40		
	FMI07 Atena	39	- +R	82-140	235/40, 235/45, 245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	B40	42	-	85-180	235/40, 235/45		Orig.-Verschr.
	B43	42	-	85-180	235/40, 235/45		Orig.-Verschr.
	B37	37	ZP560D	85-180	235/40, 235/45, 245/40		
	B40	34	ZP560D	85-176	235/40, 235/45, 245/40		
	B41	38	ZP560D	82-140	235/40, 235/45, 245/40		
	AC-521	42	-	85-180	235/40, 235/45		Orig.-Verschr.
	AC-522	40	- +R	85-180	235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1

8,5 x 21	CA 20	35	ZP560D	85-180	235/40, 235/45		
	FMI11 Elatha	34	-	82-147	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 28	35	ZP560D	85-180	235/40, 235/45, 245/40		
	B43	40	-	85-180	245/35		Orig.-Verschr.
	B41	37+40	ZP560D	82-147	245/35, 255/35		
		43	ZP560D	82-147	245/35		
	B43	38	ZP568F	85-180	245/35, 255/35		
Kodiaq Scout							
ab 2019				NS	5/112	57,1	e8*2007/46*0249*..
Sensor - direktes RDKS möglich - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	38	-	85-147	215/65		Orig.-Verschr.
				85-180	215/65M+S		
	RC34	38	-	82-147	215/65		Orig.-Verschr.
	RC27	39+43	-	85-176	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
7 x 17	RC30	40	-	85-147	215/65		Orig.-Verschr.
				85-180	215/65M+S		
	RC32	40	-	82-147	215/65		Orig.-Verschr.
				82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
	RC34	40	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
	RC32	38	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
		45	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC27	42+45	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
		45	ZP568F (V10)	85-180	215/65, 225/60, 225/65, 235/60		Ausführung "V10"
7,5 x 17	RC24	42	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
	RC27	40	-	85-176	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., ab 141 kW nur mehr M+S
	RC32	43	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	41	-	82-147	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
		45	ZP560D	82-147	215/65, 225/60, 225/65, 235/60		
	RC29	45	ZP560D	85-180	215/65, 225/60, 225/65		
	B36	35	ZP560D	85-180	215/65, 225/60, 225/65, 235/60, 245/55		
7 x 18	RC27	43	-	85-147	235/55		Orig.-Verschr.
				85-180	235/55M+S		
				85-180	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC32	43	-	82-140	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC34	43	-	82-147	235/55		Orig.-Verschr.
				82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		
	RC32	40	-	82-147	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
		45	-	82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
7,5 x 18	RC32	40	-	110-147	235/55		Orig.-Verschr.
	RC34	40	-	110-147	235/55		Orig.-Verschr.
				82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		
	RC32	45	-	82-140	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
	RC34	35	-	82-147	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC30	45	ZP560D	85-176	215/55, 225/55, 225/60		
	AC-MB6	45	- +R	85-180	215/55, 225/55, 225/60		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 18	RC29	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC32	40	-	82-140	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
		44	-	82-147	215/55, 225/55, 235/50, 235/55		Orig.-Verschr.
	RC34	40+45	-	82-147	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., ET45 nicht 245/50
	RC34	30	ZP560D	82-147	215/55, 225/55		
		34	ZP568F	82-147	215/55, 225/55, 235/50, 235/55		
		40+43	ZP560D	82-147	215/55, 225/55, 235/50, 235/55, 245/50		ET43 nicht 245/50
	B24	35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		
	B42	35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		
	B44	30	ZP560D	85-180	225/55, 225/60		
		35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55		
	AC-M10	30	AV4+R	85-180	225/55, 225/60		+ Red.Ringe BA25=66,6-57,1
		40	- +R	85-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI08 Thoe	34	F31	82-147	215/55, 225/55, 235/50, 235/55		
7 x 19	RC27	43	-	85-176	235/50		Orig.-Verschr.
	RC34	43	-	82-147	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	110-147	235/50		Orig.-Verschr.
	B32	43	-	85-176	235/45, 235/50, 245/45		Orig.-Verschr.
	RC32	40+44	-	82-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		45	-	82-147	235/45, 245/45		Orig.-Verschr.
	RC34	40	-	82-147	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		45	-	82-147	235/45, 245/45		Orig.-Verschr.

8 x 19	B40	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	40	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC34	38+43	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
	FMI07 Atena	39	- +R	82-140	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	85-180	235/45, 245/45		
39		ZP560D	85-180	235/45, 235/50, 245/45, 255/45			
8,5 x 19	B41	36	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
		39	ZP560D	82-147	235/45, 235/50, 245/45, 255/45		
	B42	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		
	B43	38	ZP568F	85-180	235/45, 235/50, 245/45, 255/45		
	B44	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		
	AC-M10	40	- +R	85-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 23	30	ZP560D	85-180	235/45		
		40	- +R	85-180	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI07 Atena	40	- +R	82-140	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	- +R	82-140	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
FMI11 Elatha	32	- +R	82-147	235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
	Oxigin 28	40	ZP560D	85-180	235/45, 245/45		
8 x 20	RC36	41	-	85-180	235/45		Orig.-Verschr.
	B40	41	-	85-176	235/45		Orig.-Verschr.
	B43	41	-	85-180	235/45		Orig.-Verschr.
	B40	40	-	85-176	235/40, 235/45, 245/40		Orig.-Verschr.
	B43	45	-	85-180	235/40, 235/45		Orig.-Verschr.
	B43	39	ZP560D	85-180	235/40, 235/45, 245/40		
	FMI08 Thoe	45	F31+R	82-147	215/45, 235/40, 235/45, 245/40		Red.Ringe BA25=66,6-57,1
8,5 x 20	B43	38	-	85-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr.
	RC29	38	-	85-180	255/40		Orig.-Verschr.
	RC34	38	ZP568F	110-140	255/40		
				82-140	235/40, 235/45, 245/40		
	B43	40	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr.
	RC29	40	ZP560D	85-180	235/40, 235/45, 245/40		
		45	ZP560D	85-180	235/40, 235/45		
	RC34	43	ZP560D	82-147	235/40, 235/45, 245/40		
	B24	42	ZP560D	85-180	235/40, 235/45		
	B32	40	ZP560D	85-176	235/40, 235/45, 245/40		
	B41	35	ZP560D	82-147	235/40, 235/45, 245/40		
		B42	30+45	ZP560D	85-180	235/40, 235/45	
	40		ZP560D	85-180	235/40, 235/45, 245/40		
	B43	35+40	ZP560D	85-180	235/40, 235/45, 245/40		
		43	ZP560D	85-180	235/40, 235/45		
	B44	35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		
		40	ZP560D	85-180	235/40, 235/45, 245/40		
	AC-521	32	- +R	85-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	-	85-180	235/40, 235/45		Orig.-Verschr.
	AC-M10	30	ZP560D	85-180	235/40, 235/45		
		40	- +R	85-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI07 Atena	39	- +R	82-140	235/40, 235/45, 245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	B43	42	-	85-180	235/40, 235/45		Orig.-Verschr.
	B37	37	ZP560D	85-180	235/40, 235/45, 245/40		
	B40	34	ZP560D	85-176	235/40, 235/45, 245/40		
	B41	38	ZP560D	82-140	235/40, 235/45, 245/40		
	AC-521	42	-	85-180	235/40, 235/45		Orig.-Verschr.
	CA 20	35	ZP560D	85-180	235/40, 235/45		
	FMI11 Elatha	34	-	82-147	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 21	Oxigin 28	35	ZP560D	85-180	235/40, 235/45, 245/40		
	B43	40	-	85-180	245/35		Orig.-Verschr.
	B41	37+40	ZP560D	82-147	245/35, 255/35		
		43	ZP560D	82-147	245/35		
B43	38	ZP568F	85-180	245/35, 255/35			

Kodiaq RS		ab 2019		NS	5/112	57,1	e8*2007/46*0249*..	
Sensor - direktes RDKS möglich - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC34	38	-	176-180	215/65		Orig.-Verschr.	
7 x 17	RC32	40	-	176-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr., nur M+S	
	RC34	40	-	176-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.	
	RC32	38	-	176	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr., nur M+S	
		45	-	176	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., nur M+S	
7,5 x 17	RC32	43	-	176-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., nur M+S	
	RC34	40+41	-	176-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., nur M+S	

		45	ZP560D	176	215/65, 225/60, 225/65, 235/60		nur M+S
7 x 18	RC27	43	-	176	235/55		Orig.-Verschr.
	RC32	43	-	176	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC34	43	-	176-180	235/55		Orig.-Verschr.
				176-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
	RC32	40	-	176-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., nur M+S
		45	-	176	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
7,5 x 18	RC32	40	-	180	235/55		Orig.-Verschr.
	RC34	40	-	180	235/55		Orig.-Verschr.
				176-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
	RC32	45	-	176	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., nur M+S
8 x 18	RC34	35	-	176-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
	RC32	40	-	176	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
		44	-	176-180	215/55, 225/55, 235/50, 235/55		Orig.-Verschr., nur M+S
	RC34	40+45	-	176-180	215/55, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S
	RC34	43	ZP560D	176-180	215/55, 225/55, 235/50, 235/55		nur M+S
	FMI08 Thoe	34	F31	176-180	215/55, 225/55, 235/50, 235/55		nur M+S
7 x 19	RC34	43	-	176-180	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	180	235/50		Orig.-Verschr.
8 x 19	RC32	40+44	-	176-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC34	40	-	176-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		45	-	176-180	235/45, 245/45		Orig.-Verschr.
	RC34	38+43	ZP560D	176-180	235/45, 235/50, 245/45, 255/45		
	FMI07 Atena	39	- +R	176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 19	B41	36+39	ZP560D	176-180	235/45, 235/50, 245/45, 255/45		
	FMI07 Atena	40	- +R	176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	- +R	176	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI11 Elatha	32	- +R	176-180	235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 20	FMI08 Thoe	45	F31+R	176-180	215/45M+S, 235/40, 235/45, 245/40		Red.Ringe BA25=66,6-57,1
8,5 x 20	RC34	38	ZP568F	176	235/40, 235/45, 245/40, 255/40		
		43	ZP560D	176	235/40, 235/45, 245/40		
	B41	35	ZP560D	176-180	235/40, 235/45, 245/40		
	FMI07 Atena	39	- +R	176	235/40, 235/45, 245/40, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	B41	38	ZP560D	176	235/40, 235/45, 245/40		
	FMI11 Elatha	34	-	176-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 21	B41	40	-	176-180	245/35, 255/35		Orig.-Verschr.
		37+40	ZP560D	176-180	245/35, 255/35		
		43	ZP560D	176	245/35		

Kodiaq NEU		Anfang 2024		PS	5/112	57,1	e8*2018/858*00107*..	
Sensor - direktes RDKS möglich - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	38	-	110, 142	215/65		Orig.-Verschr.	
				110, 142	215/65, 225/60, 235/60			
	RC34	38	-	110-195	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.	
	RC27	40	-	110-150	215/65, 225/60, 235/60		Orig.-Verschr.	
				110-195	215/65, 225/60, 235/60		Orig.-Verschr., nur M+S	
	RC34	43	-	110-142	225/60, 225/65, 235/60		Orig.-Verschr.	
7 x 17	RC32	40	-	110-195	215/65		Orig.-Verschr.	
				110-195	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.	
	RC34	40	-	110-142	215/65		Orig.-Verschr.	
				110-142	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.	
	FMI06 Koros	40	-	110-142	215/65		Orig.-Verschr.	
7,5 x 17	RC27	40	-	110, 142	215/65, 225/60, 235/60		Orig.-Verschr.	
	RC34	40	-	110-195	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.	
		41	-	110-142	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.	
7 x 18	RC32	35	-	110-195	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.	
		40	-	110-195	215/60, 225/55, 225/60, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.	
	RC34	35	-	110-142	215/60, 225/55, 225/60, 235/55		Orig.-Verschr.	
		43	-	110-150	215/60, 225/55, 225/60, 235/55, 245/50, 245/55		Orig.-Verschr.	
7,5 x 18	RC32	40	-	110-150	235/55		Orig.-Verschr.	
				110-195	215/60, 225/55, 225/60, 235/55, 245/50, 245/55			
	RC34	40	-	110-150	235/55		Orig.-Verschr.	
				110-195	215/60, 225/55, 225/60, 235/55, 245/50, 245/55			
8 x 18	RC27	40	-	110, 142	225/55, 235/55		Orig.-Verschr.	
	RC32	40	-	110-195	225/55, 225/60, 235/55		Orig.-Verschr.	
	RC34	40	-	110-195	225/55, 225/60, 235/55		Orig.-Verschr.	
		43	ZP560D	110-195	225/55, 225/60, 235/55			

8 x 18	B44	30	ZP560D	110, 142	225/55		
		35	ZP560D	110, 142	225/55, 235/55		
	AC-MB6	39	- +R	110, 142	225/55, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 20	30	ZP560D	110, 142	225/55		
7,5 x 19	RC34	40	-	110-142	215/50, 225/50, 235/50 , 245/45		Orig.-Verschr.
	CA 26	40	ZP560D	110, 142	225/50, 235/50, 245/45		
8 x 19	RC34	40	-	110-195	215/50, 225/50, 235/50, 245/45, 255/45		Orig.-Verschr.
		43	ZP560D	110-195	215/50, 225/50, 235/50, 245/45, 255/45		
8,5 x 19	CA 20	35	ZP560D	110, 142	235/50, 245/45, 255/45		
		40	- +R	110, 142	245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 20	RC36	41	-	110-195	235/45 , 245/40		Orig.-Verschr., incl. RS
	B43	41	-	110, 142	235/45 , 245/40		Orig.-Verschr.
	RC36	38	-	110-195	235/45, 245/40		Orig.-Verschr.
	B43	39	ZP560D	110, 142	235/45, 245/40		
8,5 x 20	B41	35	ZP560D	110-150	235/45		
9 x 20	RC36	42	-	110-195	235/45		Orig.-Verschr.
	B41	38	ZP560D	110-142	235/45, 245/40		
	CA 23	38	ZP560D	110, 142	235/45, 245/40		
8,5 x 21	B41	40	-	110-195	245/35, 255/35		Orig.-Verschr.
		40	-	110, 142	245/35		Orig.-Verschr.
		38	ZP568F	110, 142	245/35, 255/35		

Kodiahq PHEV NEU	im Laufe 2024	PS	5/112	57,1	e8*2018/858*00107*..
Sensor - direktes RDKS möglich - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	38	-	110	215/65	Orig.-Verschr., Plug-in-Hybrid
		40	-	110	215/65, 225/60, 235/60	Orig.-Verschr.
8 x 18	AC-MB6	39	- +R	110	225/55, 235/55	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
7,5 x 19	CA 26	40	ZP560D	110	225/50, 235/50, 245/45	
8 x 20	RC36	41	-	110	235/45 , 245/40	Orig.-Verschr., Plug-in-Hybrid
	B43	41	-	110	235/45 , 245/40	Orig.-Verschr., Plug-in-Hybrid
	RC36	38	-	110	235/45, 245/40	Orig.-Verschr.
	B43	39	ZP560D	110	235/45, 245/40	
9 x 20	RC36	42	-	110	235/45	Orig.-Verschr.

Octavia III (siehe Konfigurator)	ab 03.13	5E	5/112	57,1	e11*2007/46*0243*...., e11*2007/46*0244*..
---	----------	----	-------	------	--

Octavia III (siehe Konfigurator)	ab Facelift 2017	5E	5/112	57,1	e11*2007/46*0243*20...., e11*2007/46*0244*14..
---	------------------	----	-------	------	--

Octavia IV	ab April 2020	NX	5/112	57,1	e8*2007/46*0355*..
Sensor - direktes RDKS möglich - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	46	-	81-110	205/60, 215/55, 225/55, 235/50	 Orig.-Verschr.
	RC30	46	-	81-110	205/60, 215/55, 225/55, 235/50	 Orig.-Verschr., incl. Facelift 2024
	RC32	46	-	81-110	205/60, 215/55, 225/55, 235/50, 235/55	 Orig.-Verschr.
	RC34	46	-	81-110	205/60, 215/55, 225/55, 235/50, 235/55	 Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55	 Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC24	46	-	85, 110	205/60, 215/55, 215/60, 225/55	 Orig.-Verschr.
	RC27	42	-	81-110	205/60, 215/55, 215/60, 225/55	Orig.-Verschr.
		44	-	85, 110	205/60, 215/55, 215/60, 225/55	Orig.-Verschr.
	RC30	41+42	-	81-110	205/60, 215/55, 215/60, 225/55	Orig.-Verschr.
		44+48	-	85, 110	205/60, 215/55, 215/60, 225/55	Orig.-Verschr.
	RC32	41	-	81-110	205/60, 215/55	Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55	Orig.-Verschr., mit Mehrlenker-Hinterachse
		43	-	81-110	205/60, 215/55, 225/55	Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55	Orig.-Verschr., mit Mehrlenker-Hinterachse
		48	-	81-110	205/60, 215/55, 225/55, 235/50, 235/55	Orig.-Verschr.
	RC34	43	-	81-110	205/60, 215/55, 225/55	Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55	Orig.-Verschr., mit Mehrlenker-Hinterachse
CA 20	45	ZP560D	81-110	205/60, 215/55, 215/60, 225/55		
Pro1	48	F31+R	81-110	205/60, 215/55, 225/55, 235/50, 235/55	+ Ringe BA25, mit Verbundlenker-HA	
			110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55	+ Ringe BA25, mit Mehrlenker-HA	
6,5 x 17	RC27	46	-	81-195	205/55, 215/50, 225/50	 Orig.-Verschr., incl. Facelift 2024
	RC34	46	-	81-195	205/55	 Orig.-Verschr.
			81-110	205/55, 215/50, 225/50	 Orig.-Verschr., mit Verbundlenker-Hinterachse	
			110-195	205/55, 215/50, 215/55, 225/50, 235/50	 Orig.-Verschr., mit Mehrlenker-Hinterachse	
	RC27	39+48,5	-	85, 110	205/55, 215/50, 225/50	Orig.-Verschr.
	RC34	43	-	81-110	205/55, 215/50, 225/50	Orig.-Verschr., mit Verbundlenker-Hinterachse
110-195				205/55, 215/50, 215/55, 225/50, 235/50	Orig.-Verschr., mit Mehrlenker-Hinterachse	
	RC27	46	-	81-110	205/55, 215/50, 225/50	 Orig.-Verschr.
				110-180	205/55, 215/50, 225/50	 Orig.-Verschr.
	RC32	46	-	81-110	205/55, 215/50, 225/50	 Orig.-Verschr.

7 x 17	RC27	40+42+ 43+47	-	81-110	205/55, 215/50, 225/50		Orig.-Verschr.
				110-180	205/55, 215/50, 225/50		Orig.-Verschr., nur M+S
	RC30	38	-	85, 110	205/55, 215/50		Orig.-Verschr.
		45	-	85, 110	205/55, 215/50, 225/50		Orig.-Verschr.
	RC32	40	-	81-195	205/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
		45+49	-	81-110	205/55, 215/50, 225/50		Orig.-Verschr.
		47	-	81-110	205/55, 215/50, 225/50		Orig.-Verschr.
7,5 x 17	CA 26	45	-	81-180	205/55, 215/50, 225/50		Orig.-Verschr.
		42+47	ZP560D	81-180	205/55, 215/50, 225/50		
	RC24	42	-	81-110	205/55, 215/50, 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	205/55, 215/50, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	40	-	85, 110	205/55, 215/50, 235/45		Orig.-Verschr.
	RC32	43	-	81-110	205/55, 215/50, 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
7,5 x 18	RC34	40+41	-	81-110	205/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
		46	-	81-110	205/55, 215/50, 225/50, 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	47	-	81-110	205/55, 215/50, 225/50, 235/45		Orig.-Verschr.
				81-110	205/55, 215/50, 235/45		mit Verbundlenker-Hinterachse
	RC34	45	ZP560D	110-180	205/55, 215/50, 215/55, 225/50, 235/45, 235/50, 245/45		mit Mehrlenker-Hinterachse
	RC28 / RC29	45	ZP560D	81-110	205/55, 215/50, 225/50HA, 235/45		mit Verbundlenker-Hinterachse
				110-180	205/55, 215/50, 225/50HA, 235/45		mit Mehrlenker-Hinterachse
7 x 18	RC32	40	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
		45	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	205/45, 205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	43+49	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
7,5 x 18	RC32	48	-	81-195	205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	48	-	81-195	225/45		Orig.-Verschr.
	B32	48	-	81-180	215/45, 225/45		Orig.-Verschr.
	RC32	45	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	46	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
		48	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC30	35	ZP560D	81-180	215/45		
		45	ZP560D	81-110	215/45, 225/45		
				110	215/45		
	B32	45	ZP560D	110-180	215/45M+S, 225/45		
	B39	45	ZP560D	85, 110	215/45, 225/45		
				81-110	215/45, 225/45		
				110	215/45		incl. Facelift 2024, incl. RS
	AC-MB6 / AC-M10	45	- +R	110-195	215/45M+S, 225/45		
				81-110	215/45		Orig.-Verschr. + BA25=66,6-57,1
	Oxigin 25	51	ZP560D	110-180	215/45M+S, 225/45		
	RC27	46	-	81-110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr., incl. Facelift 2024
				110	215/45, 235/40HA		Orig.-Verschr., Allrad, incl. Facelift 2024
				110-195	215/45M+S, 225/45, 235/40HA		
	RC29	44	-	81-110	215/45, 225/45, 235/40		Orig.-Verschr.
				110	215/45		Orig.-Verschr., Allrad
				110-180	215/45M+S, 225/45, 235/40		
	RC32	44	-	81-110	215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		46	-	81-110	215/45, 225/45, 235/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	40	-	81-110	215/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 215/45, 225/45, 235/40, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
		45	-	81-110	215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-195	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B37	44	-	81-110	215/45, 225/45, 235/40		Orig.-Verschr.
				110	215/45		Orig.-Verschr., Allrad
				110-180	215/45M+S, 225/45, 235/40		
	B38	44	-	85, 110	215/45, 225/45, 235/40		Orig.-Verschr.
	B36 / B42	45	ZP560D	81-110	215/45, 225/45, 235/40HA, 245/40HA		
				110	215/45, 235/40HA		Allrad

8 x 18				110-180	215/45M+S, 225/45, 245/40HA		
	B44	45	ZP560D	81-110	215/45, 225/45, 235/40HA, 245/40HA		
				110	215/45, 235/40HA		
				110-180	215/45M+S, 225/45, 245/40HA		Allrad
	AC-MB6 / AC-M10	45	ZP560D	81-110	215/45, 225/45, 235/40HA, 245/40HA		mit Verbundlenker-HA
				110	215/45, 235/40HA		
				110-180	215/45M+S, 225/45, 245/40HA		mit Mehrlenker-Hinterachse, auch für Hybrid
	AC-521	45	- +R	81-110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr. + BA25, mit Verbundlenker-HA
				110	215/45, 235/40HA		Orig.-Verschr. + BA25=66,6-57,1, mit Mehrlenker-Hinterachse, auch für Hybrid
				110-180	215/45M+S, 225/45, 245/40HA		
	AC-522	45	-	81-110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr., mit Verbundlenker-HA
				110	215/45, 235/40HA		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
				110-180	215/45M+S, 225/45, 245/40HA		
	AF20	48	-	81-110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	215/45, 235/40HA		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
				110-180	215/45M+S, 225/45		Hybrid
	CA 20	45	ZP560D	81-110	215/45, 225/45, 235/40HA, 245/40HA		
				110	215/45, 235/40HA		
				110-180	215/45M+S, 225/45, 245/40HA		Allrad
	FMI08 Thoe	49	F31+R	81-110	215/45, 225/45, 235/40		+ Ringe BA25, mit Verbundlenker-HA
	FMI11 Elatha	45	F95	110-180	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		+ Ringe BA25, mit Mehrlenker-HA
	FMI12 Kari	45	Kit 0353	81-110	215/45, 225/45		mit Verbundlenker-Hinterachse
				110-180	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		mit Mehrlenker-Hinterachse
7,5 x 19	RC34	48	-	110-180	225/40		Orig.-Verschr., auch Hybrid
	B32	43	-	81-180	225/35, 225/40		Orig.-Verschr.
	CA 26	40	ZP560D	81-180	225/35, 225/40		Orig.-Verschr.
	Oxigin 18	50	ZP560D	81-110	225/35, 225/40		
8 x 19	RC32	44+45	-	81-110	225/35, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
		50	-	81-110	225/35, 225/40, 235/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	225/35, 225/40, 235/35		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
	RC34	45	-	81-110	225/35, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
		50	-	81-110	225/35, 225/40, 235/35		Orig.-Verschr.
				110-180	225/35, 225/40, 235/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B40	40	-	85, 110	225/35, 225/40		Orig.-Verschr.
		45	-	85, 110	225/35, 225/40, 245/35		Orig.-Verschr.
	B43	40	-	81-180	225/35, 225/40		Orig.-Verschr.
		45+47	-	81-110	225/35, 225/40, 245/35HA		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-180	225/35, 225/40, 235/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC29	45	ZP560D	81-180	225/35, 225/40, 245/35HA		
	AC-521	45	-	81-180	225/35, 225/40, 245/35HA		Orig.-Verschr.
	CA 19	47	ZP560D	81-180	225/35, 225/40		
	FMI07 Atena	47	- +R	85-110	225/35, 225/40, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		49	-	85-110	225/35, 225/40, 235/35		Orig.-Verschr.
	Oxigin 29	43	ZP560D	81-180	225/35, 225/40, 235/35		
8,5 x 19	B32	45	ZP560D	85, 110	225/35, 225/40		
	B36	45	ZP560D	81-180	225/35, 225/40		
	B37	43+45	ZP560D	81-180	225/35, 225/40		
	B42	42	ZP560D	81-180	225/35, 225/40		
	AC-M10	45	AV4+R	81-180	225/35, 225/40		+ Red.Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	81-180	225/35, 225/40		
	FMI07 Atena	45	- +R	85-110	225/35, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 18	45	ZP560D	85, 110	225/35, 225/40		
	Oxigin 28	45	ZP560D	81-180	225/35, 225/40		
8 x 20	RC36	45	-	81-110	225/30, 225/35, 235/30		Orig.-Verschr., mit Verbundlenker-HA
				110-195	225/35, 235/30		Orig.-Verschr., mit Mehrlenker-HA
		47	-	81-110	225/30, 225/35		Orig.-Verschr., incl. Facelift 2024
				110-195	225/35		
	B40	40+41	-	85, 110	225/30, 225/35		Orig.-Verschr.
	B43	41+47	-	81-110	225/30, 225/35		Orig.-Verschr., mit Verbundlenker-HA
				110-180	225/35		Orig.-Verschr., mit Mehrlenker-HA
		45	-	81-110	225/30, 225/35, 235/30		Orig.-Verschr., mit Verbundlenker-HA
				110-180	225/35, 235/30		Orig.-Verschr., mit Mehrlenker-HA
	B38 / B43	48	ZP560D	81-110	225/30, 225/35		
				110-180	225/35		
	FMI08 Thoe	45	F31+R	81-110	225/30		+ Red.Ringe BA25=66,6-57,1, mit Verbundlenker-Hinterachse
				110-180	225/30, 225/35, 245/30		+ Red.Ringe BA25=66,6-57,1, mit Mehrlenker-Hinterachse

8,5 x 20	RC29	45	ZP560D	81-180	225/35		
	RC34	43	ZP560D	81-110	235/30		✖
	B42	45	ZP560D	81-180	225/35		
	B43	43	ZP560D	81-180	225/35		
	AC-518	45	- +R	81-180	225/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	45	-	81-180	225/35		Orig.-Verschr.
	AF18	45	- +R	81-180	225/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI12 Kari	50	F94	110-180	225/35		mit Mehrlenker-Hinterachse

Octavia IV RS		ab 2020		NX	5/112	57,1	e8*2007/46*0355*..
Sensor - direktes RDKS möglich - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC32	43+46+48	-	110	205/60, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr.
6,5 x 17	RC27	46	-	110-195	205/55, 215/50, 225/50		Orig.-Verschr., incl. Facelift 2024
	RC34	46	-	81-180	205/55		Orig.-Verschr.
		43	-	110-195	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
7 x 17	RC32	46	-	81-110	205/55		Orig.-Verschr.
				110-180	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
		45	-	110-180	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
		47	-	110-180	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
		40+49	-	110-180	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
7,5 x 17	RC32	46	-	110-180	205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr.
	RC34	40	-	110-180	205/55, 215/50, 215/55, 235/45		Orig.-Verschr.
		46	-	110-180	205/55, 215/50, 215/55, 225/50, 235/45, 245/45		Orig.-Verschr., auch für Hybrid
	RC34	45	ZP560D	110-180	205/55, 215/50, 215/55, 225/50, 235/45, 235/50, 245/45		auch für Hybrid
7 x 18	RC32	40+45	-	110-180	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 18	RC32	48	-	110-195	225/45		Orig.-Verschr.
	RC34	48	-	110-195	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
		46	-	110-180	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
	Oxigin 25	51	ZP560D	81-180	225/40, 225/45		
8 x 18	RC27	46	-	110-195	215/45M+S, 225/45, 245/40HA		Orig.-Verschr., incl. Facelift 2024
	RC32	46	-	110-180	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., auch für Hybrid
	RC34	45+46	-	110-180	205/45, 215/45, 225/45, 235/40, 235/45		Orig.-Verschr., auch für Hybrid
	RC34	48	ZP560D	110-180	205/45, 215/45, 225/45, 235/40, 235/45		auch Hybrid
	B24	48	ZP560D	110-180	215/45M+S, 235/40HA		
	FMI11 Elatha	45	F95	110-180	205/45, 215/45, 225/45, 235/40, 235/45, 245/40		
7,5 x 19	RC34	48	-	110-180	225/40		Orig.-Verschr., auch für Hybrid
8 x 19	RC32	40	-	110-180	225/35, 225/40, 235/35		Orig.-Verschr., auch für Hybrid
		44+45	-	110-180	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., auch für Hybrid
		50	-	110-180	225/35, 225/40, 235/35		Orig.-Verschr., auch für Hybrid
	RC34	45	-	110-180	225/35, 225/40, 235/35, 245/35		Orig.-Verschr., auch für Hybrid
		50	-	110-180	225/35, 225/40, 235/35		Orig.-Verschr., auch für Hybrid
	RC34	43	ZP560D	110-180	225/35, 225/40, 235/35, 245/35		
		48	ZP560D	110-180	225/35, 225/40, 235/35		
	CA 19	47	ZP560D	81-180	225/35, 225/40		auch für Hybrid
8,5 x 19	B41	39	ZP560D	110-180	225/35, 225/40		mit Mehrlenker-Hinterachse
8 x 20	RC36	47	-	110-195	225/35		Orig.-Verschr., incl. Facelift 2024
	FMI08 Thoe	45	F31+R	110-180	225/30, 225/35, 245/30		+ Red.Ringe BA25=66,6-57,1, mit Mehrlenker-Hinterachse
8,5 x 20	RC34	43	ZP560D	110-180	225/35, 235/30		auch für Hybrid
	AC-518	45	- +R	110-180	225/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	FMI12 Kari	50	F94	110-180	225/35		mit Mehrlenker-Hinterachse

Octavia Scout III (siehe Konfigurator)		ab Facelift 2017		5E	5/112	57,1	e11*2007/46*0243*21-..	
Octavia Scout IV NEU		ab Februar 2021		NX	5/112	57,1	e8*2007/46*0355*..	
Sensor - direktes RDKS möglich - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	46	-	85, 110	205/60			Orig.-Verschr., nur mit Verbundlenker-HA
	RC24	42+43	-	85, 110	205/60, 215/55, 215/60, 225/55			Orig.-Verschr.
	RC27	42	-	85, 110	205/60, 215/55, 215/60, 225/55			Orig.-Verschr.
		46	-	85, 110	205/60, 215/55, 215/60, 225/55			Orig.-Verschr.
	RC30	41	-	85, 110	205/60, 215/55, 215/60, 225/55			Orig.-Verschr.
7 x 16	CA 20	45	ZP560D	85, 110	205/60, 215/55, 215/60, 225/55			
	RC30	43	-	85, 110	205/60, 215/55, 215/60, 225/55			Orig.-Verschr.
		48	-	85, 110	205/60, 215/55, 215/60, 225/55HA			Orig.-Verschr.
6,5 x 17	RC27	46	-	85, 110	205/55			Orig.-Verschr., mit Verbundlenker-HA
				110	205/55			Orig.-Verschr., Scout 4x4, mit Mehrlenker-HA
				110, 147	205/55			Orig.-Verschr., Scout 4x4, nur M+S
		46	-	85, 110	205/55, 215/50, 225/50			Orig.-Verschr., nur mit Verbundlenkerhinter.
110	205/55, 215/50, 225/50				Orig.-Verschr., Scout 4x4, mit Mehrlenkerhint.			

7 x 17	RC27			110, 147	205/55, 215/50, 225/50		Orig.-Verschr., Scout 4x4, nur M+S
		40+42+43	-	85, 110	205/55, 215/50, 225/50		Orig.-Verschr.
				110	205/55, 215/50, 225/50		Orig.-Verschr., Scout 4x4
				110, 147	205/55, 215/50, 225/50		Orig.-Verschr., Scout 4x4, nur M+S
	CA 26	45	-	85, 110	205/55, 215/50, 225/50		Orig.-Verschr.
				110	205/55, 215/50		Orig.-Verschr., Scout 4x4
				110, 147	205/55, 215/50		Orig.-Verschr., Scout 4x4, nur M+S
		42+47	ZP560D	85, 110	205/55, 215/50, 225/50		
				110	205/55, 215/50		Scout 4x4
				110, 147	205/55, 215/50		Scout 4x4, nur M+S
7,5 x 17	RC24	42	-	85, 110	205/55, 215/50, 235/45		Orig.-Verschr.
				110	205/55, 215/50, 235/45		Orig.-Verschr., Scout 4x4
				110, 147	205/55, 215/50, 235/45		Orig.-Verschr., Scout 4x4, nur M+S
	RC28 / RC29	45	ZP560D	85, 110	205/55, 215/50, 225/50HA, 235/45		
				110	205/55, 215/50, 235/45		Scout 4x4
				110, 147	205/55, 215/50, 235/45		Scout 4x4, nur M+S
	B24	47	ZP560D	85, 110	205/55, 225/50HA		
				110	205/55		Scout 4x4
				110, 147	205/55		Scout 4x4, nur M+S
	Oxigin 25	51	-	81-180	205/50, 205/55		Orig.-Verschr.
7,5 x 18	B32	48	-	85, 110	225/45		Orig.-Verschr.
				110, 147	225/45		Orig.-Verschr., Scout 4x4
	RC30	45	ZP560D	85, 110	215/45, 225/45		
				110	215/45		Scout 4x4
				110, 147	215/45M+S, 225/45		
	B39	45	ZP560D	85, 110	215/45, 225/45		
				110	215/45		Scout 4x4
				110, 147	215/45M+S, 225/45		
	AC-MB6 / AC-M10	45	- +R	110	215/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
				110, 147	215/45M+S, 225/45		
	Oxigin 25	51	ZP560D	81-180	225/40, 225/45		
8 x 18	RC29	44	-	85, 110	215/45, 225/45, 235/40		Orig.-Verschr.
				110	215/45		Orig.-Verschr., Scout 4x4
				110, 147	215/45M+S, 225/45, 235/40		
	B37	44	-	85, 110	215/45, 225/45, 235/40		Orig.-Verschr.
				110	215/45		Orig.-Verschr., Scout 4x4
				110, 147	215/45M+S, 225/45, 235/40		
	B36 / B37 / B42	45	ZP560D	85, 110	215/45, 225/45, 235/40HA, 245/40HA		
				110	215/45		Scout 4x4
				110, 147	215/45M+S, 225/45		
	B44	45	ZP560D	85, 110	215/45, 225/45, 235/40HA, 245/40HA		
				110	215/45		Scout 4x4
				110, 147	215/45M+S, 225/45		
	AC-MB6 / AC-M10	45	ZP560D	85, 110	215/45, 225/45, 235/40HA, 245/40HA		mit Verbundlenker-HA
				110	215/45		Scout 4x4, mit Mehrlenker-Hinterachse
				110, 147	215/45M+S, 225/45		
	AC-521	45	- +R	85, 110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr. + BA25, mit Verbundlenker-HA
				110	215/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, Scout 4x4, mit Mehrlenker-Hinterachse
				110, 147	215/45M+S, 225/45		
	AC-522	45	-	85, 110	215/45, 225/45, 235/40HA, 245/40HA		Orig.-Verschr., mit Verbundlenker-HA
				110	215/45		Orig.-Verschr., Scout 4x4, mit Mehrlenker-Hinterachse
				110, 147	215/45M+S, 225/45		
	AF20	48	-	85, 110	215/45, 225/45, 235/40HA		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	215/45		Orig.-Verschr., Scout 4x4, mit Mehrlenker-Hinterachse
				110, 147	215/45M+S, 225/45		
	CA 20	45	ZP560D	85, 110	215/45, 225/45, 235/40HA, 245/40HA		mit Verbundlenker-Hinterachse
				110	215/45		Scout 4x4, mit Mehrlenker-Hinterachse
				110, 147	215/45M+S, 225/45		
7,5 x 19	CA 26	40	ZP560D	85, 110	225/35, 225/40		
				110	225/35		Scout 4x4
				110, 147	225/40		
8 x 19	B38	44	-	85, 110	225/35, 225/40, 235/35		Orig.-Verschr.
				110	225/35		Orig.-Verschr., Scout 4x4
				110, 147	225/40, 235/35		
	B43	40+47	-	85, 110	225/35, 225/40		Orig.-Verschr.
				110	225/35		Orig.-Verschr., Scout 4x4
				110, 147	225/40		
		45	-	85, 110	225/35, 225/40, 245/35HA		Orig.-Verschr.
				110	225/35		Orig.-Verschr., Scout 4x4
				110, 147	225/40		
	RC29	45	ZP560D	85, 110	225/35, 225/40, 245/35HA		
				110	225/35		Scout 4x4
				110, 147	225/40		
	CA 19	47	ZP560D	81-147	225/35, 225/40		

8,5 x 19	AC-521	45	-	85, 110	225/35, 225/40, 245/35HA		Orig.-Verschr.
				110	225/35		Orig.-Verschr., Scout 4x4
				110, 147	225/40		
	Oxigin 29	43	ZP560D	85, 110	225/35, 225/40, 235/35		Scout 4x4
				110	225/35		
				110, 147	225/40, 235/35		
	B32 / B36	45	ZP560D	85, 110	225/35, 225/40		Scout 4x4
				110	225/35		
				110, 147	225/40		
	B37	43+45	ZP560D	85, 110	225/35, 225/40		Scout 4x4
				110	225/35		
				110, 147	225/40		
	B42	42	ZP560D	85, 110	225/35, 225/40		Scout 4x4
				110	225/35		
				110, 147	225/40		
	AC-M10	45	AV4+R	85, 110	225/35, 225/40		+ Red.Ringe BA25=66,6-57,1
				110	225/35		+ Red.Ringe BA25=66,6-57,1, Scout 4x4
				110, 147	225/40		
	CA 20 / CA 23	45	ZP560D	85, 110	225/35, 225/40		Scout 4x4
				110	225/35		
				110, 147	225/40		
	Oxigin 28	45	ZP560D	85, 110	225/35, 225/40		Scout 4x4
				110	225/35		
				110, 147	225/40		
8 x 20	RC36	45	-	85, 110	225/30, 225/35, 235/30		Orig.-Verschr.
				110	235/30		Orig.-Verschr., Scout 4x4
				110, 147	225/35		
	B43	47	-	85, 110	225/30, 225/35		Orig.-Verschr.
				110, 147	225/35		Orig.-Verschr., Scout 4x4
				85, 110	225/30, 225/35		Orig.-Verschr.
		41+47	-	110, 147	225/35		Orig.-Verschr., Scout 4x4
				85, 110	225/30, 225/35, 235/30		Orig.-Verschr.
				110	235/30		Orig.-Verschr., Scout 4x4
		45	-	110, 147	225/35		
	B38 / B43	48	ZP560D	85, 110	225/30, 225/35		Scout 4x4
				110, 147	225/35		
8,5 x 20	RC29	45	ZP560D	85-147	225/35		
	B42	45	ZP560D	85-147	225/35		
	B43	43	ZP560D	85-147	225/35		
	AC-521	45	-	85-147	225/35		Orig.-Verschr.
	AF18	45	- +R	85-147	225/35		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1

Rapid (siehe Konfigurator)	ab 2013	NH	5/100	57,1	e11*2007/46*0250*...., e11*2007/46*0249*...., e8*2007/46*0320*..
-----------------------------------	----------------	-----------	--------------	-------------	--

Rapid Spaceback (siehe Konfigurator)	ab 2013	NH	5/100	57,1	e11*2007/46*0250*...., e8*2007/46*0320*..
---	----------------	-----------	--------------	-------------	---

Scala	ab 07.2019	NW	5/100	57,1	e8*2007/46*0349*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC27	35	-	66-85	195/65, 205/60, 215/60		Orig.-Verschr.
	RC24	38	-	66-85	195/65, 205/60, 215/60		Orig.-Verschr.
	RC27	38	-	66-85	195/65, 205/60, 215/60		Orig.-Verschr.
	RC30	38	-	66-85	195/65, 205/60, 215/60		Orig.-Verschr.
6 x 16	RC27	35	-	66-110	195/55M+S, 195/60M+S, 205/55		Orig.-Verschr., beide ET's ECE
				66-85	195/55, 195/60		
		38	-	66-110	195/55M+S, 195/60M+S, 205/55, 215/50, 215/55		
				66-85	195/55, 195/60		
	RC30	35	-	66-110	195/55M+S, 195/60M+S, 205/55		Orig.-Verschr., beide ET's ECE
				66-85	195/55, 195/60		
		38	-	66-110	195/55M+S, 195/60M+S, 205/55, 215/50, 215/55		
				66-85	195/55, 195/60		
	RC34	35	-	66-110	195/60, 205/55		Orig.-Verschr., beide ET's ECE
		40	-	66-110	195/60, 205/55, 215/50, 215/55, 225/50		
6,5 x 16	RC27	40	-	66-85	195/55, 195/60		Orig.-Verschr.
				66-110	195/55M+S, 195/60M+S, 205/55		
	RC30	38	-	66-85	195/55, 195/60		Orig.-Verschr.
				66-110	195/55M+S, 195/60M+S, 205/55		
	RC32	40	-	66-110	195/60, 205/55, 215/50, 215/55		Orig.-Verschr.
	CA 20	38	ZP516	66-85	195/55, 195/60		
6,5 x 17	RC27	40	-	66-110	205/50		Orig.-Verschr.
				70-110	195/55M+S, 205/50		Orig.-Verschr.
	RC34	40	-	66-110	205/50		Orig.-Verschr.

7 x 18	RC27	39	-	70-110	195/55M+S, 205/50		Orig.-Verschr.
	RC34	39	-	66-110	195/50, 195/55, 205/50		Orig.-Verschr.
	RC32	39	-	66-110	205/40, 205/45 , 215/40		Orig.-Verschr., ECE nur von 70-110 KW!!!
	RC34	39	-	66-110	205/45		Orig.-Verschr.

Superb III							
ab 2015				3T	5/112	57,1	e11*2001/116*0326*32-..., e11*2007/46*0014*22-..., e8*2007/46*0317*..
Sensor - direktes RDKS möglich - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC30	41	-	88-140	215/60		Orig.Verschr., auch e8*2007/46*0317*..
				88-147	215/60, 225/55, 225/60		Orig.Verschr., incl. Scout
	RC32	41	-	88-147	215/60 , 225/55, 225/60, 235/55		Orig.Verschr.
	RC24	42+43	-	88-147	215/60, 225/55, 225/60		Orig.-Verschr., incl. Scout
	RC27	33+43+44	-	88-140	215/60, 225/55, 225/60		Orig.-Verschr.
		42	-	88-147	215/60, 225/55, 225/60		Orig.-Verschr., incl. Scout
	RC30	42	-	88-147	215/60, 225/55, 225/60		Orig.-Verschr., incl. Scout
	RC32	43	-	88-147	215/60, 225/55, 225/60, 235/55		Orig.Verschr.
	RC34	43	-	88-147	215/60, 225/55, 225/60, 235/55		Orig.Verschr.
	CA 20	45	ZP560D	88-147	215/60, 225/55, 225/60		incl. Scout
7 x 16	RC24	42	-	88-140	215/60, 225/55, 225/60		Orig.-Verschr.
	RC28	35	ZP560D	88-147	215/60, 225/55, 225/60		incl. Scout
	RC34	41	-	88-206	215/55		Orig.-Verschr., auch für Hybrid
6,5 x 17	RC27	39+43	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC27	40	-	88-206	215/50, 215/55 , 225/50, 235/50		Orig.-Verschr., incl. Scout
7 x 17	RC30	40	-	88-206	215/50, 215/55 , 225/50, 235/50		Orig.Verschr., incl. Scout
	RC32	40	-	88-206	215/50, 215/55 , 225/50, 235/50		Orig.Verschr.
	RC34	40	-	88-206	215/50, 215/55 , 225/50, 235/50		Orig.Verschr.
	B39	40	-	88-206	215/50, 215/55 , 225/50, 235/50		Orig.Verschr.
	RC27	42+43	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.Verschr., incl. Scout
	RC30	38+45	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.Verschr.
	RC32	38+45	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.Verschr.
	CA 26	42	ZP560D	88-206	215/50, 215/55, 225/50, 235/50		
		45	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.Verschr.
	RC24	35	-	88-206	215/50, 215/55, 225/50		Orig.-Verschr.
		42	-	88-206	215/50, 215/55, 225/50, 235/50, 245/45		Orig.-Verschr., incl. Scout
7,5 x 17	RC27	40	-	88-206	215/50, 215/55, 225/50, 225/55, 245/45		Orig.-Verschr.
		41	-	88-206	215/50, 215/55, 225/50, 235/50, 245/45		Orig.-Verschr., incl. Scout
	RC32	43	-	88-206	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr.
	RC34	41	-	88-206	215/50, 215/55, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr.
	RC24	42	ZP560D	88-206	215/50, 215/55, 225/50, 235/50, 245/45		
		35	ZP560D	88-206	215/50, 215/55, 225/50		
	RC28	45	ZP560D	88-162	235/50HA		
				88-206	215/50, 215/55, 225/50, 245/45		incl. Scout
				88-206	215/50, 215/55, 225/50, 245/45		
	RC29	35	ZP560D	88-206	215/50, 215/55, 225/50		
		45	ZP560D	88-162	235/50HA		nicht Bremse 340mm
	B36	45	ZP560D	88-206	215/50, 215/55, 225/50, 245/45		nicht Bremse 340mm
				88-162	235/50		
				88-206	215/50, 215/55, 225/50, 245/45		nicht Bremse 340mm
	AC-518	42	AV4+R	88-206	215/50, 215/55, 225/50, 235/50, 245/45		+ Red.Ringe BA25=66,6-57,1
7 x 18	RC32	35+40+43+45	-	88-206	215/45, 215/50, 225/45		Orig.-Verschr., ET40 auch Hybrid Fahrzeuge
	RC34	43	-	88-206	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC32	45	-	88-206	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	RC34	35+40	-	88-206	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC30	35	ZP560D	88-206	215/45, 215/50, 225/45, 235/45		
		45		88-162	215/45, 215/50, 225/45, 235/45		
	B32	35+45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45		incl. Scout
	B39	35+45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45		incl. Scout
	AC-MB6	45	- +R	88-206	215/45, 215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Scout
	Oxigin 18	37	-	88-206	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
8 x 18	RC27	44	-	88-206	235/45		Orig.-Verschr.
				88-140	215/45, 225/45, 235/45		Orig.-Verschr.
	RC29	44	-	88-206	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr., incl. Scout
	RC32	44	-	88-206	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr.
	RC34	44	-	88-206	235/45		Orig.-Verschr.
	B37	44	-	88-206	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr., incl. Scout
	B38	44	-	88-206	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr.
	RC34	40+45	-	88-206	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr.
	B36	35+45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40		ET35 bei 245/40 ✖
	B42	35	ZP560D	88-206	215/45, 225/45, 235/40, 235/45		incl. Scout
		45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40		incl. Scout
	RAA	35	ZP560D	88-206	215/45, 225/45, 235/40, 235/45		incl. Scout

		45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40		incl. Scout
	CA 20	45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40		incl. Scout
	AC-M10	40	- +R	88-206	215/45, 225/45, 235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	88-206	215/45, 225/45, 235/40, 235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	88-206	215/45, 225/45, 235/40, 235/45		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	88-206	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Scout
	AF18	35+40	AV1	88-206	215/45, 225/45, 235/40, 235/45		
	AF20	35	AV1	88-206	215/45, 225/45, 235/40, 235/45		incl. Scout
	FMI08 Thoe	34	F31	88-206	215/45, 225/45, 235/40, 235/45		
7,5 x 19	FMI11 Elatha	39+45	- +R	88-206	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
	B32	43	-	88-206	225/40		Orig.-Verschr., incl. Scout
	B39	33	ZP560D	88-206	225/40		
8 x 19	Oxigin 18	37	-	88-140	225/40		Orig.-Verschr.
	RC27	44	-	88-206	225/40, 235/40		Orig.-Verschr.
	RC32	44	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., auch für Hybrid
	B38	44	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Scout
	RC29	40	-	88-206	225/40, 235/35, 235/40		Orig.-Verschr., incl. Scout
	RC32	40	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., auch für Hybrid
	RC34	40+45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., auch für Hybrid
	B40	40	-	88-206	225/40, 235/35, 235/40		Orig.-Verschr., incl. Scout
		45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Scout
	B43	40	-	88-206	225/40, 235/35, 235/40		Orig.-Verschr., incl. Scout
		45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Scout
	RC34	38	ZP560D	88-206	225/40, 235/35		
		43	ZP560D	88-206	225/40, 235/35, 235/40, 245/35		
	B24	45	ZP560D	88-206	225/40, 235/35, 235/40, 245/35		
	CA 17	37+45	ZP560D	88-206	225/40, 235/40		
	AC-518	38	AV4+R	88-206	225/40, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Scout
	FMI07 Atena	39	- +R	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	39	ZP560D	88-206	225/40, 235/35, 235/40		incl. Scout
		43	ZP560D	88-206	225/40, 235/35, 235/40, 245/35		incl. Scout
8,5 x 19	Oxigin 18	45	ZP560D	88-162	245/35, 255/35		nicht Bremse 340mm, bei 255/35 ✖
				88-206	225/40, 235/35, 235/40		nicht Bremse 340mm
	Oxigin 20	40	ZP560D	88-206	225/40, 235/40		
		45	ZP560D	88-206	225/40		
	Oxigin 25	45	ZP560D	88-206	225/40		
	B32	45	ZP560D	88-162	245/35		incl. Scout
				88-206	225/40, 235/35, 235/40		
	B37	45	ZP560D	88-206	225/40, 235/35, 235/40		incl. Scout
	B41	36	ZP560D	88-206	225/40, 235/35		
		39	ZP560D	88-206	225/40, 235/35, 245/35		
	B42	42	ZP560D	88-206	225/40, 235/35, 235/40		
	B43	38	ZP568F	88-206	225/40		incl. Scout
	B44	42	ZP560D	88-206	225/40, 235/35, 235/40		incl. Scout
	AC-M10	40	- +R	88-206	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	88-206	225/40, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1, incl. Scout
	AF18	40	AV1	88-206	225/40, 235/35, 235/40		
	CA 23	40	- +R	88-206	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	ZP560D	88-206	225/40, 235/35, 235/40		incl. Scout
	FMI11 Elatha	32	- +R	88-206	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 19	Oxigin 28	40+45	ZP560D	88-206	225/40, 235/35, 235/40		incl. Scout
	CA 19	43+44	ZP560D	88-206	225/40		incl. Scout
8 x 20	B38	40+41	-	88-206	225/35, 235/35		Orig.-Verschr.
	B40	40+41	-	88-206	225/35, 235/35		Orig.-Verschr., incl. Scout
	B43	41	-	88-206	225/35, 235/35		Orig.-Verschr., incl. Scout
		45	-	88-206	225/35, 235/35, 245/30		Orig.-Verschr., incl. Scout
8,5 x 20	RC29	45	ZP560D	88-206	225/35, 235/30, 235/35		incl. Scout
	B24	42	ZP560D	88-206	225/35, 235/30, 235/35		incl. Scout
	B42	45	ZP560D	88-206	225/35, 235/30, 235/35		incl. Scout
	AC-521	45	-	88-206	225/35, 235/30, 235/35		Orig.-Verschr., incl. Scout

weitere Dimensionen/Designs siehe Konfigurator

Superb iV III		Plug-in-Hybrid		ab 2019		3T		5/112		57,1		e8*2007/46*0317*..	
Sensor - direktes RDKS möglich - Brocksens 2													
Dimension		Design		ET		KIT		KW		Reifendimension		Info	
7 x 17		RC27		40		-		115		215/50, 215/55, 225/50, 235/50		 Orig.-Verschr.	
		RC30		40		-		115		215/55		 Orig.-Verschr.	
		RC34		40		-		115		215/55		 Orig.-Verschr.	
		B39		40		-		115		215/50, 215/55, 225/50, 235/50		 Orig.-Verschr.	
		RC27		42+43+45		-		115		215/50, 215/55, 225/50, 235/50		Orig.-Verschr.	

	RC30	45	-	115	215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC27	45	ZP568F (V10)	115	215/50, 215/55, 225/50, 235/50		Ausführung "V10"
7,5 x 17	RC24	42	-	115	215/50, 215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC27	40+41	-	115	215/50, 215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC28	45	ZP560D	115	215/50, 215/55, 225/50, 235/50HA, 245/45		
	RC29	35	ZP560D	115	215/50, 215/55, 225/50		
		45	ZP560D	115	215/50, 215/55, 225/50, 235/50HA, 245/45		
	B24	35	ZP560D	115	215/50, 215/55, 225/50		
7,5 x 18	RC30	35+45	ZP560D	115	215/45, 215/50, 225/45, 235/45		
	B32	35+45	ZP560D	115	215/45, 215/50, 225/45, 235/45		
	B39	35+45	ZP560D	115	215/45, 215/50, 225/45, 235/45		
	AC-MB6 / M10	AC-	45	- +R	115	215/45, 215/50, 225/45, 235/45	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 18	RC27	44	-	115	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr.
	B38	44	-	115	215/45, 225/45, 235/40, 235/45 , 245/40		Orig.-Verschr.
	RC29	40	-	115	215/45, 225/45, 235/40, 235/45		Orig.-Verschr.
		44	-	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr.
	B37	44	-	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr.
	RC29	45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		
	B24	35	ZP560D	115	215/45, 225/45, 235/40, 235/45		
	B37	45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		
	B38	35+45	ZP560D	115	215/45, 225/45, 235/40, 235/45		ET45 auch 245/40
	B42	35	ZP560D	115	215/45, 225/45, 235/40, 235/45		
		45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		
	B44	35	ZP560D	115	215/45, 225/45, 235/40, 235/45		
		45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		
	AC-M10	40	- +R	115	215/45, 225/45, 235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	115	215/45, 225/45, 235/40, 235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF20	35	AV1	115	215/45, 225/45, 235/40, 235/45		
	CA 20	45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		
7,5 x 19	B32	43	-	115	225/40		Orig.-Verschr.
8 x 19	RC27	44	-	115	225/40, 235/35, 235/40 , 245/35		Orig.-Verschr.
	B38	44	-	115	225/40, 235/35, 235/40 , 245/35		Orig.-Verschr.
	RC29	40	-	115	225/40, 235/35, 235/40		Orig.-Verschr.
	B40	40	-	115	225/40, 235/35, 235/40		Orig.-Verschr.
		45	-	115	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.
	B43	40	-	115	225/40, 235/35, 235/40		Orig.-Verschr.
		45	-	115	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.
	AC-521	45	-	115	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.
	Oxigin 29	39	ZP560D	115	225/40, 235/35, 235/40		
		43	ZP560D	115	225/40, 235/35, 235/40, 245/35		
8,5 x 19	B32	45	ZP560D	115	225/40, 235/35, 235/40		
	B36	45	ZP560D	115	225/40, 235/35, 235/40, 245/35HA		
	B37	43	ZP560D	115	225/40, 235/35, 235/40		
		45	ZP560D	115	225/40, 235/35, 235/40, 245/35HA		
	B42	42	ZP560D	115	225/40, 235/35, 235/40		
	B43	38	ZP568F	115	225/40		
	AC-M10	40	- +R	115	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	115	225/40, 235/35, 235/40, 245/35HA		+ Red.Ringe BA25=66,6-57,1
	CA 23	40	- +R	115	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	ZP560D	115	225/40, 235/35, 235/40		
8 x 20	Oxigin 28	40	ZP560D	115	225/40, 235/35, 235/40		
		45	ZP560D	115	225/40, 235/35, 235/40, 245/35HA		
	B38	40+41	-	115	225/35, 235/35		Orig.-Verschr.
	B40	40+41	-	115	225/35, 235/35		Orig.-Verschr.
	B43	41	-	115	225/35, 235/35		Orig.-Verschr.
8,5 x 20	B43	45	-	115	225/35, 235/35, 245/30		Orig.-Verschr.
		45	-	115	225/35, 235/35		
	RC29	45	ZP560D	115	225/35, 235/35		
	B24	42	ZP560D	115	225/35, 235/35		
	B42	40	ZP560D	115	225/35		
		45	ZP560D	115	225/35, 235/35		
	B43	43	ZP560D	115	225/35, 235/35		
	AC-518	45	- +R	115	225/35, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
9 x 20	AC-521	45	-	115	225/35, 235/35		Orig.-Verschr.
	AC-M10	40	- +R	115	225/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	B43	42	-	115	225/35, 235/35		Orig.-Verschr.
	Oxigin 28	45	ZP560D	115	225/35, 235/35		

Superb Scout		ab 2019	3T	5/112	57,1	e8*2007/46*0317*15-17
Sensor - direktes RDKS möglich - Brocksens 2						

7 x 17	RC27	40+45	-	88-206	215/50, 215/55, 225/50, 235/50		Orig.-Verschr.
7,5 x 18	RC30	45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45		
8 x 18	B38	44	-	88-206	235/45		Orig.-Verschr.
8,5 x 19	B42	42	ZP560D	88-206	225/40, 235/35, 235/40		
Superb Combi IV NEU		ab 2024		NZ	5/112	57,1	e8*2018/858*00106*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 16	RC30	43	-	110	215/60, 225/55		Orig.-Verschr., nur Bremse 306mm
		43	-	110	215/55		Orig.-Verschr., nur Bremse 306mm
	RC27	35	-	110	215/55		Orig.-Verschr., nur Bremse 306mm
		40+42+45	-	110	215/55, 225/50, 235/50		Orig.-Verschr., nur Bremse 306mm
		35	ZP560D	110	215/55		nur Bremse 306mm
		38	-	110-195	215/55, 225/50		Orig.-Verschr.
	RC32	40+45	-	110-195	215/55, 225/50, 235/50		Orig.-Verschr.
		40	-	110-195	215/55, 225/50, 235/50		Orig.-Verschr.
	RC34	42	ZP560D	110-195	215/55, 225/50, 235/50		
		45	-	110-195	215/55, 225/50, 235/50		Orig.-Verschr.
7,5 x 17	RC27	41	-	110-195	215/55, 225/50, 245/45		Orig.-Verschr.
	RC34	41	-	110-195	215/55, 225/50, 245/45		Orig.-Verschr.
	RC27	40	-	110	215/55, 225/50, 245/45		Orig.-Verschr., nur Bremse 306mm
	RC34	40	-	110-195	215/55, 225/50, 245/45		Orig.-Verschr.
	CA 20	45	- +R	110	215/55, 225/50, 235/50, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, nur Bremse 306mm
7 x 18	RC27	45	-	110-195	215/50, 225/45		Orig.-Verschr.
	RC32	35+40	-	110-195	215/45, 215/50, 225/45		Orig.-Verschr.
	RC34	35+43	-	110-195	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC32	40+45	-	110-195	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	RC34	40+46	-	110-195	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	B32 / B39	45	ZP560D	110-195	215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	45	- +R	110-195	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8 x 18	RC27	44	-	110-195	225/45, 235/45, 245/40		Orig.-Verschr.
	RC32	44	-	110-195	215/45, 215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC34	44	-	110-195	215/45, 215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC27	40	-	110	225/45, 235/45		Orig.-Verschr., nur Bremse 306mm
	RC32	40	-	110-195	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
		40	-	110-195	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
		45	-	110-195	215/45, 215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC34	43	ZP560D	110-195	215/45, 215/50, 225/45, 235/45, 245/40, 245/45		
		35	ZP560D	110	225/45		nur Bremse 306mm
		45	ZP560D	110	225/45, 235/45, 245/40		nur Bremse 306mm
	B44	39	- +R	110-195	225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	ZP560D	110-195	225/45, 235/45, 245/40		
		45	ZP560D	110	225/45, 235/45, 245/40		nur Bremse 306mm
7,5 x 19	CA 20	45	ZP560D	110	225/45, 235/45, 245/40		nur Bremse 306mm
	RC34	40	-	110-195	215/40, 215/45, 225/40		Orig.-Verschr.
	CA 26	40	ZP560D	110-195	225/40		
	RC27	44	-	110-195	235/40		Orig.-Verschr.
8 x 19	RC32	44	-	110-195	235/40		Orig.-Verschr.
				110-195	215/40, 215/45, 225/40, 235/40, 245/35		Orig.-Verschr.
				110-195	215/40, 215/45, 225/40, 235/40		Orig.-Verschr.
	RC34	45	-	110-195	215/40, 215/45, 225/40, 235/40, 245/35		Orig.-Verschr.
				110-195	215/40, 215/45, 225/40, 235/40, 245/35		Orig.-Verschr.
				110-195	215/40, 215/45, 225/40, 235/40, 245/35		
	B43	45	-	110-195	225/40, 235/40, 245/35		Orig.-Verschr.
				110	225/40, 235/40		nur Bremse 306mm
				110	225/40, 235/40, 245/35		nur Bremse 306mm
8,5 x 19	CA 20	40	- +R	110	225/40, 235/40		nur Bremse 306mm
		45	ZP560D	110	225/40, 235/40, 245/35HA		nur Bremse 306mm
8 x 20	RC36	38+41+45	-	110-195	225/35, 235/35, 245/30		Orig.-Verschr.
	B43	41+45	-	110-195	225/35, 235/35, 245/30		Orig.-Verschr.
9 x 20	CA 20 / CA 23	45	ZP560D	110	225/35, 235/35		nur Bremse 306mm
Superb Combi PHEV IV NEU		ab 2024		NZ	5/112	57,1	e8*2018/858*00106*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 17	CA 26	45	-	110	215/55, 225/50, 235/50		Orig.-Verschr.
		42	ZP560D	110	215/55, 225/50, 235/50		
7,5 x 17	RC27	41	-	110	215/55		Orig.-Verschr.
7 x 18	RC27	45	-	110	215/50, 225/45		Orig.-Verschr.
7,5 x 18	B32 / B39	45	ZP560D	110	215/50, 225/45, 235/45		Plug-in-Hybrid
	AC-MB6	45	- +R	110	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	RC27	44	-	110	235/45		Orig.-Verschr.

8 x 18	AC-MB6	39	- +R	110	225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	ZP560D	110	225/45, 235/45, 245/40		
7,5 x 19	CA 26	40	ZP560D	110	225/40		
8 x 19	RC27	44	-	110	235/40		Orig.-Verschr.
	B43	45	-	110	225/40, 235/40, 245/35		Orig.-Verschr.
8 x 20	RC36	38+41+ 45	-	110	235/35		Orig.-Verschr.
	B43	41+45	-	110	235/35		Orig.-Verschr.

Smart	Baujahr	Typ	LK/LZ	Nabe
Fortwo (siehe Konfigurator)	ab 2014	451/453	4/100	60,1

Fortwo / Forfour electric drive		ab 11.2017	451	4/100	60,1	e1*2001/116*0413*33-... e1*2001/116*0413*35-... (FIN: WME453...)	
Sensor - Brocksens 3							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
5 x 15	RC19	32	-	41 (60)	VA 165/60, 165/65 , 175/60		Orig.-Verschr.
5,5 x 15		42			HA 185/55, 185/60 , 195/55		
6 x 15	RC24	37	ZP440F	41 (60)	165/60, 165/65, 175/60, 185/55, 185/60		ab 185/55 ✖
		40	ZP440	41 (60)	165/60, 165/65, 175/60, 185/55, 185/60		
	RC30	37	ZP440F	41 (60)	165/60, 165/65, 175/60, 185/55, 185/60		ab 185/55 ✖
		40	ZP440	41 (60)	165/60, 165/65, 175/60, 185/55, 185/60		
6,5 x 16	RC24	38	ZP440	41 (60)	VA 185/50, HA 205/45		bei 205/45 ✖
	RC30	38	ZP440	41 (60)	VA 185/50, HA 205/45		ohne Radhausverbr. bei 205/45 ✖
7 x 17	B39	38	ZP440	41 (60)	VA 185/45, 195/40, HA 205/40		ohne RTbei 205/40 ✖

Forfour		ab 2014		454/451		4/100		60,1		e1*2001/116*0413*23-...	
Sensor - Brocksens 3											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
5 x 15	RC19	32	-	45-80	165/50, 165/65 , 175/60, 185/55, 185/60				Orig.-Verschr.		
5,5 x 15		42	-		185/55, 185/60 , 195/55, 205/50, 205/55						
6 x 15	RC24	37	ZP440F	45-80	VA 165/60+HA 185/55, VA165/65+HA 185/60 VA 175/60+HA 195/55, VA185/55+HA 205/50				ab 185/55 ✖		
		40	ZP440	45-80	165/60, 165/65, 175/60, 185/55, 185/60, 195/55, 205/50, 205/55				ab 195/55 ✖		
	RC30	37	ZP440F	45,52,66	VA 165/60+HA 185/55, VA165/65+HA 185/60 VA 175/60+HA 195/55, VA185/55+HA 205/50				ab 195/55 ✖		
		40	ZP440	45-80							
6 x 16	RC34	44	-	41-80	VA 175/50, 175/55, 185/50 , 195/45				Orig.-Verschr., ohne Radhausverbr. bei 195/50 ✖		
6,5 x 16		40			HA 185/50, 195/45, 195/50, 205/45						
6,5 x 16	RC24	38	ZP440	45-80	VA 185/50, HA 205/45				✖		
7 x 17	B24	38	ZP440	45, 52, 66	VA 195/40 + HA 215/35						

Smart #1 NEU		im Laufe 2023		HX11	5/108	63,4	e1*2018/858*00227*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 18	RC27	50	-	75, 116	235/50			Orig.-Verschr.
	RC34	50	-	75-116	235/50			Orig.-Verschr.
	FMI06 Koros	50	-		235/50			Orig.-Verschr., i.V.
7,5 x 18	RC30	46	-	75, 116	245/45			Orig.-Verschr.
	RC34	46	-	75-116	245/45			Orig.-Verschr.
7,5 x 19	B32	50	-	75, 116	235/50, 245/45			Orig.-Verschr.
	CA 26	45	ZP531	75, 116	235/45			
8 x 19	RC27	48	-	75, 116	235/45, 245/40			Orig.-Verschr.
	RC34	48	-	75-116	235/45, 245/40			Orig.-Verschr., Ausführung X8
	FMI06 Koros	48	-		235/45			Orig.-Verschr.
	RC27	48,5	-(X8)	75, 116	235/45, 245/40			Orig.-Verschr., Ausführung X8
	RC32	45	ZP561F	75-116	235/45			
	RC34	45	-	75-116	235/45			Orig.-Verschr.
		48,5	-(X8)	75-116	235/45, 245/40			Orig.-Verschr., Ausführung X8
	B40	45	ZP569F	75	235/45			Orig.-Verschr.
		50	-	75, 116	235/45, 245/40			Orig.-Verschr.
	B43	47,5	-	75, 116	235/45, 245/40			Orig.-Verschr.
8 x 20	Oxigin 29	45	ZP531	75, 116	235/45			
	RC36	47,5	-	75, 116	235/40, 245/35			Orig.-Verschr.
		48,5	-	75, 116	235/40, 245/35			Orig.-Verschr.
	B43	48,5+50	-	75, 116	235/40, 245/35			Orig.-Verschr.
		50,5	-	75, 116	235/40, 245/35			Orig.-Verschr.
8,5 x 20	RC36	47,5	-	75, 116	235/40			Orig.-Verschr.
	B43	47,5	-	75, 116	235/40			Orig.-Verschr.

Smart #3 NEU		4. Quartal 2023		HC11	5/108	63,4	e1*2018/858*00349*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
	RC27	48,5	- (X8)	75, 116	225/45, 225/50, 235/45, 245/45			Orig.-Verschr., Ausführung X8
	RC34	48,5	- (X8)	75-116	245/45 , 255/45			Orig.-Verschr., Ausführung X8
		48,5	ZP561F	75-116	245/45			Ausführung X8

8 x 19	FMI06 Koros	48,5	-		245/45		Orig.-Verschr.
	RC32	45	ZP561F	75-116	245/45, 255/45		
	RC34	48	-	75-116	245/45, 255/45		Orig.-Verschr.
	RC27	48	-		245/45		Orig.-Verschr., TÜV i.V.
	B43	47,5	ZP561F	75, 116	245/45		
8,5 x 19	B32	45	-	75, 116	245/45, 255/40		Orig.-Verschr.
	B36	44	ZP531	75, 116	245/45, 255/40		
	B43	45	ZP561F	75, 116	245/45, 255/40		
	B44	42	ZP561F	75, 116	245/45, 255/40		
	RC36	48,5	-	75, 116	245/40		Orig.-Verschr.
8 x 20	B43	48,5	ZP561F	75, 116	245/40		
	RC36	47,5	-	75, 116	245/40		Orig.-Verschr.
	B43	50,5	ZP561F	75, 116	225/40, 235/40, 245/40		
8,5 x 20	RC36	45	-	75, 116	245/40, 255/35		Orig.-Verschr.
		47,5	-	75, 116	245/40, 255/35		Orig.-Verschr.
	B43	47,5	ZP561F	75, 116	245/40, 255/35		
8,5 x 21	B41	45	ZP561F	75-116	245/35, 255/35		
	B43	49,5	ZP561F	75, 116	245/35		
9,5 x 21	B43	45	ZP561F	75, 116	245/35		

Smart #5 NEU		ab 2025		HY11	5/108	63,4	e1*2018/858*00532*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 19	FMI06 Koros	43,5	-		245/50			Orig.-Verschr.
8,5 x 20	FMI10 e-Joule	43,5						i.V., Lieferzeit ca. Mitte - Ende August, nur in der Farbe glossy black erhältlich

Ssang Yong		Baujahr	Typ		LK/LZ	Nabe	
Korando 4WD (IV)		ab 2019		CW / CWN	5/112	66,6	
Sensor - HUF RDE216 - Artikelnummer 88010							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	45,5	-	100-120	225/60		Orig.-Verschr.
				100-120	225/60, 235/60		Orig.-Verschr., auch Typ CWN
7 x 17	RC30	35	ZP590F	100-120	225/60, 235/60		nur Bremse 298mm
	B39	35	ZP590F	100-120	225/60, 235/60		nur Bremse 298mm
7,5 x 17	CA 26	42	ZP590F	100-120	225/60, 235/60, 245/55		
	RC29	45	ZP590F	100-120	225/60, 235/60		nur Bremse 298mm
	B36	45	ZP590F	100-120	225/60, 235/60		nur Bremse 298mm
7,5 x 18	B32 / B39	45	ZP590F	100-120	225/55, 235/55		nur Bremse 298mm
	CA 20	40	ZP590F	100-120	225/55, 235/50, 235/55		
8 x 18	RC34	40	ZP590F	100-120	225/55, 235/50, 235/55		
	B42	35	ZP590F	100-120	225/55		
7,5 x 19	RC34	45,5	ZP590F	100-120	235/45, 235/50, 245/45		
8 x 19	RC29	45	ZP590F	100-120	235/45, 245/45		nur Bremse 298mm
	B24	45	ZP590F	100-120	235/45, 245/45		nur Bremse 298mm
	B40	43	ZP590F	100-120	235/45, 235/50, 245/45, 255/45		nur Bremse 298mm
	CA 17	37	ZP590F	100-120	235/45		
		45	ZP590F	100-120	235/45, 245/45		
	CA 24	43	ZP590F	100-120	235/45, 245/45		
	Oxigin 29	39+43	ZP590F	100-120	225/50, 235/45, 235/50, 245/45, 255/45		
8,5 x 19	B32	45	ZP590F	100-120	235/45, 245/45		nur Bremse 298mm
	B37	43+45	ZP590F	100-120	235/45, 245/45		nur Bremse 298mm
	B42	35	ZP590F	100-120	235/45		nur Bremse 298mm
		42	ZP590F	100-120	235/45, 235/50, 245/45, 255/45		nur Bremse 298mm
	B44	42	ZP590F	100-120	235/45, 235/50, 245/45, 255/45		
	AC-M10	45	ZP590F	100-120	235/45, 245/45		
	AF20	40	ZP590F	100-120	235/45, 245/45		nur Bremse 298mm
9 x 19	CA 19	43+44	ZP590F	100-120	235/45		
	FMI08 Thoe	41	F28	100-120	235/45, 245/45		
8 x 20	B38	35	ZP590F	100-120	235/40, 235/45, 245/40		nur Bremse 298mm
8,5 x 20	RC29	40	ZP590F	100-120	235/40, 235/45, 245/40		nur Bremse 298mm
	B24	42	ZP590F	100-120	235/40, 235/45, 245/40, 255/40		nur Bremse 298mm
	B32	40	ZP590F	100-120	235/40, 235/45, 245/40		nur Bremse 298mm
	B42	35+45	ZP590F	100-120	235/40, 235/45		nur Bremse 298mm
		40	ZP590F	100-120	235/40, 235/45, 245/40		nur Bremse 298mm
	B44	35	ZP590F	100-120	235/40, 235/45		
		40	ZP590F	100-120	235/40, 235/45, 245/40		
	AC-518	45	12x1,5, Kugel R13, 28mm	100-120	235/40, 235/45		nur Bremse 298mm
	CA 17	40	ZP590F	100-120	235/45		
CA 19	45	ZP590F	100-120	235/45			
9 x 20	CA 23	45	ZP590F	100-120	235/40, 235/45		
9 x 21	B32	40+48	ZP590F	100-120	245/35		nur Bremse 298mm
Korando e-Motion NEU		ab 2022		EK	5/112	66,6	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	45,5	-	75 (140)	215/65		Orig.-Verschr.
				75 (140)	215/65, 225/60, 235/60		
7 x 17	RC27	35	ZP590F	75 (140)	215/65, 225/60, 235/60		
	RC30	35	ZP590F	75 (140)	215/65, 225/60, 235/60		
	CA 26	42	ZP590F	75 (140)	215/65, 225/60, 235/60, 245/55		
7,5 x 17	RC24	42	ZP590F	75 (140)	215/65, 225/60, 235/60, 245/55		
	RC29	35	ZP590F	75 (140)	215/65, 225/60		
		45	ZP590F	75 (140)	215/65, 225/60, 235/60		
	B24	35	ZP590F	75 (140)	215/65, 225/60		
	B36	45	ZP590F	75 (140)	215/65, 225/60, 235/60		
7,5 x 18	RC30	35	ZP590F	75 (140)	215/60, 225/55		
		45	ZP590F	75 (140)	215/60, 225/55, 235/55		
	B32	45	ZP590F	75 (140)	215/60, 225/55, 235/55		
8 x 18	CA 20 / CA 23	40	ZP590F	66-75	215/60, 225/55		
	RC25	45	ZP590F	75 (140)	225/55		
	B24	35	ZP590F	75 (140)	225/55		
	B36	35+45	ZP590F	75 (140)	225/55		
	B42	35+45	ZP590F	75 (140)	225/55		
	B44	35+45	ZP590F	75 (140)	225/55		
	AC-MB6	45	ZP590F	75 (140)	225/55		
	AC-M10	45	ZP590F	75 (140)	225/55		
CA 20 / CA 23	45	ZP590F	75 (140)	225/55			

7,5 x 19	RC34	45,5	ZP566F	66-75	215/50, 225/50, 235/50, 245/45		
	RC29	45	ZP590F	75 (140)	225/50, 245/45		
	B38	45	ZP590F	75 (140)	225/50, 245/45		
	B40	43	ZP590F	75 (140)	225/50, 235/50, 245/45, 255/45		
8 x 19	Oxigin 29	39+43	ZP590F	75 (140)	225/50, 235/50, 245/45, 255/45		
	D17	44	ZP590F	75 (140)	245/45		
	B32	45	ZP590F	75 (140)	245/45		
	B37	45	ZP590F	75 (140)	245/45		
	B42 / B44	42	ZP590F	75 (140)	235/50, 245/45, 255/45		
	AC-M10	45	ZP590F	75 (140)	245/45		
	CA 20 / CA 23	45	ZP590F	75 (140)	245/45		
8,5 x 19	CA 26	40	ZP590F	75 (140)	245/45		
	RC36	39	ZP590F	75 (140)	235/40, 235/45, 245/40		
	B38	35	ZP590F	75 (140)	235/40, 235/45, 245/40		
	B24	42	ZP590F	75 (140)	235/40, 235/45, 245/40, 255/40		
8,5 x 20	B42	40	ZP590F	75 (140)	235/40, 235/45, 245/40		
	B44	35	ZP590F	75 (140)	235/40, 235/45		
		40	ZP590F	75 (140)	235/40, 235/45, 245/40		
		40	ZP590F	75 (140)	235/40, 235/45, 245/40		
9 x 20	B37	37	ZP590F	75 (140)	235/40, 235/45		
	CA 20 / CA 23	45	ZP590F	75 (140)	235/40, 235/45		

Musso		ab 2018		QK	5/130	84,1	e9*2007/46*6620*..	
Sensor - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC25T	33	-	133	235/70			Orig.-Verschr.
7,5 x 18	B45	43	-	133, 149	235/65, 245/60, 255/60			Orig.-Verschr., nicht für Blattfederung HA
8 x 20	B40	43	-	133	235/55, 255/50			Orig.-Verschr.
	B45	43	-	133, 149	235/55, 255/50			Orig.-Verschr.

Musso Grand		ab 02.2020		QK	5/130	84,1	e9*2007/46*6620*..., e6*KS07/46*0278*..	
Sensor - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
7 x 17	RC25T	33	-	133	235/70		Orig.-Verschr.	
7,5 x 18	B45	43	-	133, 149	235/65, 245/60, 255/60		Orig.-Verschr.	
8 x 20	B45	43	-	133, 149	235/55, 255/50		Orig.-Verschr.	

Rexton II (siehe Konfigurator)		ab 2002 - 2017		RJ	5/130	84,1	
--------------------------------	--	----------------	--	----	-------	------	--

Rexton III		ab 2017		YK, YKUK, YKA		5/130		84,1		e9*2007/46*6541*.., e11*2007/46*4188*.., e6*2007/46*0237*..	
Sensor - Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 17	RC25T	33	-	133-165	235/70				Orig.-Verschr.		
7,5 x 18	B45	43	-	133-165	235/65, 245/60, 255/60				Orig.-Verschr.		
8 x 20	B45	43	-	133-165	235/55, 255/50				Orig.-Verschr.		

Tivoli		ab 2015		XK, XKG		5/112		66,6		e9*2007/46*6294*..., e50*2007/46*0198*...	
Sensor - Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6 x 16	RC30	43	ZP590F	84-95	205/55, 205/60 , 215/55				2WD		
					205/55, 205/60 , 215/55, 225/50, 225/55				4WD		
6,5 x 16	RC24 / RC30	46	ZP590F	84-95	205/55, 205/60				2WD		
					205/55, 205/60, 215/55, 225/50, 225/55				4WD		
	RC32	39,5	-	94-120	205/55, 205/60, 215/55, 225/50				Orig.-Verschr.		
					205/55, 205/60				2WD		
					205/55, 205/60, 215/55, 225/50, 225/55				4WD		
CA 20	45	ZP590F	84-95	205/55, 205/60				2WD			
				205/55, 205/60, 215/55, 225/50, 225/55				4WD			
7 x 16	RC28	45	ZP590F	84-95	205/55, 205/60				2WD		
					205/55, 205/60, 215/55				4WD		
7 x 17	CA 26	42	ZP590F	84-95	205/50, 205/55, 225/45				2WD		
				84-95	205/50, 205/55, 215/50, 225/45				4WD		
7,5 x 17	RC24	42	ZP590F	84-95	205/50, 205/55, 225/45				2WD		
				84-95	205/50, 205/55, 215/50, 225/45, 235/45				4WD		
7,5 x 18	RC30	45	ZP590F	84-95	205/45, 215/45				2WD		
				84-95	205/45, 215/45, 225/40, 225/45				4WD		
	B32	35	ZP590F	84-95	205/45				2WD		
				84-95	205/45, 215/45				4WD		
		45	ZP590F	84-95	205/45, 215/45				2WD		
				84-95	205/45, 215/45, 225/40, 225/45				4WD		
	B39	35	ZP590F	84-95	205/45				2WD+4WD		
				84-95	205/45, 215/45				2WD		
		45	ZP590F	84-95	205/45, 215/45, 225/40, 225/45				4WD		
				84-95	225/40				2WD+4WD		
	RC29	45	ZP590F	84-95	215/45, 225/40, 225/45				4WD		
215/45, 225/40, 225/45					4WD						

8 x 18	B38	45	ZP590F	84-95	215/45, 225/40, 225/45		4WD
	B36 / B42 / B44	45	ZP590F	84-95	215/45, 225/40, 225/45		4WD
	AC-M10	45	ZP590F	84-95	215/45, 225/40, 225/45		4WD
	CA 23	45	ZP590F	84-95	215/45, 225/40, 225/45		4WD
Tivoli		ab MJ 2021		XK	5/112	66,6	e9*2007/46*6294*10..
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 16	RC30	43	ZP590F	94-120	205/60		
6,5 x 16	RC32	39,5	-	100-120	205/65, 215/60		Orig.-Verschr.
	CA 20	45	ZP590F	94-120	205/60		2WD
				100, 120	205/65, 215/60		
				100, 120	205/60, 205/65, 215/60		4WD
7 x 17	CA 26	42	ZP590F	100, 120	205/60, 215/55		2WD
				94-120	205/55, 215/50		
				100, 120	205/55, 205/60, 215/50, 215/55		4WD
7,5 x 18	RC30	45	ZP590F	120	215/45		2WD
				100, 120	215/45		4WD
	B32	45	ZP590F	120	215/45		2WD
				100, 120	215/45		4WD
	B39	45	ZP590F	94-120	215/45		2WD
				100, 120	215/45		4WD
7,5 x 19	RC34	45,5	ZP566F	100-120	225/40		
Torres NEU		2023		CW	5/112	66,6	e8*2007/46*0360*10-..., e6*2018/858*00325*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	45,5	-	120	225/60		Orig.-Verschr.
				120	225/60, 225/65, 235/60		
7 x 17	RC27	35	ZP590F	120	225/60, 225/65, 235/60		
	CA 26	42	ZP590F	120	225/60, 225/65, 235/60, 245/55		
7,5 x 17	B24	35	ZP590F	120	225/60, 225/65		
7,5 x 18	B32	45,5			235/55		erhältlich in den Farben TM u. HGVP
	RC30	35	ZP590F	120	225/55, 225/60		
		45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55, 255/50		
	B32	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55, 255/50		
	CA 20	40	ZP590F	120	225/50, 225/55, 225/60, 235/50, 235/55		
8 x 18	B36 / B42	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55		
	B44	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55		
	AC-MB6	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55		
	AC-M10	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55		
	CA 20 / CA 23	45	ZP590F	120	225/55, 225/60, 235/55, 245/50, 245/55		
7,5 x 19	RC34	45,5	ZP566F	120	225/45, 225/50, 225/55, 235/45, 235/50, 245/45, 245/50		
8 x 19	B40	38	ZP590F	120	225/50, 225/55, 245/45		
		43	ZP590F	120	225/50, 225/55, 235/50, 245/45, 255/45		
	CA 24	43	ZP590F	120	225/50, 245/45		
	Oxigin 29	39	ZP590F	120	225/50, 225/55, 245/45		
		43	ZP590F	120	225/50, 225/55, 235/50, 245/45, 255/45		
8,5 x 19	B32	45	ZP590F	120	235/50, 245/45, 255/45		
	B44	42	ZP590F	120	235/50, 245/45, 255/45		
	AC-M10	45	ZP590F	120	235/50, 245/45, 255/45		
	CA 20 / CA 23	45	ZP590F	120	235/50, 245/45, 255/45		
	CA 26	40	ZP590F	120	245/45		
9 x 19	FMI08 Thoe	41	F28	120	235/45		
8 x 20	RC36	39	ZP590F	120	235/45, 245/40, 245/45		
	B42	40	ZP590F	120	235/45, 245/40, 245/45		
8,5 x 20	B44	35	ZP590F	120	235/45		
		40	ZP590F	120	235/45, 245/40, 245/45		
9 x 20	CA 20 / CA 23	45	ZP590F	120	235/45, 245/40, 245/45, 255/40		
9 x 21	CA 20	45	ZP590F	120	245/35, 245/40, 255/35		

Subaru		Baujahr	Typ	LK/LZ	Nabe	
BRZ		ab 06.12	ZC	5/100	56,1	e13*2007/46*1281*..., e13*2001/116*0026*05-...
Sensor - Brocksens 6						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC34	48	-	147	205/55	 Orig.-Verschr.
	RC27	48	-	147	205/55, 225/50	 Orig.-Verschr.
7 x 16	RC28	38	ZP514	147	205/55, 225/50	bei 225/50 ✖
7 x 17	RC30	48	-	147	205/45, 205/50, 215/45, 225/45	 Orig.-Verschr.
	RC34	48	-	147	215/45	 Orig.-Verschr.
	RC27	43	ZP514	147	205/45, 205/50, 215/45, 225/45	incl. Facelift 2016, Bremse max. 294mm
	RC30	43	ZP514	147	205/45, 205/50, 215/45, 225/45	
7,5 x 17	RC28	38	ZP514	147	205/45, 205/50, 215/45, 225/45	205/50 u. 225/45 ✖
	B36	38	ZP514	147	205/45, 205/50, 215/45, 225/45	205/50 u. 225/45 ✖
7 x 18	RC27	48	-	147	215/35, 215/40	Orig.-Verschr.
7,5 x 18	B39	42	ZP514	147	215/40, 225/35, 225/40	incl. Facelift 2016
weitere Dimensionen/Designs siehe Konfigurator						

BRZ NEU i.V.		1.Halbjahr 2023	Z2	5/100	56,1	
Sensor - Brocksens 6						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 17	RC32	48	-		215/45	 Orig.-Verschr., i.V.
7,5 x 18	RC32	48	-		215/40	 Orig.-Verschr., i.V.

Crosstrek NEU		ab 2024	G6 / G6-SS	5/114,3	56,1	e13*KS18/858*00022*..., e13*2018/858*00666*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC32	55	-	100	225/60, 235/55	 Orig.-Verschr.
		48	-	100	225/60	Orig.-Verschr.
7 x 18	RC27	55	ZP578D2F	100	225/55, 235/50	 Orig.-Verschr., Felge nur in FGM erhältlich!
	RC32	48	-	100	225/55	Orig.-Verschr., Felge nur in FGM erhältlich!

Forester (siehe Konfigurator)		ab 2013	SJ	5/100	56,1	e13*2007/46*1305*..., e13*2001/116*0982*09-...
-------------------------------	--	---------	----	-------	------	--

Forester V		MJ2019	S5	5/114,3	56,1	e13*2007/46*1998*..
Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC32	48	-	110	225/60, 235/55, 245/55	 Orig.-Verschr.
7 x 18	RC32	48	-	110	225/55, 235/50, 245/50	 Orig.-Verschr., Felge nicht in SBM erhältlich!
8 x 19	CA 17	40	ZP582	110	225/45, 235/45, 245/45	bei 245/45 ✖
8,5 x 19	B32	45	ZP578D2 F+R	110	225/45, 235/45, 245/45	R=BA28->72,6-56,1 (58489)
8,5 x 20	B44	40	ZP582	110	225/40, 235/40	

Forester e-Boxer NEU			S6	5/114,3	56,1	e13*2018/858*00766*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 17	RC32	48	-	100	225/60	 Orig.-Verschr.
					225/60, 235/55, 235/60, 245/55, 255/55	 Orig.-Verschr.
7 x 18	RC32	48	-	100	225/55, 235/50, 235/55, 245/50, 255/50	Orig.-Verschr., Felge nur in FGM erhältlich!

Impreza WRX STI			V1, V	5/114,3	56,1	e1*2007/46*1203*05-..
Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 19	B32	45	ZP578D2 F+R	221	225/35, 235/35, 245/35	+ Red. Ringe BA28= 72,6-56,1, ab Modelljahr 2018

Impreza		2011 - 2017		G4	5/100	56,1	e1*2007/46*0597*...	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC34	48	-	84-110	205/55			Orig.-Verschr.
	RC27		- ou.	84	195/60			
			ZP578D2 F	84, 110	205/55, 215/55, 225/50			
7 x 17	RC30		48	-	84, 110	205/50		
		84		205/50, 215/55, 225/50, 225/55, 235/50				
		RC34	48	-	84-110	205/50		

Impreza		ab BJ 2017	G5	5/100	56,1	e13*2007/46*1648*..
Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC27	55	-	84, 115	205/55	 Orig.-Verschr., nur in SKM!!!
	RC30	55	-	84, 115	205/55	 Orig.-Verschr., incl. Hybrid
	RC27	48	-	84, 115	205/55, 215/50, 215/55, 225/50	Orig.-Verschr.
	RC27	55	-	84, 115	205/50, 215/45, 225/45	 Orig.-Verschr.

7 x 17	RC30	55	-	84-115	205/50, 215/45, 225/45		Orig.-Verschr., ET55 nur in SG!!!
	RC32	55	-	84-115	205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	55	-	84-115	205/50		Orig.-Verschr.
	RC30	43	ZP514	84, 115	205/50, 215/45, 225/45		
		48	-	84, 115	205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	CA 26	46	ZP514	84-115	205/50, 215/45, 225/45		
7 x 18	Oxigin 25	51	ZP514	84-115	215/45		incl. Hybrid
7 x 18	RC32	55	-	84-115	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC32	55	-	84-115	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
	B39	42	ZP514	84, 115	205/45, 215/40		

Impreza NEU		ab 2023		G6-SS	5/114,3	56,1	e13*KS18/858*00022*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC32	55	-	100	215/50, 225/45		Orig.-Verschr.
		48	-	100	215/50, 225/45		Orig.-Verschr.
7 x 18	RC32	48	-	100	215/45		Orig.-Verschr., Felge nur in FGM erhältlich!

Levorg		ab 02.16		V1 / V		5/114,3		56,1		e1*2007/46*1203*03-..	
Sensor - Brocksens Universal											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 17	RC30	55	-	110, 125	215/50, 225/45, 225/50				Orig.-Verschr.		
	RC32	55	-	110-125	215/50, 225/45, 225/50				Orig.-Verschr.		
		48	-	110-125	215/50, 225/45, 225/50				Orig.-Verschr.		
7 x 18	RC32	48	-	110-125	215/40, 215/45, 225/45				Orig.-Verschr., Felge nur in HGVP erhältlich!		
8,5 x 19	B32	45	ZP514		225/35, 225/40						

Legacy (siehe Konfigurator)		ab 09.09		BM/BR, BM/BRS	5/100	56,1	e1*2007/46*0079*...., e13*2007/46*1074*...
-----------------------------	--	----------	--	---------------	-------	------	--

Outback		ab 2015		B6	5/114,3	56,1	e1*2007/46*1320*..., e3*2007/46*0385*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC30	55	-	110, 129	225/60, 225/65, 235/60, 245/55			Orig.-Verschr.
	RC32	55	-	110-129	225/65, 235/60, 245/60			Orig.-Verschr.
		48	-	110-129	225/65, 235/60, 245/60			Orig.-Verschr.
7 x 18	RC27	55	ZP578D2F	110, 129	225/60, 235/55, 245/55			auch Typ B6GPL
	RC32	48	-	110-129	225/55, 225/60, 235/55, 245/50, 245/55			Orig.-Verschr., Felgen nur in HGVP erhältlich!
8,5 x 19	B32	45	ZP578D2 F+R	110, 129	235/50, 245/45, 245/50, 255/45			BA28=R-72,6-56,1; ✖

Outback		im Laufe 2020		B7	5/114,3	56,1	e13*2018/858*00010*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC30	55	-	124	225/65, 235/60		Orig.-Verschr.	
	RC32	48	-	124	225/65, 235/60, 245/60, 255/55		Orig.-Verschr., nur M+S	
		55	-	124	225/65, 235/60, 245/60		Orig.-Verschr., nur M+S	
7 x 18	RC27	55	ZP578D2F	124	225/55, 225/60 , 235/55, 245/50, 245/55			
	RC32	48	-	124	225/60, 235/55, 245/55, 255/50		Orig.-Verschr., diese Ausführung ist NICHT in SBM erhältlich!	

Solterra NEU		ab Juli 2022		EAM1S(M)		5/114,3		60,1		e6*2018/858*00162*..			
Sensor - Brocksens Universal													
Dimension		Design		ET		KIT		KW		Reifendimension		Info	
7,5 x 18		RC32		40		-		118		235/60, 245/55, 245/60, 255/55		 Orig.-Verschr., Ausführung TO2	
		RC34		40		-		118		235/60, 245/55, 245/60, 255/55		 Orig.-Verschr., Ausführung TO2	
		CA 20		40		ZP559F+R		118		235/60, 245/55, 245/60, 255/55		 + Red.Ringe 72,6-60,1	
8 x 18		B24		38		ZP559F+R		118 (160)		235/60, 245/55		+ Red.Ringe 72,6-60,1	
		B36		35		ZP559F+R		118 (160)		235/60		+ Red.Ringe 72,6-60,1	
		B42		40		ZP559F+R		118 (160)		235/60, 245/55, 255/55		+ Red.Ringe 72,6-60,1	
		B44		40		ZP559F+R		118 (160)		235/60, 245/55, 255/55		+ Red.Ringe 72,6-60,1	
8 x 19		CA 17		40		ZP534		118		235/55, 245/50, 245/55, 255/50			
8,5 x 19		B32 / B42		35		ZP559F+R		118 (160)		235/55		+ Red.Ringe 72,6-60,1	
		B36		38		ZP559F+R		118 (160)		235/55		+ Red.Ringe 72,6-60,1	
7,5 x 20		B43		40		-		118 (160)		235/50, 245/45		 Orig.-Verschr.	
		RC36		35		ZP559F		118 (160)		235/50, 245/45			
		B43		35		ZP559F		118 (160)		235/50, 245/45			
8 x 20		B40		35		ZP559F+R		118 (160)		235/50, 245/45, 255/45		+ Red.Ringe 72,6-60,1	
8,5 x 20		B44		40		ZP559F+R		118 (160)		235/50, 245/45, 255/45, 265/45		+ Red.Ringe 72,6-60,1	

XV (siehe Konfigurator)		ab 2012		G4	5/100	56,1	e1*2007/46*0597*...
-------------------------	--	---------	--	----	-------	------	---------------------

XV		ab BJ 2017		G5	5/100	56,1	e13*2007/46*1648*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC27	48	-	84, 115	215/65, 215/70, 225/65, 235/60			Orig.-Verschr.
		55	-	84, 115	225/65, 235/60			Orig.-Verschr., nur in SKM!!!
	RC30	55	-	84-115	225/65, 235/60			Orig.-Verschr., nur Bremse 294mm
7 x 17	RC27	55	-	84, 115	225/55, 225/60 , 235/55, 245/50, 245/55			Orig.-Verschr.
	RC30	55	-	84-115	225/55, 225/60 , 235/55, 245/50, 245/55			Orig.-Verschr., ET55 nur in SG!!!
	RC32	55	-	84-115	225/60 , 235/55, 245/55, 255/55			Orig.-Verschr.
	RC34	55	-	84-115	225/60			Orig.-Verschr.
	RC30	48	-	84, 115	225/55, 225/60			Orig.-Verschr.
	CA 26	46	ZP514	84-115	225/55, 225/60			nur Bremse 294mm
7,5 x 17	Oxigin 25	51	ZP514	84-115	225/60			incl. Hybrid
7 x 18	RC32	55	-	115	225/55			Orig.-Verschr.
				84-115	225/55, 235/50, 245/50, 255/50			
	RC27	48	-	115	225/55			Orig.-Verschr.
7,5 x 18	RC32	55	-	84-115	225/55, 235/50, 245/50			Orig.-Verschr.

Suzuki

Suzuki	Baujahr	Typ	LK/LZ	Nabe		
Across	ab 2020	XA5P (S) (EU,M)	5/114,3	60,1	e6*2007/46*0430*..	
Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 19	RC34	40	-	136	235/55, 245/50, 255/50	 Orig.-Verschr.
	B32	40	ZP574	136	235/50, 235/55	 Plug-in-Hybrid
8 x 19	RC29	38	ZP574	136	235/50, 235/55	Plug-in-Hybrid
	CA 17	40	ZP574	136	235/55	Plug-in-Hybrid
8,5 x 19	B32 / B37 / B42	35	ZP574	136	235/50, 235/55	Plug-in-Hybrid
7,5 x 20	RC36	35	ZP580D6F	136	235/45, 235/50, 245/45	Plug-in-Hybrid
	B43	35+40	ZP580D6F	136	235/45, 235/50, 245/45	Plug-in-Hybrid
8 x 20	RC36	35	-	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
	B38	35	ZP574	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
	B40	35	ZP574	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
	B43	35	-	136	235/45, 235/50, 245/45, 255/45	Orig.-Verschr., Plug-in-Hybrid
8,5 x 20	RC29	35	ZP574	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
		40	ZP574	136	235/45	Plug-in-Hybrid
	B24	35	ZP574	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
	B32	40	ZP574	136	235/45	Plug-in-Hybrid
	B42	35	ZP574	136	235/45, 235/50, 245/45, 255/45	Plug-in-Hybrid
	B44	30+40	ZP574	136	235/45	Plug-in-Hybrid
	AC-518	40	ZP580D6F +R	136	235/45	Plug-in-Hybrid, + Red.Ringe 73,1-60,1
9 x 20	Oxigin 28	40	ZP574	136	235/45	Plug-in-Hybrid

Celerio (siehe Konfigurator)	ab 2014	LF	4/100	54,1	e6*2007/46*0119*..
------------------------------	---------	----	-------	------	--------------------

Baleno	ab 06.16	EW	4/100	54,1	e6*2007/46*0177*..
--------	----------	----	-------	------	--------------------

Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
5,5 x 15	RC19	36	ZP442D2F	66-82	175/65, 185/60		
6,5 x 15	RC28	35	ZP424	66-82	175/65		
6 x 16	RC30	45	ZP442D2F	66-82	175/55, 175/60, 185/50, 185/55 , 195/50, 205/50		Orig.-Verschr.
	RC34	45	-	66-82	175/55, 185/50, 185/55 , 195/50		
6,5 x 16	RC24	38	ZP424	66-82	185/50, 185/55, 195/50, 205/45, 205/50		✖
	RC30	38	ZP424	66-82	185/50, 185/55, 195/50, 205/45, 205/50		✖
7 x 17	B24	45	ZP424	66-82	195/40, 195/45, 205/40, 205/45		
	B39	44	ZP424	66-82	195/40, 195/45, 205/40, 205/45		

Vitara	ab 2015	LY / LY-2S	5/114,3	60,1	e4*2007/46*0928*..., e6*2018/858*00005*..
--------	---------	------------	---------	------	---

Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC32	50	ZP590F	82-103	215/60, 225/55, 235/55		auch Hybrid Fahrzeuge
	RC24	44	ZP536	75-103	215/60, 225/55, 225/60		
	RC27	38	ZP536	88, 103	215/60		
		45	ZP536	82-103	215/60, 225/55, 225/60		
		50	ZP536	82-103	215/60, 225/55, 225/60		
	RC30	45	ZP536	82-103	215/60, 225/55, 225/60		
		50	ZP536	82-103	215/60, 225/55, 225/60		
	RC32	45	ZP590F	82-103	215/60, 225/55		
6,5 x 17	CA 20	45	ZP536	75-103	215/60, 225/55		
	RC27	50	-	75-103	215/50, 215/55, 215/60, 225/50, 225/55, 235/50		Orig.-Verschr., Felge nur in silber erhältlich!
	RC34	50	-	82-103	215/55		Orig.-Verschr., Felge nur in SGVP erhältlich!
7 x 17	RC30			75-103	215/50, 215/55, 225/50, 235/50		
		38	ZP536	82-103	215/50, 215/55, 215/60		
		45	ZP536	82-103	215/50, 215/55, 215/60, 225/50, 225/55		
	RC27	45	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55		
	B39	38	ZP536	88, 103	215/50, 215/55, 215/60		
		45	ZP536	88, 103	215/50, 215/55, 215/60, 225/50, 225/55		
	CA 26	45	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55		
	RC28	45	ZP536	88, 103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
7,5 x 17	RC24	45	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
	RC29	48	ZP536	82-103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
	B24	48	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
	B36	46	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
7 x 18	CA 20	48	ZP536	75-103	215/50, 215/55, 215/60, 225/50, 225/55, 245/45		
	Oxigin 25	45	ZP536	82-103	205/55		
	RC32	50	ZP590F	82-103	215/45, 215/50, 225/45		
	RC30	45	ZP536	88, 103	215/45, 215/50, 225/45, 235/45, 245/45		
7,5 x 18	RC32	45	ZP590F	75-103	215/45, 215/50, 225/45, 235/45		
	B32 / B39	45	ZP536	88, 103	215/45, 215/50, 225/45, 235/45, 245/45		
	AC-MB6 / AC-	45	Artikel Nr.	75-103	215/45, 215/50, 225/45, 235/45, 245/45		Kit mit Artikelnummer 98354

8 x 18	M10	75	98354	75-103	215/45, 215/50, 225/45, 235/45, 245/45	Kit mit Artikelnummer 98502
	AC-521	45	ZP590F+R	82-103	215/45, 215/50, 225/45, 235/45, 245/45	+ Red.Ringe 73,1-60,1
	Oxigin 18	35+45	ZP536	88-103	215/45	
	RC29	45	ZP536	88, 103	215/45, 225/45, 235/45, 245/40, 245/45	ab 245/40 ✖
	RC32	45	ZP590F	82-103	215/45, 225/45	
	B24	38	ZP536	75-103	215/45	
	B36 / B42	45	ZP536	75-103	215/45, 225/45, 235/45	
	B38	45	ZP590F	82-103	215/45, 225/45, 235/45	
		45+49	ZP536	82-103	215/45, 225/45, 235/45	
	B42	40	ZP536	75-103	215/45, 225/45	
	B44	40	ZP536	75-103	215/45, 225/45	
		45	ZP536	75-103	215/45, 225/45, 235/45	
8,5 x 18	AC-518	40	ZP590F+R	82-103	215/45, 225/45	+ Red.Ringe 73,1-60,1
	AC-M10	45	ZP590F+R	75-103	215/45, 225/45, 235/45	+ Red.Ringe 73,1-60,1
	CA 23	45	ZP536	75-103	215/45, 225/45, 235/45	
	B32	45	ZP536	88, 103	225/45	
7,5 x 19	B32	40	ZP536	88, 103	225/40	
	B39	40+45	ZP536	88, 103	225/40	
	AC-521	45	ZP590F+R	82-103	225/40	
	RC29	48	ZP536	75-103	225/40, 235/35, 235/40, 245/35, 245/40	
8 x 19	B24	50	ZP536	82-103	225/40, 235/35, 235/40	
	B38	45	ZP536	75-103	225/40, 235/35, 235/40	
	AC-518	40	ZP590F+R	82-103	225/40	+ Red.Ringe 73,1-60,1
	CA 19	45	ZP536	75-103	225/40, 235/35, 235/40	
	Oxigin 29	50	ZP536	75-103	225/40, 235/35, 235/40	
	B32	45	ZP536	82-103	225/40	
8,5 x 19	CA 26	46	ZP536	75-103	225/40, 235/35, 235/40	
	Oxigin 28	45	ZP536	75-103	225/40	
8 x 20	B38	45	ZP536	75-103	225/35, 235/35	
		50	ZP536	88, 103	225/35, 235/35	

weitere Dimensionen/Designs siehe Konfigurator

Grand Vitara (siehe Konfigurator)	ab 01.06	JT	5/114,3	60,1	e4*2001/116*0091*..., e4*2007/46*0292*...
-----------------------------------	----------	----	---------	------	---

Ignis	ab 01.2017	MF / MF-2S	4/100	54,1	e4*2007/46*1162*..., e6*2018/858*00227*..
-------	------------	------------	-------	------	---

Sensor - Brocksens 6						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	40	ZP424	61, 66	175/65, 185/60, 185/65, 195/55, 195/60	ohne Radhausverbr. ab 185/60 ✖
	RC30	40	ZP424	66	175/65, 185/60, 185/65, 195/55, 195/60	ohne Radhausverbr. ab 185/60 ✖
5 x 16	Originaldim.	40			175/60	

Ignis All Grip	ab 2017	MF / MF-2S	4/100	54,1	e4*2007/46*1162*..., e6*2018/858*00227*..
----------------	---------	------------	-------	------	---

Sensor - Brocksens 6						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC24	40	ZP424	61, 66	175/65, 185/60, 185/65	
	RC30	40	ZP424	66	175/65, 185/60, 185/65	

Jimny	ab 2018	GJ	5/139,7	108,3	e6*2007/46*0253*..
-------	---------	----	---------	-------	--------------------

Sensor - Brocksens 6						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
5,5 x 15	RC33X	5	-	75	195/80, 205/75, 215/70	 Orig.-Verschr.

Swace	ab 2020	ZE1HE (S) (EU,M)	5/114,3	60,1	e6*2007/46*0485*..., e6*2018/858*00057*..
-------	---------	------------------	---------	------	---

Sensor - Brocksens Universal						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 16	RC30	40	ZP580D6F	72	205/55, 215/55, 225/50	 auch Typ ZE1HE(S)-2S
7 x 17	RC27	35	ZP580D6F	72	205/50, 215/45, 225/45	
	RC32	39	ZP580D6F	72	205/45, 205/50, 215/45, 225/45	
7,5 x 17	RC24 / RC29	38	ZP574	72	205/50, 215/45, 225/45	
	B24	38	ZP574	72	205/50, 215/45, 225/45	auch Typ ZE1HE(S)-2S
7 x 18	RC27	35	ZP580D6F	72	205/45, 215/40	
7,5 x 18	RC30	35	ZP574	72	205/45, 215/40, 225/40	
	B39	35	ZP574	72	205/45, 215/40, 225/40	
	AC-MB6 / AC-M10	35	Artikel Nr. 98502	72	205/45, 215/40, 225/40	Kit mit Artikelnummer 98502
	CA 20	40	ZP574	72	205/40, 215/40, 225/35, 225/40	
8 x 18	B24	38	ZP574	72	215/40, 225/40	
	B36	35	ZP574	72	215/40, 225/40	
	B42 / B44	40	ZP574	72	215/40, 225/40, 245/35	
	AC-518	40	Artikel Nr. 98502	72	215/40, 225/40, 245/35	Kit mit Artikelnummer 98502
8,5 x 18	B32	35	ZP574	72	215/40, 225/40	

7,5 x 19	B32	40	ZP574	72	225/35		
	B39	40	ZP574	72	225/35		
8 x 19	B38	38	ZP574	72	225/35		
	CA 17	40	ZP574	72	225/35		
	Oxigin 29	40	ZP574	72	225/35, 245/30		auch Typ ZE1HE(S)-2S
8,5 x 19	B36	38	ZP574	72	225/35, 235/30		auch Typ ZE1HE(S)-2S
	B44	40	ZP574	72	225/35, 235/30		
	CA 23	40	ZP574	72	225/35, 235/30		

Swift (4/100) (siehe Konfigurator)	NZ	4/100	54,1	
------------------------------------	----	-------	------	--

Swift Sport (siehe Konfigurator)	2013 - 2017	NZ	5/114,3	60,1	e4*2007/46*0155*...
----------------------------------	-------------	----	---------	------	---------------------

Swift 4x4 (siehe Konfigurator)	2010 - 2011	FZ	4/100	54,1	e4*2007/46*0198*..., e4*2007/46*0294*...
--------------------------------	-------------	----	-------	------	--

Swift	ab 05/2017		AZ / AZ-2S		4/100	54,1	e4*2007/46*1205*..., e6*2018/858*00229*..	
Sensor - Brocksens 6								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5,5 x 15	RC19	36	ZP442D2F	61-82	175/65, 185/60, 195/55, 195/60			
6 x 15	RC24	40	ZP424	61-82	175/65, 185/60, 195/55, 195/60			
		42	ZP442D2F	61-82	175/65, 185/60, 195/55, 195/60			
	RC30	40	ZP424	66, 82	175/65, 185/60, 195/55, 195/60			
6,5 x 15	RC28	35	ZP424	66, 82	175/65			
6 x 16	RC30	45	ZP442D2F	61-82	175/55, 175/60, 185/50, 185/55 , 195/50, 205/50			
	RC34	45	-	61-82	175/55, 175/60, 185/50, 185/55 , 195/50, 205/50			Orig.-Verschr.
6,5 x 16	RC24	38	ZP424	66, 82	185/50, 185/55, 205/45			
	RC30	38	ZP424	61-82	185/50, 185/55, 205/45			
		45	ZP442D2F	61-82	185/50, 185/55, 195/50, 205/45, 205/50			
6,5 x 17	RC34	43	-	61-82	185/45, 195/45, 205/45			Orig.-Verschr.
7 x 17	B24	38	ZP424	66, 82	195/40, 195/45			
	B39	38	ZP424	66, 82	185/45, 195/40, 195/45			
		44	ZP424	61-82	185/45, 195/40, 195/45, 205/40, 205/45, 215/40			

Swift Sport		ab 2018		AZ	5/114,3	60,1	e4*2007/46*1205*..	
Sensor - Brocksens 6								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 16	RC27	50	-	95, 103	195/50, 205/50			Orig.-Verschr.
	RC30	50	ZP578D2F	95, 103	195/50, 205/50			
	RC27	45	ZP578D2F	95, 103	195/50			
6,5 x 16	RC24	44	ZP575	95, 103	195/50, 205/45			
	RC27	45	ZP575	95, 103	195/50, 205/45			
		50	ZP575	103	195/50, 205/45, 205/50			
	RC30	45	ZP575	95, 103	195/50, 205/45			
		50	ZP575	95, 103	195/50, 205/45, 205/50			
	RC32	45	-	95-103	195/50			Orig.-Verschr., auch Hybrid
		50	-	95-103	195/50, 205/50			Orig.-Verschr.
6,5 x 17	CA 20	45	ZP575	95, 103	195/50, 205/45			auch Typ AZ-S2
	RC34	50	-	95-103	195/45			Orig.-Verschr., Felge nur in SGVP erhältlich!
	RC27	45	ZP578D2F	95, 103	195/45, 205/45			auch Typ AZ-2S, Felge gibt es nur in SKM!
7 x 17	RC27	45	ZP575	95, 103	195/45, 205/40, 205/45			
	RC30	45	ZP575	95, 103	195/45, 205/40, 205/45			
	CA 26	45	ZP575	95, 103	195/45, 205/40, 205/45			
	RC24	45	ZP575	103	195/45			
7,5 x 17	RC28	45	ZP575	95, 103	195/45			auch Typ AZ-S2
	RC29	48	ZP575	95, 103	195/45, 205/40, 205/45			
	B24	48	ZP575	103	195/45, 205/40, 205/45			
	B36	46	ZP575	95, 103	195/45, 205/40, 205/45			
	CA 20	48	ZP575	95, 103	195/45, 205/40, 205/45			auch Typ AZ-S2
	Oxigin 25	45	ZP575	95-103	195/45, 205/40, 205/45			
7 x 18	RC32	50	ZP578D2F	103	215/35			
7,5 x 18	RC32	45	-	95-103	205/35, 215/35			Orig.-Verschr., ✖

Swift Typ UZ NEU		2024		4/100		54,1		e6*2018/858*00307*..	
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
6 x 16	RC34	45	-	61	185/55			Orig.-Verschr.	
				61	175/55, 185/50, 185/55, 195/50, 205/50				
6,5 x 16	RC30	45	ZP442D2F	61	185/55, 195/50				
6,5 x 17	RC34	43	-	61	185/45, 195/45, 205/45			Orig.-Verschr.	

SX4 (siehe Konfigurator)	ab 2013	JY	5/114,3	60,1	e4*2007/46*0779*...
--------------------------	---------	----	---------	------	---------------------

SX4	ab MJ2017	JY	5/114,3	60,1	e4*2007/46*0779*04-..
-----	-----------	----	---------	------	-----------------------

Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC32	50	ZP590F	82-103	215/60, 225/55, 235/55		
	RC27	45	ZP573	82-103	215/60, 225/55		
		50	ZP573	82,88,103	215/60, 225/55		
	RC30	45	ZP573	82-103	215/60, 225/55		
		50	ZP573	82-103	215/60, 225/55		
	RC32	45	ZP573	82-103	215/60, 225/55		auch für Hybrid
7 x 16	CA 20	45	ZP573	82-103	215/60, 225/55		
	RC24	45	ZP573	82,88,103	215/60, 225/55		bei 225/55 ✖
	RC28	45	ZP573	82,88,103	215/60, 225/55		bei 225/55 ✖
6,5 x 17	RC27	50	-	82-103	215/55, 225/50		Orig.-Verschr., Felge gibt es nur in silber!
	RC34	50	-	82-103	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., Felge gibt es nur in SGVP!
7 x 17	RC30	45	ZP573	82-103	215/55		
	B39	45	ZP573	82,88,103	215/55		
7,5 x 17	RC28	45	ZP573	82,88,103	215/55, 235/45		
	RC24	45	ZP573	82,88,103	215/55, 235/45		
	RC29	48	ZP573	82-103	215/55, 225/50, 235/50		
	B24	48	ZP573	82-103	215/55, 225/50, 235/45		
	B36	46	ZP573	82-103	215/55, 235/45		
7 x 18	RC32	50	ZP590F	82-103	215/45, 215/50, 225/45		
7,5 x 18	RC30	45	ZP573	82,88,103	215/45, 215/50, 225/45, 235/45		
	RC32	45	ZP590F	82-103	215/45, 215/50, 225/45, 235/45		bei 215/50 u. 235/45 ✖
	B32	45	ZP573	82-103	215/45, 215/50, 225/45, 235/45		
	B39	45	ZP573	82,88,103	215/45, 215/50, 225/45, 235/45		
	AC-MB6	45	Artikel Nr. 98354	82-103	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98354
	AC-521	45	ZP590F+R	82-103	215/45, 215/50, 225/45, 235/45		+ Red.Ringe 73,1-60,1
	Oxigin 18	45	ZP573	82-103	215/45, 225/45		bei 225/45 ✖
8 x 18	RC32	45	ZP590F	82-103	215/45		
	B36	45	ZP573	82-103	215/45, 225/45		
	B37 / B42 / B44	45	ZP573	82-103	215/45, 225/45		
	CA 24	45	ZP573	75-103	215/45		
7,5 x 19	B39	45	ZP573	82,88,103	225/40		
	AC-521	45	ZP590F+R	82-103	225/40		+ Red.Ringe 73,1-60,1
8 x 19	RC29	48	ZP573	82-103	225/40, 235/35, 235/40		
	B24	50	ZP573	82,88,103	225/40		
	Oxigin 29	50	ZP573	82-103	225/40		
8 x 20	B38	45	ZP573	82,88,103	225/35, 235/30, 235/35		ab 235/30 ✖
		50	ZP573	82,88,103	225/35		

S-Cross NEU ab Jänner 2022 JY / JY-2S 5/114,3 60,1 e4*2007/46*0779*14-..., e6*2018/858*00006*02-..							
Sensor - Brocksens 6							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC24	44	ZP573	95	215/60, 225/55		
	RC27	45	ZP573	75, 95	215/60, 225/55		
	RC30	45	ZP573	95	215/60, 225/55		
	CA 20	45	ZP573	75, 95	215/60, 225/55		
7 x 16	RC30	40	ZP590F	75, 95	215/60, 225/55		
6,5 x 17	RC27	50	-	75, 95	215/55, 225/50, 235/50		Orig.-Verschr., Felge gibt es nur in silber!
		40+45	ZP590F	75, 95	215/55, 225/50, 235/50		
7 x 17	RC27	45	ZP573	75, 95	215/55, 225/50, 235/50		
	RC30	45	ZP573	95	215/55, 225/50, 235/50		
	CA 26	45	ZP573	75, 95	215/55, 225/50, 235/50		
7,5 x 17	RC24	38	ZP573	75, 95	215/55, 235/45		
		45	ZP573	75, 95	215/55, 225/50, 235/45, 235/50, 245/45		
	RC28	45	ZP573	75, 95	215/55, 225/50, 235/45, 235/50, 245/45		
	RC29	48	ZP573	95	215/55, 225/50, 235/45, 245/45		
	B24	38	ZP573	75, 95	215/55, 235/45		
		48	ZP573	75, 95	215/55, 225/50, 235/45, 245/45		
	B36	46	ZP573	75, 95	215/55, 225/50, 235/45, 235/50, 245/45		
	CA 20	48	ZP573	75, 95	215/55, 225/50, 235/45, 245/45		
7 x 18	RC27	50	ZP590F	95	215/45, 215/50, 225/45		
7,5 x 18	AC-MB6 / AC-M10	45	Artikel Nr. 98354	75, 95	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98354
	AC-521	45	ZP590F+R	95	215/45, 215/50, 225/45, 235/45		+ Red.Ringe 73,1-60,1
8 x 18	B24	38	ZP573	75, 95	215/45, 225/45		
		35	ZP573	75, 95	215/45		
	B36	45	ZP573	75, 95	215/45, 225/45, 235/40, 235/45, 245/40		
		40	ZP573	75, 95	215/45, 225/45, 235/40, 235/45		
	B42	45	ZP573	75, 95	215/45, 225/45, 235/40, 235/45, 245/40		
		40	ZP573	75, 95	215/45, 225/45, 235/40, 235/45		
	B44	40	ZP573	75, 95	215/45, 225/45, 235/40, 235/45		
		45	ZP573	75, 95	215/45, 225/45, 235/40, 235/45, 245/40		

	AC-521	45	ZP590F+R	75, 95	215/45, 225/45, 235/40, 235/45, 245/40	+ Red.Ringe 73,1-60,1
	CA 20 / CA 23	45	ZP573	75, 95	215/45, 225/45, 235/40, 235/45, 245/40	
7,5 x 19	AC-521	45	ZP590F+R	95	225/40	+ Red.Ringe 73,1-60,1
8 x 19	RC29	48	ZP573	75, 95	225/40, 235/35, 235/40, 245/35	
	B38	45	ZP573	75, 95	225/40, 235/35, 235/40, 245/35	
	CA 19	45	ZP573	75, 95	225/40, 235/35, 235/40, 245/35	
	Oxigin 29	50	ZP573	75, 95	225/40, 235/35, 235/40	
8,5 x 19	B37	45	ZP573	75, 95	225/40, 235/35, 235/40	
	B42	45	ZP573	95	225/40, 235/35, 235/40	
	B44	40	ZP573	75, 95	225/40	
	CA 20	45	ZP573	75, 95	225/40, 235/35, 235/40	
	CA 23	40	ZP573	75, 95	225/40	
	CA 26	46	ZP573	75, 95	225/40, 235/35, 235/40	
	Oxigin 28	45	ZP573	75, 95	225/40, 235/35, 235/40	
8 x 20	B38	45	ZP573	75, 95	225/35, 235/35, 245/30	
8,5 x 20	B42	45	ZP573	95	225/35, 235/30, 235/35	
	B44	40	ZP573	75, 95	225/35	

Tesla

tesla

Baujahr

Typ

LK/LZ

Nabe

Model S

ab 2014

002

5/120

64,1

e4*2007/46*0667*..

Sensor - Brocksens Universal - ab BJ2020 BLUETOOTH Sensoren - Artikelnummer schwarz - 98182

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 19	RC27	40	-	52-169	245/45, 255/45		Orig.-Verschr.
	RC32	40	-	52-186	245/45		Orig.-Verschr.
	B40	40	-	52-186	245/45		Orig.-Verschr.
	AC-521	40	-	52-186	245/45		Orig.-Verschr.
8,5 x 19	B32	35	-	52-186	245/45, 255/40		Orig.-Verschr.
		38	-	52-90	245/45, 255/40		Orig.-Verschr.
	B41	35	-	52-186	245/45		Orig.-Verschr.
	Oxigin 19	35	ZP598	52-169	245/45, 255/40, 255/45		
8 x 20	B38	35	-	52-186	245/40		Orig.-Verschr.
8,5 x 20	RC29	40	-	52-186	245/40, 255/35, 255/40		Orig.-Verschr.
	B32	40	-	52-169	245/40, 255/35, 255/40		Orig.-Verschr.
	AC-521	40	-	52-186	245/40, 255/35		Orig.-Verschr.
9 x 20	B37	35	-	52-169	245/40, 255/40		Orig.-Verschr.
		38	-	52-69	245/40, 255/35, 255/40		Orig.-Verschr.
9,5 x 20	B37C	31	-	52-69	245/40, 255/35, 255/40		Orig.-Verschr., ab 255/35 ✖
9 x 21	B32	38	-	52-186	245/35, 255/35		Orig.-Verschr.

Model S Plaid			NEU	2023	004	5/120	64,1	e4*2018/858*00086	
Sensor - Brocksens Universal - ab BJ2020 BLUETOOTH Sensoren - Artikelnummer schwarz - 98182									
9,5 x 19	B40	40	-		VA 255/45		Orig.-Verschr.		
10,5 x 19		45			HA 285/40				
9,5 x 21	B41	40	-	218-357	VA 265/35		Orig.-Verschr.		
10,5 x 21		45			HA 295/30				
9,5 x 21	B43	40	-	218-357	VA 265/35		Orig.-Verschr., nicht Keramikbremse		
10,5 x 21		45			HA 295/30				
9,5 x 21	B43	40	-	218-357	VA 255/35, 265/35		Orig.-Verschr., nicht Keramikbremse		
10,5 x 21		45			HA 295/30				

Model X		ab 07.16	002		5/120	64,1	e4*2007/46*0667*09-..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC27	40	-	52-69	245/45			Orig.-Verschr.
8,5 x 19	B32	35	-	158-186	265/50			Orig.-Verschr.
				158-186	255/50, 265/45, 265/50, 275/45			Orig.-Verschr.
	B41	35	-	79-169	265/50, 275/45			Orig.-Verschr.
9 x 20	B37	35	-	158, 169	VA 255/45+HA 275/45			Orig.-Verschr.

Model X Plaid		NEU	2023	004		5/120	64,1	e4*2018/858*00086*..	
Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
9 x 20	RC36	VA 40	-	218, 357	VA 255/45, 265/45			Orig.-Verschr., nicht für Fahrzeuge mit Festsattelbremse an der HA	
10 x 20		HA 35			HA 275/45				
9 x 20	B43	VA 40	-	218, 357	VA 255/45, 265/45			Orig.-Verschr., nicht für Fahrzeuge mit Festsattelbremse an der HA	
10 x 20		HA 35			HA 275/45				
9 x 20	B43	VA 40	-	218, 357	VA 255/45, 265/45, 275/40			Orig.-Verschr., nicht für Fahrzeuge mit Festsattelbremse an der HA	
10 x 20		HA 35			HA 275/45, 285/40, 285/45				
9 x 20	B40	VA 40	-	218, 357	VA 255/45, 265/45, 275/40			Orig.-Verschr.	
10,5 x 20		HA 35			HA 275/45, 285/40, 285/45				

Model Y	Sommer 2021	003	5/114,3	64,1	e4*2007/46*1293*01-43
Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182					

ACHTUNG!!! Fahrzeuge mit 21 Zoll ab Werk (Performance), dürfen lt. Tesla nur 21 Zoll fahren!!!

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
9,5 x 19	B32	45	-	88-190	255/45, 265/40, 275/40		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
	B40	45	-	88-190	255/45		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
				155-190	255/45		Orig.-Verschr., 21 Zoll Serienbereifung
	CA 20	45	ZP533D13F	88-190	255/45		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
				155-190	255/45		Orig.-Verschr., 21 Zoll Serienbereifung
	FMI06 Koros	45	-	88-155	255/45		Orig.-Verschr.
	FMI10 e-Joule	45	-	88-155	255/45		Orig.-Verschr.
	WI23	45	-	88-155	255/45		Orig.-Verschr.
9 x 20	CA 23 / CA 26	45	ZP533D13 F+R	88-190	255/40, 265/35, 265/40, 275/35		19 Zoll ww. 20 Zoll Serienbereifung
				155-190	255/40, 265/40		21 Zoll Serienbereifung

				155-190	255/40, 265/35, 265/40		EA-Zoll-Serienbereifung
9,5 x 20	RC36	45	-	88-190	255/40, 265/35, 265/40		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
				155-190	255/40, 265/40, 285/35HA		Orig.-Verschr., 21 Zoll Serienbereifung
	B32	45	-	88-190	255/40, 265/35, 265/40		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
				155, 190	255/40, 265/40, 285/35HA		Orig.-Verschr., 21 Zoll Serienbereifung
	AC-521	45	-	88-190	255/40		Orig.-Verschr., e4*2018/858*00135*.. - 19 Zoll ww. 20 Zoll Serienbereifung
				155, 190	255/40		Orig.-Verschr., 21 Zoll Serienbereifung
	FMI10 e-Joule	45	-	88-155	255/40		Orig.-Verschr.
	FMI12 Kari	45	-	88-155	255/40		Orig.-Verschr.
9,5 x 21	B42	45	ZP533D13F	88-190	255/40, 265/35, 265/40		19 Zoll ww. 20 Zoll Serienbereifung
				155, 190	255/40, 265/40, 285/35HA		21 Zoll Serienbereifung
9,5 x 21	FMI10 e-Joule	40	F60C	88-155	VA+HA 255/35, 265/35 od.		
					VA 255/35+HA 275/35		

Model Y Performance	003	5/114,3	64,1	e4*2007/46*1293*..
Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182				

Kombinationen							
9,5 x 21	B41	VA 40	-	155-185	VA 255/35		Orig.-Verschr.
10,5 x 21		HA 48			HA 275/35		
9,5 x 21	B43	VA 40	-	155, 190	VA 255/35		Orig.-Verschr., 21 Zoll Serienbereifung
10,5 x 21		HA 48			HA 275/35		

Model Y NEU		ab Modelljahr 2025		003 / 005		5/114,3		64,1		e4*2007/46*1293*44..		
Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182												
Dimension		Design		ET	KIT		KW		Reifendimension		Info	
9,5 x 19		FMI06 Koros		45	-				255/45			Orig.-Verschr., i.V.
9,5 x 20		RC36		45	-		114-179		255/40, 265/35, 265/40			Orig.-Verschr., nur Variante YS

Model 3	ab 2018	003	5/114,3	64,1	e4*2007/46*1293*..
Sensor - Brocksens Universal - ab BJ2020 BLUETOOTH Sensoren - Artikelnummer schwarz - 98182					
ACHTUNG! Tesla 3 Performance mit 155KW darf 18 und 19 Zoll Räder nur montieren, wenn diese in den Fahrzeugpapieren eingetragen sind!!!					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 18	RC34	40	-	88-155	235/45, 245/45, 255/40		Orig.-Verschr., nicht Bremse 355x25mm, ohne Performance-Bremse
				153-155	235/45, 245/45, 255/40		Orig.-Verschr., nur Bremse 355x25mm, mit Performance-Bremse
	B32	40	-	88-155	235/45, 245/40, 245/45		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/45, 245/40, 245/45		Orig.-Verschr., nur Bremse 355mm, mit Performance-Bremse
	WI22	40	-	88-155	235/45		Orig.-Verschr.
	RC34	38	-	88-155	235/45, 245/40, 245/45, 255/40		Orig.-Verschr., nicht Bremse 355x25mm, ohne Performance-Bremse
				153, 155	235/45, 245/45, 255/40		Orig.-Verschr., nur Bremse 355x25mm, mit Performance-Bremse
	B32	38	-	88-155	235/45, 245/40, 245/45		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/45, 245/40, 245/45		Orig.-Verschr., nur Bremse 355mm, mit Performance-Bremse
8 x 19	CA 17	40	ZP598	88-155	235/40, 245/40		
8,5 x 19	RC32	40	-	88-155	235/40		Orig.-Verschr.
	B32	40	-	88-155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/40		Orig.-Verschr., nur Bremse 355mm, mit Performance-Bremse
	B43	40	-	88-155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 320mm
				153, 155	235/40		Orig.-Verschr., nur Bremse 355mm
	CA 26	40	ZP533D13 F	88-155	235/40		nur Bremse 320mm
				153, 155	235/40		nur Bremse 355mm
	B32	38	-	88-155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 320mm
				153, 155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 355mm
	B42	40	-	88-155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 320mm
				153, 155	235/40		Orig.-Verschr., nur Bremse 355mm
	B44	35	-	88-155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/40, 245/35, 245/40		Orig.-Verschr., nur Bremse 355mm, mit Performance-Bremse
				88-155	235/40, 245/35, 245/40		nur Bremse 320mm, ohne Performance-Bremse

8,5 x 20	CA 23	40	ZP598	100-155	235/40, 245/40, 255/35		nur Bremse 355mm, ohne Performance-Bremse
				153, 155	235/40		nur Bremse 355mm, mit Performance-Bremse
	Oxigin 25	35	ZP598	100-155	235/40, 245/40, 255/35		
	RC34	35	ZP533D13 F	155	235/35, 245/35, 255/30		nur Bremse 355mm - 4-Kolben Festsattel
	B43	35	-	153, 155	235/35, 245/35		Orig.-Verschr., nur Bremse 355 mm (mit Performance-Bremse)
				88-155	235/35, 245/35		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
	FMI12 Kari	35	-	88-155	235/35		Orig.-Verschr.
	RC34	35	ZP533D13 F	88-155	235/35		nur Bremse 355mm - 4-Kolben Festsattel
	B32	35	-	88-155	235/35, 245/35		Orig.-Verschr., nur Bremse 320mm
				155	235/35, 245/35		Orig.-Verschr., Tesla 3 Performance, nur Bremse 355mm
	B42 / B44	35	-	88-155	235/35, 245/35		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/35, 245/35		Orig.-Verschr., Tesla 3 Performance, nur Bremse 355mm
	AC-518	35	-	88-155	235/35, 245/35		Orig.-Verschr., nur Bremse 320mm
				155	235/35, 245/35		Orig.-Verschr., nur Bremse 355mm
	AC-521	35	-	88-155	235/35, 245/35		Orig.-Verschr., nur Bremse 320mm, ohne Performance-Bremse
				153, 155	235/35, 245/35		Orig.-Verschr., nur Bremse 355mm, mit Performance-Bremse
	FMI10 e-Joule	35	-		235/35		Orig.-Verschr.
	FMI10 e-Joule	34	-		245/35		Orig.-Verschr.
9 x 20	Oxigin 25	38	ZP598	100-155	235/35, 245/35		
	Oxigin 28	40	ZP598	88-155	235/35		nur Bremse 320mm, ohne Performance-Bremse

Kombinationen

9,5 x 21	B41	VA 40	-	155	VA 255/35		Orig.-Verschr.
10,5 x 21		HA 48			HA 275/35		

Model 3 (Highland) NEU ab 2023 003 5/114,3 64,1 e4*2007/46*1293*32-..

Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 18	B32	38	-	88-153	235/45, 245/40, 245/45	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	RC34	38	-	88-155	235/45, 245/45, 255/40	Orig.-Verschr., nicht Bremse 355x25mm
		40	-	88-155	235/45, 245/40, 245/45, 255/40	Orig.-Verschr., nicht Bremse 355x25mm, ohne Performance Bremse
	B32	40	-	88-153	235/45, 245/40, 245/45	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
8,5 x 19	RC34	38	-	88-155	235/40, 245/35, 245/40, 255/35	Orig.-Verschr., nicht Bremse 355x25mm, ohne Performance Bremse
	B32	38	-	88-153	235/40, 245/35, 245/40	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	FMI14 Jupiter	38	-	88-153	235/40	Orig.-Verschr.
	B32	40	-	88-153	235/40, 245/35, 245/40	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	B42	40	-	88-153	235/40, 245/35, 245/40	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	B43	40	-	88-153	235/40, 245/35, 245/40	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	B44	35	-	88-153	235/40, 245/35, 245/40	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	CA 23	40	ZP533D13 F+R	88-153	235/40, 245/35, 245/40	+Ringe 72,6-64,1, nur Bremse 320mm, ohne Performance Bremse
	CA 26	40	ZP533D13 F	88-153	235/40, 245/35, 245/40	nur Bremse 320mm, ohne Performance-Bremse
8,5 x 20	B32	35	-	88-153	235/35	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse
	B42 / B44	35	-	88-153	235/35	Orig.-Verschr., nur Bremse 320mm, ohne Performance Bremse

Model 3 (Highland) NEU mit 190kW 003 5/114,3 64,1 e4*2007/46*1293*36-..

Sensor - BLUETOOTH Sensoren - Artikelnummer schwarz - 98182

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8,5 x 19	B43	VA 38	-	190	VA 235/40	Orig.-Verschr., mit Performance-Bremse, nur Bremse 355mm
10 x 19		HA 45			HA 265/35, 275/35	
9 x 20	RC36	VA 34	-	190	VA 235/35	Orig.-Verschr., mit Performance-Bremse, nur

10 x 20	B43	HA 45	-	190	HA 275/30		Bremse 355mm
9 x 20		VA 34			VA 235/35		Orig.-Verschr., mit Permormance-Bremse, nur Bremse 355mm
10 x 20		HA 45			HA 275/30		
9 x 20		VA 34	-	190	VA 235/35, 245/30, 245/35		Orig.-Verschr., mit Permormance-Bremse, nur Bremse 355mm
10 x 20		HA 45			HA 265/30, 275/30, 285/30		

Toyota

	Baujahr	Typ	LK/LZ	Nabe	
Auris II (siehe Konfigurator)	ab 2013	E15UT/N (E18)	5/114,3	60,1	e11*2001/116*0305*14-..., e11*2007/46*0019*04-...
Auris Hybrid II (siehe Konfigurator)	ab 2013	HE15U(a) (E18)	5/114,3	60,1	e11*2007/46*0018*05...
Aygo (siehe Konfigurator)	ab 2014	AB1	4/100	54,1	e11*2001/116*0236*11-...

Aygo X NEU i.V. ab April 2023						
Dimension	Design	ET	KIT	KW	Reifendimension	Info

bZ4X NEU	ab Juni 2022	EAM1 (M) /-TGRE	5/114,3	60,1	e6*2018/858*00144*..., e13*2018/858*00303*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 18	RC32	40	-	59-118	235/60, 245/55, 245/60, 255/55	 Orig.-Verschr.
	RC34	40	-	59-118	235/60, 245/55, 245/60, 255/55	 Orig.-Verschr.
	CA 20	40	ZP559F+R	59-118	235/60, 245/55, 245/60, 255/55	 + Red.Ringe 72,6-60,1
8 x 18	B24	38	ZP559F+R	73, 118	235/60, 245/55	+ Red.Ringe 72,6-60,1
	B36	35	ZP559F+R	73, 118	235/60	+ Red.Ringe 72,6-60,1
	B42 / B44	40	ZP559F+R	73, 118	235/60, 245/55, 255/55	+ Red.Ringe 72,6-60,1
8 x 19	RC34	40	-	59-118	235/55, 245/50	Orig.-Verschr.
	CA 17	40	ZP561F+R	73-118	235/55, 245/50, 245/55, 255/50	+ Red.Ringe 72,6-60,1
8,5 x 19	B32 / B37 / B42	35	ZP559F+R	73, 118	235/55	+ Red.Ringe 72,6-60,1
	B36	38	ZP559F+R	73, 118	235/55	+ Red.Ringe 72,6-60,1
	B44	40	ZP559F+R	73, 118	235/55, 245/50	+ Red.Ringe 72,6-60,1
7,5 x 20	B43	40	-	73, 118	235/50, 245/45	 Orig.-Verschr.
	RC36	35	ZP559F	73, 118	235/50, 245/45	
	B43	35	ZP559F	73, 118	235/50, 245/45	
8 x 20	B38	35	ZP559F+R	73, 118	235/50, 245/45, 255/45	+ Red.Ringe 72,6-60,1
	B40	35	ZP559F+R	73, 118	235/50, 245/45, 255/45	+ Red.Ringe 72,6-60,1
8,5 x 20	B42	35	ZP559F+R	73, 118	235/50, 245/45, 255/45	+ Red.Ringe 72,6-60,1
	B44	40	ZP559F+R	73, 118	235/50, 245/45, 255/45, 265/45	+ Red.Ringe 72,6-60,1

Camry Hybrid	ab 10/2019	XV7 (EU,M), -/TMG	5/114,3	60,1	e6*2007/46*0322*..., e13*2007/46*2046*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC29	38	ZP574	131	215/50, 215/55, 225/50, 245/45		
		48	ZP574	131	215/50, 215/55, 225/50, 235/50, 245/45		
	RC32	40	ZP580D6F	131	215/50, 215/55, 225/50, 245/45		
		45	ZP580D6F	131	215/50, 215/55, 225/50, 235/50, 245/45		auch für Hybrid
	RC34	40	ZP580D6F	131	215/50, 215/55, 225/50		auch für Hybrid
	B24	48	ZP574	131	215/50, 215/55, 225/50, 235/50, 245/45		
	B36	38	ZP574	131	215/50, 215/55, 225/50, 245/45		
46		ZP574	131	215/50, 215/55, 225/50, 235/50, 245/45			
7,5 x 18	RC30	35+45	ZP574	131	215/45, 215/50, 225/45, 235/45		
	RC32	45	ZP580D6F	131	215/45, 215/50, 225/45, 235/45		
	B32	35+45	ZP574	131	215/45, 215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	35+45	Artikel Nr. 98502	131	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	AC-521	45	Artikel Nr. 98502	131	215/45, 215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	CA 20	40	ZP574	131	215/45, 215/50, 225/45, 235/45		
8 x 18	RC29	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	RC32	40	ZP580D6F	131	215/45, 225/45, 235/45		
		45	ZP580D6F	131	215/45, 225/45, 235/45, 245/40		
	B24	48	ZP574	131	215/45, 225/45, 235/45, 245/40		
	B37	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	B38	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
			ZP580D6F	131	215/45, 225/45, 235/45, 245/40		
	B42	40+45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	B44	40+45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	AC-518	40	Artikel Nr. 98502	131	215/45, 225/45, 235/45, 245/40		Kit mit Artikelnummer 98502
7,5 x 19	AC-M10	45	Artikel Nr. 98502	131	215/45, 225/45, 235/45, 245/40		Kit mit Artikelnummer 98502
	CA 23	45	ZP574	131	215/45, 225/45, 235/45, 245/40		
	B32	40	ZP574	131	225/40		
	AC-521	45	Artikel Nr. 98502	131	225/40		Kit mit Artikelnummer 98502
8 x 19	RC29	38+48	ZP574	131	225/40, 235/35, 235/40, 245/35		
	B24	38+50	ZP574	131	225/40, 235/35, 235/40, 245/35		
	B38	38+45	ZP574	131	225/40, 235/35, 235/40, 245/35		
	AC-518	40	Artikel Nr.	131	225/40, 235/35, 235/40, 245/35		Kit mit Artikelnummer 98502

6 x 19	RC318	70	98502	131	225/40, 235/35, 235/40, 245/35		Kit mit Artikelnummer 98502
	CA 19	45	ZP574	131	225/40, 235/35, 235/40, 245/35		
	CA 24	45	ZP574	131	225/40		
	Oxigin 29	40+50	ZP574	131	225/40, 235/35, 235/40, 245/35		
8,5 x 19	B32	45	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
	B36	44	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
	B42	45	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
	B44	40	ZP574	131	225/40, 235/35, 235/40		
	CA 20	45	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
	CA 23	40	ZP574	131	225/40, 235/35, 235/40		
	CA 26	46	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
	Oxigin 28	45	ZP574	131	225/40, 235/35, 235/40, 245/35, 255/35		
8 x 20	B38	45+50	ZP574	131	225/35, 235/35, 245/30		
	B43	35	-	131	225/35		Orig.-Verschr.
8,5 x 20	RC29	45	ZP574	131	225/35, 235/35, 245/30, 255/30		
	B24	42	ZP574	131	225/35, 235/35, 245/30		
	B42	45	ZP574	131	225/35, 235/35, 245/30, 255/30		
9 x 20	B37	43	ZP574	131	225/35, 235/35, 245/30		
	CA 23	45	ZP574	131	225/35, 235/35, 245/30		
	Oxigin 28	40	ZP574	131	225/35, 235/35		

C-HRab 01.2017AX1T5/114,360,1e11*2007/46*3641*..., e13*2007/46*1765*..., e6*2007/46*0264*..., e6*2007/46*0338*...

Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818

Dimension	Design	ET	KIT	KW	Reifendimension			Info
6,5 x 16	RC32	45	ZP580D6F	72-85	215/60, 215/65 , 225/60, 225/65, 235/55, 235/60			
	RC34	45	-	72-85	215/60, 215/65 , 225/60, 225/65, 235/55, 235/60			Orig.-Verschr., auch für Hybrid, Felge ist nur in SGVP erhältlich!!!
	RC24	44	ZP574	72, 85	215/65, 225/60, 235/60			
	RC27	38+50	ZP574	72, 85	215/65, 225/60, 235/60			ET38 bei 235/60 ✖
		45	ZP574	72, 85	215/65, 225/60, 235/60			
	RC30	45	ZP574	72, 85	215/65, 225/60, 235/60			
		50	ZP574	72, 85	215/65, 225/60, 235/60			
7 x 16	CA 20	45	ZP574	72, 85	215/65, 225/60, 235/60			
	RC24	45	ZP574	72, 85	215/65, 225/60, 235/60			
	RC28	45	ZP574	72, 85	215/65, 225/60, 235/60			
	RC30	40	ZP580D6F	72, 85	215/65			
6,5 x 17	RC27	45	ZP580D6F	72-112	215/60 , 225/55, 235/55			
	RC34	45	ZP580D6F	72-112	215/55, 215/60 , 225/55, 235/50, 235/55			auch für Hybrid
7 x 17	RC27 / RC30	45	ZP574	72-112	215/60, 225/55, 235/55			
	RC32	39	ZP580D6F	72-112	215/55			auch für Hybrid
	RC34	50	-	72-112	215/55, 215/60, 225/55, 235/50, 235/55, 245/50			Orig.-Verschr., auch für Hybrid
	B39	45	ZP574	72, 85	215/60, 225/55, 235/55			
	CA 26	45	ZP574	72-112	215/60, 225/55, 235/55			
7,5 x 17	RC28	45	ZP574	72, 85	215/60, 225/55			
	RC24	45	ZP574	72-112	215/60, 225/55			
	RC29	48	ZP574	72-112	215/60, 225/55, 235/55			
	RC32	45	ZP580D6F	72-112	215/55, 215/60, 225/55			auch für Hybrid
	B36	46	ZP574	72-112	215/60, 225/55			
	AC-518	40	Artikel Nr. 98502	72-112	215/60			Kit mit Artikelnummer 98502
7 x 18	RC27	50	ZP580D6F	72-112	205/55, 215/50, 215/55, 225/50			
	RC32	50	ZP580D6F	72-112	215/50, 215/55, 225/50 , 235/50			auch für Hybrid
	RC34	50	-	72-112	225/50			Orig.-Verschr.
7,5 x 18	RC30	45	ZP574	72-112	215/50, 215/55, 225/50, 235/45, 245/45			
	RC32	45	ZP580D6F	72-112	215/50, 215/55, 235/45			
	B32	45	ZP574	72-112	215/50, 215/55, 225/50, 235/45, 245/45			
	B39	45	ZP574	72-112	215/50, 215/55, 225/50, 235/45, 245/45			
	AC-MB6	45	Artikel Nr. 98502	72-112	215/50, 215/55, 225/50, 235/45, 245/45			Kit mit Artikelnummer 98502
	AC-521	45	Artikel Nr. 98502	72-112	215/50, 215/55, 225/50, 235/45, 245/45			Kit mit Artikelnummer 98502
	CA 20	40	ZP574	72-112	225/50, 225/55, 235/50, 245/45, 245/50			
8 x 18	RC29	45	ZP574	72-112	225/50, 235/45			
	RC32	45	ZP580D6F	72-112	235/45			
	B36	45	ZP574	72, 85	225/50, 235/45			
	B37	45	ZP574	72-112	225/50, 235/45			
	B38	45	ZP580D6F	72-112	225/50, 235/45			
		49	ZP574	72, 85	225/50, 235/45, 245/45			
	B42 / B44	45	ZP574	72-112	225/50, 235/45			
	AC-M10	45	Artikel Nr. 98502	72-112	225/50, 235/45			Kit mit Artikelnummer 98502
8,5 x 18	B32	45	ZP574	72, 85	235/45			
	RC34	40	-	72-112	225/40			Orig.-Verschr.

7,5 x 19	B32	40	ZP574	72-112	225/45, 235/45		
	B39	40+45	ZP574	72, 85	225/45, 235/45		
	AC-521	45	Artikel Nr. 98502	72-112	225/45, 235/45		Kit mit Artikelnummer 98502
8 x 19	RC29	48	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
	B38	45	ZP574	72, 85	225/45, 235/40, 235/45		
	AC-518	40	Artikel Nr. 98502	72-112	225/45		Kit mit Artikelnummer 98502
	Oxigin 29	50	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
8,5 x 19	B32	45	ZP574	72, 85	225/45, 235/40, 235/45		
	B37	45	ZP574	72-112	225/45, 235/40, 235/45		
	CA 26	46	ZP574	72-112	225/45, 235/40, 235/45		
	Oxigin 28	45	ZP574	72-112	225/45, 235/40, 235/45		
8 x 20	B38	45	ZP574	72-112	225/40, 235/35, 235/40		
8,5 x 20	RC29	45	ZP574	72-112	225/40, 235/35, 235/40		
	B42	45	ZP574	72-112	225/40, 235/35, 235/40		

C-HR NEU		ab 2024		AX2T (M), -/TGRE		5/114,3	60,1	e6*2018/858*00294*..., e13*2018/858*00573*..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6,5 x 17	RC27	30	-	72-112	215/60, 225/60				Orig.-Verschr.
	RC34	40	ZP580D6F	72-112	225/55, 235/55, 235/60				
7 x 17	RC27	35	ZP580D6F	72-112	215/60, 225/60, 235/55, 245/55				
	RC32	35	ZP580D6F	72-112	225/55, 235/55, 245/50, 245/55, 255/50				
		39	ZP580D6F	72-112	225/55, 235/55, 235/60, 245/50, 245/55, 255/50, 255/55				
	RC34	35	ZP580D6F	72-112	225/55, 235/55, 245/50, 245/55, 255/50				
7,5 x 17	RC34	40	ZP580D6F	72-112	225/55, 235/55, 235/60, 245/50, 245/55, 255/50, 255/55				
7 x 18	RC27	35	ZP580D6F	72-112	215/55, 225/50, 225/55, 235/50				
	RC34	35	-	72-112	215/55, 225/50, 225/55, 235/50, 245/50				Orig.-Verschr.
7,5 x 18	RC32	45	ZP580D6F	72-112	235/50, 245/45, 245/50				
	AC-MB6 / M10	35	Artikel Nr. 98502	72-112	215/55, 225/50, 225/55, 235/50				Kit mit Artikelnummer 98502
8 x 18	RC32	40	ZP580D6F	72-112	225/50, 225/55, 235/50, 245/45, 245/50, 255/45				
	B24	38	ZP574	72-112	225/50, 225/55, 235/50				
	B36	35	ZP574	72-112	225/50, 225/55				
	B42	30	ZP574	72-112	225/50, 225/55				
		40	ZP574	72-112	225/50, 225/55, 235/50, 245/50, 255/45				
	B44	40	ZP574	72-112	225/50, 225/55, 235/50, 245/50, 255/45				
7 x 19	RC27	35	-	72-112	225/50				Orig.-Verschr.
				72-112	215/50, 225/45, 225/50				Orig.-Verschr.
8 x 19	Oxigin 29	40	ZP574	72-112	225/45, 225/50, 235/45, 245/45				
8,5 x 19	B32	35	ZP580D6F	72-112	225/45, 225/50, 235/45				
	B36	38	ZP574	72-112	225/45, 225/50, 235/45, 245/45				
	B44	30	ZP574	72-112	225/45				
		40	ZP574	72-112	225/45, 225/50, 235/45, 245/45				
	CA 20	30	ZP574	72-112	225/45				
8 x 20	RC36	35	-	72-112	215/45, 225/40, 235/40				Orig.-Verschr.
	B43	35	-	72-112	215/45, 225/40, 235/40				Orig.-Verschr.
9 x 20	CA 23	45	ZP574	72-112	235/40, 245/40				

Corolla (siehe Konfigurator)		ab 2014		E15EJ / E18		5/114,3	60,1	e11*2001/116*0304*09*..	
------------------------------	--	---------	--	-------------	--	---------	------	-------------------------	--

Corolla		ab 04.2019		ZE1HE (EU,M)		5/114,3		60,1		e6*2007/46*0318*..., e13*2007/46*2012*..	
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 16	RC27	38	ZP574	72, 85	195/55, 195/60, 205/55, 215/55, 225/50						
	RC30	38	ZP574	72, 85, 97	195/55, 195/60, 205/55, 215/55, 225/50				incl. Hybrid		
7 x 16	RC30	40	ZP580D6F	72-112	195/55, 195/60, 205/55, 215/55, 225/50				incl. Hybrid		
6,5 x 17	RC27	30+35	-	72-97	205/50				Orig.-Verschr., incl. Hybrid		
7 x 17	RC27	35	ZP580D6F	72-112	205/50, 215/45, 225/45				incl. Hybrid		
		38	ZP574	72-112	205/50, 215/45, 225/45				incl. Hybrid		
	RC32	39	ZP580D6F	72-112	195/50, 205/45, 205/50, 215/45, 225/45						
	RC34	35	ZP580D6F	72-112	195/50, 205/45, 205/50, 215/45, 225/45				incl. Hybrid		
7,5 x 17	RC32	40	ZP580D6F	72-112	205/45, 205/50, 215/45, 225/45						
	RC34	40	ZP580D6F	72-112	205/45, 205/50, 215/45, 225/45				incl. Hybrid		
	RC24	38	ZP574	72-112	205/50, 215/45, 225/45, 235/45				incl. Hybrid		
	RC29	38	ZP574	72-112	205/50, 215/45, 225/45, 235/45				incl. Hybrid		
	B24	38	ZP574	72-112	205/50, 215/45, 225/45, 235/45				incl. Hybrid		
	B36	38	ZP574	72-112	205/50, 215/45, 225/45, 235/45				incl. Hybrid		
	AC-518	40	Artikel Nr. 98502	72-112	205/50, 215/45, 225/45, 235/45				Kit mit Artikelnummer 98502, incl. Hybrid		
7 x 18	RC34	35	-	72-112	205/40, 205/45, 215/40				Orig.-Verschr.		

7,5 x 18	RC30	35	ZP574	72, 85, 112	205/45, 215/40, 225/40		incl. Hybrid
	B32	35	ZP574	72-112	205/45, 215/40, 225/40		incl. Hybrid
	B39	35	ZP574	72,85,112	205/45, 215/40, 225/40		incl. Hybrid
	AC-MB6	35	Artikel Nr. 98502	72-112	205/45, 215/40, 225/40		Kit mit Artikelnummer 98502, incl. Hybrid
8 x 18	RC32	40	ZP580D6F	72-112	205/40, 205/45, 215/40, 225/35, 225/40, 235/35		
	RC29	35	ZP574	72,85,112	215/40, 225/40		incl. Hybrid
	B36 / B37	35	ZP574	72-112	215/40, 225/40		incl. Hybrid
	B42 / B44	40	ZP574	72-112	215/40, 225/40, 235/40, 245/35		incl. Hybrid
7,5 x 19	AC-518	40	Artikel Nr. 98502	72-112	215/40, 225/40, 235/35, 235/40, 245/35		Kit mit Artikelnummer 98502, incl. Hybrid
	RC34	40	-	72-112	225/35		Orig.-Verschr.
	B32	40	ZP574	72-112	225/35		incl. Hybrid
	RC29	38	ZP574	72-112	225/35, 235/35		incl. Hybrid
8 x 19	B24 / B38	38	ZP574	72-112	225/35, 235/35		incl. Hybrid
	AC-518	40	Artikel Nr. 98502	72-112	225/35, 235/35, 245/30		Kit mit Artikelnummer 98502, incl. Hybrid
	Oxigin 29	40	ZP574	72-112	225/35, 235/35, 245/30		incl. Hybrid
	B32	35	ZP574	72,85,112	225/35		
8,5 x 19	B36	38	ZP574	72-112	225/35, 235/30, 235/35, 245/30, 255/30		incl. Hybrid, ohne Radhausverbr. ab 245/30 ✖
	B42	35	ZP574	72-112	225/35		incl. Hybrid
	B44	40	ZP574	72-112	225/35, 235/30, 235/35		incl. Hybrid
	CA 23	40	ZP574	72-112	225/35, 235/30, 235/35		incl. Hybrid

Corolla Trek	ab 2019	ZE1HE (EU,M), -/TMG	5/114,3	60,1	e6*2007/46*0318*..., e13*2007/46*2012*..
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 16	RC30	40	ZP580D8F	72, 112	205/55	 incl. Hybrid, nur M+S
7 x 17	RC27	35	ZP580D8F	72, 112	205/50, 215/45, 225/45	incl. Hybrid, nur M+S
7,5 x 17	RC24 / RC29	38	ZP574	72, 112	205/50, 215/45, 225/45	incl. Hybrid, bis 215/45 nur M+S
	B24 / B36	38	ZP574	72, 112	205/50, 215/45, 225/45	incl. Hybrid, bis 215/45 nur M+S
7,5 x 18	RC30	35	ZP574	72, 112	205/45, 215/40	incl. Hybrid, nur M+S
	B32	35	ZP574	72, 112	205/45, 215/40	incl. Hybrid, nur M+S
	AC-M10	35	ZP580D6F+R	72, 112	205/45, 215/40	incl. Hybrid, nur M+S
8 x 18	RC29	35	ZP574	72, 112	215/40	incl. Hybrid, nur M+S
	B36 / B37	35	ZP574	72, 112	215/40	incl. Hybrid, nur M+S
	B42 / B44	40	ZP574	72, 112	215/40M+S, 225/40	incl. Hybrid
	AC-518	40	ZP580D6F+R	72, 112	215/40, 225/40	incl. Hybrid, + Red.Ringe 73,1-60,1
7,5 x 19	B32	40	ZP574	72, 112	225/35	incl. Hybrid
8 x 19	B38	38	ZP574	72, 112	225/35, 235/35	incl. Hybrid, ✖

Corolla Cross NEU	ab. Sept. 2022	XG1TJ(JP,M), -/TGRE	5/114,3	60,1	e6*2018/858*00186*..., e13*2018/858*00420*..
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 17	RC27	35	-	72-112	215/60, 225/55, 235/55	 Orig.-Verschr., auch Hybrid
		45	ZP580D6F	72-112	215/60, 225/55, 235/55	 auch Hybrid
	RC34	45	ZP580D6F	72-112	215/60, 225/55, 235/55	 Orig.-Verschr., auch Hybrid
	RC27	40	ZP580D6F	72-112	215/60, 225/55, 235/55	
7 x 17	RC27	45	ZP574	72-112	215/60, 225/55, 235/55, 245/50	
	RC32	35	ZP580D6F	72-112	215/60, 225/55	
		39	ZP580D6F	72-112	215/60, 225/55, 235/55	
	RC34	35	ZP580D6F	72-112	215/60, 225/55	
7,5 x 17	CA 26	45	ZP574	72-112	215/60, 225/55, 235/55, 245/50	
	RC24	38	ZP574	112	215/60, 225/55	
		45	ZP574	112	215/60, 225/55, 235/55, 245/50	
	RC28	45	ZP574	112	215/60, 225/55, 235/55, 245/50	
	RC32	40	ZP580D6F	72-112	215/60, 225/55, 235/55	
	RC34	40	ZP580D6F	72-112	215/60, 225/55, 235/55	
7 x 18	B24	38	ZP574	72-112	215/60, 225/55	
	RC27	40	-	72-112	225/50	 Orig.-Verschr., Ausföhr. TO
	RC34	35	-	72-112	215/55, 225/50	Orig.-Verschr., auch Hybrid, Ausföhr. TO
		45	-	72-112	215/55, 225/50, 235/50	Orig.-Verschr., auch Hybrid, Ausföhr. TO
7,5 x 18	RC32	45	ZP580D6F	72-112	215/55, 225/50, 235/50, 245/45	
	AC-MB6 / AC-M10	45	Artikel Nr. 98502	72-112	215/50, 215/55, 225/50, 235/45, 235/50, 245/45	Kit mit Artikelnummer 98502
	CA 20	40	ZP574	72-112	215/55, 225/50, 235/50, 245/45	
	RC32	45	ZP580D6F	72-112	215/55, 225/50, 235/50, 245/45, 255/45	
	B24	38	ZP574	72-112	225/50, 235/45, 245/45	
	B36	35	ZP574	112	235/45	
		45	ZP574	72-112	225/50, 235/45, 235/50, 245/45, 255/45	
	B42	35	ZP574	112	235/45	
		40	ZP574	72-112	225/50, 235/45, 245/45	

8 x 18		45	ZP574	72-112	225/50, 235/45, 235/50, 245/45, 255/45		
	B44	40	ZP574	72-112	225/50, 235/45, 245/45		
		45	ZP574	72-112	225/50, 235/45, 235/50, 245/45, 255/45		
	AC-M10	45	Artikel Nr. 98502	72-112	225/50, 235/45, 235/50, 245/45, 255/45		Kit mit Artikelnummer 98502
7 x 19	CA 20 / CA 23 RC27	45	ZP574	72-112	225/50, 235/45, 235/50, 245/45, 255/45		
		35	-	72-112	225/45		Orig.-Verschr.
7,5 x 19	RC34	40	-	72-112	225/45, 235/45		Orig.-Verschr., auch Hybrid
8 x 19	B38	38	ZP574	112	225/45, 235/40, 235/45		
		45	ZP574	112	225/45, 235/40, 235/45, 245/40		
	CA 17	40	ZP574	112	225/45		
	CA 19	45	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
8,5 x 19	Oxigin 29	40	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
	B32	35	ZP574	72-112	225/45		
	B36	38	ZP574	72-112	225/45, 235/40, 235/45		
	B37	45	ZP574	112	225/45, 235/40, 235/45, 245/40		
	B44	40	ZP574	72-112	225/45, 235/40, 235/45		
	CA 20	45	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
	CA 23	40	ZP574	72-112	225/45, 235/40, 235/45		
	Oxigin 28	45	ZP574	72-112	225/45, 235/40, 235/45, 245/40		
8 x 20	RC36	35	-	72-112	225/40, 235/35, 235/40		Orig.-Verschr.
	B38	35	ZP574	112	225/40, 235/35, 235/40		
		45	ZP574	112	225/40, 235/35, 235/40, 245/35		
	B40	35	ZP574	72-112	225/40, 235/35, 235/40		
8,5 x 20	B43	35	-	72-112	225/40, 235/35, 235/40		Orig.-Verschr.
	B42	35	ZP574	112	225/40		
	B44	40	ZP574	112	225/40, 235/35, 235/40		
9 x 20	CA 23	45	ZP574	112	225/40, 235/35, 235/40, 245/35		
	Oxigin 28	40	ZP574	112	225/40, 235/35, 235/40		

GR86 NEU		ab Juni 2022		T2	5/100	56,1	e13*2018/858*00225*..	
Sensor - Brocksens 6								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 17	RC32	48	-	172	215/45, 225/40, 225/45			Orig.-Verschr.
	B24	38	ZP512	172	215/45			
7,5 x 18	RC32	48	-	172	215/40, 225/35			Orig.-Verschr.

Highlander NEU		2021		XU7 (EU,M), I-TGRE		5/114,3		60,1		e6*2018/858*00001*..., e13*2018/858*00028*..	
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 18	B36	35	ZP574	140	235/65, 245/60, 255/60						
8,5 x 18	B32	35	ZP574	140	235/65, 245/60, 255/60						
8 x 20	RC36	35	-	140	235/55, 245/50, 255/50				Orig.-Verschr.		
	B43	35	-	140	235/55, 245/50, 255/50				Orig.-Verschr.		
	B40	30	ZP580D6F	140	235/55, 245/50, 255/50						
		35	ZP574	140	235/55, 245/50, 255/50						
8,5 x 19	B32 / B37	35	ZP574	140	235/60, 245/55, 255/55, 265/50						
	Oxigin 28	30	ZP574	140	235/60, 245/55						
8,5 x 20	RC29	35	ZP574	140	235/55, 245/50, 255/50, 265/45, 275/45						
	B24	35	ZP574	140	235/55, 245/50, 255/50, 265/45, 275/45						

Hilux (siehe Konfigurator)		ab 07.05-2015		N25S/N25T	6/139,7		
---	--	---------------	--	-----------	---------	--	--

Hilux (siehe Konfigurator)		ab 2010		N2	6/139,7	106,1	e11*2007/46*0149*..., e11*2007/46*0148*...
---	--	---------	--	----	---------	-------	--

Hilux		ab 2015		AN1P(EU, N)		6/139,7		106,1		e11*2007/46*2587*... e13*2007/46*1698*... e6*2007/46*0337*...	
Sensor - Brocksens 6											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 17	RC31	35	ZP600F	110	225/70+C, 235/65, 245/60, 245/65, 255/60				✖		
7,5 x 17	RC35	30	ZP600F	110-150	265/65, 275/60				✖		
				110	235/65, 245/60, 245/65, 255/60, 265/60, 275/55				✖		
		25	ZP600F	110-150	265/65, 275/60						
				110	235/65, 245/60, 245/65, 255/60, 265/60, 275/55				✖		
	RC14-6S	25	ZP600F	110-150	265/65, 275/60						
		30		110-150	265/65, 275/60				nur SKM!!		
8 x 18	RC31	25	ZP600F	110	235/60, 235/65, 255/55, 255/60, 265/55, 265/60						
	8400 Bluster	20	-	110-150	265/60				Orig.-Verschr.		
9 x 20	8400 Bluster	28	-	110-150	275/45				Orig.-Verschr.		

Landcruiser		ab 2009		J15TM/TMG	6/139,7	106,1	e6*2007/46*0001*..., e1*2007/46*0231*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 17	RC31	20	ZP600D6F	127-207	255/65			

7,5 x 17	RC35	25	ZP600D6F	127-207	265/65, 275/60		
8 x 18	RC31	25	ZP600SF	127-207	265/60		
	8400 Bluster	20	-	127-207	265/60, 285/55		Orig.-Verschr., bei 285/55 
9 x 20	Oxigin 24	20	ZP600SF	127-207	265/50, 275/45, 275/50		auch Typ J15TN

Landcruiser		NEU i.V.		2024		J25M(T)		95,1		e6*2018/858*00296*..	
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8 x 18	RC31	55	-	151	245/70, 245/75, 255/65, 255/70, 265/65, 265/70, 275/60, 275/65, 285/60, 285/65				Orig.-Verschr., Ausführung TO4, i.V., Lieferzeit ca. KW21		

Mirai NEU		im Laufe 1. Quartal 2021		AD1 (EU, M)		5/114,3		60,1		e11*KS07/46*2839*..	
Sensor - Brocksens 6											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 17	RC32	35	ZP580D6F	55	215/50, 215/55						
		39	ZP580D6F	55	215/50, 215/55						
	RC34	35	ZP580D6F	55	215/50, 215/55						
7 x 18	RC34	35	-	55	215/45, 225/45				Orig.-Verschr.		
7,5 x 18	CA 20	40	ZP574	55	215/45, 225/45						
8 x 18	RC32	40	ZP580D6F	55	215/45, 225/45						
7,5 x 19	RC34	40	-	55	225/40				Orig.-Verschr.		

Prius Plus (siehe Konfigurator)		2012 - 2015		XW4(a)		5/114,3		60,1		e11*2007/46*0157*...., e11*2001/116*0264*	
--	--	-------------	--	--------	--	---------	--	------	--	---	--

Prius Plus TMG (siehe Konfigurator)				XW3(a) / TMG		5/114,3		60,1		e13*2007/46*1956*..	
--	--	--	--	--------------	--	---------	--	------	--	---------------------	--

Prius IV		ab 03.16		XW5 (EU,M), -/TMG		5/100		54,1		e11*2007/46*2971*...., e13*2007/46*1931*...., e6*2007/46*0339*..	
Sensor - Brocksens 6											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 15	Originaldim.	40		72	195/65						
	RC28	38	ZP510	72	195/65, 205/60						
7 x 16	RC28	38	ZP510	72	195/55, 195/60, 205/55						
7 x 17	Originaldim.	50		72	215/45						
	RC27 / RC30	43	ZP510	72	205/45, 205/50, 215/45, 225/45						
7,5 x 17	RC29	38	ZP510	72	205/45, 205/50, 215/45						
	B24	38	ZP510	72	205/45, 205/50, 215/45						
	B36	38	ZP510	72	205/45, 205/50, 215/45						
7,5 x 18	B39	42	ZP510	72	205/40, 205/45, 215/40						

Prius PHV IV		ab 06.2017		XW5P (EU,M)		5/100		54,1		e11*2007/46*3704*...., e6*2007/46*0340*..	
Sensor - Brocksens 6											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
6,5 x 15	Originaldim.	40		72	195/65						
	RC28	38	ZP510	72	195/65, 205/60						
7 x 16	RC28	38	ZP510	72	195/55, 195/60, 205/55						
7,5 x 17	B24	38	ZP510	72	205/45, 205/50, 215/45						
	B36	38	ZP510	72	205/45, 205/50, 215/45						

Prius V PHEV NEU		ab 2024		XW6(M)		5/114,3		60,1		e6*2018/858*00260*..	
Sensor - Brocksens Universal											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
6,5 x 17	RC27	40	ZP580D8F	111	195/60, 205/55, 215/50, 215/55				17 Zoll Serienbereifung		
		30	-	111	195/60				Orig.-Verschr.		
7 x 17	RC27	35	ZP580D8F	111	195/60				17 Zoll Serienbereifung		
7,5 x 18	AC-M10	35	ZP580D8F+ R	111	215/45				+ Red.Ringe 73,1-60,1, 17 Zoll Serienbereifung		
8 x 18			40	ZP580D8	111	215/45				17 Zoll Serienbereifung	

Proace		ab 2016		V		5/108		65,1		e2*2007/46*0537*..., e2*2007/46*0538*..	
Sensor - Brocksens Universal											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
7 x 16	RC30	46	- od. ZP541F	70-130	215/65, 215/65C				Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto , ohne erhöhte Nutzlast!		
	RC25T		- od. ZP541F	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55				Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto , ohne erhöhte Nutzlast!		
			- od. ZP541F	70-130	215/60C, 225/55C				Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto , mit erhöhter Nutzlast!		
	RC30T		- od. ZP541F	70-130	215/60+C, 225/55, 235/50, 235/55				Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto		
	RC31		- od.	70-130	215/60+C, 225/55				Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F		

7 x 17			ZP537F	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		mit € 28,00 netto!!
	B45	46	- od. ZP541F	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, ohne erhöhte Nutzlast!
			- od. ZP541F	70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, mit erhöhter Nutzlast!
	AC-V51	45	-	70-130	215/60, 215/60C, 225/55, 225/55C, 235/50, 235/55		Orig.-Verschr. von Stahlfelge, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
			-	70-130	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, mit erhöhter Nutzlast, nicht für elektr. Parkbremse
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 18	RC25T	45	- od. ZP541F	70-130	215/55, 225/50, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, sonst ZP541F m. € 32,00 netto, ohne erhöhte Nutzlast!!
	B45	45	- od. ZP541F	70-130	215/55, 225/50, 225/50C, 235/45, 245/45		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, ohne erhöhte Nutzlast
				70-130	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, mit erhöhter Nutzlast
	AC-V51	47	-	70-130	245/45		Orig.-Verschr. von Stahlfelge, geschl. Aufbau, ohne erhöhte Nutzlast, nicht für elektr. Parkbremse
	CA 20	45	ZP538F	57-130	235/45, 245/45		
8 x 18	RC34	44	ZP538F	70-130	235/45, 245/45		

Proace electric NEU							
ab 2022			V		5/108	65,1	e2*2007/46*0538*11-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis von € 32,00 netto
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis von € 32,00 netto
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, geschl. Aufbau
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45		

Proace Verso electric NEU							
ab 2022			V		5/108	65,1	e2*2007/46*0537*15-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC25T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis von € 32,00 netto
	RC30T	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis von € 32,00 netto
	B45	46	- od. ZP541F	57 (100)	215/60C, 225/55, 225/55C, 235/55		Orig.-Verschr. von Stahlfelge, wenn Alu, dann ZP541F mit Aufpreis € 32,00 netto, geschl. Aufbau
	Pro1	45	-	57-130	215/55, 215/60, 215/60C, 225/55, 225/55C, 235/50		Orig.-Verschr.
7,5 x 18	B45	45	- od. ZP541F	57 (100)	225/50C		Orig.-Verschr. von Stahlfelge, wenn Alu, dann Kit ZP541F mit € 32,00 netto Aufpreis, geschl. Aufbau
	CA 20	45	ZP538F	57-130	235/45, 245/45		

Proace City Verso EV NEU i.V.							
ab Mai 2022			V		5/108	65,1	e2*2007/46*0537*15-..
Dimension	Design	ET	KIT	KW	Reifendimension		Info

Proace City			ab 2020	E, E(EU,N)-TMG	5/108	65,1	e2*2007/46*0686*..., e13*2007/46*2270*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC30	47	ZP538F	55-96	205/55, 205/60, 215/55			nicht Bremse 283mm, nicht bei 15Zoll Serie
	RC34	47	- od. ZP537F	56-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC32	47	ZP538F	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55			
	CA 20	45	ZP538	55-96	205/55, 205/60, 215/55, 225/50, 225/55			
	Pro1	42	-	56-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55			Orig.-Verschr., Serienreifen bis 205/..
7 x 16	RC28	44	ZP538F	55-96	205/55, 205/60, 215/55			nicht Bremse 283mm
	RC30	44	ZP538F	55-96	205/55, 205/60, 215/55			
	RC30	50	ZP538F	55-96	205/50, 205/55, 225/45			
	RC34	50	- od. ZP537F	75-96	205/55			Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!

7 x 17	CA 26	50	ZP538F	55-96	205/55		
				55-96	205/50, 205/55, 225/45		
	RC27	42	- od. ZP537F	55-81	205/50, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!! bei 15" Serie
				55-96	205/50, 205/55, 215/50, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC30	42	ZP538F	55-81	205/50, 215/45, 225/45		bei 15Zoll Serie
				55-96	205/50, 205/55, 215/50, 225/45		nicht bei 15Zoll Serie
7,5 x 17	CA 26	42	ZP538F	55-81	205/50, 215/45, 225/45		15Zoll Serie
				55-96	205/50, 205/55, 215/50, 225/45		
	Pro1	45	-	56-96	205/45, 205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr., Serienreifen bis 205/..
	RC29	45	ZP538	55-96	205/50, 205/55, 225/45		
7 x 18	B24	45	ZP538	55-96	205/50, 205/55, 225/45		nicht bei 15Zoll Serie
	B36	45	ZP538	55-96	205/50, 205/55, 225/45		
	RC27	44+48	- od. ZP537F	55-96	205/45, 215/45, 225/45		Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45		nicht bei 15Zoll Serie
	B32 / B39	45	ZP538	55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15Zoll Serie
	AC-MB6 / AC-M10	42	ZP538F+R	55-81	205/45, 215/40, 225/40		bei 15Zoll Serie
				55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15Zoll Serie, + Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	55-81	205/45, 215/40, 225/40		bei 15Zoll Serie
				55-96	205/45, 215/45, 225/40, 225/45		nicht bei 15Zoll Serie, + Red.Ringe 73,1-65,1
8 x 18	CA 20	45	ZP538F	56-96	215/40, 215/45, 225/40		Serienreifen bis 205/..
	RC29	45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15Zoll Serie
	RC34	44	ZP538F	56-96	215/40, 215/45		Serienreifen bis 205/..
				56-96	215/50, 235/45		Serienreifen ab 215/..
	B24	45	ZP538	55-96	215/45, 225/40, 225/45		nicht bei 15Zoll Serie
	B37	45	ZP538	55-96	215/45, 225/40, 225/45		nicht Bremse 283 u. 304mm
	B42 / B44	42	ZP538	55-81	215/40		bei 15Zoll Serie
				55-96	215/45		
	AC-M10	42	ZP538F+R	55-81	215/40		+ Red.Ringe 73,1-65,1, bei 15Zoll Serie
				55-96	215/45		+ Red.Ringe 73,1-65,1, nicht Bremse 283mm
7,5 x 19	AC-521	43	ZP538F+R	55-96	215/45		+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538	55-96	215/45, 225/40, 225/45		nicht Bremse 283 u. 304mm
	B32	42	ZP538F	55-81	225/35		bei 15 Zoll Serie
	AC-521	42	ZP538F+R	55-81	225/35		bei 15 Zoll Serie, + Red.Ringe 73,1-65,1

Proace City Verso	ab 2020	E, E(EU,N)-TMG	5/108	65,1	e2*2007/46*0685*..., e13*2007/46*2269*..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC30	47	ZP538F	75-96	205/55, 205/60, 215/55	 nicht Bremse 283mm, nicht bei 15Zoll Serie
	RC34	47	- od. ZP537F	56-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55, 225/50, 225/55	 Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	RC32	47	ZP538F	55-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55	
	CA 20	45	ZP538	75-96	205/55, 205/60, 215/55, 225/50, 225/55	
	Pro1	42	-	56-96	195/55, 195/60, 205/55, 205/60, 215/50, 215/55	Orig.-Verschr., Serienreifen bis 205/..
7 x 16	RC28	44	ZP538F	75-96	205/55, 205/60, 215/55	nicht Bremse 283mm
	RC30	44	ZP538F	75-96	205/55, 205/60, 215/55	
7 x 17	RC30	50	ZP538F	55-96	205/50, 205/55, 225/45	
	RC34	50	- od. ZP537F	75-96	205/55	 Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
	CA 26	50	ZP538F	75-96	205/55	
				75-96	205/50, 205/55, 225/45	
	RC27	42	- od. ZP537F	75-96	205/50, 205/55, 215/50, 225/45	Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 17	RC30	42	ZP538F	75-96	205/50, 205/55, 215/50, 225/45	nicht bei 15Zoll Serie
	CA 26	42	ZP538F	75-96	205/50, 205/55, 215/50, 225/45	
	RC29	45	ZP538	75-96	205/50, 205/55, 225/45	
	B24	45	ZP538	75-96	205/50, 205/55, 225/45	nicht bei 15Zoll Serie
	B36	45	ZP538	75-96	205/50, 205/55, 225/45	
7 x 18	RC27	44+48	- od. ZP537F	75-96	205/45, 215/45, 225/45	Orig.-Verschr. von Alufelge, bei Stahlfelge ZP537F mit € 28,00 netto!!
7,5 x 18	RC30	49	ZP538F	55-96	205/45, 215/45	nicht bei 15Zoll Serie
	B32 / B39	45	ZP538	75-96	205/45, 215/45, 225/40, 225/45	nicht bei 15Zoll Serie
	AC-M10	42	ZP538F+R	75-96	205/45, 215/45, 225/40, 225/45	+ Red.Ringe 73,1-65,1
	AC-MB6	42	ZP538F+R	75-96	205/45, 215/45, 225/40, 225/45	+ Red.Ringe 73,1-65,1
	AC-521	42	ZP538F+R	75-96	205/45, 215/45, 225/40, 225/45	+ Red.Ringe 73,1-65,1, nicht bei 15Zoll Serie
8 x 18	RC29	45	ZP538	75-96	215/45, 225/40, 225/45	nicht bei 15Zoll Serie
	B24 / B37	45	ZP538	75-96	215/45, 225/40, 225/45	nicht bei 15Zoll Serie
	B42 / B44	42	ZP538	75-96	215/45	
	AC-521	43	ZP538F+R	75-96	215/45	+ Red.Ringe 73,1-65,1
	CA 20	45	ZP538	75-96	215/45, 225/40, 225/45	nicht Bremse 283 u. 304mm

RAV 4 IV (siehe Konfigurator)	ab Facelift 2016	XA3(a)	5/114,3	60,1	e6*2001/116*0105*14-..., e13*2007/46*1657*..
--------------------------------------	-------------------------	---------------	----------------	-------------	--

RAV 4 Hybrid (siehe Konfigurator)	ab 03.16	XA4	5/114,3	60,1	e6*2007/46*0166*..., e13*2007/46*1658*..
--	-----------------	------------	----------------	-------------	--

RAV 4 (V)	ab 2019	XA5 (EU, M), -/TMG	5/114,3	60,1	e6*2007/46*0289*..., e13*2007/46*1991*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 17	RC27	35	ZP580D8F	129, 131	225/65, 235/60, 255/55		
	RC34	35	ZP580D8F	129-131	225/65, 225/70, 235/60, 235/65, 245/60		
	RC27	38	ZP574	129, 131	225/65, 235/60		
	RC30	38	ZP574	129, 131	225/65, 235/60		
	RC32	39	ZP580D8F	129-131	225/65, 225/70, 235/60, 235/65, 245/60, 255/55, 255/60		
7,5 x 17	B39	38	ZP574	129, 131	225/65, 235/60		
	RC24	38	ZP574	129, 131	225/65, 235/60		
	RC29	38	ZP574	129, 131	225/65, 235/60		
	RC32	40	ZP580D8F	129-131	225/65, 225/70, 235/60, 235/65, 245/60, 255/55		
	RC34	40	ZP580D8F	129-131	225/65, 225/70, 235/60, 235/65, 245/60, 255/55, 255/60		auch für Hybrid
7,5 x 17	B24 / B36	38	ZP574	129, 131	225/65, 235/60		
	AC-518	40	Artikel Nr. 98502	129, 131	225/65, 235/60		Kit mit Artikelnummer 98502
7 x 18	RC27	35	ZP580D6F	129, 131	225/60, 235/55		
	RC34	35	-	129-131	225/60, 235/55, 235/60, 245/50, 245/55		Orig.-Verschr.
7,5 x 18	RC30	35	ZP574	129, 131	225/60, 235/55, 235/60		
	B32 / B39	35	ZP574	129, 131	225/60, 235/55, 235/60		
	AC-MB6 / AC-M10	35	Artikel Nr. 98502	129, 131	225/60, 235/55, 235/60		Kit mit Artikelnummer 98502
	CA 20	40	ZP574	129-131	225/60, 235/55, 235/60, 245/50, 245/55, 255/50		
8 x 18	RC25	35	ZP574	129, 131	225/60, 235/55, 235/60		
	RC29	35	ZP574	129, 131	225/60, 235/55, 235/60		
	RC32	40	ZP580D8F	129-131	225/60, 235/55, 235/60, 245/50, 245/55		
	B24	38	ZP574	129, 131	225/60, 235/55, 235/60		
	B37 / B38	35	ZP574	129, 131	225/60, 235/55, 235/60		
	B42	30+40	ZP574	129, 131	225/60		
	B44	40	ZP574	129, 131	225/60		
	AC-518	40	Artikel Nr. 98502	129, 131	225/60		Kit mit Artikelnummer 98502
8,5 x 18	B32	35	ZP574	129, 131	225/60, 235/55, 235/60		
7 x 19	RC27	35	-	129, 131	225/55, 235/50, 235/55, 245/45		Orig.-Verschr.
7,5 x 19	RC34	40	-	129-131	235/55, 245/45, 245/50		Orig.-Verschr.
	B32	40	ZP574	129, 131	225/55, 235/50, 235/55		
8 x 19	RC29	38	ZP574	129, 131	225/55, 235/50, 235/55		
	B24 / B38	38	ZP574	129, 131	225/55, 235/50, 235/55		
	AC-518	40	Artikel Nr. 98502	129, 131	225/55		Kit mit Artikelnummer 98502
	CA 17	40	ZP574	129-136	225/55, 235/55, 255/45		
	Oxigin 29	40	ZP574	129, 131	225/55		
8,5 x 19	B32 / B37	35	ZP574	129, 131	235/50, 235/55, 255/45		
	B42	35	ZP574	129, 131	235/50, 235/55, 255/45		
	Oxigin 25	35	ZP574	129-131	235/55, 255/45		
7,5 x 20	RC36	35	ZP580D6F	129, 131	235/45, 235/50, 245/45		
	B43	35+40	ZP580D6F	129, 131	235/45, 235/50, 245/45		
8 x 20	RC36	35	-	129, 131	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B38	35	ZP574	129, 131	235/45, 235/50, 245/45, 255/45		
	B40	30	ZP580D8F	129, 131	235/45, 235/50, 245/45		bei 235/50 ✖
	B40	35	ZP574	129, 131	235/45, 235/50, 245/45, 255/45		
	B43	35	-	129, 131	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
8,5 x 20	RC29	35	ZP574	129, 131	235/45, 235/50, 245/45, 255/40, 255/45		
	RC29	40	ZP574	129, 131	235/45		
	B24	35	ZP574	129, 131	235/45, 235/50, 245/45, 255/40, 255/45		
	B32	40	ZP574	129, 131	235/45		
	B42	35	ZP574	129, 131	235/45, 235/50, 245/45, 255/40, 255/45		255/40 nicht zulässig bei 19 Zoll Serie
	B44	30+40	ZP574	129, 131	235/45		
9 x 20	AC-518	40	Artikel Nr. 98502	129, 131	235/45		Kit mit Artikelnummer 98502
	B37	40	ZP574	129, 131	235/45		
	Oxigin 28	40	ZP574	129, 131	235/45		

RAV 4 (V) Plug-in-Hybrid	ab 2020	XA5P (EU, M), -/TGRE	5/114,3	60,1	e6*2007/46*0429*..., e13*2007/46*2356*..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC24	38	ZP574	136	225/65, 235/60		

7 x 18	RC27	35	ZP580D8F	136	225/60		
	RC34	35	-	136	225/60, 235/55, 235/60, 245/55		Orig.-Verschr.
7,5 x 18	RC30	35	ZP574	136	225/60, 235/55, 235/60		
	B32	35	ZP574	136	225/60, 235/55, 235/60		
	AC-MB6 / AC-M10	35	Artikel Nr. 98502	136	225/60, 235/55, 235/60		Kit mit Artikelnummer 98502
	CA 20	40	ZP574	136	225/60, 235/55, 235/60, 245/55, 255/50, 255/55		
8 x 18	RC29	35	ZP574	136	225/60, 235/55, 235/60		
	B24	38	ZP574	136	225/60, 235/55, 235/60		
	B38	35	ZP574	136	225/60, 235/55		
	B42	30	ZP574	136	225/60		
	B44	40	ZP574	136	225/60		
7 x 19	RC27	35	-	136	225/55, 235/50, 235/55, 245/45		Orig.-Verschr.
7,5 x 19	RC34	40	-	136	225/55, 235/55, 245/50, 255/50		Orig.-Verschr.
	B32	40	ZP574	136	225/55, 235/50, 235/55		
8 x 19	RC29	38	ZP574	136	225/55, 235/50, 235/55		
	AC-518	40	Artikel Nr. 98502	136	225/55		Kit mit Artikelnummer 98502
	CA 17	40	ZP574	136	225/55, 235/55, 255/45		
	Oxigin 29	40	ZP574	136	225/55		
8,5 x 19	B32 / B37	35	ZP574	136	235/50, 235/55, 255/45		
	B42	35	ZP574	136	235/50, 235/55, 255/45		
7,5 x 20	RC36	35	ZP580D6F	136	235/45, 235/50, 245/45		
	B43	35+40	ZP580D6F	136	235/45, 235/50, 245/45		
8 x 20	RC36	35	-	136	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B38	35	ZP574	136	235/45, 235/50, 245/45, 255/45		
	B40	35	ZP574	136	235/45, 235/50, 245/45, 255/45		
	B43	35	-	136	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
8,5 x 20	B24	35	ZP574	136	235/45, 235/50, 245/45, 255/40, 255/45		
	B32	40	ZP574	136	235/45		
	B42	35	ZP574	136	235/45, 235/50, 245/45, 255/40, 255/45		255/40 nicht zulässig bei 19 Zoll Serie
	B44	30+40	ZP574	136	235/45		
	AC-518	40	Artikel Nr. 98502	136	235/45		Kit mit Artikelnummer 98502
9 x 20	Oxigin 28	40	ZP574	136	235/45		

Supra		ab 2019	JBSC / JTSC	5/112	66,6	e1*2007/46*1982*..., e1*2007/46*1983*..			
Sensor - Brocksens 1									
Dimension	Design	ET	KIT	KW	Reifendimension	Info			
7,5 x 17	RC27	27	-	145-250	225/50, 245/45	Orig.-Verschr., nur M+S			
7,5 x 18	B32	25	-	145-250	225/45	Orig.-Verschr., nur M+S			
8 x 18	B42	30	-	145-250	225/45, 245/40	Orig.-Verschr., nur M+S			
	B44	30	-	145-250	225/45, 245/40	Orig.-Verschr., nur M+S			
	AC-M10	30	-	145-250	225/45, 245/40	Orig.-Verschr., nur M+S			
	CA 23 / CA 26	30	ZP599F	145-250	225/45, 245/40	nur M+S			
	FMI08 Thoe	26	-	145-250	245/40	Orig.-Verschr., nur M+S			
	FMI12 Kari	26	Kit 0334	145-250	245/40	nur M+S			
9 x 18	RC32	32	-	145-250	255/40	Orig.-Verschr.			
8 x 19	B40	30	-	145-250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S			
	B43	28	-	145-250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S			
8,5 x 19	B32	25	-	145, 190	VA 225/40+HA 255/35	Orig.-Verschr.			
				145-250	225/40, 235/35, 245/35	Orig.-Verschr., nur M+S			
	B42	30	-	145, 190	VA 225/40+HA 255/35	Orig.-Verschr.			
				145-250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S			
	B43	25+29	-	145, 190	VA 225/40+HA 255/35	Orig.-Verschr.			
				145-250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S			
	B44	25+30	-	145, 190	VA 225/40+HA 255/35	Orig.-Verschr.			
				145-250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S			
	AC-M10	30	-	145, 190	VA 225/40+HA 255/35	Orig.-Verschr.			
				145-250	225/40, 235/35, 245/35, 255/35	Orig.-Verschr., nur M+S			
	CA 23	30	ZP593F	145, 190	VA 225/40+HA 255/35				
				145-250	225/40, 235/35, 245/35, 255/35	nur M+S			
	Oxigin 28	30	ZP593F	145, 190	VA 225/40+HA 255/35				
				145-250	225/40, 235/35, 245/35, 255/35	nur M+S			
FMI07 Atena	28	F93	145-250	245/35M+S, 255/35	auch Typ JBSC				
			8300 - 1972	21	-	145-250	225/40M+S, 245/35M+S, 255/35	Orig.-Verschr.	
				32	-	145-250	255/35	Orig.-Verschr.	
8 x 20	RC36	27	-	145-250	245/30	Orig.-Verschr., nur M+S			
	B43	27+30	-	145-250	245/30	Orig.-Verschr., nur M+S			
8,5 x 20	RC29	26	-	145-250	245/30, 255/30	Orig.-Verschr., nur M+S			
	B32	30	-	145-250	245/30, 255/30	Orig.-Verschr., nur M+S			
	B42 / B43	30	-	145-250	245/30, 255/30	Orig.-Verschr., nur M+S			
	B44	25+30	-	145-250	245/30, 255/30	Orig.-Verschr., nur M+S			

	AC-M10	30	-	145-250	245/30, 255/30		Orig.-Verschr., nur M+S
--	--------	----	---	---------	----------------	--	-------------------------

Yaris (siehe Konfigurator)	ab 10.11	XP13M (a), XP13N (a)	4/100	54,1	e11*2007/46*0152*..., r11*2007/46*0153*...		
----------------------------	----------	----------------------	-------	------	--	--	--

Yaris Hybrid (siehe Konfigurator)	ab 2012	XP13M (a)	4/100	54,1	e11*2007/46*0152*...		
-----------------------------------	---------	-----------	-------	------	----------------------	--	--

Yaris (IV)	ab 2020	XPA1F (EU,M/N), -/TGRE	5/100	54,1	e6*2007/46*0437*... e13*2007/46*2342*... e13*2018/858*00004*, e20*2018/858*00007*..
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC27	45	-	53, 68, 92	185/65, 195/60, 205/55		Orig.-Verschr.
	RC24	45	ZP580D6F	68, 92	185/65, 195/60, 205/55		nur Bremse 282mm
6 x 16	RC30	50	ZP580D8F	53, 68, 92	185/55, 195/55, 205/50		
	RC34	50	ZP580D6F	53-92	195/55		
				53-92	185/55, 195/50, 195/55, 205/50, 215/50		Serienräder ab 15 Zoll
				68-92	195/50, 195/55		Serienräder ab 16 Zoll
					205/45		auch für Hybrid
6,5 x 17	RC34	50	ZP580D6F	68-92	205/45		
7 x 17	RC27 / RC30	43	ZP510	53, 68, 92	195/45, 205/45		

Yaris GR (IV)	ab 2020	XPA1G (EU,M)	5/114,3	60,1	e6*2007/46*0454*..		
Sensor - Brocksens Universal							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	B38	45	ZP580D6F	192	225/40, 245/35		
	RC29	45	ZP574	192	225/40, 245/35		
	RC32	40	ZP580D6F	192-206	225/40, 235/35, 245/35		
		45	ZP580D6F	192	225/40, 235/35		
	B24	38	ZP574	192	225/40, 235/40, 245/35		
	B36	35	ZP574	192	225/40		
	B37	45	ZP574	192	225/40, 245/35		
		35	ZP574	192	225/40		
	B42	40	ZP574	192	225/40, 235/40, 245/35		
	B44	40	ZP574	192	225/40, 235/40, 245/35		
		45	ZP574	192	225/40, 235/40, 245/35		
	AC-518	40	ZP580D6F+ R	192	225/40, 245/35		+ Red. Ringe 73,1-60,1
8,5 x 18	AC-M10	45	ZP580D6F+ R	192	225/40, 235/40, 245/35		+ Red. Ringe 73,1-60,1
	CA 24	45	ZP574	192-206	225/40		
	B32	35	ZP574	192	225/40		
8 x 19	RC29	38	ZP574	192	225/35, 245/30		
	B38	38+45	ZP574	192	225/35, 245/30		
	AC-518	40	ZP580D6F+ R	192	225/35, 245/30		+ Red. Ringe 73,1-60,1
	CA 19	45	ZP574	192	225/35, 245/30		
	CA 24	45	ZP574	192	225/35		
	Oxigin 29	40	ZP574	192	225/35, 245/30		
	B32	45	ZP574	192	225/35, 235/30, 245/30, 255/30		
8,5 x 19	B36	38	ZP574	192	225/35, 235/30		
	B37	45	ZP574	192	225/35, 235/30, 245/30, 255/30		
	B42	35	ZP574	192	225/35		
	B44	40	ZP574	192	225/35, 235/30, 245/30		
	CA 20	45	ZP574	192	225/35, 235/30, 245/30, 255/30		
	CA 23	40	ZP574	192	225/35, 235/30, 245/30		
	Oxigin 28	45	ZP574	192	225/35, 235/30, 245/30, 255/30		
8 x 20	RC36	35	-	192, 206	225/30		Orig.-Verschr.
	B38	45	ZP574	192	225/30		
	B40	30	ZP580D6F	192	225/30		
		35	ZP574	192	225/30		
	B43	35	-	192, 206	225/30		Orig.-Verschr.

Yaris Cross	ab 2021	XPB1F (M,EUM), -/TGRE	5/114,3	60,1	e6*2018/858*00013*..., e13*2018/858*00156*..		
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC32	45	ZP580D6F	68-92	205/65, 215/60, 225/60, 235/55		
	RC34	45	-	68-92	205/65, 215/60, 225/60, 235/55		Orig.-Verschr., Felge ist nur in SGVP erhältlich!!!
	RC24	44	ZP574	68, 95	205/65, 215/60, 225/55, 225/60		
	RC27	45	ZP574	68, 92	205/65, 215/60, 225/55, 225/60		
	RC30	45	ZP574	68, 92	205/65, 215/60, 225/55, 225/60		
	CA 20	45	ZP574	68, 92	205/65, 215/60, 225/55, 225/60		
7 x 16	RC30	40	ZP580D6F	68, 92	205/65, 215/60		
6,5 x 17	RC27	35	-	68, 92	205/60, 215/55		Orig.-Verschr.
		40+45	ZP580D6F	68, 92	205/55, 215/55, 225/50, 235/50		ET40 bei 235/50 ✖

7 x 17	RC34	45	ZP580D6F	68-92	205/60, 215/55, 225/50, 235/50		
	RC34	50	-	68-92	205/60, 215/55 , 225/50, 235/50		Orig.-Verschr.
	RC27	45	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
	RC30	45	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
	CA 26	45	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
7,5 x 17	RC24 / RC28	45	ZP574	68, 92	205/55, 215/55, 225/50		
	RC29	48	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
	RC32	40	ZP580D6F	68-92	205/60		
		45	ZP580D6F	68-92	205/60, 215/55		
	RC34	40	ZP580D6F	68-92	205/60		
	B24	38	ZP574	68, 92	205/55		
		48	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
	B36	46	ZP574	68, 92	205/55, 215/55, 225/50		
	CA 20	48	ZP574	68, 92	205/55, 215/55, 225/50, 235/50		
7 x 18	RC27	50	ZP580D6F	68, 92	215/50 , 225/45		
	RC32	50	ZP580D6F	68-92	215/50 , 225/45		
	RC34	50	-	68-92	215/50		Orig.-Verschr.
		45	-	68-92	215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC32	45	ZP580D6F	68-92	215/50, 225/45, 235/45		
	B32	45	ZP574	68, 92	215/50, 225/45, 235/45		
	B39	45	ZP574	68, 92	215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	45	Artikel Nr. 98502	68, 92	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	AC-521	45	Artikel Nr. 98502	68, 92	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	CA 20	40	ZP574	68-92	225/45		
8 x 18	RC32	45	ZP580D6F	68-92	215/50, 225/45, 235/45		
	B36 / B37	45	ZP574	68, 92	215/50, 225/45, 235/45		
	B38	49	ZP574	68, 92	215/50, 225/45, 235/45, 245/40		
	B42 / B44	45	ZP574	68, 92	215/50, 225/45, 235/45		
	AC-M10	45	Artikel Nr. 98502	68, 92	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	CA 20 / CA 23	45	ZP574	68, 92	215/50, 225/45, 235/45		
7,5 x 19	CA 24	45	ZP574	68-92	225/45		
	RC34	40	-	68-92	225/40		Orig.-Verschr.
	AC-521	45	Artikel Nr. 98502	68, 92	225/40		Kit mit Artikelnummer 98502
8 x 19	RC29	48	ZP574	68, 92	225/40, 235/40, 245/35		
	B38	45	ZP574	68, 92	225/40, 235/40		
	CA 19	45	ZP574	68, 92	225/40, 235/40		
	CA 24	45	ZP574	68	225/40		
	Oxigin 29	40	ZP574	68, 92	225/40		
50		ZP574	68, 92	225/40, 235/40, 245/35			
8,5 x 19	B36	44	ZP574	68, 92	225/40		
	B37 / B42	45	ZP574	68, 92	225/40, 235/40		
	CA 20	45	ZP574	68, 92	225/40, 235/40		
	CA 26	46	ZP574	68, 92	225/40, 235/40		
	Oxigin 28	45	ZP574	68, 92	225/40, 235/40		
8 x 20	B38	45	ZP574	68, 92	225/35, 235/35		
8,5 x 20	RC29	45	ZP574	68, 92	225/35, 235/35		
	B42	45	ZP574	68, 92	225/35, 235/35		

Yaris Cross AWD NEU		XPB1F (M,EUM), -/TGRE			5/114,3	60,1	e6*2018/858*00013*... e13*2018/858*00156*..	
Sensor - Brocksens Universal od. HUF ECR220 - Artikelnummer 97818								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 16	RC24	44	ZP574	68	205/65, 215/60, 225/55, 225/60			
	RC27	45	ZP574	68	205/65, 215/60, 225/55, 225/60			
	RC30	45	ZP574	68	205/65, 215/60, 225/55, 225/60			
	CA 20	45	ZP574	68	205/65, 215/60, 225/55, 225/60			
7 x 16	RC30	40	ZP580D6F	68	205/65, 215/60			
6,5 x 17	RC27	35	-	68	205/55, 205/60, 215/55		Orig.-Verschr.	
		40+45	ZP580D6F	68	205/55, 205/60, 215/55, 225/50, 235/50		ET40 bei 235/50 ✖	
7 x 17	RC27	45	ZP574	68	205/55, 205/60, 215/55, 225/50, 235/50			
	RC30	45	ZP574	68	205/55, 205/60, 215/55, 225/50, 235/50			
	CA 26	45	ZP574	68	205/55, 205/60, 215/55, 225/50, 235/50			
7,5 x 17	RC24 / RC28	45	ZP574	68	205/55, 205/60, 215/55, 225/50			
	RC29	48	ZP574	68	205/55, 205/60, 215/55, 225/50			
	B24	38	ZP574	68	205/55, 205/60			
		48	ZP574	68	205/55, 205/60, 215/55, 225/50			
	B36	46	ZP574	68	205/55, 205/60, 215/55, 225/50			
	CA 20	48	ZP574	68	205/55, 205/60, 215/55, 225/50			
7 x 18	RC27	50	ZP580D6F	68	215/50, 225/45			
	B32	45	ZP574	68	215/50, 225/45, 235/45			

7,5 x 18	B39	45	ZP574	68	215/50, 225/45, 235/45		
	AC-MB6 / AC-M10	45	Artikel Nr. 98502	68	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	AC-521	45	Artikel Nr. 98502	68	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
8 x 18	B36 / B42	45	ZP574	68	215/50, 225/45, 235/45		
	B44	45	ZP574	68	215/50, 225/45, 235/45		
	AC-M10	45	Artikel Nr. 98502	68	215/50, 225/45, 235/45		Kit mit Artikelnummer 98502
	CA 20 / CA 23	45	ZP574	68	215/50, 225/45, 235/45		
	CA 24	45	ZP574	68	225/45		
7,5 x 19	AC-521	45	Artikel Nr. 98502	68	225/40		Kit mit Artikelnummer 98502
8 x 19	RC29	48	ZP574	68	225/40, 235/40, 245/35, 245/40		
	B38	45	ZP574	68	225/40, 235/40		
	CA 19	45	ZP574	68	225/40, 235/40		
	CA 24	45	ZP574	68	225/40		
	Oxigin 29	40	ZP574	68	225/40		
		50	ZP574	68	225/40, 235/40		
8,5 x 19	B42	45	ZP574	68	225/40, 235/40		
	CA 20	45	ZP574	68	225/40, 235/40		
	CA 26	46	ZP574	68	225/40, 235/40		
	Oxigin 28	45	ZP574	68	225/40, 235/40		
8 x 20	B38	45	ZP574	68	225/35, 235/35		
8,5 x 20	RC29	45	ZP574	68	225/35, 235/35		
	B42	45	ZP574	68	225/35, 235/35		

Volvo		Baujahr	Typ	LK/LZ	Nabe		
C40 elektro NEU		ab Jänner 2022		X	5/108	63,4	e9*2007/46*3146*13-15
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 19	B32	45	ZP531	80, 160	VA 235/50+HA 255/45		
		45	-	80, 160	VA 235/50+HA 255/45		Orig.-Verschr.
	B43	45	-	80, 160	VA 235/50+HA 255/45		Orig.-Verschr.
	CA 20	45	ZP569F	80, 160	VA 235/50+HA 255/45		
	CA 23	45	ZP531	160 (300)	VA 235/50+HA 255/45		
8 x 20 9 x 20	B40	VA 50,5 HA 58,5	-	80, 160	VA 235/45 u. HA 255/40		 Orig.-Verschr.
8 x 20 9 x 20	B43	VA 50,5 HA 58,5	-	80, 160	VA 235/45 u. HA 255/40		 Orig.-Verschr.
8 x 20 9 x 20	B43	VA 50,5 HA 58,5	-	80, 160	VA 235/45, 245/40		 Orig.-Verschr.
			HA 255/40, 265/40, 275/35				
8 x 20 9 x 20			VA 50 HA 53	-	160 (300)	VA 235/45 u. HA 255/40	
8,5 x 20	RC29	45	-	160 (300)	VA 235/45+HA 255/40		Orig.-Verschr.
	RC36	45+47,5	-	80, 160	VA 235/45+HA 255/40		Orig.-Verschr.
	B42	45	-	80, 160	VA 235/45+HA 255/40		Orig.-Verschr.
	B43	45	-	160 (300)	VA 235/45+HA 255/40		Orig.-Verschr.
		47,5	-	80, 160	VA 235/45+HA 255/40		Orig.-Verschr.

C40 elektro NEU		ab Modell 2023			X	5/108	63,4	e9*2007/46*3146*16-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 19	RC32	VA 50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.		
8,5 x 19		HA 56							
7,5 x 19	RC34	VA 50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.		
8,5 x 19		HA 56							
8,5 x 19	B32	45	ZP531	120-128	VA 235/50+HA 255/45		Heckantrieb		
				183	VA 235/50+HA 255/45		Allrad		
		45	-	120-128	VA 235/50+HA 255/45		Orig.-Verschr., Heckantrieb		
				183	VA 235/50+HA 255/45		Orig.-Verschr., Allrad		
	B43	45	-	120-128	VA 235/50+HA 255/45		Orig.-Verschr., Heckantrieb		
				183	VA 235/50+HA 255/45		Orig.-Verschr., Allrad		
	CA 20	45	ZP569F	101-128	VA 235/50+HA 255/45		Heckantrieb		
				183	VA 235/50+HA 255/45		Allrad		
8 x 20	B40	VA 50,5	-	120-128	VA 235/45, 245/40		Orig.-Verschr., Heckantrieb		
183				VA 235/45, 245/40	Orig.-Verschr., Allrad				
9 x 20		HA 58,5		120-128	HA 255/40, 265/40, 275/35		Orig.-Verschr., Heckantrieb		
				183	HA 255/40, 265/40, 275/35		Orig.-Verschr., Allrad		
8 x 20	B43	VA 50,5	-	101-128	VA 235/45, 245/40		Orig.-Verschr., Heckantrieb		
183				VA 235/45, 245/40	Orig.-Verschr., Allrad				
9 x 20		HA 58,5		101-128	HA 255/40, 265/40, 275/35		Orig.-Verschr., Heckantrieb		
				183	HA 255/40, 265/40, 275/35		Orig.-Verschr., Allrad		
8,5 x 20	RC36	45+47,5	-	101-128	VA 235/45+HA 255/40		Orig.-Verschr., Heckantrieb		
				183	VA 235/45+HA 255/40		Orig.-Verschr., Allrad		
	B42	45	-	120-128	VA 235/45+HA 255/40		Orig.-Verschr., Heckantrieb		
				183	VA 235/45+HA 255/40		Orig.-Verschr., Allrad		
	B43	47,5	-	101-128	VA 235/45+HA 255/40		Orig.-Verschr., Heckantrieb		
				183	VA 235/45+HA 255/40		Orig.-Verschr., Allrad		

EC40 elektro NEU		ab Modell 2023			X	5/108	63,4	e9*2007/46*3146*16-..	
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7,5 x 19	RC32	VA 50,5	-	80-183	VA 235/50 + HA 255/45				Orig.-Verschr.
8,5 x 19		HA 56							
7,5 x 19	RC34	VA 50,5	-	80-183	VA 235/50 + HA 255/45				Orig.-Verschr.
8,5 x 19		HA 56							
8,5 x 19	CA 20	45	ZP569F	101-128	VA 235/50+HA 255/45				Heckantrieb
				183	VA 235/50+HA 255/45				Allrad
8 x 20	B43	VA 50,5	-	101-128	VA 235/45, 245/40				Orig.-Verschr., Heckantrieb
				183	VA 235/45, 245/40				Orig.-Verschr., Allrad
9 x 20		HA 58,5		101-128	HA 255/40, 265/40, 275/35				Orig.-Verschr., Heckantrieb
				183	HA 255/40, 265/40, 275/35				Orig.-Verschr., Allrad
8,5 x 20	RC36	45+47,5	-	101-128	VA 235/45+HA 255/40				Orig.-Verschr., Heckantrieb
				183	VA 235/45+HA 255/40				Orig.-Verschr., Allrad
	B43	47,5	-	101-128	VA 235/45+HA 255/40				Orig.-Verschr., Heckantrieb
				183	VA 235/45+HA 255/40				Orig.-Verschr., Allrad

Kombinationen

8 x 19	RC34	45	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.
9 x 19		45	-	80-183			

EX30 NEU		ab 2024		2	5/108	63,4	e9*2018/858*11478*..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 18	RC30	46	- (X8)	75, 116	225/55, 235/50, 245/50		Orig.-Verschr., Ausführung X8	
	RC34	46	- (X8)	75-116	225/55		Orig.-Verschr., Ausführung X8	
				75-116	225/55, 235/50			
	RC30	46	- (X4)	75, 116	225/55, 235/50, 245/50		Orig.-Verschr., Ausführung X4 = kein ECE	
	RC32	45	-	75-116	225/55, 235/50		Orig.-Verschr.	
	RC34	45	ZP561F	75-116	225/55, 235/50			
	B32	50	ZP561F	75, 116	225/55, 235/50			
8 x 18	AC-MB6	42	ZP569F+R	75, 116	225/55, 235/50		+ Red.Ringe 73,1-63,4	
	AC-M10	42	ZP569F+R	75, 116	225/55, 235/50		+ Red.Ringe 73,1-63,4	
8 x 18	RC27	45	-	75, 116	225/55, 235/50, 255/45		Orig.-Verschr.	
	RC34	45	ZP561F	75-116	225/55			
	B36	45	ZP531	75, 116	225/55, 235/50, 255/45			
	B42	42	ZP531	75, 116	225/55			
	B44	42	ZP531	75, 116	225/55			
8 x 19	RC27	48,5	- (X8)	75, 116	225/45, 225/50, 235/45, 245/45		Orig.-Verschr., Ausführung X8	
	RC34	48,5	- (X8)	75-116	225/50, 235/45, 245/45		Orig.-Verschr., Ausführung X8	
	RC32	45	-	75-116	225/50, 235/45, 245/45		Orig.-Verschr.	
	B43	47,5	ZP561F	75, 116	225/45, 225/50, 235/45, 245/45			
8,5 x 19	B32	45	-	75, 116	225/45, 235/45, 245/45		Orig.-Verschr.	
	B36	44	ZP531	75, 116	225/45, 235/45, 245/45		nicht Bremse 345mm	
	B43	45	ZP561F	75, 116	225/45, 235/45, 245/45			
	B44	42	ZP561F	75, 116	225/45, 235/45			
8 x 20	RC36	48,5	-	75, 116	225/40, 235/40, 245/40		Orig.-Verschr.	
	B43	48,5	ZP561F	75, 116	225/40, 235/40, 245/40			
	RC36	47,5	-	75, 116	225/40, 235/40, 245/40		Orig.-Verschr.	
	B43	50,5	ZP561F	75, 116	225/40, 235/40, 245/40			
8,5 x 20	RC36	45	-	75-116	225/40, 235/40, 245/40		Orig.-Verschr.	
	B41	45	-	75-116	235/40		Orig.-Verschr.	
8,5 x 21	B43	49,5	ZP561F	75, 116	245/35			

EX40 NEU		ab 2024		X	5/108	63,4	e9*2007/46*3146*16-..	
Sensor - Brocksens 8								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7,5 x 19	RC32	VA 50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.	
8,5 x 19		HA 56						
7,5 x 19	RC34	VA 50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.	
8,5 x 19		HA 56						
8,5 x 19	CA 20	45	ZP569F	101-128	VA 235/50+HA 255/45		Heckantrieb	
				183	VA 235/50+HA 255/45		Allrad	
8,5 x 20	RC36	45+47,5	-	101-128	VA 235/45+HA 255/40		Orig.-Verschr., Heckantrieb	
				183	VA 235/45+HA 255/40		Orig.-Verschr., Allrad	

Kombinationen

8 x 19	RC34	VA 50	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.
9 x 19		HA 53					
8 x 20	B43	VA 50,5	-	101-128	VA 235/45, 245/40		Orig.-Verschr., Heckantrieb
				183	VA 235/45, 245/40		Orig.-Verschr., Allrad
9 x 20		HA 58,5		101-128	HA 255/40, 265/40, 275/35		Orig.-Verschr., Heckantrieb
				183	HA 255/40, 265/40, 275/35		Orig.-Verschr., Allrad

EX90 NEU		ab 2024		T		5/120		63,4		e4*2018/858*00203*..	
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321											
Dimension	Design	ET	KIT	KW		Reifendimension			Info		
8,5 x 20	RC36	VA 40,5	-			VA 255/50			Orig.-Verschr., Lieferzeit im Laufe Juli		
9,5 x 20		HA 39				HA 285/45					
9 x 21	B43	VA 38,5	-			VA 265/45			Orig.-Verschr., i.V.		
10 x 21		HA 44,5				HA 295/40					

Polestar 2		ab 2020		V	5/108	63,4	e9*2007/46*6834*...., e9*2018/858*11085*00-03	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC34	VA 50	-	80-192	VA+HA 245/45		Orig.-Verschr., nicht Bremse 375x35mm	
9 x 19		HA 53						
8 x 19	RC36	VA 50	-		VA+HA 245/45		Orig.-Verschr., i.V., in Planung	
9 x 19		HA 53						
8 x 19	B40	VA 50	-	160 (300)	VA+HA 245/45		Orig.-Verschr., nicht Bremse 375mm	
9 x 19		HA 53						
8 x 19	RC32	45	-	80-192	245/45		Orig.-Verschr.	
		45	-	80-160	245/45		Orig.-Verschr.	
	RC34	48,5	-(X8)	80-192	245/45		Orig.-Verschr., Ausführung X8 , nicht Bremse	

		70,5	(P5)	80-160	245/45		375x35mm
8,5 x 19	B32	45	ZP531	80, 160	245/45		nicht Bremse 375mm
			ZP569F	80, 160	245/45		nicht Bremse 375mm
	B36	44	ZP531	80, 160	245/45		nicht Bremse 375mm
	B43	45	-	80, 160	245/45		Orig.-Verschr., nicht Bremse 375mm
	CA 23	45	ZP531	80, 160	245/45		nicht Bremse 375mm
8 x 20	B40	VA 41	-	80, 160	VA+HA 245/40		Orig.-Verschr.
9 x 20		HA 46					
8 x 20	RC36	VA 50	-		VA+HA 245/40		Orig.-Verschr., i.V., in Planung
9 x 20		HA 53					
8 x 20	B43	VA 50	-	80, 160	VA+HA 245/40		Orig.-Verschr., nicht Bremse 375 mm
9 x 20		HA 53					
8,5 x 20	RC34	45	-	160	245/40, 255/35		Orig.-Verschr., nicht Bremse 375x35mm ✖
		45	-	80, 160	245/40		Orig.-Verschr.
	RC36	47,5	-	80, 160	245/40		Orig.-Verschr., ET47,5 nicht Bremse 375mm
		45	ZP569F	80, 160	245/40		nicht Bremse 375mm
	B43	45	-	80, 160	245/40		Orig.-Verschr.
9 x 20	B37	48	ZP569F	80, 160	245/40		nicht Bremse 375mm
8,5 x 21	B43	49,5	-	80, 160	245/35		Orig.-Verschr., nicht Bremse 375mm

Polestar 2 Performance	ab 2020	V	5/108	63,4
Sensor - Brocksens Universal				

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

Kombinationen

8 x 20	B40	VA 41	-	300	VA+HA 245/40		Orig.-Verschr.
9 x 20		HA 46					

Polestar 2 NEU	ab Modelljahr 2024	V	5/108	63,4	e9*2018/858*11085*04-..
Sensor - Brocksens Universal					

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
-----------	--------	----	-----	----	-----------------	------	--

Kombinationen

8 x 19	RC34	VA 50	-		VA 245/45		Orig.-Verschr.
9 x 19		HA 53			HA 245/45		
8 x 19	B40	VA 50	-	192	VA 245/45		Orig.-Verschr., nicht Bremse 375mm, Allrad
				141	VA 245/45		Orig.-Verschr., nicht Bremse 375mm, Heckantr.
9 x 19		HA 53	-	192	HA 245/45		Orig.-Verschr., nicht Bremse 375mm, Allrad
				141	HA 245/45		Orig.-Verschr., nicht Bremse 375mm, Heckantr.
8,5 x 19	B32	45	ZP531	192	245/45		nicht Bremse 375mm, Allrad
				141	245/45		nicht Bremse 375mm, Heckantrieb
		45	ZP569F	192	245/45		nicht Bremse 375mm, Allrad
				141	245/45		nicht Bremse 375mm, Heckantrieb
	B43	45	-	192	245/45		Orig.-Verschr., nicht Bremse 375mm, Allrad
				141	245/45		Orig.-Verschr., nicht Bremse 375mm, Heckantr.
	CA 20	45	ZP569F	192	245/45		Orig.-Verschr., nicht Bremse 375mm, Allrad
				109-141	245/45		Orig.-Verschr., nicht Bremse 375mm, Heckantr.
8,5 x 20	RC36	45	-	192	245/40		Orig.-Verschr., Allrad
				109-141	245/40		Orig.-Verschr., Heckantrieb
	B42	45	ZP569F	192	245/40		nicht Bremse 375mm, Allrad
				141	245/40		nicht Bremse 375mm, Heckantrieb
	B43	47,5	-	192	245/40		Orig.-Verschr., nicht Bremse 375mm, Allrad
				109-141	245/40		Orig.-Verschr., nicht Bremse 375mm, Heckantr.
8,5 x 21	B43	49,5	-	192	245/35		Orig.-Verschr., nicht Bremse 375mm, Allrad
				109-141	245/35		Orig.-Verschr., nicht Bremse 375mm, Heckantr.

Polestar 3 NEU		4.Quartal 2023		Y	5/120	63,4	e9*2018/858*11452*..
Sensor - Brocksens Universal							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 20	RC36	VA 40,5	-		VA 255/50		Orig.-Verschr., in Planung
9,5 x 20		HA 39			HA 285/45		
9 x 21	B43	VA 38,5	-	132-252	VA 265/45		Orig.-Verschr., nur Bremse 400mm
10 x 21		HA 44,5			HA 295/40		

Polestar 4 NEU		2024		4	5/108	63,4	e9*2018/858*11568*..
-------------------------------	--	------	--	---	-------	------	----------------------

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8,5 x 20	B43	47,5	-	75, 150	255/50, 265/45, 275/45		Orig.-Verschr., nicht Brembo Bremse
	RC36	47,5	-	75, 150	255/50, 265/45, 275/45		Orig.-Verschr., nicht Brembo Bremse
		45	-	75, 150	255/50, 265/45, 275/45		Orig.-Verschr., nicht Brembo Bremse
9,5 x 21	B43	45	-	75, 150	255/45		Orig.-Verschr., nicht Brembo Bremse
			-	75	285/40		Orig.-Verschr., nicht Brembo Bremse
				75, 150	255/45, 265/40, 265/45		

V40 (siehe Konfigurator)	ab 2012	M / M-N2E	5/108	63,4	e4*2001/116*0076*27-..., e13*2007/46*1337*...
---------------------------------	----------------	------------------	--------------	-------------	---

V40 CC (Cross Country) (siehe Konfigurator)	ab 2013	M / M-N2E	5/108	63,4	e4*2001/116*0076*29..., e13*2007/46*1337*...
--	----------------	------------------	--------------	-------------	--

S60, V60 (siehe Konfigurator)	ab 07.10	F / F-N2D	5/108	63,4	e9*2007/46*0023*..., e13*2007/46*1157*...
--------------------------------------	-----------------	------------------	--------------	-------------	---

S60CC / V60CC Cross Country (siehe Konfigurator)	ab 2010	F	5/108	63,4	e9*2007/46*0023*...
---	----------------	----------	--------------	-------------	---------------------

V60	ab 2018	Z	5/108	63,4	e4*2007/46*1315*..
------------	----------------	----------	--------------	-------------	--------------------

Sensor - Brocksens Universal

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7 x 16	RC30	37	-	110-147	215/60, 225/55	 Orig.-Verschr., nur Bremse 296mm
7 x 17	RC30	40,5	-	110-184	225/50	 Orig.-Verschr.
		40,5	ZP569F	110-147	215/55	 nicht Bremse ab 345mm
				110-186	225/50	
		40,5	-	110-186	215/50, 215/55, 225/50 , 225/55, 235/50	 Orig.-Verschr.
	RC32	40,5	-	110-186	225/50	 Orig.-Verschr.
	RC34	40,5	-	110-186	225/50	 Orig.-Verschr.
7,5 x 17	Pro1	45	-	110-186	215/50, 215/55, 225/50, 225/55, 235/50	Orig.-Verschr.
	RC34	45	-	110-186	215/50, 215/55, 225/50, 225/55	Orig.-Verschr., nur Bremse 296mm
7,5 x 18	RC32	45	-	110-233	215/45, 215/50, 225/45, 225/50, 235/45	Orig.-Verschr.
	RC34	45	-	110-233	215/45, 215/50, 225/45, 225/50, 235/45, 245/45	Orig.-Verschr.
		46	-	110-233	215/45, 215/50, 225/45, 235/45, 245/45	Orig.-Verschr.
	AC-MB6 / AC-M10	42	ZP569F+R	110-147	215/50	 + Red.Ringe 73,1-63,4
				110-186	225/45, 235/45	
	AC-521	42	ZP569F+R	110-147	215/50	 + Red.Ringe 73,1-63,4
				110-186	225/45, 235/45	
8 x 18	RC27	42	-	140-228	235/45	 Orig.-Verschr.
	RC32	42	-	110-240	215/45, 225/45, 225/50, 235/40, 235/45	 Orig.-Verschr.
	RC34	42	-	110-240	215/45, 225/45, 225/50, 235/40, 235/45 , 245/40, 245/45	 Orig.-Verschr.
	RC27	42,5	-	140-228	235/40, 235/45	Orig.-Verschr.
		45	-	110-240	215/45, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr.
	RC32	45	-	110-240	215/45, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr.
	RC34	45	-	110-240	215/45, 225/45, 235/40, 235/45, 245/40, 245/45	Orig.-Verschr.
	B42 / B44	42	ZP531	110-186	225/45	
				110-240	235/45	
	AC-MB6	42	ZP569F+R	110-186	225/45	 + Red.Ringe 73,1-63,4
				110-240	235/45	
7,5 x 19	B32	44,5	ZP569F	110-186	225/40	
	AC-521	42	ZP569F+R	110-186	225/40	 + Red.Ringe 73,1-63,4
	CA 26	45	ZP531	110-186	225/40	
8 x 19	RC27	42,5	-	110-240	235/40	 Orig.-Verschr.
	RC32	42	-	110-240	235/40	 Orig.-Verschr.
	RC34	42	-	110-240	225/40, 225/45, 235/35, 235/40 , 245/35	 Orig.-Verschr.
	RC27	45	-	110-228	235/40	Orig.-Verschr., nicht Brembo od. Bremse 296mm
	RC29	42,5	ZP531	110-240	235/40, 245/40	
		45	ZP531	110-240	235/40, 245/40	
	RC34	45	-	110-240	225/40, 225/45, 235/35, 235/40, 245/35	Orig.-Verschr.
	B24	45	ZP531	110-240	235/40, 245/40	
	B38	45	ZP531	110-240	235/40, 245/40	
	B40	45	ZP569F	110-186	225/40	
				110-240	235/40, 245/40	
	B43	42	ZP569F	110-186	225/40	
				110-240	235/40, 245/40	
	AC-518	45	ZP569F+R	110-240	235/40, 245/40	 + Red.Ringe 73,1-63,4
	Oxigin 29	45	ZP531	110-186	225/40	
				110-240	235/40, 245/40	
8,5 x 19	B41	42	-	110-240	225/40, 235/35, 235/40	Orig.-Verschr.
8 x 20	B43	45,5	-	110-240	245/35	 Orig.-Verschr.
				110-186	225/35	 Orig.-Verschr.
				110-240	235/35, 245/30, 245/35	
	B38	45	-	110-240	235/35, 245/30, 245/35	Orig.-Verschr.
	B40	45	-	110-240	235/35, 245/30, 245/35	Orig.-Verschr.
	B43	40	-	110-186	225/35	Orig.-Verschr.
				110-240	235/35, 245/30, 245/35	
				110-186	225/35	
8,5 x 20	AC-521	43	ZP569F+R	110-186	225/35	 + Red.Ringe 73,1-63,4
				110-240	235/35, 245/30, 245/35	
				110-240	235/35, 245/30, 245/35	
8,5 x 20	RC34	45	-	110-240	225/35	Orig.-Verschr.
	B41	45	-	110-240	225/35	Orig.-Verschr.

V60 Cross Country	ab 2018	Z	5/108	63,4	e4*2007/46*1315*..
--------------------------	----------------	----------	--------------	-------------	--------------------

Sensor - Brocksens Universal

Dimension	Design	ET	KIT	KW	Reifendimension	Info
	RC30	50,5	-	110-186	215/55	 Orig.-Verschr.

7,5 x 18	B32	50	-	110-186	215/55, 225/50, 225/55, 245/45		Orig.-Verschr. nicht Bremse 345 mm
	B39	45	ZP531	110-186	215/55		
8 x 18	RC27	55	-	110-186	225/50, 225/55, 245/45		Orig.-Verschr.
	AC-518	50	ZP569F+R	110-147	215/55, 225/50, 225/55, 245/45		+ Red.Ringe 73,1-63,4, nicht Bremse ab 345mm
7,5 x 19	B32	44,5	ZP569F	110-186	225/45, 235/45		
		50,5+55	ZP569F	110-186	225/45, 235/45, 245/45		
	AC-521	42	ZP569F+R	110-186	225/45		+ Red.Ringe 73,1-63,4
	CA 26	45	ZP531	110-186	225/45, 235/45		
8 x 19	RC27	55	-	110-186	235/45		Orig.-Verschr.
	B43	55	-	1180-186	225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
	B40	45	ZP569F	110-186	225/45		
		50	-	110-186	225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
	B43	47,5	ZP569F	110-186	225/45, 235/45		
	Oxigin 29	45	ZP531	110-186	225/45		
8 x 20	B43	55	-	110-186	215/45, 225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
	RC36	48,5	-	110-186	215/45, 225/40		Orig.-Verschr.
	B38	45	-	110-186	215/45, 225/40		Orig.-Verschr.
	B40	45	-	110-186	215/45, 225/40		Orig.-Verschr.
		52,5	-	110-186	215/45, 225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
	B43	45,5	-	110-186	215/45, 225/40		Orig.-Verschr.
		50+50,5	-	110-186	215/45, 225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
		52	-	110-186	215/45, 225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
	AC-521	43	ZP569F+R	110-186	215/45, 225/40		+ Red.Ringe 73,1-63,4
8,5 x 20	RC29	52	ZP569F	110-186	225/40, 235/40		

S60, V60 Twin Engine Hybrid T6/T8							
ab 2019				Z	5/108	63,4	e4*2007/46*1315*..
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 18	B32 / B39	45	ZP531	186-233	235/45		nur M+S, nur Bremse 345mm
	AC-MB6	42	ZP569F+R	186-233	235/45M+S		+ Red.Ringe 73,1-63,4, nur Bremse 345mm
	AC-M10	42	ZP569F+R	186-233	235/45M+S		+ Red.Ringe 73,1-63,4, nur Bremse 345mm
	AC-521	42	ZP569F+R	186-233	235/45		+ Red.Ringe 73,1-63,4, nur Bremse 345mm
8 x 18	RC27	42	-	186-233	235/45		Orig.-Verschr., nur Bremse 345mm
	B42 / B44	42	ZP531	186-233	235/45		nur Bremse 345mm
	AC-MB6	42	ZP569F+R	186-233	235/45		+ Red.Ringe 73,1-63,4, nur Bremse 345mm
8 x 19	RC27	42,5	-	186-233	235/40		Orig.-Verschr., nicht Bremse 370mm
	B43	42	-	186-233	235/40		Orig.-Verschr., nicht Bremse 370mm
	RC29	45	ZP531	186-233	235/40, 245/40		nur Bremse 345mm
	B24	45	ZP531	186-233	235/40, 245/40		nicht Bremse 370mm
	B40	45	ZP569F	186-233	235/40, 245/40		nicht Bremse 370mm
	B43	42	-	186-233	235/40, 245/40		Orig.-Verschr., nicht Bremse 370mm
	AC-518	45	ZP569F+R	186-233	235/40, 245/40		+ Red.Ringe 73,1-63,4, nur Bremse 345mm
	Oxigin 29	45	ZP531	186-233	235/40, 245/40		nicht Bremse 370mm
8 x 20	B40	45	-	186-233	245/35		Orig.-Verschr., nicht Bremse 370mm
	B43	45,5	-	186-233	245/35		Orig.-Verschr., nicht Bremse 370mm
	B38	45	-	186-233	245/35		Orig.-Verschr., nicht Bremse 370mm
	B43	40	-	186-233	245/35		Orig.-Verschr., nicht Bremse 370mm
	AC-521	43	ZP569F+R	186-233	245/35		+ Red.Ringe 73,1-63,4

S60		ab 2019		Z	5/108	63,4	e4*2007/46*1315*05-..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
7 x 16	RC30	37	-	120-145	215/60		Orig.-Verschr.	
			ZP569F	120-145	215/60, 225/55		nur Bremse max. 296mm	
7 x 17	RC34	40,5	ZP569F	120-186	225/50			
	RC30	40,5	ZP569F	120-145	215/55		nicht Bremse ab 345mm	
120-186				225/50				
7,5 x 18	B32	45	ZP531	120-145	215/50		nicht Bremse ab 345mm	
				120-186	225/45, 235/45			
	B39	45	ZP531	140-186	225/45, 235/45			
				120-145	215/50			
	AC-MB6 / AC-M10	42	ZP569F+R	120-186	225/45, 235/45		+ Red.Ringe 73,1-63,4	
				120-145	215/50			
AC-521	42	ZP569F+R	120-186	225/45, 235/45		+ Red.Ringe 73,1-63,4		
8 x 18	RC27	42	-	120-240	235/45		Orig.-Verschr.	
	RC25	42,5	ZP569F	140-240	235/45			
	B42 / B44	42	ZP531	120-186	225/45			
				120-240	235/45			
	AC-MB6	42	ZP569F+R	120-186	225/45		+ Red.Ringe 73,1-63,4	
				120-240	235/45			
7,5 x 19	B32	44,5	ZP569F	120-186	225/40			
	AC-521	42	ZP569F+R	120-186	225/40		+ Red.Ringe 73,1-63,4	
	CA 26	45	ZP531	120-186	225/40			

8 x 19	RC27	42,5	-	120-240	235/40		Orig.-Verschr.
	B43	42	-	110-240	235/40		Orig.-Verschr.
	RC29	42,5	ZP569F	140-240	235/40, 245/40		
		45	ZP531	120-240	235/40, 245/40		
	B40	45	ZP569F	120-186	225/40		
				120-240	235/40, 245/40		
	B43	42	ZP569F	120-186	225/40		
				120-240	235/40, 245/40		
8 x 20	AC-518	45	ZP569F+R	140-240	235/40, 245/40		+ Red.Ringe 73,1-63,4
	Oxigin 29	45	ZP531	120-186	225/40		
				120-240	235/40, 245/40		
	B40	45	-	120-240	235/35, 245/30, 245/35		Orig.-Verschr.
				120-186	225/35		
	B43	45,5	-	120-240	245/35		Orig.-Verschr.
				120-186	225/35		Orig.-Verschr.
	B38	45	-	120-240	235/35, 245/30, 245/35		Orig.-Verschr.
	B43	40	-	120-186	225/35		Orig.-Verschr.
				120-240	235/35, 245/30, 245/35		

S90, V90

ab 08.16

P

5/108

63,4

e4*2007/46*1067*..

Sensor - Brocksens Universal

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	42	-	110-235	235/45, 245/45		Orig.-Verschr.
	RC32	42	-	110-240	235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	RC34	42	-	110-240	225/50, 225/55, 235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	RC27	42,5	-	140-235	225/60		Orig.-Verschr.
		45	-	110-187	225/50, 225/55, 235/45, 235/50		Orig.-Verschr., bei 235/50 u. 255/45 ✖
				110-235	245/45, 255/45		
	RC29	45	ZP531	110-187	235/45		nicht Bremse ab 345mm
				110-235	245/45		
	RC32	45	-	110-240	235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	RC34	45	-	110-240	225/50, 225/55, 235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	B24	45	ZP531	140-187	235/45, 245/45		nicht Bremse ab 345mm
	B37	45	ZP531	140-187	235/45		nicht Bremse ab 345mm
				140-235	245/45		
	B38	45	ZP531	110-187	235/45		
				110-235	245/45		
	B42 / B44	42	ZP531	110-187	225/50, 235/45		
				110-240	245/45		
8 x 19	AC-MB6	42	ZP569F+R	110-187	225/50, 235/45		+ Red.Ringe 73,1-63,4
				110-240	245/45		
	CA 26	45	ZP569F+R	110-187	235/45		+ Red.Ringe 65,1-63,4
				110-240	245/45		
	RC27	42,5	-	110-240	225/45, 235/40, 235/45		Orig.-Verschr.
		45	-	110-240	225/45, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC29	42,5	ZP569F	110-187	225/45, 235/40		
				110-235	245/40		
		45	ZP531	110-187	225/45, 235/40		
				110-240	245/40		
	RC34	42+45	-	110-240	225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
		48,5	-(X8)	110-240	225/45, 235/45, 245/40, 245/45		Orig.-Verschr., Ausführung X8
	B24 / B38	45	ZP531	110-187	225/45, 235/40		
				110-235	245/40		
	B40	45	ZP569F	110-187	225/45, 235/40		
				110-240	245/40		
	B43	42+47,5	ZP569F	110-187	225/45, 235/40		
				110-240	245/40		
	AC-518	45	ZP569F+R	110-187	225/45, 235/40		+ Red.Ringe 73,1-63,4
				110-235	245/40		
	CA 19	45	-	110-240	225/45, 235/40, 235/45, 245/40, 245/45		Orig.-Verschr.
	CA 24	45	ZP531	110-240	225/45, 235/40, 235/45, 245/40, 245/45		
	Oxigin 29	45	ZP531	110-187	225/45, 235/40		
				110-240	245/40		
	RC32	47	-	110-240	255/40		Orig.-Verschr.
	FMI07 Atena	47	-		255/40		Orig.-Verschr.
	B36	44	ZP531	140-187	225/45, 235/40		
				140-235	245/40, 255/35, 255/40		
	B38	45	ZP531	140-187	225/45, 235/40		
				140-235	245/40		
	B41	42	-	110-240	225/45, 235/45, 245/40, 245/45, 255/40		Orig.-Verschr.

8,5 x 19	B42	42	ZP569F	110-187 110-240	225/45, 235/40 245/40, 255/35, 255/40		
	B43	45	-	110-187 110-240	225/45 245/40, 255/35, 255/40		Orig.Verschr.
	B44	42	-	110-187 110-240	225/45, 235/40 245/40, 255/35, 255/40		Orig.Verschr.
	CA 23	45	ZP531	110-187 110-240	225/45 245/40, 255/35, 255/40		
	Oxigin 18	45	ZP531	110-187 110-240	225/45 245/40, 255/35, 255/40		
	Oxigin 25	45	ZP531	110-240	225/45, 235/40, 235/45		
	Oxigin 28	38	ZP531	110-187 110-240	225/45, 235/40 245/40		
8 x 20	B38	45	-	110-187 110-240	235/35 245/35		Orig.Verschr.
	B40	45	-	110-187 110-240	235/35 245/35		Orig.Verschr.
	B43	40+45,5 48,5	-	110-187 110-240	235/35 245/35		Orig.Verschr.
	AC-521	43	ZP569F+R	110-187 110-240	235/35 245/35		+ Red.Ringe 73,1-63,4
8,5 x 20	RC36	47,5	-	110-240	255/35		Orig.-Verschr.
	B43	47,5	-	110-240	255/35		Orig.-Verschr.
	RC29	40 45	ZP531 ZP569F	110-187 110-240	235/35, 245/35, 255/30, 255/35 245/35, 255/30, 255/35		
	RC34	45	-	110-240	245/35, 245/40, 255/35		Orig.-Verschr.
	B24	45	ZP531	110-240	245/35, 255/30, 255/35		
	B32	45 48	ZP531 ZP569F	110-240 110-240	245/35, 255/30, 255/35 245/35, 255/30, 255/35		
	B41 / B43	45	-	110-240	245/35, 245/40, 255/35		Orig.-Verschr.
	B42	45	ZP569F	110-240	245/35, 255/30, 255/35		
	B44	40	-	110-187 110-240	235/35 245/35, 255/30, 255/35		Orig.Verschr.
8,5 x 21	B41	38,5 45	-	110-240 110-240	245/30, 255/30 245/30, 245/35, 255/30		Orig.-Verschr., auch für Hybrid
	B43	38,5	-	110-240	245/30, 245/35		Orig.-Verschr.
9 x 22	AF18	40	14x1,5x35	110-240	245/30		

S90, V90 / T8 Twin Engine Hybrid				ab 2017	P	5/108	63,4	e4*2007/46*1067*..
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	B38	45	ZP531	235	245/45			
	B42 / B44	42	ZP531	186-235	245/45		nur Bremse 345mm	
	CA 26	45	ZP569F+R	186-235	245/45		+ Red.Ringe 65,1-63,4, nur Bremse 345mm	
	AC-MB6	42	ZP569F+R	186-235	245/45		+ Red.Ringe 73,1-63,4	
8,5 x 18	B32	45	ZP531	186-235	245/45			
8 x 19	RC29	42,5 45	ZP569F ZP531	223-235 223-235	245/40 245/40		nur Bremse 345mm	
	B24	45	ZP531	223-235	245/40		nur Bremse 345mm	
	B38	45	ZP531	235	245/40			
	B40	45	ZP569F	186-235	245/40		nur Bremse 345mm	
	B43	42+47,5	ZP569F	186-235	245/40		nur Bremse 345mm	
	AC-518	45	ZP569F+R	235	245/40		+ Red.Ringe 73,1-63,4, nur Bremse 345mm	
	Oxigin 29	45	ZP531	186-235	245/40		nur Bremse 345mm	
8,5 x 19	B36	44	ZP531	223-235	245/40, 255/35, 255/40		nur Bremse 345mm	
	B42	42	ZP569F	186-235	245/40, 255/35, 255/40		nur Bremse 345mm	
	B43	45	-	186-235	245/40, 255/35, 255/40		Orig.-Verschr., nur Bremse 345mm	
	B44	42	-	186-235	245/40, 255/35, 255/40		Orig.-Verschr., nur Bremse 345mm	
	CA 23	45	ZP531	186-235	245/40, 255/35, 255/40		nur Bremse 345mm	
8 x 20	Oxigin 18	45	ZP531	223-235	245/40, 255/35, 255/40		nur Bremse 345mm	
	B38	45	-	186-235	245/35, 245/40		Orig.-Verschr., nur Bremse 345mm	
	B40	45	-	186-235	245/35, 245/40		Orig.-Verschr., nur Bremse 345mm	
	B43	40+45,5 48,5	-	186-235 186-235	245/35, 245/40 245/35, 245/40		Orig.-Verschr., nur Bremse 345mm	
	AC-521	43	ZP569F+R	186-235	245/35, 245/40		+ Red.Ringe 73,1-63,4, nur Bremse 345mm	
8,5 x 20	RC36	47,5	-	186-235	245/40		Orig.-Verschr., nur Bremse 345mm	
	B43	47,5	-	186-235	245/40		Orig.-Verschr., nur Bremse 345mm	
	RC29	45	ZP569F	223-235	245/35, 245/40, 255/35		nur Bremse 345mm	
	B24	45	ZP531	235	245/35, 245/40, 255/35			
	B32	48	ZP569F	223-235	245/35, 245/40, 255/35		nur Bremse 345mm	
		45	ZP531	223-235	245/35, 245/40, 255/35		nur Bremse 345mm	

8,5 x 21	B42	45	ZP569F	186-235	245/35, 245/40, 255/35		nur Bremse 345mm
	B43	45	-	186-235	245/35, 245/40, 255/35		Orig.-Verschr., nur Bremse 345mm
	B44	40	-	186-235	245/35, 245/40, 255/35		Orig.-Verschr., nur Bremse 345mm
8,5 x 21	B43	38,5	-	186-235	245/35		Orig.-Verschr., nur Bremse 345mm
V90 CC							
ab 01.2017			P	5/108	63,4	e4*2007/46*1067*01-..	
Sensor - Brocksens Universal							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC30	50,5	-	120-240	235/55		Orig.-Verschr.
	RC32	50,5	-	140-235	235/55		Orig.-Verschr.
	RC34	50,5	-	120-240	235/55		Orig.-Verschr.
	RC30	46	ZP569F	140-235	235/55, 245/50		
	RC32	45	-	120-240	235/55		Orig.-Verschr.
	RC34	45	-	120-240	235/55		Orig.-Verschr.
		46	-	120-240	235/55, 245/50, 245/55		Orig.-Verschr.
	B39	45	ZP531	120-240	235/55		
8 x 18	AC-521	42	ZP569F+R	120-240	235/55		+ Red.Ringe 73,1-63,4
	Oxigin 18	45	ZP531	140-235	235/55, 245/50, 245/55		Achtung Bremse!
	RC27	42	-	120-240	225/60		Orig.-Verschr.
		45	-	140-235	225/60, 235/55, 245/50		Orig.-Verschr., ab 245/50 ✖
	RC32 / RC34	45	-	120-240	235/55		Orig.-Verschr.
	B38	45	ZP531	140-235	235/55		
	CA 26	45	ZP569F+R	120-240	235/55		+ Red.Ringe 65,1-63,4
	7,5 x 19	RC32	50,5	-	120-240	235/45, 235/50, 245/45	
RC34		50,5	-	120-240	235/45, 235/50, 245/45		Orig.-Verschr., auch Hybrid
B32		50,5	-	120-240	235/50, 245/45		Orig.-Verschr.
		44,5	ZP569F	140-235	235/50, 245/45		
AC-521		42	ZP569F+R	120-240	235/50, 245/45		+ Red.Ringe 73,1-63,4
CA 26		45	ZP531	120-240	235/50, 245/45		
8 x 19	Oxigin 18	45	ZP531	140-235	235/50, 245/45		
	RC27	42,5	-	120-240	225/55, 245/45		Orig.-Verschr.
		45	-	120-240	225/55, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC29	45	ZP531	120-240	235/50, 245/45, 255/45		
	RC32	45	-	120-240	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., auch für Hybrid Fahrzeuge
	RC34	42	-	120-240	235/45, 245/45		Orig.-Verschr.
		45	-	120-240	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		48,5	-(X8)	120-240	235/45, 245/45		Orig.-Verschr., Ausführung X8
	B24 / B38	45	ZP531	140-235	235/50, 245/45, 255/45		
	B40	45	ZP569F	120-240	235/50, 245/45, 255/45		
	B43	47,5	ZP569F	120-240	235/50, 245/45, 255/45		
	AC-518	45	ZP569F+R	140-235	235/50, 245/45, 255/45		+ Red.Ringe 73,1-63,4
	CA 19	45	-	120-240	225/55, 235/50, 245/45, 255/45		Orig.-Verschr.
	CA 24	45	ZP531	120-240	225/55, 235/50, 245/45, 255/45		
	Oxigin 29	45	ZP531	120-240	235/50, 245/45, 255/45		
8,5 x 19	B41	42	-	120-240	235/45		Orig.-Verschr.
	B43	45	-	120-240	245/45		Orig.-Verschr.
	CA 23	45	ZP531	120-240	245/45		
8 x 20	RC36	47,5	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
		48,5	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
	B38	45	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
	B40	45	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
	B43	40	-	120-240	235/45		Orig.-Verschr.
		45,5+50	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
		48,5+50,5	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
8,5 x 20	AC-521	43	ZP569F+R	120-240	235/45, 245/40, 245/45		+ Red.Ringe 73,1-63,4
	RC29	45	ZP569F	140-235	235/45, 245/40, 245/45		
	RC34	45	-	120-240	235/40, 235/45, 245/40		Orig.-Verschr.
	RC36	45+47,5	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
	B24	45	ZP531	120-240	235/45, 245/40, 245/45		
		48	ZP569F	120-240	235/45, 245/40, 245/45		
		45	ZP531	120-240	235/45, 245/40, 245/45		
	B41 / B43	45	-	120-240	235/40, 235/45, 245/40		Orig.-Verschr.
	B42	45	ZP569F	120-240	235/45, 245/40, 245/45		
	B44	40	-	120-240	235/45		Orig.-Verschr.
	AC-518	45	14x1,5, Kegel,35mm +R	120-240	235/45, 245/40, 245/45		+ Red.Ringe 73,1-63,4
9 x 20	B40	46	-	120-240	235/45, 245/40, 245/45		Orig.-Verschr.
8,5 x 21	B41	45	-	120-240	245/35		Orig.-Verschr., auch für Hybrid
	B43	49,5	-	120-240	245/35, 245/40		Orig.-Verschr.
XC40							
ab 2018			X	5/108	63,4	e9*2007/46*3146*..	
kein Sensor - indirektes RDKS							

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 17	RC27	50,5	-	95-184	235/60, 235/65, 245/55		Orig.-Verschr. nicht Bremse ab 345 mm
	RC32	50,5	-	95-184	235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	50,5	-	95-184	235/60, 245/55, 245/60		Orig.-Verschr.
	RC24	47	ZP531	95-184	235/60, 245/55		nicht Bremse ab 345mm
	RC28	45	ZP531	95-184	235/60		nicht Bremse ab 345mm
	RC32	52,5	-	95-182	235/60, 245/55, 245/60		Orig.-Verschr.
	AC-518	45	ZP569F+R	110-184	235/60		nicht Bremse ab 345mm, + Red.Ringe 73,1-63,4
7,5 x 18	RC30	50,5	-	95-184	235/55		Orig.-Verschr.
				95-184	235/55, 245/50		
	RC32	50,5	-	95-182	235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	RC34	50,5	-	95-184	235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	B32	50	-	95-184	235/55, 245/50		Orib.-Verschr. nicht Bremse 345mm, auch Hybrid
	RC32	45	-	95-184	235/50, 235/55		Orig.-Verschr.
	RC34	45+46	-	95-184	235/50, 235/55		Orig.-Verschr.
	B32	45	ZP531	110-184	235/55		
	B39	45	ZP531	95-184	235/55		nicht Bremse ab 345mm
8 x 18	Oxigin 18	45	ZP531	110-184	235/55, 235/60		
	RC27	42+45	-	95-184	225/55, 225/60		Orig.-Verschr.
	RC29	45	ZP531	110-184	235/55		
	B38	45	ZP531	110-184	235/55		
	B36 / B37	45	ZP531	95-184	235/55		nicht Bremse ab 345mm
	AC-518	45+50	ZP569F+R	110-184	235/55		nicht Bremse ab 345mm, + Red.Ringe 73,1-63,4
7,5 x 19	CA 26	45	ZP569F+R	95-184	235/55		+ Red.Ringe 65,1-63,4
	RC32	50,5	-	95-182	235/45, 235/50, 245/45, 245/50		Orig.-Verschr.
		50,5	-	95-184	235/45, 235/50, 245/45, 245/50		Orig.-Verschr., auch Hybrid
		50,5	-	95-184	235/50		Orig.-Verschr.
	B32	50,5	ZP569F	95-184	235/50, 245/45, 245/50		
8 x 19	AC-521	42	ZP569F+R	95-184	245/45		+ Red.Ringe 73,1-63,4
	CA 26	45	ZP531	95-184	235/50, 245/45		
	RC27	45	-	95-184	225/55, 245/45		Orig.-Verschr.
	RC29	45	ZP531	95-184	235/50, 245/45, 255/45		nicht Bremse ab 345mm
	RC32	45	-	95-184	235/45, 245/45		Orig.-Verschr., auch für Hybrid Fahrzeuge
	RC34	45	-	95-184	235/45, 245/45		Orig.-Verschr.
		48,5	-(X8)	95-184	235/45, 235/50, 245/45, 245/50, 255/45		Orig.-Verschr., Ausführung X8
		52,5	-	95-184	235/45, 235/50, 245/45, 245/50, 255/45		Orig.-Verschr.
	B24	45	ZP531	95-184	235/50, 245/45, 255/45		nicht Bremse ab 345mm
	B38	45	ZP531	110-184	235/50, 245/45, 255/45		
	B40	45	ZP569F	95-184	235/50, 245/45, 255/45		nicht Bremse ab 345mm
		50	-	95-184	235/50, 245/45, 255/45		Orig.-Verschr., auch Hybrid
	B43	47,5	ZP569F	95-184	235/50, 245/45, 255/45		
	AC-518	45	ZP569F+R	110-184	235/50, 245/45, 255/45		nicht Bremse ab 345mm, + Red.Ringe 73,1-63,4
	CA 19	45	-	95-184	225/55, 245/45		Orig.-Verschr., incl. Hybrid
	CA 24	45	ZP531	95-184	225/55, 245/45		
	Oxigin 29	45	ZP531	95-184	235/50, 245/45, 255/45		
8,5 x 19	B43	45	-	95-184	245/45		Orig.-Verschr.
	CA 23	45	ZP531	95-184	245/45		
	Oxigin 18 / 25	45	ZP531	95-184	245/45		nicht Bremse ab 345mm
8 x 20	Originaldim.	50,5			245/45		
	RC36	47,5	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
		48,5	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
	B38	45	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse ab 345mm
	B40	45	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse ab 345mm
	B43	40	-	95-184	235/45		Orig.-Verschr.
		45,5+50	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
		48,5+50,5	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
	AC-521	43	ZP569F+R	95-184	235/45, 245/40, 245/45		+ Red.Ringe 73,1-63,4
8,5 x 20	RC29	45	ZP569F	95-184	235/45, 245/40, 245/45		nicht Bremse ab 345mm
	RC34	45	-	95-184	235/40, 235/45		Orig.-Verschr.
	RC36	45	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
		47,5	-	95-184	235/45, 245/40, 245/45 , 255/40		Orig.-Verschr.
	B24	45	ZP531	95-184	235/45, 245/40, 245/45		nicht Bremse ab 345mm
	B32	45	ZP531	95-184	235/45, 245/40, 245/45		
		48	ZP569F	95-184	235/45, 245/40, 245/45, 255/40		nicht Bremse ab 345mm
	B41	45	-	95-184	235/40, 235/45		Orig.-Verschr., auch für Hybrid
	B42	45	ZP569F	95-184	235/45, 245/40, 245/45		
	B43	45	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr.
	B44	40	-	95-184	235/45		Orig.-Verschr.
	AC-518	45	14x1,5, Kegel,35mm +R	95-184	235/45, 245/40, 245/45		+ Red.Ringe 73,1-63,4
9 x 20	B37	48	-	95-184	235/45, 245/40, 245/45		Orig.-Verschr., nicht Bremse 296mm
	B40	46	-	95-184	235/45		
8 x 21	Originaldim.	50,5			245/40		

8,5 x 21	B43	49,5	-	95-184	245/35, 245/40		Orig.-Verschr.
XC40 Recharge electric ab 2020 X 5/108 63,4 e9*2007/46*3146*09-15							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 19	RC32	50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.
8,5 x 19		56	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.
7,5 x 19		50,5	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.
8,5 x 19		56	-	80-183	VA 235/50 + HA 255/45		Orig.-Verschr.
8,5 x 19	B32	45	ZP531	80, 160	VA 235/50+HA 255/45		
			ZP569F	80, 160	VA 235/50+HA 255/45		
	B43	45	-	80, 160	VA 235/50+HA 255/45		Orig.-Verschr.
	CA 20	45	ZP569F	80-160	VA 235/50+HA 255/45		
	CA 23	45	ZP531	80, 160	VA 235/50+HA 255/45		
8 x 20	B40	50,5	-	80, 160	VA 235/45, 245/40		Orig.-Verschr.
9 x 20		58,5	-	80, 160	HA 255/40, 265/40, 275/35		Orig.-Verschr.
8 x 20	B43	50,5	-	80, 160	VA 235/45, 245/40		Orig.-Verschr.
9 x 20		58,5	-	80, 160	HA 255/40, 265/40, 275/35		Orig.-Verschr.
8,5 x 20	RC29	45	ZP569F	80, 160	VA 235/45+HA 255/40		
	RC36	45+47,5	-	80, 160	VA 235/45+HA 255/40		Orig.-Verschr.
	B24	45	ZP531	80, 160	VA 235/45+HA 255/40		
	B32	45	ZP531	160 (300)	VA 235/45+HA 255/40		
	B41	45	-	80-183	VA 235/45+HA 255/40		Orig.-Verschr., bei 255/40 ✖
	B42	45	ZP569F	80, 160	VA 235/45+HA 255/40		
	B43	45	-	80, 160	VA 235/45+HA 255/40		Orig.-Verschr.
	AC-518	45	14x1,5x35 +R	160 (300)	VA 235/45+HA 255/40		
9 x 20	B37	48	ZP569F	160 (300)	VA 235/45+HA 255/40		
Kombinationen							
8 x 19	RC34	50	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.
9 x 19		53	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.
8 x 20	B43	50	-	80, 160	VA 235/45, 245/40		Orig.-Verschr., HA bei 275/35 ✖
9 x 20		53	-	80, 160	HA 255/40, 265/40, 275/35		Orig.-Verschr., HA bei 275/35 ✖
8,5 x 20	B32	48	ZP569F	160 (300)	VA 235/45, 245/40		
9,5 x 20		52	ZP569F	160 (300)	HA 255/40, 265/40, 275/35		HA ab 265/40 ✖

XC40 Recharge		electric NEU	ab Modell 2023		X	5/108	63,4	e9*2007/46*3146*16-..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension				
Kombinationen									
8,5 x 19	B32	45	ZP531	120-128	VA 235/50+HA 255/45			Heckantrieb	
			ZP569F	120-128	VA 235/50+ HA 255/45			Heckantrieb	
				183	VA 235/50+ HA 255/45			Allrad	
	B43	45	-	120-128	VA 235/50+ HA 255/45			Orig.-Verschr., Heckantrieb	
				183	VA 235/50+ HA 255/45			Orig.-Verschr., Allrad	
	CA 20	45	ZP569F	101-128	VA 235/50+ HA 255/45			Heckantrieb	
			183	VA 235/50+ HA 255/45			Allrad		
8 x 20	B40	VA 50,5	-	120-128	VA 235/45, 245/40			Orig.-Verschr., Heckantrieb	
		183		VA 235/45, 245/40		Orig.-Verschr., Allrad			
9 x 20		HA 58,5		120-128	HA 255/40, 265/40, 275/35			Orig.-Verschr., Heckantrieb	
				183	HA 255/40, 265/40, 275/35			Orig.-Verschr., Allrad	
8 x 20	B43	VA 50,5	-	101-128	VA 235/45			Orig.-Verschr., Heckantrieb	
		183		VA 235/45		Orig.-Verschr., Allrad			
9 x 20		HA 58,5		101-128	HA 255/40			Orig.-Verschr., Heckantrieb	
				183	HA 255/40			Orig.-Verschr., Allrad	
8,5 x 20	RC36	45+47,5	-	101-128	VA 235/45+HA 255/40			Orig.-Verschr., Heckantrieb	
				183	VA 235/45+HA 255/40			Orig.-Verschr., Allrad	
	B42	45	ZP569F	120-128	VA 235/45+HA 255/40			Heckantrieb	
				183	VA 235/45+HA 255/40			Allrad	
	B43	47,5	-	101-128	VA 235/45+HA 255/40			Orig.-Verschr., Heckantrieb	
				183	VA 235/45+HA 255/40			Orig.-Verschr., Allrad	

Kombinationen							
8 x 19	RC34	50	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.
9 x 19		53	-	80-183	VA 235/50+HA 255/45, VA 245/45+HA 265/40		Orig.-Verschr.

XC60 ab 07.2017 U 5/108 63,4 e4*2007/46*1220*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		
	RC27	50,5	-	110-220	235/60, 235/65		Orig.-Verschr. nicht Bremse 345mm
	RC32	50,5	-	110-235	235/65		Orig.-Verschr.

7,5 x 17	RC34	50,5	-	110-235	235/65		Orig.-Verschr., nicht Bremse 345x30mm
	RC24	47	ZP531	110-187	235/60, 235/65		nicht Bremse ab 345mm
	RC27	52,5	-	140-187	235/65		Orig.-Verschr.
	RC28	45	ZP531	110-220	235/60, 235/65		nicht Bremse ab 345mm
	AC-518	45	ZP569F+R	110-187	235/60, 235/65		nicht Bremse ab 345mm, + Red.Ringe 73,1-63,4
7,5 x 18	RC30	50,5	-	110-240	235/60		Orig.-Verschr.
			-	140-235	235/55, 235/60		
	RC32	50,5	-	110-235	235/60		Orig.-Verschr.
			-	110-240	235/55, 235/60		
	RC34	50,5	-	110-240	235/55, 235/60		Orig.-Verschr.
	B32	50	-	110-240	235/55, 235/60		Orig.-Verschr. nicht Bremse 345mm
	RC30	46	ZP569F	140-235	235/55, 235/60, 245/60		ohne Radhausverbr. bei 245/60 ✖
	RC32	45	-	110-240	235/55, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	45+46	-	110-240	235/55, 235/60, 245/55, 245/60		
	B32	45	ZP531	140-235	235/55, 235/60, 245/60		nicht Bremse ab 345mm, ohne Radhausverbr. ab 245/60 ✖
	RC27	45	-	110-240	235/60, 245/55, 245/60		Orig.-Verschr., ab 245/55 ✖
	RC29	45	ZP531	110-240	235/55, 235/60		nicht Bremse ab 345mm, nur mit Kotflügelverbreiterungen ohne Auflagen
	RC32	42	-	110-240	235/55, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
		45	-	110-240	235/55, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	42	-	110-240	235/55, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr.
		45	-	110-240	235/55, 235/60, 245/55, 245/60		Orig.-Verschr.
8 x 18	B37 / B38	45	ZP531	110-240	235/55, 235/60		nur mit Kotflügelverbreiterungen ohne Auflagen
	AC-518	45	ZP569F+R	110-240	235/55, 235/60		+ Red.Ringe 73,1-63,4, nicht Bremse ab 345mm, nur mit Kotflügelverbreiterungen ohne Auflagen
	RC32	50,5	-	110-240	235/50, 235/55		Orig.-Verschr.
	RC34	50,5	-	110-240	235/50, 235/55		Orig.-Verschr., nicht Bremse 371x30mm
	B32	50,5	-	110-240	235/55		Orig.-Verschr.
7,5 x 19	B39	45	ZP531	140-235	235/55, 235/60, 245/60		ohne Radhausverbr. bei 245/60 ✖
	AC-521	42	ZP569F+R	110-240	235/50, 235/55, 245/50, 255/45		+ Red.Ringe 73,1-63,4, ohne Radhausverbr. ✖
8 x 19	RC27	45	-	110-235	235/50, 235/55, 245/50, 255/45		Orig.-Verschr., ab 245/50 ✖
	RC29	42,5	ZP569F	140-235	235/50, 235/55, 245/50, 255/45, 255/50		mit Kotflügelverbr. ohne Auflagen ✖
		45	ZP531	110-240	235/50, 235/55, 245/50, 255/45		mit Kotflügelverbr. ohne Auflagen ✖
	RC34	42	-	110-240	235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
		45	-	110-240	235/50, 235/55, 245/50		Orig.-Verschr.
		48,5	- (X8)	110-240	235/50, 235/55		Orig.-Verschr., Ausführung X8, nicht Bremse 371x32mm
	B24	45	ZP531	110-240	235/50, 235/55, 245/50, 255/45		ohne Kotflügelverbr. ✖
	B38	45	ZP531	140-235	235/50, 235/55, 245/50, 255/45		ohne Kotflügelverbr. ✖
	B40	45	ZP569F	110-240	235/50, 235/55, 245/50, 255/45		ohne Kotflügelverbr. ✖
		50	-	110-240	235/50, 235/55, 255/45		Orig.-Verschr.
	B43	47,5	ZP569F	110-240	235/50, 235/55, 255/45		
	AC-518	45	ZP569F+R	110-240	235/50, 235/55, 245/50, 255/45		+ Red.Ringe 73,1-63,4, ohne Radhausverbr. ✖
	CA 24	45	ZP531	110-240	235/50, 235/55		nicht Bremse 400mm
	Oxigin 29	45	ZP531	110-240	235/50, 235/55, 245/50, 255/45		ohne Kotflügelverbr. ✖
	B32	45	ZP531	140-240	235/50, 235/55, 255/45		ohne Radhausverbr. ✖
	B36	44	ZP531	110-240	235/50, 235/55, 255/45		ohne Radhausverbr. ✖
8,5 x 19	B41	42	-	110-240	235/50, 235/55, 245/50, 265/45		Orig.-Verschr.
	B42	42	ZP569F	110-240	235/50, 235/55, 245/50, 255/45, 265/45		ohne Radhausverbr. ✖
	B43	45	-	110-240	235/50, 235/55, 255/45		Orig.-Verschr., ohne Radhausverbr. ✖
	Oxigin 20	45	ZP531	110-235	235/50, 235/55		
	Oxigin 25	45	ZP531	110-240	235/50, 235/55		nicht Hybrid
	B40	52,5	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr.
	RC36	47,5	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr.
	B38	45	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr., ohne Verbr. bei 255/45 ✖
8 x 20	B40	45	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr., ohne Radhausverbr. bei 255/45 ✖
	B43	40+45,5	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr., mit Radhausverbreiterungssatz für 9 Zoll Breite Serie
		50+50,5	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr.
		52	-	110-240	235/45, 245/45, 255/45		Orig.-Verschr.
	AC-521	43	ZP569F+R	110-240	235/45, 245/45, 255/45		+ Red.Ringe 73,1-63,4, ohne Radhausverbr. ✖
	RC29	45	ZP569F	140-235	235/45, 245/45, 255/40, 255/45		ohne Radhausverbr. ab 245/45 ✖
		52,5	ZP569F	110-240	235/45, 245/45		
	RC34	45	-	110-240	235/45, 245/45, 255/45, 265/45		Orig.-Verschr.
	B24	45	ZP531	140-235	235/45		ohne Radhausverbr.
					235/45, 245/45, 255/40, 255/45		mit Kotflügelverbreiterung

8,5 x 20	B32	48	ZP569F	110-240	235/45, 245/45		ohne Radhausverbr. ab 255/40 ✖
		45	ZP531	140-235	235/45, 245/45, 255/40, 255/45		ohne Radhausverbr. ab 245/45 ✖
	B41	45	-	110-240	235/45, 245/45, 255/45, 265/45		Orig.-Verschr.
	B42	45	ZP569F	110-240	235/45, 245/45, 255/40, 255/45		ohne Radhausverbr. ab 245/45 ✖
	B43	45	-	110-240	235/45, 245/45, 255/40, 255/45		Orig.-Verschr., ohne Radhausverbr. ab 245/45 ✖
	AC-518	45	14x1,5, Kegel, 35mm+R	110-240	235/45, 245/45, 255/40, 255/45		+ Red.Ringe 73,1-63,4, ohne Radhausverbr. ab 245/45 ✖
9 x 20	B43	38,5	-	110-240	255/45		Orig.-Verschr., mit Radhausverbreiterung
	B37	48	ZP569F	110-240	235/45, 245/45, 255/40, 255/45		ohne Radhausverbr. ab 245/45 ✖
	B40	46	-	110-240	235/45, 245/45, 255/40, 255/45		Orig.-Verschr., ohne Radhausverbr. ab 245/45 ✖
	B43	49,5	-	110-240	245/40, 255/40		Orig.-Verschr., mit Radhausverbreiterungen
8,5 x 21	B41	38,5+45	-	110-240	245/40, 255/40		Orig.-Verschr., auch für Hybrid, Achtung!!! passt nicht bei Polestar-Bremse
	B43	38,5	-	110-240	255/40		Orig.-Verschr., mit Radhausverbreiterungssatz für 9 Zoll Breite Serie
9 x 22	AF18	40	14x1,5x35	110-240	255/30, 255/35, 265/30, 265/35		mit Radhausverbreiterungen

XC60 T6/T8 Twin Engine Hybrid				ab 2017	U	5/108	63,4	e4*2007/46*1220*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension				
7,5 x 17	RC27	50,5	-	186-233	235/60, 235/65			Orig.-Verschr., nicht Bremse 345mm	
	RC28	45	ZP531	186-233	235/60, 235/65			nicht Bremse ab 345mm	
7,5 x 18	RC30	50,5	-	186-235	235/60			Orig.-Verschr., nicht Bremse 370mm	
			ZP569F	235	235/55, 235/60				
		46	ZP569F	235	235/55, 235/60, 245/60			ohne Radhausverbr. bei 245/60 ✖	
8 x 18	RC25	42,5	ZP569F	223-235	235/55, 235/60			nur Bremse 345mm, ohne Radhausverbr. ✖	
	RC27	45	-	223-235	235/60, 245/55, 245/60			Orig.-Verschr., ab 245/55 ✖	
7,5 x 19	B32	50,5	-	186-235	235/55			Orig.-Verschr.	
				186-235	235/50, 235/55				
	AC-521	42	ZP569F+R	186-235	235/50, 235/55, 245/50, 255/45			+ Red.Ringe 73,1-63,4, ohne Radhausverbr. ✖	
8 x 19	RC27	45	-	235	235/50, 235/55, 245/50, 255/45			Orig.-Verschr., ab 245/50 ✖	
	RC29	45	ZP531	223-235	235/50, 235/55, 245/50, 255/45			mit Kotflügelverbr. ohne Auflagen ✖	
	B24	45	ZP531	223-235	235/50, 235/55, 245/50, 255/45			ohne Radhausverbr. ✖	
	B40	45	ZP569F	223-235	235/50, 235/55, 245/50, 255/45			ohne Radhausverbr. ✖	
		50	-	186-235	235/50, 235/55, 255/45			Orig.-Verschr., nicht Bremse 370 u. 400mm	
	B43	47,5	ZP569F	186-235	235/50, 235/55, 255/45			nicht Bremse 370 u. 400mm	
	AC-518	45	ZP569F+R	223-235	235/50, 235/55, 245/50, 255/45			+ Red.Ringe 73,1-63,4, nur Bremse 345mm, ohne Radhausverbr. ✖	
	CA 24	45	ZP531	223-235	235/50, 235/55			nicht Bremse 400mm	
	Oxigin 29	45	ZP531	186-235	235/50, 235/55, 245/50, 255/45			ohne Radhausverbr. ✖	
	B32	45	ZP531	223-235	235/50, 235/55, 255/45			ohne Radhausverbr. ✖	
8,5 x 19	B42	42	ZP569F	186-235	235/50, 255/45, 265/45			nicht Bremse 370 u. 400mm, ohne Radhausverbr. ✖	
	B43	45	-	186-235	235/50, 235/55, 255/45			Orig.-Verschr., ohne Radhausverbr. ✖	
	Oxigin 20	45	ZP531	235	235/50, 235/55				
	Oxigin 25	45	ZP531	223-235	235/50, 235/55				
8 x 20	B40	52,5	-	186-235	235/45, 245/45, 255/45			Orig.-Verschr., nicht Bremse 370mm	
		45	-	186-235	235/45, 245/45, 255/45			Orig.-Verschr., ohne Radhausverbr. bei 255/45 ✖	
	B43	40+45,5	-	186-235	235/45, 245/45, 255/45			Orig.-Verschr., mit Radhausverbreiterungssatz für 9 Zoll Breite Serie	
		50+50,5	-	186-235	235/45, 245/45, 255/45			Orig.-Verschr.	
		52	-	186-235	235/45, 245/45, 255/45			Orig.-Verschr., nicht Bremse 370 u. 400mm	
	AC-521	43	ZP569F+R	186-235	235/45, 245/45, 255/45			+ Red.Ringe 73,1-63,4, nicht Bremse 370 u. 400mm, ohne Radhausverbr. ✖	
8,5 x 20	RC29	45	ZP569F	235	235/45, 245/45, 255/40			ohne Radhausverbr. ab 245/45 ✖	
		52,5	ZP569F	223-235	235/45, 245/45			nicht Bremse 370mm	
	B24 / B32	45	ZP531	235	235/45, 245/45, 255/40, 255/45			ohne Radhausverbr. ab 245/45 ✖	
	B42	45	ZP569F	186-235	235/45, 245/45, 255/40, 255/45			ohne Radhausverbr. ab 245/45 ✖	
	B43	45	-	186-235	235/45, 245/45, 255/40, 255/45			Orig.-Verschr., nicht Bremse 370 u. 400mm, ohne Radhausverbr. ab 245/45 ✖	
	AC-518	45	14x1,5, Kegel, 35mm+R	186-235	235/45, 245/45, 255/40, 255/45			+ Red.Ringe 73,1-63,4, nicht Bremse 400mm, ohne Radhausverbr. ab 245/45 ✖	
9 x 20	B43	38,5	-	186-235	255/45			Orig.-Verschr., mit Radhausverbreiterungen, nicht Bremse 400mm	
	B37	48	ZP569F	186-235	235/45, 245/45, 255/40, 255/45			nicht Bremse 370 u. 400mm, ohne Radhausverbr. ab 245/45 ✖	
	B40	46	-	186-235	235/45, 245/45, 255/40, 255/45			Orig.-Verschr., nicht Bremse 370 u. 400mm, ohne Radhausverbr. ab 245/45 ✖	
8,5 x 21	B43	38,5	-	186-235	255/40			Orig.-Verschr., nicht Bremse 400mm	

8,5 x 21	B43	49,5	-	186-235	245/40, 255/40		Orig.-Verschr., nicht Bremse 370 u. 400mm
9 x 21	B43	38,5	-	186-235	255/40		Orig.-Verschr., mit Radhausverbreiterungssatz für 9 Zoll Breite Serie, nicht Bremse 400mm
9 x 22	AF18	40	14x1,5x35	186-235	255/30, 255/35, 265/30, 265/35		mit Radhausverbreiterungen

XC70			D-N2E		5/108	63,4	e13*2007/46*1213*..	
Sensor - Brocksens Universal								
Dimension	Design	ET	KIT	KW	Reifendimension			
7,5 x 17	RC27	55	-	120-224	235/65		Orig.-Verschr.	
8 x 18	RC27	55	-	120-224	235/60		Orig.-Verschr.	
8 x 19	RC27	55	-	120-224	235/45		Orig.-Verschr.	
	B43	55	-	120-224	235/45		Orig.-Verschr.	

XC90 (siehe Konfigurator)		ab 2015		L	5/108	63,4	e4*2007/46*0929*...
---------------------------	--	---------	--	---	-------	------	---------------------

XC90 T8 Twin Engine Hybrid				ab 2018	L	5/108	63,4	e4*2007/46*0929*...	
Sensor - Brocksens Universal									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 19	RC32	42,5	-	235	235/55			Orig.-Verschr., i.V.	
	CA 24	45	ZP531	223-235	235/55, 245/50, 245/55				
8,5 x 19	Oxigin 25	45	ZP531	223-235	235/55				
	Oxigin 28	38	ZP531	223-235	235/55				
8 x 20	RC36	40	-	223-235	235/55, 245/50, 255/45			Orig.-Verschr.	
	B43	40	-	223-235	235/55, 245/50, 255/45			Orig.-Verschr.	
	AC-521	43	- +R	223-235	235/55, 245/50, 255/45			Orig.-Verschr. + Red.Ringe 73,1-63,4	
8,5 x 20	RC29	40	-	235	235/55, 245/50, 255/45, 265/45			Orig.-Verschr.	
9 x 20	B40	38,5	-	223-235	275/45			Orig.-Verschr.	
	B43	38,5	-	223-235	275/45			Orig.-Verschr.	
	B37	38,5	-	223-235	255/45, 265/45, 275/45			Orig.-Verschr., ohne Radhausverbr. ab 265/45 ✖	
	B43	38,5	-	223-235	255/45, 265/45, 275/45			Orig.-Verschr., ohne Radhausverbr. ab 265/45 ✖	
	Oxigin 28	40	ZP531	223-235	255/45				
9 x 21	B43	38,5	-	223-235	275/40			Orig.-Verschr.	
	B32	38,5	-	223-235	255/40			Orig.-Verschr.	
9 x 22	AF18	40	-	223-235	265/35, 275/35			Orig.-Verschr., ohne Verbreiter. ✖	
10 x 22	B32	35	-	223-235	265/35, 275/35			Orig.-Verschr., ohne Verbreiter. ✖	

XC90 NEU i.V.		4. Quartal 2022					
Dimension	Design	ET	KIT	KW	Reifendimension		Info

VW		Baujahr		Typ		LK/LZ		Nabe	
Amarok		ab 2016		2H, 2HS2		5/120		65,1	
e1*2007/46*0356*..., e1*2007/46*0750*...									
Sensor - Brocksens 2									
Dimension	Design	ET	KIT	KW	Reifendimension		Info		
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!									
6,5 x 16	Pro1	51	-	90-132	205/75C, 205/16C, 215/75, 215/75C, 215/75CP, 215/16C, 225/70, 225/75, 225/75C, 225/75CP, 235/65, 235/70			Orig.-Verschr.	
7 x 17	AC-V51	55	-	90-132	225/70, 235/65, 235/70, 245/65, 255/60, 255/65			Orig.-Verschr., ohne Verbreiterung ab 255/60 ✖	
	B45	55	-	90-132	225/70, 235/65, 235/70, 245/65, 255/60, 255/65			Orig.-Verschr., ohne Verbreiterung ab 255/60 ✖, nicht Bremse 332mm	
	Pro1	50	-	90-132	215/65, 215/70, 225/65, 225/70, 225/70C 245/60, 245/65, 245/70, 255/60, 255/65			Orig.-Verschr., ohne Radhausverbreiterung Orig.-Verschr., mit Radhausverbreiterung	
7,5 x 17	RC25	47	-	90-190	245/65, 245/70, 255/60, 255/65, 265/60, 275/60			Orig.-Verschr., mit Radhausverbreiterung	
		53	-	90-132	235/65, 235/70			Orig.-Verschr., mit Radhausverbreiterung	
			-	90-190	245/65, 245/70, 255/60, 255/65				
8,5 x 17	8400 Bluster	45	-	90-190	245/60, 245/65, 255/60, 255/65, 265/60, 265/65			Orig.-Verschr., mit Radhausverbreiterung	
7,5 x 18	B45	45	-	90-120	265/60			Orig.-Verschr., mit Radhausverbreiterung	
				90-190	255/60				
				90-165	265/60			Orig.-Verschr., ohne Radhausverbr. ✖	
				90-190	245/60, 255/55, 255/60, 265/60				
	RC25T	45	-	90-190	245/60, 255/55, 255/60, 265/60			Orig.-Verschr., mit Radhausverbreiterung	
	RC32	60	-	90-190	245/55, 255/55+C			Orig.-Verschr., mit Radhausverbreiterung	
AC-V51	50	-	90-190	245/60, 255/55, 255/60, 265/60		Orig.-Verschr., ohne Radhausverbreiterung ✖			
8 x 18	RC32	50	-	90-190	245/55, 245/60, 255/55+C, 255/60, 265/55, 275/50, 285/50			Orig.-Verschr., nur mit Radhausverbreiterungen auflagenfrei!	
	AC-V51	50	-	90-190	245/60, 255/55, 255/60			Orig.-Verschr., nur mit Radhausverbreiterungen auflagenfrei!	
	8400 Bluster	50	-	90-190	245/55, 245/60, 255/55, 255/55C, 255/60, 265/55, 265/60, 275/50, 285/50			Orig.-Verschr., nur mit Radhausverbreiterungen auflagenfrei!	
8 x 19	RC34	58	-	90-132	235/55, 255/45			Orig.-Verschr.	
				90-190	245/50, 255/50			Orig.-Verschr., mit Radhausverbreiterung	
8,5 x 19	RC25	50	-	90-190	255/50, 255/55			Orig.-Verschr., mit Radhausverbreiterung	
	B32	50	-	90-190	255/50, 255/55			Orig.-Verschr., mit Radhausverbreiterung	
	B37	50	-	90-190	255/50, 255/55			Orig.-Verschr., mit Radhausverbreiterung	
	B41	45	-	90-190	245/50, 245/55, 255/50, 255/55, 265/50, 275/45			Orig.-Verschr., mit Radhausverbreiterung	
	AF18	47	-	90-190	255/50, 255/55, 265/50			Orig.-Verschr., mit Radhausverbreiterung	
	Oxigin 14	40	-	90-190	255/50, 255/55, 275/45			Orig.-Verschr., mit Radhausverbreiterung	
	Oxigin 18	40	-	90-190	255/50			Orig.-Verschr., mit Radhausverbreiterung	
8 x 20	B40	43	-	90-190	255/50			Orig.-Verschr., mit Radhausverbreiterung	
				90-165	265/50			Orig.-Verschr., ohne Radhausverbr. ✖	
					-	90-190	245/50, 255/45, 255/50, 265/50		
9 x 20	B45	43	-	90-190	255/50			Orig.-Verschr., mit Radhausverbreiterung	
	B37	45	-	90-165	255/45, 255/50, 265/45, 265/50, 275/45			Orig.-Verschr., mit Radhausverbreiterung	
	B40	45	-	90-190	245/45, 255/45, 255/50, 265/45, 275/40, 275/45		Orig.-Verschr., mit Radhausverbreiterung		
	AC-522	45	-	90-190	255/45		Orig.-Verschr., mit Radhausverbreiterung		
	Oxigin 18	40	-	90-165	255/45, 255/50, 265/45, 275/40, 275/45		Orig.-Verschr., mit Radhausverbreiterung		
	Oxigin 19 / 20	42	-	90-165	255/45, 265/45		Orig.-Verschr., mit Radhausverbreiterung		
8400 Bluster	44	-	90-190	245/45, 255/45, 255/50, 265/45, 275/40, 275/45		Orig.-Verschr., mit Radhausverbreiterung			
9 x 21	B32	57	-	90-190	255/40			Orig.-Verschr., mit Radhausverbreiterung	

Amarok	NEU	2. Quartal 2023	T1	6/139,7	93,1	e5*2018/858*00042*..
Sensor - Brocksens 4						

Dimension	Design	ET	KIT	KW	Reifendimension			Info	
7 x 16	RC31	55	-	125	255/70, 265/70, 265/70C, 275/70			Orig.-Verschr., nicht Bremse 341x34mm VA u. nicht 332x24mm HA	
7 x 17	RC31	55	-	125	255/65, 255/70			Orig.-Verschr.	
	B45	55	-	125	255/65, 255/70			Orig.-Verschr.	
7,5 x 17	RC35	55	-	125-151	255/65, 255/70 , 265/65, 275/60, 275/65			 Orig.-Verschr.	
8,5 x 17	8400 Bluster	50	-	125-151	255/65, 255/70, 265/65, 275/60, 275/65			Orig.-Verschr. ✖	
7,5 x 18	B45	55	-	125-177	255/65, 265/60				Orig.-Verschr.
				125	255/60				
8 x 18	RC31	55	-	125-177	255/60, 255/65, 265/55, 265/60, 275/60			Orig.-Verschr.	
8 x 20	B45	55,1	-	125	255/50				Orig.-Verschr.
				125-177	255/55				
9 x 20	8400 Bluster	48	-	125-177	255/50, 255/55, 265/45, 265/50, 275/45, 275/50, 285/45, 285/50			Orig.-Verschr., ✖	

Arteon	ab 06.2017	3H	5/112	57,1	e1*2007/46*1725*..
Sensor - Brocksens 2					

Dimension	Design	ET	KIT	KW	Reifendimension		Info		
	RC27	38	-	110-206	215/55, 225/50, 225/55, 235/50			Orig.-Verschr., nur M+S, auch Shooting Brake	

7 x 17	RC32	38	-	110-206	215/50, 215/55 , 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., nur M+S	
	RC27	35+40	-	110-206	215/55, 225/50, 225/55, 235/50		Orig.-Verschr., nur M+S, auch Shooting Brake	
	RC30	38	-	110-206	215/55, 225/50, 225/55, 235/50		Orig.-Verschr., nur M+S	
		40	-	110-206	215/55, 225/50, 225/55, 235/50		Orig.-Verschr., nur M+S	
	RC32	39+40	-	110-206	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., nur M+S	
	RC34	40	-	110-206	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., nur M+S, auch Shooting Brake	
7,5 x 17	B39	40	-	110-206	215/55, 225/50, 225/55, 235/50		Orig.-Verschr., nur M+S	
	RC27	40	-	110-206	215/55M+S, 225/50, 225/55 , 235/50, 245/50		Orig.-Verschr., auch Shooting Brake	
	RC24	35	-	110-206	215/55M+S, 225/50, 225/55, 235/50		Orig.-Verschr., auch Shooting Brake	
	RC34	40	-	110-206	215/50M+S, 215/55M+S, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr., auch Shooting Brake u. Hybrid	
	RC28	35	ZP560D	110-206	215/55M+S, 225/50, 225/55, 235/50			
	RC29	35	ZP560D	110-206	215/55M+S, 225/50, 225/55, 235/50		auch Shooting Brake	
	B24	35	ZP560D	110-206	215/55M+S, 225/50, 225/55, 235/50		auch Shooting Brake	
7 x 18	B36	35	ZP560D	110-206	215/55M+S, 225/50, 225/55, 235/50		auch Shooting Brake	
	Oxigin 25	45	ZP560D	110-206	215/55M+S			
	RC27	43	-	110-206	225/45, 225/50		Orig.-Verschr.	
		45			225/45		Orig.-Verschr.	
	RC32	35+40	-	110-206	215/50, 225/45, 225/50		Orig.-Verschr., nur M+S, auch Shooting Brake	
	7,5 x 18	RC32	40	-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Shooting Brake, 215er Reifen nur M+S
		RC34	35	-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Shooting Brake, 215er Reifen nur M+S
40			-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr., auch Shooting Brake, 215er Reifen nur M+S	
RC30		35	ZP560D	110-206	215/50M+S, 225/45, 225/50, 235/45, 245/45		auch Shooting Brake	
B32		35	ZP560D	110-206	215/50M+S, 225/45, 225/50, 235/45, 245/45			
B39		35	ZP560D	110-206	215/50M+S, 225/45, 225/50, 235/45, 245/45		auch Shooting Brake	
Oxigin 18		45	-	110-206	225/45, 235/45		Orig.-Verschr.	
RC27		40	-	110-206	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr. , auch Shooting Brake	
RC29		40	-	110-206	225/45, 225/50, 235/45, 245/40, 245/45 , 255/45		Orig.-Verschr., ohne Shooting Brake	
8 x 18		RC32	40	-	110-206	245/45		Orig.-Verschr.
	110-235				215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45, 255/45		Orig.-Verschr., auch Shooting Brake	
	RC34	40	-	110-206	225/45, 225/50, 235/45, 245/45 , 255/45		Orig.-Verschr.	
	B38	40	-	110-206	245/45		Orig.-Verschr.	
	FMI07 Atena	40	-	110-206	245/45		Orig.-Verschr.	
	RC27	44	-	110-206	225/45		Orig.-Verschr.	
	B36 / B37	35	ZP560D	110-206	225/45, 225/50, 235/45, 245/40, 245/45		auch Shooting Brake	
	B38 / B42	35	ZP560D	110-206	225/45, 225/50, 235/45, 245/40, 245/45		auch Shooting Brake	
	B44	30	ZP560D	110-206	225/45, 235/45		auch Shooting Brake	
		35	ZP560D	110-206	225/45, 225/50, 235/45, 245/40, 245/45		auch Shooting Brake	
	AC-M10	40	- +R	110-206	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake	
	AC-518	40	AV4+R	110-206	225/45, 225/50, 235/45, 245/40, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1	
	AF18	35	AV1	110-206	225/45, 225/50, 235/45, 245/40, 245/45			
		40	AV1	110-206	225/45, 225/50, 235/45, 245/40, 245/45, 255/45			
	AF20	28	AV1	110-206	225/45, 235/45		nicht Shooting Brake	
		35	AV1	110-206	225/45, 225/50, 235/45, 245/40, 245/45		nicht Shooting Brake	
	CA 17	45	ZP560D	110-206	225/45			
	FMI08 Thoe	34	F31+R	110-235	215/45M+S, 215/50M+S, 225/45, 225/50, 235/45, 245/40, 245/45		+ Red.Ringe BA25=66,6-57,1	
7,5 x 19	RC34	40	-	110-206	225/40, 225/45		Orig.-Verschr., auch Shooting Brake	
	Oxigin 18	37	-	110-206	225/40, 225/45		Orig.-Verschr.	
8 x 19	RC29	40	-	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., auch Shooting Brake	
	RC32	40	-	110-235	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., auch Shooting Brake u. Hybrid	
	RC34	40	-	110-235	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., auch Shooting Brake u. Hybrid	
	B38	40	-	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., auch Shooting Brake	
	B40	40	-	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., auch Shooting Brake	
	B43	40	-	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., auch Shooting Brake u. Hybrid	
	RC27	44	-	110-206	225/40, 225/45		Orig.-Verschr.	
	RC29	35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40			
		27	ZP560D	110-206	225/40, 225/45			
	RC34	38	ZP560D	110-206	225/40, 225/45, 235/40, 245/35, 245/40		auch Shooting Brake	
		35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40			
	B24	35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40			
	AC-518	38	AV4+R	110-206	225/40, 225/45, 235/40, 245/40		+ Red.Ringe BA25=66,6-57,1	
	AC-521	35	- +R	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake	
	CA 17	37	ZP560D	110-206	225/40, 225/45, 235/40			
		45	ZP560D	110-206	225/40, 225/45			
	FMI07 Atena	39	- +R	110-206	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
	Oxigin 29	32+39	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		auch Shooting Brake	
	RC32	38	-	110-235	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., auch Shooting Brake	
	RC34	38	-	110-235	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr., auch Shooting Brake	

8,5 x 19	B32	34,5	ZP560D	110-206	225/40, 225/45, 235/40		
	B37	35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		auch Shooting Brake
	B41	36	ZP560D	110-235	225/40, 225/45, 235/40, 245/35, 245/40		auch Shooting Brake
		39	ZP560D	110-235	225/40, 225/45, 235/40, 245/35, 245/40, 255/35, 255/40		auch Shooting Brake
	B42	30	ZP560D	110-206	225/40, 225/45		
		35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		ohne Shooting Brake
	B43	38	ZP568F	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		auch Shooting Brake
	B44	30	ZP560D	110-206	225/40, 225/45		auch Shooting Brake
		35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		auch Shooting Brake
	AC-M10	40	- +R	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	AF18	40	AV1	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		
	AF20	40	- +R	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , nicht Shooting Brake
	CA 20 / CA 23	40	- +R	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	FMI11 Elatha	32	- +R	110-235	225/40, 225/45, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	Oxigin 18	35	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		
	Oxigin 25	35	ZP560D	110-206	225/40, 225/45		
	Oxigin 28	30	ZP560D	110-206	225/40, 225/45		auch Shooting Brake
		40	ZP560D	110-206	225/40, 225/45, 235/40, 245/40, 255/35, 255/40		auch Shooting Brake
8 x 20	B38	40	-	110-206	235/35, 245/30, 245/35		Orig.-Verschr., auch Shooting Brake
	B40	40	-	110-206	235/35, 245/30, 245/35		Orig.-Verschr., auch Shooting Brake
	B43	39	ZP560D	110-206	235/35, 245/30, 245/35		auch Shooting Brake
8,5 x 20	RC29	38	-	110-206	235/35, 245/30, 245/35, 255/30, 255/35		Orig.-Verschr., auch Shooting Brake
	B43	38+40	-	110-206	235/35, 245/30, 245/35, 255/30, 255/35		Orig.-Verschr., auch Shooting Brake
	B24	33	ZP560D	110-206	235/35		
	B32	40	ZP560D	110-206	235/35, 245/30, 245/35, 255/30, 255/35		nicht Shooting Brake
	B41	35	ZP560D	110-206	225/35, 235/35		
	B42	35	ZP560D	110-206	235/35, 245/30, 245/35		auch Shooting Brake
		40	ZP560D	110-206	235/35, 245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	B43	40	ZP560D	110-206	235/35, 245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	B44	35	ZP560D	110-206	235/35, 245/30, 245/35		auch Shooting Brake
		40	ZP560D	110-206	235/35, 245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	CA 17	40	ZP560D	110-206	235/35		
	AC-M10	40	- +R	110-206	235/35, 245/30, 245/35, 255/30, 255/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
9 x 20	FMI07 Atena	39	- +R	110-206	225/35, 235/35, 245/30, 245/35, 255/30, 255/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	B37	37	ZP560D	110-206	245/30, 245/35		auch Shooting Brake
	B41	38	ZP560D	110-206	225/35, 235/35, 245/30, 245/35		
8,5 x 21	B41	40	-	110-235	245/30, 255/30		Orig.-Verschr., auch Shooting Brake
	B43	40	-	110-206	245/30, 255/30		Orig.-Verschr., auch Shooting Brake
	B41	37	ZP560D	110-235	245/30		auch Shooting Brake
		40	ZP560D	110-235	245/30, 255/30		auch Shooting Brake
	B43	38	ZP568F	110-206	245/30, 255/30		auch Shooting Brake
9 x 21	B32	40	ZP560D	110-206	245/30		

Arteon R NEU im Laufe 1. Quartal 2021 3H 5/112 57,1 e1*2007/46*1725*..							
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC27	40	-	235	245/40, 245/45 , 255/45		Orig.-Verschr., auch Shooting Brake
	B38	40	-	235	245/40, 245/45 , 255/45		Orig.-Verschr., auch Shooting Brake
	B24 / B37	35	ZP560D	235	245/40, 245/45		
	B36 / B38	35	ZP560D	235	245/40, 245/45		auch Shooting Brake
	B42 / B44	35	ZP560D	235	245/40, 245/45		auch Shooting Brake
8 x 19	AC-M10	40	- +R	235	245/40, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	B40	40	-	235	245/40		Orig.-Verschr., auch Shooting Brake
	B43	40	-	235	245/40		Orig.-Verschr., auch Shooting Brake
	B38	40	-	235	245/40		Orig.-Verschr., auch Shooting Brake
	RC29	40	-	235	245/40		Orig.-Verschr., auch Shooting Brake
	AC-521	35	- +R	235	245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	Oxigin 29	32+39	ZP560D	235	245/40		auch Shooting Brake
8,5 x 19	B37	35	ZP560D	235	245/40		auch Shooting Brake
	B43	38	ZP568F	235	245/40, 255/35, 255/40		auch Shooting Brake
	B44	35	ZP560D	235	245/40		auch Shooting Brake
	AC-M10	40	- +R	235	245/40, 255/35, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	CA 20 / CA 23	40	- +R	235	245/40, 255/35, 255/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , auch Shooting Brake
	Oxigin 28	40	ZP560D	235	245/40, 255/35, 255/40		auch Shooting Brake

8 x 20	B40	40	-	235	245/35		Orig.-Verschr., auch Shooting Brake
	B38	40	-	235	245/30, 245/35		Orig.-Verschr., auch Shooting Brake
	B38	35	ZP560D	235	245/30, 245/35		auch Shooting Brake
	B43	39	ZP560D	235	245/30, 245/35		auch Shooting Brake
8,5 x 20	RC29	38	-	235	245/30, 245/35, 255/30, 255/35		Orig.-Verschr., auch Shooting Brake
	B43	38+40	-	235	245/30, 245/35, 255/30, 255/35		Orig.-Verschr., auch Shooting Brake
	RC29	40	ZP560D	235	245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	B42	35	ZP560D	235	245/30, 245/35		auch Shooting Brake
		40	ZP560D	235	245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	B44	35	ZP560D	235	245/30, 245/35		auch Shooting Brake
		40	ZP560D	235	245/30, 245/35, 255/30, 255/35		auch Shooting Brake
	AC-M10	40	- +R	235	245/30, 245/35, 255/30, 255/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, auch Shooting Brake
9 x 20	B37	37	ZP560D	235	245/30, 245/35		auch Shooting Brake
8,5 x 21	B43	40	-	235	245/30, 255/30		Orig.-Verschr., auch Shooting Brake
	B43	38	ZP568F	235	245/30, 255/30		auch Shooting Brake

Beetle / Cabrio II (siehe Konfigurator)	ab 10.11	16	5/112	57,1	e1*2007/46*0539*...
---	----------	----	-------	------	---------------------

Caddy IV (siehe Konfigurator)	ab MJ2016	2K, 2KN	5/112	57,1	e1*2001/116*0252*42-..., e1*2007/46*0217*20-...
-------------------------------	-----------	---------	-------	------	---

Caddy Alltrack IV (siehe Konfigurator)	ab MJ2016	2K, 2KN	5/112	57,1	e1*2001/116*0252*44-..., e1*2007/46*0217*20-...
--	-----------	---------	-------	------	---

Caddy Maxi IV (siehe Konfigurator)	ab MJ2016	2K, 2KN	5/112	57,1	e1*2001/116*0252*42-..., e1*2007/46*0217*20-...
------------------------------------	-----------	---------	-------	------	---

Caddy V	ab Jänner 2021	SK, SKN	5/112	57,1	e13*2018/858*00002*..., e13*2018/858*00003*..
---------	----------------	---------	-------	------	---

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6 x 15	RC30	47	-	55, 75	205/65, 215/65, 225/60	 Orig.-Verschr., nur Bremse 288mm
	RC24	43	-	55, 75	205/65, 215/65	Orig.-Verschr., nur Bremse 288mm
		47	-	55, 75	205/65, 215/65, 225/60	 Orig.-Verschr., nur Bremse 288mm
	RC30	43	-	55, 75	205/65, 215/65	Orig.-Verschr., nur Bremse 288mm
6 x 16	RC30	48	-	55, 75	205/60, 215/55, 215/60, 225/55	Orig.-Verschr.
6,5 x 16	RC30	48	-	55-90	205/60	 Orig.-Verschr.
	RC32	48	-	55-90	205/60, 215/55, 215/60	 Orig.-Verschr.
	RC34	48	-	55-90	205/60, 215/55, 215/60	 Orig.-Verschr.
	RC24	46+50	-	55-90	205/60, 215/55, 215/60	Orig.-Verschr.
	RC27	46+50	-	55-90	205/60, 215/55, 215/60	Orig.-Verschr.
	RC32	46	-	55-90	205/60, 215/55, 215/60	Orig.-Verschr.
	RC34	43	-	55-90	205/60	Orig.-Verschr.
		46	-	55-90	205/60, 215/55, 215/60	Orig.-Verschr.
	CA 20	45	ZP560D	55-90	205/60	
	Pro1	48	F31+R	55-90	205/60, 215/55, 215/60	 + Red.Ringe BA25=66,6-57,1
6,5 x 17	RC27	49	-	55-96	205/55, 215/50, 215/55	 Orig.-Verschr.
	RC34	49	-	55-90	215/55	 Orig.-Verschr.
	RC27	48,5	-	55-90	205/55, 215/50, 215/55	Orig.-Verschr.
7 x 17	RC27	46+47	-	55-90	205/55	Orig.-Verschr.
	RC30	45+49	-	55-90	205/55	Orig.-Verschr.
	RC32	47	-	55-90	205/50, 205/55, 225/45	Orig.-Verschr.
		49	-	55-90	205/55, 215/50, 215/55	Orig.-Verschr.
	B39	49	-	55-90	205/55	Orig.-Verschr.
7,5 x 17	RC32	49	-	55-90	205/50, 205/55, 225/45	Orig.-Verschr.
		51	-	55-90	205/55, 215/50, 215/55, 235/45	Orig.-Verschr.
	RC34	51	-	55-90	205/50, 205/55, 215/50, 215/55, 235/45	Orig.-Verschr.
	B24	47	ZP560D	55-90	205/55	
	Oxigin 25	45	ZP560D	55-90	205/50, 205/55	
	CA 20	47	ZP560D	55-90	205/55	
7 x 18	RC32	49	-	55-90	225/45	 Orig.-Verschr.
	RC34	49	-	55-90	225/45	 Orig.-Verschr.
				55-90	205/45, 205/50, 215/45, 215/50, 225/45	
	RC32	40	-	55-90	205/45	Orig.-Verschr.
		45	-	55-90	205/45, 205/50, 215/45	Orig.-Verschr.
7,5 x 18	RC27	45	-	55-90	215/45, 225/45	 Orig.-Verschr.
	RC32	49+50+51	-	55-90	205/45, 205/50, 215/45, 225/40, 225/45	Orig.-Verschr.
		46	-	55-90	205/45, 215/45	Orig.-Verschr.
	RC34	49+50	-	55-90	205/45, 205/50, 215/45, 225/40, 225/45	Orig.-Verschr.
		46+49	-	55-90	215/45	Orig.-Verschr.
	B32	48	-	55-90	215/45, 225/45	Orig.-Verschr.
		49	-	55-90	215/45	Orig.-Verschr.
	RC30	45	ZP560D	55-90	215/45	
	Oxigin 25	44	ZP560D	55-90	215/45, 225/45	
	RC34	44+45	-	55-90	205/45	Orig.-Verschr.

8 x 18	B24	48	ZP560D	55-90	215/45		
	FMI08 Thoe	49	F31+R	55-90	205/45, 215/45		+ Red.Ringe BA25=66,6-57,1
7,5 x 19	RC32	50+51	-	55-90	205/45, 225/40		Orig.-Verschr.
	RC34	48	-	55-90	225/40		Orig.-Verschr.
		50+51	-	55-90	225/40		Orig.-Verschr.

Crafter (siehe Konfigurator)	ab 05.06	2EK, 2EC	6/130	84,1	e1*2001/116*0355*...., e1*2001/116*0356*...., L770, L767, L768, L769, e1*2007/46*0513*...
------------------------------	----------	----------	-------	------	---

Crafter	ab 2017	SYN1E, SYMWE	5/120	65,1	e1*2007/46*1613*..., e1*2007/46*1935*..
---------	---------	--------------	-------	------	---

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC25T	60	-	103, 130	235/65C		Orig.-Verschr., nur Heckantrieb, geschl. Aufbau
					205/75C, 235/65C		Orig.-Verschr., Allrad, geschl. Aufbau
		75,103,130	205/75C, 235/65C		Orig.-Verschr., auch Allrad		
	Pro1	51	-	75-130	205/75C, 225/65C, 225/65CP, 235/65C, 235/65CP		Orig.-Verschr., geschlossener Kasten
7 x 17	B45	55	-	75,103,130	235/60C		Orig.-Verschr., Frontantrieb, geschl. Aufbau
				90-130	235/60C		Orig.-Verschr., Heckantrieb, geschl. Aufbau
		103, 130	235/60C		Orig.-Verschr., Allrad, geschl. Aufbau		
	AC-V51	55	-	75,103,130	235/60C		Orig.-Verschr., Frontantrieb, geschl. Aufbau
103, 130				235/60C		Orig.-Verschr., Heck- u. Allradantrieb	
7,5 x 17	RC25	55	-	75,103,130	235/60C		Orig.-Verschr., Frontantrieb, geschl. Aufbau
				103, 130	235/60C		Orig.-Verschr., Allrad, geschl. Aufbau
8 x 20	B45	52	-	75-130	235/45C		Orig.-Verschr., Front- u. Heckantrieb
				103, 130	235/45C		Orig.-Verschr., Allrad, geschl. Aufbau

Crafter	ab 2019	SYN2E, SYMVE	5/120	65,1	e1*2007/46*1614*..., e1*2007/46*1953*..
---------	---------	--------------	-------	------	---

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC25T	60	-	75-130	205/75C, 235/65C		Orig.-Verschr., nur Frontantrieb, geschl. Aufbau
				90-130	235/65C		Orig.-Verschr., nur Heckantrieb, geschl. Aufbau
				103, 130	235/65C		Orig.-Verschr., Allrad, geschl. Aufbau
7 x 17	B45	55	-	75-130	235/60C		Orig.-Verschr., Frontantrieb, geschl. Aufbau
				90-130	235/60C		Orig.-Verschr., Heckantrieb, geschl. Aufbau
				103, 130	235/60C		Orig.-Verschr., Allrad, geschl. Aufbau
8 x 20	B45	52	-	75-130	235/45C		Orig.-Verschr., Front- u. Heckantrieb
				103, 130	235/45C		Orig.-Verschr., Allrad, geschl. Aufbau

Golf VII / -Variant	ab 10.12	AU, AUV	5/112	57,1	e1*2007/46*0623*...., e1*2007/46*0627*...., e1*2007/46*0490*05-... , e1*2007/46*0492*06-..
---------------------	----------	---------	-------	------	--

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC24	43	-	63-110	195/65		Orig.-Verschr., Bremse max. 288mm
				63-110	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, auch Allrad, Bremse max. 288mm
				81	185/70		
	47	-	90	195/65, 205/50			
	RC27	43	-	63-110	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, auch Allrad, max. Bremse 288mm
RC30	43	-	63-110	195/65, 205/60		Orig.-Verschr., incl. FL2017, nur Bremse 288mm	
6 x 16	RC27	48	-	63-162	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017, Bremse max. 312mm, auch Variant
	RC30	48	-	63-162	205/55, 215/55		Orig.-Verschr.,incl. FL2017, Bremse max. 312mm
	RC34	48	-	63-162	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
6,5 x 16	RC24	46	-	63-110	205/55		Orig.-Verschr.
	RC27	46	-	63-162	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2017
	RC30	46	-	63-162	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2017, nur Bremse 312mm
	RC32	46	-	63-162	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	46	-	63-162	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
7 x 17	RC34	49	-	63-180	225/45		Orig.-Verschr.
	RC30	49	-	63-169	225/45		Orig.-Verschr., incl. FL2017, auch Allrad
	RC32	49	-	63-169	225/45		Orig.-Verschr.
	RC34	49	-	63-180	225/45		Orig.-Verschr.
	B39	49	-	63-169	225/45		Orig.-Verschr., incl. FL2017, auch Allrad
7,5 x 17	RC27	49	-	63-180	225/45		Orig.-Verschr., incl. Facelift 2017
	RC29	49	-	63-162	225/45		Orig.-Verschr., incl. Facelift 2017, nicht Bremse 340mm
	RC32	49	-	63-180	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC30	49+51	-	63-195	225/40		Orig.-Verschr.
7,5 x 18	RC32	49	-	110-180	225/40		Orig.-Verschr.
	B32	51	-	63-180	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
		49	-	63-213	225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
		51	-	63-195	225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	B39	49+51	-	63-195	225/40		Orig.-Verschr., incl. Facelift 2017, beide ET's ECE
	Oxigin 18	51	-	63-221	225/40		Orig.-Verschr.

7,5 x 19	Oxigin 18	51	-	90-169	215/35, 225/35		Orig.-Verschr.
	RC32	51	-	63-180	225/35		Orig.-Verschr.
	RC34	51	-	90-180	225/35		Orig.-Verschr., auch Hybrid
	B32	51	-	63-195	225/35		Orig.-Verschr., incl. Facelift 2017
	B39	51	-	63-195	215/35, 225/35		Orig.-Verschr., incl. Facelift 2017
	CA 26	51	-	63-195	225/35		Orig.-Verschr., incl. Facelift 2017
8 x 19	RC27	50	-	206-221	235/35		Orig.-Verschr.
	RC32	50	-	195, 228	235/35		Orig.-Verschr., i.V.
	B38	50	-	195	235/35		Orig.-Verschr., incl. Facelift 2017
	B40	50	-	195, 213	235/35		Orig.-Verschr., incl. Facelift 2017, 215er nur bis 169 KW
	B43	50	-	195, 213	235/35		Orig.-Verschr., incl. Facelift 2017

Golf VII R (siehe Konfigurator)	ab 2013	AU	5/112	57,1	Limo: e1*2007/46*0623*..., Kombi: e1*2007/46*0627*...
--	----------------	-----------	--------------	-------------	--

Golf VII Alltrack	ab 2015	AUV	5/112	57,1	e1*2007/46*0627*...
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	43	-	81-135	205/50, 205/55, 215/50, 225/50		Orig. Verschr.
		39+46+48,5	-	81-135	205/50, 205/55, 215/50		Orig. Verschr.
7 x 17	RC27	42	-	81-135	205/50, 205/55 , 215/50, 225/45		Orig.-Verschr.
		38	-	81-135	205/50, 205/55, 225/45		Orig. Verschr.
		43	-	81-135	205/50, 205/55, 215/50, 225/45		Orig. Verschr.
	RC30	38	-	81-135	205/50, 205/55, 215/45, 225/45		Orig. Verschr.
		40+45	-	81-135	205/50, 205/55, 215/50, 225/45		Orig. Verschr., incl. Facelift 2017
	RC32	38	-	81-135	205/50, 205/55, 215/50, 225/45		Orig. Verschr.
		45	-	81-135	205/50, 205/55, 215/45, 215/50, 225/45, 225/50		Orig. Verschr.
		46+47+49	-	81-135	205/50, 205/55, 215/45, 215/50, 225/45		Orig. Verschr.
	B39	40	-	81-135	205/50, 205/55, 215/50, 225/45		Orig. Verschr.
	RC27	45	ZP568F (V10)	81-135	205/50, 205/55, 215/50, 225/45		incl. Facelift 2017, Ausführung "V10"
7,5 x 17	RC24	42	-	81-135	205/50, 205/55, 225/45		Orig. Verschr.
	RC27	40	-	81-135	215/45		Orig. Verschr.
		41	-	81-135	205/50, 205/55, 225/45		Orig. Verschr.
	RC24	42	ZP560D	81-135	205/50, 205/55, 225/45		
	RC28 / RC29	45	ZP560D	81-135	205/50, 205/55, 225/45		
	B36	45	ZP560D	81-135	205/50, 205/55, 225/45		
7 x 18	AC-518	42	AV4+R	81-135	205/50, 205/55, 225/45		incl. Facelift 2017, + Red.Ringe BA25=66,6-57,1
7,5 x 18	RC32	35+40+43+45	-	81-135	205/40, 205/45, 215/40, 215/45, 225/45		Orig. Verschr., ET35 nicht 225/45
	RC32	45	-	81-135	225/45		Orig. Verschr., Variant Alltrack
		48	-	81-135	205/40, 205/45, 215/40, 215/45, 225/40		Orig. Verschr.
		49	-	81-135	205/40, 205/45, 215/40, 225/35, 225/40		Orig. Verschr.
	RC34	46	-	81-135	205/40, 205/45, 215/40, 215/45, 225/40, 225/45		Orig. Verschr.
		40+49	-	81-135	205/40, 205/45, 215/40, 215/45, 225/40		Orig. Verschr.
8 x 18	B32 / B39	45	ZP560D	81-135	205/45, 215/45, 225/40, 225/45		
	RC27	44	-	81-135	215/40, 215/45		Orig. Verschr.
	RC29	44	-	81-135	215/45, 225/40, 225/45		Orig. Verschr.
	RC32	40	-	81-135	205/40, 205/45, 215/40, 215/45		Orig. Verschr.
		44+46	-	81-135	205/40, 205/45, 215/40, 215/45, 225/40, 235/35		Orig. Verschr.
	RC34	40	-	81-135	205/40, 205/45, 215/40, 215/45		Orig. Verschr.
		44+45	-	81-135	205/40, 205/45, 215/40, 215/45, 225/40, 235/35		Orig. Verschr.
	B37	44	-	81-135	215/45, 225/40, 225/45		Orig. Verschr.
	B38	44	-	81-135	215/45, 225/40, 225/45		Orig. Verschr.
	RC34	34	ZP568F	81-135	205/40, 205/45		
		40	ZP560D	81-135	205/40, 205/45, 215/40, 215/45		
		43+48	ZP560D	81-135	205/40, 205/45, 215/40, 215/45, 225/40		
	B37 / B38	45	ZP560D	81-135	215/45, 225/40, 225/45		
	B36 / B42	45	ZP560D	81-135	215/45, 225/40, 225/45		
	B44	45	ZP560D	81-135	215/45, 225/40, 225/45		incl. FL2017
	AC-518	40	AV4+R	81-135	215/45		incl. FL2017, + Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	81-135	215/45, 225/40, 225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2017
	AC-M10	45	AV4+R	81-135	215/45, 225/40, 225/45		+ Red.Ringe BA25=66,6-57,1 , incl. Facelift 2017
	CA 17	45	ZP560D	81-135	215/40, 215/45		
	CA 20	45	ZP560D	81-135	215/45, 225/40, 225/45		
	FMI08 Thoe	49	F31+R	81-135	205/40, 205/45, 215/40, 215/45, 225/40		+ Red.Ringe BA25=66,6-57,1
7,5 x 19	RC34	48	-	81-135	225/35		Orig.-Verschr.
	B32	43	-	81-135	225/35, 225/40		Orig.-Verschr.
	RC34	45,5	ZP560D	81-135	225/35		
	B39	43	ZP560D	81-135	225/35, 225/40		

8 x 19	RC29	40	-	81-135	215/45		Orig.-Verschr.
	RC34	45	-	81-135	225/35		Orig.-Verschr.
	B38	44	-	81-135	225/35, 225/40		Orig.-Verschr.
	B40	45	-	81-135	225/35, 225/40		Orig.-Verschr.
	B43	45	-	81-135	225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	RC29	45	ZP560D	81-135	225/35, 225/40		
	RC34	43+48	ZP560D	81-135	225/35		
	B24	45	ZP560D	81-135	225/35, 225/40		
	B38	45	ZP560D	81-135	225/35, 225/40		
	B40	43	ZP560D	81-135	225/35, 225/40		
		45	-	81-135	225/35, 225/40		Orig.-Verschr.
	AC-521	45	-	81-135	225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
8 x 20	FMI07 Atena	47	- +R	81-135	225/35		Orig.-Verschr. + Ringe BA25=66,6-57,1
	Oxigin 29	43	ZP560D	81-135	225/35, 225/40		incl. Facelift 2017
8 x 20	B43	45	-	81-135	225/35		Orig.-Verschr., incl. Facelift 2017

Golf VII Sportsvan	ab 2014	AUV	5/112	57,1	e1*2007/46*0627*..., e1*2007/46*0492*08-...
--------------------	---------	-----	-------	------	---

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC24	43	-	63-110	195/65, 205/60		Orig. Verschr., incl. Facelift 2017, max. Bremse 288mm
	RC27	43	-	63-110	195/65, 205/60		Orig.-Verschr., nur Bremse 288mm
	RC30	43	-	63-110	195/65		Orig.-Verschr.
					195/65, 205/60		Orig. Verschr.,incl. FL2017,max. Bremse 288mm
	RC27	47	-	63-110	195/65, 205/60		
6 x 16	RC30	47	-	63-110	195/65, 205/60		Orig. Verschr.,incl. FL2017,max. Bremse 288mm
	RC27	48	-	63-110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017, Bremse max. 312mm
	RC30	48	-	63-162	205/55, 215/55		Orig.-Verschr., Bremse max. 312mm
	RC34	48	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC27	43+50	-	63-110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017, Bremse max. 312mm
	RC30	43+50	-	63-110	205/55, 215/55		Orig.-Verschr., Bremse max. 312mm
6,5 x 16	RC34	43	-	63-110	195/55, 195/60, 205/55, 215/50, 225/50		Orig.-Verschr.
		50	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC27	46	-	63-110	205/55		Orig.-Verschr.
	RC30	46	-	63-110	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2017, max 312mm Bremse
	RC32	46	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	46	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC24	42+43	-	63-110	205/55, 215/55		Orig.-Verschr.,incl. FL2017,Bremse max. 312mm
		46	-	63-110	205/55, 215/55, 225/50		Orig.-Verschr., Bremse max. 312mm
		50	-	63-110	205/55, 215/55, 225/50		Orig.-Verschr.,incl. FL2017,Bremse max. 312mm
	RC27	43	-	63-110	205/55, 215/55		Orig.-Verschr., Bremse max. 312mm
		44+50	-	63-110	205/55, 215/55, 225/50		Orig.-Verschr., ab 92KW Bremse max. 312mm
	RC32	41	-	63-110	195/55, 195/60, 205/55, 215/50		Orig.-Verschr.
		43	-	63-110	195/55, 195/60, 205/55, 215/50, 225/50		Orig.-Verschr.
		48	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	43	-	63-110	195/55, 195/60, 205/55, 215/50, 225/50		Orig.-Verschr.
		48	-	63-110	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
6,5 x 17	RC27	39+43	-	63-110	205/50		Orig.Verschr.
		46+48,5	-	63-110	205/50		Orig.Verschr.
7 x 17	RC30	49	-	63-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	49	-	63-110	205/45, 205/50, 215/45, 225/45		Orig.Verschr.
	RC34	49	-	63-110	225/45		Orig.-Verschr.
	B39	49	-	63-110	205/50, 215/45, 225/45		Orig.Verschr.
	RC27	40+42+ 43+45+ 46+47	-	63-110	205/50, 215/45, 225/45		Orig.Verschr., incl. Facelift 2017
	RC30	40+45	-	63-110	205/50, 215/45, 225/45		Orig.Verschr., incl. Facelift 2017
	RC32	45+46+ 47	-	63-110	205/45, 205/50, 215/45, 225/45		Orig.Verschr.
	B39	40	-	63-110	205/50, 215/45, 225/45		Orig.Verschr.
	RC32	49	-	63-110	225/45		Orig.-Verschr.
7,5 x 17	RC24	51	-	63-110	205/50, 215/45, 225/45		Orig.Verschr.
	RC29	49	-	63-110	205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
		51	-	63-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	43	-	63-110	205/45, 215/45, 225/45		Orig.-Verschr.
	RC28 / RC29	45	ZP560D	63-110	205/50, 215/45, 225/45		
		45	ZP560D	63-110	205/50, 215/45, 225/45		
	AC-518	42	AV4+R	63-110	215/45		+ Red.Ringe BA25=66,6-57,1, incl. FL2017
		47	AV4	63-110	205/50, 215/45, 225/45, 235/45		incl. Facelift 2017
7 x 18	RC32	35+40+ 43	-	63-110	205/40, 215/40		Orig.-Verschr.

		45	-	63-110	205/40, 205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC30	51	-	63-110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	RC32	51	-	63-110	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	B32	51	-	63-110	225/40		Orig.-Verschr.
	B39	51	-	63-110	205/45, 215/40, 225/35, 255/40		Orig.-Verschr.
	Oxigin 18	51	-	63-110	225/40		Orig.-Verschr.
	RC32	48+49	-	63-110	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr., ET48 bei 225/40 ✖
		45	-	63-110	205/40, 215/40, 225/35		Orig.-Verschr.
	RC34	46	-	63-110	205/40, 215/40, 225/35		Orig.-Verschr.
	B32	48	-	63-110	205/45, 215/40, 225/35, 255/40		Orig.-Verschr., incl. Facelift 2017
	B39	49	-	63-110	205/45, 215/40, 225/35, 255/40		Orig.-Verschr.
8 x 18	AC-521	50	-	63-110	205/45, 215/40, 225/35, 255/40		Orig.-Verschr., incl. Facelift 2017
	RC25	50	-	63-110	215/40, 225/35, 225/40		Orig.-Verschr.
	RC27	46	-	63-221	205/40, 215/40, 225/40		Orig.-Verschr., ab 215/40 ✖
	RC29	50	-	63-110	215/40, 225/35, 225/40		Orig.-Verschr.
	RC32	44	-	63-110	205/40, 215/40, 225/35		Orig.-Verschr.
		46	-	63-110	205/40, 215/40, 225/35, 235/35		Orig.-Verschr.
	RC34	40	-	63-110	205/40, 215/40		Orig.-Verschr.
		44+45	-	63-110	205/40, 215/40, 225/35		Orig.-Verschr.
	B37	50	-	63-110	215/40, 225/35, 225/40		Orig.-Verschr.
	B38	50	-	63-110	215/40, 225/35, 225/40		Orig.-Verschr.
8,5 x 18	AF18	48	-	63-110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	CA 20	45	ZP560D	63-110	215/40, 225/35, 225/40		
	B32	48	ZP560D	63-110	215/40, 225/35, 225/40		
	Oxigin 14	50	ZP560	63-110	215/40, 225/35, 225/40		
	RC32	51	-	63-110	215/35, 225/35		Orig.-Verschr.
	RC34	51	-	96-110	225/35		Orig.-Verschr.
				63-110	215/35, 225/35		Orig.-Verschr.
		48	-	63-110	215/35, 225/35		Orig.-Verschr.
	B32	43	-	63-110	215/35, 225/35		Orig.-Verschr.
	B39	51	-	63-110	215/35, 225/35		Orig.-Verschr.
7,5 x 19	AC-521	50	-	63-110	215/35, 225/35		Orig.-Verschr.
	Oxigin 18	51	-	63-169	215/35, 225/35		Orig.-Verschr.
		50	ZP560D	63-169	215/35, 225/35		
	RC29	49	-	63-110	215/35, 225/35		Orig.-Verschr., incl. Facelift 2017
	RC32	50	-	63-110	215/35, 225/30, 225/35		Orig.-Verschr.
	RC34	45	-	63-110	215/35, 225/30		Orig.-Verschr.
		50	-	63-110	215/35, 225/30, 225/35		Orig.-Verschr.
	B38	50	-	63-110	215/35, 225/35		Orig.-Verschr.
	B40	45+49+ 50	-	63-110	215/35, 225/35		Orig.-Verschr., incl. Facelift 2017
	B43	49	-	63-110	215/35, 225/35		Orig.-Verschr., incl. Facelift 2017
8 x 19	RC29	45	ZP560D	63-110	215/35, 225/35, 235/35		bei 235/35 ✖
	RC34	43+48	ZP560D	63-110	215/35, 225/30		
	B24	45	ZP560D	63-110	215/35, 225/35		
	AC-518	47	AV4	63-110	215/35, 225/35		incl. Facelift 2017
	CA 17	43	ZP560D	63-169	215/35, 225/35		nicht Bremse 345mm
	CA 19	47	ZP560D	63-100	215/35, 225/35		
	FMI07 Atena	47	- +R	63-110	215/35, 225/30		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	B42	47	ZP560D	63-110	215/35		incl. Facelift 2017
	AF18	48	-	63-110	215/35, 225/35		Orig.-Verschr.
	B38	48	ZP560D	63-110	225/30, 235/30		ab 235/30 ✖

E-Golf VII		ab 2015		AU	5/112	57,1	e1*2007/46*0623*10-..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 15	RC24	43	-	85, 100	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, nur M+S	
	RC27	43	-	85, 100	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, nur M+S	
	RC30	43	-	85, 100	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, nur M+S	
6,5 x 15		47	-	85, 100	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, nur M+S	
	RC28	44	-	85, 100	195/65, 205/60		Orig.-Verschr., incl. Facelift 2017, nur M+S	
6 x 16	RC27	48	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017	
	RC30	48	-	85, 100	205/55, 215/55		Orig.-Verschr.	
	RC34	48	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.	
	RC27	43+50	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017	
	RC30	43+50	-	85, 100	205/55, 215/55		Orig.-Verschr.	
	RC34	43+50	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.	
	RC27	46	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017	
	RC30	46	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017	
	RC32	46	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.	
	RC34	46	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.	
	RC24	46	-	85	205/55, 215/55		Orig.-Verschr.	

6,5 x 16	RC27	46+50	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017
		42+50	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017
		43	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017
	RC30	39	-	85, 100	205/55		Orig.-Verschr., incl. FL2017
		42+44	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017
		50	-	85, 100	205/55, 215/55		Orig.-Verschr., incl. FL2017
	RC32	41	-	85-100	205/55, 215/50		Orig.-Verschr.
		43	-	85-100	205/55, 215/50, 225/50		Orig.-Verschr.
		48	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	43	-	85-100	205/55, 215/50, 225/50		Orig.-Verschr.
		48	-	85-100	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	Pro1	48	F31+R	85-100	205/55, 215/50, 215/55, 225/50		+ Red.Ringe BA25=66,6-57,1
6,5 x 17	RC27	43	-	85	205/50		Orig.-Verschr.
		46	-	85, 100	205/50		Orig.-Verschr., incl. FL2017
		39+48,5	-	85, 100	205/50		Orig.-Verschr., incl. FL2017
7 x 17	RC30	49	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC32	49	-	85-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	49	-	85-100	225/45		Orig.-Verschr.
	B39	49	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC27	40+42+ 43+45+ 46+47	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. FL2017
	RC30	40	-	85	205/50, 215/45, 225/45		Orig.-Verschr.
		45	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC32	45+46+ 47	-	85-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	B39	40	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
7,5 x 17	RC24	51	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC29	49	-	85, 100	205/50, 215/45, 225/45, 235/45		Orig.-Verschr., incl. Facelift 2017
		51	-	85, 100	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC32	49	-	85-100	205/45, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC28	45	ZP560D	85, 100	205/50, 215/45, 225/45		incl. Facelift 2017
	B24	47	ZP560D	85	205/50, 215/45, 225/45, 235/45		
	AC-518	42	AV4+R	85, 100	215/45		incl. Facelift 2017, + Red.Ringe BA25=66,6-57,1
		47	AV4	85, 100	205/50, 215/45, 225/45, 235/45		incl. Facelift 2017
	RC32	40+43+ 45+52	-	85-100	205/40, 205/45, 215/40		Orig.-Verschr., ET40 nicht 205/45
7,5 x 18	RC30	49+51	-	85, 100	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	RC32	45	-	85-100	205/40, 215/40		Orig.-Verschr.
		48+49	-	85-100	205/40, 205/45, 215/40		Orig.-Verschr.
		51	-	85-100	205/40, 205/45, 215/40, 225/40		Orig.-Verschr.
	RC34	46+49	-	85-100	205/40, 205/45, 215/40		Orig.-Verschr.
		50	-	85-100	205/40, 205/45, 215/40		Orig.-Verschr.
	B32	48+49	-	85, 100	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
		51	-	85, 100	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	B39	49+51	-	85, 100	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	AC-521	50	-	85, 100	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
8 x 18	RC25	50	-	85	215/40, 225/35, 225/40		Orig.-Verschr.
	RC29	50	-	85, 100	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	RC32	44+46	-	85-100	205/40, 215/40		Orig.-Verschr.
	RC34	44+45	-	85-100	205/40, 215/40		Orig.-Verschr.
	B37	50	-	85	215/40, 225/35, 225/40		Orig.-Verschr.
	B38	50	-	85	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	B24	48	ZP560D	85	215/40, 225/35, 225/40		
	B36	45	ZP560D	85	215/40, 225/35, 225/40		
	B37	45	ZP560D	85	215/40, 225/35, 225/40		
	B42 / B44	45	ZP560D	85, 100	215/40, 225/35, 225/40		incl. Facelift 2017
	AC-518	50	AV4	85, 100	215/40, 225/35, 225/40		incl. Facelift 2017
	AC-521	45	- +R	85, 100	215/40, 225/35, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2017
	AC-M10	45	AV4+R	85, 100	215/40, 225/35, 225/40		+ Red.Ringe BA25=66,6-57,1, incl. Facelift 2017
	AF18 / AF20	48	-	85, 100	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	CA 20	45	ZP560D	85, 100	215/40, 225/35, 225/40		incl. Facelift 2017
8,5 x 18	B32	48	ZP560D	85, 100	215/40, 225/35, 225/40		
7,5 x 19	RC32	51	-	85-100	225/35		Orig.-Verschr.
	RC34	48	-	85-100	225/35		Orig.-Verschr.
		50+51	-	85-100	225/35		Orig.-Verschr.
	B32	43	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
		51	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	B39	51	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	AC-521	50	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	Oxigin 18	51	-	85	225/35		Orig.-Verschr.
	RC29	49	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	RC32	50	-	85-100	225/35		Orig.-Verschr.

8 x 19	RC34	50	-	85-100	225/35		Orig.-Verschr.
	B38	50	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	B40	45+49+50	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	B43	49+50	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
	B24	45	ZP560D	85	225/35, 235/35		bei 235/35 ✖
	AC-518	47	AV4	85, 100	225/35		incl. Facelift 2017
	AC-521	45	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017
8,5 x 19	AF18	48	-	85, 100	225/35		Orig.-Verschr., incl. Facelift 2017

Golf VII GTE Hybrid	ab 2015	AU	5/112	57,1	e1*2007/46*0623*11-...		
----------------------------	----------------	-----------	--------------	-------------	------------------------	--	--

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC27	48	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC30	48	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC27	43+50	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC30	43+50	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC27	46	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC30	46	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
6,5 x 16	RC24	46	-	110	205/55, 215/55		Orig.-Verschr.
		46+50	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC27	42+43+50	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
		39	-	110	205/55		Orig.-Verschr., incl. Facelift 2017
	RC30	42+44+48+50	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
7 x 16	RC24	42	-	110	205/55		Orig.-Verschr., incl. Facelift 2017
		48	-	110	205/55, 215/55		Orig.-Verschr., incl. Facelift 2017
	RC30	48	-	110	205/55, 215/55		Orig.-Verschr., incl. FL2017
	RC28	45	ZP560D	110	205/55, 215/55		incl. Facelift 2017
6,5 x 17	RC27	39+43	-	110	205/50		Orig.-Verschr.
		46+48,5	-	110	205/50		Orig.-Verschr., incl. Facelift 2017
7 x 17	RC30	49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. FL2017
	B39	49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
		38	-	110	215/45		Orig.-Verschr.
	RC27	40+42+43+45+46	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
		47	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC30	38	-	110	215/45		Orig.-Verschr.
		45	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	B39	40	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC27	45	ZP568F (V10)	110	205/50, 215/45, 225/45		incl. Facelift 2017, Ausführung "V10"
7,5 x 17	RC27	49	-	110	225/45		Orig.-Verschr., incl. Facelift 2017
	RC29	49	-	110	205/50, 215/45, 225/45 , 235/45		Orig.-Verschr., incl. Facelift 2017
	RC24	42+51	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017, ET42 nur 215/45 auflagenfrei!
	RC27	51	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2017
	RC28	45	ZP560D	110	205/50, 215/45, 225/45		incl. Facelift 2017
	B24	47	ZP560D	110	205/50, 215/45, 225/45, 235/45		
	B36	45	ZP560D	110	205/50, 215/45, 225/45		
	AC-518	42	AV4+R	110	215/45		incl. Facelift 2017, + Red.Ringe BA25=66,6-57,1
		47	AV4	110	205/50, 215/45, 225/45, 235/45		incl. Facelift 2017
7,5 x 18	RC30	49+51	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	B39	49+51	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. FL2017, beide ET's ECE
	B32	49+51	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
		48	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	AC-521	50	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
8 x 18	RC25	50	-	110	215/40, 225/35, 225/40		Orig.-Verschr.
	RC29	50	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	B37	50	-	110	215/40, 225/35, 225/40		Orig.-Verschr.
	B38	50	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	RC29	45	ZP560D	110	215/40, 225/35, 225/40		
	B24	48	ZP560D	110	215/40, 225/35, 225/40		
	B36 / B37	45	ZP560D	110	215/40, 225/35, 225/40		
	B42 / B44	45	ZP560D	110	215/40, 225/35, 225/40		incl. Facelift 2017
	AC-518	50	AV4	110	215/40, 225/35, 225/40		incl. Facelift 2017
	AC-521	45	- +R	110	215/40, 225/35, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2017
	AC-M10	45	AV4+R	110	215/40, 225/35, 225/40		+ Red.Ringe BA25=66,6-57,1 , incl. Facelift 2017
	AF18 / AF20	48	-	110	215/40, 225/35, 225/40		Orig.-Verschr., incl. Facelift 2017
	CA 20	45	ZP560D	110	215/40, 225/35, 225/40		incl. Facelift 2017
8,5 x 18	B32	48	ZP560D	110	215/40, 225/35, 225/40		

7,5 x 19	B32	43+51	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	B39	51	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	AC-521	50	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
8 x 19	RC29	49	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	B38	50	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	B40	45+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	B43	45	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
		49+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
	B24	45	ZP560D	110	225/35		
	AC-518	47	AV4	110	225/35		incl. Facelift 2017
	AC-521	45	-	110	225/35		Orig.-Verschr., incl. Facelift 2017
8,5 x 19	AF18	48	-	110	225/35		Orig.-Verschr., incl. Facelift 2017

Golf VII GTI Clubsport				ab 2018	AU	5/112	57,1	e1*2007/46*0623*::
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC34	46	-	195-228	205/50, 215/50			Orig.-Verschr., nur M+S
7 x 17	RC32	40	-	195-228	205/50, 215/45, 225/45			Orig.-Verschr., nur M+S
		45+46+47+49	-	195-228	205/50, 215/45, 215/50, 225/45			Orig.-Verschr., nur M+S
7,5 x 17	RC32	49	-	195-228	205/50, 215/45, 225/45			Orig.-Verschr., nur M+S
7 x 18	RC32	40+43+45+52	-	195-228	205/40, 205/45, 215/40			Orig.-Verschr., nur M+S, ET40 nicht 205/45
7,5 x 18	RC32	49+51	-	195-228	205/40, 205/45, 215/40, 215/45, 225/40			Orig.-Verschr., nur M+S außer 225/40, beide ET's original
		45+48	-	195-228	205/40, 205/45, 215/40, 215/45, 225/40			Orig.-Verschr., nur M+S außer 225/40
	RC34	46	-	195-228	205/40, 205/45, 215/40			Orig.-Verschr., nur M+S
		49	-	195-228	205/40, 205/45, 215/40			Orig.-Verschr., nur M+S
		50	-	195-228	205/40, 205/45, 215/40, 215/45, 225/40			Orig.-Verschr., nur M+S außer 225/40
8 x 18	RC32	40	-	195-228	205/40			Orig.-Verschr., nur M+S
		44+46	-	195-228	205/40, 215/40			Orig.-Verschr., nur M+S
	RC34	44+45	-	195-228	205/40, 215/40			Orig.-Verschr., nur M+S
		43	ZP560D	195-228	205/40, 215/40			nur M+S
7,5 x 19	RC32	51	-	195-228	225/35			Orig.-Verschr.
		51	-	195	225/35			Orig.-Verschr.
	RC34		-	195-228	215/35, 225/35			Orig.-Verschr.
		48	-	195-228	215/35, 225/35			Orig.-Verschr.
	8 x 19	RC32	50	-	195-228	225/35, 235/35		
RC34		45	-	195-213	215/35			Orig.-Verschr., nur M+S
			-	195-228	225/35			Orig.-Verschr.
		50	-	195-228	225/35, 235/35			Orig.-Verschr.
RC34		48	ZP560D	195-213	215/35			
				195-228	225/35			
	FMI07 Atena	47	- +R	195-228	215/35			Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , nur M+S

Golf VII GTI TCR							
ab 02.2019				AU	5/112	57,1	e1*2007/46*0623*::
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC34	46	-	195-228	205/50, 215/50		Orig.-Verschr., nur M+S
7 x 17	RC32	45+46+47+49	-	195-228	205/50, 215/45, 215/50, 225/45		Orig.-Verschr., nur M+S
7,5 x 17	RC32	49	-	195-228	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC34	47+51	-	195-228	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
7 x 18	RC32	45+52	-	195-228	205/40, 205/45, 215/40		Orig.-Verschr., nur M+S
7,5 x 18	RC32	51	-	195-228	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr.
		45+48	-	195-228	205/40, 205/45, 215/40, 215/45, 225/40		Orig.-Verschr., nur M+S außer 225/40, nur zulässig bei Fahrzeugen mit Serie 235/35 R19
	RC34	46+49	-	195-228	205/40, 205/45, 215/40		Orig.-Verschr., nur M+S
8 x 18	RC32	40	-	195-228	205/40		Orig.-Verschr., nur M+S
		44+46	-	195-228	205/40, 215/40		Orig.-Verschr., nur M+S
	RC34	44+45	-	195-228	205/40, 215/40		Orig.-Verschr., nur M+S
		43	ZP560D	195-228	205/40, 215/40		nur M+S
		48	ZP560D	195-228	205/40, 205/45, 215/40		nur M+S
7,5 x 19	RC32	51	-	195-228	225/35		Orig.-Verschr.
	RC34	51	-	195	225/35		Orig.-Verschr.
				195-228	215/35, 225/35		Orig.-Verschr.
			-	195-228	215/35, 225/35		Orig.-Verschr.
	RC32	50	-	195-228	225/35, 235/35		Orig.-Verschr.
	RC34	45	-	195-213	215/35		Orig.-Verschr., nur M+S
				195-228	225/35		Orig.-Verschr.

8 x 19		50	-	195-228	225/35, 235/35		Orig.-Verschr.
	RC34	48	ZP560D	195-213 195-228	215/35 225/35		
	FMI07 Atena	47	- +R	195-228	215/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , nur M+S

Golf VIII	ab 2019	CD	5/112	57,1	e1*2007/46*2014*..		
kein Sensor - indirektes RDKS							

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 15	RC27	43	-	66-110	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
	RC30	43	-	66-110	195/65, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312 mm
	RC24	43	-	66-85	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
		47	-	66-110	195/65, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312 mm
	RC27	47	-	85-110	195/65, 205/60		Orig.-Verschr., nicht Bremse 312 mm
6 x 16	RC27	43+48+50	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
	RC30	43	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-85	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
		48	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-85	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
	RC34	43	-	66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
		48+50	-	66-96	205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
6,5 x 16	RC27	46	-	66-140	205/55, 215/55, 225/50		Orig.-Verschr.
	RC30	46	-	66-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2024
	RC32	46	-	66-110	205/55, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC34	46	-	66-140	205/55		Orig.-Verschr.
				66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC24	46	-	85-110	205/55, 215/55, 225/50		Orig.-Verschr.
				66-96	205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	44	-	85-110	205/55, 215/55, 225/50		Orig.-Verschr.
		50	-	66-96	205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC30	41	-	66-110	205/55		Orig.-Verschr.
		42+44+48+50	-	110	205/55, 215/55, 225/50		Orig.-Verschr., ET42 bei 225/50 ✖
	RC32	48	-	66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	195/55, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	48	-	66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	Pro1	48	F31+R	66-96	205/55, 215/55		+ Ringe BA25, mit Verbundlenker-Hinterachse
				110-140	205/55, 215/55, 225/50		+ Ringe BA25, mit Mehrlenker-Hinterachse
7 x 16	RC30	48	-	66-140	205/55, 215/55, 225/50		Orig.-Verschr.
6,5 x 17	RC27	46	-	66-140	205/50		Orig.-Verschr., incl. Facelift 2024
				66-140	205/50		
	RC34	46	-	66-140	205/50		Orig.-Verschr.
	RC27	43	-	66-110	205/50		Orig.-Verschr.
		39+48,5	-	66-110	205/50		Orig.-Verschr.
7 x 17	RC27	42+43+45+46+47	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr.
	RC30	40+45	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
		49	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	45+49	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
		46	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
		47	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr.
	B39	49	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr.
7,5 x 17	CA 26	45	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2024
		42+47	ZP560D	66-140	205/50, 215/45, 225/45		incl. Facelift 2024
	RC27	51	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2024
	RC32	51	-	66-140	225/45		Orig.-Verschr.
				66-140	205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	51	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr., auch Kombi CDV
	RC24	51	-	66-96	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	49	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	49	-	66-96	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC29	49	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., nur Bremse 312mm
		51	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	46+47	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., auch Kombi CDV

	RC28	45	ZP560D	66-140 110	205/50, 215/45, 225/45 205/50, 215/45		
	B36	45	ZP560D	66-140 110	205/50, 215/45, 225/45 205/50, 215/45		nicht Bremse 340mm
	Oxigin 25	51	-	66-110 66-96	205/50, 215/45 205/45		Orig.-Verschr., nicht Bremse 357x34mm
7 x 18	RC32	40	-	110-140	205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				66-110	205/45, 215/40		Orig.-Verschr.
				66-110	205/45, 215/40		Orig.-Verschr.
	RC34	43+49	-	66-140	205/45, 215/40		Orig.-Verschr.
7,5 x 18	RC30	51	-	66-110	205/45, 215/40, 225/40		Orig.-Verschr.
	RC32	51	-	66-110	225/40		Orig.-Verschr.
		51	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	51	-	66-140	225/40		Orig.-Verschr.
	B32	51	-	66-110	225/40		Orig.-Verschr., incl. Facelift 2024
				66-140	205/45, 215/40, 225/40		
	RC30	49	-	66-140	205/45, 215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC32	48+49	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		50	-	66-140	205/45, 215/40, 225/40		Orig.-Verschr.
	RC34	46	-	66-96	205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		49+50	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B32	48	-	85-110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
		49	-	66-110	205/45, 215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	AC-MB6 / AC-M10	45	- +R	66-96	205/45, 215/40, 225/40		Orig.-Verschr. +BA25 , mit Verbundlenker-HA
				110	205/45, 215/40		Orig.-Verschr. +BA25 , mit Mehrlenker-Hinterachse
				110, 140	205/45, 215/40, 225/40		Orig.-Verschr. +BA25 , nur M+S, mit Mehrlenker-HA
	AC-521	50	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
				110, 140	205/45, 215/40, 225/40		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
	Oxigin 25	51	ZP560D	66-110	205/45, 215/40		
8 x 18	RC29	50	-	66-110	215/40, 225/40		Orig.-Verschr.
	RC32	44	-	110	205/45, 215/40		Orig.-Verschr.
		46	-	110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr.
	RC34	44	-	66-96	205/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		45	-	66-96	205/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/45, 215/40, 225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	43	ZP560D	66-96	205/45		mit Verbundlenker-Hinterachse
				110	205/45, 215/40		mit Mehrlenker-Hinterachse
		48	ZP560D	66-96	205/45, 215/40		mit Verbundlenker-Hinterachse
				110	205/45, 215/40, 225/35, 225/40		mit Mehrlenker-Hinterachse
	B24	48	ZP560D	66-140	215/40, 225/40		
	B42 / B44	45	ZP560D	66-96	215/40		mit Verbundlenker-Hinterachse
				110, 140	215/40M+S, 225/40		mit Mehrlenker-Hinterachse
	B36	45	ZP560D	66-140	215/40, 225/40		
	AC-521	45	- +R	66-96	215/40		Orig.-Verschr. + BA25 , mit Verbundlenker-HA
				110	215/40		Orig.-Verschr. + Red. Ringe BA25=66,6-57,1 , mit Mehrlenker-Hinterachse
				110, 140	215/40M+S, 225/40		
	AC-M10	45	AV4+R	66-96	215/40		+ Red.Ringe BA25 , mit Verbundlenker-HA
				110	215/40		+ Red. Ringe BA25=66,6-57,1 , mit Mehrlenker-Hinterachse
		48	-	66-110	215/40M+S, 225/40		
				66-110	215/40, 225/40		Orig.-Verschr.
	CA 20	45	ZP560D	66-96	215/40		mit Verbundlenker-Hinterachse
				110	215/40, 225/40		mit Mehrlenker-Hinterachse
	FMI08 Thoe	49	F31+R	66-96	205/45, 215/40		+ Red.Ringe BA25 , mit Verbundlenker-HA
				110-140	205/45, 215/40, 225/40		+ Red.Ringe BA25 , mit Mehrlenker-Hinterachse
7,5 x 19	RC32	50+51	-	66-96	205/35, 215/35, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	215/35, 225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC34	48	-	66-110	215/35, 225/35		Orig.-Verschr.
	B32	43+51	-	66-110	215/35, 225/35		Orig.-Verschr.
	RC34	45,5	ZP560D	66-96	215/35		mit Verbundlenker-Hinterachse
				110-140	215/35, 225/35		mit Mehrlenker-Hinterachse
	AC-521	50	-	66-110	215/35		Orig.-Verschr.
				66-140	225/35		
	CA 26	51	F90	66-110	215/35		incl. Facelift 2024
				66-140	225/35		
	Oxigin 18	50	ZP560D	66-110	225/35		
	RC27	50	-	66-110	215/35		Orig.-Verschr., incl. Facelift 2024
				66-140	225/35		

8 x 19	RC29	49	-	66-110	215/35, 225/35		Orig.-Verschr.
	RC32	45	-	110	215/35, 225/30, 225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
		50	-	66-96	215/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	215/35		Orig.-Verschr., mit Mehrlenker-Hinterachse, auch für Hybrid
	RC34	45	-	66-96	215/35, 225/30		Orig.-Verschr., mit Verbundlenker-HA, ✖
		50	-	110	215/35, 225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
				66-140	215/35		Orig.-Verschr.
	B38	50	-	66-140	215/35, 225/35		Orig.-Verschr.
		50	-	66-110	215/35, 225/35		Orig.-Verschr.
	B40	45+49+ 50	-	66-110	215/35		Orig.-Verschr., incl. Facelift 2024
	B43	45+49+ 50	-	66-140	225/35		Orig.-Verschr., ET49+ET50 incl. Facelift 2024
				66-110	215/35		
	B24	45	ZP560D	85-110	225/35		
8,5 x 19	B36	45	ZP560D	96, 110	215/35		
				66-110	215/35		Orig.-Verschr.
8,5 x 20	B42	47	ZP560D	66-110	225/35		
				66-96	215/35		Orig.-Verschr.
8,5 x 20	B44	49	-	110	215/35, 225/30, 225/35		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	215/35, 225/30, 225/35		Orig.-Verschr., mit Mehrlenker-Hinterachse
8,5 x 19	B36	45	ZP560D		215/35, 225/35		TÜV i.V.
8,5 x 20	B42	47	ZP560D	66-110	215/35, 225/35		
8,5 x 20	B44	40	ZP560D		235/30		i.V.

Golf VIII Alltrack

ab 2020

CD

5/112

57,1

e1*2007/46*2180*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC34	46	-	140-147	205/50M+S		Orig.-Verschr.
7 x 17	RC32	40	-	140-147	205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr.
		45+47	-	140-147	205/50, 205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC34	40	-	140-147	205/50, 205/55, 215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 17	RC32	43	-	140-147	205/50, 205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
		40	-	140-147	205/50, 205/55, 215/45, 225/45		Orig.-Verschr.
	RC34	41	-	140-147	205/50, 205/55, 215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
7 x 18	RC32	35	-	140-147	205/45, 215/40, 215/45		Orig.-Verschr.
		40+45	-	140-147	205/45, 205/50, 215/40, 215/45, 225/45		Orig.-Verschr.
	RC34	43	-	140-147	205/45, 205/50, 215/40, 215/45, 225/45		Orig.-Verschr.
7,5 x 18	RC32	40	-	140-147	205/45, 205/50, 215/40, 215/45, 225/40		Orig.-Verschr.
		45	-	140-147	205/45, 205/50, 215/40, 215/45, 225/40, 225/45		Orig.-Verschr.
	RC34	35	-	140-147	205/45, 215/40		Orig.-Verschr.
		40	-	140-147	205/45, 205/50, 215/40, 215/45, 225/40		Orig.-Verschr.
		46	-	140-147	205/45, 205/50, 215/40, 215/45, 225/40, 225/45		Orig.-Verschr.
8 x 18	Oxigin 25	44	ZP560D	140-147	225/45		
	RC32	44	-	140-147	205/45, 215/40, 215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
	RC34	44+45	-	140-147	205/45, 215/40, 215/45, 225/40, 225/45, 235/40		Orig.-Verschr.
	RC34	48	ZP560D	140-147	205/45, 215/40, 215/45, 225/40, 225/45, 235/40		
	FMI12 Kari	34	Kit 0353	140-147	205/45		

Golf VIII R

ab 2021

CD / CDV

5/112

57,1

e1*2007/46*2014*..., e1*2007/46*2180*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC30	51	-	235	225/40		Orig.-Verschr.
	B32	51	-	235	225/40		Orig.-Verschr.
	B39	51	-	235, 245	225/40		Orig.-Verschr., incl. Facelift 2024, auch Variant
	RC30	49	-	235, 245	225/40		Orig.-Verschr., incl. Facelift 2024, auch Variant
	B39	49	-	235, 245	225/40		Orig.-Verschr., incl. Facelift 2024, auch Variant
		45	ZP560D	235	225/40		
	AC-MB6 / AC-M10	45	- +R	235, 245	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2024, auch Variant
	Oxigin 25	51	ZP560D	235	225/40		
8 x 18	RC27	46	-	235, 245	225/40, 235/40		Orig.-Verschr., incl. Facelift 2024
	RC29	50	-	235	225/40, 235/40		Orig.-Verschr.
	B37	50	-	235, 245	225/40, 235/40		Orig.-Verschr., incl. Facelift 2024, auch Variant
	B38	50	-	235	225/40, 235/40		Orig.-Verschr.
	B24	48	ZP560D	235	225/40, 235/40		auch Variant
				235, 245	225/40, 235/40		nur M+S, auch Variant
	B36 / B42 / B44	45	ZP560D	235	225/40, 235/40		
				235, 245	225/40, 235/40		nur M+S
	AC-518	50	ZP568F	235	225/40, 235/40		
8 x 18	AC-521	45	- +R	235	225/40, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, auch Variant
	CA 20	45	ZP560D	235	225/40, 235/40		

	OR 20	70	ET 300D	235, 245	225/40, 235/40		nur M+S
8,5 x 18	B32	48	ZP560D	235	225/40, 235/40		
7,5 x 19	B32	51	-	235	225/35		Orig.-Verschr.
	B39	51	-	235	225/35		Orig.-Verschr.
	AC-521	50	-	235	225/35		Orig.-Verschr.
	B39	43	ZP560D	235	225/35		
	CA 26	51	F90	235, 245	225/35		incl. Facelift 2024
8 x 19	RC27	50	-	235	235/35		Orig.-Verschr., incl. Facelift 2024
				235, 245	225/35, 235/35		
	B40	50	-	235	235/35		Orig.-Verschr.
				235, 245	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
	B43	50	-	235, 245	235/35		Orig.-Verschr., incl. Facelift 2024
				235, 245	225/35, 235/35		
	RC29	49	-	235	225/35, 235/35		Orig.-Verschr.
	B40	49	-	235, 245	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
	B43	45	-	235, 245	225/35		Orig.-Verschr., incl. Facelift 2024
		47	-	235	225/35		Orig.-Verschr.
		49	-	235, 245	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
8,5 x 19	AC-521	45	-	235	225/35		Orig.-Verschr.
	B32 / B36	45	ZP560D	235	225/35		auch Variant
				235, 245	225/35M+S		
	B42	47	ZP560D	235	225/35		auch Variant
				235, 245	225/35M+S		
	CA 23	45	ZP560D	235	225/35		auch Variant
				235, 245	225/35M+S		
	Oxigin 28	45	ZP560D	235	225/35		auch Variant
8 x 20	RC36	50	-	235, 245	235/30		Orig.-Verschr., incl. Facelift 2024, auch Variant
		50	-	235, 245	235/30		Orig.-Verschr., incl. Facelift 2024
	B43	48	ZP560D	235, 245	235/30		auch Variant
8,5 x 20	B44	40	ZP560D		235/30		i.V.
Golf VIII Variant							
ab 2021				CDV	5/112	57,1	e1*2007/46*2180*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 15	RC30	43	-	66-110	195/65, 205/60		Orig.-Verschr., nicht Bremse 312mm
	RC27	43	-	66-110	195/65, 205/60		Orig.-Verschr., nicht Bremse 312mm
	RC24	47	-	66-110	195/65, 205/60		Orig.-Verschr., nur M+S, nicht Bremse 312mm
6 x 16	RC27	43+48+50	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-96	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
	RC30	43	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-85	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
		48	-	110	205/55, 215/55		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
				66-85	205/55, 215/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
	RC34	43+48+50	-	81-110	195/60, 205/55, 215/55, 225/50		Orig.-Verschr.
6,5 x 16	RC27	46	-	66-140	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2024
	RC30	46	-	66-140	205/55		Orig.-Verschr., incl. Facelift 2024
	RC32	46	-	81-110	195/60, 205/55, 215/55, 225/50		Orig.-Verschr.
	RC34	46	-	81-140	205/55		Orig.-Verschr.
				81-96	195/60, 205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	195/55, 195/60, 205/55, 215/50, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC24	43	-	66-96	205/55		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/55, 215/55		Orig.-Verschr., mit Mehrlenker-Hinterachse
		50	-	66-96	205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	50	-	66-96	205/55, 215/55, 225/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/55, 215/55, 225/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC32	43	-	81-140	195/60, 205/55, 215/55		Orig.-Verschr.
		48	-	81-110	195/60, 205/55, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC34	43	-	81-140	195/60, 205/55, 215/55		Orig.-Verschr.
		48	-	81-140	195/60, 205/55, 215/55, 225/50, 235/50		Orig.-Verschr.
	Pro 1	48	F31+R	81-140	195/60, 205/55, 215/55, 225/50, 235/50		+ Ringe BA25=66,6-57,1
	RC30	48	-	66-140	205/55, 215/55		Orig.-Verschr.
6,5 x 17	RC27	46	-	66-110	205/50		Orig.-Verschr., nur M+S
				66-140	205/50		Orig.-Verschr., incl. Facelift 2024
	RC34	46	-	81-150	205/50		Orig.-Verschr.
				81-96	195/50, 205/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	195/50, 205/45, 205/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	48,5+49	-	66-110	205/50		Orig.-Verschr.
	RC34	43	-	81-96	195/50, 205/50		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	195/50, 205/45, 205/50		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	42+43+45+46	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr.

7 x 17	RC30	40+45	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	40	-	81-150	195/50, 205/50, 215/45		Orig.-Verschr.
		45+47	-	81-110	195/50, 205/50, 215/45, 225/45		Orig.-Verschr.
		49	-	81-110	195/50, 195/55, 205/50, 215/45, 225/45		Orig.-Verschr.
	RC34	40	-	81-140	195/50, 205/50, 215/45		Orig.-Verschr.
		45+49	-	81-110	195/50, 195/55, 205/50, 215/45, 225/45		Orig.-Verschr.
	B39	49	-	66-140	205/50, 215/45, 225/45		Orig.-Verschr.
	B39	47	ZP560D	66-110	205/50, 215/45, 225/45		
7,5 x 17	RC27	51	-	66-140	225/45		Orig.-Verschr., incl. Facelift 2024
		51	-	81-150	205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
	RC34	51	-	81-150	225/45		Orig.-Verschr.
				81-96	205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-150	205/45, 205/50, 215/45, 225/45, 235/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	Oxigin 25	51	-	81-140	225/45		Orig.-Verschr.
	RC24	51	-	66-96	205/50, 215/45, 225/45		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110, 140	205/50, 215/45, 225/45		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC27	49	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC29	49	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr., nur Bremse 312mm
		51	-	66-110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC32	43+46	-	81-110	205/50, 215/45, 225/45		Orig.-Verschr.
		49	-	81-140	205/50, 215/45, 225/45, 235/45		Orig.-Verschr.
	RC28	45	ZP560D	66-140	205/50, 215/45, 225/45		
	B24	47	ZP560D	110	205/50, 215/45		
				66-140	205/50, 215/45, 225/45		
7 x 18	RC32	40	-	81-96	195/45, 205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-150	195/45, 205/40, 205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		45	-	81-110	205/45, 215/40		Orig.-Verschr.
		52	-	81-110	205/45, 215/40		Orig.-Verschr.
	RC34	43+49	-	81-96	205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/40, 205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	RC30	51	-	66-110	205/45, 215/40, 225/40		Orig.-Verschr.
				81-110	225/40		Orig.-Verschr.
	RC32	51	-	81-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-150	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
7,5 x 18	RC34	51	-	81-140	225/40		Orig.-Verschr.
				81-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/40, 205/45, 215/40, 225/35, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B32	51	-	66-110	225/40		Orig.-Verschr., incl. Facelift 2024
				66-140	205/45, 215/40, 225/40		
	B39	51	-	66-110	205/45, 215/40		Orig.-Verschr., incl. Facelift 2024
				66-140	205/45, 215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC34	46	-	66-96	205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
		49+50	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/45, 215/40, 225/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	AC-MB6 / AC-M10	45	- +R	66-96	205/45, 215/40, 225/40		Orig.-Verschr. +BA25, mit Verbundlenker-HA
				110	205/45, 215/40		Orig.-Verschr. +BA25, mit Mehrlenker-Hinterachse
				110, 140	205/45, 215/40, 225/40		Orig.-Verschr. +BA25, nur M+S, mit Mehrlenker-HA
	AC-521	50	-	66-96	205/45, 215/40, 225/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110	205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
				110, 140	205/45, 215/40, 225/40		Orig.-Verschr., nur M+S, mit Mehrlenker-HA
	Oxigin 25	51	ZP560D	81-110	205/45, 215/40		
				81-235	225/40		
8 x 18	RC27	46	-	66-110	215/40		Orig.-Verschr., incl. Facelift 2024
				66-140	215/40, 225/40		
	RC29	50	-	66-110	215/40, 225/40		Orig.-Verschr.
	RC34	44	-	81-96	205/45, 215/40		Orig.-Verschr., mit Verbundlenker-Hinterachse
				110-140	205/40, 205/45, 215/40		Orig.-Verschr., mit Mehrlenker-Hinterachse
	B37	50	-	66-110	215/40, 225/40		Orig.-Verschr.
	B38	50	-	66-110	215/40, 225/40		Orig.-Verschr.
	B24	48	ZP560D	66-140	215/40, 225/40		
	B42 / B44	45	ZP560D	66-96	215/40		mit Verbundlenker-Hinterachse
				110, 140	215/40M+S, 225/40		Mit Mehrlenker-Hinterachse
	B36	45	ZP560D	66-140	215/40, 225/40		
	AC-518	50	ZP568F	66-110	215/40, 225/40		
	AC-521	45	- +R	66-96	215/40		Orig.-Verschr. + BA25, mit Verbundlenker-HA
				110	215/40		Orig.-Verschr. + Red. Ringe BA25=66,6-57,1, mit Mehrlenker-Hinterachse
				110, 140	215/40M+S, 225/40		
	AF20	48	-	66-110	215/40, 225/40		Orig.-Verschr.
	CA 20	45	ZP560D	66-96	215/40		mit Verbundlenker-Hinterachse
				110	215/40, 225/40		Mit Mehrlenker-Hinterachse

	FMI08 Thoe	49	F31+R	81-140	205/45, 215/40, 225/40		+ Ringe BA25=66,6-57,1
7,5 x 19	RC32	50	-	81-140	215/35, 225/35		Orig.-Verschr.
		51	-	81-140	215/35, 225/35		Orig.-Verschr.
	RC34	48	-	81-140	225/35		Orig.-Verschr.
		50+51	-	81-140	225/35		Orig.-Verschr.
	B39	51	-	66-110	215/35, 225/35		Orig.-Verschr.
	AC-521	50	-	66-110	215/35		Orig.-Verschr.
				66-140	225/35		
8 x 19	CA 26	51	F90	66-110	215/35		incl. Facelift 2024
				66-140	225/35		
	RC27	50	-	66-110	215/35		Orig.-Verschr., incl. Facelift 2024
				66-140	225/35		
	RC29	49	-	66-110	215/35, 225/35		Orig.-Verschr.
	RC32	50	-	81-140	225/35		Orig.-Verschr.
	RC34	45	-	81-110	225/35		Orig.-Verschr.
		50	-	81-140	225/35		Orig.-Verschr.
8,5 x 19	B40	49	-	66-110	215/35, 225/35		Orig.-Verschr., incl. Facelift 2024
	B43	45+49+	-	66-110	215/35		Orig.-Verschr.
		50		66-140	225/35		
	RC34	48	ZP560D	81-110	225/35		
	AC-521	45	-	66-110	215/35		Orig.-Verschr.
8,5 x 19	B42	47	ZP560D	66-110	215/35, 225/35		
8,5 x 20	B44	40	ZP560D		235/30		i.V.
Golf VIII Plug-in-Hybrid				ab 2020	CD	5/112	57,1
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 16	RC27	46	-	110	205/55, 215/55, 225/50		Orig.-Verschr.
	RC30	46	-	110	205/55, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2024
	RC24	43	-	110	205/55, 215/55		Orig.-Verschr., nicht Bremse 340mm
		50	-	110	205/55, 215/55, 225/50		Orig.-Verschr., nicht Bremse 340mm
7 x 16	RC27	50	-	110	205/55, 215/55, 225/50		Orig.-Verschr., nicht Bremse 340mm
	RC30	41+42	-	110	205/55, 215/55		Orig.-Verschr., nicht Bremse 340mm
	RC30	48	-	110	205/55		Orig.-Verschr.
	RC27	46	-	110	205/50, 215/55, 225/50HA		Orig.-Verschr., nur M+S, incl. Facelift 2024
6,5 x 17	RC34	46	-	110	205/50		Orig.-Verschr.
	RC27	48,5	-	110	205/50		Orig.-Verschr.
		49	-	110	205/50		Orig.-Verschr., incl. Facelift 2024
7 x 17	RC27	42+43+	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC30	45+49	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
	B39	49	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC30	47	ZP560D	110	205/50, 215/45, 225/45		
	B39	47	ZP560D	110	205/50, 215/45, 225/45		
	CA 26	45	-	110	205/50, 215/45, 225/45		Orig.-Verschr., incl. Facelift 2024
		42+47	ZP560D	110	205/50, 215/45, 225/45		
7,5 x 17	RC27	51	-	110	225/45		Orig.-Verschr., incl. Facelift 2024
		49	-	110	205/50, 215/45, 225/45		Orig.-Verschr.
	RC29	51	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nicht Bremse 340mm
		49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nicht Bremse 340mm
	RC28 / RC29	45	ZP560D	110	205/50, 215/45, 225/45, 235/45		RC29 nicht Bremse 340mm
	B24	47	ZP560D	110	205/50, 215/45, 225/45		
	B36	45	ZP560D	110	205/50, 215/45, 225/45, 235/45		bis 215/45 nur M+S, nicht Bremse 340mm
7 x 18	RC27	45	-	110	205/45, 215/40		Orig.-Verschr., incl. Facelift 2024
7,5 x 18	RC30	51	-	110	205/45, 215/40, 225/40		Orig.-Verschr.
	B32	51	-	110	205/45, 215/40, 225/40		Orig.-Verschr.
	B39	51	-	110	205/45, 215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC30	49	-	110	205/45, 215/40, 225/40		Orig.-Verschr.
	RC32	50	-	110	225/40		Orig.-Verschr.
	B39	49	-	110	205/45, 215/40, 225/40		Orig.-Verschr.
	AC-MB6 / AC-M10	45	- +R	110	205/45, 215/40, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2024
		50	-	110	205/45, 215/40, 225/40		Orig.-Verschr.
8 x 18	RC27	46	-	110	215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC29	50	-	110	215/40, 225/40		Orig.-Verschr.
	B37	50	-	110	215/40, 225/40		Orig.-Verschr., incl. Facelift 2024
	B38	50	-	110	215/40, 225/40		Orig.-Verschr.
	B24	48	ZP560D	110	215/40, 225/40		
	B36 / B38 / B42	45	ZP560D	110	215/40, 225/40		
		45	ZP560D	110	215/40, 225/40		
	B44	45	ZP568F	110	215/40, 225/40		
	AC-518	45	- +R	110	215/40, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	48	-	110	215/40, 225/40		Orig.-Verschr.
	AF20	48	-	110	215/40, 225/40		
	CA 20	45	ZP560D	110	215/40, 225/40		

8,5 x 18	B32	48	ZP560D	110	215/40, 225/40		
	B32	51	-	110	225/35		Orig.-Verschr.
	B39	51	-	110	225/35		Orig.-Verschr.
7,5 x 19	B39	43	ZP560D	110	225/35		
	AC-521	50	-	110	225/35		Orig.-Verschr.
	CA 26	51	F90	110	225/35		incl. Facelift 2024
8 x 19	RC27	50	-	110	225/35		Orig.-Verschr., incl. Facelift 2024
	RC29	49	-	110	225/35		Orig.-Verschr.
	B38	50	-	110	225/35		Orig.-Verschr.
	B40	45+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2024
		49	-	110	225/35		Orig.-Verschr., incl. Facelift 2024
	B43	45+49+50	-	110	225/35		Orig.-Verschr., incl. Facelift 2024
		47	-	110	225/35		Orig.-Verschr.
	AC-521	45	-	110	225/35		Orig.-Verschr.
8,5 x 19	B42	47	ZP560D	110	225/35		
	AF20	48	-	110	225/35		Orig.-Verschr.
8,5 x 20	B44	40	ZP560D		235/30		i.V.

Golf VIII GTD

ab 2020

CD

5/112

57,1

e1*2007/46*2014*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	46	-	147	205/50		Orig.-Verschr.
	RC34	46	-	147-195	205/50		Orig.-Verschr., nur M+S
	RC27	48,5+49	-	147	205/50		Orig.-Verschr., nur M+S
7 x 17	RC27	42+43+46+47	-	147	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC30	40+45	-	147	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC32	40+47+49	-	147-180	205/45, 205/50		Orig.-Verschr., nur M+S
	RC34	45+49	-	110-180	205/50		Orig.-Verschr., nur M+S
	B39	49	-	147	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC30	47	ZP560D	147	205/50, 215/45, 225/45		nur M+S
	B39	47	ZP560D	147	205/50, 215/45, 225/45		nur M+S
	CA 26	45	-	147	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
		42+47	ZP560D	147	205/50, 215/45, 225/45		nur M+S
7,5 x 17	RC27	51	-	147	225/45		Orig.-Verschr.
	RC32	51	-	147-195	205/45M+S, 205/50M+S, 225/45, 235/45		Orig.-Verschr., auch Hybrid
	RC34	51	-	147-195	225/45		Orig.-Verschr.
				110-195	205/50M+S, 225/45		Orig.-Verschr., ohne Serienreifen 235/35 R19
				147-195	205/45M+S, 205/50M+S, 225/45, 235/45		Orig.-Verschr., mit Serienreifen 235/35 R19
	RC24	51	-	147	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr.
	RC27	49	-	147	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr.
		51	-	147	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr., nicht Bremse 340mm
	RC29	49	-	147	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr., nicht Bremse 340mm
		49	-	147	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr., nicht Bremse 340mm
	RC32	43+46	-	147-180	205/45, 205/50, 225/45, 235/45		Orig.-Verschr., 205er Reifen nur M+S
		49	-	147-180	205/45, 205/50, 225/45, 235/45, 245/45		Orig.-Verschr., 205er Reifen nur M+S
	RC28 / RC29	45	ZP560D	147	205/50M+S, 215/45M+S, 225/45, 235/45		RC29 nicht Bremse 340mm
	B24	47	ZP560D	147	205/50M+S, 215/45M+S, 225/45, 235/45		
	B36	45	ZP560D	147	205/50M+S, 215/45M+S, 225/45, 235/45		nicht Bremse 340mm
7,5 x 18	RC30	51	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	RC32	51	-	147-180	225/35, 225/40		Orig.-Verschr.
	RC34	51	-	110-195	225/40		Orig.-Verschr.
	B32	51	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	RC30	49	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	RC32	48+49	-	147-180	225/35, 225/40		Orig.-Verschr.
		50	-	147-180	225/35, 225/40		Orig.-Verschr.
	RC34	46+50	-	147-180	225/35, 225/40		Orig.-Verschr.
	B32	46	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
		48+49	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	B39	49	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
		51	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	AC-MB6	45	- +R	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	50	-	147	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	Oxigin 25	51	ZP560D	147	225/40		
8 x 18	RC27	46	-	147	215/40M+S, 225/40		Orig.-Verschr.
	RC29	50	-	147	215/40M+S, 225/40, 235/40		Orig.-Verschr.
	RC34	44	-	147-180	225/35, 225/40		Orig.-Verschr.
		45	-	147-180	225/40		Orig.-Verschr.
	B37	50	-	147	215/40M+S, 225/40, 235/40		Orig.-Verschr.
	B38	50	-	147	215/40M+S, 225/40, 235/40		Orig.-Verschr.
	RC34	43	ZP560D	147-180	225/40		
		48	ZP560D	147-180	225/40, 235/40		
	B24	48	ZP560D	147	215/40M+S, 225/40, 235/40		

8,5 x 18	B36 / B42	45	ZP560D	147	215/40M+S, 225/40		
	B44	45	ZP560D	147	215/40M+S, 225/40		
	AC-518	50	ZP568F	147	215/40M+S, 225/40, 235/40		
	AC-521	45	- +R	147	215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-M10	45	AV4+R	147	215/40M+S, 225/40		+ Red.Ringe BA25=66,6-57,1
	AF20	48	-	147	215/40, 225/40, 235/40		Orig.-Verschr.
	CA 20	45	ZP560D	147	215/40M+S, 225/40		
	FMI08 Thoe	49	F31+R	147-180	225/35, 225/40, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1
7,5 x 19	B32	48	ZP560D	147	215/40M+S, 225/40		
	RC32	50	-	147-195	225/35		Orig.-Verschr.
	RC34	48	-	147-180	225/35		Orig.-Verschr.
		50+51	-	147-180	225/35		Orig.-Verschr.
	B32	51	-	147	225/35		Orig.-Verschr.
	B39	51	-	147	225/35		Orig.-Verschr.
	RC34	45,5	ZP560D	147-180	225/35		
	B39	43	ZP560D	147	225/35		
8 x 19	AC-521	50	-	147	225/35		Orig.-Verschr.
	CA 26	51	F90	147	225/35		
	RC27	50	-	147	225/35, 235/35		Orig.-Verschr.
	RC32	50	-	147-195	225/35, 235/35		Orig.-Verschr.
	B38	50	-	147	225/35, 235/35		Orig.-Verschr.
	B40	50	-	147	235/35		Orig.-Verschr.
	B43	50	-	147	225/35, 235/35		Orig.-Verschr.
	RC29	49	-	147	225/35, 235/35		Orig.-Verschr.
	RC32	45	-	147-180	225/35		Orig.-Verschr.
	RC34	45	-	147-180	225/35		Orig.-Verschr.
		50	-	147-180	225/35, 235/35		Orig.-Verschr.
	B40	50	-	147	225/35, 235/35		Orig.-Verschr.
		45+47	-	147	225/35		Orig.-Verschr.
	B43	49	-	147	225/35, 235/35		Orig.-Verschr.
		43	ZP560D	147-195	225/35		
	RC34	48	ZP560D	147-180	225/35, 235/35		
8 x 20	AC-521	45	-	147	225/35		Orig.-Verschr.
	RC36	50	-	147	235/30		Orig.-Verschr.
	B43	50	-	147	235/30		Orig.-Verschr.
	B38 / B43	48	ZP560D	147	235/30		
		40	ZP560D		235/30		i.V.
8,5 x 20	B44	40	ZP560D		235/30		
Golf VIII GTE Plug-in-Hybrid ab 2020 CD 5/112 57,1 e1*2007/46*2014*..							
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	46	-	110, 130	205/50		Orig.-Verschr., nur M+S, incl. Facelift 2024
	RC34	46	-	110	205/50		Orig.-Verschr.
	RC27	48,5	-	110	205/50		Orig.-Verschr., nur M+S
		49	-	110, 130	205/50		Orig.-Verschr., nur M+S, incl. Facelift 2024
7 x 17	RC27	42+43+46+47	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC30	45+49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC34	45+49	-	110	205/50		Orig.-Verschr., nur M+S
	B39	49	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	B39	47	ZP560D	110	205/50, 215/45, 225/45		nur M+S
	CA 26	45	-	110	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S, incl. Facelift 2024
		42+47	ZP560D	110	205/50, 215/45, 225/45		incl. Facelift 2024, nur M+S
7,5 x 17	RC27	51	-	110, 130	225/45		Orig.-Verschr., incl. Facelift 2024
	RC32	51	-	110	225/45		Orig.-Verschr., auch Hybrid
	RC24	51	-	110	205/50M+S, 215/45M+S, 225/45		Orig.-Verschr.
	RC27	49	-	110	205/50M+S, 215/45M+S, 225/45		Orig.-Verschr.
		43	-	110	205/50M+S, 225/45		Orig.-Verschr.
	RC32	49	-	110	205/50M+S, 225/45, 235/45		Orig.-Verschr.
		45	ZP560D	110	205/50M+S, 215/45M+S, 225/45, 235/45		
	B24	47	ZP560D	110	205/50M+S, 215/45M+S, 225/45		
7 x 18	RC27	45	-	110, 130	205/45, 215/40		Orig.-Verschr., nur M+S, incl. Facelift 2024
7,5 x 18	RC30	51	-	110	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	RC34	51	-	110	225/40		Orig.-Verschr.
	B32	51	-	110, 130	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC30	49	-	110, 130	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC32	50	-	110	225/40		Orig.-Verschr.
	B39	49	-	110, 130	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
		51	-	110, 130	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	AC-MB6	45	- +R	110, 130	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-521	50	-	110	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	Oxigin 25	51	ZP560D	110	205/45, 215/40, 225/40		
	RC27	46	-	110, 130	215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC29	50	-	110	215/40M+S, 225/40		Orig.-Verschr.

8 x 18	B37	50	-	110, 130	215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	B38	50	-	110	215/40, 225/40		Orig.-Verschr.
	B24	48	ZP560D	110	215/40M+S, 225/40		
	B36 / B42	45	ZP560D	110	215/40M+S, 225/40		
	B38 / B44	45	ZP560D	110	215/40M+S, 225/40		
	AC-518	50	ZP568F	110	215/40M+S, 225/40		
	AC-521	45	- +R	110	215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-M10	45	AV4+R	110	215/40M+S, 225/40		+ Red.Ringe BA25=66,6-57,1
	AF20	48	-	110	215/40, 225/40		Orig.-Verschr.
8,5 x 18	CA 20	45	ZP560D	110	215/40M+S, 225/40		
	B32	48	ZP560D	110	215/40M+S, 225/40		
7,5 x 19	RC34	48	-	110	225/35		Orig.-Verschr.
		50+51	-	110	225/35		Orig.-Verschr.
	B32	51	-	110	225/35		Orig.-Verschr.
	B39	51	-	110	225/35		Orig.-Verschr.
	B39	43	ZP560D	110	225/35		
	AC-521	50	-	110	225/35		Orig.-Verschr.
	CA 26	51	F90	110, 130	225/35		incl. Facelift 2024
8 x 19	RC27	50	-	110, 130	225/35		Orig.-Verschr., incl. Facelift 2024
	RC29	49	-	110	225/35		Orig.-Verschr.
	RC32	45	-	110	225/35		Orig.-Verschr.
	B38	50	-	110	225/35		Orig.-Verschr.
	B40	45	-	110	225/35		Orig.-Verschr.
		49+50	-	110, 130	225/35		Orig.-Verschr., incl. Facelift 2024
	B43	45+49+50	-	110, 130	225/35		Orig.-Verschr., incl. Facelift 2024
		47	-	110	225/35		Orig.-Verschr.
	AC-521	45	-	110	225/35		Orig.-Verschr.
8,5 x 19	B42	47	ZP560D	110	225/35		
8,5 x 20	B44	40	ZP560D		235/30		i.V.
Golf VIII GTI				ab 2020	CD	5/112	57,1
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	46	-	180, 195	205/50		Orig.-Verschr., nur M+S, incl. Facelift 2024
	RC34	46	-	195	205/50		Orig.-Verschr., nur M+S
	RC27	48,5	-	180	205/50		Orig.-Verschr., nur M+S
		49	-	180, 195	205/50		Orig.-Verschr., nur M+S, incl. Facelift 2024
7 x 17	RC27	42+46+47	-	180	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC30	45+49	-	180	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	RC32	38+45	-	180	205/50		Orig.-Verschr., nur M+S
	RC34	45+49	-	180	205/50		Orig.-Verschr., nur M+S
	B39	49	-	180	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S
	B39	47	ZP560D	180	205/50, 215/45, 225/45		nur M+S
	CA 26	45	-	180, 195	205/50, 215/45, 225/45		Orig.-Verschr., nur M+S, incl. Facelift 2024
		42+47	ZP560D	180, 195	205/50, 215/45, 225/45		incl. Facelift 2024, nur M+S
7,5 x 17	RC27	51	-	180, 195	225/45		Orig.-Verschr., incl. Facelift 2024
	RC32	51	-	180	225/45		Orig.-Verschr., auch Hybrid
	RC34	51	-	180	225/45		Orig.-Verschr.
	RC24	51	-	180	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr.
	RC27	49	-	180	205/50M+S, 215/45M+S, 225/45, 235/45		Orig.-Verschr.
		43	-	180	205/45M+S, 205/50M+S, 225/45, 235/45		Orig.-Verschr.
	RC32	49	-	180	205/50M+S, 225/45, 235/45		Orig.-Verschr.
		45	ZP560D	180	205/50M+S, 215/45M+S, 225/45, 235/45		
	B24	47	ZP560D	180	205/50M+S, 215/45M+S, 225/45, 235/45		
7 x 18	RC27	45	-	180, 195	205/45, 215/40		Orig.-Verschr., incl. Facelift 2024
7,5 x 18	B32	51	-	180	225/40		Orig.-Verschr.
				180, 195	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC30	51	-	180	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	RC34	51	-	180	225/40		Orig.-Verschr.
	RC30	49	-	180, 195	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC32	51	-	180	225/40		Orig.-Verschr.
		50	-	180	225/40		Orig.-Verschr.
	B39	49	-	180, 195	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
		51	-	180, 195	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
		45	ZP560D	180	205/45M+S, 215/40M+S, 225/40		
	AC-MB6 / AC-M10	45	- +R	180, 195	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2024
	AC-521	50	-	180	205/45M+S, 215/40M+S, 225/40		Orig.-Verschr.
	Oxigin 25	51	ZP560D	180	225/40		
	RC27	46	-	180, 195	215/40M+S, 225/40		Orig.-Verschr., incl. Facelift 2024
	RC29	50	-	180	215/40M+S, 225/40, 235/40		Orig.-Verschr.
	B37	50	-	180, 195	215/40M+S, 225/40, 235/40		Orig.-Verschr., incl. Facelift 2024

8 x 18	B38	50	-	180	215/40M+S, 225/40, 235/40		Orig.-Verschr.
	B24	48	ZP560D	180	215/40M+S, 225/40, 235/40		
	B36 / B42	45	ZP560D	180	215/40M+S, 225/40		
	B44	45	ZP560D	180	215/40M+S, 225/40		
	AC-518	50	ZP568F	180	215/40M+S, 225/40, 235/40		
	AC-521	45	- +R	180	215/40M+S, 225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-M10	45	AV4+R	180	215/40M+S, 225/40		+ Red.Ringe BA25=66,6-57,1
	AF20	48	-	180	215/40M+S, 225/40, 235/40		Orig.-Verschr.
8,5 x 18	CA 20	45	ZP560D	180	215/40M+S, 225/40		
	B32	48	ZP560D	180	215/40M+S, 225/40		
7,5 x 19	RC32	50+51	-	180	225/35		Orig.-Verschr.
	RC34	48	-	180	225/35		Orig.-Verschr.
		50+51	-	180	225/35		Orig.-Verschr.
	B32	51	-	180	225/35		Orig.-Verschr.
	B39	51	-	180	225/35		Orig.-Verschr.
	AC-521	50	-	180	225/35		Orig.-Verschr.
8 x 19	CA 26	51	F90	180, 195	225/35		incl. Facelift 2024
	RC27	50	-	180	235/35		Orig.-Verschr., incl. Facelift 2024
				180, 195	225/35, 235/35		
	B38	50	-	180	225/35, 235/35		Orig.-Verschr.
	B40	50	-	180	235/35		Orig.-Verschr.
				180, 195	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
	B43	50	-	180, 195	235/35		Orig.-Verschr., incl. Facelift 2024
				180, 195	225/35, 235/35		
	RC29	49	-	180	225/35, 235/35		Orig.-Verschr.
	RC32	45	-	180	225/35		Orig.-Verschr.
	RC34	50	-	180	225/35, 235/35		Orig.-Verschr.
	B40	49	-	180, 195	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
		45	-	180, 195	225/35		Orig.-Verschr., incl. Facelift 2024
	B43	47	-	180	225/35		Orig.-Verschr.
		49	-	180, 195	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
8 x 20	AC-521	45	-	180	225/35		Orig.-Verschr.
	RC36	50	-	180, 195	235/30		Orig.-Verschr., incl. Facelift 2024
	B43	50	-	180, 195	235/30		Orig.-Verschr., incl. Facelift 2024
8,5 x 20	B38 / B43	48	ZP560D	180	235/30		
	B44	40	ZP560D		235/30		i.V.

Golf VIII GTI Clubsport

ab 2021

CD

5/112

57,1

e1*2007/46*2014*..

kein Sensor - indirektes RDKS

Dimension	Design	ET	KIT	KW	Reifendimension		Info
7,5 x 18	RC30	51	-	221	225/40		Orig.-Verschr.
	RC32	51	-	221-235	225/40		Orig.-Verschr.
				221-245	225/40		
	RC34	51	-	221-245	225/40		Orig.-Verschr.
	B32	51	-	221	225/40		Orig.-Verschr., incl. Facelift 2024
	RC30	49	-	221	225/40		Orig.-Verschr., incl. Facelift 2024
		48+49	-	221-235	225/40		Orig.-Verschr.
	RC32	50	-	221-245	225/40		Orig.-Verschr.
		46	-	221-245	225/40		Orig.-Verschr.
	RC34	50	-	221-235	225/40		Orig.-Verschr.
		48+49	-	221	225/40		Orig.-Verschr.
	B39	49	-	221	225/40		Orig.-Verschr., incl. Facelift 2024
		51	-	221	225/40		Orig.-Verschr., incl. Facelift 2024
		45	ZP560D	221	225/40		
8 x 18	AC-MB6 / AC-M10	45	- +R	221	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2024
	AC-521	50	-	221	225/40		Orig.-Verschr.
	Oxigin 25	51	ZP560D	221	225/40		
	RC27	46	-	221	225/40, 235/40		Orig.-Verschr., incl. Facelift 2024
	RC29	50	-	221	225/40, 235/40		Orig.-Verschr.
	RC32	44	-	221-245	225/40		Orig.-Verschr.
	RC34	44	-	221-245	225/40		Orig.-Verschr.
	B37	50	-	221	225/40, 235/40		Orig.-Verschr., incl. Facelift 2024
	B38	50	-	221	225/40, 235/40		Orig.-Verschr.
	RC34	48	ZP560D	221-235	225/40, 235/35, 235/40		
	B36 / B42 / B44	45	ZP560D	221	225/40, 235/40		
	AC-518	50	ZP568F	221	225/40, 235/40		
	AC-521	45	- +R	221	225/40, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
8,5 x 18	AC-M10	45	AV4+R	221	225/40, 235/40		+ Red.Ringe BA25=66,6-57,1
	CA 20	45	ZP560D	221	225/40, 235/40		
	FMI08 Thoe	49	F31+R	221-245	225/40, 235/35, 235/40		+ Red.Ringe BA25=66,6-57,1
	B32	48	ZP560D	221	225/40, 235/40		
	RC32	50+51	-	221-245	225/35		Orig.-Verschr.
	RC34	48	-	221-245	225/35		Orig.-Verschr.

7,5 x 19		50+51	-	221-245	225/35		Orig.-Verschr.
	B32	51	-	221	225/35		Orig.-Verschr.
	B39	51	-	221	225/35		Orig.-Verschr.
	RC34	45,5	ZP560D	221-245	225/35		
	AC-521	50	-	221	225/35		Orig.-Verschr.
8 x 19	CA 26	51	F90	221	225/35		incl. Facelift 2024
	RC27	50	-	221	225/35, 235/35		Orig.-Verschr.
	RC32	50	-	221-245	225/35, 235/35		Orig.-Verschr.
	B40	50	-	221	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
	B43	50	-	221	235/35		Orig.-Verschr., incl. Facelift 2024
				221	225/35, 235/35		
	RC29	49	-	221	225/35, 235/35		Orig.-Verschr.
	RC32	44	-	221-245	225/35		Orig.-Verschr.
		45	-	221-245	225/35		Orig.-Verschr.
	RC34	45	-	221-245	225/35		Orig.-Verschr.
		50	-	221-245	225/35, 235/35		Orig.-Verschr.
	B40	49	-	221	225/35, 235/35		Orig.-Verschr.
	B43	45	-	221	225/35		Orig.-Verschr., incl. Facelift 2024
		47	-	221	225/35		Orig.-Verschr.
		49	-	221	225/35, 235/35		Orig.-Verschr., incl. Facelift 2024
	RC34	43	ZP560D	221-235	225/35		
		48	ZP560D	221-235	225/35, 235/35		
	AC-521	45	-	221	225/35		Orig.-Verschr.
	FMI08 Thoe	47	F31+R	221-245	225/35, 235/35		+ Red.Ringe BA25=66,6-57,1
8 x 20	RC36	50	-	221	235/30		Orig.-Verschr., incl. Facelift 2024
	B43	50	-	221	235/30		Orig.-Verschr., incl. Facelift 2024
		48	ZP560D	235	235/30		

ID.3 (58-82 kWh Batterie)	im Laufe 2020	E1	5/112	57,1	e1*2007/46*2033*00-15
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
7,5 x 18	RC32	50	-	70	215/55	Orig.-Verschr.
	RC34	50	-	70	215/55	Orig.-Verschr.
	RC30	49+51	-	70 (150)	215/55	Orig.-Verschr., für Trommelbremse an der HA
	RC32	49	-	70	215/55	Orig.-Verschr.
	RC34	46	-	70	215/55	Orig.-Verschr.
	B32	49+51	-	70 (150)	215/55	Orig.-Verschr.
	B39	49+51	-	70 (150)	215/55, 235/50HA	Orig.-Verschr., ET49 bei HA ✖
	AC-521	50	-	70	215/55, 235/50HA	Orig.-Verschr., für Trommelbremse an der HA
	Oxigin 25	51	ZP560D	70	215/55	
	RC34	48	ZP560D	70	215/55	
7,5 x 19	RC32	50	-	70	215/50 , 225/45, 235/45	Orig.-Verschr.
	RC34	50	-	70	215/50 , 225/45, 235/45	Orig.-Verschr.
	RC32	51	-	70	215/50, 225/45	Orig.-Verschr.
	RC34	48	-	70	215/50, 225/45, 235/45	Orig.-Verschr.
		51	-	70	215/50, 225/45	Orig.-Verschr.
	RC34	45,5	ZP560D	70	215/50, 225/45, 235/45	
	AC-521	50	-	70	215/50, 225/45, 235/45	Orig.-Verschr., für Trommelbremse an der HA
	Oxigin 18	50	ZP560D	70	215/50	
8 x 19	RC27	50	-	70 (150)	225/45	Orig.-Verschr.
	RC29	49	-	70 (150)	225/45	Orig.-Verschr.
	RC32	45+50	-	70	225/45	Orig.-Verschr.
	RC34	45+50	-	70	225/45	Orig.-Verschr.
	B38	50	-	70 (150)	225/45	Orig.-Verschr.
	B40	49+50	-	70	225/45	Orig.-Verschr.
	RC34	48	ZP560D	70	225/45, 235/45	
	FMI08 Thoe	47	F31+R	70	225/45	+ Red.Ringe BA25=66,6-57,1
7,5 x 20	RC36	44	-	70	215/45	Orig.-Verschr.
	B43	44	-	70	215/45	Orig.-Verschr., für Trommelbremse an der HA
	AC-518	44	-	70 (150)	215/45	Orig.-Verschr.
	AC-521	44	-	70	215/45	Orig.-Verschr.
8 x 20	B43	47	-			Orig.-Verschr., ECE i.V.
				70	215/45	Orig.-Verschr.
		45	-	70	215/45	Orig.-Verschr., für Trommelbremse an der HA
		50	-	70	215/45, 225/40	Orig.-Verschr.
	B38	48	ZP560D	70	215/45, 225/40	
	FMI08 Thoe	45	F31+R	70	215/45	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1

ID.3 Pure, Pro, Pro Perf. NEU	2024	E1	5/112	57,1	e1*2007/46*2033*17-..
kein Sensor - indirektes RDKS					

Dimension	Design	ET	KIT	KW	Reifendimension	Info
	RC30	49	-	70	215/50, 235/50HA	Orig.-Verschr., bei 235/50 ✖

7,5 x 18	B32	48+49	-	70	215/55, 235/50HA		Orig.-Verschr., bei 235/50 ✖
		51	-	70	215/55, 235/50HA		Orig.-Verschr.
	B39	51	-	70	215/55, 235/50HA		Orig.-Verschr.
8 x 19	RC27	50	-	70	225/45		Orig.-Verschr.
	B40	49+50	-	70	225/45		Orig.-Verschr.
	B43	49+50	-	70	225/45		Orig.-Verschr.
7,5 x 20	RC36	44	-	70	215/45		Orig.-Verschr.
	B43	44	-	70	215/45		Orig.-Verschr.
8 x 20	RC36	50	-	70	215/45, 225/40		Orig.-Verschr.

ID.3 GTX Performance		NEU	2024		E1	5/112		57,1		e1*2007/46*2033*18...	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 20	RC36	47	-	89	215/45, 235/40				Orig.-Verschr.		
				70	215/45						
				89	235/40						
	B43	47	-	89	215/45, 235/40				Orig.-Verschr.		

ID.3 GTX, ProS, ProS Perf.		NEU	2024		E1	5/112		57,1		e1*2007/46*2033*16...	
kein Sensor - indirektes RDKS											
Dimension	Design	ET	KIT	KW	Reifendimension			Info			
8 x 20	RC36	47	-	70, 89	215/45				Orig.-Verschr.		
	B43	47	-	70, 89	215/45				Orig.-Verschr.		

ID.3 GTX, ProS, ProS Perf. NEU				2024	E1	5/112	57,1	e1*2007/46*2033*16..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
8 x 20	RC36	47	-	70, 89	215/45				Orig.-Verschr.
	B43	47	-	70, 89	215/45				Orig.-Verschr.

ID.4		ab 2020	E2	5/112	57,1	e1*2018/858*00004*..	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8 x 18	RC34	45	-	70	235/60, 245/55, 255/55		Orig.-Verschr.
	RC32	44+46	-	70	235/60, 245/55, 255/55		Orig.-Verschr.
	RC34	44	-	70	235/60, 245/55, 255/55		Orig.-Verschr.
	RC34	43	ZP560D	70	235/60, 245/55		
	CA 17	45	ZP560D	70	235/60		
8 x 19	RC27	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr.
	RC32	45	-	70-89	VA+HA 235/55		Orig.-Verschr.
				70-89	VA 235/55 u. HA 255/50		
					VA+HA 235/55, 245/50, 255/50 od.		
	RC34	45	-	70-89	VA 235/55+HA 255/50		Orig.-Verschr.
				VA+HA 235/55, 245/50, 255/50 od.			
	B40	45	-	70, 77	VA 235/55 u. HA 255/50		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA
	B43	45	-	70-89	VA 235/55 + HA 255/50		Orig.-Verschr.
	RC27	44	-	70	VA 235/55 u. HA 255/50		Orig.-Verschr.
	RC32	40	-	70-77	VA 235/55 u. HA 255/50		Orig.-Verschr.
		44	-	70-89	VA+HA 235/55, 245/50, 255/50 od.		Orig.-Verschr.
	RC34	44	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr.
					VA+HA 235/55, 245/50, 255/50 od.		
					VA 235/55+HA 255/50		
	RC34	43	ZP560D	70-89	VA+HA 235/55, 245/50 od.		
					VA 235/55+HA 255/50		
	AC-521	45	-	70	VA 235/55 u. HA 255/50		Orig.-Verschr., für Trommelbremse an HA, nur Bremse 358mm VA
	FMI08 Thoe	47	F31+R	70-89	VA+HA 235/55, 245/50 od.		+ Red.Ringe BA25=66,6-57,1
					VA 235/55+HA 255/50		
Oxigin 29	43	ZP560D	70-89	VA 235/55+HA 255/50		mit Trommelbremse an der HA	
8,5 x 19	B32	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA
	B37	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA
	B41	39	ZP560D	70-89	235/55		
	AC-M10	45	AV4+R	70-89	VA 235/55+HA 255/50 od. VA 255/50 u. HA 275/45		+ Red.Ringe BA25=66,6-57,1, mit Trommelbremse an HA
	CA 20	45	ZP560D	70-89	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		
	CA 23	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA
	Oxigin 28	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA
8 x 20	B40	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 20		42					
8 x 20	B40	45	-	70, 77	VA 235/50, 245/45, 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, HA bei 275/40 ✖
9 x 20		42					
8 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA
9 x 20		42					
8 x 20	B43	45	-	70-89	VA 235/50, 245/45, 255/45		Orig.-Verschr., HA bei 275/40 ✖
9 x 20		42					
8 x 20	AC-521	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., für Trommelbremse an HA
9 x 20		42					
	RC36	41+45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.

8 x 20	B40	40	-	70	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA	
		41+45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA	
	B43	41	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA	
		45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.	
		39	ZP560D	70-89	VA 235/50 u. HA 255/45			
FMI08 Thoe	45	F31+R	70-77	VA+HA 235/50, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1		
				VA 235/50+HA 255/45				
8,5 x 20	RC29	38	-	70	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA	
	B43	38+40	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA	
	RC29	40+45	ZP560D	70	VA 235/50 u. HA 255/45		nur für Trommelbremse HA, nur Bremse 358mm VA	
	RC34	43	ZP560D	70	VA 235/50 u. HA 255/45			
	B24	42	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA, nur Bremse 358mm VA	
	B43	40+43	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA	
	AF18	45	- +R	70	VA 235/50 u. HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
	AC-M10	40	- +R	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, für Trommelbremse an der HA	
	CA 17	40	ZP560D	70-77	VA 235/50 u. HA 255/45			
	FMI12 Kari	40	F94	70-77	VA+HA 235/50, 245/45, 255/45 VA 235/50+HA 255/45			
9 x 20	RC36	42	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.	
	B40	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.	
	B43	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.	
	B37	37	ZP560D	70	VA 245/45 u. HA 275/40		nur für Trommelbremse HA, nur Bremse 358mm VA, bei HA ✖	
	B41	38	ZP560D	70-77	245/45			
	AC-521	42	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr.	
	AC-522	40	- +R	70-77	VA 245/45 u. HA 265/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
	CA 20 / CA 23	45	ZP560D	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		für Trommelbremse an HA	
	FMI11 Elatha	46	- +R	70-77	VA 235/50+HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
	Oxigin 26	45	ZP560D	77	VA 245/45 u. HA 265/40			
Oxigin 28	45	ZP560D	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA		
8,5 x 21 9 x 21	B43	VA 40 HA 42	-	70, 77	VA 235/45+HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA	
VA 40 HA 42		70, 77						VA 235/45, 245/40, 255/40 HA 255/40, 275/35
8,5 x 21	B41		40	-	70-77	VA+HA 235/45		
		70-89			VA 235/45+HA 255/40			
		70-89			VA+HA 235/45, 245/40, 255/40			
		70-89			VA 235/45+HA 255/40			
	B43	40	-	70-89	VA 235/45 u. HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA	
	B41	37+43	ZP560D	70-89	VA+HA 235/45, 245/40 VA 235/45 u. HA 255/40			
9 x 21	CA 20	38	ZP568F	70-89	VA 235/45 u. HA 255/40		nur für Trommelbremse HA	
		37	ZP560D	70-89	VA 235/45 u. HA 255/40		für Trommelbremse an der HA	
		45	ZP560D	70-89	VA 235/45 u. HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA	
	FMI07 Atena	40	- +R	70-89	VA+HA 245/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
9,5 x 21	FMI10 e-Joule	41,5	F95	70-77	VA+HA 245/40			
9,5 x 22	B41	45	ZP560D	70-77	VA 245/35		HA ✖	
					HA 275/30, 285/30			

Kombinationen

8 x 19	RC32	VA 45	-	70-89	VA+HA 235/55, 245/50 od.		Orig.-Verschr.
8,5 x 19		HA 42			VA 255/50+HA 275/45		
8 x 19	RC34	VA 45	-	70-89	VA+HA 235/55, 245/50, 255/50 od.		Orig.-Verschr.
8,5 x 19		HA 42			VA 255/50+HA 275/45		

ID.4 GTX		ab 2021		E2	5/112	57,1	e1*2018/858*00004*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC27	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr.	
	B40	45	-	70, 77	VA 235/55 u. HA 255/50		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA	
	B43	45	-	70-89	VA 235/55 + HA 255/50		Orig.-Verschr.	
	FMI08 Thoe	47	F31+R	70-89	VA+HA 235/55, 245/50 od.		+ Red.Ringe BA25=66,6-57,1	
					VA 235/55+HA 255/50			
8,5 x 19	Oxigin 29	43	ZP560D	70-89	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an der HA	
	B32	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA	
	B37	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA	
	AC-M10	45	AV4+R	70-89	VA 235/55+HA 255/50 od. VA 255/50 u. HA 275/45		+ Red.Ringe BA25=66,6-57,1, mit Trommelbremse an HA	
	CA 20	45	ZP560D	70-89	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45			
	CA 23	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA	

	Oxigin 28	45	ZP560D	70, 77	VA 235/55+HA 235/50 od. VA 235/50 u. HA 275/45		mit Trommelbremse an HA
8 x 20	B40	45	-	70, 77	VA: 235/50 u. HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 20	B40	42	-	70, 77	VA 235/50, 245/45, 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, HA bei 275/40 ✖
8 x 20	B40	45	-	70, 77	HA 255/45, 275/40		
9 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA
9 x 20	B43	42	-	70-89	VA 235/50, 245/45, 255/45		Orig.-Verschr., HA bei 275/40 ✖
8 x 20	B43	42	-	70-89	HA 255/45, 275/40		
8 x 20	AC-521	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., für Trommelbremse an HA
9 x 20	AC-521	42	-	70, 77	VA 235/50 u. HA 255/45		
8 x 20	RC36	41+45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
	B40	41+45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA
	B43	41	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA
		45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
8,5 x 20	B43	38+40	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA
	B24	42	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA, nur Bremse 358mm VA
	B43 CA 17	40+43	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA
		40	ZP560D	70-77	VA 235/50 u. HA 255/45		
	AC-M10	40	- +R	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
9 x 20	RC36	42	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B40	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA
	B43	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA
	AC-521	42	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr., für Trommelbremse an HA
	AC-522	40	- +R	77	VA 245/45 u. HA 265/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
	Oxigin 26	45	ZP560D	77	VA 245/45 u. HA 265/40		
	Oxigin 28	45	ZP560D	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45+HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 21		HA 42	-	70, 77			
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45, 245/40, 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, bei 275/35 ✖
9 x 21		HA 42	-	70, 77	HA 255/40, 275/35		
8,5 x 21	B43	40	-	70-89	VA 235/45 u. HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA
	B43	38	ZP568F	70-89	VA 235/45 u. HA 255/40		nur für Trommelbremse HA
9 x 21	CA 20	37	ZP560D	70-89	VA 235/45 u. HA 255/40		für Trommelbremse an der HA
		45	ZP560D	70-89	VA 235/45 u. HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA
	CA 17	45	ZP560D	77	VA 245/40+HA 275/35		

ID.4 PURE	ab 2022	5/112	57,1	e1*2018*858*00004*...
kein Sensor - indirektes RDKS				

Dimension	Design	ET	KIT	KW	Reifendimension	Info
8 x 18	RC27	44	-	70	235/60, 245/55, 245/60, 255/55	Orig.-Verschr., für Trommelbremse an der HA
	AC-MB6	45	ZP560D	70	235/60, 245/55, 245/60, 255/55	
	AC-M10	40	- +R	70	235/60, 245/55, 245/60, 255/55	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
		45	AV4+R	70	235/60, 245/55, 245/60, 255/55	+ Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	AC-521	45	- +R	70	235/60, 245/55, 245/60, 255/55	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	AC-522	40	- +R	70	235/60, 245/55, 245/60, 255/55	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	CA 17	45	ZP560D	70	235/60, 245/55, 245/60, 255/55	für Trommelbremse an der HA
	CA 20	45	ZP560D	70	235/60, 245/55, 245/60, 255/55	
8 x 19	RC27	45	-	70	235/55	 Orig.-Verschr.
	B40	45	-	70	235/55, 245/50, 255/50	 Orig.-Verschr., für Trommelbremse an der HA
	B43	45	-	70	235/55, 245/50, 255/50	 Orig.-Verschr., für Trommelbremse an der HA
	RC29	40	-	70	235/55, 245/50, 255/50HA	Orig.-Verschr., für Trommelbremse an der HA
	RC29	45	ZP560D	70	235/55, 245/50, 255/50	 für Trommelbremse an der HA
	Oxigin 29	43	ZP560D	70	235/55, 245/50, 255/50HA	mit Trommelbremse an der HA
8,5 x 19	B32	45	ZP560D	70	235/55, 245/50, 255/50HA, 275/45HA	für Trommelbremse an der HA
	B37	45	ZP560D	70	235/55, 245/50, 255/50HA, 275/45HA	für Trommelbremse an der HA
	AC-M10	45	AV4+R	70	235/55, 245/50, 255/50HA, 275/45HA	+ Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	CA 20	45	ZP560D	70	235/55, 245/50, 255/50HA, 275/45HA	
	CA 23	45	ZP560D	70	235/55, 245/50, 255/50HA, 275/45HA	für Trommelbremse an der HA
	Oxigin 28	45	ZP560D	70	235/55, 245/50, 255/50HA, 275/45HA	für Trommelbremse an der HA
8 x 20	RC36	45	-	70	235/50, 245/45, 255/45	 Orig.-Verschr.
	B43	45	-	70	235/50, 245/45, 255/45	 Orig.-Verschr.
	RC36	41	-	70	235/50, 245/45, 255/45	Orig.-Verschr.
	RC36	45	-	70	235/50, 245/45, 255/45	 Orig.-Verschr.

	B43	41	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
		41	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
		39	ZP560D	70	235/50, 245/45, 255/45		
8,5 x 20	B43	38+40	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
	B42	40+45	ZP560D	70	235/50, 245/45, 255/45		für Trommelbremse an der HA
	B43	40	ZP560D	70	235/50, 245/45, 255/45		für Trommelbremse an der HA
	AC-521	45	-	70	245/45, 255/45		Orig.-Verschr.
	AC-M10	40	- +R	70	235/50, 245/45, 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, für Trommelbremse an der HA
	CA 17	40	ZP560D	70	235/50, 245/45		
9 x 20	RC36	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
	B40	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
	AC-521	42	-	70	235/50, 245/45, 255/45		Orig.-Verschr.
	AC-522	40	- +R	70	245/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	70	235/50, 245/45, 255/45, 275/40HA		mit Trommelbremse an der HA
	Oxigin 28	45	ZP560D	70	235/50, 245/45, 255/45, 275/40HA		mit Trommelbremse an der HA
8 x 20	B40	45	-	70	VA 235/50, 245/45, 255/45		Orig.-Verschr., mit Trommelbremse an der HA, HA bei 275/40 ✖
9 x 20		42			HA 245/45, 255/45, 275/40		
8 x 20	AC-521	45	-	70	VA 235/50, 245/45, 255/45		Orig.-Verschr., mit Trommelbremse an der HA, HA bei 275/40 ✖
9 x 20		42			HA 245/45, 255/45, 275/40		
8,5 x 21	B43	40	-	70	235/45, 245/40, 255/40		Orig.-Verschr.
		38	ZP568F	70	235/45, 245/40, 255/40		für Trommelbremse an der HA
9 x 21	CA 20	37	ZP560D	70	235/45, 245/40, 255/40HA		für Trommelbremse an der HA
		45	ZP560D	70	235/45, 245/40, 255/40, 275/35HA		für Trommelbremse an der HA

Kombinationen

8,5 x 20	B42	VA 40	ZP560D	70	VA 235/50		
9,5 x 20		HA 42			HA 255/45		

ID.5							
ab April 2022				E2	5/112	57,1	e1*2018/858*00004*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
8 x 18	RC32	40	-	70	235/60		Orig.-Verschr.
		44	-	70	235/60, 245/55, 255/55		Orig.-Verschr.
	RC34	40	-	70	235/60		Orig.-Verschr.
		44	-	70	235/60, 245/55, 255/55		Orig.-Verschr.
8 x 19	RC27	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr.
	RC32	45	-	70-89	VA+HA 235/55, 245/50, 255/50 od. VA 235/55 u. HA 255/50		Orig.-Verschr.
					VA+HA 235/55, 245/50, 255/50 od. VA 235/55 u. HA 255/50		Orig.-Verschr.
	RC34	45	-	70-89	VA+HA 235/55, 245/50, 255/50 od. VA 235/55 u. HA 255/50		Orig.-Verschr.
					VA+HA 235/55, 245/50, 255/50 od. VA 235/55 u. HA 255/50		Orig.-Verschr.
	B40	45	-	70, 77	VA 235/55 + HA 255/50		Orig.-Verschr., für Trommelbremse an der HA, nur Bremse 358mm VA
	B43	45	-	70-89	VA 235/55 + HA 255/50		Orig.-Verschr.
	AC-521	45	-	70	VA 235/55 u. HA 255/50		Orig.-Verschr., für Trommelbremse an HA, nur Bremse 358mm VA
	RC32	44	-	70-89	VA+HA 235/55, 245/50, 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr.
					VA+HA 235/55, 245/50, 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr.
	RC34	44	-	70-89	VA+HA 235/55, 245/50, 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr.
					VA+HA 235/55, 245/50, 255/50 od. VA 235/55+HA 255/50		Orig.-Verschr.
8,5 x 19	FMI08 Thoe	47	F31+R	70-89	VA 235/55, 245/50 od. VA 235/55+HA 255/50		+ Red.Ringe BA25=66,6-57,1
	Oxigin 29	43	ZP560D	70-89	VA 235/55+HA 255/50		mit Trommelbremse an der HA
	B32	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA
	B37	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA
	B41	39	ZP560D	70-89	235/55		
	AC-M10	45	AV4+R	70-89	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		+ Red.Ringe BA25=66,6-57,1, mit Trommelbremse an HA
	CA 20	45	ZP560D	70-89	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		
	CA 23	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA
	FMI05 Makhai	45	- +R	70-89	VA 235/55+HA 255/50		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 28	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA
8 x 20	B40	45	-	70, 77	VA: 235/50 u. HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 20		42			VA 235/50, 245/45, 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, HA bei 275/40 ✖
8 x 20	B40	45	-	70, 77	HA 255/45, 275/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, HA bei 275/40 ✖
9 x 20		42			VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA
8 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA
9 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA
8 x 20		42			VA 235/50, 245/45, 255/45		Orig.-Verschr. HA bei 275/40 ✖

9 x 20	AC-521	42	-	70, 77	HA 255/45, 275/40		Orig.-Verschr., für Trommelbremse an HA
8 x 20		45			VA 235/50 u. HA 255/45		Orig.-Verschr., für Trommelbremse an HA
9 x 20		42					
8 x 20	RC36	41+45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
	B40	41+45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA
	B43	41	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
		45	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.
39		ZP560D	70-89	VA 235/50 u. HA 255/45			
8,5 x 20	B43	38+40	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B43	40	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA
	CA 17	40	ZP560D	70-77	VA 235/50 u. HA 255/45		
	AC-M10	40	- +R	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, für Trommelbremse an der HA
	FMI12 Kari	40	F94	70-77	VA+HA 235/50, 245/45, 255/45 od. VA 235/50 u. HA 255/45		
9 x 20	RC36	42	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B40	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B43	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	AC-521	42	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr.
	AC-522	40	- +R	70-77	VA 245/45+HA 265/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
	FMI11 Elatha	46	- +R	70-77	VA 235/50+HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
8,5 x 20	Oxigin 28	45	ZP560D	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
	B24	42	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA, nur Bremse 358mm VA
	B43	43	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45+HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 21		HA 42					
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45, 245/40, 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, bei 275/35 ✖
9 x 21		HA 42			HA 255/40, 275/35		
8,5 x 21	B41	40+43	-	70-89	VA+HA 235/45, 245/40, 255/40 od. VA 235/45+HA 255/40		Orig.-Verschr.
		B43	40	-	70-89	VA 235/45+HA 255/40	
	B41	37	ZP560D	70-89	VA+HA 235/45, 245/40 VA 235/45 u. HA 255/40		
		B43	38	ZP568F	70-89	VA 235/45 u. HA 255/40	
	9 x 21	CA 20	37	ZP560D	70-89	VA 235/45 u. HA 255/40	
45			ZP560D	70-89	VA 235/45 u. HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA
FMI07 Atena		40	- +R	70-89	VA+HA 245/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
9,5 x 21	FMI10 e-Joule	41,5	F95	70-77	VA+HA 245/40		

Kombinationen

8 x 19	RC32	VA 45	-	70-89	VA+HA 235/55, 245/50 od.		Orig.-Verschr.
8,5 x 19		HA 42			VA 255/50+HA 275/45		

ID.5 GTX				ab April 2022	E2	5/112	57,1	e1*2018/858*00004*..
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension	Info		
8 x 19	RC27	45	-	70-89	VA 235/55 u. HA 255/50		Orig.-Verschr.	
	B40	45	-	70, 77	VA 235/55 + HA 255/50		Orig.-Verschr., für Trommelbremse an der HA, nur Bremse 358mm VA	
	B43	45	-	70-89	VA 235/55 + HA 255/50		Orig.-Verschr.	
	FMI08 Thoe	47	F31+R	70-89	VA+HA 235/55, 245/50 od.		+ Red.Ringe BA25=66,6-57,1	
	Oxigin 29	43	ZP560D	70-89	VA 235/55+HA 255/50		mit Trommelbremse an der HA	
8,5 x 19	B32	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA	
	B37	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA	
	AC-M10	45	AV4+R	70-89	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		+ Red.Ringe BA25=66,6-57,1, mit Trommelbremse an HA	
	CA 20	45	ZP560D	70-89	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45			
	CA 23	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA	
	Oxigin 28	45	ZP560D	70, 77	VA 235/55+HA 255/50 od. VA 245/50 u. HA 275/45		nur für Trommelbremse HA	
8 x 20	B40	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA	
9 x 20		42						
8 x 20	B43	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur Trommelbremse HA	
9 x 20		42						
8 x 20	B43	45	-	70-89	VA 235/50, 245/45, 255/45		Orig.-Verschr., HA bei 275/40 ✖	
9 x 20		42			HA 255/45, 275/40			

8 x 20	AC-521	45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., für Trommelbremse an HA
9 x 20		42					
8 x 20	RC36	41+45	-	70-89	VA 235/50+HA 255/45		Orig.-Verschr.
	B40	41+45	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr., nur für Trommelbremse HA, nur Bremse 358mm VA
	B43	41	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
		45	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.
		39	ZP560D	70-89	VA 235/50 u. HA 255/45		
8,5 x 20	B43	38+40	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B24	42	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA, nur Bremse 358mm VA
	B43 CA 17	40+43	ZP560D	70, 77	VA 235/50 u. HA 255/45		nur für Trommelbremse HA
		40	ZP560D	70-77	VA 235/50 u. HA 255/45		
9 x 20	AC-M10	40	- +R	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1 , für Trommelbremse an der HA
	RC36	42	-	70-89	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B40	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	B43	42	-	70, 77	VA 235/50 u. HA 255/45		Orig.-Verschr.
	AC-521	42	-	70, 77	VA 235/50+HA 255/45		Orig.-Verschr., für Trommelbremse an HA
	AC-522	40	- +R	70-77	VA 245/45+HA 265/40		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
8,5 x 21	CA 23	45	ZP560D	70-89	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
	Oxigin 28	45	ZP560D	70, 77	VA 235/50+HA 255/45 od. VA 245/45+HA 275/40		mit Trommelbremse an der HA
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45+HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA
9 x 21		HA 42					
8,5 x 21	B43	VA 40	-	70, 77	VA 235/45, 245/40, 255/40		Orig.-Verschr., mit Trommelbremse an der HA, nur mit Bremse 358mm VA, bei 275/35 ✖
9 x 21		HA 42			HA 255/40, 275/35		
8,5 x 21	B43	40	-	70-89	VA 235/45 u. HA 255/40		Orig.-Verschr., mit Trommelbremse an der HA
	B43	38	ZP568F	70-89	VA 235/45 u. HA 255/40		für Trommelbremse an der HA
9 x 21	CA 20	37	ZP560D	70-89	VA 235/45 u. HA 255/40		für Trommelbremse an der HA
		45	ZP560D	70-89	VA 235/45 u. HA 255/40, VA 245/40+HA 275/35		für Trommelbremse an der HA

ID.Buzz Cargo / Pro NEU		4. Quartal 2022		EB / EBN		5/112		57,1		e1*2018/858*00165*..., e1*2018/858*00164*...			
kein Sensor - indirektes RDKS													
Dimension		Design		ET		KIT		KW		Reifendimension		Info	
8 x 18 8,5 x 18		RC34		VA 45 HA 56		- (V12)		70		VA 235/60+HA 255/55		 Orig.-Verschr., Ausführung V12	
8 x 18 8,5 x 18		AC-521		VA 44 HA 55		Kit Art.Nr. 98547		70, 89		VA 235/60+HA 255/55		 Kit mit Artikelnummer 98547 verwenden, mit Trommelbremse an der HA	
8 x 19 9 x 19		RC34		VA 45 HA 58		- (V12)		70-89		VA 235/55+HA 255/50		 Orig.-Verschr.	
8 x 19 9 x 19		B40		VA 45 HA 58		- (V12)		70 (150)		VA 235/55+HA 255/50		 Orig.-Verschr., mit Trommelbremse an der HA, Ausführung V12 , Felge i.V.	
8 x 19 9 x 19		B43		VA 45 HA 58		- (V12)		70 (150)		VA 235/55+HA 255/50		 Orig.-Verschr., Felge u. TÜV i.V., Ausführung V12	
8 x 19 9 x 19		B43		VA 43 HA 53		ZP560D				VA 235/55+HA 255/50			
8 x 20 10 x 20		RC36		VA 45 HA 58		- (V12)		70-89		VA 235/50+HA 265/45		 Orig.-Verschr., normaler Radstand, nur Bremse 358mm VA	
8 x 20 10 x 20		RC36		VA 45 HA 58		- (V12)		89, 90		VA 235/50+HA 265/45		 Orig.-Verschr., langer Radstand, nur Bremse 358mm VA	
8 x 20 10 x 20		B43		VA 45 HA 58		- (V12)		70-89		VA 235/50+HA 265/45		 Orig.-Verschr., normaler Radstand, nur Bremse 358mm VA	
8 x 20 10 x 20		B43		VA 45 HA 58		- (V12)		89, 90		VA 235/50+HA 265/45		 Orig.-Verschr., langer Radstand, nur Bremse 358mm VA	
8,5 x 21 10 x 21		B43		VA 40 HA 58		- (V12)		70 (150)		VA 235/45+HA 265/40		 Orig.-Verschr., mit Trommelbremse an der HA, Ausführung V12	
8,5 x 21 10 x 21		B43		VA 40 HA 58		- (V12)		70 (150)		VA 235/45, 245/40, 255/40 HA 255/40, 265/40, 275/35, 285/35		 Orig.-Verschr., mit Trommelbremse an der HA, Ausführung V12 , normaler Radstand, nur Bremse 358mm VA	

ID.Buzz GTX NEU		ab 2024		EB	5/112	57,1	e1*2018/858*00164*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 20	RC36	VA 45	-	70-89	VA 235/50		Orig.-Verschr., normaler Radstand, nur Bremse 358mm VA	
10 x 20		HA 58			HA 265/45			
8 x 20		VA 45	-	89, 90	VA 235/50		Orig.-Verschr., langer Radstand, nur Bremse 358mm VA	
10 x 20		HA 58			HA 265/45			
8 x 20	B43	VA 45	-	70-89	VA 235/50		Orig.-Verschr., normaler Radstand, nur Bremse 358mm VA	
10 x 20		HA 58			HA 265/45			
8 x 20		VA 45	-	89, 90	VA 235/50		Orig.-Verschr., langer Radstand, nur Bremse 358mm VA	
10 x 20		HA 58			HA 265/45			

8,5 x 21	B43	VA 40	-	89, 90	VA 235/45, 245/40, 255/40		Orig.-Verschr., langer Radstand, nur Bremse 358mm VA
10 x 21		HA 58			HA 255/40, 265/40, 275/35, 285/35		

ID.7 NEU		2.Quartal 2023		ED	5/112	57,1	e1*2018/858*00306*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 19	RC32	VA 45	-	89-90	VA 235/50+HA 255/45		Orig.-Verschr.	
8,5 x 19		HA 42						
8 x 19	RC34	VA 45	-	89-90	VA 235/50+HA 255/45		Orig.-Verschr.	
8,5 x 19		HA 42						
8,5 x 19	RC32	38	-	89-90	VA 235/50+HA 255/45		Orig.-Verschr., VA ✖	
	RC34	38	-	89-90	VA 235/50+HA 255/45		Orig.-Verschr., VA ✖	
	B41	39	ZP560D	89	VA 235/50+HA 255/45		VA ✖	
	AC-M10	45	AV4+R	89 (210)	VA 235/50+HA 255/45 od. HA 265/45		+Red.Ringe BA25=66,6-57,1, mit Trommelbremse an HA	
	CA 20	45	ZP560D	89, 90	VA 235/50+HA 255/45 od. HA 265/45			
	FMI05 Makhai	45	- +R	89	VA 235/50+HA 255/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	
9 x 19	FMI08 Thoe	41	F31+R	89	VA 245/45+HA 265/40		+Red.Ringe BA25=66,6-57,1	
8,5 x 20	B41	35	ZP560D	89-90	VA 235/45+HA 255/40			
	RC36	42	-	89, 90	VA 235/45+HA 265/40 od. VA 245/40+HA 275/35		Orig.-Verschr., incl. Tourer	
9 x 20	B41	38	ZP560D	89	VA 235/45+HA 255/40			
	CA 20 / CA 23	45	ZP560D	89 (210)	VA 235/45+HA 255/40, VA 235/45+HA 265/40, VA 245/40+HA 275/35		mit Trommelbremse an HA	
	FMI11 Elatha	34	- +R	89	VA 235/45+HA 255/40		Orig.-Verschr. +Red.Ringe BA25, VA ✖	
	B43	40	-	89 (210)	255/35		Orig.-Verschr., mit Trommelbremse an HA ✖	
9 x 21	CA 20	45	ZP560D	89 (210)	VA 245/35+HA 275/30		mit Trommelbremse an HA	
	FMI07 Atena	40	- +R	89	VA 245/35+HA 275/30		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1	

Kombinationen

8 x 20	B43	VA 45	-	89, 90	VA 235/45, 245/40		Orig.-Verschr.
9 x 20		HA 42			HA 255/40, 265/40, 275/35		
8,5 x 20	B42	VA 40	ZP560D	89, 90	VA 235/45		incl. Tourer
9,5 x 20		HA 42			HA 255/40		
8,5 x 21	B43	VA 40	-	89	VA 245/35		Orig.-Verschr.
9 x 21		HA 42		89	HA 275/30		
				89, 90	HA 265/35		

ID.7 GTX Kombi NEU		im Laufe 2024		ED	5/112	57,1	e1*2018/858*00306*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
Kombinationen								
8,5 x 20	B42	VA 40	ZP560D	89, 90	VA 235/45			incl. Tourer
9,5 x 20		HA 42		HA 255/40				
8,5 x 21	B43	VA 40	-	89	VA 245/35			Orig.-Verschr.
9 x 21		HA 42		89	HA 275/30			
				89, 90	HA 265/35			

Taigo NEU		1. Quartal 2022			CS	5/100	57,1	e13*2018/858*00140*..	
kein Sensor - indirektes RDKS									
Dimension	Design	ET	KIT	KW	Reifendimension			Info	
6 x 16	RC27	35	-	70, 81	205/55, 205/60, 215/55				Orig.-Verschr.
				70,81,110	195/60, 195/65, 205/55, 205/60, 215/55				Orig.-Verschr., nur M+S
	RC30	35	-	70, 81	205/55, 205/60, 215/55				Orig.-Verschr.
				70,81,110	195/60, 195/65, 205/55, 205/60, 215/55				Orig.-Verschr., nur M+S
	RC34	35	-	70-110	195/60, 205/60				Orig.-Verschr.
	RC27	38	-	70, 81	205/55, 205/60, 215/55				Orig.-Verschr.
				70,81,110	195/60, 195/65, 205/55, 205/60, 215/55			Orig.-Verschr., nur M+S	
	RC30	38	-	70, 81	205/55, 205/60, 215/55				Orig.-Verschr.
70,81,110				195/60, 195/65, 205/55, 205/60, 215/55				Orig.-Verschr., nur M+S	
6,5 x 16	RC27	40	-	70, 81	205/55, 205/60, 215/55, 225/50, 225/55				Orig.-Verschr.
				70,81,110	195/60, 195/65, 205/55, 205/60, 215/55				Orig.-Verschr., nur M+S
	RC30	38	-	70, 81	205/55, 205/60, 215/55, 225/50, 225/55				Orig.-Verschr.
				70,81,110	195/60, 195/65, 205/55, 205/60, 215/55				Orig.-Verschr., nur M+S
	RC34	40	-	70-110	205/55, 215/55, 215/60, 225/50, 225/55, 235/50, 235/55				Orig.-Verschr.
	CA 20	38	ZP516	70, 81	205/55, 205/60, 215/55, 225/50, 225/55				
70,81,110				195/60, 195/65, 205/55, 205/60, 215/55				nur M+S	
6,5 x 17	RC27	39	-	70,81,110	205/55				Orig.-Verschr.
	RC34	39	-	70-110	205/50, 205/55, 215/50, 225/50				
7,5 x 17	RC28 / RC29	38	ZP516	70,81,110	205/50, 205/55, 215/50, 225/45, 235/45				
	B24	38	ZP516	70,81,110	205/50, 205/55, 215/50, 225/45, 235/45				
	B36	38	ZP516	70,81,110	205/50, 205/55, 215/50, 225/45, 235/45				
7 x 18	RC32	39	-		215/45				Orig.-Verschr., i.V.

	RC34	39	-	70-110	215/45		Orig.-Verschr.
8 x 18	B24	38	ZP516	70, 81, 110	215/45		
	B42 / B44	35	ZP516	70,81,110	215/45		
8 x 19	B40	39	ZP516	70,81,110	215/35, 225/35, 225/40		

T-ROC							
ab 11.2017				A1	5/112	57,1	e13*2007/46*1845*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 16	RC27	43	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC30	43	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC34	43	-	81-140	205/60, 215/60		Orig.-Verschr.
			-	81-110	205/60, 205/65, 215/55, 215/60, 225/55		Orig.-Verschr., Frontantrieb
			-	110-140	205/60, 205/65, 215/60, 225/55		Orig.-Verschr., Allrad
	RC27	48	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC30	48	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
6,5 x 16	RC24	43	-	81-140	205/60, 205/65, 215/60 , 225/55, 225/60		Orig.-Verschr.
		43	-	81-140	205/60, 205/65, 215/60 , 225/55, 225/60		Orig.-Verschr.
	RC32	43	-	85-110	205/60, 205/65, 215/55, 215/60 , 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
			-	110-140	205/60, 205/65, 215/60 , 225/55, 235/55		Orig.-Verschr., Allrad
	RC34	43	-	81-110	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
			-	110-140	205/60, 205/65, 215/60, 225/55, 235/55		Orig.-Verschr., Allrad
	RC27	42+46	-	81-140	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
		44	-	85-140	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
	RC30	39+41+ 42+44+ 46	-	85-140	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr.
		41+46+ 48	-	85-110	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
			-	110-140	205/60, 205/65, 215/60, 225/55, 235/55		Orig.-Verschr., Allrad
	RC34	46+48	-	81-110	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., Frontantrieb
			-	110-140	205/60, 205/65, 215/60, 225/55, 235/55		Orig.-Verschr., Allrad
	CA 20	45	ZP560D	81-140	205/60, 205/65, 215/60, 225/55, 225/60		
	Pro1	48	F31+R	81-110	205/60, 205/65, 215/55, 215/60, 225/55, 235/50, 235/55		+ Ringe BA25=66,6-57,1, Frontantrieb
				110-140	205/60, 205/65, 215/60, 225/55, 235/55		+ Ringe BA25=66,6-57,1, Allrad
6,5 x 17	RC27	39+43	-	85-140	205/55, 205/60, 215/50, 215/55, 225/50		Orig.-Verschr.
		46+48,5	-	85-140	205/55, 205/60, 215/50, 215/55, 225/50		Orig.-Verschr.
7 x 17	RC27	45	-	81-140	205/55, 205/60, 215/50, 215/55 , 225/50		Orig.-Verschr.
	RC30	45	-	81-140	205/55, 205/60, 215/50, 215/55 , 225/50		Orig.-Verschr.
	RC32	45	-	85-140	215/55		Orig.-Verschr.
			-	85-110	205/55, 215/50, 215/55, 225/45, 225/50, 225/55, 235/50		Orig.-Verschr., Frontantrieb
			-	110-140	205/55, 215/55, 225/50, 235/50		Orig.-Verschr., Allrad
	RC34	45	-	81-140	215/55		Orig.-Verschr.
	CA 26	45	-	81-140	205/55, 205/60, 215/50, 215/55 , 225/50		Orig.-Verschr.
	RC32	46+47	-	85-110	205/55, 215/50, 215/55, 225/45, 225/50, 225/55, 235/50		Orig.-Verschr., Frontantrieb
			-	110-140	205/55, 215/55, 225/50, 235/50		Orig.-Verschr., Allrad
	RC34	40	-	81-110	205/55, 215/50, 215/55, 225/45, 225/50, 225/55		Orig.-Verschr., Frontantrieb
7,5 x 17	RC24	40	-	81-140	205/55, 215/55, 225/50		Orig.-Verschr., Allrad
		40	-	81-140	205/55, 205/60, 215/50, 215/55		Orig.-Verschr.
	RC27	42+47	ZP560D	81-140	205/55, 205/60, 215/50, 215/55, 225/50		
		35	-	85-140	205/55, 205/60, 215/50, 215/55		Orig.-Verschr.
	RC32	43	-	81-110	205/55, 215/50, 215/55, 225/45, 225/50, 225/55, 235/45, 245/45		Orig.-Verschr.
			-	110-140	205/55, 215/55, 225/50, 245/45		Orig.-Verschr.
	RC34	41	-	81-110	205/55, 215/50, 215/55, 225/45, 235/45		Orig.-Verschr., Frontantrieb
		46+47	-	110-140	205/55, 215/55		Orig.-Verschr., Allrad
	RC28 / RC29	45	ZP560D	85-140	205/55, 205/60, 215/50, 215/55		Orig.-Verschr.
		47	ZP560D	81-140	205/55, 205/60, 215/50, 215/55		
	B24 / B38	45	ZP560D	81-221	205/50, 205/55, 205/60, 215/50, 215/55, 235/45		
	Oxigin 25	45	-	81-140	205/50, 205/55, 205/60, 215/50, 215/55, 235/45		auch Allrad
			-	85-140	205/55, 215/45, 215/50 , 225/45, 225/50		Orig.-Verschr.
	RC32	45	-	85-110	215/50		Orig.-Verschr.
			-	85-110	205/50, 215/45, 215/50, 225/45		Orig.-Verschr., Frontantrieb
			-	110-140	205/50, 215/50, 225/45		Orig.-Verschr., Allrad
7 x 18	RC34	45	-	81-140	215/50		Orig.-Verschr.

7,5 x 18	RC27	43	-	85-140	205/55, 215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
	RC32	45+48	-	85-110	205/50, 215/45, 215/50, 225/40, 225/45, 235/45, 245/45		Orig.-Verschr., Frontantrieb
				110-140	205/50, 215/50, 225/45, 235/45		Orig.-Verschr., Allrad
	RC34	40	-	81-110	205/50, 215/45, 215/50, 225/40, 225/45, 235/45		Orig.-Verschr., Frontantrieb
				110-140	205/50, 215/50, 225/45, 235/45		Orig.-Verschr., Allrad
		46	-	81-110	205/50, 215/45, 215/50, 225/40, 225/45, 235/45, 245/45		Orig.-Verschr., Frontantrieb
	110-140			205/50, 215/50, 225/45, 235/45		Orig.-Verschr., Allrad	
	B32	48	-	85-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC30	45	ZP560D	81-140	215/45, 215/50, 225/45, 235/45		
	B39	45	ZP560D	85-140	215/45, 215/50, 225/45, 235/45		
AC-MB6	45	- +R	81-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
Oxigin 18	45	-	85-140	205/55, 215/45, 215/50, 225/40, 225/45, 235/45		Orig.-Verschr., auch Allrad	
Oxigin 25	51	ZP560D	110-221	215/45			
8 x 18	RC27	40	-	85-140	215/45, 225/40, 225/45		Orig.-Verschr., auch Allrad
		44	-	81-140	215/50, 225/45, 235/45		Orig.-Verschr.
		46	-	85-140	225/40, 225/45		Orig.-Verschr., auch Allrad
	RC29	40	-	85-140	225/45		Orig.-Verschr.
		44	-	85-140	215/50, 225/45, 235/45		
	RC32	40	-	85-110	215/45, 225/40, 225/45		Orig.-Verschr., Frontantrieb
				110-140	225/45		Orig.-Verschr., Allrad
		44	-	85-110	215/45, 225/40, 225/45, 235/40, 235/45		Orig.-Verschr., Frontantrieb
				110-140	225/45, 235/45, 245/40		Orig.-Verschr., Allrad
		46	-	85-110	215/45, 225/40, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., Frontantrieb
				110-140	225/45, 235/45, 245/40		Orig.-Verschr., Allrad
	RC34	40	-	85-110	215/45, 225/40, 225/45		Orig.-Verschr., Frontantrieb
				110-140	225/45		Orig.-Verschr., Allrad
		44	-	81-110	215/45, 215/50, 225/40, 225/45, 235/40, 235/45		Orig.-Verschr., Frontantrieb
				110-140	215/50, 225/45, 235/45, 245/40		Orig.-Verschr., Allrad
		45	-	85-110	215/45, 225/40, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., Frontantrieb
				110-140	215/50, 225/45, 235/45, 245/40		Orig.-Verschr., Allrad
	B37	44	-	81-140	215/50, 225/45, 235/45		Orig.-Verschr.
	B38	44	-	85-140	215/50, 225/45, 235/45		Orig.-Verschr.
	B24	48	ZP560D	81-140	225/45		
	B36 / B37 / B42	45	ZP560D	81-140	215/50, 225/45, 235/45		
	B44	45	ZP560D	81-140	215/50, 225/45, 235/45		
	AC-M10	40	- +R	81-140	225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-518	40	AV4+R	85-140	225/45		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	81-140	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-522	40	- +R	81-140	225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-M10	45	AV4+R	81-140	215/50, 225/45, 235/45		+ Red.Ringe BA25=66,6-57,1
	AF18 / AF20	48	-	85-140	225/45		Orig.-Verschr.
	CA 17 / CA 20	45	ZP560D	81-140	215/50, 225/45, 235/45		
	7,5 x 19	FMI12 Kari	45	Kit 0353	81-110	215/45, 215/50, 225/45, 235/45, 245/40	
110-140					215/50, 225/45, 235/45, 245/40		Allrad
RC34		48	-	81-110	215/35, 225/35, 225/40		Orig.-Verschr., Frontantrieb
				110-140	225/40		Orig.-Verschr., Allrad
B32		43	-	85-140	225/40		Orig.-Verschr.
RC34		45,5	ZP560D	81-110	215/35, 225/35, 225/40		Frontantrieb
				110-140	225/40		Allrad
CA 26		40	ZP560D	81-140	225/40		
Oxigin 18		37	-	85-140	225/35, 225/40		Orig.-Verschr.
8 x 19		B43	47	-	81-140	225/40	
	RC27	44	-	85-140	225/35, 225/40, 235/35, 235/40		Orig.-Verschr.
	RC29	40	-	85-140	225/40		Orig.-Verschr.
	RC32	40	-	81-110	215/35, 225/35, 225/40		Orig.-Verschr., Frontantrieb
				110-140	225/40		Orig.-Verschr., Allrad
		45	-	81-110	215/35, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr., Frontantrieb
				110-140	225/40, 235/40, 245/35		Orig.-Verschr., Allrad
	RC34	40	-	81-110	215/35, 225/35, 225/40		Orig.-Verschr., Frontantrieb
				110-140	225/40		Orig.-Verschr., Allrad
		45	-	81-110	215/35, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr., Frontantrieb
				110-140	225/40, 235/40, 245/35		Orig.-Verschr., Allrad
	B38	44	-	85-140	225/40, 235/40		Orig.-Verschr.
	B40	40	-	85-140	225/40		Orig.-Verschr.
		45	-	85-140	225/40, 235/40		Orig.-Verschr.
	B43	40	-	81-140	225/40		Orig.-Verschr.
		45	-	81-140	225/40, 235/40		Orig.-Verschr.
	RC29	45	ZP560D	85-140	225/40, 235/40		
	RC34	43	ZP560D	85-110	215/35, 225/35, 225/40, 235/35		Frontantrieb
				110-140	225/40, 235/40		Allrad
		48	ZP560D	85-110	215/35, 225/35, 225/40, 235/35, 235/40, 245/35		Frontantrieb
110-140				225/40, 235/40, 245/35		Allrad	

	B24 / B38	45	ZP560D	85-140	225/40, 235/40		
	B40	43	ZP560D	85-140	225/40, 235/40		
		45	-	85-140	225/40, 235/40		Orig.-Verschr.
	AC-518	38	AV4+R	85-140	225/40		+ Red.Ringe BA25=66,6-57,1
		47	AV4	85-140	225/40		
	AC-521	45	-	81-140	225/40, 235/40		Orig.-Verschr.
	CA 17	45	ZP560D	110-221	225/35, 225/40		
	CA 19	47	ZP560D	81-221	225/35, 225/40		
	FMI07 Atena	47	- +R	85-110	215/35, 225/35, 225/40, 235/35, 235/40, 245/35		Orig.-Verschr., + Ringe BA25 , Frontantrieb
				110-140	225/40, 235/40, 245/35		Orig.-Verschr., + Ringe BA25 , Allrad
	FMI08 Thoe Oxigin 29	47	F31+R	81-140	225/40, 235/40, 245/35		+ Red.Ringe BA25=66,6-57,1
		43	ZP560D	81-140	225/40, 235/40		
	B32	42	-	85-140	225/40, 235/40		Orig.-Verschr., bei 235/40 ✖
8,5 x 19	B36	45	ZP560D	85-140	225/40		
	B37	43+45	ZP560D	85-140	225/40		
	B42 / B44	42	ZP560D	81-140	225/40		
	AC-M10	45	AV4+R	81-140	225/40		+Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	81-140	225/40		
	FMI07 Atena	45	- +R	85-110	225/35, 225/40, 235/35		Orig.-Verschr. +Ringe BA25 , Frontantrieb
				110-140	225/40, 235/40		Orig.-Verschr. +Ringe BA25 , Allrad
	8300 - 1972	45	F85+R	81-110	225/35, 225/40, 235/35		+ Ringe BA25 , Frontantrieb
				110-140	225/40, 235/40		+ Ringe BA25 , Allrad
	Oxigin 18	45	ZP560D	85-140	225/40		
	Oxigin 19 / 20	45	ZP560D	85-221	225/35, 225/40		
	Oxigin 25	45	ZP560D	85-221	225/35, 225/40		
	Oxigin 28	45	ZP560D	81-140	225/40		
8 x 20	RC36	45	-	81-140	235/35		Orig.-Verschr.
	B43	45	-	81-140	235/35		Orig.-Verschr.
	FMI08 Thoe	45	F31+R	81-110	225/30, 225/35, 245/30		+Ringe BA25=66,6-57,1 , Frontantrieb
				110-140	225/35, 235/35, 245/30		+Ringe BA25=66,6-57,1 , Allrad

T-ROC R	ab 2018	A1	5/112	57,1	e13*2007/46*1845*..		
kein Sensor - indirektes RDKS							

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	39+40	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
		43	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
7 x 17	RC34	45	-	221	215/55		Orig.-Verschr.
	RC27	42	-	221	215/55, 225/50, 235/50		Orig.-Verschr., nur M+S
		35+45+ 47	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
	RC32	38+40+ 45+46+ 47	-	221	215/50, 215/55		Orig.-Verschr., Allrad, nur M+S
		40	-	221	215/50, 215/55		Orig.-Verschr., nur M+S
	B39	40	-	221	215/55, 225/50, 235/50		Orig.-Verschr., nur M+S
	CA 26	45	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
		42+47	ZP560D	221	215/55, 225/50		nur M+S
	RC24	42	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
	RC27	40+41	-	221	215/55, 225/50		Orig.-Verschr., nur M+S
7,5 x 17	RC34	41+46+ 47	-	221	215/50, 215/55		Orig.-Verschr., Allrad, nur M+S
	RC28	45	ZP560D	221	215/55		nur M+S
	B24	35+47	ZP560D	221	215/55		nur M+S
	CA 20	47	ZP560D	221	215/55		nur M+S
	RC27	45	-	221	215/50 , 225/45		Orig.-Verschr.
7 x 18	RC32	45	-	221	215/45, 215/50 , 225/45		Orig.-Verschr.
	RC34	45	-	221	215/50		Orig.-Verschr.
	RC27	43	-	221	215/50, 225/45		Orig.-Verschr.
	RC32	40	-	221	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC32	40	-	221	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	RC34	40+46	-	221	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	RC30	35+45	ZP560D	221	215/50, 225/45, 235/45		
	B32	48	-	221	215/50, 225/45, 235/45		Orig.-Verschr.
		35+45	ZP560D	221	215/50, 225/45, 235/45		
	AC-MB6	45	- +R	221	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	RC27	40	-	221	215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr.
		44	-	221	215/50, 225/45, 235/45		Orig.-Verschr.
	RC32	44+46	-	221	215/45, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr., Allrad
		40	-	221	215/45, 225/45, 235/45		Orig.-Verschr., Allrad
	RC34	44	-	221	215/45, 215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr., Allrad
		45	-	221	215/45, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr., Allrad
	RC34	40	ZP560D	221	215/45, 225/45, 235/45		Allrad
		43	ZP560D	221	215/45, 225/45, 235/45, 245/40, 245/45		Allrad
	R24	35	ZP560D	221	215/50, 225/45, 235/45		

8 x 18		48	ZP560D	221	225/45		
	B36	35+45	ZP560D	221	215/50, 225/45, 235/45		
	B42	45	ZP560D	221	215/50, 225/45, 235/45		
	B44	35+45	ZP560D	221	215/50, 225/45, 235/45		
	AC-M10	40	- +R	221	215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	221	215/50, 225/45, 235/45		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	221	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-522	35	- +R	221	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		40	- +R	221	215/50, 225/45, 235/45, 245/40, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	CA 17	45	ZP560D	221	215/50, 225/45, 235/45		
7,5 x 19	CA 20	45	ZP560D	221	215/50, 225/45, 235/45		
	RC34	45,5	ZP560D	221	225/40		
8 x 19	CA 26	40	ZP560D	221	225/40		
	RC27	44	-	221	235/40		Orig.-Verschr.
	RC32	44	-	221	235/40		Orig.-Verschr.
	RC34	44	-	221	235/40		Orig.-Verschr.
	RC32	40	-	221	225/40, 235/40		Orig.-Verschr.
		45	-	221	225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
	RC34	40	-	221	225/40, 235/40		Orig.-Verschr.
		45	-	221	225/40, 235/40, 245/35, 245/40		Orig.-Verschr.
	B43	40+45	-	221	225/40, 235/40		Orig.-Verschr.
		47	-	221	225/40		Orig.-Verschr.
	RC34	38	ZP560D	221	225/40, 235/40		Allrad
		43	ZP560D	221	225/40, 235/40, 245/35, 245/40		Allrad
	AC-521	45	-	221	225/40, 235/40		Orig.-Verschr.
	FMI07 Atena	39	- +R	221	225/40, 235/40		Orig.-Verschr.+Red.Ringe BA25
		47	- +R	221	225/40, 235/40, 245/35		Orig.-Verschr.+Red.Ringe BA25
	Oxigin 29	43	ZP560D	221	225/40, 235/40		
8,5 x 19	B32	42	-	221	225/40, 235/40		Orig.-Verschr.
	B32 / B36	45	ZP560D	221	225/40		
	B41	39	ZP560D	221	225/40		Allrad
	B42 / B44	42	ZP560D	221	225/40, 235/40		
	B43	38	ZP568F	221	225/40, 235/40		
	AC-M10	45	AV4+R	221	225/40		+ Red.Ringe BA25=66,6-57,1
	CA 20	45	ZP560D	221	225/40		
	CA 23	40	- +R	221	225/40, 235/40		Orig.-Verschr.+Red.Ringe BA25
		45	ZP560D	221	225/40		
	FMI07 Atena	45	- +R	221	225/40, 235/40, 245/35		Orig.-Verschr.+Red.Ringe BA25
	Oxigin 28	40	ZP560D	221	225/40, 235/40		
		45	ZP560D	221	225/40		
8 x 20	RC36	45	-	221	235/35		Orig.-Verschr.
	B43	41+45	-	221	235/35		Orig.-Verschr.
	FMI08 Thoe	45	F31+R	221	225/35, 235/35, 245/30		+ Red.Ringe BA25=66,6-57,1
8,5 x 20	B43	38+40	-	221	235/35		Orig.-Verschr.
	RC34	43	ZP560D	221	225/35, 235/30, 235/35		
	B42 / B43	40	ZP560D	221	235/35		
	B44	40	ZP560D	221	235/35		
	AC-M10	40	- +R	221	235/35		Orig.-Verschr.+Red.Ringe BA25
	FMI07 Atena	39	- +R	221	225/35		Orig.-Verschr.+Red.Ringe BA25
9 x 20	FMI11 Elatha	46	- +R	221	235/30		Orig.-Verschr.+Red.Ringe BA25

T-ROC Cabrio		ab Frühjahr 2020		A1	5/112	57,1	e13*2007/46*1845*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 16	RC27	43	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC30	43	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC34	43	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC27	48	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC30	48	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC34	48	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC30	43	ZP560D	85-110	205/60, 205/65, 215/60		nur M+S	
6,5 x 16	RC24	42+43	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr., nur M+S	
	RC27	42+46	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr., nur M+S	
	RC30	41+46	-	85-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr., nur M+S	
	RC32	41+43	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
	RC34	43+46+48	-	81-110	205/60, 205/65, 215/60		Orig.-Verschr., nur M+S	
7 x 16	Pro1	48	F31+R	81-110	205/60, 205/65, 215/60		+ Red.Ringe BA25=66,6-57,1, nur M+S	
	RC30	43	-	81-110	205/60, 205/65, 215/60, 225/55, 225/60		Orig.-Verschr., nur M+S	
	RC28	35	ZP560D	81-110	205/60, 205/65		nur M+S	
6,5 x 17	RC27	39+43+46+48,5	-	85-110	205/55, 205/60, 215/50, 215/55, 225/50		Orig.-Verschr., nur M+S	
	RC34	38	-	81-110	205/55M+S, 215/55, 225/50		Orig.-Verschr.	
	RC27	45	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55, 225/50		Orig.-Verschr.	

7 x 17	RC30	45	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55 , 225/50		Orig.-Verschr.
	RC34	45	-	81-110	215/55		Orig.-Verschr.
	CA 26	45	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55 , 225/50		Orig.-Verschr.
	B39	40	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		Orig.-Verschr.
	RC27	42+43+46	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55, 225/50		Orig.-Verschr.
		47	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55, 225/50		Orig.-Verschr.
	RC32	38	-	85-110	205/55, 215/55		Orig.-Verschr.
		40	-	81-110	215/55, 225/50		Orig.-Verschr.
		45	-	85-110	205/55, 215/55, 225/50, 235/50		Orig.-Verschr.
		47	-	81-110	205/55, 215/55, 225/50, 235/50		Orig.-Verschr.
	RC34	40	-	81-110	205/55M+S, 215/55, 225/50		Orig.-Verschr.
	CA 26	42+47	ZP560D	81-110	205/55M+S, 205/60M+S, 215/50, 215/55, 225/50		
7,5 x 17	RC24	42	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		Orig.-Verschr.
	RC27	41	-	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		Orig.-Verschr.
	RC32	43	-	81-110	205/55M+S, 215/55, 225/50, 245/45		Orig.-Verschr.
		46	-	81-110	215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC34	40+41	-	81-110	205/55M+S, 215/55		Orig.-Verschr.
		46+47	-	85-110	215/55, 225/50, 235/50, 245/45		Orig.-Verschr.
	RC28 / RC29	45	ZP560D	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		
7 x 18	B24	47	ZP560D	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		
	B36 / B37	45	ZP560D	81-110	205/55M+S, 205/60M+S, 215/50, 215/55		
	RC27	45	-	81-110	215/50		Orig.-Verschr.
	RC34	45	-	81-110	215/50		Orig.-Verschr.
7,5 x 18	RC32	40	-	85-110	205/50, 215/50, 225/45		Orig.-Verschr.
		45	-	85-110	205/50, 215/50, 225/45		Orig.-Verschr.
	RC32	40	-	81-110	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	40+46	-	81-110	215/50, 225/45, 235/45		Orig.-Verschr.
	RC30	45	ZP560D	81-110	215/45, 215/50, 225/45, 235/45		
8 x 18	B32	48	-	85-110	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	AC-MB6	45	- +R	81-110	215/45, 215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	RC27	44	-	81-110	215/50, 225/45, 235/45		Orig.-Verschr.
	RC29	44	-	85-110	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	40	-	85-110	225/45		Orig.-Verschr.
		44	-	81-110	215/50, 225/45, 235/45, 245/40		Orig.-Verschr.
		45	-	85-110	215/50, 225/45, 235/45, 245/40		Orig.-Verschr.
	B37	44	-	81-110	215/50, 225/45, 235/45		Orig.-Verschr.
	B24	48	ZP560D	81-110	225/45		
	B38	45	ZP560D	85-110	215/50, 225/45, 235/45		
	B42 / B44	45	ZP560D	81-110	215/50, 225/45, 235/45		
	AC-M10	40	- +R	81-110	225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		45	AV4+R	81-110	215/50, 225/45, 235/45		+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	81-110	215/50, 225/45, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AC-522	40	- +R	81-110	225/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	AF20	48	-	85-110	225/45		Orig.-Verschr.
	CA 17 / CA 20	45	ZP560D	81-110	215/50, 225/45, 235/45		
	FMI11 Elatha	45	F95	81-110	215/50, 225/45, 235/45, 245/40		
	FMI12 Kari	45	Kit 0353	81-110	215/50, 225/45, 235/45, 245/40		
7,5 x 19	RC34	48	-	81-110	225/40		Orig.-Verschr.
	B32	43	-	85-110	225/40		Orig.-Verschr.
	RC34	45,5	ZP560D	81-110	225/40		
	CA 26	40	ZP560D	81-110	225/40		
8 x 19	B43	47	-	81-110	225/40		Orig.-Verschr.
	RC32	40	-	81-110	225/40		Orig.-Verschr.
		45	-	81-110	225/40, 235/40, 245/35		Orig.-Verschr.
	RC34	40	-	81-110	225/40		Orig.-Verschr.
		45	-	81-110	225/40, 235/40, 245/35		Orig.-Verschr.
	B40	40	-	85-110	225/40		Orig.-Verschr.
		45	-	85-110	225/40, 235/40		Orig.-Verschr.
	B43	40	-	81-110	225/40		Orig.-Verschr.
		45	-	81-110	225/40, 235/40		Orig.-Verschr.
	RC29	45	ZP560D	85-110	225/40, 235/40		
	RC34	48	ZP560D	81-110	225/40, 235/40, 245/35		
	AC-521	45	-	81-110	225/40, 235/40		Orig.-Verschr.
	Oxigin 29	43	ZP560D	81-110	225/40, 235/40		
8,5 x 19	B32	45	ZP560D	85-110	225/40		
	B42 / B44	42	ZP560D	81-110	225/40		
	AC-M10	45	AV4+R	81-110	225/40		+Red.Ringe BA25=66,6-57,1
	CA 20 / CA 23	45	ZP560D	81-110	225/40		
	Oxigin 28	45	ZP560D	81-110	225/40		
8 x 20	RC36	45	-	81-110	235/35		Orig.-Verschr.
	B43	45	-	81-110	235/35		Orig.-Verschr.
	FMI08 Thoe	45	F31+R	81-110	225/35, 235/35, 245/30		+Red.Ringe BA25=66,6-57,1

Jetta (siehe Konfigurator)	ab 03.11	16/16H	5/112	57,1	e1*2007/46*0539*..., e1*2007/46*0584*...
-----------------------------------	-----------------	---------------	--------------	-------------	--

Passat	ab 11.2014 / Modell 2015	3C (B8/3G)	5/112	57,1	e1*2001/116*0307*37-...
---------------	---------------------------------	-------------------	--------------	-------------	-------------------------

Sensor - Brocksens 2						
Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC24	42	-	88-140	215/60, 225/55, 225/60	 Orig.-Verschr.
	RC27	42	-	88-140	215/60, 225/55, 225/60	 Orig.-Verschr.
	RC30	41	-	88-140	215/60	 Orig.-Verschr.
		41+42	-	88-140	215/60, 225/55, 225/60	 Orig.-Verschr.
	RC32	41	-	81-147	215/60, 225/55, 225/60, 235/55	 Orig.-Verschr.
	RC27	43	-	88-140	215/60, 225/55, 225/60	Orig.-Verschr.
	RC30	39	-	88-140	215/60, 225/55, 225/60	Orig.-Verschr., incl. Facelift 2019
	RC32	43	-	81-147	215/60, 225/55, 225/60, 235/55	Orig.-Verschr.
	RC34	43	-	81-147	215/60, 225/55, 225/60, 235/55	Orig.-Verschr.
7 x 16	CA 20	45	ZP560D	88-147	215/60, 225/55, 225/60	incl. Facelift 2019
	RC24	42	-	88-140	215/60, 225/55, 225/60	Orig.-Verschr.
		35	ZP560D	88-147	215/60	incl. Facelift 2019
6,5 x 17	RC28	45	ZP560D	88-140	215/60, 225/55, 225/60	
		41	-	81-206	215/55	 Orig.-Verschr.
7 x 17	RC27	39+43	-	88-206	215/50, 215/55, 225/50, 235/50	Orig.-Verschr., incl. Facelift 2019
	RC27	40	-	88-206	215/50, 215/55, 225/50	 Orig.-Verschr., incl. Facelift 2019
	RC30	40	-	88-176	215/55	 Orig.-Verschr.
			88-206	215/50, 215/55, 225/50	 Orig.-Verschr., incl. Facelift 2019	
	RC32	40	-	81-206	215/55	 Orig.-Verschr.
			81-206	215/50, 215/55, 225/50	 Orig.-Verschr.	
	RC34	40	-	81-206	215/50, 215/55, 225/50	 Orig.-Verschr.
	B39	40	-	88-206	215/50, 215/55, 225/50	 Orig.-Verschr.
	RC27	42	-	88-206	215/50, 215/55, 225/50, 235/50	Orig.-Verschr., incl. Facelift 2019
	RC32	38+39	-	81-206	215/50, 215/55, 225/50	Orig.-Verschr.
		45	-	81-206	215/50, 215/55, 225/50, 235/50	Orig.-Verschr.
	CA 26	42	ZP560D	88-206	215/50, 215/55, 225/50, 235/50	incl. Facelift 2019
7,5 x 17	RC24	35	-	88-206	215/50, 215/55	Orig.-Verschr.
		42	-	88-176	215/50, 215/55, 225/50, 235/50, 245/45	Orig.-Verschr.
	RC27	40	-	88-206	215/50, 215/55, 225/50, 225/55, 245/45	Orig.-Verschr.
		41	-	88-206	215/50, 215/55, 225/50, 245/45	Orig.-Verschr.
	RC32	43	-	81-206	215/50, 215/55, 225/50, 235/45, 245/45	Orig.-Verschr.
	RC34	41	-	81-206	215/50, 215/55, 225/50, 235/45, 245/45	Orig.-Verschr.
	Oxigin 19	45	ZP560D	88-206	215/50, 215/55, 225/50, 225/55	
	RC28	45	ZP560D	88-140	235/50 HA	
88-206				215/50, 215/55, 225/50, 245/45		
AC-518	42	AV4+R	88-206	215/50, 215/55, 225/50, 245/45	+ Red.Ringe BA25=66,6-57,1	
7 x 18	RC32	35+40+ 43+45	-	81-206	215/45, 215/50, 225/45	Orig.-Verschr.
7,5 x 18	RC32	45	-	81-206	215/45, 215/50, 225/45, 235/45, 245/45	Orig.-Verschr.
	RC34	40	-	81-206	215/45, 215/50, 225/45, 235/45	Orig.-Verschr.
	RC30	35+45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45	
	B32	35+45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45	incl. Facelift 2019
	B39	35+45	ZP560D	88-206	215/45, 215/50, 225/45, 235/45	
8 x 18	RC27	44	-	88-206	225/45, 235/45	 Orig.-Verschr.
	RC29	44	-	88-206	215/45, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr., incl. Facelift 2019
	RC32	44	-	81-206	215/45, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr.
	RC34	44	-	81-206	215/45, 215/50, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr.
	B37	44	-	88-206	215/45, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr.
	B38	44	-	88-206	215/45, 225/45, 235/40, 235/45, 245/40	 Orig.-Verschr.
	B36	45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40	
	B37 / B38	45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40	
	B42	35	ZP560D	88-206	215/45, 225/45	incl. Facelift 2019
		45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40	incl. Facelift 2019
	B44	35	ZP560D	88-206	215/45, 225/45	incl. Facelift 2019
		45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40	incl. Facelift 2019
	AC-M10	40	- +R	88-206	215/45, 225/45, 235/40, 235/45	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
		45	AV4+R	88-206	215/45, 225/45, 235/40, 235/45, 245/40	+ Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
	AC-518	40	AV4+R	88-206	215/45, 225/45, 235/40, 235/45	+ Red.Ringe BA25=66,6-57,1
	AC-521	45	- +R	88-206	215/45, 225/45, 235/40, 235/45, 245/40	Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
	AF18	40	AV1	88-206	215/45, 225/45, 235/40, 235/45	
	AF20	35	AV1	88-206	215/45, 225/45	incl. Facelift 2019
CA 20	45	ZP560D	88-206	215/45, 225/45, 235/40, 235/45, 245/40	incl. Facelift 2019	
7,5 x 19	RC34	40	-	81-206	225/40	Orig.-Verschr.
	B39	33+43	ZP560D	88-206	225/40	
	Oxigin 18	37	-	88-206	225/40	Orig.-Verschr.
	RC27	44	-	81-206	225/40, 235/40	 Orig.-Verschr.
			220	235/35		

8 x 19	RC32	44	-	81-206	235/40		Orig.-Verschr.
	RC34	44	-	220	235/35		Orig.-Verschr.
				81-206	235/40		
				220	235/35		
				81-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr.
	B38	44	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019
	RC29	40	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019, bei 245/35 ✖
	RC32	40+45	-	81-206	225/40, 235/35		Orig.-Verschr.
	RC34	40+45	-	81-206	225/40, 235/35		Orig.-Verschr.
	B40 / B43	40	-	88-206	225/40, 235/35, 235/40		Orig.-Verschr., incl. Facelift 2019
		45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019
	RC34	38	ZP560D	81-206	225/40		
		43	ZP560D	81-206	225/40, 235/35, 235/40		
	B40	38	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019
		43	ZP560D	88-206	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019
	CA 17	37	ZP560D	81-206	225/40		
		45	ZP560D	81-206	225/40, 235/40		
AC-521	35	- +R	88-206	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2019	
	45	-	88-206	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019	
FMI07 Atena	39	- +R	81-206	225/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
Oxigin 29	39	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019	
	43	ZP560D	88-206	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019	
8,5 x 19	B32	42	-	88-140	255/35		Orig.-Verschr.
				88-206	225/40, 235/35, 235/40, 245/35		
	B42	42	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019
	B43	38	ZP568F	88-206	225/40		incl. Facelift 2019
	B44	42	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019
	AC-M10	40	- +R	88-206	225/40, 235/35, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
	AF18	40	AV1	88-206	225/40, 235/35, 235/40		
	AF20	40	- +R	88-206	225/40, 235/35, 235/40		Orig.-Verschr. + Ringe BA25=66,6-57,1 - incl. Facelift 2019
	CA 23	40	- +R	88-206	225/40, 235/35, 235/40		Orig.-Verschr. + Ringe BA25=66,6-57,1
		45	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019
Oxigin 25	45	ZP560D	81-206	225/40, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1	
Oxigin 28	40+45	ZP560D	88-206	225/40, 235/35, 235/40		incl. Facelift 2019	
9 x 19	CA 19	43	ZP560D	81-206	225/40		
8 x 20	RC36	41	-	88-140	225/35, 245/30		Orig.-Verschr., incl. Facelift 2019
				88-206	225/35, 235/35, 245/30		
	B38	40+41	-	88-140	225/35, 245/30		Orig.-Verschr., incl. Facelift 2019, ET40 bei 245/30 ✖
				88-206	225/35, 235/35, 245/30		
	B40	40+41	-	88-140	225/35, 245/30		Orig.-Verschr., incl. Facelift 2019, ET40 bei 245/30 ✖
				88-206	225/35, 235/35, 245/30		
	B43	41+45	-	88-140	225/35, 245/30		Orig.-Verschr., incl. Facelift 2019
				88-206	225/35, 235/35, 245/30		
	B43	40	-	88-110	235/30		Orig.-Verschr., incl. Facelift 2019
				88-140	225/35, 235/30		
				88-206	225/35, 235/35		
RC29	45	ZP560D	88-110	235/30		incl. Facelift 2019, bei 255/30 ✖	
			88-140	225/35, 235/30, 255/30			
			88-206	225/35, 235/35			
B32	45	ZP560D	88-206	235/30, 235/35, 255/30		ab 141 KW nur 235/35	
8,5 x 20	B42	40+45	ZP560D	88-110	235/30		incl. Facelift 2019
				88-140	225/35, 235/30		
	88-206	225/35, 235/35					
	B43	43	ZP560D	88-110	235/30		incl. Facelift 2019
				88-140	225/35, 235/30		
				88-206	225/35, 235/35		
	B44	40	ZP560D	88-110	235/30		incl. Facelift 2019
				88-140	225/35, 235/30		
	88-206	225/35, 235/35					
	AC-518	45	- +R	88-140	225/35, 235/30		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
				88-206	225/35, 235/35		
	AC-521	45	-	88-140	225/35, 235/30		Orig.-Verschr., incl. Facelift 2019
				88-206	225/35, 235/35		
	AC-M10	40	- +R	88-140	225/35, 235/30		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
				88-206	225/35, 235/35		
	AF18	45	- +R	88-206	225/35, 235/30		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, incl. Facelift 2019

Passat Alltrack		ab 2014		3C (B8)	5/112	57,1	e1*2001/116*0307*...
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension		Info

6,5 x 17	RC27	39	-	103-155	205/50, 205/55, 215/50, 225/50		Orig.-Verschr., nur M+S
	RC32	38	-	110-176	215/50, 215/55 , 225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
7 x 17	RC27	42	-	103-155	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
	RC32	38+39	-	110-200	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
		40	-	110-200	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
	RC34	40	-	110-206	215/50, 215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr.
	B39	40	-	110-206	215/55, 225/50, 225/55, 235/50, 245/50		Orig.-Verschr., nur M+S, incl. Facelift 2019
	CA 26	42	ZP560D	110-206	215/55, 225/50, 225/55, 235/50		nur M+S, incl. Facelift 2019
7,5 x 17	RC27	40	-	110-176	215/55, 225/50, 225/55, 245/45		Orig.-Verschr.
		41	-	110-206	215/55, 225/50, 225/55, 235/50		Orig.-Verschr., nur M+S, incl. Facelift 2019
	RC34	41	-	110-206	215/50, 215/55, 225/50, 225/55, 235/50, 245/45, 245/50		Orig.-Verschr.
	RC29	35	ZP560D	110-206	215/55, 225/50, 225/55		nur M+S, incl. Facelift 2019
	B24	35	ZP560D	110-206	215/55, 225/50, 225/55		nur M+S, incl. Facelift 2019
	Oxigin 14	35	ZP560	110-176	225/50, 245/45		
7 x 18	RC32	35	-	110-206	215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
		40	-	110-200	215/45, 215/50, 225/45, 225/50		Orig.-Verschr.
7,5 x 18	RC32	40	-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
		35	-	110-206	215/45, 215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	RC34	40	-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
		40	-	110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/45		Orig.-Verschr.
8 x 18	RC27	40	-	103-155	225/45		
				110-206	225/45, 225/50, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2019
	RC32	40	-	103-155	225/45		
				140-200	245/45		
				110-206	215/45, 215/50, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC34	40	-	140-200	215/45, 225/45, 225/50, 235/45, 245/40, 245/45		Orig.-Verschr.
	RC27	44	-	110-176	225/45, 235/45		Orig.-Verschr.
	RC34	30	ZP560D	110-200	215/45, 225/45		
		34	ZP568F	110-200	215/45, 225/45, 235/45, 245/40		
		40	ZP560D	110-200	215/45, 225/45, 225/50, 235/45, 245/40, 245/45		
	B24 / B42	35	ZP560D	110-206	225/45, 235/45		incl. Facelift 2019
	B44	35	ZP560D	110-206	225/45, 235/45		incl. Facelift 2019
	CA 17	45	ZP560D	110-176	225/45		
				110-200	235/45		
	AC-M10	40	- +R	110-206	225/45, 225/50, 235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
	FMI08 Thoe	34	F31+R	110-206	215/45, 215/50, 225/45, 235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
	FMI11 Elatha	26	- +R	110-206	215/45		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
7,5 x 19	RC34	40	-	110-206	225/40, 225/45		Orig.-Verschr.
	Oxigin 18	37	-	110-176	225/40		Orig.-Verschr.
8 x 19	RC32	40	-	110-206	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	RC34	40	-	110-206	225/40, 225/45, 235/40, 245/35, 245/40		Orig.-Verschr.
	B43	40	-	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr., incl. Facelift 2019
	CA 17	37	ZP560D	110-200	225/40		
		45	ZP560D	110-200	225/40, 235/40		
	AC-521	35	- +R	110-206	225/40, 225/45, 235/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
	FMI07 Atena	39	- +R	110-200	225/40, 225/45, 235/40, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	32	ZP560D	110-206	225/40, 225/45		incl. Facelift 2019
		39	ZP560D	110-206	225/40, 225/45, 235/40, 245/35		incl. Facelift 2019
8,5 x 19	RC27	44	-	110-176	225/40, 235/40		Orig.-Verschr.
	RC32	38	-	110-206	225/40, 235/40, 245/35		Orig.-Verschr.
	B41	36	ZP560D	110-206	225/40		
		39	ZP560D	110-206	225/40, 235/40, 245/35		
	B43	38	ZP568F	110-206	225/40, 225/45, 235/40		incl. Facelift 2019
	B44	35	ZP560D	110-206	225/40, 225/45		incl. Facelift 2019
	AC-M10	40	- +R	110-206	225/40, 225/45, 235/40, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2019
	CA 23	40	- +R	110-206	225/40, 225/45, 235/40, 245/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
		40	ZP560D	110-176	225/40		
	Oxigin 20	45	ZP560D	110-200	225/40		
		45	ZP560D	110-200	225/40		
	Oxigin 25	45	ZP560D	110-200	225/40		
	Oxigin 28	45	ZP560D	110-206	225/40, 225/45, 235/40, 245/40		incl. Facelift 2019
9 x 19	CA 19	43	ZP560D	110-206	225/40		
8 x 20	RC36	38+41	-	110-206	245/35		Orig.-Verschr., incl. Facelift 2019
	B38	41	-	110-206	245/35		Orig.-Verschr., incl. Facelift 2019
	B43	41	-	110-206	245/35		Orig.-Verschr., incl. Facelift 2019
	B43	39	ZP560D	110-206	245/35		incl. Facelift 2019
8,5 x 20	B43	40	-	110-206	245/35		Orig.-Verschr., incl. Facelift 2019
	B44	40	ZP560D	110-206	245/35		incl. Facelift 2019
	AC-M10	40	- +R	110-206	245/35		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1, incl. Facelift 2019

	FMI07 Atena	39	- +R	110-200	235/35		Orig.-Verschr. +Red.Ringe BA25=66,6-57,1
--	-------------	----	------	---------	--------	--	---

Passat GTE Hybrid (VIII)							
ab MJ2015				3C (B8)	5/112	57,1	e1*2001/116*0307*41-..
Sensor - Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	39+43	-	115	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., incl. Facelift 2019
7 x 17	RC27	40	-	115	215/50, 215/55 , 225/50		Orig.-Verschr., incl. Facelift 2019
	RC30	40	-	115	215/50, 215/55 , 225/50		Orig.-Verschr., incl. Facelift 2019
	RC34	40	-	81-206	215/55		Orig.-Verschr.
	RC30	38	-	115	215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
		45	-	115	215/50, 215/55, 225/50, 235/50		Orig.-Verschr., incl. Facelift 2019
	B39	40	-	115	215/50, 215/55, 225/50		Orig.-Verschr., incl. Facelift 2019
	RC27	45	ZP568F (V10)	115	215/50, 215/55, 225/50, 225/55		incl. Facelift 2019, Ausführung "V10"
7,5 x 17	CA 26	42	ZP560D	115	215/50, 215/55, 225/50, 245/45		incl. Facelift 2019
	RC24	42	-	115	215/50, 215/55, 225/50, 245/45		Orig.-Verschr., incl. Facelift 2019
	RC27	40	-	115	215/50, 215/55, 225/50, 245/45		Orig.-Verschr., incl. Facelift 2019
		41	-	115	215/50, 215/55, 225/50, 245/45		Orig.-Verschr., incl. Facelift 2019
	RC28	45	ZP560D	115	215/50, 215/55, 225/50, 235/50HA, 245/45		incl. Facelift 2019
7,5 x 18	RC29	35	ZP560D	115	215/50, 215/55		incl. Facelift 2019
	B32	35+45	ZP560D	115	215/45, 215/50, 225/45, 235/45		incl. Facelift 2019
8 x 18	B38	44	-	115	235/45		Orig.-Verschr., incl. Facelift 2019
	RC29	40	-	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2019
		44	-	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2019
	B42	45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		incl. Facelift 2019
	B44	35	ZP560D	115	215/45, 225/45		incl. Facelift 2019
		45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		incl. Facelift 2019
	AC-M10	40	- +R	115	215/45, 225/45, 235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
		45	AV4+R	115	215/45, 225/45, 235/40, 235/45, 245/40		+ Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
	AC-521	45	- +R	115	215/45, 225/45, 235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
	AF20	35	AV1	115	215/45, 225/45		incl. Facelift 2019
	CA 20	45	ZP560D	115	215/45, 225/45, 235/40, 235/45, 245/40		incl. Facelift 2019
	7,5 x 19	B32	43	-	115	225/40	Orig.-Verschr., incl. Facelift 2019
		RC29	40	-	115	225/40, 235/35, 235/40	Orig.-Verschr., incl. Facelift 2019
8 x 19	B40 / B43	40	-	115	225/40, 235/35, 235/40		Orig.-Verschr., incl. Facelift 2019
		45	-	115	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019
	B24	45	ZP560D	115	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019
	AC-521	35	- +R	115	225/40		Orig.-Verschr. + Ringe BA25=66,6-57,1 , incl. Facelift 2019
		45	-	115	225/40, 235/35, 235/40, 245/35		Orig.-Verschr., incl. Facelift 2019
	Oxigin 29	39	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
		43	ZP560D	115	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019
	B32	45	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
8,5 x 19	B37	43	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
		45	ZP560D	115	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019
	B42	42	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
	B43	38	ZP568F	115	225/40		incl. Facelift 2019
	B44	42	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
	AC-M10	40	- +R	115	225/40, 235/35, 235/40		Orig.-Verschr. + Ringe BA25=66,6-57,1 - incl. Facelift 2019
		45	AV4+R	115	225/40, 235/35, 235/40, 245/35		+ Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019
	AF20	40	- +R	115	225/40, 235/35, 235/40		Orig.-Verschr. + Ringe BA25=66,6-57,1 - incl. Facelift 2019
	CA 23	40	- +R	115	225/40, 235/35, 235/40		Orig.-Verschr. + Ringe BA25=66,6-57,1 - incl. Facelift 2019
		45	ZP560D	115	225/40, 235/35, 235/40, 245/35		incl. Facelift 2019
	Oxigin 28	40	ZP560D	115	225/40, 235/35, 235/40		incl. Facelift 2019
		45	ZP560D	115	225/40, 235/35, 235/40, 245/35HA		incl. Facelift 2019
8 x 20	RC36	41	-	115	225/35, 235/35, 245/30		Orig.-Verschr., incl. Facelift 2019
	B38	41	-	115	225/35, 235/35, 245/30		Orig.-Verschr., incl. Facelift 2019
	B40	40+41	-	115	225/35, 235/35, 245/30		Orig.-Verschr., incl. FL2019, ET40 bei 245/30 ✖
	B43	41+45	-	115	225/35, 235/35, 245/30		Orig.-Verschr., incl. Facelift 2019
8,5 x 20	B43	40	-	115	225/35, 235/35		Orig.-Verschr., incl. Facelift 2019
	RC29	45	ZP560D	115	225/35, 235/35		incl. Facelift 2019
	B24	42	ZP560D	115	225/35, 235/35		incl. Facelift 2019
	B42	40+45	ZP560D	115	225/35, 235/35		incl. Facelift 2019
	B43	43	ZP560D	115	225/35, 235/35		incl. Facelift 2019
	B44	40	ZP560D	115	225/35, 235/35		incl. Facelift 2019
	AC-518	45	- +R	115	225/35, 235/35		Orig.-Verschr. + Red.Ringe BA25 , incl. FL2019
	AC-521	45	-	115	225/35, 235/35		Orig.-Verschr., incl. Facelift 2019
	AC-M10	40	- +R	115	225/35, 235/35		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2019

Passat (IX) NEU		ab 2024		CJ / B9	5/112	57,1	e13*2018/858*00366*..
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
7 x 16	RC30	43	-	90, 110	215/60, 225/55		Orig.-Verschr., nur Bremse 306mm
		35	-	90, 110	215/55		Orig.-Verschr., nur Bremse 306mm
7 x 17	RC27	40+42+45	-	90, 110	215/55, 225/50, 235/50		Orig.-Verschr., nur Bremse 306mm
		38+40	-	90-142	215/55, 225/50		Orig.-Verschr.
	RC32	45	-	90-142	215/55, 225/50, 235/50		Orig.-Verschr.
		40	-	110	215/55, 225/50		Orig.-Verschr.
	RC27	35	ZP560D	90, 110	215/55		nur Bremse 306mm
	CA 26	45	-	90, 110	215/55, 225/50, 235/50		Orig.-Verschr.
42		ZP560D	90, 110	215/55, 225/50, 235/50			
7,5 x 17	RC27	41	-	90-195	215/55, 225/50, 245/45		Orig.-Verschr.
	RC34	41	-	90-195	215/55, 225/50, 245/45		Orig.-Verschr.
	RC27	40	-	90-195	215/55, 225/50, 245/45		Orig.-Verschr.
	RC34	40	-	90-195	215/55, 225/50, 245/45		Orig.-Verschr.
	CA 20	45	- +R	90-195	215/55, 225/50, 235/50, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
	7 x 18	RC27	43	-	90, 110	215/50, 225/45	
35			-	90-142	225/45		Orig.-Verschr.
RC32		40	-	90-142	215/50, 225/45		Orig.-Verschr.
		35	-	90-142	225/45		Orig.-Verschr.
RC34		43	-	90-142	215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC32	40+45	-	90-195	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	35	-	110	225/45		Orig.-Verschr.
		40	-	90-195	215/50, 225/45, 235/45		Orig.-Verschr.
		46	-	90-195	215/50, 225/45, 235/45, 245/45		Orig.-Verschr.
	B32 / B39	45	ZP560D	90-195	215/50, 225/45, 235/45		
	AC-MB6	45	- +R	90-195	215/50, 225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
8 x 18	AC-M10	45	- +R	90-195	215/50, 225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
	RC27	44	-	90-195	225/45, 235/45 , 245/40		Orig.-Verschr., nur Bremse 306mm
	RC32	44	-	90-195	215/50, 225/45, 235/45 , 245/40		Orig.-Verschr.
	RC34	44	-	90-195	215/50, 225/45, 235/45 , 245/40		Orig.-Verschr.
	RC27	40	-	90-195	225/45, 235/45		Orig.-Verschr., nur Bremse 306mm
	RC32	40	-	90-195	215/50, 225/45, 235/45		Orig.-Verschr.
		40	-	90-195	215/50, 225/45, 235/45		Orig.-Verschr.
	RC34	45	-	90-195	215/50, 225/45, 235/45, 245/40		Orig.-Verschr.
		B44	35	ZP560D	90-195	225/45	
	45		ZP560D	90-195	225/45, 235/45, 245/40		nur Bremse 306mm
	AC-MB6	39	- +R	90-195	225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
		45	ZP560D	90-195	225/45, 235/45, 245/40		
7,5 x 19	CA 20	45	ZP560D	90-195	225/45, 235/45, 245/40		
	RC34	40	-	90-195	215/40, 225/40		Orig.-Verschr.
8 x 19	CA 26	40	ZP560D	90-195	225/40		
	RC27	44	-	90-195	235/40		Orig.-Verschr.
		RC32	44	-	90-195	235/40	
	90-195				215/40, 225/40, 235/40, 245/35		Orig.-Verschr.
	RC34	44	-	90-195	235/40		Orig.-Verschr.
				90-195	215/40, 225/40, 235/40, 245/35		Orig.-Verschr.
				40	-	110	215/40, 225/40
	45	-	110	215/40, 225/40, 235/40, 245/35		Orig.-Verschr.	
B43	45	-	90-195	225/40, 235/40, 245/35		Orig.-Verschr.	
8,5 x 19	RC34	43	ZP560D	90-195	215/40, 225/40		
	RC32	38	-	90-195	215/40		Orig.-Verschr.
	RC34	38	-	90-195	215/40		Orig.-Verschr.
		40	- +R	90-195	225/40, 235/40		Orig.-Verschr. +Ringe BA25=66,6-57,1
	CA 20	45	ZP560D	90-195	225/40, 235/40, 245/35HA		
8 x 20	RC36	41+45	-	90-195	225/35, 235/35, 245/30		Orig.-Verschr.
	B43	41+45	-	90-195	225/35, 235/35, 245/30		Orig.-Verschr.
		39	ZP560D	90-195	225/35, 235/35		
9 x 20	CA 23	45	ZP560D	90-195	225/35, 235/35		

Passat (IX) PHEV NEU ab 2024 CJ / B9 5/112 57,1 e13*2018/858*00366*..							
Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7,5 x 17	RC27	41	-	110, 130	215/55		Orig.-Verschr.
7,5 x 18	B32 / B39	45	ZP560D	110, 130	215/50, 225/45, 235/45		
	AC-MB6	45	- +R	110, 130	215/50, 225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
	AC-M10	45	- +R	110, 130	215/50, 225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
8 x 18	AC-MB6	39	- +R	110, 130	225/45, 235/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
		45	ZP560D	110, 130	225/45, 235/45, 245/40		
7,5 x 19	CA 26	40	ZP560D	110, 130	225/40		
8 x 19	RC27	44	-	110, 130	235/40		Orig.-Verschr.

8 x 20	B43	45	-	110, 130	225/40, 235/40, 245/35		Orig.-Verschr.
	RC36	41	-	110, 130	235/35		Orig.-Verschr.
	B43	41+45	-	110, 130	235/35		Orig.-Verschr.
		39	ZP560D	110, 130	235/35		

Polo VI		ab 10.2017		AW	5/100	57,1	e1*2007/46*1783*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
5 x 14	RC30	38	-	48-70	185/70, 185/75, 195/70		Orig.-Verschr.	
		35	-	48-70	185/70, 185/75, 195/70		Orig.-Verschr.	
5,5 x 15	RC19	40	-	48-110	185/65, 195/60, 195/65, 205/55, 205/60		Orig.-Verschr.	
6 x 15	RC24	38	-	48-85	185/65, 195/60, 195/65		Orig.-Verschr.	
	RC27	38	-	48-110	185/65, 195/60, 195/65		Orig.-Verschr.	
	RC30	38	-	48-110	185/65, 195/60, 195/65		Orig.-Verschr.	
6 x 16	RC27	45	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC30	45	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC34	45	-	48-110	185/55, 185/60, 195/55, 205/50		Orig.-Verschr.	
	RC27	35	-	48-110	185/55, 185/60		Orig.-Verschr.	
		38	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.	
	RC30	38	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.	
	RC34	35	-	48-110	185/55, 185/60		Orig.-Verschr.	
		40	-	48-110	185/55, 185/60, 195/55		Orig.-Verschr.	
6,5 x 16	RC27	47	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC30	47	-	48-110	185/55, 185/60, 195/55, 205/50, 205/55		Orig.-Verschr.	
	RC32	47	-	48-85	195/55		Orig.-Verschr.	
	RC34	47	-	48-110	185/55, 185/60, 195/55, 205/50		Orig.-Verschr.	
	RC27	40	-	48-110	185/55, 185/60		Orig.-Verschr.	
		38	-	48-110	185/55, 185/60		Orig.-Verschr.	
	RC32	40	-	48-110	185/55, 185/60		Orig.-Verschr.	
		47	-	48-110	185/55, 185/60, 195/55, 205/50		Orig.-Verschr.	
	RC34	40	-	48-110	185/55, 185/60		Orig.-Verschr.	
7 x 16	CA 20	38	ZP516	48-110	185/55, 185/60			
	RC30	46	-	48-85	195/55		Orig.-Verschr.	
6,5 x 17	RC27	39+40	-	48-110	185/50, 205/45		Orig.-Verschr.	
	RC34	39	-	48-110	185/45, 185/50, 195/45, 205/45		Orig.-Verschr.	
7 x 17	RC27	51	-	48-110	205/45, 215/45		Orig.-Verschr.	
	RC30	51	-	48-85	215/45		Orig.-Verschr.	
				48-110	205/45, 215/45			
	RC32	51	-	48-85	185/45, 195/45, 195/50, 205/45, 215/40, 215/45, 225/45		Orig.-Verschr.	
	RC34	51	-	48-110	215/45		Orig.-Verschr.	
	CA 26	51	-	48-110	205/45, 215/45		Orig.-Verschr.	
	RC30	46	-	48-110	205/45, 215/45		Orig.-Verschr.	
7,5 x 17	B39	46	-	48-85	205/45, 215/45		Orig.-Verschr.	
	RC27	46	-	48-147	195/45, 205/45		Orig.-Verschr.	
		51	-	48-85	195/45, 205/45, 215/40		Orig.-Verschr.	
	RC32	46	-	48-110	195/45, 205/45		Orig.-Verschr.	
	RC34	51	-	48-110	195/45, 205/45, 215/40, 215/45		Orig.-Verschr.	
	Oxigin 25	51	ZP516	48-152	195/45, 205/45, 215/40, 215/45		nicht Bremse 312mm	
7 x 18	RC32	47+51	-	48-110	205/40, 215/35, 215/40		Orig.-Verschr.	
7,5 x 18	RC32	46	-	48-110	205/35, 205/40		Orig.-Verschr.	
		51	-	48-110	205/35, 205/40, 215/35, 215/40		Orig.-Verschr.	

Polo GTI (VI)		ab 2021		AW	5/100	57,1	e1*2007/46*1783*..	
kein Sensor - indirektes RDKS								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6 x 16	RC27	45	-	147, 152	185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	RC30	45	-	147, 152	185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	RC34	45	-	147-152	185/55, 185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	RC27	38	-	147	185/60			Orig.-Verschr., nur M+S
	RC30	38	-	147	185/60			Orig.-Verschr., nur M+S
	RC34	35	-	147-152	185/55, 185/60			Orig.-Verschr., nur M+S
		40	-	147-152	185/55, 185/60, 195/55			Orig.-Verschr., nur M+S
6,5 x 16	RC27	40	-	147	185/60			Orig.-Verschr., nur M+S
		47	-	147	185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	RC30	38	-	147	185/60			Orig.-Verschr., nur M+S
	RC32	40	-	147	185/55, 185/60			Orig.-Verschr., nur M+S
		47	-	147-152	185/55, 185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	RC34	40	-	147-152	185/55, 185/60			Orig.-Verschr., nur M+S
		47	-	147-152	185/55, 185/60, 195/55, 205/50, 205/55			Orig.-Verschr., nur M+S
	CA 20	38	ZP516	147, 152	185/60			nur M+S
	7 x 16	RC30	46	-	147	195/55		
6,5 x 17	RC27	39+40	-	147	185/50, 205/45			Orig.-Verschr., nur M+S
	RC34	39	-	147-152	185/50, 195/45, 205/45			Orig.-Verschr., nur M+S

7 x 17	RC30	46	-	147	205/45, 215/45		Orig.-Verschr., nur M+S
	RC27 / RC30	43	ZP516	147	205/45		nur M+S
	CA 26	51	-	147, 152	205/45, 215/45		Orig.-Verschr., nur M+S
		46	ZP516	147, 152	205/45, 215/45		nur M+S
7,5 x 17	RC27	51	-	147, 152	205/45 M+S, 215/45		Orig.-Verschr.
	RC32	51	-	147-152	195/45M+S, 205/45M+S, 215/45		Orig.-Verschr.
	RC34	51	-	147-152	195/45M+S, 205/45M+S, 215/45		Orig.-Verschr.
	RC27	46	-	147	195/45, 205/45		Orig.-Verschr.
	RC32	46	-	147-152	195/45, 205/45		Orig.-Verschr., nur M+S
	Oxigin 25	51	ZP516	147-152	195/45, 205/45, 215/40, 215/45		nicht Bremse 312mm
7 x 18	RC27	47	-	147	215/35, 215/40		Orig.-Verschr.
7,5 x 18	RC32	51	-	147	215/40		Orig.-Verschr.
	RC34	51	-	147-152	215/40		Orig.-Verschr.
	RC32	46	-	147	215/35, 215/40		Orig.-Verschr.

Sharan	(siehe Konfigurator)	ab 07.10	7N	5/112	57,1	e1*2007/46*0401*..., e1*2007/46*0434*...
--------	----------------------	----------	----	-------	------	--

Tayron	NEU	2024	R4	5/112	57,1	e1*2018/858*00403*..
--------	-----	------	----	-------	------	----------------------

Sensor - HUF RDE254 - Artikelnummer silber - 102320 / schwarz - 102321							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC34	38	-	110-150	215/65 , 225/60, 225/65, 235/60		Orig.-Verschr., nur M+S, ohne R-Line Paket
				110-195	215/65 , 225/60, 235/60		Orig.-Verschr., nur M+S, mit R-Line Paket
7 x 17	RC32	40	-	110-150	215/65 , 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., ohne R-Line Paket
				110-195	215/65 , 225/60, 235/60, 245/55		Orig.-Verschr., nur M+S, mit R-Line Paket
	RC34	40	-		215/65		Orig.-Verschr., TÜV i.V.
7,5 x 17	RC34	40	-	110-150	215/65, 225/60, 225/65, 235/60, 245/60		Orig.-Verschr., ohne R-Line Paket
				110-195	215/65, 225/60, 235/60		Orig.-Verschr., nur M+S, mit R-Line Paket
7 x 18	RC32	35	-	110-150	215/60, 225/55, 225/60, 235/55		Orig.-Verschr., ohne R-Line Paket
				110-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S, mit R-Line Paket
				110-150	215/60, 225/55, 225/60, 235/55, 245/50, 245/55		Orig.-Verschr., ohne R-Line Paket
		40	-	110-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., nur M+S, mit R-Line Paket
				110-150	215/60, 225/55, 225/60, 235/55 , 245/50, 245/55		Orig.-Verschr., ohne R-Line Paket
7,5 x 18	RC32	40	-	110-195	215/55, 215/60, 225/55, 235/50, 235/55 , 245/50		Orig.-Verschr., nur M+S, mit R-Line Paket
				110-150	215/60, 225/55, 225/60, 235/50, 235/55 , 245/50		Orig.-Verschr., ohne R-Line Paket
	RC34	40	-	110-195	215/60, 225/55, 225/60, 235/55 , 245/50, 245/55		Orig.-Verschr., ohne R-Line Paket
				110-195	215/55, 215/60, 225/55, 235/50, 235/55 , 245/50		Orig.-Verschr., nur M+S, mit R-Line Paket
8 x 19	RC34	40	-	110-150	215/50, 225/50, 235/50, 245/45, 255/45		Orig.-Verschr., ohne R-Line Paket
				110-195	215/50, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr., nur M+S, mit R-Line Paket
8,5 x 19	RC34	38	-	110-150	255/45		Orig.-Verschr., R-Line Paket
8,5 x 21	B41	40	-	110-150	245/35		Orig.-Verschr., ohne R-Line Paket

T-Cross	ab 2019	C1	5/100	57,1	e13*2007/46*1985*..
---------	---------	----	-------	------	---------------------

kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 16	RC27	35	-	70-110	195/60 , 195/65, 205/55, 205/60 , 215/55, 215/60		Orig.-Verschr., 195er Reifen M+S
	RC30	35	-	70-110	195/60 , 195/65, 205/55, 205/60 , 215/55, 215/60		Orig.-Verschr., 195er Reifen M+S
	RC34	35	-	70-110	195/60 , 195/65, 205/55, 205/60 , 215/55, 215/60, 225/50, 225/55		Orig.-Verschr.
	RC27	38	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60		Orig.-Verschr., 195er Reifen M+S
	RC30	38	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60		Orig.-Verschr., 195er Reifen M+S
	RC34	40	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., 195er Reifen M+S
6,5 x 16	RC30	38	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., 195er Reifen M+S
	RC32	40	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., 195er Reifen M+S
	RC34	40	-	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 215/60, 225/50, 225/55		Orig.-Verschr., 195er Reifen M+S
	CA 20	38	ZP516	70-110	195/60, 195/65, 205/55, 205/60, 215/55, 225/50, 225/55		195er Reifen M+S
6,5 x 17	RC27	39	-	70-110	195/55M+S, 205/50, 205/55 , 215/50, 225/50		Orig.-Verschr.
	RC34	39	-	70-110	205/55 , 215/50, 225/50		Orig.-Verschr.
	RC27	40	-	70-110	195/55M+S, 205/50, 205/55, 215/50, 225/50		Orig.-Verschr.
7,5 x 17	RC28 / RC29	38	ZP516	70-110	205/50, 205/55, 215/50, 225/45, 235/45		
	B24	38	ZP516	70-110	205/50, 205/55, 215/50, 225/45, 235/45		
	B36	38	ZP516	70-110	205/50, 205/55, 215/50, 225/45, 235/45		
7 x 18	RC32	39	-	70-110	205/45, 215/40, 215/45 , 225/45		Orig.-Verschr.
	RC34	39	-	70-110	215/45		Orig.-Verschr.
8 x 18	B38	35	ZP516	70, 85	215/45		
	B42 / B44	35	ZP516	70-110	215/45		
8 x 19	B40	39	ZP516	70-110	215/35, 225/35, 225/40		
8,5 x 19	B32	40	ZP516	70-110	215/35, 225/35, 225/40		

Tiguan II	ab 04.2016	5N	5/112	57,1	e1*2001/116*0450*24-..
-----------	------------	----	-------	------	------------------------

indirekt - teilweise direkt	Brocksens 2						
-----------------------------	-------------	--	--	--	--	--	--

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 17	RC27	38	-	85-180	215/65		Orig.-Verschr.
	RC34	38	-	85-180	215/65		Orig.-Verschr.
	RC27	39+43	-	85-176	215/65, 225/60, 225/65, 235/60		Orig.-Verschr.
7 x 17	RC27	40	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC30	40	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC32	40	-	85-180	215/65		Orig.-Verschr.
				85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	40	-	85-180	215/65		Orig.-Verschr.
	B39	40	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr.
	RC27	35+42+ 43+45	-	85-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC32	38+39	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC34	40	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	CA 26	42	ZP560D	85-180	215/65, 225/60, 225/65, 235/60		incl. Facelift 2021
7 x 18	RC27	43	-	85-180	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., 255/50 ✖ u. auch R-Line
	RC32	43	-	85-176	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
	RC34	43	-	85-180	235/55		Orig.-Verschr.
		35	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
		45	-	85-176	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
7,5 x 18	RC32	40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
		45	-	85-176	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	RC34	35	-	85-180	215/55, 215/60, 225/55, 225/60		Orig.-Verschr.
		40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	Oxigin 18	37	-	85-176	215/55, 215/60, 225/55		Orig.-Verschr., auch R-Line
	RC30	35	ZP560D	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		incl. FL2021, ohne Radhausverbr. ab 245/50 ✖
		45	ZP560D	85-180	215/55, 215/60, 225/55, 225/60		incl. Facelift 2021
	B32	35	ZP560D	85-176	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		ohne Radhausverbr. ab 245/50 ✖
		45	ZP560D	85-176	215/55, 225/55, 225/60		auch R-Line
	B39	35	ZP560D	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 255/50		incl. Facelift 2021, ohne Radhausverbr. ab 245/50 ✖
		45	ZP560D	85-180	215/55, 215/60, 225/55, 225/60		incl. Facelift 2021, auch R-Line
8 x 18	RC27	40	-	85-176	225/55		Orig.-Verschr.
	RC29	40	-	85-176	225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
	RC32	40	-	85-176	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		44	-	85-176	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC34	40+45	-	85-180	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		44	-	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		Orig.-Verschr.
	B38	35	ZP560D	85-176	225/55, 225/60, 235/50, 235/55, 245/50		ohne Radhausverbr. ab 235/50 ✖
	B42 / B44	35	ZP560D	85-180	225/55, 225/60, 235/50, 235/55, 245/50		incl. Facelift 2021, ohne Radhausverbr. ab 235/50 ✖
	AC-M10	40	- +R	85-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2021
	AC-518	40	AV4+R	85-176	225/55, 225/60, 235/50, 235/55		+ Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	85-176	225/55, 225/60, 235/50, 235/55		
	AF20	35	AV1	85-180	225/55, 225/60		incl. Facelift 2021, auch für Hybrid
	FMI11 Elatha	39	F95	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		ohne Radhausverbr. nur bis 235/55
		45	F95	85-180	215/55, 225/55, 225/60, 235/50, 235/55		
7 x 19	RC27	43	-	85-180	235/50		Orig.-Verschr., incl. FL2021, auch R-Line
	RC34	43	-	85-180	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	85-180	235/45, 235/50, 245/45, 245/50		Orig.-Verschr.
	B32	43	-	85-176	235/45, 235/50, 245/45		Orig.-Verschr.
	B39	33+43	ZP560D	85-176	235/45, 235/50, 245/45		ET33 ohne Radhausverbr. bei 235/50 ✖
	Oxigin 18	37	-	85-176	235/45, 235/50, 245/45		Orig.-Verschr., nicht R-Line, bei 235/50 ✖
8 x 19	RC29	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC32	40+44+ 45	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC34	40+45	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B40	40	-	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	40	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., incl. Facelift 2021
	RC29	35	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	RC34	38	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
		43	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
	B38	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	B40	38	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
	CA 17	37	ZP560D	85-176	235/45, 245/45, 255/45		

				45	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
				38	AV4+R	85-176	235/45, 235/50, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1
				35	- +R	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. FL2021, ohne Radhausverbr. bei 235/50 u. 255/45 ✖
				39	- +R	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
				39	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021
				38	-	85-180	255/45		Orig.-Verschr.
				38	-	85-180	255/45		Orig.-Verschr.
				38	ZP568F	85-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, nur R-Line, mit Radhausverbr.
				38	ZP568F	85-180	255/45		incl. FL2021, nur R-Line, mit Radhausverbr.
				34,5	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
				35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, ohne Radhausverbr. ab 235/50 ✖
				35	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
				36	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
				39	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
				35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, ohne Radhausverbr. ab 235/50 ✖
				40	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, incl. Facelift 2021
				40	AV1	85-176	235/45, 245/45		
				40	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, incl. Facelift 2021
				40	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, incl. Facelift 2021
				40	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, incl. Facelift 2021
				45	- +R	85-176	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
				32	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1, mit Verbreiterungen
				35	ZP560D	85-176	235/45		
				40	ZP560D	85-180	235/45, 245/45		incl. Facelift 2021
				41	-	85-180	235/45		Orig.-Verschr., incl. FL2021, auch Hybrid
				41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. FL2021, auch Hybrid
				41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
				41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
				40	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
				40	-	85-176	235/40, 235/45, 245/40		Orig.-Verschr., auch R-Line
				45	-	85-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021
				35	ZP560D	85-176	235/40, 235/45, 245/40		auch R-Line
				30	ZP560D	85-180	235/40, 235/45		incl. Facelift 2021, auch R-Line
				39	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021, auch R-Line
				45	F31+R	85-180	235/45, 245/40		+Ringe BA25=66,6-57,1, ohne Verbreiterung
						85-180	235/40, 235/45, 245/40		+Ringe BA25=66,6-57,1, mit Verbreiterung
				38	-	85-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., nur R-Line, auch Hybrid, FL2021
				38	-	85-180	255/40		Orig.-Verschr., incl. Facelift 2021, R-Line
				38	ZP568F	85-176	255/40		Orig.-Verschr., incl. Facelift 2021, R-Line
				38	-	85-180	255/40		Orig.-Verschr., incl. Facelift 2021, R-Line
				38	-	85-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., incl. Facelift 2021, ohne Radhausverbr. bei 255/40 ✖
				41	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
				40	-	85-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
				42	ZP560D	85-176	235/40, 235/45		
				40	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021
				45	ZP560D	85-176	235/40, 235/45, 245/40		
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. ab 245/40 ✖
				40	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021
				45	ZP560D	85-180	235/40, 235/45		incl. Facelift 2021
				40	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021
				43	ZP560D	85-180	235/40, 235/45		incl. Facelift 2021
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. ab 245/40 ✖
				40	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021
				45	- +R	85-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25, incl. FL2021
				45	-	85-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021
				40	- +R	85-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25, incl. FL2021
				45	- +R	85-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25, incl. FL2021
				40	ZP560D	85-176	235/45, 255/40		ohne Radhausverbr. bei 255/40 ✖
				39	- +R	85-176	235/45, 245/40, 245/45, 255/40		Orig.-Verschr. + Red.Ringe BA25, ohne Radhausverbr. bei 255/40 ✖
				37	ZP560D	85-180	245/35, 255/35		mit Radhausverbreiterungen
				42	-	85-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021
				37	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021, ohne Radhausverbr. bei 245/40 ✖
				38	ZP560D	85-176	235/45, 245/40		ohne Radhausverbr. bei 245/40 ✖
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. Facelift 2021, ohne Radhausverbr. ab 245/40 ✖
				38	ZP560D	85-180	235/40, 235/45, 245/40		incl. Facelift 2021
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. Facelift 2021
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. Facelift 2021
				35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. Facelift 2021, ohne Radhausverbr. ab 245/40 ✖

8,5 x 21	B41	40	ZP560D	85-180	245/35, 245/40, 255/35		ohne Radhausverbr. bei 255/35 ✖
		43	ZP560D	85-180	245/35		
9 x 22	B43	38	ZP568F	85-180	245/35, 255/35		incl. FL2021, ohne Radhausverbr. bei 255/35 ✖
	AF18	35	-	85-176	245/30		Orig.-Verschr., mit Radhausverbreiterungen

Tiguan II Allspace							
ab 09.2017				5N	5/112	57,1	e1*2001/116*0450*31
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	38	-	110-180	215/65		Orig.-Verschr.
	RC34	38	-	85-180	215/65		Orig.-Verschr.
	RC27	39+43	-	110-176	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., auch R-Line
7 x 17	RC27	40	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., auch R-Line
	RC30	40	-	110-180	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC32	40	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., auch R-Line
	RC34	40	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	RC27	35	-	110-176	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		Orig.-Verschr., ohne R-Line ab 245/55 ✖
		38	-	110-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., auch R-Line
	RC32	38+39	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., auch R-Line
		45	-	85-176	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr.
	B39	40	-	110-176	215/65, 225/60, 225/65, 235/60, 245/55		Orig.-Verschr., auch R-Line
	CA 26	42	ZP560D	110-180	215/65, 225/60, 225/65, 235/60		incl. Facelift 2021
7,5 x 17	RC24	35+42	-	110-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC27	40	-	110-176	215/65, 225/60		Orig.-Verschr.
		41	-	110-180	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	RC32	43	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., auch für Hybrid
	RC34	41	-	85-180	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr., ohne Radhausverbr. bei 255/55 ✖
	RC24	42	ZP560D	110-176	215/65, 225/60, 225/65, 235/60		auch R-Line
	RC28	35	ZP560D	110-176	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne R-Line ab 245/55 ✖
		45	ZP560D	110-180	215/65, 225/60, 225/65		auch R-Line, incl. Facelift 2021
	RC29	35	ZP560D	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne R-Line ab 245/55 ✖
		45	ZP560D	110-180	215/65, 225/60, 225/65		auch R-Line, ET45 nicht Bremse 340mm
	B24	35	ZP560D	110-176	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		ohne R-Line ab 245/55 ✖
	B36	35	ZP560D	110-180	215/65, 225/60, 225/65, 235/60, 245/55, 255/55		incl. FL2021, ohne R-Line ab 245/55 ✖
		45	ZP560D	110-180	215/65, 225/60, 225/65		incl. Facelift 2021, nicht Bremse 340mm
	AC-518	42	AV4+R	110-176	215/65, 225/60, 225/65, 235/60		+ Red.Ringe BA25=66,6-57,1
7 x 18	RC27	43	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
				110-176	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC32	43	-	85-176	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
	RC34	43	-	85-180	235/55		Orig.-Verschr.
	RC32	35	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		Orig.-Verschr.
		45	-	85-176	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
7,5 x 18	RC32	40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	RC34	35	-	110-180	215/55, 215/60, 225/55, 225/60		
		40	-	85-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55		Orig.-Verschr.
	RC30	35	ZP560D	110-180	215/55, 225/55, 225/60, 235/50, 235/55		auch R-Line, incl. Facelift 2021
	B32	45	ZP560D	110-180	215/55, 215/60, 225/55, 225/60		auch R-Line, incl. Facelift 2021
		45	ZP560D	110-176	215/55, 225/55, 225/60		auch R-Line
	B39	35	ZP560D	110-180	215/55, 215/60, 225/55, 225/60, 235/50, 235/55, 245/50		incl. Facelift 2021, ohne Radhausverbr. bei 245/40 ✖
8 x 18	RC27	40	-	110-176	225/55, 235/50, 235/55		Orig.-Verschr., ab 235/50 ✖
		44	-	110-176	225/55, 235/50, 235/55		Orig.-Verschr.
	RC29	40	-	110-176	225/55, 235/50, 235/55		Orig.-Verschr., auch R-Line
	RC32	40	-	85-176	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		44	-	85-176	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		Orig.-Verschr.
	RC34	40+45	-	85-180	215/55, 225/55, 225/60, 235/50, 235/55		Orig.-Verschr.
		44	-	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50		Orig.-Verschr.
	B24 / B36 / B37	35	ZP560D	110-180	225/55, 225/60, 235/50, 235/55, 245/50		incl. Facelift 2021, ohne R-Line ab 235/50 ✖
	B38	35	ZP560D	110-176	225/55, 225/60		
	B42 / B44	35	ZP560D	110-180	225/55, 225/60, 235/50, 235/55, 245/50		incl. Facelift 2021, ohne Verbr. ab 235/50 ✖
	AC-M10	40	- +R	110-180	225/55, 225/60, 235/50, 235/55		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1, incl. Facelift 2021
	AC-518	40	AV4+R	110-176	225/55, 225/60, 235/50, 235/55		+ Red.Ringe BA25=66,6-57,1
	AF18	40	AV1	110-176	225/55, 225/60, 235/50, 235/55		
	FMI11 Elatha	39	F95	85-180	215/55, 225/55, 225/60, 235/50, 235/55, 245/50, 245/55, 255/50		ohne Radhausverbr. nur bis 235/55

		45	F95	85-180	215/55, 225/55, 225/60, 235/50, 235/55		
7 x 19	RC27	43	-	110-180	235/50		Orig.-Verschr., auch R-Line
	RC34	43	-	85-180	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	85-180	235/45, 235/50, 245/45, 245/50		Orig.-Verschr.
	B32	43	-	110-176	235/45, 235/50, 245/45		Orig.-Verschr., auch R-Line
	Oxigin 18	37	-	110-176	235/45, 235/50, 245/45		Orig.-Verschr., nicht R-Line, bei 235/50 ✖
8 x 19	RC27	44	-	110-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC29	40	-	110-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC32	40+44+ 45	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	RC34	40+45	-	85-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B40	40	-	110-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	B43	40	-	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., incl. Facelift 2021
	RC29	35	ZP560D	110-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	RC34	38	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
		43	ZP560D	85-176	235/45, 235/50, 245/45, 255/45		
	B38	35	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	B40	38	ZP560D	110-176	235/45, 235/50, 245/45, 255/45		auch R-Line, incl Facelift 2016
	CA 17	37	ZP560D	110-176	235/45, 245/45, 255/45		
		45	ZP560D	110-176	235/45, 235/50, 245/45, 255/45		
	AC-518	38	AV4+R	110-176	235/45, 235/50, 245/45, 255/45		+ Red.Ringe BA25=66,6-57,1
	AC-521	35	- +R	110-180	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. FL2021, ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	FMI07 Atena	39	- +R	85-176	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 29	39	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021
8,5 x 19	RC32	38	-	85-180	255/45		Orig.-Verschr.
	RC34	38	-	85-180	255/45		Orig.-Verschr.
	B43	38	ZP568F	110-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, nur R-Line, mit Radhausverbreiterung
	CA 26	38	ZP568F	110-180	255/45		incl. FL2021, nur R-Line, mit Radhausverbreiterung
	B36	35	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, ohne Radhausverbr. ab 235/50 ✖
	B37	32	ZP560D	110-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, ohne Radhausverbr. ab 235/50 ✖
	B41	36	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. ab 235/50 ✖
		39	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		ohne Radhausverbr. bei 235/50 u. 255/45 ✖
	B42	35	ZP560D	85-180	235/45, 235/50, 245/45, 255/45		incl. FL2021, ohne Radhausverbr. ab 235/50 ✖
	AC-M10	40	- +R	110-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1 , incl. Facelift 2021
	AF18	40	AV1	110-176	235/45, 245/45		
	CA 23	40	- +R	110-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1 , incl. Facelift 2021
	FMI07 Atena	45	- +R	85-176	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1
	FMI11 Elatha	32	- +R	85-180	235/45, 245/45		Orig.-Verschr. +Ringe BA25=66,6-57,1 , mit Verbreiterungen
	Oxigin 20 / 25	45	ZP560D	110-176	235/45, 235/50, 245/45		ohne Radhausverbr. bei 235/50 ✖
	Oxigin 28	40	ZP560D	110-180	235/45, 245/45		incl. Facelift 2021
	CA 19	43	ZP560D	110-176	235/45		
	RC36	41	-	110-180	235/45		Orig.-Verschr., incl. Facelift 2021
	B38	41	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	B40	41	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr.
8 x 20	B43	41	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
	B38	40	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021, auch R-Line
	B40	40	-	110-176	235/40, 235/45, 245/40		Orig.-Verschr., auch R-Line
	B43	45	-	110-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021
8,5 x 20	FMI08 Thoe	45	F31+R	85-180	235/45, 245/40		+Ringe BA25=66,6-57,1 , ohne Verbreiterung
				85-180	235/40, 235/45, 245/40		+Ringe BA25=66,6-57,1 , mit Verbreiterung
	B43	38	-	110-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., nur R-Line, incl. FL2021
	RC29	38	-	110-180	235/40, 235/45, 245/40, 255/40		Orig.-Verschr., incl. Facelift 2021, R-Line
	RC34	38	ZP568F	85-176	255/40		
	RC36	38	-	110-180	255/40		Orig.-Verschr., incl. Facelift 2021, R-Line
	B32	41	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr.
	B43	40	-	110-180	235/40, 235/45, 245/40		Orig.-Verschr., incl. Facelift 2021
	RC29	40	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021
		45	ZP560D	110-180	235/40, 235/45		incl. Facelift 2021
	B24	42	ZP560D	110-176	235/40, 235/45		
	B32	45	ZP560D	110-176	235/40, 235/45, 245/40, 255/40		ohne Radhausverbr. ✖
	B42	35	ZP560D	110-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. ab 245/40 ✖
		40	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021
		45	ZP560D	110-180	235/40, 235/45		incl. Facelift 2021
	B43	40	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021
		43	ZP560D	110-180	235/40, 235/45		incl. Facelift 2021
	B44	35	ZP560D	110-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. ab 245/40 ✖
		40	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021
	AC-518	45	- +R	110-180	235/40, 235/45		Orig.-Verschr. +Red.Ringe BA25
	AC-521	45	-	110-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021

	AC-M10	40	- +R	110-180	235/40, 235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25 , incl. FL2021
	AF18	45	- +R	110-180	235/40, 235/45		Orig.-Verschr. + Red.Ringe BA25
	CA 17	40	ZP560D	110-176	235/45, 255/40		ohne Radhausverbr. bei 255/40 ✖
	CA 19	45	ZP560D	110-180	235/45, 255/40		
	FMI07 Atena	39	-	85-176	235/45, 245/40, 245/45, 255/40		Orig.-Verschr. + Red.Ringe BA25 , ohne Radhausverbr. bei 255/40 ✖
9 x 20	B43	42	-	110-180	235/40, 235/45		Orig.-Verschr., incl. Facelift 2021
	B37	37	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021, ohne Radhausverbr. bei 245/40 ✖
	B41	38	ZP560D	85-176	235/45, 245/40		ohne Radhausverbr. bei 245/40 ✖
	CA 20	35	ZP560D	110-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. ab 245/40 ✖
	CA 23	38	ZP560D	110-180	235/40, 235/45, 245/40		incl. Facelift 2021
	Oxigin 28	35	ZP560D	85-180	235/40, 235/45, 245/40, 255/40		incl. FL2021, ohne Radhausverbr. bei 245/40 ✖
8,5 x 21	B41	37	ZP560D	85-180	245/35, 255/35		mit Radhausverbreiterungen
		40	ZP560D	85-180	245/35, 245/40, 255/35		ohne Radhausverbr. bei 255/35 ✖
		43	ZP560D	85-180	245/35		
	B43	38	ZP568F	110-180	245/35, 255/35		incl. FL2021, ohne Radhausverbr. bei 255/35 ✖
9 x 22	AF18	35	-	85-176	245/30		Orig.-Verschr., mit Radhausverbreiterungen

Tiguan II R							
ab 2021				5N	5/112	57,1	e1*2001/116*0450*54-..
indirekt - teilweise direkt Brocksens 2							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
7 x 19	RC27	43	-	235	235/50		Orig.-Verschr., incl. FL2021, nur M+S
	RC34	43	-	235	235/50		Orig.-Verschr.
7,5 x 19	RC34	40	-	235	235/50, 245/45		Orig.-Verschr.
8 x 19	RC32	40+44	-	235	235/50, 245/45, 255/45		Orig.-Verschr., nur M+S
	RC34	40+45	-	235	235/50, 245/45, 255/45		Orig.-Verschr.
	B43	40	-	235	235/45, 235/50, 245/45, 255/45		Orig.-Verschr., incl. FL2021, nur M+S
	AC-521	35	- +R	235	235/45, 235/50, 245/45, 255/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	Oxigin 29	39	ZP560D	235	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021, nur M+S
8,5 x 19	RC32	38	-	235	235/50, 245/45, 255/45		Orig.-Verschr., nur M+S
	B36 / B42	35	ZP560D	235	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021, nur M+S
	B37	32	ZP560D	235	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021, nur M+S
	B41	36	ZP560D	235	235/50, 245/45, 255/45		
		39	ZP560D	235	235/50, 245/45, 255/45, 265/45		
	B42	35	ZP560D	235	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021, nur M+S
	B43	38	ZP568F	235	235/45, 235/50, 245/45, 255/45		incl. Facelift 2021, nur M+S
	B44	30	ZP560D	235	235/45, 235/50, 245/45		incl. Facelift 2021, nur M+S
	AC-M10	40	- +R	235	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	AF20	30	- +R	235	235/45, 235/50, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
		40	- +R	235	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	CA 23	30	ZP560D	235	235/45, 235/50, 245/45		incl. Facelift 2021, nur M+S
		40	- +R	235	235/45, 245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	FMI11 Elatha	32	- +R	235	245/45		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , nur M+S
	Oxigin 28	40	ZP560D	235	235/45, 245/45		incl. Facelift 2021
	CA 19	43	ZP560D	235	235/45		
8 x 20	B38	40+41	-	235	235/45, 245/40		Orig.-Verschr., incl. Facelift 2021, nur M+S
	B43	41	-	235	235/45, 245/40		Orig.-Verschr., incl. Facelift 2021, nur M+S
		45	-	235	235/45		Orig.-Verschr., incl. Facelift 2021, nur M+S
	B43	30	ZP560D	235	235/45, 245/40		incl. Facelift 2021, nur M+S
	FMI08 Thoe	45	F31+R	235	235/45, 245/40		+ Red.Ringe BA25=66,6-57,1
8,5 x 20	B43	38	-	235	235/45M+S, 245/40M+S, 255/40		Orig.-Verschr., incl. Facelift 2021
	RC29	38	-	235	235/45M+S, 245/40M+S, 255/40		Orig.-Verschr., incl. Facelift 2021
	RC34	38	ZP568F	235	235/45M+S, 245/40M+S, 255/40		
	RC36	38	-	235	235/45M+S, 245/40M+S, 255/40		Orig.-Verschr., incl. Facelift 2021
	RC34	43	ZP560D	235	235/45, 245/40		nur M+S
	B42 / B44	35	ZP560D	235	235/45M+S, 245/40M+S, 255/40		incl. Facelift 2021
	AC-518	32	- +R	235	235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	AC-521	32	- +R	235	235/45, 245/40		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1 , incl. Facelift 2021, nur M+S
	AC-M10	30	ZP560D	235	235/45, 245/40		incl. Facelift 2021, nur M+S
	B41	38	ZP560D	235	235/45M+S, 245/40M+S, 255/40		
9 x 20	CA 20	35	ZP560D	235	235/45M+S, 245/40M+S, 255/40		incl. Facelift 2021
	FMI11 Elatha	34	- +R	235	235/45M+S, 245/40M+S		Orig.-Verschr. + Red.Ringe BA25=66,6-57,1
	Oxigin 28	35	ZP560D	235	235/45M+S, 245/40M+S, 255/40		incl. Facelift 2021
8,5 x 21	B41	37+40	ZP560D	235	245/35M+S, 255/35		
		43	ZP560D	235	245/35		nur M+S

	B43	38	ZP568F	235	245/35M+S, 255/35		incl. Facelift 2021
--	------------	----	--------	-----	-------------------	--	---------------------

Tiguan III NEU							
ab 2024				CT	5/112	57,1	e1*2018/858*00302*..
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6,5 x 17	RC27	38	-	96-142	215/65		Orig.-Verschr.
				96-195	215/65		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-142	215/65, 225/60, 235/60		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 235/60		Orig.-Verschr., nur M+S, mit Verbreiterung / R-Line Paket
	RC34	38	-	96-150	215/65		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-150	215/65, 225/60, 225/65, 235/60		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 235/60		Orig.-Verschr., mit Verbreiterung / R-Line Paket
7 x 17	RC27	40	-	96-150	215/65, 225/60, 235/60		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 235/60		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-150	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 245/55, 255/55		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	RC34	40	-	96-195	215/65		Orig.-Verschr.
				96-142	215/65, 225/60, 225/65, 235/60, 245/55, 245/60, 255/55		Orig.-Verschr., ohne Verbreiterung
				96-142	215/65, 225/60, 235/60, 245/55, 255/55		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-142	215/65		Orig.-Verschr.
7,5 x 17	RC27	40	-	96-142	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., ohne Verbreiterung
				96-142	215/65, 225/60, 235/60, 245/55, 255/55		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	RC34	40	-	96-150	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 235/60, 245/55, 255/55		Orig.-Verschr., mit Verbreiterung / R-Line Paket
7 x 18	RC32	35	-	96-142	215/65, 225/60, 225/65, 235/60, 245/55, 245/60		Orig.-Verschr., ohne Verbreiterung
				96-195	215/65, 225/60, 235/60, 245/55, 255/55		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	RC34	40	-	96-150	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Verbreiterung
				96-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit Verbreiterung / R-Line Paket
7,5 x 18	RC32	40	-	96-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
				96-142	215/55, 215/60, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Verbreiterung
	RC34	35	-	90-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-150	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., ohne R-Line Paket
8 x 18	RC32	40	-	96-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit R-Line Paket
				96-150	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., ohne R-Line Paket
	RC34	40	-	96-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit R-Line Paket
				96-195	215/55, 215/60, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., ohne Verbreiterung bei 255/50 ✖
8 x 19	RC34	40	-	96-142	215/55, 215/60, 225/55, 235/50, 235/55, 245/50		Orig.-Verschr., ohne Verbreiterung bei 245/50 ✖
				96-142	225/55, 235/55		Orig.-Verschr.
	RC27	40	-	96-142	225/55, 235/55		Orig.-Verschr., R-Line
				96-150	215/55, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Verbreiterung
7,5 x 19	RC32	40	-	96-195	215/55, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-150	215/55, 225/55, 235/50, 235/55		Orig.-Verschr., ohne Verbreiterung
	RC34	40	-	96-195	215/55, 225/55, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-195	215/55, 225/55, 235/50, 235/55, 245/50, 255/50		ohne Verbreiterung
8 x 19	B44	35	ZP560D	96-142	225/55, 235/55, 245/50		nur M+S, R-Line
				96-142	225/55, 235/55		Orig.-Verschr. +Ringe BA25=66,6-57,1
	AC-MB6	39	- +R	96-195	225/55, 235/55		Orig.-Verschr. +Ringe BA25=66,6-57,1, nur M+S, mit Verbreiterung
				96-142	215/55, 225/55		+Ringe BA25=66,6-57,1, ohne Verbreiterung
8 x 19	FMI08 Thoe	34	F31+R	96-142	215/55, 225/55, 235/50, 235/55		+Ringe BA25, mit Verbreiterung / R-Line Paket
				96-142	215/50, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr., ohne Verbreiterung
	RC34	40	-	96-195	215/50, 225/50, 235/45, 235/50, 245/45		Orig.-Verschr., mit Verbreiterung / R-Line Paket
				96-142	225/50, 235/50, 245/45		ohne Verbreiterung
8 x 19	CA 26	40	ZP560D	96-195	225/50, 235/50, 245/45		nur M+S, mit Verbreiterung / R-Line Paket
				96-195	225/50, 235/50, 245/45		Orig.-Verschr.
	RC34	40	-	96-142	215/50, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
				96-142	215/50, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
8 x 19	FMI08 Thoe	26	F31+R	96-142	215/50, 235/45		+Ringe BA25, mit Verbreiterung / R-Line Paket
				96-142	255/45		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	RC32	38	-	96-142	235/45, 245/45		Orig.-Verschr., ohne Verbreiterung
				96-195	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Verbreiterung / R-Line Paket
8 x 19	RC34	38	-	96-150	255/45		Orig.-Verschr., R-Line Paket
				96-142	235/45, 245/45		Orig.-Verschr., ohne Verbreiterung

8,5 x 19				96-195	235/45, 235/50, 245/45, 255/45, 265/45		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	B43	38	ZP568F	96-142	255/45		Orig.-Verschr., R-Line
	CA 26	38	ZP568F	96-142	255/45		mit Verbreiterung / R-Line
	B41	39	ZP560D	96-142	235/45, 245/45		ohne Verbreiterung
	CA 20	40	- +R	96-142	235/45, 235/50, 245/45, 255/45, 265/45		mit Verbreiterung / R-Line
9 x 19	FMI08 Thoe	41	F31+R	96-142	235/45, 245/45		+Ringe BA25=66,6-57,1, ohne Verbreiterung
					235/45, 245/45, 255/45, 265/40, 265/45		+Ringe BA25, mit Verbreiterung / R-Line Paket
8 x 20	RC36	38	-	96-150	235/45, 245/40		Orig.-Verschr.
	B43	39	ZP560D	96-142	235/45, 245/40		
8,5 x 20	RC36	38	-	96-195	255/40		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	B43	38	-	96-195	255/40		Orig.-Verschr., mit Verbreiterung / R-Line Paket
	B41	35	ZP560D	96-150	235/40, 235/45		ohne Verbreiterung
				96-195	235/40, 235/45, 245/40, 255/40		mit Verbreiterung / R-Line Paket
9 x 20	B41	38	ZP560D	96-142	235/40, 235/45		ohne Verbreiterung
					235/40, 235/45, 245/40, 255/40		mit Verbreiterung / R-Line Paket
9,5 x 20	CA 23	38	ZP560D	96-142	235/45		
	CA 17	36	ZP560D	96-142	235/40		nur M+S, R-Line
8,5 x 21	B41	40	-	96-150	245/35, 255/35		Orig.-Verschr., ohne Verbreiterung
				96-195	245/35, 255/35		Orig.-Verschr., mit Verbreiterung
	B43	40	-	96-142	245/35		Orig.-Verschr.
	B41	37	ZP560D	96-142	245/35, 255/35		ohne Verbreiterung bei 255/35 ✖
	B43	38	ZP568F	96-142	245/35, 255/35		ohne Verbreiterung bei 255/35 ✖
9 x 21	FMI07 Atena	40	- +R	96-142	245/35		Orig.-Verschr. +Red.Ringe 66,6-57,1, ohne Verbreit.
					245/35, 255/35, 265/30		Orig.-Verschr. +Red.Ringe 66,6-57,1, mit Verbreit.

Tiguan III PHEV NEU				ab 2024	CT	5/112	57,1	e1*2018/858*00302*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
6,5 x 17	RC27	38	-	110, 130	215/65		Orig.-Verschr., Plug-in-Hybrid, auch R-Line	
		40	-	110, 130	215/65, 225/60, 235/60		Orig.-Verschr., auch R-Line	
8 x 18	AC-MB6	39	- +R	110, 130	225/55, 235/55		Orig.-Verschr. +Ringe BA25=66,6-57,1,auch R-Line	
7,5 x 19	CA 26	40	ZP560D	110, 130	225/50, 235/50, 245/45			
8,5 x 19	B43	38	ZP568F	110, 130	255/45		Orig.-Verschr., Plug-in-Hybrid, nur R-Line	
8 x 20	RC36	38	-	110, 130	235/45, 245/40		Orig.-Verschr., Plug-in-Hybrid	
	B43	39	ZP560D	110, 130	235/45, 245/40			
8,5 x 20	RC36	38	-	110, 130	255/40		Orig.-Verschr., Plug-in-Hybrid, nur R-Line	
	B43	38	-	110, 130	255/40		Orig.-Verschr., Plug-in-Hybrid, nur R-Line	

Touareg (siehe Konfigurator)	ab 04.10	7P/7PH	5/130	71,6	DE/e1*2007/46*0400*, e1*2007/46*0376*, 0498*, DE/e1*2007/46*0404*, e1*2007/46*0403*, 0499*
---	----------	--------	-------	------	--

Touareg				ab 2018	CR	5/112	66,6	e1*2007/46*1827*..
Sensor - Brocksens 2								
Dimension	Design	ET	KIT	KW	Reifendimension		Info	
8 x 18	RC27	25	-	170-250	235/65, 245/60, 255/60, 265/55, 265/60		Orig.-Verschr.	
	RC32	25	-	170-250	235/65, 255/60		Orig.-Verschr.	
				170-250	235/65, 245/60, 255/60, 265/55		Orig.-Verschr., Stahlfederung	
				170-250	235/60, 235/65, 245/60, 255/60, 265/55		Orig.-Verschr., Luftfederung	
	RC25	25	-	170-250	235/65, 245/60, 255/60		Orig.-Verschr.	
	FMI08 Thoe	26+34	F31	170-250	235/65, 245/60, 255/60, 265/55		Stahlfederung	
				170-250	235/60, 235/65, 245/60, 255/60, 265/55		Luftfederung	
	FMI11 Elatha	26	F95	170-250	235/65, 245/60, 255/60, 265/55		Stahlfederung	
8 x 19	RC27	28	-	170-250	245/55, 255/55M+S, 265/50, 265/55, 275/50		Orig.-Verschr.	
		28	-	170-340	255/55		Orig.-Verschr.	
	B43	28	ZP559F	170-310	255/55, 265/50, 275/50		auch Hybrid	
		27+34	ZP559F	170-310	255/55, 265/50, 275/50			
	CA 24	30	ZP569F	170-310	245/55, 255/55, 265/50, 265/55, 275/50		incl. Hybrid	
				170-340	255/55, 265/50, 265/55, 275/50		nur M+S, incl. Hybrid	
	FMI08 Thoe	26	ZP568F	170-250	235/55, 245/55, 255/55, 265/50, 275/50		Stahlfederung	
				170-340	235/55, 245/55, 255/50, 255/55, 265/50, 275/50		Luftfederung	
8,5 x 19	Oxigin 29	32	ZP561F	170-310	255/55, 265/50, 275/50		nicht Bremse 400mm	
	RC34	28	-	170-250	255/55		Orig.-Verschr., Stahlfederung	
				170-340	255/55		Orig.-Verschr., Luftfederung	
				170-250	235/55, 245/55, 255/55, 265/50, 275/50		Orig.-Verschr., Stahlfederung	
				170-310	235/55, 245/55, 255/50, 255/55, 265/50, 275/50		Orig.-Verschr., Luftfederung	
	B41	28	ZP559F	170-310	235/55, 245/55, 255/55, 265/50, 275/50			
	FMI07 Atena	28	F95	170-310	235/55, 245/55, 255/55, 265/50, 275/50			
	RC25	28	-	170-250	255/55, 265/50, 275/50		Orig.-Verschr.	
	B32	25	-	170-310	255/55, 265/50		Orig.-Verschr.	
	B41	20	ZP559F	170-310	235/55, 245/55, 255/55			
		21	ZP559F	170-250	235/55, 245/55, 255/55, 265/50		Stahlfederung	
				170-310	235/55, 245/55, 255/50, 255/55		Luftfederung	

	B43	25	ZP559F	170-310	255/55, 265/50		
	CA 20	35	ZP561F	170-310	255/55, 265/50, 275/50		
	Oxigin 14	25	ZP568	170-210	245/55, 255/55, 265/50, 265/55		
9 x 19	CA 19	25	ZP568F	170-340	255/55, 265/50, 265/55		
8 x 20	B40	28	-	170-310	255/50		Orig.-Verschr.
	B43	27+30	ZP559F	170-310	255/50		
	FMI08 Thoe	26	F31	170-250	235/55, 245/50, 255/50		Stahlfederung
8,5 x 20	B41	20+35	ZP559F	170-250	235/55, 245/50, 255/50, 265/45, 275/45		Stahlfederung
				170-310	235/55, 245/50, 255/45, 255/50, 265/45, 275/45		Luftfederung, ET20 nicht 255/50
	B43	30+35	ZP559F	170-310	255/50, 265/45, 275/45		
	AF18	20	-	170-250	265/45		Orig.-Verschr.
	CA 17	23	ZP568F	170-310	235/55, 245/50, 265/45, 265/50, 275/45		
9 x 20	CA 19	32	ZP568F	170-340	265/50, 275/45		
	B37	33	-	170-310	255/50, 265/45, 275/45, 285/45		Orig.-Verschr.
	B40	33	-	170-310	255/50, 265/45, 275/45, 285/45		Orig.-Verschr.
	B41	33	ZP559F	170-310	285/45		
				170-250	255/50, 265/45, 275/45, 285/45		Stahlfederung
				170-310	255/45, 255/50, 265/45, 275/45, 285/45		Luftfederung
	FMI07 Atena	33	AV1	170-310	255/45, 255/50, 265/45, 275/45, 285/45		Luftfederung
				170-250	255/50, 265/45, 275/45, 285/45		Stahlfederung
				170-250	255/50, 265/45, 275/45		Stahlfederung
	B41	20	ZP559F	170-310	255/45, 265/45		Luftfederung
				170-250	255/50, 265/45, 275/45, 285/45		Stahlfederung
				170-310	255/45, 255/50, 265/45, 275/45, 285/45		Luftfederung
	B43	33	ZP559F	170-310	255/50, 265/45, 275/45, 285/45		
		35	ZP559F	170-310	255/50, 265/45, 275/45, 285/45		
	AC-518	33	-	170-310	265/45, 265/50, 275/45, 285/45		Orig.-Verschr.
	AC-522	20	-	170-340	265/45, 275/45		Orig.-Verschr., incl. Hybrid
		25	AV1	170-340	265/45, 265/50, 275/45, 285/45		incl. Hybrid
	AC-M08	33	-	170-340	265/45, 265/50, 275/45, 285/45		Orig.-Verschr., incl. Hybrid
		25	AV1	170-310	265/45, 265/50, 275/45, 285/45		incl. Hybrid
		33	-	170-310	265/45, 265/50, 275/45, 285/45		Orig.-Verschr.
	AF18	33	-	170-250	255/50, 265/45, 275/45, 285/45		Orig.-Verschr.
	CA 20	35	ZP561F	170-310	255/50, 265/45, 275/45, 285/45		
	CA 23	30	ZP561F	170-310	255/50, 265/45, 275/45, 285/45		nicht Bremse 400mm
	FMI07 Atena	20	AV1	170-250	255/50, 265/45, 275/45		Stahlfederung
				170-310	255/45, 265/45		Luftfederung
				170-250	255/50, 265/45, 275/45		Stahlfederung
	FMI11 Elatha	20	F95	170-310	255/45, 265/45		Luftfederung, nicht Bremse 420x40mm
				170-250	255/50, 265/45, 275/45, 285/45		Stahlfederung
				170-310	255/45, 255/50, 265/45, 275/45, 285/45		Luftfederung, nicht Bremse 420x40mm
9,5 x 20	B37C	22	-	170-250	265/45		Orig.-Verschr.
	CA 19	25	ZP568F	170-340	265/45, 275/45		incl. Hybrid
8,5 x 21	B41	30+34	ZP559F	170-310	245/45, 255/45, 265/45		
9 x 21	B32	25	-	170-310	255/40, 265/40, 265/45, 275/40		Orig.-Verschr.
	CA 17	25+30	ZP561F	170-340	265/45		incl. Hybrid
	FMI07 Atena	26+33	F95	170-340	245/45, 255/45, 265/40, 265/45, 275/40		
	Oxigin 18	20	ZP568F	170-250	265/45		
9,5 x 21		28	ZP568F	170-340	265/45		
	B41	31	ZP559F	170-340	285/40		
	B43	31	ZP559F	170-310	255/40, 265/40, 265/45, 275/40, 285/40		
	AF18	31	-	170-310	255/40, 265/40, 265/45, 275/40, 285/40		Orig.-Verschr.
10 x 21	FMI07 Atena	31	F95	170-340	265/40, 265/45, 275/40, 285/40		
9 x 22	AC-M08	26	-	170-340	255/40, 265/35		Orig.-Verschr.
9,5 x 22	AF18	31	-	170-310	255/40, 265/35, 285/35		Orig.-Verschr.
10 x 22	B32	25	-	170-310	255/40, 265/35, 265/40		Orig.-Verschr.
		32	-	170-310	255/40, 265/35, 265/40, 275/35, 285/35		Orig.-Verschr.
	AC-M08	19	-	170-340	255/40		Orig.-Verschr.
	AF18	26	-	170-310	255/40, 265/35, 265/40		Orig.-Verschr.
	CA 17	20	ZP568F	170-310	255/40		
		30	ZP568F	170-310	255/40, 265/35, 285/35		incl. Hybrid
	FMI07 Atena	31	-	170-340	265/35, 265/40, 275/35, 285/35		Orig.-Verschr.
	FMI09 Cratos	21	F31	170-250	265/35, 265/40		mit Stahlfederung
		31	F31	170-250	265/35, 265/40, 275/35, 285/35		

Kombinationen

8 x 20	FMI08 Thoe	26	F31	170-250	255/50		Stahlfederung
				170-310	255/45, 255/50		Luftfederung, nicht Bremse 420x40mm
9 x 20		25	F31	170-250	255/50		Stahlfederung
				170-310	255/45, 255/50		Luftfederung, nicht Bremse 420x40mm

Touran II	ab 09.2015	1T	5/112	57,1	e1*2001/116*0211*36-..., e1*2007/46*0357*14-...		
indirekt - teilweise direkt Brocksens 2							

Dimension	Design	ET	KIT	KW	Reifendimension		Info
6 x 16	RC34	48	-	110-140	205/60		Orig.-Verschr.
		-	-	81-140	205/60		Orig.-Verschr.
		43+50	-	81-140	205/60		Orig.-Verschr.
6,5 x 16	RC30	48	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC32	48	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC34	48	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC24	43	-	81-140	205/60, 205/65, 215/60, 225/55		Orig.-Verschr., ab 215/60 ✖
		46	-	81, 110	205/60, 205/65, 215/60, 225/55		Orig.-Verschr.
		50	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC27	43	-	81-140	205/60, 205/65		Orig.-Verschr.
		44+46	-	81-140	205/60, 205/65, 215/60, 225/55		Orig.-Verschr., ab 215/60 ✖
		50	-		205/60, 205/65, 215/60, 225/55		Orig.-Verschr., bei 225/55 ✖
	RC30	44+46	-	81-140	205/60, 205/65, 215/60, 225/55		Orig.-Verschr., ab 215/60 ✖
		50	-	81-140	205/60, 205/65, 215/60, 225/55		Orig.-Verschr., ab 225/55 ✖
	RC32	43	-	81-140	205/60, 205/65		Orig.-Verschr.
		46	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	RC34	43	-	81-140	205/60, 205/65		Orig.-Verschr.
		46	-	81-140	205/60, 205/65, 215/60		Orig.-Verschr.
	CA 20 Pro1	45	ZP560D	81-140	205/60, 205/65		
		48	F31+R	81-140	205/60, 205/65, 215/60		+ Red.Ringe BA25=66,6-57,1
6,5 x 17	RC27	48,5	-	81, 110	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., ab 225/50 ✖
		-	-	81-140	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., ab 225/50 ✖
		43	-	81-140	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., ab 215/50 ✖
7 x 17	RC27	46	-	81-140	205/55		Orig.-Verschr.
		47	-	81, 110	205/55, 215/50, 215/55, 225/50, 235/50		Orig.-Verschr., ab 215/50 ✖
	RC30	49	-	81-140	205/55, 215/50, 215/55		Orig.-Verschr.
	RC32	45+47	-	81-140	205/55, 215/55, 225/50		Orig.-Verschr., ab 215/55 ✖
		49	-	81-140	205/55, 215/55, 225/50, 235/50		Orig.-Verschr., ab 225/50 ✖
7,5 x 17	B39	49	-	81-140	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., bei 225/50 ✖
	RC24	51	-	81-140	205/55, 215/50, 215/55		Orig.-Verschr., ab 215/50 ✖
	RC27	49	-	81-140	205/50, 205/55, 235/45		Orig.-Verschr., bei 235/45 ✖
	RC29	49	-	81-140	205/55, 215/50, 215/55, 225/50		Orig.-Verschr., ab 215/50 ✖
		51	-	81-140	205/55, 215/50, 215/55		Orig.-Verschr., ab 215/50 ✖
	RC32	49	-	81-140	205/55		Orig.-Verschr.
	Oxigin 14	50	ZP560	81-140	205/50, 205/55		
	Oxigin 19	45	ZP560D	81-110	205/50, 205/55, 215/50, 215/55, 225/50, 235/45		
7 x 18	RC27	52	-	81-140	225/45		Orig.-Verschr.
	RC32	52	-	81-140	215/45, 215/50, 225/45		Orig.-Verschr.
	RC27	45	-	81-140	215/50, 225/45		Orig.-Verschr.
	RC32	45	-	81-140	215/45, 225/45		Orig.-Verschr.
	RC34	49	-	81-140	215/45, 215/50, 225/45		Orig.-Verschr.
7,5 x 18	RC30	49+51	-	81-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	RC32	48+49	-	81-140	215/45, 225/45		Orig.-Verschr.
		45	-	81-140	215/45		Orig.-Verschr.
	RC34	46	-	81-140	215/45		Orig.-Verschr.
		50	-	81-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr.
	B32	48	-	81-140	215/45		Orig.-Verschr.
		49	-	81-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr., bei 215/50 u. 235/45 ✖
	B39	49+51	-	81-140	215/45, 215/50, 225/45, 235/45		Orig.-Verschr., bei 215/50 u. 235/45 ✖
8 x 18	AC-521	50	-	81-140	215/45, 225/45		Orig.-Verschr.
	RC25	50	-	81-140	215/45, 225/45, 235/45		Orig.-Verschr., ab 225/45 ✖
	RC27	46	-	81-140	215/45, 225/40, 225/45, 235/40, 235/45		Orig.-Verschr., ab 225/40 ✖
	RC29	44	-	81-140	215/45, 225/45, 235/45, 245/40		Orig.-Verschr., ✖
		50	-	81-140	215/45, 225/45, 235/45		Orig.-Verschr., ab 225/45 ✖
	RC32	46	-	81-140	225/45		Orig.-Verschr.
	B37	50	-	81, 110	215/45, 225/45, 235/45		Orig.-Verschr., ab 225/45 ✖
	B38	50	-	81-140	215/45, 225/45, 235/45		Orig.-Verschr., ab 225/45 ✖
	RC34	48	ZP560D	81-140	215/45		
	B24	48	ZP560D	81-140	215/45, 225/45, 235/45		ab 225/45 ✖
7,5 x 19	AC-518	50	AV4	81-140	215/45		
	RC32	51	-	81-140	225/40		Orig.-Verschr.
	RC34	48	-	81-140	225/40		Orig.-Verschr.
		50+51	-	81-140	225/40		Orig.-Verschr.
	B32	51	-	81-140	225/40		Orig.-Verschr.
	B39	51	-	81-140	225/40		Orig.-Verschr.
	AC-521	50	-	81-140	225/40		Orig.-Verschr.
	Oxigin 18	51	-	81-140	225/40		Orig.-Verschr.
8 x 19	RC29	49	-	81-140	225/40, 235/35, 235/40		Orig.-Verschr., ✖
	RC32	50	-	81-140	225/40		Orig.-Verschr.
	RC34	50	-	81-140	225/40		Orig.-Verschr.
	B38	50	-	81-140	225/40		Orig.-Verschr., ✖
	B40	50	-	81-140	225/40		Orig.-Verschr., ✖

UP!							
ab 2011				AA/ AAN	4/100	57,1	
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
5 x 14	RC30	35	-	44,50,55	165/70, 175/65		Orig.-Verschr.
				44-66	165/70, 175/65, 185/60, 185/65		Orig.-Verschr., incl. Facelift 2016
6 x 15	RC30	39	ZP436	44,50,55	165/70, 175/65, 185/60, 185/65		
	RC24	40	ZP436	44-66	165/60, 165/65, 175/55, 175/60, 185/55		incl. Facelift 2016
6 x 16	RC30	40	ZP436	44-66	165/60, 165/65, 175/55, 175/60, 185/55		incl. Facelift 2016
	RC30	43	-	44-66	175/50, 185/50, 195/45		Orig.-Verschr., incl. Facelift 2016
6,5 x 16	RC34	43	-	44-66	165/50, 175/50, 175/55, 185/50, 195/45		Orig.-Verschr.
	RC24	38	ZP436	44-66	195/45		incl. Facelift 2016
6,5 x 17	RC30	38	ZP436	44, 55	195/45		
	RC34	43	-	44-66	195/40		Orig.-Verschr.

e-UP! (18,7 - 32,3 kWh-Batterie)							
ab 2013				AA, AAN	4/100	57,1	e13*2007/46*1167*..., e13*2007/46*1182*...
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
5 x 14	RC30	35	-	60	165/70		Orig.-Verschr.
				60, 61	165/70, 175/65		Orig.-Verschr., incl. Facelift 2016, nur M+S
6 x 15	RC30	39	ZP436	60, 61	165/70, 175/65, 185/60, 185/65		incl. Facelift 2016
	RC24	40	ZP436	60, 61	165/60, 165/65, 175/55, 175/60, 185/55		incl. Facelift 2016
6 x 16	RC30	40	ZP436	60, 61	165/60, 165/65, 175/55, 175/60, 185/55		incl. Facelift 2016
	RC30	43	-	60, 61	175/50, 185/50, 195/45		Orig.-Verschr., incl. Facelift 2016
6,5 x 16	RC34	43	-	60-61	165/50, 175/50, 175/55, 185/50, 195/45		Orig.-Verschr.
	RC24 / RC30	38	ZP436	60, 61	195/45		incl. Facelift 2016

cross UP! (siehe Konfigurator)							
ab 2013				AA	4/100	57,1	e13*2007/46*1167*..

UP! GTI							
ab 2018				AA	4/100	57,1	e13*2007/46*1167*..
kein Sensor - indirektes RDKS							
Dimension	Design	ET	KIT	KW	Reifendimension	Info	
6 x 16	RC34	43	-	85	185/50		Orig.-Verschr.
6,5 x 17	RC34	43	-	85	195/40		Orig.-Verschr.
7 x 17	B24	38	ZP436	85	195/40		

T5 Bus (siehe Konfigurator)							
ab 05.03				7HM / 7HC / /HK	5/120	65,1	ACHTUNG: Achslast beachten

T5 Bus (Facelift) (siehe Konfigurator)							
ab 2010				7J0	5/120	65,1	ACHTUNG: Achslast beachten

T6 Bus							
ab 2015				7HC, 7HMA, 7J0	5/120	65,1	e1*2001/116*0220*36-..., e1*2001/116*0289*25-..., e1*2007/46*0130*16-...
indirekt - teilweise direkt Brocksens 2							

Dimension	Design	ET	KIT	KW	Reifendimension	Info	
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!							
6,5 x 16	RC25T	51	-	62-110	205/65C, 215/65+C, 225/60+C, 225/65+C, 235/60		Orig.-Verschr.
	Pro1	51	-	62-132	205/60C, 205/65C, 215/65, 215/65C, 215/70C, 225/60, 225/60C, 225/65, 225/65C, 235/60		Orig.-Verschr.
7 x 17	RC25T	55	-	62-150	215/60C, 225/55+C, 225/60, 235/55		Orig.-Verschr.
	RC30T	55	-	62-150	215/60C, 225/55+C, 225/60, 235/55		Orig.-Verschr.
	B45	55	-	62-150	215/60C, 225/55+C, 225/60, 235/55		Orig.-Verschr., nicht Bremse 340mm
	AC-V51	55	-	62-150	215/60C, 225/55, 225/55C, 225/60, 235/55		Orig.-Verschr.
	B45	47	-	62-150	215/60C, 225/55, 225/55C, 225/60, 235/55, 245/55, 255/50		Orig.-Verschr.
	Pro1	50	-	62-150	215/55, 215/60, 215/60C, 225/50, 225/55, 225/55C, 235/50, 235/55, 245/50, 255/50		Orig.-Verschr.
7,5 x 17	RC25	47	-	62-150	225/55+C, 225/60, 235/55, 245/55, 255/50		Orig.-Verschr., auch Allrad
		53+55	-	62-150	225/55+C, 225/60, 235/55		Orig.-Verschr., auch Allrad
8,5 x 17	8400 Bluster	45	-	62-150	225/50, 225/55, 235/50, 235/55, 245/45, 255/45		Orig.-Verschr.
7,5 x 18	RC25T	45	-	62-150	235/50, 245/45		Orig.-Verschr., auch Allrad
	B45	45+53	-	62-150	235/50, 245/45		Orig.-Verschr., ET53 nicht Bremse 340mm
	AC-V51	50	-	62-150	235/50, 245/45		Orig.-Verschr.
				75-150	235/50, 255/45		Orig.-Verschr., Typ 7HMA
8 x 18	RC32	50	-	62-150	215/55, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
	8400 Bluster	50	-	62-150	215/55, 225/50, 235/45, 235/50, 245/45, 255/45		Orig.-Verschr.
		RC25	50	-	62-150	235/50, 245/45, 255/45	
	AC-V51	50	-	62-150	235/50, 245/45, 255/45		Orig.-Verschr.
				75-150	235/50, 255/45		Orig.-Verschr., Typ 7HMA
8,5 x 19	RC25 geht nicht, da die Schiebetür bei der Felgenspeiche ansteht						
	B32	50	-	62-150	255/40		Orig.-Verschr.
	B37	50	-	62-150	255/40		Orig.-Verschr.
	B41	45	-	62-150	235/45, 245/40, 245/45, 255/40		Orig.-Verschr.
	AF18	47	-	62-150	245/45, 255/40		Orig.-Verschr.
	CA 20	45	-	62-150	245/40, 245/45, 255/40		Orig.-Verschr.

	Oxigin 18 / 20	40	-	75-150	245/40, 245/45		Orig.-Verschr., Typ 7HMA
	B37	45	-	62-150	235/45, 255/40		Orig.-Verschr., ab 255/40 ✖
	B40	45	-	62-150	275/35		Orig.-Verschr., ✖
	Oxigin 18	40	-	62-150	265/35, 275/35		Orig.-Verschr., ✖
	Oxigin 19 / 20	42	-	62-150	265/35		Orig.-Verschr., ✖
	8400 Bluster	44	-	62-150	275/35		Orig.-Verschr., ✖
					245/35, 255/35, 265/35		Orig.-Verschr., ab 255/35 ✖

T6.1 Bus

ab Facelift 2019

7HC, 7HMA, 7JO

5/120

65,1

e1*2001/116*0220*55-..., e1*2001/116*0289*44-..., e1*2007/46*0130*32-...

indirekt - teilweise direkt Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
ACHTUNG! ACHSLASTEN ÜBERPRÜFEN!						
6,5 x 16	RC25T	51	-	66-110	205/65C, 215/65+C, 225/60+C, 225/65+C, 235/60	 Orig.-Verschr.
	Pro1	51	-	62-132	205/60C, 205/65C, 215/65, 215/65C, 215/70C, 225/60, 225/60C, 225/65, 225/65C, 235/60	 Orig.-Verschr.
7 x 17	RC25T	55	-	66-150	215/60C, 225/55+C, 225/60, 235/55	 Orig.-Verschr.
	RC30T	55	-	66-150	215/60C, 225/55+C, 225/60, 235/55	 Orig.-Verschr.
	B45	55	-	62-150	215/60C, 225/55+C, 225/60, 235/55	 Orig.-Verschr., nicht Bremse 340mm
	AC-V51	55	-	66-150	215/60C, 225/55, 225/55C, 225/60, 235/55	 Orig.-Verschr.
	B45	47	-	66-150	215/60C, 225/55, 225/55C, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
	Pro1	50	-	62-150	215/55, 215/60, 215/60C, 225/50, 225/55, 225/55C, 235/50, 235/55, 245/50, 255/50	Orig.-Verschr.
7,5 x 17	RC25	47	-	66-146	225/55+C, 225/60, 235/55, 245/55, 255/50	Orig.-Verschr.
		53+55	-	66-150	225/55, 225/55C, 225/60, 235/55	Orig.-Verschr.
8,5 x 17	8400 Bluster	45	-	62-150	225/50, 225/55, 235/50, 235/55, 245/45, 255/45	Orig.-Verschr.
7,5 x 18	RC25T	45	-	81-146	235/50, 245/45	Orig.-Verschr., nicht Bremse 308 mm
	B45	45	-	66-150	235/50, 245/45	Orig.-Verschr.
	AC-V51	50	-	66-150	235/50, 245/45	Orig.-Verschr.
8 x 18	RC32	50	-	62-150	255/45	 Orig.-Verschr.
	8400 Bluster	50	-	62-150	215/55, 225/50, 235/45, 235/50, 245/45, 255/45	 Orig.-Verschr.
	RC25	50	-	66-150	235/50, 245/45, 255/45	 Orig.-Verschr.
	AC-V51	50	-	66-150	235/50, 245/45, 255/45	 Orig.-Verschr.
8,5 x 19	B32	50	-	66-146	245/45, 255/40	Orig.-Verschr.
	B37	50	-	66-146	245/45, 255/40	Orig.-Verschr.
	B41	45	-	62-150	235/45, 245/40, 245/45, 255/40	Orig.-Verschr.
	AF18	47	-	66-150	245/45, 255/40	Orig.-Verschr.
	CA 20	45	-	66-150	245/40, 245/45, 255/40	Orig.-Verschr.
9 x 20	B40	45	-	62-150	265/35, 275/35	Orig.-Verschr., ✖
	8400 Bluster	44	-	62-150	245/35, 255/35, 265/35	Orig.-Verschr., ab 255/35 ✖

T7 Bus NEU

1. Quartal 2022

ST

5/120

65,1

e1*2018/*858*00018*..

Sensor - Brocksens 2

Dimension	Design	ET	KIT	KW	Reifendimension	Info
6,5 x 16	RC34	60	-	100-110	195/75, 215/65	 Orig.-Verschr., Ausführung V4, auch Hybrid
				100-110	195/75, 205/65, 205/70, 215/65, 215/70, 225/60, 225/65, 235/60	 Orig.-Verschr., Ausführung V4, auch Hybrid
	RC25T	51+60	-	100, 110	215/65, 215/65C, 225/60, 225/65, 225/65C, 235/60	Orig.-Verschr., nicht Bremse 332mm
	Pro1	51	-	100-110	195/75, 205/65, 205/70, 215/65, 215/70, 225/60, 225/65, 235/60	Orig.-Verschr.
6,5 x 17	RC34	60	-	100-150	205/60, 215/55, 215/60, 215/60C , 215/65C, 225/55+C, 225/60, 235/50, 235/55 , 235/60C	 Orig.-Verschr., Ausführung V4, auch Hybrid
7 x 17	RC25T	55	-	100	215/60+C, 225/55+C, 225/60+C	Orig.-Verschr., nur Bremse 332mm
				100-150	215/60+C, 225/55+C, 225/60+C, 235/55, 245/55	Orig.-Verschr., bis 225/60 nur M+S, nur Bremse 332mm
	RC30T	55	-	100	215/60+C, 225/55+C, 225/60+C	Orig.-Verschr.
				100-150	215/60+C, 225/55+C, 225/60+C, 235/55, 245/55	Orig.-Verschr., bis 225/60 nur M+S, nur Bremse 332mm
	B45	47+55	-	100, 110	215/60+C, 225/55+C, 225/60+C	Orig.-Verschr.
				100-150	215/60+C, 225/55+C, 225/60+C, 235/55, 245/55	Orig.-Verschr., bis 225/60 nur M+S, ET47 ab 235/55 ✖
	AC-V51	55	-	100	215/60+C, 225/55+C, 225/60+C	Orig.-Verschr., nur Bremse 332mm
				100-150	215/60+C, 225/55+C, 225/60+C, 235/55, 245/55	Orig.-Verschr., bis 225/60 nur M+S, nur Bremse 332mm
7,5 x 17	Pro1	50	-	100-150	205/60, 215/55, 215/60, 215/60C, 215/65C, 225/55, 225/55C, 225/60, 235/50, 235/55, 235/60C	Orig.-Verschr.
				100	215/60, 225/55, 225/55C, 225/60, 225/60C	Orig.-Verschr., nur Bremse 332mm
	RC25	53+55	-	100-150	215/60, 225/55, 225/55C, 225/60, 225/60C, 235/55	Orig.-Verschr., nur M+S, nur Bremse 332mm
	RC32	60	-	100-150	215/55, 225/50, 225/55, 235/45, 235/50 , 245/45,	 Orig.-Verschr., auch Hybrid Ausführung V4

7,5 x 18	RC34	60	-	100-150	245/50		Orig.-Verschr., auch Hybrid
	RC34	60	-	100-150	215/55, 225/50, 225/55, 235/45, 235/50 , 245/45, 245/50		Orig.-Verschr., auch Hybrid
	B45	53		100, 110	215/55, 225/50, 225/55		Orig.-Verschr.
	AC-V51	50	-	100-150	215/55, 225/50, 225/55, 235/50, 245/45		Orig.-Verschr., bis 225/55 nur M+S
8 x 18	8400 Bluster	50	-	100-150	215/55, 225/50, 225/55, 235/45, 245/45		Orig.-Verschr., auch Hybrid
8 x 19	RC34	58	-	100-150	225/50, 235/45, 245/40, 245/45		Orig.-Verschr., Ausführung V4, auch Hybrid
	FMI10 e-Joule	58	-	100-150	245/45		Orig.-Verschr.
8 x 20	B45	52	-	100-150	245/40		Orig.-Verschr.

T7 Bus Transporter		NEU i.V.	2024	NSN / NVN	6/120	74,6	e5*2018/858*00262*..., e5*2018/858*00263*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC35	50	-	81-125	215/65C		 Orig.-Verschr.
6,5 x 17	RC35	50	-	81-125	215/60C		 Orig.-Verschr.

T7 Bus Transporter		elektro NEU i.V	2024	NSN / NVN	6/120	74,6	e5*2018/858*00262*..., e5*2018/858*00263*..
Sensor - Brocksens 4							
Dimension	Design	ET	KIT	KW	Reifendimension		Info
6,5 x 16	RC35	50	-	63-85	215/65C		 Orig.-Verschr., e-Transporter, e-Caravelle
6,5 x 17	RC35	50	-	63-85	215/60C		 Orig.-Verschr., e-Transporter, e-Caravelle

Xpeng

		Baujahr		Typ	LK/LZ	Nabe	
Xpeng G6		ab 2024		F30	5/112	60,1	e4*2018/858*00205*..
Dimension	Design	ET	KIT	KW	Reifendimension		Info
8,5 x 20	RC36	50	-	110, 160	255/45		 Orig.-Verschr.

Xpeng G9		ab 2024		G9A		5/112		60,1		e5*2018/858*00201*..	
Sensor - Brocksens 2											
Dimension	Design	ET	KIT	KW	Reifendimension				Info		
8,5 x 21	FMI11 Elatha	30	-	80	255/45					Orig.-Verschr.	